



US008083769B2

(12) **United States Patent**
Cauldwell et al.

(10) **Patent No.:** **US 8,083,769 B2**
(45) **Date of Patent:** **Dec. 27, 2011**

(54) **WIRED SUTURES**

(75) Inventors: **Nathan Cauldwell**, Attleboro, MA (US);
Gregory R. Whittaker, Stoneham, MA
(US); **Gary McAlister**, Franklin, MA
(US); **Jose E. Lizardi**, Franklin, MA
(US); **Jason Hamilton**, Dartmouth, MA
(US); **Frank Capuano**, Stoneham, MA
(US)

(73) Assignee: **DePuy Mitek, Inc.**, Raynham, MA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 630 days.

(21) Appl. No.: **11/555,568**

(22) Filed: **Nov. 1, 2006**

(65) **Prior Publication Data**

US 2008/0147119 A1 Jun. 19, 2008

(51) **Int. Cl.**
A61B 17/04 (2006.01)

(52) **U.S. Cl.** **606/232**

(58) **Field of Classification Search** 606/300-331,
606/232, 139, 144-145, 222-225; 411/387.5,
411/402

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,382,019 A 8/1945 Miller
2,453,247 A 11/1948 Moss
3,438,299 A 4/1969 Gutshall
3,541,918 A 11/1970 Johnson
3,762,418 A * 10/1973 Wasson 606/226
RE28,111 E 8/1974 Lavery
3,861,269 A 1/1975 Lavery
4,175,555 A 11/1979 Herbert et al.

4,241,638 A 12/1980 Shimizu et al.
4,372,293 A * 2/1983 Vijil-Rosales 128/898
4,463,753 A 8/1984 Gustilo
4,576,534 A 3/1986 Barth et al.
4,632,100 A 12/1986 Somers et al.
4,643,178 A * 2/1987 Nastari et al. 606/74
4,870,957 A 10/1989 Goble et al.
4,946,468 A 8/1990 Li
5,041,129 A 8/1991 Hayhurst et al.
5,100,417 A 3/1992 Cerier et al.
5,152,790 A * 10/1992 Rosenberg et al. 623/13.14
5,156,616 A * 10/1992 Meadows et al. 606/232
5,176,682 A 1/1993 Chow
5,258,016 A 11/1993 DiPoto et al.
5,320,629 A * 6/1994 Noda et al. 606/139
5,336,231 A * 8/1994 Adair 606/148
5,370,662 A 12/1994 Stone et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0464479 A 1/1992

(Continued)

OTHER PUBLICATIONS

Office Action dated Aug. 17, 2010, U.S. Appl. No. 11/855,728.

(Continued)


Primary Examiner — Melanie Tyson

Assistant Examiner — Son Dang

(57) **ABSTRACT**

Methods and devices are provided for anchoring suture to bone. In one exemplary embodiment, a cannulated suture anchor is provided and it includes a suture-engaging member formed therein and configured to receive a suture therearound such that trailing ends of the suture can extend through the suture anchor. The present invention also provides exemplary sutures and drivers that can be used with the various methods and devices disclosed herein, or with other methods and devices known in the art.

12 Claims, 15 Drawing Sheets



US 8,083,769 B2

Page 2

U.S. PATENT DOCUMENTS

5,374,278 A * 12/1994 Chesterfield et al. 606/228
 5,417,712 A 5/1995 Whittaker et al.
 5,423,860 A 6/1995 Lizardi et al.
 5,443,509 A 8/1995 Boucher et al.
 5,454,823 A * 10/1995 Richardson et al. 606/148
 5,464,427 A 11/1995 Curtis et al.
 5,470,334 A 11/1995 Ross et al.
 5,486,197 A * 1/1996 Le et al. 606/232
 5,505,736 A 4/1996 Reimels et al.
 5,527,322 A * 6/1996 Klein et al. 606/144
 5,534,011 A 7/1996 Greene, Jr. et al.
 5,571,139 A 11/1996 Jenkins, Jr.
 5,573,547 A 11/1996 LeVeen et al.
 5,573,548 A 11/1996 Nazre et al.
 5,575,801 A 11/1996 Habermeyer et al.
 5,584,835 A 12/1996 Greenfield
 5,593,410 A 1/1997 Vrespa
 5,601,557 A 2/1997 Hayhurst
 5,607,428 A 3/1997 Lin
 5,643,295 A * 7/1997 Yoon 606/151
 5,674,230 A * 10/1997 Tovey et al. 606/139
 5,707,395 A 1/1998 Li
 5,720,766 A 2/1998 Zang et al.
 5,733,307 A 3/1998 Dinsdale
 5,779,417 A 7/1998 Barth et al.
 5,782,864 A * 7/1998 Lizardi 606/232
 5,814,070 A 9/1998 Borzone et al.
 5,851,219 A 12/1998 Goble et al.
 5,868,789 A 2/1999 Huebner
 5,891,168 A 4/1999 Thal
 5,895,351 A 4/1999 Nottage et al.
 5,916,224 A 6/1999 Esplin
 5,935,129 A 8/1999 McDevitt et al.
 5,941,882 A 8/1999 Jammet et al.
 5,957,953 A 9/1999 DiPoto et al.
 5,961,524 A 10/1999 Crombie
 6,001,101 A 12/1999 Augagneur et al.
 6,027,523 A 2/2000 Schmieding
 6,045,573 A 4/2000 Wenstrom, Jr. et al.
 6,096,060 A 8/2000 Fitts et al.
 6,117,162 A 9/2000 Schmieding et al.
 6,123,711 A 9/2000 Winters
 6,129,730 A 10/2000 Bono et al.
 6,139,565 A 10/2000 Stone et al.
 6,146,406 A 11/2000 Shluzas et al.
 6,149,653 A 11/2000 Deslauriers
 6,159,235 A 12/2000 Kim
 6,214,031 B1 4/2001 Schmieding et al.
 6,234,797 B1 5/2001 Ura
 6,261,292 B1 7/2001 Diebold et al.
 6,264,677 B1 7/2001 Simon et al.
 6,319,270 B1 11/2001 Grafton et al.
 6,432,115 B1 * 8/2002 Mollenauer et al. 606/148
 6,436,100 B1 8/2002 Berger
 6,436,124 B1 8/2002 Anderson et al.
 6,461,373 B2 10/2002 Wyman et al.
 6,464,706 B1 10/2002 Winters
 6,503,251 B1 1/2003 Shaddock
 6,508,830 B2 1/2003 Steiner
 6,554,852 B1 4/2003 Oberlander
 6,569,186 B1 5/2003 Winters et al.
 6,569,188 B2 5/2003 Grafton et al.
 6,585,730 B1 7/2003 Foerster
 6,610,080 B2 8/2003 Morgan
 6,616,665 B2 9/2003 Grafton et al.
 6,623,492 B1 9/2003 Berube et al.
 6,652,563 B2 * 11/2003 Dreyfuss 606/232
 6,656,183 B2 12/2003 Colleran et al.
 6,660,023 B2 12/2003 McDevitt et al.
 6,685,728 B2 2/2004 Sinnott et al.
 6,699,250 B1 3/2004 Osterle et al.
 6,770,076 B2 * 8/2004 Foerster 606/326
 6,773,440 B2 * 8/2004 Gannoe et al. 606/142
 6,773,450 B2 * 8/2004 Leung et al. 606/232
 6,840,953 B2 1/2005 Martinek
 6,923,824 B2 * 8/2005 Morgan et al. 606/232
 7,090,690 B2 * 8/2006 Foerster et al. 606/232
 7,217,279 B2 5/2007 Reese

7,306,614 B2 * 12/2007 Weller et al. 606/151
 7,390,328 B2 * 6/2008 Modesitt 606/144
 7,473,252 B2 * 1/2009 Barry 606/41
 7,556,640 B2 7/2009 Foerster
 7,695,494 B2 4/2010 Foerster
 2001/0004694 A1 6/2001 Carchidi et al.
 2001/0037113 A1 11/2001 Justin
 2001/0053913 A1 12/2001 Freedland
 2002/0016594 A1 2/2002 Schlapfer et al.
 2002/0052629 A1 5/2002 Morgan et al.
 2002/0147463 A1 10/2002 Martinek
 2002/0173822 A1 11/2002 Justin et al.
 2002/0183751 A1 12/2002 Justin et al.
 2003/0004545 A1 1/2003 Burkhart et al.
 2003/0065332 A1 4/2003 TenHuisen et al.
 2003/0065361 A1 * 4/2003 Dreyfuss 606/232
 2003/0074002 A1 4/2003 West
 2003/0088252 A1 5/2003 Kaikkonen et al.
 2003/0125745 A1 7/2003 Tseng et al.
 2003/0144696 A1 7/2003 Sinnott et al.
 2003/0158555 A1 8/2003 Sanders et al.
 2003/0187446 A1 10/2003 Overaker et al.
 2003/0187477 A1 10/2003 Lintner
 2003/0229350 A1 12/2003 Kay
 2004/0006346 A1 1/2004 Holmen et al.
 2004/0098050 A1 * 5/2004 Foerster et al. 606/232
 2004/0106949 A1 * 6/2004 Cohn et al. 606/224
 2004/0116963 A1 * 6/2004 Lattouf 606/224
 2005/0107828 A1 5/2005 Reese
 2005/0119698 A1 6/2005 Martinek
 2005/0222618 A1 10/2005 Dreyfuss et al.
 2005/0222619 A1 10/2005 Dreyfuss et al.
 2005/0267479 A1 12/2005 Morgan et al.
 2005/0283158 A1 12/2005 West
 2006/0079904 A1 4/2006 Thal
 2006/0099109 A1 5/2006 Olofsson et al.
 2006/0100630 A1 5/2006 West
 2006/0276841 A1 12/2006 Barbieri et al.
 2006/0282083 A1 12/2006 Fanton et al.
 2007/0060922 A1 * 3/2007 Dreyfuss 606/72
 2007/0073299 A1 3/2007 Dreyfuss et al.
 2007/0203498 A1 8/2007 Gerber et al.
 2007/0213730 A1 9/2007 Martinek et al.
 2007/0219557 A1 9/2007 Bourque et al.
 2007/0219558 A1 9/2007 Deutsch
 2007/0225719 A1 9/2007 Stone et al.
 2007/0233122 A1 10/2007 Denis et al.
 2007/0282341 A1 12/2007 Hes et al.
 2007/0288025 A1 12/2007 Peukert et al.
 2008/0004659 A1 1/2008 Burkhart et al.
 2008/0009904 A1 1/2008 Bourque et al.
 2008/0147063 A1 6/2008 Cauldwell et al.
 2008/0147064 A1 6/2008 Cauldwell et al.
 2009/0076544 A1 3/2009 DiMatteo et al.
 2009/0076545 A1 3/2009 DiMatteo et al.
 2010/0185238 A1 7/2010 Cauldwell et al.

FOREIGN PATENT DOCUMENTS

EP 0465910 1/1992
 EP 0673624 A 9/1995
 EP 1448543 A1 8/2004
 EP 1719450 A1 11/2006
 GB 1448543 9/1976
 WO WO-97/30649 A 8/1997
 WO WO-0209601 A2 2/2002
 WO WO-03029237 A1 4/2003
 WO WO-03070108 A1 8/2003
 WO 2006099109 9/2006

OTHER PUBLICATIONS

Partial European Search Report, Application No. 08164065.8, mailed Mar. 29, 2010, 7 pages.
 European Search Report Application No. 07254115.4 dated Apr. 11, 2008.
 European Search Report Application No. 07254114.7 dated Dec. 28, 2007.
 Office Action dated Aug. 25, 2010, U.S. Appl. No. 11/855,670.

US 8,083,769 B2

Page 3

Canadian Examiner's Requisition, CA Appln. No. 2,608,903, dated Mar. 8, 2010.

Office Action mailed Mar. 4, 2010, U.S. Appl. No. 11/855,728.

Office Action mailed Mar. 23, 2010, U.S. Appl. No. 11/855,670.

European Search Report, App. No. 08164065.8, mailed Aug. 18, 2010, 12 pages.

* cited by examiner

FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 12A




FIG. 12B




FIG. 12C





FIG. 12D



1

WIRED SUTURES

FIELD OF THE INVENTION

The present invention relates generally to medical devices and procedures, and more particularly to systems and methods for attaching soft tissue to bone.

BACKGROUND OF THE INVENTION

The complete or partial detachment of ligaments, tendons and/or other soft tissues from their associated bones within the body are relatively commonplace injuries, particularly among athletes. Such injuries are generally the result of excessive stresses being placed on these tissues. By way of example, tissue detachment may occur as the result of an accident such as a fall, over-exertion during a work-related activity, during the course of an athletic event, or in any one of many other situations and/or activities.

In the case of a partial detachment, the injury will frequently heal itself, if given sufficient time and if care is taken not to expose the injury to further undue stress. In the case of complete detachment, however, surgery may be needed to re-attach the soft tissue to its associated bone or bones. Numerous devices are currently available to re-attach soft tissue to bone. Examples of such currently-available devices include screws, staples, suture anchors and tacks. In soft tissue re-attachment procedures utilizing screws, the detached soft tissue is typically moved back into its original position over the bone. Then the screw is screwed through the soft tissue and into the bone, with the shank and head of the screw holding the soft tissue to the bone. Similarly, in soft tissue re-attachment procedures utilizing staples, the detached soft tissue is typically moved back into its original position over the bone. Then the staple is driven through the soft tissue and into the bone, with the legs and bridge of the staple holding the soft tissue to the bone.

In soft tissue re-attachment procedures utilizing suture anchors, an anchor-receiving hole is generally first drilled in the bone at the desired point of tissue re-attachment. Then a suture anchor is deployed in the hole using an appropriate installation tool. This effectively locks the suture to the bone, with the free end(s) of the suture extending out of the bone. The free ends of the suture are passed through or around the soft tissue and are used to tie the soft tissue securely to the bone.

While current suture anchors are effective in anchoring soft tissue to bone, one drawback with current devices is that the suture anchor must have a head with a length that is sufficient to withstand a torque applied thereto by a driver. As a result of the increased length, the suture anchor will typically extend at least partially into underlying soft cancellous bone in order to position the head beneath the outer surface of the bone. The bone-engaging portion of the suture anchor will thus be mostly disposed within and engaged with cancellous bone, rather than cortical bone. This is due to the fact that the cortical bone is only about 1 mm to 3 mm in length, and the driver head is often longer than 3 mm. Once implanted, tension applied to the anchor via the sutures can cause the anchor to migrate into the cortical bone and thus the head of the suture anchor can become proud, resulting in a weak fixation among other problems.

Accordingly, there remains a need for improved methods and devices for attaching soft tissue to bone.

SUMMARY OF THE INVENTION

In one embodiment, a suture anchor is provided having an elongate body with proximal and distal ends and an inner

2

lumen extending therethrough. At least one bone-engaging surface feature, such as a thread, can be formed on at least a portion of an external surface thereof for engaging bone. The inner lumen of the elongate body can include a suture-engaging member extending substantially transverse to an axis of the inner lumen and adapted to receive a suture therearound such that a suture can extend around the suture-engaging member and trailing ends of the suture can extend through the inner lumen and out of the proximal end of the elongated body.

The elongate body can have a variety of configurations. In one embodiment, the elongate body can include cut-outs formed in opposed sidewalls thereof and extending proximally from the distal end of the elongate body. The cut-outs can be in communication with the inner lumen. In an exemplary embodiment, the suture-engaging member is positioned distal of a proximal end of the cut-outs. The suture-engaging member can be, for example, a post extending between opposed walls of the inner lumen. In another embodiment, the suture-engaging member can be positioned just proximal to a distal-most end of the elongated body such that the distal end of the elongated body includes a suture-seating groove formed therein and configured to seat at least one suture. The elongate body can also include other features. For example, at least a portion of the inner lumen can have an asymmetrical cross-sectional shape, such as a hexagonal cross-sectional shape, for receiving a driver tool therein. In another embodiment, the distal end of the elongate body can be rounded.

In another embodiment, a suture anchor is provided having a threaded, cannulated body with proximal and distal ends. The distal end can include opposed cut-outs formed in opposed sidewalls thereof and a suture-engaging member extending between the opposed sidewalls and adjacent to the opposed cut-outs such that a suture can extend around the suture-engaging member and trailing ends of the suture can extend through the body. In an exemplary embodiment, the suture-engaging member extends substantially perpendicular to a longitudinal axis of the body. The device can also include a suture disposed around the suture-engaging member and having trailing ends extending through the body.

In yet another embodiment, an apparatus for anchoring tissue to bone is provided and includes a suture anchor having an inner lumen extending between proximal and distal ends thereof. The distal end can include opposed cut-outs formed in opposed sidewalls thereof and a suture-engaging member extending between the opposed sidewalls and adjacent to the opposed cut-outs such that a suture can extend around the suture-engaging member and trailing ends of the suture can extend through the inner lumen of the suture anchor. The apparatus can also include a driver having an elongate shaft and a distal end adapted to be received within and to engage a proximal portion of the inner lumen of the suture anchor. In an exemplary embodiment, the elongate shaft includes an inner lumen extending therethrough for receiving a suture extending through the inner lumen of the suture anchor. A distal end of the elongate shaft can include opposed cut-outs formed therein for allowing a suture extending from the suture anchor to extend externally along the elongate shaft of the driver. In other embodiments, the distal end of the elongate shaft can include a hexagonal cross-sectional shape, and at least a proximal portion of the inner lumen the suture anchor can have a complementary hexagonal cross-sectional shape.

Methods for anchoring suture to bone are also provided. In one exemplary embodiment, the method can include coupling a suture to a suture anchor such that the suture extends around a suture-engaging member formed in a distal end of the suture

anchor and trailing ends of the suture extend through an inner lumen extending through the suture anchor. A driver can be inserted into the proximal end of the suture anchor, and the trailing ends of the suture anchor can extend through an inner lumen formed in the driver. The driver can then be actuated to insert the suture anchor into bone to anchor the suture to the bone. While the suture can have various configurations, in one embodiment the suture can include first and second suture strands that extend around the suture-engaging member and that have trailing ends that extend through the inner lumen of the suture anchor and through the inner lumen of the driver. In other aspects, the suture anchor can include threads formed thereon and the driver can be rotated to drive the suture anchor into bone. In an exemplary embodiment, the threads extend from a proximal end of the suture anchor to a distal end of the suture anchor such that the suture anchor is fully threaded into bone.

In yet another embodiment, a suture anchor is provided having an elongate body with proximal and distal ends and an inner lumen extending therethrough. At least one bone-engaging surface feature can be formed on an external surface thereof for engaging bone. The suture anchor can also include a rotatable member extending between opposed sidewalls of the inner lumen and adapted to rotate relative to the elongate body. In one embodiment, the rotatable member can be disposed adjacent the distal end of the elongate body, and it can extend substantially perpendicular to a longitudinal axis of the suture anchor. The rotatable member can be, for example, a post extending between opposed walls of the inner lumen. In another embodiment, the elongate body can include cut-outs formed in opposed sidewalls thereof, extending proximally from the distal end of the elongate body, and in communication with the inner lumen. The rotatable member can be positioned distal of a proximal end of the cut-outs. In another embodiment, the rotatable member can be positioned just proximal to a distal-most end of the elongated body such that the distal end of the elongated body includes a suture-seating groove formed therein and configured to seat at least one suture. The device can also include a suture disposed around the rotatable member and having trailing ends extending through the suture anchor.

In other aspects, an apparatus for anchoring tissue to bone is provided and includes a suture anchor having at least one surface feature formed on an external surface thereof and adapted to engage bone, an inner lumen extending there-through between proximal and distal ends thereof, and a rotatable member extending across opposed sidewalls of the inner lumen such that a suture can extend around the rotatable member and trailing ends of the suture can extend through the inner lumen of the suture anchor. The apparatus can also include a driver having an elongate shaft and a distal end adapted to be received within and to engage a proximal portion of the inner lumen of the suture anchor.

Exemplary methods for anchoring suture to bone are also provided, and in one embodiment the method can include coupling a suture to a suture anchor such that the suture extends around a rotatable member rotatably disposed within in a distal end of the suture anchor and trailing ends of the suture extend through an inner lumen extending through the suture anchor. A driver can be inserted into the proximal end of the suture anchor, and the driver can be actuated to insert the suture anchor into bone and thereby anchor the suture to the bone. The method can also include pulling one of the trailing ends of the suture to cause the rotatable member to rotate. In one embodiment, the driver can be removed from the suture anchor prior to pulling one of the trailing end of the suture. In an exemplary embodiment, the suture can include a

wire attached thereto and pulling the suture can include pulling the wire. In other embodiments, a second suture can be coupled to the wire such that pulling the wire pulls both sutures around the rotatable member and through the inner lumen of the suture anchor.

In yet another embodiment, a suture anchoring system is provided and includes a suture anchor having an inner lumen extending therethrough and a suture-engaging member extending across opposed sidewalls of the inner lumen, and at least one suture having a terminal end that is coupled to at least one wire extending through the inner lumen of the suture anchor and around the suture-engaging member. In an exemplary embodiment, the wire(s) has a diameter that is less than a diameter of the suture(s) coupled thereto. The wire(s) can be connected to the suture(s) using various techniques, such as threading the wire(s) through the terminal end of the suture(s), looping the wire(s) around the terminal end of the suture(s), welding the wire(s) to the terminal end of the suture(s), mating the wire to the terminal end of the at least one suture using a crimp band, and winding a coiled portion of the wire(s) around the terminal end of the suture(s). The suture anchoring system can also include a driver having a distal end adapted to extend into and engage the inner lumen of the suture anchor. The wire(s) can include a first terminal end coupled to the terminal end of the sutures(s), and a second terminal end coupled to the driver.

In yet another embodiment, a suture anchoring system is provided having a threaded, cannulated suture anchor with proximal and distal ends, and a suture-engaging member disposed within a distal end of the suture anchor, and at least one suture having a terminal end that is coupled to a wire extending through the suture anchor and extending around the suture-engaging member. The system can also include a driver having a distal end adapted to extend into and engage the a proximal end of the suture anchor.

In other aspects, a method for anchoring suture to bone is provided and includes coupling a wire to a suture anchor such that the wire extends around a suture-engaging member extending across opposed sidewalls of an inner lumen of the suture anchor and first and second terminal ends of the wire extend through the inner lumen of the suture anchor, inserting the suture anchor into bone, and pulling the first terminal end of the wire to pull at least one suture strand coupled to the second terminal end of the wire through the inner lumen of the suture anchor and around the suture-engaging member. In one embodiment, the wire can be coupled to first and second suture strands such that pulling the first terminal end of the wire pulls the first and second suture strands through the inner lumen of the suture anchor and around the suture-engaging member. Alternatively, the wire can be coupled to a driver that is inserted into the inner lumen of the suture anchor, and that is actuated to drive the suture anchor into bone. Removing the driver from the suture anchor can be effective to pull the wires. The method can also include injecting a material through the inner lumen of the driver and into the inner lumen of the suture anchor. The material can be, for example, a bone-growth promoting material, a sealant, an adhesive, and combinations thereof. The method can also include attaching the suture(s) to tissue to anchor the tissue to the bone.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be more fully understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

FIG. 1A is a perspective view of one embodiment of a cannulated suture anchor;

5

FIG. 1B is a cross-sectional view of the suture anchor of FIG. 1A;

FIG. 1C is a perspective view of the suture anchor of FIG. 1A having first and second sutures coupled thereto;

FIG. 2 is a cross-sectional view of a distal portion of a suture anchor having a rotatable suture-engaging member according to another embodiment of the present invention;

FIG. 3A is a cross-sectional view of one embodiment of a driver tool;

FIG. 3B is a perspective view of the driver tool of FIG. 3A;

FIG. 3C is a perspective view of the driver tool of FIG. 3A coupled to a suture anchor and having a suture extending therethrough;

FIG. 4A is a cross-sectional view of the suture anchor of FIG. 1A having another embodiment of a driver tool disposed therein;

FIG. 4B is a cross-sectional view of the driver tool of FIG. 4A taken across line B-B;

FIG. 5A is a perspective view of the suture anchor of FIG. 1A having first and second sutures coupled thereto, showing a wire coupled to the terminal end of each suture;

FIG. 5B is a perspective view of the suture anchor of FIG. 1A having first and second sutures coupled thereto, showing first and second wires coupled to the terminal ends of the first and second sutures, respectively;

FIG. 5C is a perspective view of the suture anchor and sutures of FIG. 5B, showing the wires pulling the sutures through the suture anchor;

FIG. 6 is a side view of a technique for threading a wire to a suture;

FIG. 7 is a side view of a technique for tying a wire to a suture;

FIG. 8 is a side view of a technique for welding a wire to a suture;

FIG. 9 is a side view of a technique for mating a wire to a suture using a clamp;

FIG. 10 is a side view of a technique for mating a wire to a suture using a coil formed on the wire;

FIG. 11A is a cross-sectional view of the suture anchor of FIG. 1A having a wire extending therethrough and coupled to a distal end of a driver;

FIG. 11B is a cross-sectional view of the suture anchor of FIG. 1A having a wire extending therethrough and coupled to a proximal end of a driver;

FIG. 11C is a cross-sectional view of a portion of a driver tool, showing a technique for mating a wire thereto;

FIG. 12A is a cross-sectional view of the suture anchor of FIG. 1A, showing one technique for coupling two sutures thereto;

FIG. 12B is a cross-sectional view of the suture anchor of FIG. 1A, showing another technique for coupling two sutures thereto;

FIG. 12A is a cross-sectional view of the suture anchor of FIG. 1A, showing a technique for coupling a suture thereto; and

FIG. 12A is a cross-sectional view of the suture anchor of FIG. 1A, showing yet another technique for coupling a suture thereto.

DETAILED DESCRIPTION OF THE INVENTION

Certain exemplary embodiments will now be described to provide an overall understanding of the principles of the structure, function, manufacture, and use of the devices and methods disclosed herein. One or more examples of these embodiments are illustrated in the accompanying drawings. Those of ordinary skill in the art will understand that the

6

devices and methods specifically described herein and illustrated in the accompanying drawings are non-limiting exemplary embodiments and that the scope of the present invention is defined solely by the claims. The features illustrated or described in connection with one exemplary embodiment may be combined with the features of other embodiments. Such modifications and variations are intended to be included within the scope of the present invention.

The present invention generally provides methods and devices for anchoring suture to bone. In an exemplary embodiment, a cannulated suture anchor is provided and it includes a suture-engaging member formed therein and configured to receive a suture therearound such that trailing ends of the suture can extend through the suture anchor. The use of a cannulated suture anchor also allows a driver to be inserted into the inner lumen of the suture anchor for driving the suture anchor into bone. Such a configuration will allow the torque strength of the suture anchor to be maximized due to the increased engagement between the suture anchor and the driver. This in turn will allow the suture anchor to be formed from a broad range of materials, including bioabsorbable and/or osteoconductive materials. The use of a cannulated suture anchor will also eliminate the need for a driver head formed on the suture anchor, and as a result the entire length of the suture anchor can be configured to be fully engaged through the thickness of hard cortical bone, thus optimizing cortical bone fixation to provide a more secure fixation. This will help prevent migration of the suture anchor. A cannulated suture anchor is also particularly advantageous as it allows materials, such as bone-growth promoting materials, sealants, adhesives, etc., to be introduced therein to facilitate fixation. The present invention also provides exemplary sutures and drivers that can be used with the various methods and devices disclosed herein, or with other methods and devices known in the art. A person skilled in the art will appreciate that, while methods and devices are disclosed herein for anchoring soft tissue to bone, the methods and devices can be used in a variety of other medical procedures for anchoring various objects to one another.

FIGS. 1A-1C illustrate one exemplary embodiment of a cannulated suture anchor 10 for anchoring soft tissue to bone. As shown, the suture anchor 10 is in the form of a generally elongate body having proximal and distal ends 10a, 10b with an inner lumen 10c extending therethrough. At least one bone-engaging surface feature 12 can be formed on at least a portion of an external surface thereof for engaging bone. The suture anchor 10 also includes a suture-engaging member 14 disposed within the inner lumen 10c adjacent to the distal end 10b of the suture anchor 10. As shown in FIG. 1C, the suture-engaging member 14 is adapted to receive one or more sutures (two sutures 16, 18 are shown) therearound such that the suture(s) can extend around the suture-engaging member 14 and trailing ends of the suture(s) can extend through the inner lumen 10c and out of the proximal end 10a of the suture anchor 10.

The body of the suture anchor 10 can have a variety of configurations, shapes, and sizes. In an exemplary embodiment, the body is configured to be implanted within a bone tunnel formed in bone, and more preferably it has a size and shape that allows it to be fully engaged through the thickness of the cortical bone. In the illustrated embodiment the body has a generally elongate cylindrical shape with a blunt or rounded distal end 10b to facilitate introduction into a bone tunnel. The proximal end 10a of the body is head-free, as the cannulated configuration of the body allows a driver to be inserted into the inner lumen 10c to drive the suture anchor 10 into bone. As indicated above, the suture anchor 10 can also

include one or more bone-engaging surface features formed thereon and adapted to engage bone. While various surface features can be used, such as teeth, ridges, protrusions, etc., in an exemplary embodiment the body can include one or more threads extending therearound. In the illustrated embodiment a single thread extends around the body from the proximal end **10a** and it terminates proximal to the distal end **10b**. The particular location at which the thread terminates can vary depending on the particular configuration of the suture anchor **10**. As will be discussed in more detail below, the illustrated suture anchor **10** can include opposed cut-outs formed in the distal end thereof and the thread can terminate just proximal to the proximal end of the cut-outs.

The suture anchor **10** can also be formed from a variety of materials. In an exemplary embodiment, the material has physical properties that are sufficient to allow a driver to be inserted into the inner lumen **10c** of the suture anchor **10** and to be used to drive the suture anchor **10** into bone without damaging the suture anchor **10**. The properties of the material will of course depend on the particular configuration of the suture anchor **10**. For example, the inner lumen **10c** of the suture anchor **10** can have a length that maximizes the torque strength of the suture anchor **10** as well as the amount of surface contact between a driver and the suture anchor **10**, thus allowing weaker materials, such as bioabsorbable and/or osteoconductive materials to be used. A person skilled in the art will appreciate that a variety of other materials, including plastics and metals, can be used to form the suture anchor **10**.

As previously indicated above, the suture anchor **10** can also include a suture-engaging member **14** formed therein. The suture-engaging member **14** can have a variety of configurations, but in an exemplary embodiment it is adapted to engage one or more sutures that extend through the inner lumen **10c** of the suture anchor **10**. As shown in FIGS. 1A and 1B, the suture-engaging member **14** is in the form of a post that extends transversely across the inner lumen **10c** and between opposed inner sidewalls of the suture anchor **10**. The angular orientation of the suture-engaging member **14** relative to a longitudinal axis **A** of the inner lumen **10c** can vary, but in an exemplary embodiment the suture-engaging member **14** extends substantially perpendicular to the longitudinal axis **A** of the inner lumen **10c**. The location of the suture-engaging member **14** can also vary, but in an exemplary embodiment the suture-engaging member **14** is positioned at or adjacent to the distal end **10b** of the suture anchor **10**. In the embodiment shown in FIGS. 1A and 1B, the suture-engaging member **14** is located just proximal to the distal-most end **10b** of the suture anchor **10** so as to form a suture-seating groove **22a** in the distal-most end of the suture anchor **10**. This recessed configuration of the suture-engaging member **14** can allow a suture(s) disposed around the suture-engaging member **14** to sit flush or sub-flush with the distal end **10b** of the suture anchor **10** such that the suture(s) will not interfere with insertion of the suture anchor **10** into bone. A person skilled in the art will appreciate that the suture-engaging member **14** can be integrally formed with the suture anchor **10**, i.e., the suture anchor **10** and suture-engaging member **14** can be molded as a single unit or formed from a single piece of material, or the suture-engaging member **14** can be fixedly or removably mated to the suture anchor **10**.

As further shown in FIGS. 1A-1C, in order to facilitate positioning of a suture(s) around the suture-engaging member **14**, the suture anchor **10** can include one or more cut-outs formed in a sidewall thereof adjacent to the suture-engaging member **14**. As best shown in FIG. 1A, in an exemplary embodiment the suture anchor **10** includes a cut-out **22** that begins just proximal to the location of the suture-engaging

member **14**, and that extends around the distal end **10b** of the suture anchor **10** such that the suture anchor **10** includes opposed cut-outs or openings formed on opposed sides of the suture-engaging member **14** and a distal cut-out that defines the suture-seating groove **22a** for seating a suture(s). The cut-out **22** can also define opposed distal arms **11a**, **11b** on the suture anchor **10** that are spaced a distance apart from one another and that have the suture-engaging member **14** extending therebetween.

A person skilled in the art will appreciate that the particular location and configuration of the cut-out **22** can define the particular location and configuration of the suture-engaging member **14**, as the cut-out **22** can be formed during manufacturing to create the suture-engaging member **14**. Alternatively, the particular location and configuration of the opposed arms **11a**, **11b** can define the particular location and configuration of the cut-out **22**, as the shape and size of the arms **11a**, **11b** defines the shape and size of the cut-out **22**. The location of the suture-engaging member **14** relative to the cut-out **22** and/or arms **11a**, **11b** will also define the configuration of the distal end of the suture anchor **10**, and whether the suture anchor **10** includes a distal groove **22a** for seating a suture(s).

As further shown in FIGS. 1A and 1B, the inner lumen **10c** of the suture anchor **10** can be adapted to receive a driver therein for driving the suture anchor **10** into bone. While various techniques can be used to facilitate engagement between the inner lumen **10c** and a driver mechanism, in an exemplary embodiment the inner lumen **10c**, or at least a portion thereof, has an asymmetrical shape that complements a corresponding asymmetrical shape of a driver. The asymmetrical portion preferably extends along a substantial length of the inner lumen **10c** so as to maximum surface contact between a driver and the suture anchor. By way of non-limiting example, FIGS. 1A and 1B illustrate a hexagonal cross-sectional shape formed in a proximal portion of the inner lumen **10c** for receiving a driver having a corresponding hexagonal drive tip, as will be discussed in more detail below. The hexagonal cross-section extends from the proximal-most end **10a** of the suture anchor **10** and terminates just proximal to the proximal end of the cut-out **22**.

In another embodiment, rather than having a fixed suture-engaging member **14**, the suture anchor can include a suture-engaging member that is rotatably disposed therein. Such a configuration will allow for suture slidability, providing a pulley system to facilitate longitudinal movement of a suture through the inner lumen of the suture anchor. In particular, one or more terminal ends of one or more sutures disposed around the suture-engaging member can be pulled to slide the suture(s) longitudinally within the inner lumen of the suture anchor, and the suture-engaging member can rotate to facilitate such longitudinal movement.

While the rotatable suture-engaging member can have a variety of configurations, FIG. 2 illustrates one exemplary embodiment of a rotatable suture-engaging member **14'** that is disposed within an inner lumen **10c'** of a suture anchor **10'**. As shown, the suture-engaging member **14'** is in the form of a generally cylindrical body having opposed sidewalls **15a'**, **15b'** and a continuously curved outer wall **15c'** extending therearound and between the opposed sidewalls **15a'**, **15b'**. A groove **15d'** is formed in the outer wall **15c'** for seating one or more sutures, such as suture **16'**. The suture-engaging member **14'** also includes a bore **15e'** extending therethrough between the opposed sidewalls **15a'**, **15b'** for receiving a pin member **20'** that allows the suture-engaging member **14'** to rotate therearound. The pin member **20'** can extend into opposed bores or openings **9a'**, **9b'** formed in an inner surface

of the opposed arms **11a'**, **11b'** of the suture anchor **10**. A person skilled in the art will appreciate that a variety of other techniques can be used to rotatably mate the suture-engaging member **14'** to the suture anchor **10'**. Alternatively, other techniques can be used to facilitate suture slidability, such as a lubricious coating applied to the suture engaging member.

As previously indicated, the suture anchors disclosed herein can be cannulated for receiving a driver. While various drivers known in the art can be used, FIGS. **3A** and **3B** illustrate one exemplary embodiment of a driver **30** for driving a suture anchor into bone. In this embodiment, the driver **30** is adapted to allow the terminal ends of a suture(s) extending through the suture anchor to extend along an external surface thereof. As shown, the driver **30** is in the form of a generally elongate shaft having proximal and distal ends **30a**, **30b**. While not shown, the proximal end **30a** can include a handle or other grasping mechanism formed thereon to facilitate grasping and manipulation of the device. The distal end **30b** includes a reduced diameter portion or tip **32** that is configured to fit within the inner lumen of a suture anchor, such as lumen **10c** of anchor **10**. The shape of the tip **32** can vary, but in an exemplary embodiment it has an asymmetrical shape that allows the tip **32** to engage the inner lumen **10c** of the anchor **10**. In the illustrated embodiment the tip **32** has a generally hexagonal cross-sectional shape that complements the generally hexagonal cross-sectional shape of the inner lumen **10c** in the anchor. The length of the tip **32** can also vary, but in an exemplary embodiment the tip **32** has a length that allows it to extend through a substantial portion of the lumen **10c** in the anchor **10** so as to maximize surface contact between the tip **32** and the anchor **10**. For example, the length **32** can correspond to a length of the hexagonal portion of the inner lumen **10c** in the anchor. A person skilled in the art will appreciate that the tip **32** can have a variety of other shapes, sizes, and configurations.

As further shown in FIGS. **3A** and **3B**, the tip can also include one or more suture-receiving recesses or grooves formed therein and extending longitudinally along the length of the tip **32** for seating one or more sutures. In the illustrated embodiment first and second opposed suture-receiving grooves **34a**, **34b** are formed in the tip **32** and extend along the length thereof. The grooves **34a**, **34b** can also optionally extend a distance beyond a proximal end of the tip **32**, as shown, or along the entire length of the driver **30**, so as to further prevent the suture(s) from interfering with insertion of the suture anchor **10**.

FIG. **3C** illustrates a cut-away view of the driver **30** disposed within a suture anchor **100** that is similar to suture anchor **10**. As shown, a suture **36** is disposed through the lumen **100c** of the suture anchor **100** and around the suture-engaging member **114** such that first and second trailing ends **36a**, **36b** of the suture **36** extend proximally from the proximal end **100a** of the suture anchor **100**. In order to allow the distal tip **32** of the driver **30** to fit within and engage the inner lumen **100c** of the suture anchor **100**, the opposed ends of the suture **36** extending from the suture-engaging member **14** can be seated within the opposed grooves (only one groove **34a** is shown) formed in the tip **32**.

In another embodiment, as shown in FIGS. **4A** and **4B**, the driver **40** can be cannulated to allow the terminal ends of a suture(s) extending through the suture anchor to extend there-through, rather than extending external to the driver. In particular, the driver **40** is similar to driver **30**, except that the driver **40** includes an inner lumen **40c** extending through the entire length thereof for receiving one or more sutures, rather than having suture-receiving grooves formed in the distal tip. FIG. **4A** illustrates the distal tip **42** of the driver **40** disposed

within and engaging the inner lumen **10c** of suture anchor **10**. As shown, the diameter of the remainder of the driver **40** as compared to the reduced-diameter of the distal tip **42** can provide a stop surface **44** that limits the depth of insertion of the distal tip **42** into the inner lumen **10c** of the anchor **10**. As previously discussed, the length of the distal tip **42**, and thus the depth of insertion of the tip **42** into the inner lumen **10c** of the anchor **10**, can vary depending on the size and shape of the suture anchor **10**. In an exemplary embodiment, the tip **42** is configured to be inserted into a substantial portion of the inner lumen **10c** so as to maximum surface contact between the driver **40** and the suture anchor **10**. In other embodiments, the cannulated driver **40** can also optionally be used to allow other materials, such as bone-growth promoting materials, adhesives, biologics, and other injectable materials, to be introduced through the driver and into the suture anchor.

As previously indicated, the suture anchors and drivers disclosed herein can be configured for use with one or more sutures. The particular quantity of sutures used with a suture anchor and driver can depend on the size of the suture anchor and the driver, and in particular on the diameter of the inner lumen of the suture anchor and the size of the suture-engaging groove formed in the driver (for driver **30**) or the diameter of the lumen in the driver (for driver **40**). For example, where the suture anchor has a relatively small inner lumen, the driver will necessarily have a relatively small diameter and thus small suture-engaging grooves (for driver **30**) or a small inner lumen (for driver **40**). It may therefore only be possible to use a single suture that is positioned around the suture-engaging member on the suture anchor, and that has two trailing ends extending through the suture-receiving grooves in the driver (for driver **30**) or through the inner lumen in the driver (for driver **40**). While a single suture can be sufficient to anchor tissue to bone, it is preferred to use more than one, and more preferably two, sutures. Thus, rather than increasing a size of the suture anchor and/or the driver, the present invention provides various exemplary techniques for utilizing two sutures with a suture anchor and driver that are configured to seat only one suture. This is particularly advantageous as the suture anchor can be sized to be fully disposed within cortical bone, while the diameter of the inner lumen of the suture anchor and of the distal tip of the driver are maximized to increase the torque failure rating. This also enables the anchor to be made from a broad range of materials, including brittle or weaker materials such as those previously disclosed herein.

In one embodiment, one or more sutures can be coupled to a thin wire, thread, string, small diameter suture, etc. (hereinafter generically referred to as a wire), and the wire can extend through the suture-receiving grooves or inner lumen in the driver. Since the wire will have a diameter that is significantly smaller than a diameter of the suture, one or more wires can be used in place of the trailing end of one or more sutures, thus allowing multiple sutures to be used. This is illustrated, by way of non-limiting example, in FIGS. **5A** and **5B**.

FIG. **5A** illustrates a suture anchor **10** having first and second sutures **16**, **18** extending therethrough and around the suture-engaging member (not shown). Since all four trailing ends (i.e., the ends extending from the suture-engaging member) of the sutures **16**, **18** will not fit within the suture-receiving grooves in driver **30** (not shown) or through the inner lumen of driver **40** (not shown), only one trailing end of each suture **16**, **18** can extend through the driver and the terminal end **16b**, **18b** of the other trailing end of each suture **16**, **18** can be positioned just distal to the proximal end of the cut-out **22**. A wire **50** can be mated to each terminal end **16b**, **18b** and the

11

wire can extend proximally from the terminal ends **16b**, **18b** and through the driver. In use, once the suture anchor **10** is implanted in bone, the driver can be removed and the wire **50** can be pulled to pull the terminal ends **16b**, **18b** of the sutures **16**, **18** proximally around the suture-engaging member and through the suture anchor **10**. The terminal ends can thereafter be used to secure tissue to bone. A person skilled in the art will appreciate that the sutures can remain external to the driver and anchor while only the wire(s) extend through the driver and anchor, and the sutures can be pulled into the anchor after placement of the suture anchor.

In another embodiment, shown in FIG. **5B**, the terminal ends **16b**, **18b** of the sutures **16**, **18** can be mated to separate wires **52**, **54** that extend through the inner lumen of the driver. FIG. **5B** illustrates a partially cut-away view of the suture anchor **10**, showing the distal tip **42** of driver **40** disposed therein and having the wires **52**, **54** extending therethrough. As with the embodiment shown in FIG. **5A**, one trailing end of each suture **16**, **18** and the wires **52**, **54** can extend through the driver **40**, thus allowing two sutures **16**, **18** to be used with the anchor **10**. After the suture anchor is implanted, the driver **40** can be removed and the wires **52**, **54** can be used to pull the terminal ends **16b**, **18b** of the sutures **16**, **18** around the suture-engaging member in a proximal direction, as shown in FIG. **5C**. A person skilled in the art will appreciate that while FIG. **5B** illustrates driver **40**, the wires can be used with driver **30**, or with any other driver known in the art.

The use of wires extending through a cannulated driver can also be advantageous in that various materials, such as those previously discussed, can be introduced through the inner lumen of the driver with the wires in place. For example, an adhesive can be injected through the inner lumen of the driver prior to pulling the terminal ends **16b**, **18b** of the sutures **16**, **18** proximally, thus allowing the suture **16**, **18** to be secured to the suture anchor **10**.

A person skilled in the art will appreciate that a variety of techniques can be used to mate a wire to one or more sutures. By way of non-limiting example, FIGS. **6-10** illustrate various exemplary mating techniques. In the embodiment shown in FIG. **6**, a single wire **60** is threaded through a terminal end **62a** of a first suture **62** and then is threaded back through a terminal end **64a** of a second suture **64** such that trailing ends **60a**, **60b** of the wire **60** extend from the terminal ends **62a**, **64a** of the sutures **62**, **64**. In another embodiment, shown in FIG. **7**, the wire **70** is looped or knotted around the terminal ends **72a**, **74a** of two sutures **72**, **74** such that trailing ends **70a**, **70b** of the wire **70** extend from the terminal ends **72a**, **74a** of the sutures **72**, **74**. In the embodiment shown in FIG. **8**, the wire **80** is positioned between two sutures **82**, **84** and it is welded to the sutures **82**, **84** using an ultrasonic welder **86**, or using other welding techniques known in the art. In another embodiment, shown in FIG. **9**, a wire **90** can be attached to a clamp or crimp band **96** that is disposed around and closed to engage the terminal ends **92a**, **94a** of two sutures **92**, **94**. In yet another embodiment, shown in FIG. **10**, the wire **110** can include a spring or coiled portion **110c** formed on a terminal end thereof. The coiled portion **110c** can be positioned around the terminal end **112a** of a suture **112**, and it can be biased to a shape in which the coiled portion **110c** engages the suture **112**. When the wire **110** is pulled to pull the suture **112**, the coiled portion **110c** can optionally decrease in diameter to provide a more secure engagement between the wire **110** and the suture **112**. A person skilled in the art will appreciate that the aforementioned mating techniques can be used to mate a single wire to one or more sutures, or to mate multiple wires to a single suture. Moreover, a variety of other mating techniques can be used, including adhesives etc.

12

In another embodiment, one of the trailing ends of a suture or a wire can be mated to the driver. As the driver is removed from the suture anchor, the driver will pull the suture or wire attached thereto around the suture engaging member. This is illustrated in FIGS. **11A** and **11B**. In the embodiment shown in FIG. **11A**, a first end **132a** of a wire **132** is attached to a distal end **130d** of a driver **130**. The second end **132b** of the wire **132** extends through the suture anchor **10** and proximally from the driver **130**, where it can be coupled to a suture. The wire **132** can be pulled into the suture anchor **10** and around the suture-engaging member **14** as the driver **130** is removed. In another embodiment shown in FIG. **11B**, the first end **132a'** of the wire **132'** can be attached to a proximal end **130p'** of the driver **130'**. A person skilled in the art will appreciate that the particular attachment location of the wire to the driver can vary. Moreover, a variety of techniques can be used to attach a suture or a wire to a driver. By way of non-limiting example, FIG. **11C** illustrates one exemplary embodiment of an attachment technique. As shown, the distal tip **152** of a driver includes first and second bores **152a**, **152b** formed therein, and the trailing ends of first and second wires **154**, **156** are inserted through the bores **152a**, **152b**. A knot is formed in the terminal end of each wire **154**, **156** to retain the wires **154**, **156** within the bores **152a**, **152b**. In use, instead of having four trailing ends of two sutures extending through the driver, only one trailing end of each suture or wire will extend through the driver while the other end will remain attached to the distal tip **152**. Alternatively, the trailing ends of two wires can extend through the driver and attach to sutures positioned external to the driver. When the driver is removed, the driver will pull the sutures around the suture-engaging member to allow the trailing ends of the sutures to be used to secure tissue to bone. The knots can be cut or otherwise removed to detach the sutures from the driver.

In other embodiments, shown in FIGS. **12A-12D**, various threading techniques can be used to allow two sutures to be used with the suture anchors disclosed herein. FIG. **12A** illustrates suture anchor **10** having two sutures **16**, **18** extending through the inner lumen **10c** of the suture anchor **10** and looped around the suture-engaging member **14**. Conversely, one of the sutures, e.g., suture **18**, can extend along an external surface of the suture anchor **10**, as shown in FIG. **12B**. Similarly, a single suture can be used and it can extend through both the inner lumen **10c** of the suture anchor **10**, as well as along an external surface of the suture anchor **10**. This is illustrated in FIG. **12C**. As shown, a first trailing end **16a** of the suture **16** is positioned along an external surface of the suture anchor **10**, and the second trailing end **16b** of the suture **16** is threaded around the suture-engaging member **14** and up through the inner lumen **10c**, where a first loop is formed. The second trailing end **16b** of the suture **16** is then passed back through the inner lumen **10c** and positioned to extend externally along the length of the suture anchor **10**. While FIG. **12C** illustrates both trailing ends **16a**, **16b** of the suture **16** extending externally along the suture anchor **10**, in another embodiment one trailing end can extend externally along the suture anchor **10** while the other trailing end can extend through the inner lumen **10c** of the suture anchor **10**. This is illustrated in FIG. **12D**, which shows the suture **16** having a first trailing end **16a** extending through the inner lumen **10c** of the suture anchor **10** and proximally beyond the proximal end **10a** of the suture anchor **10**. The second trailing end **16b** is passed through the inner lumen **10**, around the suture-engaging member **14**, and externally around the suture anchor **10**. It is then passed back into the proximal end **10a** of the suture anchor and through the inner lumen **10c**, where it is positioned around the suture-engaging member **14** and externally

13

along the suture anchor **10**. A person skilled in the art will appreciate that a variety of other threading techniques can be used to allow one or more sutures to be used with the various suture anchors and/or drivers disclosed herein.

The present invention also provides exemplary methods for anchoring tissue to bone. While the method is described in connection with attaching soft tissue to bone, the methods and devices disclosed herein can be used in a variety of medical procedures for anchoring one structure to another. In general, a bore is formed in bone of a patient. The diameter of the bore is preferably slightly less than the largest outer diameter of the suture anchor, and the length of the bore is preferably the same as or slightly greater than a length of the suture anchor. The bore will extend fully through the cortical bone to allow the suture anchor to be fully engaged through the thickness of the cortical bone. The bore can also extend into the cancellous bone depending on the length of the suture anchor. One or more sutures (including sutures with wires coupled thereto) can be coupled to the suture anchor using various techniques, as previously discussed herein, and the distal tip of a driver can be inserted into the lumen in the suture anchor. The trailing ends of the suture(s) or wire(s) can extend externally along the driver or they can extend through an inner lumen of the driver. The driver can then be used to insert the suture anchor into the bone tunnel. For example, where the suture anchor includes threads formed thereon, the driver can be rotated to thread the suture anchor into the bone hole. The threads will engage the bone hole thereby preventing removal of the suture anchor. In other embodiments, the driver can be used to tap the bone anchor into the bone hole, and an interference fit, compression fit, and/or surface features, such as ribs or protrusions, formed on the suture anchor can be used to retain the suture anchor within the bone hole. The driver can also optionally be used to impact a threaded suture anchor into the bone hole. The threads can allow for later removal of the suture anchor.

Once the bone anchor is properly anchored within the bone hole, various materials, such as those previously discussed herein, can be introduced through the driver and into or around the suture anchor. The driver can then be removed. Where the suture(s) have wire(s) attached thereto, the wire(s) can be pulled to pull the suture(s) around the suture-engaging member of the suture anchor. If the suture anchor includes a rotatable suture-engaging member, the suture-engaging member will rotate as the suture(s) is pulled therearound. The trailing ends of the suture(s) can then be used to anchor soft tissue to the bone. For example, one or both trailing ends of the suture(s) can be attached to a needle to allow the needle to be used to thread the suture through tissue to be anchor to the bone. The suture(s) can be threaded through tissue either prior to or after insertion of the suture anchor into bone. Once the soft tissue is approximated toward the bone, the trailing ends of the suture(s) can be secured together and the excess trimmed as is typical in these situations to complete the surgery.

One skilled in the art will appreciate further features and advantages of the invention based on the above-described embodiments. Accordingly, the invention is not to be limited by what has been particularly shown and described, except as indicated by the appended claims. All publications and references cited herein are expressly incorporated herein by reference in their entirety.

What is claimed is:

1. A suture anchoring system, comprising:

a suture anchor having an inner lumen extending there-through and a suture-engaging member extending across opposed sidewalls of the inner lumen;

14

at least one suture having a terminal end that is coupled to a first terminal end of a flexible wire disposed in the inner lumen of the suture anchor and extending around the suture-engaging member, the wire having a second terminal end coupled to a driver, and the wire having a maximum diameter that is smaller than a minimum diameter of the at least one suture.

2. The suture anchoring system of claim **1**, wherein the at least one wire is threaded through the terminal end of the at least one suture.

3. The suture anchoring system of claim **1**, wherein the at least one wire is looped around the terminal end of the at least one suture.

4. The suture anchoring system of claim **1**, wherein the at least one wire is welded to the terminal end of the at least one suture.

5. The suture anchoring system of claim **1**, wherein the at least one wire is coupled to a coil wound around the terminal end of the at least one suture and adapted to engage the terminal end of the at least one suture.

6. The suture anchoring system of claim **1**, wherein the driver has a distal end adapted to extend into and engage the inner lumen of the suture anchor.

7. A suture anchoring system, comprising:

a threaded, cannulated suture anchor having proximal and distal ends, and a suture-engaging member disposed within a distal end of the suture anchor;

at least one suture having a terminal end that is coupled to a flexible wire extending through the suture anchor and extending around the suture-engaging member, wherein the wire includes a first terminal end coupled to the at least one suture, and a second terminal end coupled to a driver, and wherein a portion of the wire between the first and second terminal ends of the wire is disposed within the suture anchor.

8. The suture anchoring system of claim **7**, wherein the wire is coupled to the at least one suture using a mating technique selected from the group consisting of threading the wire through the terminal end of the at least one suture, looping the wire around the terminal end of the at least one suture, welding the wire to the at least one suture, mating the wire to the terminal end of the at least one suture using a crimp band, and winding a coil coupled to the wire around the at least one suture.

9. The suture anchoring system of claim **7**, wherein the driver has a distal end adapted to extend into and engage the proximal end of the suture anchor.

10. A suture anchoring system, comprising:

a suture anchor having an inner lumen extending there-through and a suture-engaging member extending across opposed sidewalls of the inner lumen;

at least one suture having a terminal end that is coupled to a flexible wire having first and second portions positioned in the inner lumen of the suture anchor and having a mid-portion located between the first and second portions and positioned around the suture-engaging member, the wire having a maximum diameter that is smaller than a minimum diameter of the at least one suture.

11. The suture anchoring system of claim **10**, wherein the at least one suture comprises first and second sutures each having a terminal end that is coupled to the wire.

12. The suture anchoring system of claim **10**, wherein a first terminal end of the wire is coupled to the at least one suture, and a second terminal end of the wire is coupled to a driver.