



US008104850B2

(12) **United States Patent**
Hager et al.

(10) **Patent No.:** **US 8,104,850 B2**
(45) **Date of Patent:** **Jan. 31, 2012**

(54) **FURNITURE STORAGE UNIT**

(75) Inventors: **Allen C. Hager**, Grand Rapids, MI (US);
Robert E. Jeffers, Ada, MI (US);
William K. Hofman, Ada, MI (US);
Brian L. Bultsma, Byron Center, MI
(US); **Scott Michael Miller**, Middleville,
MI (US); **Marvin C. Knauf**, Conklin,
MI (US); **Karl Heinz Mueller**,
Rosenheim (DE); **John R. Hamilton**,
Grand Rapids, MI (US); **Karl J. Mead**,
East Grand Rapids, MI (US)

(73) Assignee: **Steelcase Inc.**, Grand Rapids, MI (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 824 days.

(21) Appl. No.: **12/129,097**

(22) Filed: **May 29, 2008**

(65) **Prior Publication Data**

US 2008/0296457 A1 Dec. 4, 2008

Related U.S. Application Data

(60) Provisional application No. 60/940,913, filed on May
30, 2007, provisional application No. 60/940,879,
filed on May 30, 2007, provisional application No.
60/940,899, filed on May 30, 2007, provisional
application No. 60/940,891, filed on May 30, 2007.

(51) **Int. Cl.**

A47F 5/08 (2006.01)

A47B 47/00 (2006.01)

(52) **U.S. Cl.** **312/245**; 312/323

(58) **Field of Classification Search** 312/242,
312/245, 246, 257.1, 263, 265.5, 265.6, 322,
312/323, 327; 52/36.4, 36.5, 36.6; 108/106,
108/107, 108; 248/201, 220.21, 220.31,
248/220.41, 220.43, 225.21, 243, 246

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

359,094 A	3/1887	Perkins
360,611 A	4/1887	Mix
367,436 A	8/1887	Orum
579,722 A	3/1897	Petersen
620,594 A	3/1899	Ketchum
669,907 A	3/1901	Wemicke et al.
688,390 A	12/1901	Casler
715,243 A	12/1902	Casler
726,117 A	4/1903	Tobey
726,957 A	5/1903	Macey
739,007 A	9/1903	Kershaw
742,751 A	10/1903	Taylor
761,312 A	10/1903	Luellen

(Continued)


Primary Examiner — James O Hansen

(74) *Attorney, Agent, or Firm* — Price Heneveld LLP

(57) **ABSTRACT**

An office furniture unit has an outer face with slotted hangers, and a removable storage unit assembly including a bottom panel positioned in a generally horizontal orientation along the office furniture unit, and a top panel disposed above and generally parallel with the bottom panel. First and second panels are disposed at opposite ends of the top and bottom panels and are connected therewith to define a rigid, box-shaped case having an open back portion. The first and second end panels have rear portions with multiple vertically spaced slots. First and second hanger brackets have a rear portion with first hooks selectively received in the slotted hangers of the office furniture units, and a forward portion with second hooks selectively received in the slots in the rear portions of the first and second end panels to detachably support the case against the outer face of the office furniture unit.

25 Claims, 59 Drawing Sheets



U.S. PATENT DOCUMENTS							
769,705	A	9/1904	Mauro	3,713,257	A	1/1973	Beavers
781,562	A	1/1905	Senge	3,729,113	A	4/1973	Lopatka
795,931	A	8/1905	Pierce	3,748,005	A	7/1973	Chovanec et al.
880,132	A	2/1908	Ewing	3,748,006	A	7/1973	Levit et al.
884,550	A	4/1908	Wilmot	3,754,806	A *	8/1973	Nakagawa 312/265.5
887,369	A	5/1908	Wilmot	3,771,847	A	11/1973	Aylworth
890,207	A	6/1908	Anderson	3,771,849	A	11/1973	Barber
899,049	A	9/1908	Honor	3,779,623	A	12/1973	Motohashi
972,412	A	10/1910	Taussig	3,794,401	A	2/1974	Dean et al.
984,793	A	2/1911	Blomberg	D231,430	S	4/1974	Steinhauser
1,124,570	A	1/1915	Woltz	3,811,728	A	5/1974	Redemske
1,203,589	A	11/1916	Curtenius	3,814,491	A	6/1974	Kackley
1,327,426	A	1/1920	Erickson	3,818,672	A	6/1974	Moore, Sr.
1,342,083	A	6/1920	Arnold	3,825,215	A	7/1974	Borglum
1,348,680	A	8/1920	Woltz	3,834,659	A	9/1974	Siegal
1,629,270	A	5/1927	Hammer	3,853,294	A	12/1974	Albinson et al.
1,654,470	A	10/1927	Alheit	3,862,524	A	1/1975	McCrackin
1,720,050	A	7/1929	Morris et al.	3,875,711	A	4/1975	Palmer
2,010,660	A	8/1935	Ferris	3,886,698	A	6/1975	Raith et al.
2,092,531	A	9/1937	Dimick	3,915,328	A	10/1975	Hawes et al.
2,123,264	A	7/1938	Walter	3,936,107	A	2/1976	Gourdeau et al.
2,427,335	A	3/1945	Antonia et al.	RE28,994	E	10/1976	Aylworth
2,480,965	A	9/1949	Remke et al.	3,991,877	A	11/1976	Kraft et al.
2,481,935	A	9/1949	Larson	4,013,254	A	3/1977	Boundy et al.
D157,076	S	1/1950	Nemes	4,018,019	A	4/1977	Raith et al.
2,504,765	A	4/1950	Von Palmenberg	4,020,604	A	5/1977	Legler et al.
2,506,642	A	5/1950	Jacobi	4,040,588	A	8/1977	Papsco et al.
2,558,852	A	7/1951	Jacobi	4,042,287	A	8/1977	Hallen
2,571,622	A	10/1951	Schmidt	4,052,100	A	10/1977	Nikitits et al.
2,612,663	A	10/1952	Pearse	4,054,268	A	10/1977	Sher
2,618,682	A	11/1952	Thumim	4,060,277	A	11/1977	Leib
2,629,248	A	2/1953	Burdick	4,067,548	A	1/1978	Murphy
2,688,525	A	9/1954	Lindstrom	4,092,751	A	6/1978	Burkholder et al.
2,694,614	A	11/1954	Dent	4,097,014	A	6/1978	Boundy
2,744,714	A	5/1956	Parke	4,103,981	A	8/1978	Donahue et al.
2,772,846	A	12/1956	Skar	4,106,476	A	8/1978	Harsha
2,776,735	A	1/1957	Bancroft	4,119,287	A	10/1978	Mollenkopf
2,781,558	A	2/1957	Tarzia	4,120,124	A	10/1978	Temple et al.
2,845,187	A	7/1958	Bianchi	4,122,617	A	10/1978	Nielsen
2,903,316	A	9/1959	Schmidt	4,123,879	A	11/1978	Blodee et al.
2,936,147	A	5/1960	Stewart	4,141,612	A *	2/1979	Rowe 312/245
2,942,924	A	6/1960	Stangert	4,147,393	A	4/1979	Nelson et al.
D188,318	S	7/1960	Niederman	4,154,419	A	5/1979	Breidenbach
2,948,141	A	8/1960	Vahlstrom	4,190,926	A	3/1980	Cronin
3,002,787	A	10/1961	Ziegenfuss	4,193,650	A	3/1980	Gray et al.
3,009,739	A	11/1961	Hamilton	4,205,470	A	6/1980	Kapnek
3,018,861	A	1/1962	Somville	4,205,815	A	6/1980	Sauer et al.
3,051,427	A	8/1962	Alvarez	D256,297	S	8/1980	Gera et al.
3,067,882	A	12/1962	Ribbens et al.	4,222,542	A	9/1980	Wilson et al.
3,074,772	A	1/1963	Kessler et al.	4,228,906	A	10/1980	Jones
3,169,281	A	2/1965	Clements, Jr.	4,237,636	A	12/1980	Matthews
3,261,640	A	7/1966	Straits	4,265,500	A	5/1981	Berton et al.
3,294,461	A	12/1966	Barnard et al.	4,265,502	A	5/1981	Blodee et al.
3,296,745	A	1/1967	Johnson et al.	4,295,693	A	10/1981	Viklund
3,312,443	A	4/1967	Levigne	D263,097	S	2/1982	Poole
3,325,130	A	6/1967	Smith et al.	4,320,852	A	3/1982	Nagelkirk
3,342,514	A	9/1967	Ivanhoe et al.	4,320,935	A	3/1982	Nagelkirk
3,349,536	A	10/1967	Halko, Jr. et al.	4,322,958	A	4/1982	Eigemeier
D209,758	S	1/1968	Blink et al.	D265,952	S	8/1982	Theodore
3,371,454	A	3/1968	Anderson	4,349,113	A	9/1982	Schreiner
3,425,729	A	2/1969	Bisbing	4,375,907	A	3/1983	Vander Kooi et al.
3,456,995	A	7/1969	Nyquist	4,377,915	A	3/1983	Zossimas et al.
3,464,161	A	9/1969	Jonsson	4,382,311	A	5/1983	Watts
3,465,488	A	9/1969	Miller	4,384,567	A	5/1983	Katona
3,472,543	A	10/1969	Biro	4,401,222	A	8/1983	Kulikowski et al.
3,489,479	A	1/1970	Sulentic	4,403,434	A	9/1983	Jenkins
3,491,820	A	1/1970	Ostling	4,403,700	A	9/1983	Manlove
3,533,190	A	10/1970	Hilfinger et al.	4,404,776	A	9/1983	Ball et al.
3,553,916	A	1/1971	Lickliter et al.	4,405,255	A	9/1983	Wallace
3,563,626	A	2/1971	Ferdinand et al.	4,415,091	A	11/1983	Wolff
3,606,419	A	9/1971	Virkler et al.	D272,108	S	1/1984	Morris, Jr.
3,620,588	A	11/1971	Ferdinand et al.	4,437,712	A	3/1984	Wissinger
3,659,445	A	5/1972	Eads et al.	4,457,436	A	7/1984	Kelley
3,662,981	A	5/1972	Hogrebe	4,457,569	A	7/1984	Scheerhorn
3,664,275	A	5/1972	Kleinert	4,471,575	A	9/1984	Stout
3,697,363	A	10/1972	Martinez	4,471,638	A	9/1984	Scheerhorn
3,698,114	A	10/1972	Hirsch et al.	4,477,128	A	10/1984	Hasbrouck
3,712,698	A	1/1973	Propst et al.	4,515,494	A	5/1985	Robilliard et al.
				4,516,813	A	5/1985	Sekerich

US 8,104,850 B2

4,538,936 A	9/1985	Zeidl	5,078,461 A	1/1992	Beck et al.
4,541,599 A	9/1985	Schoumaker	5,088,250 A	2/1992	DeLong et al.
4,549,712 A	10/1985	Simon et al.	5,092,063 A	3/1992	Shultz
4,550,893 A	11/1985	Wiersema et al.	5,092,253 A	3/1992	Grund et al.
4,566,743 A	1/1986	Henriott	5,094,174 A	3/1992	Grund et al.
4,570,406 A	2/1986	DiFazio	D325,309 S	4/1992	Worrell
D282,886 S	3/1986	Williams	5,103,741 A	4/1992	Grund et al.
4,586,759 A	5/1986	Wrobel	5,104,182 A	4/1992	Rasnick et al.
4,591,214 A	5/1986	Reuter et al.	5,108,063 A	4/1992	Koerber, Sr. et al.
4,600,254 A	7/1986	Whalen	5,108,165 A	4/1992	Rorke et al.
4,615,570 A	10/1986	Goodman	D327,374 S	6/1992	Perez
4,618,192 A	10/1986	Kelley	5,121,976 A	6/1992	Haab et al.
4,619,727 A	10/1986	Hamisch, Jr.	5,123,549 A	6/1992	Finses et al.
4,620,743 A	11/1986	Eke	D327,794 S	7/1992	Zapf
4,629,167 A	12/1986	Kimura et al.	5,149,180 A	9/1992	Haab et al.
4,631,881 A	12/1986	Charman	5,154,388 A	10/1992	Magaro
4,633,789 A	1/1987	Kortering et al.	5,155,955 A	10/1992	Ball et al.
4,641,896 A	2/1987	Imura et al.	5,158,346 A	10/1992	Marks et al.
4,647,107 A	3/1987	Hoover et al.	D330,641 S	11/1992	Zapf
4,655,489 A	4/1987	Bisbing	D330,642 S	11/1992	Zapf
4,662,679 A	5/1987	Franck et al.	5,160,188 A	11/1992	Rorke et al.
4,671,481 A	6/1987	Beard	5,172,969 A	12/1992	Reuter et al.
4,677,780 A	7/1987	Shuman	5,176,435 A	1/1993	Pipkens
4,681,289 A	7/1987	Gronlund et al.	5,183,319 A	2/1993	Pearson et al.
4,688,750 A	8/1987	Teauge et al.	5,209,035 A	5/1993	Hodges et al.
D292,051 S	9/1987	Martin	5,220,871 A	6/1993	Grund et al.
4,694,598 A	9/1987	Eisenloeffel	5,226,705 A	7/1993	Rorke et al.
4,699,067 A	10/1987	Okopny	5,230,492 A	7/1993	Zwart et al.
4,703,598 A	11/1987	Wilson et al.	D339,243 S	9/1993	Durling
4,703,603 A	11/1987	Hills	D339,934 S	10/1993	Reuter
4,704,838 A	11/1987	Wendt	5,249,443 A	10/1993	Anderson
4,709,517 A	12/1987	Mitchell et al.	5,251,467 A	10/1993	Anderson
4,722,285 A	2/1988	Goodman	5,265,358 A	11/1993	Borod
4,726,352 A	2/1988	Radke	5,292,177 A	3/1994	Balderi et al.
4,729,612 A	3/1988	Stone	5,307,575 A	5/1994	Ivansson et al.
4,733,841 A	3/1988	Wilson	5,307,919 A	5/1994	Wente et al.
D295,950 S	5/1988	Johnston	5,322,344 A	6/1994	Hoffman et al.
4,755,010 A	7/1988	Wilson et al.	5,335,962 A	8/1994	Gera
4,774,792 A	10/1988	Ballance	5,335,987 A	8/1994	Hodge et al.
4,776,132 A	10/1988	Gold	5,341,749 A	8/1994	Noakes
D298,784 S	12/1988	Friedman	5,347,778 A	9/1994	Bray
4,799,436 A	1/1989	Goodman	5,348,385 A	9/1994	Berg
4,815,364 A	3/1989	Wagner et al.	5,360,263 A	11/1994	Nakano et al.
4,815,797 A	3/1989	Haab et al.	5,371,985 A	12/1994	Suttles
4,821,375 A	4/1989	Kozon	D354,628 S	1/1995	Lee
4,824,190 A	4/1989	Bartlett et al.	5,383,318 A	1/1995	Kelley et al.
4,826,115 A	5/1989	Novitski	5,384,978 A	1/1995	Peters
4,826,123 A	5/1989	Hannah et al.	D355,981 S	3/1995	Kim
4,828,120 A	5/1989	Beil et al.	5,394,658 A	3/1995	Schreiner et al.
4,834,555 A	5/1989	Grass	5,398,622 A	3/1995	Lubinkas et al.
4,836,478 A	6/1989	Sweere	5,399,010 A	3/1995	McClung et al.
4,841,697 A	6/1989	Hogg et al.	5,409,308 A	4/1995	Reuter et al.
4,844,387 A	7/1989	Sorgi et al.	5,410,899 A	5/1995	McConnell
4,852,212 A	8/1989	Amann	D359,394 S	6/1995	Durling
4,852,500 A	8/1989	Ryburg et al.	5,423,450 A	6/1995	Shillington et al.
4,863,124 A	9/1989	Ball et al.	5,425,577 A	6/1995	Gembler
4,870,793 A	10/1989	Tomlinson	5,435,159 A	7/1995	Ramsauer
4,872,567 A	10/1989	Bustos	5,437,426 A	8/1995	MacDonald
4,873,852 A	10/1989	Neyret	5,448,859 A	9/1995	Walker et al.
4,884,375 A	12/1989	Wendt	5,450,701 A	9/1995	White
4,910,982 A	3/1990	Dana	5,452,936 A	9/1995	Koehring
4,920,717 A	5/1990	Hooper, Jr.	5,454,331 A	10/1995	Green
4,925,258 A	5/1990	Ludwig et al.	5,454,638 A	10/1995	Bird et al.
4,947,601 A	8/1990	McGuire	5,470,128 A	11/1995	Kerkham
4,949,519 A	8/1990	Jeffers	5,470,143 A	11/1995	Gill
4,960,258 A	10/1990	Stocker et al.	D366,770 S	2/1996	Mabon
4,961,295 A	10/1990	Kosch, Sr. et al.	5,494,246 A	2/1996	McCarthy et al.
4,971,281 A	11/1990	Steinbeck	D368,218 S *	3/1996	Klein, III D8/354
D312,734 S	12/1990	Friedman	5,511,349 A	4/1996	Kelley et al.
4,976,502 A	12/1990	Kelley et al.	5,517,731 A	5/1996	Spykerman
5,005,492 A	4/1991	Ogino et al.	5,520,451 A	5/1996	Oshima
5,026,130 A	6/1991	Wright et al.	5,524,979 A	6/1996	Carson et al.
5,035,464 A	7/1991	Spallholtz	5,530,993 A	7/1996	Hayakawa
5,048,698 A	9/1991	Konrad	5,538,213 A	7/1996	Brown
5,050,944 A	9/1991	Fricano	5,566,844 A	10/1996	Bernardin
5,058,297 A	10/1991	McGinnis	D375,726 S	11/1996	Witte
D322,183 S	12/1991	Martin et al.	5,571,276 A	11/1996	Kobos et al.
5,071,281 A	12/1991	Murphy et al.	D376,705 S	12/1996	Stoddard et al.
D323,251 S	1/1992	Zapf	5,606,920 A	3/1997	Meyer et al.

US 8,104,850 B2

Page 4

5,607,070 A	3/1997	Hellyer	6,148,567 A	11/2000	DeRuiter et al.
5,609,317 A	3/1997	Glynn et al.	6,161,347 A	12/2000	Yu et al.
5,626,404 A	5/1997	Kelley et al.	6,167,664 B1	1/2001	Reuter et al.
5,630,566 A	5/1997	Case	6,167,665 B1	1/2001	Dame et al.
5,632,542 A	5/1997	Krivec	6,173,660 B1	1/2001	Emmert
5,645,333 A	7/1997	Sakurai	6,179,263 B1	1/2001	Rosen et al.
5,664,749 A	9/1997	Kump et al.	6,196,648 B1	3/2001	Henriott
5,685,113 A	11/1997	Reuter et al.	6,202,965 B1	3/2001	Chong
D391,243 S	2/1998	Rosen	6,202,966 B1	3/2001	MacDonald et al.
D391,262 S	2/1998	Rosen	6,223,485 B1	5/2001	Beck et al.
D391,946 S	3/1998	Rosen	6,227,635 B1	5/2001	Teppo et al.
5,746,490 A	5/1998	Domenig	6,256,941 B1	7/2001	Yu et al.
5,749,125 A	5/1998	Davis et al.	6,273,534 B1	8/2001	Bueley et al.
5,758,937 A	6/1998	Lammens et al.	6,279,278 B1	8/2001	Morris et al.
D395,874 S	7/1998	Rosen	6,282,854 B1	9/2001	Vos et al.
D395,896 S	7/1998	Rosen	6,296,337 B1	10/2001	Kawanabe
D396,042 S	7/1998	Rosen	D450,937 S	11/2001	Pomeroy et al.
5,775,786 A	7/1998	Lieberts	D451,004 S	11/2001	Lewis
5,784,843 A	7/1998	Greer et al.	6,330,773 B1	12/2001	MacDonald et al.
5,785,401 A	7/1998	Bowyer et al.	6,339,891 B1	1/2002	Cox
5,791,751 A	8/1998	Meyer et al.	6,341,457 B1	1/2002	Aerts et al.
5,791,752 A	8/1998	Hartman	6,349,911 B1	2/2002	Feldpausch et al.
5,799,430 A	9/1998	Fremstad	6,361,132 B2	3/2002	Kawanabe
5,806,942 A	9/1998	Jenkins, Jr. et al.	6,363,663 B1	4/2002	Kane et al.
5,820,208 A	10/1998	Miklinevich	6,367,213 B1	4/2002	Reuter et al.
5,823,120 A	10/1998	Holmquist	6,378,255 B1	4/2002	Eich et al.
5,833,332 A	11/1998	Marshall et al.	6,393,676 B1	5/2002	Dowzall et al.
5,839,240 A	11/1998	Elsholz et al.	6,394,564 B1	5/2002	Mrotz, III et al.
5,842,743 A	12/1998	Wright et al.	6,394,566 B1	5/2002	Slivon et al.
5,845,980 A	12/1998	Fricano et al.	6,397,533 B1	6/2002	Hornsberger et al.
5,852,904 A	12/1998	Yu et al.	6,402,644 B2	6/2002	Stanford et al.
5,870,867 A	2/1999	Mitchell	6,408,579 B1	6/2002	Anderson et al.
5,871,189 A	2/1999	Hoftman	D459,924 S	7/2002	Heidmann et al.
D407,011 S	3/1999	Boije	6,415,567 B1	7/2002	Mead et al.
5,881,518 A	3/1999	Edwards et al.	6,416,145 B1	7/2002	Singh
5,884,424 A	3/1999	Smith	6,418,671 B1	7/2002	DeRuiter et al.
5,890,784 A	4/1999	Domig	6,419,209 B1	7/2002	Shepherd
5,893,616 A	4/1999	MacDonald et al.	6,434,905 B1	8/2002	Sprague
5,897,147 A	4/1999	Alyanakian et al.	6,435,635 B1	8/2002	Lyon
5,899,035 A	5/1999	Waalkes et al.	6,438,884 B1	8/2002	Saarnia et al.
5,904,411 A	5/1999	Hayakawa	6,442,909 B2	9/2002	Waalkes et al.
5,904,412 A	5/1999	Lammens	6,449,909 B1	9/2002	Baloga et al.
5,918,432 A	7/1999	Mahone et al.	6,453,826 B1	9/2002	Fookes et al.
5,934,115 A	8/1999	Bernier et al.	6,464,423 B1	10/2002	Klein
5,941,488 A	8/1999	Rosen	6,471,312 B1	10/2002	Coffey et al.
5,944,398 A	8/1999	Wu	6,484,647 B2	11/2002	Lininger, Jr. et al.
5,946,772 A	9/1999	DeBower	6,487,978 B1	12/2002	Hamberg
5,950,371 A	9/1999	Rives et al.	6,536,858 B1	3/2003	Heidmann et al.
5,953,882 A	9/1999	Vallance et al.	6,536,860 B1	3/2003	Heidmann et al.
5,957,530 A	9/1999	Gutgsell	6,550,875 B1	4/2003	Compton et al.
5,966,893 A	10/1999	Quillin	6,554,354 B1	4/2003	Hoffman et al.
5,971,514 A	10/1999	Hayakawa	6,557,310 B2	5/2003	Marshall et al.
5,975,658 A	11/1999	Verbeek et al.	6,557,958 B1	5/2003	Motta et al.
5,979,118 A	11/1999	Gortsema et al.	6,574,835 B2	6/2003	Mulhuish
5,980,007 A	11/1999	Singh	6,574,928 B2	6/2003	Mueller et al.
5,988,576 A	11/1999	Ehrlich	6,588,866 B2	7/2003	Cheng
5,996,954 A	12/1999	Rosen et al.	6,591,555 B2	7/2003	King et al.
6,007,036 A	12/1999	Rosen	6,592,194 B2	7/2003	Lininger et al.
6,007,171 A	12/1999	Varellas-Olree	6,609,285 B1	8/2003	Kinney
6,009,675 A	1/2000	Waalkes et al.	6,625,935 B1	9/2003	King et al.
6,019,331 A	2/2000	Hoogland et al.	6,626,407 B1	9/2003	Miller et al.
6,047,509 A	4/2000	Savoie	D482,596 S	11/2003	Laabs et al.
6,048,127 A	4/2000	Kern et al.	6,640,387 B2	11/2003	Alonso
6,053,585 A	4/2000	Osen	6,644,748 B2	11/2003	Tholkes et al.
6,058,667 A	5/2000	MacDonald et al.	6,648,047 B2	11/2003	Kimmet
6,073,412 A	6/2000	Verch	6,658,677 B2	12/2003	Paul
6,076,308 A	6/2000	Lyon et al.	6,658,778 B2	12/2003	Roy
6,076,474 A	6/2000	Grabowski et al.	6,658,805 B1	12/2003	Yu et al.
6,097,590 A	8/2000	Genevieve et al.	6,669,315 B2	12/2003	Heidmann et al.
6,098,358 A	8/2000	Waalkes et al.	D484,709 S	1/2004	Cronk et al.
D430,743 S	9/2000	Pomeroy et al.	6,684,929 B2	2/2004	MacDonald et al.
6,115,977 A	9/2000	Hornsberger et al.	6,691,626 B2	2/2004	Warner
6,123,402 A	9/2000	Bowyer et al.	6,695,270 B1	2/2004	Smed
D432,404 S	10/2000	Garfinkle	6,701,758 B2	3/2004	Hoffmann
D432,816 S	10/2000	Hellwig et al.	6,702,372 B2	3/2004	Tholkes et al.
6,131,347 A	10/2000	Hornsberger et al.	6,711,871 B2	3/2004	Beirise et al.
6,138,484 A	10/2000	Sauerland et al.	6,718,709 B2	4/2004	Koutras et al.
6,138,583 A	10/2000	Mahone et al.	6,719,337 B1	4/2004	Ji
6,138,584 A	10/2000	Waite	6,726,035 B2	4/2004	Zadak

US 8,104,850 B2

6,732,988 B2	5/2004	Ihalainen et al.	2002/0112411 A1	8/2002	Gravel et al.
6,736,360 B1	5/2004	Buczek	2002/0113532 A1	8/2002	Hornsberger et al.
6,736,364 B2	5/2004	Oddsens, Jr.	2002/0121755 A1	9/2002	Workman et al.
6,748,710 B2	6/2004	Gresham et al.	2002/0126110 A1	9/2002	Bowron
6,748,778 B1	6/2004	Higdon et al.	2003/0051415 A1	3/2003	Remelts et al.
6,754,998 B2	6/2004	Diffrient et al.	2003/0085328 A1	5/2003	Oddsens, Jr.
6,759,589 B1	7/2004	VandeVelde	2003/0160551 A1*	8/2003	Beyer et al. 312/323
6,761,004 B2	7/2004	Anglin et al.	2003/0173878 A1*	9/2003	Youngs et al. 312/257.1
6,764,148 B2	7/2004	Morris et al.	2003/0196392 A1	10/2003	Edwards
6,779,856 B2	8/2004	Hornberger et al.	2003/0233965 A1	12/2003	Braxier
6,783,105 B2	8/2004	Oddsens, Jr.	2004/0020137 A1	2/2004	Batthey et al.
6,807,776 B2	10/2004	Girdwood et al.	2004/0035082 A1	2/2004	Hudoba et al.
6,817,147 B1	11/2004	MacDonald	2004/0036391 A1	2/2004	Vardon
6,817,149 B2	11/2004	Diffrient et al.	2004/0055713 A1	3/2004	Kimmet
6,827,376 B2	12/2004	Fontaine	2004/0094072 A1	5/2004	Fabian
6,848,741 B2	2/2005	Ford et al.	2004/0163574 A1	8/2004	Schoenbach et al.
6,851,226 B2	2/2005	MacGregor et al.	2004/0178312 A1	9/2004	Parsons
6,854,233 B2	2/2005	Pitsch et al.	2004/0200034 A1	10/2004	Salice
6,863,358 B2	3/2005	Beyer et al.	2004/0217677 A1	11/2004	Durand et al.
6,896,102 B1	5/2005	Nichol	2004/0222725 A1	11/2004	Park et al.
D506,630 S	6/2005	Schweikarth	2004/0239217 A1	12/2004	Patel
6,912,818 B2	7/2005	Sprague	2004/0250480 A1	12/2004	Matthai
6,920,727 B2	7/2005	Yu et al.	2004/0254020 A1	12/2004	Dragusin
6,942,306 B2	9/2005	Youngs et al.	2005/0006997 A1	1/2005	Yoshioka
6,964,138 B2	11/2005	Carroll et al.	2005/0022699 A1	2/2005	Goza
6,964,410 B1	11/2005	Hansen	2005/0045787 A1	3/2005	Magnusson
6,966,206 B2	11/2005	Masseh, Jr. et al.	2005/0045788 A1	3/2005	Mongeau
6,968,661 B2	11/2005	Kopish et al.	2005/0046243 A1	3/2005	Cimino et al.
6,988,780 B2	1/2006	Anderson et al.	2005/0052058 A1	3/2005	Nyo et al.
6,990,909 B2	1/2006	Gosling et al.	2005/0067925 A1	3/2005	Stone, III
6,994,410 B2	2/2006	Hogan	2005/0073224 A1	4/2005	Livingston et al.
D517,345 S	3/2006	Verbeek et al.	2005/0091899 A1	5/2005	Houssian
7,014,155 B1	3/2006	Schnabel et al.	2005/0093409 A1	5/2005	Vardon
7,021,730 B2	4/2006	Remmers	2005/0204646 A1	9/2005	Tupper et al.
7,036,799 B2	5/2006	Shepherd	2005/0264144 A1	12/2005	Verbeek et al.
7,055,287 B2	6/2006	Yu et al.	2005/0280341 A1	12/2005	Vardon
D525,441 S	7/2006	Pomeroy et al.	2005/0284025 A1	12/2005	Balbo De Vinadio
7,117,802 B2	10/2006	Hoke, Jr. et al.	2006/0049327 A1	3/2006	Chen
7,117,927 B2	10/2006	Kent et al.	2006/0050471 A1	3/2006	Chen
7,146,766 B2	12/2006	Finkelstein	2006/0050472 A1	3/2006	Chen
7,146,831 B2	12/2006	Antonucci et al.	2006/0113443 A1	6/2006	Remmers
7,210,270 B1	5/2007	King et al.	2006/0163981 A1	7/2006	Conrad
7,237,845 B2	7/2007	Mulmed	2006/0230705 A1	10/2006	Grandi et al.
2001/0024984 A1	9/2001	Stanford et al.	2006/0267466 A1	11/2006	Marroquin et al.
2002/0043349 A1	4/2002	Rigby et al.	2007/0138843 A1	6/2007	Jonsson et al.
2002/0066843 A1	6/2002	Oddsens, Jr. et al.			
2002/0079789 A1	6/2002	Grubb et al.			
2002/0108330 A1	8/2002	Yu et al.			

* cited by examiner




FIG. 1





FIG. 2














FIG. 4








FIG. 14A









FIG. 14B






FIG. 20




FIG. 21A




FIG. 21B




FIG. 22




FIG. 23




FIG. 25A




FIG. 24







FIG. 25B






FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33A




FIG. 33B




FIG. 34




FIG. 35




FIG. 36A




FIG. 36B




FIG. 37




FIG. 38




FIG. 39




FIG. 40








FIG. 41






FIG. 46




FIG. 47




FIG. 48






FIG. 49








FIG. 58




FIG. 59




FIG. 60




FIG. 61A




FIG. 61B




FIG. 62




FIG. 63




FIG. 64




FIG. 65






FIG. 66






FIG. 70A




FIG. 70B





FIG. 71A






FIG. 72




FIG. 73




FIG. 74A




FIG. 74B




FIG. 75




FIG. 76A




FIG. 76B




FIG. 77




FIG. 78




FIG. 79




FIG. 80




FIG. 81



FIG. 82




FIG. 83





FIG. 84






FIG. 86

FIG. 87

FIG. 89

FIG. 90

FIG. 91




FIG. 88




FIG. 92




FIG. 93




FIG. 94




FIG. 95




FIG. 96




FIG. 97A




FIG. 97B






FIG. 97C






FIG. 105




FIG. 106




FIG. 107A




FIG. 107B




FIG. 107C




FIG. 108




FIG. 109




FIG. 110




FIG. 111




FIG. 112




FIG. 113




FIG. 114




FIG. 116




FIG. 117




FIG. 115




FIG. 118




FIG. 119








FIG. 120

FIG. 120A






FIG. 125




FIG. 126




FIG. 127




FIG. 128




FIG. 129




FIG. 130




FIG. 131






FIG. 132








FIG. 133B






FIG. 137




FIG. 138




FIG. 139




FIG. 140




FIG. 141




FIG. 142




FIG. 143




FIG. 144




FIG. 145




FIG. 146



FIG. 147











FIG. 148








FIG. 156




FIG. 157




FIG. 158




FIG. 160A




FIG. 159

FIG. 160

FIG. 161




FIG. 162




FIG. 164A




FIG. 163

FIG. 164

FIG. 165

FURNITURE STORAGE UNIT**CROSS REFERENCE TO RELATED APPLICATIONS**

The present application claims benefit under 35 U.S. C. §119(e) of provisional application Ser. No. 60/940,913, filed May 30, 2007, entitled FURNITURE STORAGE UNIT AND METHOD; provisional application Ser. No. 60/940,879, entitled STORAGE UNIT ATTACHMENT SYSTEM AND METHODS, filed May 30, 2007; provisional application Ser. No. 60/940,899, entitled STORAGE UNIT DOOR APPARATUS AND METHOD, filed May 30, 2007; and provisional application Ser. No. 60/940,891 filed May 30, 2007, entitled STORAGE UNIT BACK STOP AND METHOD, and is related to co-pending application entitled STORAGE UNIT BACK STOP AND METHOD, filed on even date herewith. The entire contents of each of the aforementioned applications are incorporated herein by reference.

BACKGROUND OF THE INVENTION

The present invention relates to storage units for office furniture and the like, and in particular to an adaptable modular construction therefor.

Modular office systems are oftentimes used to convert large open floor spaces in buildings into individual workstations and other useable office settings. Due to constantly changing work environments, office systems that are versatile and allow for easy and convenient rearrangement are quite beneficial. Some panel systems require specifically configured storage components and case assemblies, and therefore lack the ability to interface with other types of furniture systems.

In an effort to increase the versatility of storage units, components that may be used across a wide variety of furniture systems and in multiple storage unit assemblies would be useful. In the past, such arrangements have proven difficult to design and costly to produce. Accordingly, a storage unit construction and associated components that can be used in multiple office environments with fewer parts and provide easy installation is desired and would be considered advantageous.

SUMMARY OF THE INVENTION

One aspect of the present invention is a storage unit assembly for office furniture units of the type having an outer face with slotted hangers extending therealong, and includes a bottom panel operably positioned in a generally horizontal orientation, and shaped to abuttingly support objects thereon. A top panel is disposed above and generally parallel with the bottom panel, and is shaped to cover at least a portion of the bottom panel. First and second end panels are disposed at opposite ends of the top and bottom panels and are connected therewith to define a rigid, box-shaped case having a generally rigid bottom portion and a generally open back portion. First and second end panels have rear portions with a plurality of vertically spaced apart slots disposed therein. First and second hanger brackets each have a rear portion with first hooks shaped for reception in the slotted hangers of an associated one of the office furniture units, and a forward portion with second hooks selectively received in the slots in the rear portions of the first and second end panels to detachably support the case in a panel-hung condition against the outer face of the associated one of the office furniture units. An up-mount bracket has a lower portion shaped for connection

with an associated one of the office furniture units, and an upper portion connected with and supporting the bottom portion of the case to detachably mount the case in an up-mounted condition above a top portion of the associated one of the furniture units. A removable back panel is shaped to enclose at least a portion of the open back portion of the case, and has side portions with outwardly protruding hooks selectively received in the slots in the rear portions of the first and second end panels to detachably connect the back panel with the case and enclose at least that portion of the open back portion of the case disposed above the top portion of the associated one of the office furniture units when the case is in the up-mounted condition.

Another aspect of the present invention is an office furniture unit having an outer face with slotted hangers extending therealong, and a removable storage unit assembly including a bottom panel operably positioned in a generally horizontal orientation along the office furniture unit, and a top panel disposed above and generally parallel with the bottom panel. First and second panels are disposed at opposite ends of the top and bottom panels and are connected therewith to define a rigid, box-shaped case having a generally open back portion. The first and second end panels have rear portions with a plurality of vertically spaced apart slots disposed therein. First and second hanger brackets each have a rear portion with first hooks selectively received in the slotted hangers of the office furniture units, and a forward portion with second hooks selectively received in the slots in the rear portions of the first and second end panels to detachably support the case in a panel-hung condition against the outer face of the office furniture unit.

Yet another aspect of the present invention is an office furniture unit, and a storage unit assembly including a bottom panel operably positioned in a generally horizontal orientation along the office furniture unit. A top panel is disposed above and generally parallel with the bottom panel. First and second end panels are disposed at opposite ends of the top and bottom panels and are connected therewith to define a rigid, box-shaped case having a generally rigid bottom portion and a generally open back portion. The first and second end panels have rear portions with a plurality of vertically spaced apart slots disposed therein. An up-mount bracket has a lower portion connected with the office furniture unit, and an upper portion connected with and supporting the bottom portion of the case to detachably mount the case in an up-mounted condition above a top portion of the furniture unit. A removable back panel encloses at least a portion of the open back portion of the case, and has side portions with outwardly protruding hooks received in the slots in the rear portions of the first and second end panels to detachably connect the back panel with the case and encloses at least that portion of the open back portion of the case disposed above the top portion of the office furniture unit.

Yet another aspect of the present invention is a method for making a storage unit assembly for office furniture units of the type having a like construction with slotted hangers extending along outer faces thereof including forming a bottom panel shaped to abuttingly support objects thereon. A top panel is formed in a shape to cover at least a portion of the bottom panel. The top panel is positioned in a generally parallel, spaced apart relationship with the bottom panel. First and second end panels are formed with rear portions having a plurality of vertically spaced apertures therein. The first and second end panels are positioned at opposite ends of the top and bottom panels and interconnected with the same to define a rigid, box-shaped case having a generally rigid bottom portion and a generally open back portion. First and second

hanger brackets are formed, each having a rear portion with first hooks shaped for reception in the slotted hangers of a first selected one of the office furniture units, and a forward portion with second hooks shaped for reception in the slots in the rear portions of the first and second end panels. The first hooks on the first and second hanger brackets are inserted into the slotted hangers on the first selected furniture unit. The second hooks on the first and second hanger brackets are inserted into the slots in the rear portions of the first and second end panels to detachably support the case in a panel-hung condition against the outer face of the first selected office furniture unit. An up-mount bracket is formed with a lower portion shaped for connection with a second selected one of the office furniture units, and an upper portion shaped for connection with the bottom portion of said case. The lower portion of the up-mount bracket is mounted with the second selected furniture unit. The upper portion of the up-mount bracket is connected with the bottom portion of the case to detachably mount the case in an up-mounted condition above a top portion of the second selected furniture unit. A removable back panel is formed in a shape to enclose at least a portion of the open back portion of the case, and has side portions with outwardly protruding hooks shaped for reception in the slots in the rear portions of the first and second end panels. The hooks on the back panel are inserted into the slots in the rear portions of the first and second end panels to detachably connect the back panel with the case and enclose at least that portion of the open back portion of the case disposed above the top portion of the second selected office furniture unit when the case is in the up-mounted condition.

Yet another aspect of the present invention is to provide a storage unit assembly adapted to be secured to a variety of different types of furniture systems and which includes components that can be used in a wide variety of storage unit assemblies. The kit of parts associated with these storage unit assemblies is efficient in use, economical to manufacture, capable of a long operating life, and particularly adapted for its proposed use.

These and other features, advantages and objects of the present invention will be further understood and appreciated by those skilled in the art by reference to the following written specification, claims and appended drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a top perspective view of one embodiment of a storage unit assembly of the present invention in a panel-hung condition;

FIG. 2 is an exploded perspective view of the storage unit assembly of FIG. 1;

FIG. 3 is a top perspective view of a storage unit assembly in an up-mounted condition;

FIG. 4 is an exploded perspective view of the storage unit assembly of FIG. 3;

FIG. 5 is a top perspective view of a bottom panel of the instant invention;

FIG. 6 is a top elevational view of the bottom panel of FIG. 5;

FIG. 7 is a rear elevational view of the bottom panel of FIG. 5;

FIG. 8 is a side elevational view of the bottom panel of FIG. 5;

FIG. 9 is a front elevational view of the bottom panel of FIG. 5;

FIG. 10 is a top perspective view of a back stop rail of the instant invention;

FIG. 11 is a side elevational view of the back stop rail of FIG. 10;

FIG. 12 is a front elevational view of the back stop rail of FIG. 10;

FIG. 13 is a back elevational view of the back stop rail of FIG. 10;

FIG. 14A is a front perspective view of the bottom panel connected with a back stop rail;

FIG. 14B is a bottom panel attached to the back stop rail and an accessory mounted thereto;

FIG. 15 is a top perspective view of a connector bracket of the instant invention;

FIG. 16 is a first side elevational view of the connector bracket of FIG. 15;

FIG. 17 is a second side elevational view of the connector bracket of FIG. 15;

FIG. 18 is a top elevational view of the connector bracket of FIG. 15;

FIG. 19 is a front elevational view of the connector bracket of FIG. 15;

FIG. 20 is a top perspective view of an end panel of the instant invention;

FIG. 21A is a first side elevational view of the end panel of FIG. 20;

FIG. 21B is a second side elevational view of the end panel of FIG. 20;

FIG. 22 is a top elevational view of the end panel of FIG. 20;

FIG. 23 is a bottom elevational view of the end panel of FIG. 20;

FIG. 24 is a rear elevational view of the end panel of FIG. 20;

FIG. 25A is a top perspective view of an end panel attached to a connector bracket;

FIG. 25B is a first side elevational view of the end panel and connector bracket of FIG. 25A;

FIG. 26 is a side elevational view of the bottom panel during connection with an end panel;

FIG. 27 is a side elevational view of the bottom panel connected with an end panel;

FIG. 28 is an enlarged elevational view of a portion of the connector bracket connected to the bottom panel;

FIG. 29 is a top perspective view of a top panel of the present invention;

FIG. 30 is a side elevational view of the top panel of FIG. 29;

FIG. 31 is a top elevational view of the top panel of FIG. 29;

FIG. 32 is a bottom elevational view of the top panel of FIG. 29;

FIG. 33A is a top perspective view of the bottom panel, end panels and top panel assembled;

FIG. 33B is a front elevational view of the bottom panel, end panels and top panel assembled;

FIG. 34 is a top perspective view of a removable back of the instant invention;

FIG. 35 is a side elevational view of the removable back of FIG. 34;

FIG. 36A is a top elevational view of the removable back of FIG. 34;

FIG. 36B is a bottom elevational view of the removable back of FIG. 34;

FIG. 37 is a front elevational view of removable back of FIG. 34;

FIG. 38 is a top perspective view of a metal door of the instant invention;

FIG. 39 is a side elevational view of the metal door of FIG. 38;

5

FIG. 40 is a front elevational view of the metal door of FIG. 38;

FIG. 41 is a rear elevational view of the metal door of FIG. 38;

FIG. 42 is a top perspective view of a wood door of the instant invention;

FIG. 43 is a side elevational view of the wood door of FIG. 42;

FIG. 44 is a front elevational view of the wood door of FIG. 42;

FIG. 45 is a rear elevational view of the wood door of FIG. 42;

FIG. 46 is a top perspective view of a curved front door of the instant invention;

FIG. 47 is a side elevational view of the curved front door of FIG. 46;

FIG. 48 is a front elevational view of the curved front door of FIG. 46;

FIG. 49 is a rear elevational view of the curved front door of FIG. 46;

FIG. 50 is a top perspective view of a picture frame door of the instant invention;

FIG. 51 is a side elevational view of the picture frame door of FIG. 50;

FIG. 52 is a front elevational view of the picture frame door of FIG. 50;

FIG. 53 is a rear elevational view of the picture frame door of FIG. 50;

FIG. 54 is a top perspective view of an over-the-case storage unit assembly of the instant invention in a closed position;

FIG. 55 is an enlarged view of section LV of the over-the-case storage unit assembly of FIG. 54;

FIG. 56 is a top perspective view of an over-the-case storage unit assembly of the instant invention in an open position;

FIG. 57 is an enlarged view of section LVII of the over-the-case storage unit assembly of FIG. 56;

FIG. 58 is rear elevational view of an over-the-case door;

FIG. 59 is a partial rear elevational view of an over-the-case door;

FIG. 60 is a side elevational view of an over-the-case door;

FIG. 61 is a bottom perspective view of a door slide with quick attach clip for the over-the-case door;

FIG. 62 is a bottom perspective view of a door slide in a nearly fully open position;

FIG. 63 is a bottom elevational view of the door slide of FIG. 62;

FIG. 64 is a bottom perspective view of a door slide for the over-the-case application in an nearly fully closed position;

FIG. 65 is a top perspective view of an in-the-case storage unit assembly of the instant invention in a closed position;

FIG. 66 is a top perspective view of an in-the-case storage unit assembly with the door in an open position;

FIG. 67 is side elevational view of an in-the-case guide rail of the instant invention;

FIG. 68 is a top perspective view of the in-the-case guide rail of FIG. 67;

FIG. 69 is a top perspective view of the in-the-case guide rail of FIG. 67 mounted in an end panel;

FIG. 70A is a rear elevational view of an in-the-case door of the instant invention;

FIG. 70B is a partial bottom perspective view of the in-the-case door of FIG. 70 between open and closed positions;

FIG. 71A is an enlarged perspective view of a dampener assembly;

FIG. 71B is a partial side elevational view of the in-the-case door dampener with the door closed;

6

FIG. 71C is a partial side elevational view of the in-the-case door dampener with the door partially opened;

FIG. 71D is a partial side elevational view of the in-the-case door dampener with the door open;

FIG. 72 is a bottom elevational view of an anti-racking mechanism attached to a metal door;

FIG. 73 is a bottom elevational view of the anti-racking mechanism of FIG. 72 in a partially extended position;

FIG. 74A is a top perspective view of an anti-racking mechanism prior to installation;

FIG. 74B is a top perspective view of the anti-racking mechanism of 74A after installation;

FIG. 75 is a bottom perspective view of the anti-racking mechanism of FIG. 74A after installation;

FIG. 76A is a side elevational view of the anti-racking mechanism attached;

FIG. 76B is an enlarged view of section LXXVIB of FIG. 76A;

FIG. 77 is a top perspective view of the anti-racking mechanism between fully open and fully closed positions;

FIG. 78 is a top perspective view of the anti-racking mechanism in the fully closed position;

FIG. 79 is a top perspective view of an integral end panel of the instant invention;

FIG. 80 is a top elevational view of the integral end panel of FIG. 79;

FIG. 81 is a first side elevational view of the integral end panel of FIG. 79;

FIG. 82 is a bottom elevational view of the integral end panel of FIG. 79;

FIG. 83 is a second side elevational view of the integral end panel of FIG. 79;

FIG. 84 is a top perspective view of a storage unit assembly with integral end panels prior to installation;

FIG. 85 is a side elevational view of a storage unit assembly with integral end panels after installation;

FIG. 86 is a top perspective view of an on-module hanger bracket of the instant invention;

FIG. 87 is a first side elevational view of the on-module hanger bracket of FIG. 86;

FIG. 88 is a top elevational view of the on-module hanger bracket of FIG. 86;

FIG. 89 is a rear elevational view of the on-module hanger bracket of FIG. 86;

FIG. 90 is a second side elevational view of the on-module hanger bracket of FIG. 86;

FIG. 91 is a front elevational view of the on-module hanger bracket of FIG. 86;

FIG. 92 is a top perspective view of a storage unit assembly of the instant invention prior to being installed in a panel-hung condition with hanger brackets;

FIG. 93 is a top perspective view of a storage unit assembly of the instant invention prior to being installed in a panel-hung condition with hanger brackets installed;

FIG. 94 is a side elevational view of a storage unit assembly of the instant invention prior to being installed in a panel-hung condition with hanger brackets installed;

FIG. 95 is a partial rear perspective view of a storage unit assembly of the instant invention prior to being panel-hung with hanger brackets;

FIG. 96 is a top perspective view of a storage unit assembly in an on-module panel-hung condition;

FIG. 97A is a side elevational view of the storage unit assembly in an on-module panel-hung condition;

FIG. 97B is a rear exploded perspective view of an end panel; hanger bracket; and anti-dislodgement clip;

FIG. 97C is a rear perspective view of an end panel engaged with a hanger bracket and anti-dislodgement clip;

FIG. 98 is a top perspective view of an off-module support bracket of the present invention;

FIG. 99 is an enlarged partial perspective view of a top portion of the off-module support bracket of FIG. 98;

FIG. 100 is a front elevational view of the off-module support bracket of FIG. 98;

FIG. 101 is a rear elevational view of the off-module support bracket of FIG. 98;

FIG. 102 is a bottom elevational view of the off-module support bracket of FIG. 98;

FIG. 103 is a side elevational view of the off-module support bracket of FIG. 98;

FIG. 104 is an enlarged partial side elevational view of the bottom portion of the off-module support bracket of FIG. 98;

FIG. 105 is a top perspective view of a storage unit assembly of the instant invention prior to being panel hung in a vertical off-module condition;

FIG. 106 is a side elevational view of a storage unit assembly prior to being panel hung in a vertical off-module condition;

FIG. 107A is a side elevational view of a storage unit assembly of the instant invention in a panel hung off-module condition;

FIG. 107B is an enlarged side elevational view of a storage unit assembly of the instant invention in a panel hung off-module condition;

FIG. 107C side elevational view of a storage unit assembly of the instant invention in a panel hung off-module condition;

FIG. 108 is a top perspective view of a top bracket of a horizontal off-module support bracket of the instant invention;

FIG. 109 is a front elevational view of the top bracket of FIG. 108;

FIG. 110 is a rear elevational view of the top bracket of FIG. 108;

FIG. 111 is a side elevational view of the top bracket of FIG. 108;

FIG. 112 is a bottom elevational view of the top bracket of FIG. 108;

FIG. 113 is a top perspective view of a bottom bracket of a horizontal off-module support bracket of the instant invention;

FIG. 114 is a front elevational view of the bottom bracket of FIG. 113;

FIG. 115 is a bottom elevational view of the bottom bracket of FIG. 113;

FIG. 116 is a side elevational view of the bottom bracket of FIG. 113;

FIG. 117 is a back elevational view of the bottom bracket of FIG. 113;

FIG. 118 is a top elevational view of the bottom bracket of FIG. 113;

FIG. 119 is a top perspective view of a storage unit assembly of the instant invention prior to being panel hung in a horizontal off-module condition;

FIG. 120 is a side elevational view of a storage unit assembly of the instant invention prior to being panel hung in a horizontal off-module condition;

FIG. 120A is a bottom elevational view of a bottom bracket during installation;

FIG. 121 is a front perspective view of horizontal off-module support brackets engaged with slotted hangers of office furniture unit prior to connection with vertical off-module support bracket;

FIG. 122 is a rear perspective view of horizontal off-module support brackets engaged with slotted hangers of office furniture unit prior to connection with vertical off-module support bracket;

FIG. 123 is a side elevational view of a vertical off-module bracket engaging a horizontal off-module bracket;

FIG. 124 is a side elevational view of a vertical off-module bracket engaged with a horizontal off-module bracket;

FIG. 125 is a side elevational view of a storage unit assembly of the instant invention before installation in a panel hung horizontal off-module condition;

FIG. 126 is a top perspective view of a storage unit assembly of the instant invention in a panel hung horizontal off-module condition;

FIG. 127 is a top perspective view of an up-mount bracket of the instant invention;

FIG. 128 is a top elevational view of the up-mount bracket of FIG. 127;

FIG. 129 is a side elevational view of the up-mount bracket of FIG. 127;

FIG. 130 is a rear elevational view of the up-mount bracket of FIG. 127;

FIG. 131 is a top perspective view of a storage unit assembly of the instant invention prior to installation in an up-mounted condition;

FIG. 132 is a side elevational view of a storage unit assembly of the instant invention prior to installation in an up-mounted condition;

FIG. 133A is a side elevational view of a storage unit assembly of the instant invention in an up-mounted condition;

FIG. 133B is a front elevational view of a storage unit assembly in a desk/service module arrangement;

FIG. 134 is a top perspective view of a storage unit assembly of the instant invention in an up-mounted condition;

FIG. 135 is a top perspective view of a lock assembly of the instant invention;

FIG. 136 is a top elevational view of the lock assembly of FIG. 135;

FIG. 137 is a front elevational view of the lock assembly of FIG. 135;

FIG. 138 is a side elevational view of the lock assembly of FIG. 135;

FIG. 139 is a top elevational view of the lock assembly installed in a bottom panel;

FIG. 140 is a top perspective view of a dual door top panel of the present invention;

FIG. 141 is a bottom elevational view of the dual door top panel of FIG. 140;

FIG. 142 is a front elevational view of a dual door support of the present invention;

FIG. 143 is an exploded top perspective view a dual door storage unit of the present invention;

FIG. 144 is a top perspective view of a shelf bracket of the instant invention;

FIG. 145 is a front elevational view of the shelf bracket of FIG. 144;

FIG. 146 is a first side elevational view of the shelf bracket of FIG. 144;

FIG. 147 is a top elevational view of the shelf bracket of FIG. 144;

FIG. 148 is a second side elevational view of the shelf bracket of FIG. 144;

FIG. 149 is an exploded top perspective view of the shelf prior to installation;

FIG. 150 is a top perspective view of the shelf of FIG. 149 installed;

FIG. 151 is a top perspective view of a shelf with end walls of the instant invention;

FIG. 152 is a front elevational view of the shelf of FIG. 151;

FIG. 153 is a first side elevational view of the shelf of FIG. 151;

FIG. 154 is a top elevational view of the shelf of FIG. 151;

FIG. 155 is a second side elevational view of the shelf of FIG. 151;

FIG. 156 is an exploded top perspective view of the shelf with end walls of the instant invention;

FIG. 157 is a top perspective view of the shelf with end walls installed;

FIG. 158 is a top perspective view of a binder bin with a support vertical strut installed;

FIG. 159 is a top perspective view of a support strut;

FIG. 160 is a side elevational view of the support strut of FIG. 159;

FIG. 160A is an enlarged side elevational view of section CLXA of FIG. 160;

FIG. 161 is a rear elevational view of the support strut FIG. 159;

FIG. 162 is a top perspective view of a binder bin with a temporary strut installed;

FIG. 163 is a top perspective view of a temporary strut;

FIG. 164 is a side elevational view of the temporary strut of FIG. 163;

FIG. 164A is an enlarged side elevational view of section CLXIVA of FIG. 164; and

FIG. 165 is a rear elevational view of the temporary vertical strut FIG. 163.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

For purposes of description herein the terms “upper”, “lower”, “right”, “left”, “rear”, “front”, “vertical”, “horizontal” and derivatives thereof shall relate to the invention as oriented in FIGS. 1-4. However, it is to be understood that the invention may assume various alternative orientations and step sequences, except where expressly specified to the contrary. It is also to be understood that the specific devices and processes illustrated in the attached drawings, and described in the following specification are simply exemplary embodiments of the inventive concepts defined in the appended claims. Hence, specific dimensions and other physical characteristics relating to the embodiments disclosed herein are not to be considered as limiting, unless the claims expressly state otherwise.

The reference numeral 10 (FIG. 1) generally designates a storage unit assembly for office furniture units 12 of the type having an outer face 14 with slotted hangers 16 extending therealong. The storage unit 10 includes a bottom panel 20 operably positioned in a generally horizontal orientation, and shaped to abuttingly support objects thereon, and a top panel 18 disposed above and generally parallel with the bottom panel 20, and shaped to cover at least a portion of the bottom panel 20. First and second end panels 22, 24 are disposed at opposite ends of the top and bottom panels 18, 20 and connected with the top and bottom panels 18, 20 to define a rigid, box-shaped case 26 having a generally rigid bottom portion 28 and a generally open back portion 30. The first and second end panels 22, 24 have rear portions 32 with a plurality of vertically spaced apart slots 34 disposed therein. First and second hanger brackets 35, 36 each have a rear portion 38 with first hooks 40 shaped for reception in the slotted hangers 16 of an associated one of the office furniture units 12 and a forward portion 42 with second hooks 44 selectively received

in the slots 34 in the rear portions 32 of the first and second end panels 22, 24 to detachably support the case 26 in a panel-hung condition against the outer face 14 of the associated one of the office furniture units 12, as shown in FIGS. 133 and 134. An up-mount bracket 48 has a lower portion 50 shaped for connection with an associated one of the office furniture units 12, and an upper portion 52 connected with and supporting the bottom portion of the case 26 to detachably mount the case 26 in an up-mounted condition above a top portion 54 of the associated one of the furniture units 12. A removable back panel 56 is shaped to enclose at least a portion of the open back portion 30 of the case 26 and has side portions 58 with outwardly protruding hooks 60 selectively received in the slots 34 in the rear portions 32 of the first and second end panels 22, 24 to detachably connect the back panel 56 with the case 26 and enclose at least that portion of the open back portion 30 of the case 26 disposed above the top portion 54 of the associated one of the office furniture units 12 when the case 26 is in the up-mounted condition (FIGS. 133 and 134).

In the example shown in FIGS. 5-9, bottom panel 20 includes a substantially planar top surface 70 adapted to support objects thereon and a bottom surface 72 including a socket 74 adapted to engage and secure a lock housing 76 therein, as will be described later in FIGS. 135-139. Bottom panel 20 further includes side walls 78, as well as a front portion 80 and back portion 82. Socket 74 is defined by the bottom surface 72, front portion 80 and a socket flange 84. Back portion 82 of bottom panel 20 includes a downwardly extending flange 86 shaped to abut and connect with back stop rail 62. Fastener apertures 88 in the back portion 82 of bottom panel 20 as well as in back stop rail 62 allow back stop rail 62 to be fastened to the back portion 82 of bottom panel 20 by mechanical fasteners. The front portion 80 of bottom panel 20 includes a lock aperture 90 that allows a lock arm 92 to protrude from and be received in bottom panel 20. The side walls 78 of bottom panel 20 include a key hole slot 94 adapted for engagement with a tab 96 on a connector bracket 98 that secures the first and second end panels 22, 24 to bottom panel 20.

Referring to FIGS. 10-13, 14A and 14B, the illustrated case 26 includes an elongate, rigid, channel-shaped back stop rail 62 that connects with rail brackets 100 (FIGS. 25A and 25B) attached to the first and second end panels 22, 24, as disclosed in greater detail in related application Ser. No. 12/128,920, filed May 29, 2008, entitled STORAGE UNIT BACK STOP AND METHOD. The back stop rail 62 provides rigidity to the case and is designed to support accessories that can be hung therefrom including dividers, small shelves, communication/electrical line manager, etc. The back stop rail 62 extends between the first and second end panels 22, 24 in the interior of the case 26. The back stop rail 62 has a rearwardly opening, generally U-shaped upper portion 102 defined by a generally flat upper vertical web 104 with upper and lower horizontal flanges 106, 108 projecting rearwardly from the top and bottom of the vertical web 104. Back stop rail 62 also includes a lower portion 110 that extends below bottom panel 20 and terminates at an inwardly extending base flange 112. Back stop rail 62 is supported along the back portion 82 of bottom panel 20 by fasteners and the vertical web 104 projects inwardly into the interior of the case 26 to retain objects on bottom panel 20.

As shown in FIG. 14A, an accessory 120 may be provided having a first portion 122 configured to equip the interior of the case 26 and a second portion 124 detachably engaged with the upper horizontal flange 106 on the back stop rail 62. The accessory 120 hangs from and is supported by and abuts

11

against vertical web 104 of said back stop rail 62 at a selected one of a wide variety of positions along back stop rail 62. The accessory 120 functions as an interior divider inside the bin and also functions as a wire manager through which communication/electrical lines can be routed.

As shown in FIGS. 15-19, the illustrated connector bracket 98 includes a top support flange 132, a side engagement wall 134 having engagement tabs 96, a bottom support flange 138, and an upwardly extending flange 140. Side engagement wall 134 includes an upper portion 142 offset from a lower portion 144. This construction of connector bracket 98 provides a small gap 146 between upper portion 142 of side engagement wall 134 and end panel 22 or 24 to which connector bracket 98 is attached. This small gap 146 allows side wall 78 of bottom panel 20 to be frictionally forced into gap 146. Top support flange 132 is of adequate length to support the underside of bottom panel 20. Bottom support flange 138 of connector bracket 98 includes apertures 148 adapted for reception of fasteners when storage unit assembly 10 has been secured in an up-mounted condition.

Referring now to FIGS. 20-24, first end panel 22 includes a substantially planar exterior wall 160 with a top flange 162 extending orthogonally inward toward the interior of storage unit assembly 10 after construction. The second end panel 24 will have identical features only oriented in a mirror-like fashion. Accordingly, all features described with respect to the first end panel 22 will be mirror images to that of the second end panel 24. Top flange 162 includes first and second clips 164, 166 adapted to receive a portion of top panel 18 as will be disclosed in further detail below. A detent stop 168 is located between first and second clips 164, 166 and helps secure top panel 18 in position when installed. A front flange 167 on the end panel includes a bottom end 169 adapted to abut and secure the top surface of bottom panel 20 after assembly. Rear portion 32 of first end panel 22 includes multiple slots 34, adapted to engage either the removable back 56 in an up-mounted condition or a hanger bracket 35, 36 when the storage unit assembly 10 is installed in a panel hung condition as discussed in further detail below.

FIGS. 25A and 25B illustrate connector bracket 98 attached with first end panel 22. Connector bracket 98 may be attached to the inside of first end panel 22 by fasteners, welding etc. The attachment of connector bracket 98 is such that gap 146 is created between upper portion 142 of side engagement wall 134 and the inside of first end panel 22.

Referring now to FIGS. 26-28, each end panel 22, 24 is connected to bottom panel 20 by connector brackets 98. During assembly, front portion 80 of bottom panel 20 is slid forward at an angle so that front portion 80 of bottom panel 20 is below bottom end 169 of front flange 167 of first end panel 22, as shown in FIG. 26. Back portion 82 of bottom panel 20 is then rotated downwardly so that key hole slot 94, located on both side portions of bottom panel 20, engages the rearmost engagement tab 96 on connector brackets 98 located on either side of bottom panel 20, as shown in FIG. 27. When the rearmost engagement tab 96 reaches key hole slot 94, it springs outwardly into interference with a bottom edge 180 of key hole slot 94, as shown in FIGS. 27 and 28, preventing bottom panel 20 from being accidentally lifted or removed. During disassembly, to remove bottom panel 20, a user would utilize a prying device, such as a screwdriver, and push the rearmost engagement tab 96 in a direction toward the first end panel 22 thereby preventing interference with bottom edge 180 of key hole slot 94 so that back portion 82 of bottom panel 20 can be rotated upwardly and bottom panel 20 can be slid out from between the first and second end panels 22, 24. There are three slots 34 (FIG. 24) each of which has a shaped

12

adapted receive the hooks 44 of hanger brackets 35, 36. The slots 34 include a wide base 181 that narrows to an acute top portion 182 and are aligned vertically with one another.

In the example shown in FIGS. 29-32, top panel 18 includes cutouts 190 adapted to receive a portion of a hinge for an over-the-case configuration. For an in-the-case configuration (FIGS. 65 and 66), the cutouts 190 would likely not be present. Top panel 18 is substantially planar and includes an underside with first and second inwardly extending side flanges 192, 194 having clip apertures 196 disposed therein, as well as an inwardly extending rear flange 198. The clip apertures 196 are adapted to engage first and second clips 164, 166 on end panels 22, 24. A central aperture 200 is adapted to engage detent stop 168 that exists between first and second clips 164, 166 on end panels 22, 24. Top panel 18 is slid onto the clips 164, 166 until detent stop 168 engages central aperture 200, at which point top panel 18 is held in position and cannot be removed. A prying tool, such as a screwdriver, can be used to separate inwardly extending side flanges 192, 194 of top panel 18 from end panels 22, 24 so that top panel 18 can be withdrawn from connection with end panels 22, 24.

Referring to FIGS. 33A and 33B, the assembly of first and second end panels 22, 24 with top and bottom panels 18, 20 defines the rigid box-shaped case 26 with a generally rigid bottom portion 28 and a generally open back portion 30.

As shown in FIGS. 34-37, the illustrated removable back panel 56 includes a top engagement flange 210, a bottom engagement flange 212, and top hooks 60A, middle hooks 60B and bottom hooks 60C (collectively referred to as hooks 60) that protrude outwardly from side portions 58 in a direction generally orthogonal to the planar extent of the removable back panel 56. Hooks 60 of removable back panel 56 are designed for engagement with slots 34 in the rear portion 32 of each of the first and second end panels 22, 24. The bottom hook 60C on each side of back panel 56 includes an anti-dislodgment aperture 218 designed for engagement with an anti-dislodgment clip located on each of the first and second end panels 22, 24 (shown in FIGS. 97B and 97C) in a similar fashion to that described below with respect to hook 44C of connector brackets 35, 36. In addition the middle hook 60B on each side of back panel 56 includes an anti-dislodgment aperture 220 for receiving an optional anti-dislodgment pin. The hooks 60 have a shape and size very similar to the shape and size of hooks 44 on hanger brackets 35, 36. The three hooks 60A, 60B and 60C are aligned vertically on both side portions 58 of the removable back 56 and are adapted to engage the three vertical slots 34. The back panel 56 is typically installed onto case 26 when the case is to be secured in an up-mounted condition.

Referring now to FIGS. 38-53, the storage unit assemblies are adapted for use with metal doors 64A, wood doors 64B, curved front doors 64C and picture frame doors 64D. The metal doors 64A shown in FIGS. 38-41 are substantially planar and include slide cutouts 230 adapted to receive quick attach clips 232, as shown in FIG. 61, that hold slide assemblies in place in an over-the-case application. A back side 234 of the metal door 64A also includes two sets of lock apertures 236, 238 adapted to receive and retain locking arm 92 in a locking housing 76. The top set of apertures 236 is used for a short case construction and the bottom set of apertures 238 is used for a tall case construction. Doors may be installed on the storage unit assembly in a variety of ways, including those disclosed in U.S. Provisional Application Ser. No. 60/940, 899, filed May 30, 2007, entitled STORAGE UNIT DOOR APPARATUS AND METHOD, which is hereby incorporated by reference.

FIGS. 42-45 illustrate wood door 64B, which is similar in construction to the metal door 64A described above, but is solid wood, and includes metal side reinforcements 250. Wood door 64B is adapted for use in an in-the-case application, although it is contemplated that wood door 64B could be used in an over-the-case application as well.

FIGS. 46-49 illustrate curved front door 64C having side walls 260 and a curved front side 262. A back side 264 of the curved front door 64C includes three bracket assemblies 266, 268, 270. The central bracket assembly 268 provides structural support while the side brackets 266 and 270 are adapted to connect with slide assemblies in an over-the-case application.

Referring now to FIGS. 50-52, 53A and 53B, picture frame door 64D includes a frame construction 280 having a top member 282, bottom member 284, and side members 286, 288 configured to frame a planar sheet 290. The planar sheet 290 may be a marker board, translucent or opaque material, or a solid material, for example. Picture frame door 34D also includes a set of lock apertures 292 for installation on storage unit assemblies in either an over-the-case (FIG. 53B) or in-the-case application (FIG. 53A). The over-the-case picture frame door 64D also includes slide cutouts for receiving a slide mechanism.

Referring now to FIGS. 54-57, the metal door 64A, wood door 64B, curved front door 64C or picture frame door 64D may be used as an over-the-case door 64' for an over-the-case configuration or application. The door 64' is connected to a planar attachment bracket 300 in the cutouts 190 in the top panel 18 and not directly to the front portion of the top panel 18. As a result, a reduced gap 302 is created. In the over-the-case construction, the door 64' can be moved from a vertical closed position to a horizontal open position where the door 64' rests on the top panel 18.

In the example shown in FIGS. 58-60, a rear side portion 310 of the over-the-case door 64' includes an over-the-case door support mechanism 312 having optional dampener assemblies 314 and optional spring assists 315 connected with first and second door slides 316, 318. Door slides 316, 318 are attached rear side 310 of door 64' and to hinges 320 located at the inside top of door 64' and each door slide 316, 318 includes a carriage 319. The hinges 320 allow door 64' to move between open and closed positions. The slides 316, 318 allow relative movement of door 64' to an open position above storage unit assembly 10 and to a closed vertical position in front of storage unit assembly 10. As shown in FIG. 59, the dampener assembly 314 has a piston 324 and a spring cylinder 326. Piston 324 is biased outward from the spring cylinder 326, and acts to slow movement of the over-the-case door 64' during closure. Piston 324 is attached to a pivot pin 328 disposed below and further inside the case 26 than hinges 320. Spring assists 315 secured on either side of the dampener assembly 314 act to assist the user during opening of the over-the-case door 64'.

FIGS. 61A and 61B illustrate the quick attach clip 232 that may be used to secure door slides 316, 318 to door 64'. The quick attach clip 232 includes first and second wings 342, 344 with first and second tabs 346, 348, respectively, designed to provide an interference fit with slide cutouts 230 in the over-the-case door 64'. Legs 350 extend into the slides 316, 318 and hold the slide in position. A center tab 352 extends and locks into a loop 354 on slide 316 keeping slide 316 from slipping out of quick attach clip 232. Both slides 316 and 318 may be attached in the manner described above. A door-side engagement tab 353 on track is selectively received in a tab receiving aperture 355 (FIG. 61B) in a hat channel near the top of interior side of door 64'. Engagement tab 353 includes

a fastener aperture 357 for receiving a mechanical fastener that can be secured through both engagement tab 353 and hat channel of door 64'. Alternatively, as shown in FIG. 62, a permanent bracket 356 with fasteners 358 may be used.

FIG. 62-64 illustrate over-the-case door 64' at a nearly fully open position. The door 64' is allowed to slide along slide 316 (or 318) until reaching the top of the slide at the inside top of the door. As shown in FIG. 64, slides 316 and 318 allow the over-the-case door 64' to move downwardly relative to top panel 18 of storage unit assembly 10 until the bottom of the over-the-case door 64' can abut bottom panel 20. Spring assist 315 lessens the rate of travel when the door 64' is closed and minimizes the likelihood of injury to a user. In addition, when door 64' is being opened, spring assist 315 assists door 64' to open and come to rest above storage unit assembly 10.

Referring now to FIGS. 65-71, a door 64" having a substantially planar construction (such as the aforementioned wood door, metal door or picture frame door) may be used in an in-the-case construction or application. An in-the-case construction allows door 64" to be in a closed position perpendicular with and below top panel 18 or an open position wherein in-the-case door 64" is disposed parallel with top panel 18 and inside case 26. Door 64" is adapted to slide in and out of case 26 in the in-the-case construction on guide rails 360 that are shown in FIGS. 67 and 68. The guide rails 360 are attached to first and second end panels 22, 24 and include a vertical portion 362 fixedly attached to the inside of first and second end panels 22, 24 as well as a rail portion 364 having forward and rearward hook-like stops 366, 368. As shown in FIG. 69, guide rail 360 is located at a top portion of the inside of first and second end panels 22, 24.

Referring to FIGS. 70 and 71, an in-the-case door support mechanism 361 includes in-the-case door 64" attached to first and second pivot pins 381A, 381B located at an rear top portion of in-the-case door 64". Each pivot pin 381A, 381B rests below guide rail 360 and is adapted to slide along the bottom of guide rail 360 between forward stop 366 (in a closed door position) and the rearward stop 368 (in an open door position). In the fully open position, in-the-case door 64" rests on top of the guide rail 360. As mentioned above, the metal door 64A, wood door 64B, or picture frame door 64D may be used for an in-the-case application. As shown in FIGS. 71A-71D, a dampener mechanism 370 may be included that provides assistance to the user when the door is being closed. The dampener 370 includes a housing 371 pivotally attached to a top portion of a door 64" and a rod 372 attached to an interior portion of case 26.

Referring now to FIGS. 72-75, an optional anti-racking mechanism 380 may be utilized that prevents in-the-case door 64" from binding during opening or closing. Anti-racking mechanism 380 includes a door side bracket 382 attached to hinges 384 that are fixedly attached to a top portion of the rear of the in-the-case door 64". Anti-racking mechanism 380 also includes first and second scissor members 386, 388 that cross and attach to a rear bracket 390. Rear bracket 390 releasably engages a quick connect bracket 392 (FIG. 75) which is fixedly attached to the underside of top panel 18 inside storage unit assembly 10. Rear bracket 390 includes tabs 393A and 393B with protuberances 394A and 394B, respectively, and a center tab 395 all of which laterally align and releasably attach rear bracket 390 with quick connect bracket 392. Rear bracket 390 includes center slot 396 and tab receiving apertures 397A and 397B which are adapted to receive protuberances 394A and 394B. Optionally, a spring assist 398 may be installed which is connected to the rear bracket 390 and door-side bracket 382.

As shown in FIGS. 74A and 74B, to install anti-racking mechanism 380 the hinges are first fastened to the in-the-case door 64". Rear bracket 390 is then lined up with quick connect bracket 392 such that tab receiving apertures 397A and 397B are aligned vertically with protuberances 394A and 394B (FIG. 74A). The rear bracket 390 is then lifted vertically. The center tab 395 engages and laterally aligns with the slot 396 while the rear bracket is lifted vertically until the protuberances 394A and 394B snappingly engage the receiving apertures 397A and 397B, holding rear bracket 390 in place. To remove rear bracket 390 from quick connect bracket 392, a prying tool, such as a screwdriver is used to separate the protuberances 394A, 394B from the receiving apertures 397A and 397B and the rear bracket is lowered out of position. Quick connect bracket 392 can be installed without the use of fasteners, allowing for easy and fast installation of the anti-racking mechanism 380. The hinges 384 attached to the front bracket 382 of the anti-racking mechanism 380 allow door 64" to open and close while the anti-racking mechanism 380 maintains a substantially horizontal alignment, as shown in FIGS. 77 and 78. A bumper 399 may also be included which prevents the anti-racking mechanism and door from being slammed shut by a user.

Referring now to FIGS. 79-83, end panel 22 (and also end panel 24) may include integral hooks 400 instead of or in addition to the slots 34 located at a rear portion 32 of first and second end panels 22, 24. As shown in FIGS. 84 and 85, when attached to top and bottom panels 18, 20, back stop rail 62 and bottom panel 20, the end panels 22, 24 act to support case 26 in a panel-hung condition.

As shown in FIGS. 86-134, storage unit 10 may be installed on a panel or desk system in a variety of ways, as disclosed in further detail below and as disclosed in U.S. Provisional Application Ser. No. 60/940,879, filed May 30, 2007, entitled STORAGE UNIT ATTACHMENT ARRANGEMENT AND METHODS, which is hereby incorporated by reference.

Referring now to FIGS. 86-91, for end panels 22, 24 having multiple slots 34 in the rear portion 32 of end panels 22, 24, hanger brackets 35, 36 are used to suspend case 26 in a panel hung condition. The first and second hanger brackets 35, 36 are mirror images of one another and have like components. The first hooks, or wall-side hooks 40 of the hanger bracket extend from a rear portion of the hanger bracket 35 and are shaped for reception in the slotted hangers 16 in an office furniture unit 12. Second hooks, or case-side hooks 44A, 44B, 44C (collectively referred to as 44) are shaped for reception in the slots 34 in the rear portions 32 of the first and second end panels 22, 24 and support the case 26 when installed in the panel-hung condition against the outer face 46 of office furniture unit 12. Hanger brackets 35, 36 may include an anti-dislodgement clip 418 designed to engage a slotted hanger 16 in office furniture unit 12 and prevent the hanger brackets 35, 36 as well as case 26 from being accidentally removed. It should be understood that any number or configuration of first hooks 40 may be present on the hanger brackets 35, 36 so that the hanger brackets 35, 36 can interface properly with the relevant slotted hanger in the associated furniture unit 12. The lowermost case-side hook 44C includes an anti-dislodgement aperture 420 for receiving an anti-dislodgement clip 422, as will be discussed in greater detail below. Also, the middle case-side hook 44B includes an anti-dislodgement aperture 424 for receiving an anti-dislodgement pin 426 (FIGS. 98 and 105) in a vertical off-module arrangement.

Referring now to FIG. 92, during installation of storage unit assembly 10 to office furniture unit 12, first and second hanger brackets 35 and 36 are first inserted into the slotted

hangers 16 in office furniture unit 12. If an anti-dislodgement clip 418 is present, the same is properly inserted into a slotted hanger 16 to prevent dislodgement of the hanger bracket 35 after installation. After the hanger brackets 35 and 36 have been installed, the storage unit 10 is lined up vertically and horizontally (FIGS. 94 and 95) so that the case-side hooks 44A, 44B, 44C are directly behind the slots 34 in the first and second end panels 22, 24. First and second end panels 22, 24 are then inserted onto the case-side hooks 44A, 44B, 44C and storage unit assembly 10 is allowed to lower onto the hooks 44A, 44B, 44C (FIGS. 96 and 97A).

Referring now to FIGS. 97B and 97C, the anti-dislodgement clips 430 on end panels 22, 24 are designed to engage anti-dislodgement aperture 420 of hanger brackets 35, 36 through an aperture 422 in the rear portion 32 of the end panel 22. During installation, the anti-dislodgement clips 430 are simply pulled back against the spring force of the clip 430 and allowed to spring back into aperture 422 and consequently anti-dislodgement aperture 420 when case-side hook 44C of hanger bracket 35 has been fully inserted into bottom slot 34 in the rear portion 32 of end panel 22, as illustrated in FIG. 97C. The same is done with respect to end panel 24 and hanger bracket 36. The anti-dislodgement clips 430 prevent end panels 22, 24 from becoming accidentally dislodged from the hanger brackets 35, 36.

In many instances, a storage unit assembly 10 must be installed in an off-module arrangement. In these situations, a bracket that translates the binder bin from an on-module position to an off-module position is necessary.

FIGS. 98-104 illustrate a vertical off-module support bracket 440. The vertical off-module bracket 440 includes a substantially planar front portion 442 and a rear portion 444 that has two sets of vertically-oriented slots 446, 448 that extend through inwardly extending flanges 449. The two sets of vertically-oriented slots 446, 448 allow the vertical off-module bracket 440 to be used on either side of storage unit assembly 10. The slots 446, 448 receive the case-side hooks 44 of the first and second hanger brackets 35, 36 when storage unit assembly 10 is placed in a vertical off-module panel-hung condition. A forward bottom portion 450 includes a lower support ledge 452 adapted to support the base flange of back stop rail 62 when storage unit assembly 10 is placed in a vertical off-module panel hung condition (FIG. 107B). A forward top portion 454 of the vertical off-module support bracket 440 includes a forward top ledge 456 adapted to provide lateral support to storage unit assembly 10 to prevent the same from rotating off of the lower support ledge 452. A fastener aperture 457 is located in forward top portion 454 on each side of vertical off module bracket 440. Case 26 is hung on the vertical off-module support bracket 440 in a manner which permits case 26 to shift laterally relative to first and second hanger brackets 35, 36. An anti-dislodgement clip 458 is mounted on the forward bottom portion 450 of the vertical off-module support bracket 440 and prevents accidental dislodgement of back stop rail 62 from the lower support ledge 452. Further, an anti-dislodgement aperture 460 in the vertical off-module bracket 440 is designed to receive a pin that also penetrates the anti-dislodgement aperture 424 in the hanger bracket 35, thus preventing the vertical off-module support bracket 440 from being disengaged from the hanger bracket 35.

Referring now to FIGS. 105-107, during installation of storage unit assembly 10 into a vertical off-module condition, first and second hanger brackets 35, 36 are inserted into the slotted hangers 16 in office furniture unit 12. One of the sets of vertically-oriented slots 446, 448 in the rear portion 444 of first and second vertical off-module brackets 440A and 440B

are lined up and inserted over the case-side hooks **44A**, **44B**, **44C** of the hanger brackets **35**, **36**, respectively. The vertical off-module brackets **440A** and **440B** are allowed to hang from the hanger brackets **35** and **36** and storage unit assembly **10** is rested on the lower support ledge **452** of each vertical off-module bracket **440A**, **440B**. As the base flange **112** of back stop rail **62** comes to rest against the lower support ledge **452**, the forward top ledge **456** abuts the inwardly extending rear flange **198** of the top panel **18**. The anti-dislodgement clip **458** of each vertical off-module bracket **440A**, **440B** snaps over the base flange **112** of back stop rail **62** as storage unit assembly **10** is lowered into place, as shown in FIG. **107B**.

FIGS. **108-112** illustrate a top bracket **470** of a horizontal off-module support bracket system **472**. The top bracket **470** includes a rear portion **474** with horizontal hooks **476** shaped for reception in horizontal slotted hangers **16** on an associated office furniture unit. A forward top portion **478** has upwardly extending flanges **480** that selectively engage the rear flanges **449** of the vertical off-module support bracket **440**. Upwardly extending flanges **480** include fastener apertures that, after installation, align with fastener apertures **457** of vertical off-module bracket **440**. The top bracket **470** also includes an anti-dislodgement clip **482**.

FIGS. **113-118** show a bottom bracket **490** of the horizontal off-module support bracket system **472**. The bottom bracket **490** has side portions **491A** and **491B**, a rear portion **492** with two small horizontal hooks **494A** and a large horizontal hook **494B** shaped for reception in horizontal slotted hangers **16** in office furniture unit **12**. A forward portion **496** of the bottom bracket **490** includes vertical hooks **498** that can be selectively received in the lowermost of slots **446**, **448** in the rear portion **444** of the vertical off-module bracket **440** to detachably support storage unit assembly **10** in a panel-hung condition against the outer face of office furniture unit **12**. As shown in FIG. **120A**, an anti-dislodgement feature **499** includes a spring joint **500** that connects the side portions **491A** and **491B** which are spring biased away from one another. Anti-dislodgement feature **499** prevents bottom bracket **490** from being dislodged from the horizontal slotted hangers **16** accidentally, as will be explained in further detail below.

Referring to FIGS. **119-126**, during installation, the horizontal off-module bracket system **472**, including the top and bottom brackets **470**, **490**, are first inserted into horizontal slotted hangers **16** in office furniture unit **12** with the top bracket **470** in position directly above bottom bracket **490**. Large horizontal hook **494B** is first inserted into one of the horizontal slotted hangers and side portions **491A** and **491B** are pushed toward one another to allow small horizontal hooks **494A** to engage slots in slotted hanger **16**. Bottom bracket **490** is then rotated laterally until small horizontal hooks **494A** are received in adjacent slots in horizontal slotted hanger **16**. Large horizontal hook **494B** fills an entire slot, while small horizontal hooks **494A** do not.

Referring again to FIGS. **119-126**, the vertical off-module support bracket **440** is then inserted into the top bracket **470** with the inwardly extending rear flanges **449** sliding behind the upwardly extending flanges **480** of the top bracket **470** of the horizontal off-module bracket system **472**, as shown in FIG. **123**. The middle and lowermost of the slots **446**, **448** of the vertical off-module brackets **440** are then aligned with the vertical hooks **498** of the bottom bracket **490** and inserted thereon. After vertical off-module support bracket **440** is inserted onto bottom bracket **490**, bottom bracket **490** cannot be separated from horizontal slotted hanger **16**. The vertical off-module bracket **440** prevents spreading of the side portions **491A** and **491B** from one another and consequently,

bottom bracket cannot be removed from slotted hanger **16** while vertical off-module bracket **440** is connected therewith. A mechanical fastener may be secured through an aperture to secure top bracket **470** to vertical off-module bracket **440**.

As shown in FIGS. **125** and **126**, storage unit assembly **10** is now ready to be installed on the vertical off-module bracket **440** similarly to the manner of installation disclosed with respect to FIGS. **105-107** above.

Alternatively, storage unit assembly **10** may be installed in an up-mounted condition. To install storage unit assembly **10** in an up-mounted condition, up-mount brackets are necessary. As shown in FIGS. **127-130**, up-mount bracket **48** has a lower portion **502** shaped for connection with an associated one of office furniture unit **12**, and an upper portion **504** adapted to connect with and support the connector brackets at the bottom of case **26** to detachably mount case **26** in an up-mounted condition above the top of a furniture unit. The lower portion of up-mount bracket **48** includes a triangular shape with a lower arcuate flange **506** and a hook portion **508**. The hook portion **508** includes a plurality of hooks **510** adapted to engage slotted hangers **16** in office furniture unit **12**. The lower arcuate flange **506** can be used to route electrical/communication wires and the arcuate construction minimizes the likelihood of injury to a user that may accidentally contact up-mount bracket **48**. The upper portion **504** includes a top horizontal support flange **509** and a top vertical support flange **512**. An anti-dislodgement clip **514** may be present on the hook portion **508** to prevent up-mount bracket **48** from being accidentally dislodged.

To install storage unit assembly **10**, the hook portion **508** of two up-mount brackets **48** is first installed into the slotted hangers **16** in office furniture unit **12**. Connector brackets **98**, described above with reference to FIGS. **15-19**, of storage unit assembly **10** are then placed on the horizontal support flanges **509** of the up-mount brackets **48** and fastened thereto as shown in FIGS. **133A** and **134**. Alternatively, storage unit assembly **10** may be installed in an up-mounted condition on a desk/service module assembly **511** as shown in FIG. **133B**.

As shown in FIGS. **135-139**, a lock assembly **520** includes a lock housing **76** with spring tabs **524** adapted to engage bottom panel socket **74** shown in FIGS. **5** and **8** and located on the underside of bottom panel **20**. The lock housing **76** covers the lock assembly **520** and lock arm **92** designed to engage lock apertures **236**, **238** in a door **64A**, **64B**, **64C**, or **64D**, thereby locking storage unit assembly **10** when not in use.

Referring to FIGS. **135-139**, during installation, the lock housing **76** is installed beneath bottom panel **20**. The lock housing **76** is inserted so that a key hole **523** extends downwardly through a lock cylinder aperture **530** (FIG. **138**) that extends downwardly. During installation, the spring tabs **524** are in abutting contact with the underside of bottom panel **20**. As the lock housing **76** is forced into position, spring tabs **524** flex inwardly until the lock assembly **520** projects through the lock cylinder aperture **530** that extends through socket flange **84**, at which time spring tabs **524** force lock housing **76** downward and frictionally secure lock housing **76** inside the socket **74**.

Referring to FIGS. **140-143**, in a dual door assembly **600**, a top panel **18'** having four cutouts **604** for hinge mechanisms of two doors **64A'**, **64B'**, **64C'**, or **64D'** is used. The underside of the top panel **18'** includes two quick connect brackets **392** for two anti-racking mechanisms **380**. In addition, to supply structural rigidity, a hat channel **606** is secured to the underside of the top panel **18'**. FIG. **142** shows a dual door support **608** including multiple guide rails **360** that is used to provide guides for in-the-case constructions. Specifically, the dual door support **608** includes two guide rails **360** connected by a

19

bracket assembly 610 that supports the guide rails 360 adjacent to the underside of top panel 18'. FIG. 143 illustrates the dual door assembly 600 which is similar to the single door construction except it includes two doors 64 and the dual door support 608 as well as the modified top panel 18' with additional cutouts 604 for hinge mechanisms and reinforcing hat channel 606. Note that the cutouts 604 for the hinge mechanisms may not be present in a dual door in-the-case application.

Referring now to FIGS. 149-150, a shelf assembly 701 having no side walls and integral shelving brackets 700 may be supplied to complement the office furniture system. A shelf 703 is included and is substantially similar to the bottom panel 20 but does not include a lock aperture 90. Shelf brackets (shown in FIGS. 144-148) are included and have integral hooks 702 connected at a rearward end 704 of the shelf bracket and also include an anti-dislodgement clip 706. Shelf brackets 700 also include a connector bracket 708 that connects the shelf bracket 700 with the shelf 703. As shown in FIG. 150, the shelf assembly 701 does not include a back stop rail nor side walls.

Referring now to FIGS. 156-157, a second shelf assembly 800 having a shelf 802 with end walls 804 may be used to complement an office furniture setting. The shelf 802 engages connector brackets 807 on the end walls 804. The second shelf assembly 800 also includes a back stop rail 62 and anti-dislodgement clips 806. Back stop rail 62 engages rail brackets 808 attached to the shelf brackets 802.

Referring now to FIGS. 158-161, for a dual door assembly, a support strut 900 is supplied to add structural integrity to case 26 and may be permanently fastened to the rear of storage unit assembly 10. The support strut 900 includes a top engagement portion 902 with a top tab 903A and an abutment portion 903B, a bottom engagement portion 904, and an elongate body 906. Top tab 903A includes a horizontal extension 914, a vertical extension 916 and a horizontally extending distal end 918 that engages a strut aperture 920 (FIG. 32) in the inwardly extending rear flange 198 below top panel 18. The horizontally extending distal end of top tab 903A is inserted into the strut aperture 920 and the inwardly extending rear flange 198 rests on the abutment portion 903B. The bottom engagement portion 904 includes a flat downwardly extending flange 922 offset from the elongate body 906. A fastener aperture 924 that extends through the bottom engagement portion 904 receives a mechanical fastener 928 secured in a receiving aperture 926 in back stop rail 62.

FIGS. 162-165 illustrate a support strut 940 may be used for transporting storage unit assembly 10. The support strut 940 includes a top engagement portion 942 with a cam surface 943A, and an abutment portion 943B, a bottom engagement portion 944, and an elongate body 946. Cam surface 943A is rotated into place which results in cam surface 943A being inserted into a strut aperture 920 (FIG. 32) and the inwardly extending rear flange 198 of case 26 rests on the abutment portion 943B. The bottom engagement portion 944 includes a flat downwardly extending flange 947 offset from the elongate body 946. A fastener receiver 948 having an open portion 950 receives a mechanical fastener 952 secured in a receiving aperture 956 in back stop rail 62.

A method for making a storage unit assembly for office furniture units of the type having a like construction with slotted hangers extending along outer faces thereof includes forming bottom panel 20 to abuttingly support objects thereon. Top panel 18 is formed in a shape to cover at least a portion of bottom panel 20. Top panel 18 is positioned in a generally parallel, spaced apart relationship with bottom panel 20. First and second end panels 22, 24 are formed with

20

rear portions 32 having a plurality of vertically spaced slots 34 therein. First and second end panels 22, 24 are positioned at opposite ends of top and bottom panels 18, 20 and are interconnected to define rigid, box-shaped case 26 having generally rigid bottom portion 28 and generally open back portion 30. First and second hanger brackets 35, 36 are formed, each having rear portion 38 with first hooks 40 shaped for reception in the slotted hangers 16 of a first selected one of the office furniture units 12, and a forward portion 42 with second hooks 44 shaped for reception in the slots 34 in rear portions 32 of first and second end panels 22, 24. First hooks 40 on first and second hanger brackets 35, 36 are inserted into the slotted hangers 16 on the first selected furniture unit. Second hooks 44 on the first and second hanger brackets 35, 36 are inserted into slots 34 in rear portions 32 of first and second end panels 22, 24 to detachably support case 26 in a panel-hung condition against the outer face 14 of the first selected office furniture unit. An up-mount bracket 48 is formed with a lower portion 52 shaped for connection with a second selected one of the office furniture units, and an upper portion 54 shaped for connection with the bottom portion 28 of case 26. Lower portion 52 of the up-mount bracket 48 is mounted with the second selected furniture unit. The upper portion 54 of the up-mount bracket 48 is connected with bottom portion 28 of case 26 to detachably mount case 26 in an up-mounted condition above a top portion 54 of the second selected furniture unit. A removable back panel 56 is formed in a shape to enclose at least a portion of the open back portion 30 of case 26, and has side portions 58 with outwardly protruding hooks 60 shaped for reception in slots 34 in rear portions 32 of first and second end panels 22, 24. Hooks 60 on the back panel 56 are inserted into slots 34 in rear portions 32 of first and second end panels 22, 24 to detachably connect back panel 56 with case 26 and enclose at least that portion of the open back portion 30 of case 26 disposed above top portion 54 of the second selected office furniture unit when the case is in the up-mounted condition.

An anti-dislodgement clip 430 can be mounted on the case 26 adjacent to one of the first and second end panels 22, 24. The second hooks 44 on said first hanger bracket 35 are engaged in the panel-hung condition, and the hooks 60 on the back panel 56 are engaged in the up-mounted condition. The back stop rail 62 is formed and is configured to extend along a rearward portion of the bottom panel 20 between the first and second end panels 22, 24. The back stop rail 62 is connected with the bottom panel 20 and the first and second end panels 22, 24 to rigidify the case 26, and the back stop rail 62 is positioned to project upwardly from the bottom panel 20 to retain objects on the bottom panel 20. At least one accessory is provided and is configured to equip the interior portion of the case 26 and may be detachably connected with the back stop rail 62.

The first off-module support bracket 440 is formed having a rear portion 444 thereof with slots 446, 448 selectively receiving therein the second hooks 44 of the first and second hanger brackets 35, 36 in a vertical off-module panel-hung condition, a forward bottom portion 450 thereof abuttingly supporting thereon the bottom panel 20 of the case 26, and a forward top portion 454 thereof connected with the top panel 18 of the case 26 in a manner which permits the case 26 to shift laterally relative to the first and second hanger brackets 35, 36. The second off-module support bracket 472 is formed and includes a top bracket 470 having a rear portion 474 with horizontal hooks 476 shaped for reception in horizontal ones of the slotted hangers 16 on an associated one of the office furniture units 12, a top portion 478 with an upwardly extending flange 480 selectively engaging the top panel 18 of the

21

case 26, a bottom bracket 490 having a rear portion 492 with horizontal hooks 494A, 494B shaped for reception in horizontal ones of the slotted hangers 16 in the associated one of the office furniture units 12, and a forward portion 496 with vertical hooks 498 selectively received in the slots 446, 448 in the rear portion 32 of the first and second end panels 22, 24 to detachably support the case 26 in a panel-hung condition against the outer face of the associated one of the office furniture units 26.

The socket 74 is formed in the bottom panel 20 along the bottom edge thereof and a lock housing 76 is formed with spring flanges 524 that frictionally engage adjacent portions of the socket 74 to securely retain the lock housing 76 in the bottom panel 20. A generally open front portion 80 in the case 26 is formed and disposed opposite the generally open back portion 30. The door 64A, 64B, 64C, 64D is operably connected with the case 26 to selectively enclose the generally open front portion 80 of the case 26. The over-the-case door support mechanism 312 is formed and the first portion the mechanism 312 is connected with the case 26 and the second portion of the mechanism 312 is connected with the door 64A, 64B, 64C, 64D to permit shifting the door 64A, 64B, 64C, 64D between the closed position over the open front portion 80 of the case 26 and an open position outside of the case 26 over the top panel 18. The in-the-case door support mechanism 361 is formed and a first portion of the mechanism 361 is connected with the case 26 and a second portion of the mechanism 361 is connected to the door 64" to permit shifting the door 64" between the closed position over the open front of the case 26 and the open position inside of the case 26 portion under the top panel 18.

The anti-racking mechanism 380 is formed and a first portion of the mechanism 380 is connected with the door 64" and a second portion of the mechanism 380 with the case 26 to alleviate binding of the door 64" when the same is shifted between the open and closed positions. A quick connect bracket 392 is formed and connects the second portion of the anti-racking mechanism 380 with the case 26.

The door dampener 370 is formed with the housing 371 pivotally attached to a top portion of the door 64" and a rod portion 372 pivotally attached to an interior portion of the case 26. A door 64" open assist 398 is provided having a longitudinally resilient construction with one end operably connected with the door 64" and the opposite end operably connected with the case 26 to assist shifting the door 64" from the closed position to the open position. A rigid reinforcing strut 900 is provided and is positioned along a medial portion of the back panel 56, and an upper end of the strut 900 is detachably connected with the top panel 18 and a lower end of the strut 900 with the bottom panel 20 to stiffen the case 26.

It is to be understood that variations and modifications can be made to the aforementioned structure without departing from the concepts of the present invention, and further it is to be understood that such concepts are intended to be covered by the following claims unless these claims by their language expressly state otherwise.

The invention claimed is:

1. A storage unit assembly for office furniture units of the type having an outer face with slotted hangers extending therealong, comprising:

a bottom panel operably positioned in a generally horizontal orientation, and shaped to abuttingly support objects thereon;

a top panel disposed above and generally parallel with said bottom panel, and shaped to cover at least a portion of said bottom panel;

22

first and second end panels disposed at opposite ends of said top and bottom panels and connected therewith to define a rigid, box-shaped case having a generally rigid bottom portion and a generally open back portion; said first and second end panels having rear portions with a plurality of vertically spaced apart slots disposed therein;

first and second hanger brackets each having a rear portion with first hooks shaped for reception in the slotted hangers of an associated one of the office furniture units, and a forward portion with second hooks selectively received in said slots in said rear portions of said first and second end panels to detachably support said case in a panel-hung condition against the outer face of the associated one of the office furniture units;

an up-mount bracket having a lower portion shaped for connection with an associated one of the office furniture units, and an upper portion connected with and supporting said bottom portion of said case to detachably mount said case in an up-mounted condition above a top portion of the associated one of the furniture units; and

a removable back panel shaped to enclose at least a portion of said open back portion of said case, and having side portions with outwardly protruding hooks selectively received in said slots in said rear portions of said first and second end panels to detachably connect said back panel with said case and enclose at least that portion of said open back portion of said case disposed above the top portion of the associated one of the office furniture units when said case is in said up-mounted condition.

2. A storage unit assembly as set forth in claim 1, including: an anti-dislodgement clip mounted on said case adjacent to one of said first and second end panels, and engaging said second hooks on said first hanger bracket in said panel-hung condition, and said hooks on said back panel in said up-mounted condition.

3. A storage unit assembly as set forth in claim 1, including: a back stop rail extending along a rearward portion of said bottom panel between said first and second end panels; said back stop rail is connected with said bottom panel and said first and second end panels to rigidify said case, and projects upwardly from said bottom panel to retain objects thereon.

4. A storage unit assembly as set forth in claim 1, including: a pair of connector brackets mounted on inside surfaces of said first and second end panels, and engaging said opposite ends of said bottom panel to rigidly interconnect said first and second end panels.

5. A storage unit assembly as set forth in claim 1, including: a pair of clips mounted on top surfaces of said first and second end panels, and engaging said opposite ends of the top panel to interconnect said first and second end panels.

6. A storage unit assembly as set forth in claim 1, wherein: said panel-hung condition defines an on-module panel-hung condition and includes

a first off-module support bracket having a rear portion thereof with slots selectively receiving therein said second hooks of said first and second hanger brackets in a vertical off-module panel-hung condition, a forward bottom portion thereof abuttingly supporting thereon said back stop rail, and a forward top portion thereof connected with said top panel of said case in a manner which permits said case to shift laterally relative to said first and second hanger brackets.

23

7. A storage unit assembly as set forth in claim 6, wherein: said panel-hung condition defines an off-module panel-hung condition and includes
- a second off-module support bracket including a top bracket having a rear portion with horizontal hooks 5 shaped for reception in horizontal ones of the slotted hangers on an associated one of the office furniture units, a top portion with an upwardly extending flange selectively engaging said first off-module support bracket, a bottom bracket having a rear portion with horizontal 10 hooks shaped for reception in horizontal ones of the slotted hangers in the associated one of the office furniture units, and a forward portion with vertical hooks selectively received in said slots in said rear portion of said first off-module bracket to detachably support said 15 case in a panel-hung condition against the outer face of the associated one of the office furniture units.
8. A storage unit assembly as set forth in claim 1, wherein: said bottom panel includes a socket positioned along a 20 bottom edge thereof; and including
- a lock housing having spring flanges that frictionally engage adjacent portions of said socket to securely retain said lock housing in said bottom panel.
9. A storage unit assembly as set forth in claim 1, wherein: said case includes a generally open front portion disposed 25 opposite said generally open back portion; and including:
- a door operably connected with said case, and shaped to selectively enclose said generally open front portion of said case.
10. A storage unit assembly as set forth in claim 9, including:
- an over-the-case door support mechanism having a first portion thereof connected with said case and a second 30 portion thereof connected with said door, and configured to permit shifting said door between a closed position over said open front portion of said case and an open position outside of said case over said top panel.
11. A storage unit assembly as set forth in claim 9, including:
- an in-the-case door support mechanism having a first portion thereof connected with said case and a second 35 portion thereof connected with said door, and configured to permit shifting said door between a closed position over said open front of said case and an open position inside 40 of said case under said top panel.
12. A storage unit assembly as set forth in claim 9, wherein: said door comprises one of a plurality of different door constructions, including:
- at least one solid door construction; 45
- at least one curved front door construction; and
- at least one picture frame door construction.
13. A storage unit assembly as set forth in claim 1, including:
- an anti-racking mechanism having a first portion thereof 50 operably connected with said door and a second portion thereof operably connected with said case, and configured to alleviate binding of said door when the same is shifted between said open and closed positions; and
- a quick connect bracket connecting said second portion of 55 said anti-racking mechanism with said case.
14. A storage unit assembly as set forth in claim 1, including:
- a door dampener having a cylinder portion thereof pivotally 60 attached to a top portion of said door, and a piston portion thereof pivotally attached to an interior portion of said top panel.

24

15. A storage unit assembly as set forth in claim 1, including:
- a door open assist having a longitudinally resilient construction with one end thereof operably connected with said door and the opposite end thereof operably connected with said case to assist shifting said door from said closed position to said open position.
16. A storage unit assembly as set forth in claim 1, including:
- a rigid reinforcing strut disposed along a medial portion of said back panel, and having an upper end thereof detachably connected with said top panel and a lower end thereof detachably connected with said bottom panel to stiffen said case.
17. A storage unit assembly as set forth in claim 1, wherein: said rear portions of said first and second end panels define generally flat rear edges through which said slots extend.
18. A storage unit assembly as set forth in claim 1, wherein: said first and second end panels have a formed, one-piece construction with said rear edges formed integral therein.
19. A storage unit assembly as set forth in claim 1, wherein: said back panel includes an upper lip that extends inwardly from an upper portion of said back panel, and further includes a lower flange that extends inwardly and substantially orthogonally from a lower portion of said back panel.
20. A storage unit assembly as set forth in claim 19, wherein:
- said upper lip of said back panel engages said top panel and said lower flange extends below said case proximate a pair of connector brackets mounted on inside surfaces of said first and second end panels when said case is in said up-mounted condition.
21. A storage unit assembly as set forth in claim 1, wherein: said first and second end panels include a front flange extending therealong, wherein said front flange includes a lower edge adapted to receive and retain a front portion of said bottom panel.
22. A storage unit assembly as set forth in claim 1, wherein: said top panel includes side flanges that extend below said top panel and which include clip apertures adapted to engage a pair of clips mounted on top surfaces of said first and second end panels and further includes a detent stop aperture for engaging a detent stop on said top surfaces of said first and second end panels.
23. In an office furniture unit having an outer face with slotted hangers extending therealong, the improvement of a removable storage unit assembly, comprising:
- a bottom panel operably positioned in a generally horizontal orientation along said office furniture unit;
- a top panel disposed above and generally parallel with said bottom panel;
- first and second end panels disposed at opposite ends of said top and bottom panels and connected therewith to define a rigid, box-shaped case having a generally open back portion; said first and second end panels having rear portions with a plurality of vertically spaced apart slots disposed therein;
- a back stop rail extending along a rearward portion of said bottom panel between said first and second end panels; said back stop rail is connected with said bottom panel and said first and second end panels to rigidify said case; and
- first and second hanger brackets each having a rear portion with first hooks selectively received in said slotted hangers of said office furniture units, and a forward portion

25

with second hooks selectively received in said slots in said rear portions of said first and second end panels to detachably support said case in a panel-hung condition against said outer face of said office furniture unit; wherein said panel-hung condition defines an on-module panel-hung condition and includes a first off-module support bracket having a rear portion thereof with slots selectively receiving therein said second hooks of said first and second hanger brackets in a vertical off-module panel-hung condition, a forward bottom portion thereof abuttingly supporting thereon said back stop rail, and a forward top portion thereof connected with said top panel of said case in a manner which permits said case to shift laterally relative to said first and second hanger brackets.

24. A storage unit assembly as set forth in claim **23**, including: an anti-dislodgement clip mounted on said case adjacent to one of said first and second end panels, and engaging said second hooks on an adjacent one of said hanger brackets in said panel-hung condition.

26

25. A storage unit assembly as set forth in claim **23**, wherein:

said panel-hung condition defines an off-module panel-hung condition and includes

a second off-module support bracket including a top bracket having a rear portion with horizontal hooks shaped for reception in horizontal ones of the slotted hangers on an associated one of the office furniture units, a top portion with an upwardly extending flange selectively engaging said first off-module support bracket, a bottom bracket having a rear portion with horizontal hooks shaped for reception in horizontal ones of the slotted hangers in the associated one of the office furniture units, and a forward portion with vertical hooks selectively received in said slots in said rear portion of said first off-module bracket to detachably support said case in a panel-hung condition against the outer face of the associated one of the office furniture units.

* * * * *