

US008123245B2

(12) **United States Patent**
Johnson et al.

(10) **Patent No.:** **US 8,123,245 B2**
(45) **Date of Patent:** **Feb. 28, 2012**

- (54) **STABILIZED MOBILE UNIT OR WHEELCHAIR**
- (75) Inventors: **Charles E. Johnson**, Rogersville, TN (US); **Phillip N. Brown**, Rogersville, TN (US)
- (73) Assignee: **Life Changing Chair, LLC**, Rogersville, TN (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

4,613,151	A	9/1986	Kielczewski	
4,717,169	A *	1/1988	Shaffer	280/648
4,997,200	A *	3/1991	Earls	280/648
5,011,175	A	4/1991	Nicholson et al.	
5,259,664	A	11/1993	Cottle	
5,333,887	A	8/1994	Luther	
5,601,302	A	2/1997	Beard et al.	
5,730,236	A	3/1998	Miller et al.	
5,772,237	A	6/1998	Finch et al.	
6,381,781	B1 *	5/2002	Bourgraf et al.	5/618
6,530,445	B1	3/2003	Flowers et al.	
6,726,279	B1 *	4/2004	Figel et al.	297/340

(Continued)

- (21) Appl. No.: **12/835,245**
- (22) Filed: **Jul. 13, 2010**
- (65) **Prior Publication Data**
US 2010/0276898 A1 Nov. 4, 2010

Related U.S. Application Data

- (63) Continuation of application No. 11/835,963, filed on Aug. 8, 2007, now Pat. No. 7,758,063.
- (60) Provisional application No. 60/836,293, filed on Aug. 8, 2006.
- (51) **Int. Cl.**
B62B 7/06 (2006.01)
- (52) **U.S. Cl.** **280/647; 280/650**
- (58) **Field of Classification Search** 280/642, 280/643, 647, 648
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,147,039	A *	9/1964	Smith et al.	297/90
3,882,949	A	5/1975	Anderson	
4,079,990	A	3/1978	McMunn et al.	
4,105,242	A *	8/1978	Terbeek	296/20
4,453,732	A *	6/1984	Assanah et al.	280/648

OTHER PUBLICATIONS

International Search Report for Application PCT/US09/02757, with related Notification and Written Opinion (Jun. 30, 2009).



(Continued)

Primary Examiner — Jeffrey J Restifo
(74) *Attorney, Agent, or Firm* — Kilyk & Bowersox, P.L.L.C.

(57) **ABSTRACT**

A mobile vehicle or wheelchair has the ability to provide stabilized transport to at least one individual on a variety of surfaces, slopes and/or terrains. The mobile unit or wheelchair may travel across smooth and very rough surfaces, slopes of varying or different angles and various outdoor terrains (including grassy, rocky, sandy, muddy and/or hilly terrains). In one aspect, the height of any part of the unit or the overall height of the device may be adjusted preferably to raise or lower the center of gravity. For example, the height of the device may be lowered to provide more stable transportation. In another aspect, the device may be adjusted to increase or decrease the size of the footprint (or any part of the footprint) of the device. For example, the footprint of the device may be enlarged to provide more stable transportation. Preferably, both the height of the device (or any part of the device) and the size of the footprint (or any part of the footprint) may be adjusted preferably to provide more stability.

7 Claims, 12 Drawing Sheets



US 8,123,245 B2

Page 2

U.S. PATENT DOCUMENTS

6,846,042 B2 * 1/2005 Hanson et al. 297/411.36
6,886,194 B2 * 5/2005 Hodgetts 5/86.1
6,912,746 B2 * 7/2005 Grove 5/618
7,055,840 B1 * 6/2006 Kelso 280/250.1
7,100,718 B2 9/2006 Bancroft
7,360,840 B2 4/2008 Barlow et al.
7,641,211 B2 * 1/2010 Ivanchenko 280/250.1
7,661,696 B1 * 2/2010 Acebo 280/647
7,758,063 B2 * 7/2010 Johnson et al. 280/647
7,841,611 B2 * 11/2010 Ivanchenko 280/250.1
2004/0212177 A1 * 10/2004 Kuiken 280/647

2005/0116440 A1 6/2005 Bernatsky et al.
2006/0061067 A1 * 3/2006 Kuiken 280/647
2008/0100036 A1 * 5/2008 Ivanchenko 280/648
2010/0276898 A1 * 11/2010 Johnson et al. 280/6.151

OTHER PUBLICATIONS

International Preliminary Report on Patentability and International Search Report for corresponding Application PCT/US2007/017549, with related Notification and Written Opinion (IPRP dated Feb. 10, 2009).

* cited by examiner




FIG. 1




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 9




FIG. 8




FIG. 10




FIG. 11




FIG. 12




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20

1

STABILIZED MOBILE UNIT OR WHEELCHAIR

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 11/835,963, filed Aug. 8, 2007, which claims the benefit of U.S. Provisional Application No. 60/836,293, filed Aug. 8, 2006, the disclosures of which is incorporated by reference herein in their entirety.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention is directed to a mobile vehicle or wheelchair having the ability to provide stabilized transport to at least one individual on a variety of surfaces, slopes and/or terrains.

2. Background Art

Wheelchairs have proven to be the most practical solution to mobility for individuals that have problems walking, due to age, sickness, and/or disabilities. While both conventional and motorized wheelchairs provide improved mobility to such individuals, current designs fail to adequately address the need of the individual to have broad access to various locations. In particular, current designs pose hazards to the occupant when operated on sloped and/or uneven surfaces. Current designs also fail to address various medical issues for certain individuals including poor circulation. Moreover, little has been done to provide an affordable design allowing broader availability.

The present invention addresses these and other needs.

BRIEF SUMMARY OF THE INVENTION

The present invention relates in general to a mobile unit, a vehicle, a mobile device and/or wheelchair which provides stabilized transportation for one or more passengers. In one aspect of the invention, the height of any part of the unit or the overall height of the device may be adjusted preferably to raise or lower the center of gravity, and in a preferred aspect, the height of the device is lowered to provide more stable transportation for the user of the invention. In another aspect, the device may be adjusted to lengthen or shorten the base of the device, and in a preferred aspect, the base of the device is lengthened to provide more stable transportation for the user of the invention. Preferably, both the height of the device (or any part of the device) and the length of the base (or any part of the footprint) may be adjusted to provide more stability.

In one embodiment, the wheelbase of the wheelchair extends or retracts to vary the size of the footprint, while the height of the seat member of the wheelchair increases or decreases, which varies the location of the center of gravity.

In another embodiment, the base of the wheelchair extends or retracts to vary the size of the footprint, while the height of the seat member of the wheelchair increases or decreases, which varies the location of the center of gravity. The location of the center of gravity as well as the size of the footprint may contribute to the stability of the wheelchair, and through their adjustment the stability can be increased or decreased. In one aspect, while the height of the seat member pivots to a decreased height, leg rests pivot and extend from the main frame to support a user's legs throughout transition.

In another embodiment, the base of the wheelchair extends or retracts to vary the size of the footprint, while the height of the seat member of the wheelchair increases or decreases,

2

which varies the location of the center of gravity. In one aspect, the seat member is adjustable between an upright and a lowered position, while the base is adjustable between a compacted and an extended position. In one aspect, when the seat member in an upright position, and the base is in a compacted position, the wheelchair is suited to support a user sitting upright, legs bent at the knee. This position is conducive to indoor use, as the smaller footprint of the device and higher seat member in this configuration makes it easy to maneuver in an indoor environment, among other benefits. When the seat member is in a lowered position, and the base is in an extended position, the wheelchair is suited to support a user sitting in a reclined straight-leg (or substantially straight-leg) seated position. This position is conducive to outdoor use, as the lengthened wheelbase, larger footprint and lowered seat member in this configuration provide for greater stability in traveling over potentially uneven terrain, among other benefits.

In one embodiment, the relative movement of the base (or one or more wheels as part of the base configuration) and the lowering of the seat allows the center of gravity of the user/unit combination to be lowered and thus provides more stability for the operation of the unit by the user. The combination of lowering the seat and increasing the size of the footprint allows the user to sit in a relatively flat position. Preferably the operation of the invention allows the legs of the user to be extended (preferably the legs being flat or substantially flat). This feature of the invention allows the user's legs to extend in such a manner as to provide comfort to the user and/or increase blood circulation in the user's legs.

The invention is particularly suited for use by handicapped individuals or any user who desires aid in moving from place to place. In a preferred aspect, the device of the invention comprises a base or platform (which may be prepared of any material such as metal, plastic, wood and the like or combinations thereof, and can be designed in various configurations such as a frame, a solid platform and the like or combinations thereof). In another aspect, the base or platform (or any part of the base or platform) may be adjusted to increase or decrease the size of the footprint of the base or platform. In a preferred embodiment, the footprint is increased in size to provide more stability to the unit. Preferably, the size of the footprint may be increased by extending one or more portions of the base or platform. Such one or more portions may be extended or retracted, for example, by utilizing extension/retraction tracks and/or extension/retraction rods and/or extenders that allow two or more parts of the base or platform to separate and move away from or toward each other in such a manner to allow the overall footprint size of the base to increase or decrease.

In yet another aspect, the base or platform comprises a plurality of wheels, wherein the wheels may be designed (including various shapes, sizes and/or tread configurations) to accommodate any terrain. Preferably, the invention utilizes any number of wheels including at least two, at least three, at least four, at least five, at least six, at least seven, at least eight or more wheels depending on the need. In another aspect, the size of the footprint of the base may be increased or decreased by extending or retracting one or more wheels which may be included as part of the base or platform configuration. For example, one or more wheels may be extended or retracted, for example, by utilizing one or more extension/retraction tracks and/or extension/retraction rods and/or extenders that allow at least one wheel to separate and move away from or toward the base or platform in such a manner to allow the overall footprint size of the base or platform to increase or decrease.

In another aspect, the invention may be powered or moved manually by an individual or user or may be motorized (such as by one or more electric and/or combustion motors or combinations thereof). In yet another aspect, any one or a number of the wheels of the device may be powered by such one or more motors and preferably the unit of the invention is a multi-wheel drive unit, wherein a number or all of the wheels of the unit are driven by one or more drive motors. Preferably, the device of the invention comprises four (4) wheels and preferably at least two of such wheels (and preferably all four) are capable of being driven by one or more motors. In another embodiment, one or more motors of the invention are utilized to raise and/or lower all or any part of the unit. In another aspect, one or more motors are utilized to increase and/or decrease the size of the footprint of the unit (or any part of the unit). In another embodiment, the same or different motors may be used to operate all or any number of the functions of the unit, and in a preferred aspect one motor is utilized to move the device, to increase and/or decrease the size of the footprint (or any part of the footprint) and to raise and/or lower all or any part of the unit. In utilizing the unit of the invention, the different functions of the device may be operated separately or simultaneously depending on the need of the user. When one or more motors provide operation of any or all of the features of the unit, the unit may also comprise one or more control devices allowing the user to control and operate the different features of the invention. For example, one or more control panels may be used to move the unit, adjust the size of the footprint and/or adjust the center of gravity.

The device of the invention preferably comprises at least one seat or chair unit, and in a preferred aspect, the seat or chair may be adjusted to provide more comfort and/or stability for the user. In a preferred aspect, the at least one chair or seat may be adjusted up or down relative to the base or platform. Preferably, the chair or seat is lowered to provide more stability. Lowering the chair or seat according to the invention also provides better access to ground level activities, while increasing the height of the chair or seat provides better access to off the ground activities, such as easy access to table tops and counters. In a preferred aspect of the invention, the chair or seat is lowered by moving it generally forward relative to the front of the unit or the front of the chair, preferably by pivoting the seat such that it is lowered as it moves forward. In a different aspect, the chair or seat is lowered by moving it generally back away from the front of the unit or relative to the front of the chair, preferably by pivoting the seat such that it is lowered as it moves back. In another aspect, the seat or chair is lowered by moving it down with little or no general movement forward or backward relative to the base of the unit.

In a preferred embodiment of the invention, both the chair/seat adjustment and the footprint size adjustment may be operated simultaneously or separately. Preferably, the chair/seat is lowered and the size of the footprint is increased and this operation provides the unit with more stability during operation. In one aspect, the seat/chair is lowered by moving it forward relative to the base or relative to the front of the chair, and the front of the base (or one or more wheels of the base configuration) is extended. In another aspect, the seat/chair is lowered by moving it back relative to the base or relative to the front of the chair, and the back of the base (or one or more wheels of the base configuration) is extended. In a different aspect, the chair may be lowered backwards while the front of the base (or one or more wheels of the base configuration) is extended. In a related aspect, the chair may be lowered by moving it forward while the back of the base

(or one or more wheels of the base configuration) is extended. As will be apparent, one or multiple parts of the base (or one or more wheels of the base) may be extended as the chair/seat is adjusted.

BRIEF DESCRIPTION OF THE DRAWINGS/FIGURES

The advantages and features of the present invention will become better understood with reference to the following more detailed description and claims taken in conjunction with the accompanying drawings, in which like elements are identified with like symbols, and in which:

FIG. 1 is a pictorial view of one embodiment of the wheelchair or device of the invention in which the wheelchair is in the uppermost position, with the leg protection cover on the footrest member and the component cover on the main frame, both of which are removed on all other drawings to better show operation.

FIG. 2 is another pictorial view of one embodiment of the wheelchair or device of the invention in which the wheelchair is in the uppermost position.

FIG. 3 is a pictorial view of one embodiment of the wheelchair or device of the invention in which the wheelchair is in the lowest position.

FIG. 4 is a schematic representation of one embodiment of the wheelchair or device of the invention showing the operating mechanisms with the wheelchair in the uppermost position.

FIG. 5 is a schematic representation of one embodiment of the wheelchair or device of the invention showing the operating mechanisms with the wheelchair in the lowest position.

FIG. 6 is a pictorial view of one embodiment of the wheelchair or device of the invention showing the telescopic device operably secured to the main frame.

FIG. 7 is a pictorial view of one embodiment of the wheelchair or device of the invention showing the front portion of the base.

FIG. 8 is a partial section and view of a telescopic device of the device or wheelchair of the invention which when operated allows the footprint of the device or wheelchair to be increased (when extended) or decreased (when retracted).

FIG. 9 is a partial section and rearward view of the telescopic device and the motor connected by a drive belt or chain for operation of the telescopic device.

FIG. 10 is a pictorial view of the seat member or seat support which when operated pivots forward or backward to allow it to move up or down.

FIG. 11 is a partial section and view of the forward connection of the seat member or seat support showing various pivot points allowing movement of the support up or down.

FIG. 12 is a partial section and view of the rearward connection of the seat member or seat support showing one pivot point allowing movement of the support up or down.

FIG. 13 is a pictorial view of one embodiment of the operating mechanism showing the motor, the extender(s) (or telescopic device), the seat support and the base adjuster.

FIG. 14 is a partial section and rearward view of an optional lifting assist device connected to the main frame (or platform) and a seat member or seat support.

FIG. 15 is a partial section and view of the extension structure and footrest and leg rest pivotally connected by a swing arm support.

FIG. 16 is a partial section and view of the footrest/leg rest member connected to a seat member or seat support by a slide mount enabling the footrest/leg rest to be adjusted.

5

FIG. 17 is a pictorial view of the tray embodiment to contain various components for the unit or wheelchair of the invention, including one or more batteries and/or one or more circuit boards.

FIG. 18 is a pictorial view of another embodiment of the wheelchair in an upright position, in this embodiment a linear actuator is used to extend or retract the device.

FIG. 19 is a side view of another embodiment of the wheelchair in an upright position, in this embodiment a linear actuator is used to extend or retract the device.

FIG. 20 is a pictorial view of another embodiment of the wheelchair in a lowered position, in this embodiment a linear actuator is used to extend or retract the device.

FIG. 21 is a side view of another embodiment of the wheelchair in a lowered position, in this embodiment a linear actuator is used to extend or retract the device.

DETAILED DESCRIPTION OF THE INVENTION

The present invention relates in general to a wheelchair, a mobile unit, a vehicle, or another similar mobile device which provides stabilized transportation for one or more passengers. In one aspect of the invention, the height of the seat member may be adjusted preferably to raise or lower the user's position, and in a preferred aspect, the height of the seat member is lowered to provide more stable transportation for the user of the invention by lowering the center of gravity closer to the operating surface. In another aspect, the wheelchair, mobile unit, vehicle, or mobile device may be adjusted to increase or decrease the size of its footprint (or any part of the footprint), and in a preferred aspect, the footprint is enlarged to provide more stable transportation for the user of the invention. Both the height of the seat member and the size of the footprint (or any part of the footprint) may be adjusted to provide more stability.

Preferred embodiments of the present invention are now described. While specific configurations and arrangements are discussed, it should be understood that this is done for illustrative purposes only. A person skilled in the relevant art will recognize that other configurations and arrangements can be used without departing from the spirit and scope of the invention. It will also be apparent to a person skilled in the relevant art that this invention can be employed in a variety of other devices and applications. While specific examples described may refer to a wheelchair, the invention may equally apply to any mobile unit, vehicle, or any other mobile device.

As depicted in FIGS. 1-5, wheelchair 2 of the present invention is basically comprised of base assembly 15 (further comprising extension structure 8 and main frame 4), seat assembly 13, and leg support assembly 17.

Base assembly 15 provides the base structural support for wheelchair 2. Base assembly 15 is comprised of extension structure 8 and main frame 4. In operation, a user can control extension structure 8 to extend away from or move toward main frame 4, increasing or decreasing the size of the footprint of wheelchair 2. As the footprint increases, the stability of wheelchair 2 increases, as the footprint decreases, the maneuverability of wheelchair 2 increases. By varying the footprint, a user can achieve the optimum balance of maneuverability and stability for a given situation. The components of base assembly 15 may be prepared of any material such as metal, plastic, wood and the like or combinations thereof, and can be designed in various configurations such as a frame, a solid platform and the like or combinations thereof. Preferably, base assembly 15 is made of aluminum, or other suitable durable, lightweight metal, such as chrome molly.

6

Extension structure 8 may be extended or retracted by utilizing telescopic devices 12, depicted in FIG. 6. Telescopic devices 12 allow part of the frame to extend or retract to increase or decrease the size of the footprint of the wheelchair or unit. Telescopic devices 12 may be extension/retraction tracks and/or extension/retraction rods and/or extenders that allow extension structure 8 to move away from or toward main frame 4 in such a manner to allow the overall footprint size of the base to increase or decrease. Extension structure 8 is secured operable to the main frame 4 by telescopic devices 12. Preferably extension structure 8 is made of the same or similar material as main frame 4. FIG. 7 shows the front portion of the base (which may comprise one or more wheels) and this portion of the base may be extended or retracted based on adjustment of the extension device or telescopic device. Adjusting the front portion of the wheelchair allows the footprint of the base to be increased when extended or decrease when retracted. Main frame 4 and extension structure 8 are supported by two rear wheel assemblies 9 and two front wheel assemblies 11, respectively. The substantially rectangular shape formed between the four wheel assemblies provides for a much more stable structure than would a triangular shape formed between three wheel assemblies. In yet another aspect, the base or platform comprises a plurality of wheel assemblies 9, 11 wherein wheel assemblies 9, 11 may be designed (including various shapes, sizes and/or tread configurations) to accommodate any terrain. In the embodiment shown in the figures, front wheel assemblies 11 and rear wheel assemblies 9 are utilized, but the invention may utilize any number of wheel assemblies, including at least two, at least three, at least four, at least five, at least six, at least seven, at least eight or more wheel assemblies, depending on the need. In another aspect, the size of the footprint of the base may be increased or decreased by extending or retracting one or more wheel assemblies 9, 11 which may be included as part of the base or platform configuration. For example, one or more wheel assemblies 9, 11 may be extended or retracted, for example, by utilizing one or more telescopic devices 12 that allow at least one wheel assembly 9, 11 to separate and move away from or toward the base or platform in such a manner to allow the overall footprint size of the base or platform to increase or decrease.

Outer guide housings 14 of telescopic devices 12 are secured to main frame 8, and slide sections 16 of telescopic devices 12 are secured to extension structure 8. In addition to, or in place of telescopic devices 12, any other extending/retracting device or devices that are mechanical, electrical, pneumatic or hydraulic could be used, for example a screw cylinder, linear actuator, or total hydraulic system can be used to drive the extending/retracting device or devices. In one embodiment, depicted in FIGS. 6 and 8, slide section 16 moves through bearing(s) 18. Suitable bearings include a flanged or sleeve type journal bearing, a brushing, a fluid bearing, Rulon, Orlite, Frelon or other type linear bearings that give adequate support while substantially reducing sliding friction. Threaded shaft 20, similar to a jackscrew, is secured operable to outer guide housing 14 as by angular contact bearings 22 or other type thrust bearings. Female threaded member 24, which can be, for example, a nut, is secured to slide section 16 and adapted to move along threaded shaft 20 as that member rotates. A lubricant, such as grease, may be used on the threaded shaft to reduce friction. As shown in FIG. 9, motor 26, secured to main frame 4, transmits torque to gears 28 on threaded shafts 20 of telescopic devices 12 through gear 30 on motor shaft 32, via a belt, gear train, or chain 34. As threaded shaft 20 rotates, female threaded member 24 and slide section 16 move exten-

sion structure **8** away from or draw extension structure **8** to main frame **4**. Adjustable motor brackets **35** achieve chain tension.

In another embodiment (not shown), motor **26** drives a worm gear, which in turn meshes with and drives the rotational motion of a pinion gear. The pinion gear in turn meshes with and drives the translational motion of a rack, as in a typical rack and pinion mechanism. The rack is secured to extension structure **8**, and the translational motion of the rack moves extension structure **8** away from or draws extension structure **8** to main frame **4**. Other mechanisms may also be used to translate power from motor **26** to telescopic devices **12**.

In another embodiment, as discussed below with respect to FIGS. **18-21**, the motion of extension structure **8** is controlled by a mechanism in which slide tubes controlled by a linear actuator replace the threaded shaft and female threaded member above. The slide tubes are connected at one end to main frame **4**, and at the other end to extension structure **8**. Activation of the linear actuator causes slide tubes to extend or retract, which moves extension structure **8** away from or toward main frame **4**, respectively.

At least one seat may be attached to the seat member or seat support in such a manner that when operated, the seat is raised or lowered based on movement of the seat member or support. Components of seat assembly **13** connect to both extension structure **8** and main frame **4**. Seat assembly **13** comprises at least one seat member **6**, and in a preferred aspect, seat member **6** may be adjusted to provide more comfort and/or stability for the user. In a preferred aspect, seat member **6** may be adjusted up or down relative to the base or platform. Preferably, seat member **6** is lowered to provide more stability. Lowering seat member **6** according to the invention also provides better access to ground level activities and is more stable, which is useful for outdoor use, where the terrain may be more uneven and unpredictable, while increasing the height of seat member **6** provides better access to off the ground activities, such as easy access to table tops and counters and is more maneuverable, which is useful for indoor use, where turning tight corners and fitting through narrow doorways is a concern. In this manner, the single wheelchair can be used for a variety of activities, providing the user with a greater range of motion, and can operate both indoors and outdoors. In a preferred aspect of the invention, seat member **6** is lowered by moving it in the direction of the front of the unit or generally forward relative to the base or platform, preferably by pivoting seat member **6** such that it is lowered as it moves forward. In a different aspect, seat member **6** is lowered by moving it generally back relative to base or platform, preferably by pivoting seat member **6** such that it is lowered as it moves back. In another aspect, seat member **6** is lowered by moving it down with little or no general movement forward or backward relative to the base or platform.

Seat assembly **13**, depicted in FIG. **10**, which in operation lowers or raises seat member **6** as described above, is a rigid, yet operable framework. Much of this framework is made up of preferably aluminum tube stock or other suitable durable, lightweight metal such as chrome molly, but can also be steel, fiber, wood, plastic, metal, any other material with suitable functional qualities, or any combination thereof. Seat member sides **36** are secured to and conjoined by axle rods **38** and **40**, as shown in FIGS. **11** and **12**. At least one seat member **6** may be attached to seat member sides **36**. Seat member links **42** and **44** are pivotally secured to axle rod **38** and maintained in a uniform manner by spacers **46** and **48**, depicted in FIG. **11**. Seat member links **50** are pivotally secured to axle rod **40** and maintained in a uniform manner by spacer **52**, depicted in

FIG. **12**. Seat member **6** is coupled to telescopic devices **12** and extension structure **8** by seat member links **42**, **44** and **50**, depicted in FIG. **13**. Seat member links **44** and **50** are pivotally secured to outer housing guides **14** of telescopic devices **12** by four connecting pins **56**, which can be pins, bolts, rivets, radial bearings, or any other suitable connection mechanism, best depicted in FIG. **6**. Seat member links **42** are pivotally secured to a pin block **54** on extension structure **8**, depicted in FIG. **7**. Connecting pins **56** on outer housing guides **14** of telescopic devices **12** and pin block **54** on extension structure **8** are anodized to prevent wear. Pivotal connections **58** of seat member links **42**, **44** and **50** contain brass bushings **60**, or other type bushings or bearings, and bushings **62**, made of an engineering plastic, such as that available from DuPont under the tradename DELRIN, or other type bushings or bearings are placed at the sides of pivotal connections **58** to prevent binding and galling when the seat is raised or lowered.

Due in part to the formation of seat assembly **13** and the pivotal connections of seat assembly **13** to extension structure **8** and main frame **4** (through the pivotal connections on telescopic devices **12**), as base assembly **15** operates to move extension structure **8** away from or toward main frame **4**, this motion drives a transition in seat assembly **13** which causes seat member **6** to move forward and down or backward and up, while maintaining a horizontal surface. In this manner, the footprint size may increase or decrease simultaneously, or otherwise in synchronization, as seat member **6** raises and lowers. As shown in FIG. **13**, by operation of the motor, the extenders may be extended or retracted and such extenders are operably linked to the seat support and the front of the base (the wheel configuration of the base). As the extenders are extended or lengthened, the seat support pivots in such a manner as to allow the seat support to move forward so that the support is lowered. The lengthening of the extenders also allows the base front (the wheel configuration of the base) to be extended thus increasing the footprint of the base. This operation will be explained in greater detail below.

Due to an occupant's bodyweight, when seat member **6** is in a lower position, a large amount of torque is needed from motor **26**, and deflection problems of seat member links **42**, **44** and **50** may occur when lifting seat member **6**. In FIG. **14**, a gas spring cylinder **64** or cylinders is used to assist lifting. Gas spring cylinder **64** may also be a torsion spring. Gas spring cylinders **64** could also be a spring mechanism, a hydraulic mechanism, or any other suitable lifting mechanism. Gas spring cylinder **64** provides additional force to assist seat member links **50** (occupied or not occupied by a user) to move up, thus raising seat member **6**. One or more gas spring cylinders **64** may be used according to the invention depending on the need. Gas spring cylinders **64** are pivotally secured to main frame **4** and to swing arms **66** pivotally secured to seat member links **50**.

Depicted in FIG. **15**, leg support assembly **17** is comprised of leg rest member **10**, swing arms **68**, spacers **70**, and protection cover **82**. Alternatively, leg rest member **10** can be a bent-tube type leg rest. Leg rest member **10** is pivotally secured to extension structure **8** by swing arms **68** and pins **74** connected to slide blocks **76**. A spacer **70**, made of an engineering plastic, such as that available from DuPont under the tradename DELRIN, is used on the sides of pivotal connections **72** of swing arms **68** to prevent seizing and galling. Pins **74**, best depicted in FIG. **16**, are securely attached to slide blocks **76** on seat member links **42** and travel through parallel slots **78** on leg rest member **10**. Washers **80**, made of an engineering plastic, such as that available from DuPont under the tradename DELRIN, are used on the front and rear of parallel slots **78** of footrest member **10** to prevent binding and

galling. Protection cover **82** is secured to footrest member, depicted in FIG. 1, over parallel slots **78** and pins **74** on slide block **76**, to prevent injury to the occupant's legs. As the front portion of the unit extends, the footrest/leg rest pivots preferably in a flat or horizontal position or substantially flat or substantially horizontal position. In addition to, or in place of swing arms **68** and slide blocks **76**, any other extending/retracting device or devices that are mechanical, electrical, pneumatic or hydraulic could be used, for example a screw cylinder, linear actuator, or hydraulic system can be used to drive the extending/retracting and pivoting motions of leg rest member **10**. In operation, which is discussed in greater detail below, leg support assembly **17** protects and guides a user's legs throughout motion of wheelchair **2**, in such a way as to maintain comfort and facilitate independent operation by the user, without assistance from others.

In another embodiment, the position of leg rest member **10** is controlled by a linear actuator between seat **6** and leg rest member **10**. A linear bearing and rod are attached to each of seat member links **42**. In this embodiment, due to the force of the linear bearing and rod throughout the transition, leg rest member **10** extends and pivots to allow a user's legs to lay flat as seat **6** changes from an upper position to a lower position, and leg rest member retracts and pivots to allow a user's legs to bend at the knee as seat **6** changes from a lower position to an upper position. As shown in FIGS. 18-21, extension structure **8** extends from main frame **4** driven by linear actuator **19**. Linear actuator **19** is pivotally connected at one end to seat member link **42**, and pivotally connected at the opposite end to main frame **4**. In this embodiment seat member link **42** is forced away from or toward main frame **4** by the linear motion of linear actuator **19**. As seat member link **42** moves, it pivots at the point of connection with linear actuator **19**, and in a fully extended state, seat member link **42** lays over linear actuator **19** to provide additional stability. Actuator support member **21** is attached to main frame **4**, and is shaped to accommodate linear actuator **19** axially. When linear actuator **19** extends it pivots at the point of connection with main frame **4** and lays itself into the recess in actuator support member **21**, providing additional support and stability for wheelchair **2**. Extension support members **23** are attached to extension structure **8** at one end, and main frame **4** at the opposite end. During the extension/retraction of linear actuator **19**, extension support members **23** extend or retract accordingly, in order to provide support on each side of wheelchair **2**.

In one embodiment, the relative movement of the base (or one or more wheel assemblies **9**, **11** as part of the base configuration) and the lowering of seat member **6** allows the center of gravity of the user/unit combination to be lowered and thus provides more stability for the operation of wheelchair **2** by the user. In one aspect, the combination of lowering the seat and increasing the size of the footprint allows the user to sit in a relatively flat position. Preferably the operation of the invention allows the legs of the user to be extended (preferably the legs being flat or substantially flat). Leg rest member **10** supports the legs and feet of the user throughout the transitions of wheelchair **2**. Leg rest member **10** is shaped in such a way so as to retain and guide the legs of the user through the transitions, which is a key feature especially for an individual without internal control of his or her legs, such as a paralyzed individual. This feature of the invention allows the user's legs to extend in such a manner as to provide comfort to the user and/or increase blood circulation in the user's legs. It assists in transitioning the position of the user's body without requiring him or her to leave wheelchair **2**.

Since electrical components are used in the present application, battery or batteries tray **84** and circuit board tray **86**,

depicted in FIG. 17 are secured to main frame **4**. Batteries tray **84** and circuit board tray **86** may be removable for service and repair, and may be replaceable. In FIG. 1, cover **88** is secured to main frame **4** to protect the occupant from pinch points when seat is being raised or lowered and the electrical components from the environment.

In preferred embodiments of the invention, both the seat adjustment and the footprint size adjustment may be operated simultaneously or separately. Preferably, seat member **6** is lowered as the size of the footprint is increased and this operation provides the unit with more stability during operation. In one aspect, seat member **6** is lowered by moving it forward relative to the base, and the front of the base, extension structure **8**, is extended. In another aspect (not shown), seat member **6** is lowered by moving it back relative to the base, and the back of the base (or one or more wheel assemblies **9** of the base configuration) is extended. In a different aspect (not shown), the chair may be lowered backwards while the front of the base, extension structure **8**, (or one or more wheel assemblies **11** of the base configuration) is extended. In a related aspect (not shown), seat member **6** may be lowered by moving it forward while the back of the base (or one or more wheel assemblies **9** of the base configuration) is extended. As will be apparent, one or multiple parts of the base (or one or more wheel assemblies **9**, **11** of the base) may be extended as seat member **6** is adjusted.

Operationally, wheelchair **2** components are able to move relative to one another in order to change the size and shape of the footprint of wheelchair **2**, as well as change the height of seat member **6** relative to a surface on which wheelchair **2** is operating. In combination these functions allow an operator to use wheelchair **2** while sitting upright, or while reclining, and to change between these positions.

For explanatory purposes, the fully upright formation of wheelchair **2** (depicted in FIGS. 1, 2, and 4) is referred to as Position A, while the fully reclined formation of wheelchair **2** (depicted in FIGS. 3 and 5) is referred to as Position B. Also for explanatory purposes it is assumed that wheelchair **2** begins in Position A.

In Position A, seat member links **42** are substantially vertical, while seat member links **44** form an acute angle with seat member links **44**. Seat member links **50** remain substantially parallel with seat member links **44**, forming a four-bar mechanism with seat member sides **36** as the connecting link. A user in wheelchair **2** while it was in Position A would be sitting upright, legs resting within leg rest member **10**, bent at the knees, for example, at an angle approximating 90 degrees, such as at an angle within 20 degrees of 90 degrees (e.g. 70, 80, 90, 100 or 110 degrees).

Upon activation of motor **26**, motor **26** drives rotation of threaded shaft **20**. As threaded shaft **20** rotates, female threaded member **24** is forced along threaded shaft **20**, in an axial direction moving away from motor **26**. The axial motion of female threaded member **24** drives slide section **16** and extension structure **8** away from main frame **4**, increasing the footprint of wheelchair **2** as it does so. Wheel assemblies **11** move with and support extension structure **8** during this transition. Seat member links **42** are pivotally attached a pin block **54** on extension structure **8**.

As extension structure **8** moves away from main frame **4**, the angle between seat member links **42** and seat member links **44** increases, as does the distance between pin block **8** and main frame **4**. This motion draws seat member links **44** and **50** to rotate forward, about fixed pivot points at connecting pins **56**. This rotation forces seat member sides **36** forward and down, while remaining substantially horizontal, ensuring that the operator, who is seated on seat member **6** which

11

bridges seat member links **36**, will remain safely and comfortably in place while seat member **6** is lowered.

While seat **6** transitions in this manner, leg support assembly **17** extends away from seat member **6** and pivots along with the user's legs at the knee, as the user's legs extend, increasing the angle between the lower leg and upper leg, as that angle approaches 180 degrees. Throughout the transition, swing arm **68**, pins **74** and slide blocks **76** maintain support for and control of the user's legs, ensuring that the transition occurs ergonomically, comfortably and safely for the user.

Once extension structure **8** is fully extended, wheelchair **2** is in Position B, as depicted in FIG. **3**. In this position, the front of the device (including the front wheels) is moved forward and the seat is lowered (preferably the seat pivots forward as it is lowered). In a preferred aspect, the distance between the footrest and the seat in the down position is such that the legs of a user will lay flat to provide for better blood circulation. In position B, because leg rest member **10** travels away from main frame **4** with extension structure **8**, a user's legs are fully extended, for example, the angle between the upper and lower legs in this position may be substantially 180 degrees, such as within 20 degrees of 170 degrees (e.g. 150, 160, 170 or 180 degrees), and the user is in a seated-reclined position. In position B seat member **6** is at its lowest, and the footprint is at its largest. The two wheel assemblies **11** are fully extended at their farthest distance from the two wheel assemblies **9**, resulting in maximum stability. In a preferred aspect, the distance between the footrest and the seat in the down position is such that the legs of a user will lay flat to provide for better blood circulation. In Position B, seat member links **42**, **44**, and **50** are nearly horizontal, however they retain a sufficient angle from horizontal so as to facilitate the transition from Position B to Position A by way of the driving horizontal force of extension structure **8**, to help prevent deflection or binding of the structure. Additionally, gas spring cylinders **64** assist in returning seat member links **42**, **44**, and **50** to Position A, by introducing a force along the body of seat member links **50**. In so doing, gas spring cylinders **64** also decrease the amount of torque that must be supplied by motor **26** in order to initially draw extension structure **8** toward itself.

While in Position B wheelchair **2** of the preferred embodiment is in its most stable position. By rotating seat assembly **13** forward and down, and at the same time extending extension structure **8** forward, the result is to place the center of gravity centrally between wheel assemblies **9** and **11**, as well as to lower the center of gravity toward the operating surface or ground.

When it is desired to transition from Position B to Position A, wheelchair **2** is operated such that threaded shaft **20** rotates in the opposite direction as when transitioning from Position A to Position B. This causes female threaded member **24** to travel back along threaded shaft **20** axially toward motor **26**, which draws extension structure **8** toward main frame **4**, and drives a reversal of the above-described motions of seat member links **42**, **44**, and **50**, so that the angle between seat member links **42** and **44** decreases, and seat member links **44** and **50** rotate backward about connecting pins **56**, until all components have returned to the initial state of Position A.

Throughout this cycle, seat member sides **36** remain substantially horizontal, allowing a user to transition from Position A to Position B and back again while remaining seated on seat member **6**. Additionally, either transition (from Position A to Position B or from Position B to Position A) can be interrupted at an intermediate position and either reversed or held at that position if the user desires to use wheelchair **2** in such a formation.

12

Also throughout this cycle, the user is retained within the confines of wheelchair **2** in part by armrests **5** and leg rest member **10**. This is particularly important for a user who may have diminished control of his or her body. He or she may desire to change positions for any reason, including comfort, functionality, or for medical reasons, as discussed above. Armrests **5** will help to retain the torso and upper body of the user in place, while leg rest member **10** will help to retain the legs and lower body of the user in place. The particularized guidance that leg rest member **10** provides for the user's legs throughout this cycle is of pivotal importance, as it plays a significant part in the autonomy of the device, and allows the user to control the position of his or her legs through external means by activating the mechanisms of wheelchair **2**, when that user may not be able to control the position of his or her legs on his or her own. Because of the potential for injury while moving, leg rest member **10** is shaped such that it will protect the legs, and additionally provides for protection cover **82** to further prevent injury.

Also throughout the cycle, battery or batteries tray **84** and circuit board tray **86** remain in a fixed position relative to main frame **4**. This results in increased stability and operative simplicity as opposed to a system where battery or batteries tray **84** and/or circuit board tray **86** would be required to change position in order to accommodate the motion of the mechanisms during a transition.

At Position A or Position B, or any point while fixed or in transition in therebetween, the wheelchair **2** may be operated to travel in either a substantially forward or reverse direction by way of the drive wheels, which are preferably rear wheel assemblies **9**. Rear wheel drive provides greater stability and control. Wheelchair **2** may be powered or moved manually by an individual or user or may be motorized by one or more driving motors (not shown). Such motors may be electric and/or combustion motors or combinations thereof. In yet another aspect, any one or a number of wheel assemblies **9**, **11** of the device may be powered by such one or more driving motors and preferably the unit of the invention is a multi-wheel drive unit, wherein a number or all of wheel assemblies **9**, **11** of the unit are driven by one or more driving motors. Preferably, the device of the invention comprises four (4) wheel assemblies **9**, **11** and preferably at least two of such wheel assemblies **9**, **11** (and preferably all four) are capable of being driven by one or more driving motors. In another embodiment, one or more motors **26** of the invention are utilized to raise and/or lower all or any part of the unit. In another aspect, one or more motors **26** are utilized to increase and/or decrease the size of the footprint of the unit (or any part of the unit). In another embodiment, the same or different motors may be used to operate all or any number of the functions of the unit, and in a preferred aspect one motor **26** is utilized to move the device, to increase and/or decrease the size of the footprint (or any part of the footprint) and to raise and/or lower all or any part of the unit.

In utilizing wheelchair **2**, the different functions of the device may be operated separately or simultaneously depending on the need of the user. When one or more motors provide operation of any or all of the features of the unit, the unit may also comprise one or more control devices **7** allowing the user to control and operate the different features of the invention. For example, one or more control devices **7** may be used to move wheelchair **2**, adjust the size of the footprint, and/or adjust the height of the unit and/or adjust the center of gravity.

The present invention provides a number of advantages. In one aspect, the invention prevents the unit from tipping over during use on different types of terrain and in general the invention allows the user to perform a wider range of activi-

ties and provides a means by which a user can access a variety of places, some of which may have been previously difficult to reach. The invention also provides more comfort to the user and importantly may address medical concerns for certain individuals by for example allowing better circulation in lower extremities and preventing stiffness. The device decreases the amount of assistance from others that the user will need by allowing the user to autonomously change positions and thus prevent stiffness, and improve circulation, as well as improve the quality of life of the user by allowing him or her to operate more independently.

It is to be appreciated that the Detailed Description section, and not the Summary and Abstract sections, is intended to be used to interpret the claims. The Summary and Abstract sections may set forth one or more but not all exemplary embodiments of the present invention as contemplated by the inventor(s), and thus, are not intended to limit the present invention and the appended claims in any way.

The present invention has been described above with the aid of functional building blocks illustrating the implementation of specified functions and relationships thereof. The boundaries of these functional building blocks have been arbitrarily defined herein for the convenience of the description. Alternate boundaries can be defined so long as the specified functions and relationships thereof are appropriately performed.

The foregoing description of the specific embodiments will so fully reveal the general nature of the invention that others can, by applying knowledge within the skill of the art, readily modify and/or adapt for various applications such specific embodiments, without undue experimentation, without departing from the general concept of the present invention. Therefore, such adaptations and modifications are intended to be within the meaning and range of equivalents of the disclosed embodiments, based on the teaching and guidance presented herein. It is to be understood that the phraseology or terminology herein is for the purpose of description and not of limitation, such that the terminology or phraseology of the present specification is to be interpreted by the skilled artisan in light of the teachings and guidance.

The breadth and scope of the present invention should not be limited by any of the above-described exemplary embodiments, but should be defined only in accordance with the following claims and their equivalents.

What is claimed is:

1. A wheelchair comprising a plurality of wheels, a base, a seat member, and a leg support assembly, the base comprising a main frame and an extendable member, the extendable member being configured to extend and retract in relation to the main frame, the main frame comprising at least two wheels, the extendable member comprising at least two wheels, the leg support assembly being pivotably connected to the extendable member, the length of the base being configured to be increased by extending the member from the main frame and decreased by retracting the member into the main frame, the main frame and extendable member being configured such that the distance between the at least two wheels of the main frame and the at least two wheels of the extended member increases or decreases as the extendable member respectively extends and retracts, the height of the seat member being configured to be increased or decreased, and the leg support assembly being configured to pivot along with a user's legs at the knees as the leg support assembly extends away from the seat member and the user's legs extend.

2. The wheelchair of claim 1, wherein the extendable member is operably connected to at least one extender device.

3. The wheelchair of claim 2, wherein the base is lengthened when the at least one extender device is extended.

4. The wheelchair of claim 2, wherein the seat member is operably connected to at least one extender device.

5. The wheelchair of claim 4, wherein the seat member is configured to be lowered when the at least one extender device is extended.

6. The wheelchair of claim 1, wherein the wheelchair further comprises at least one motor operably connected to the main frame.

7. The wheelchair of claim 6, wherein the motor is configured to adjust the length of the base, the height of the seat member, or both.

* * * * *