



US008136151B2

(12) **United States Patent**  
**Smith et al.**

(10) **Patent No.:** **US 8,136,151 B2**  
(45) **Date of Patent:** **Mar. 13, 2012**

(54) **SYSTEMS AND METHODS FOR REMOTELY MAINTAINING VIRTUAL PRIVATE NETWORKS**

(75) Inventors: **Robert Douglas Smith**, Mainz (DE);  
**Olaf Alexander Wobst**, Mainz (DE)

(73) Assignee: **Anxebusiness Corp.**

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 283 days.

6,366,563	B1	4/2002	Weldon et al.
6,701,358	B1	3/2004	Poisson et al.
6,765,591	B2	7/2004	Poisson et al.
7,373,661	B2	5/2008	Smith
7,409,709	B2	8/2008	Smith
2003/0103615	A1	6/2003	Baltes
2003/0105839	A1	6/2003	Ben
2003/0140131	A1	7/2003	Chandrashekar et al.
2004/0083290	A1	4/2004	Chen et al.
2004/0158601	A1	8/2004	Wing et al.
2004/0224668	A1	11/2004	Shell et al.
2007/0199066	A1	8/2007	Smith

(Continued)

(21) Appl. No.: **11/778,064**

(22) Filed: **Jul. 15, 2007**

(65) **Prior Publication Data**

US 2008/0046996 A1 Feb. 21, 2008

**Related U.S. Application Data**

(62) Division of application No. 11/057,860, filed on Feb. 14, 2005, now Pat. No. 7,373,661.

(51) **Int. Cl.**  
**G06F 9/00** (2006.01)

(52) **U.S. Cl.** ..... **726/15; 713/1; 713/2; 709/229**

(58) **Field of Classification Search** ..... **726/15; 713/1, 2; 709/229**

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,751,967	A	5/1998	Raab et al.
6,012,088	A	1/2000	Li et al.
6,049,826	A	4/2000	Beser
6,070,246	A	5/2000	Beser
6,079,020	A	6/2000	Liu
6,092,200	A	7/2000	Muniyappa et al.
6,212,559	B1	4/2001	Bixler et al.
6,226,751	B1	5/2001	Arrow et al.
6,314,516	B1	11/2001	Cagle et al.

**OTHER PUBLICATIONS**

Response Filed Mar. 22, 2010 in Related U.S. Appl. No. 11/705,628 and courtesy Office Action of Sep. 24, 2009 (8 pages).

(Continued)


*Primary Examiner* — Jacob Lipman

(74) *Attorney, Agent, or Firm* — Flaster/Greenberg P.C.

(57) **ABSTRACT**

Systems and methods are disclosed for automatically configuring, managing, and maintaining a network device or VPN using a public network such as the Internet. Initial configuration of a network device or VPN occurs upon a user entering minimal information via a simple HTML page. After receipt of this minimal information, the present invention automatically configures the network device or VPN without user intervention. Thereafter, a user may modify the network device or VPN configuration via an easy-to-use and easy-to-understand graphical user interface. Parameters are presented such that a user simply checks and unchecks boxes, or clicks on radio buttons, to configure network device parameters. Upon completion of the selection, the user clicks on save, and the configuration is automatically modified. In addition, upon a significant change to any network device, the changed network device automatically initiates reconfiguration of the network device or VPN with zero input from a user.

**15 Claims, 19 Drawing Sheets**



# US 8,136,151 B2

Page 2

---

## U.S. PATENT DOCUMENTS

2007/0277226 A1 11/2007 Smith  
2008/0043640 A1 2/2008 Smith

## OTHER PUBLICATIONS

Notice of Allowance dated Dec. 14, 2009 in related U.S. Appl. No. 11/778,052 (7 pages).  
Office Action (outstanding) dated Jan. 14, 2010 from related U.S. Appl. No. 11/705,783 (6 pages).

Response Filed in Related U.S. Appl. No. 11/057,862 dated Jun. 14, 2007 and courtesy related Office Action and Advisory Action (23 pages).

Response Filed in Related U.S. Appl. No. 11/057,862 dated Dec. 17, 2007 and courtesy related Office Action, Advisory Action and Interview Summary (26 pages).

Response Filed in Related U.S. Appl. No. 11/057,862 resubmitted dated Jan. 22, 2008 after RCE (12 pages).

Notice of Allowance of Apr. 2008 and Comments After Allowance dated Jun. 2008 in Related U.S. Appl. No. 11/057,862 (11 pages).

FIG. 1




FIG. 2




FIG. 3





FIG. 4




**FIG. 5**500

FIG. 6

600






FIG. 7

700




FIG. 8

800





FIG. 9

900







FIG. 11




**FIG. 12**

FIG. 13

1300




FIG. 14

1400

The screenshot shows a web browser window with a title bar containing three window control buttons on the left and the text "You are logged on the Systems of: eli eli" on the right. The main content area is divided into two sections. On the left is a vertical sidebar menu with several expandable categories, each with a small upward-pointing arrow icon: "General", "Router", "Email", "Firewall", and "Parental Control". Each category contains a list of sub-items with checkboxes. Under "General", the items are "Start", "Logout", and "Profile". Under "Router", the items are "WLAN-Settings" and "VPN-Settings". Under "Email", the items are "Spam Protection" and "Virus Protection". Under "Firewall", the item is "System Policies". Under "Parental Control", the item is "URL filtering". The right section is titled "Profile" and contains the text "Here you can change your personal data." Below this text are two input fields: "New password:" followed by an empty text box, and "Retype new password:" followed by another empty text box. A "Save" button is positioned below the second input field.



FIG. 15

1500

You are logged on the Systems of: eli eli

**General** ^

- Start
- Logout
- Profile

**Router** ^

- WLAN-Settings
- VPN-Settings

**Email** ^

- Spam Protection
- Virus Protection

**Firewall** ^

- System Policies

**Parental Control** ^

- URL filtering

**WLAN Settings**

Here you can configure the WLAN-Settings of your eli-box.

**Activate Wireless Network**

ESSID:

ESSID

Broadcast:

Channel:

OFF (Deactivates encryption, not recommended)

WEP64 (chooses 64 bit WEP encryption)

HEX (chooses 128 bit WEP encryption)

WPA (chooses 256 bit WPA encryption)

Wep-Key:

FIG. 16

1600

The screenshot shows a web browser window with a title bar that reads "You are logged on the Systems of: eli eli". The interface is divided into a left sidebar and a main content area. The sidebar contains a list of settings categories: "General" (with sub-items: Start, Logout, Profile), "Router" (with sub-items: WLAN-Settings, VPN-Settings), "Email" (with sub-items: Spam Protection, Virus Protection), "Firewall" (with sub-item: System Policies), and "Parental Control" (with sub-item: URL filtering). The main content area is titled "Spam Protection" and contains the following text: "Here you can configure the SPAM filter, to eliminate unwanted, unsolicited commercial eMail-messages." Below this is a message box: "The SPAM protection rules have successfully been updated." A list of radio button options follows: "Off (Deactivates the SPAM filter)", "Mark (Inserts header that marks the message as SPAM)", "Drop (Automatically deletes the message)", "Bounce (Bounces the message back to the sender)", and "Forward (Forwards the message to the specified address)". The "Drop" option is selected. Below the list is an "eMail:" label followed by an empty text input field. At the bottom of the main content area is a "Save" button.

FIG. 17

1700




FIG. 18

1800

The screenshot shows a web browser window with a title bar containing three window control buttons on the left and the text "You are logged on the Systems of: eli eli" on the right. The main content area is divided into two sections. On the left is a sidebar with a tree view of settings categories: "General" (with sub-items "Start", "Logout", "Profile"), "Router" (with "WLAN-Settings", "VPN-Settings"), "Email" (with "Spam Protection", "Virus Protection"), "Firewall" (with "System Policies"), and "Parental Control" (with "URL filtering"). Each category has an expand/collapse arrow. The "System Policies" category is selected. The main content area is titled "System Policies" and contains the text "Here you can select the policy that reflects your security needs:". Below this text are five radio button options: "Simple Surfer" (selected), "Gamer", "Telecommuter", "Power User", and "All Outbound". A "Save" button is located below the radio buttons.

FIG. 19

1900

You are logged on the Systems of: eli eli

---

### URL Filtering Categories

Here you can select the URL categories, that you want blocked:

<input checked="" type="checkbox"/> Adult/Mature Content	<input type="checkbox"/> Cultural Institutions	<input type="checkbox"/> Religion
<input checked="" type="checkbox"/> Pornography	<input type="checkbox"/> Financial Services	<input type="checkbox"/> Shopping
<input checked="" type="checkbox"/> Sex Education	<input checked="" type="checkbox"/> Brokerage/Trading	<input type="checkbox"/> Auctions
<input checked="" type="checkbox"/> Intimate Apparel/Swimsuit	<input type="checkbox"/> Games	<input type="checkbox"/> Real Estate
<input checked="" type="checkbox"/> Nudity	<input type="checkbox"/> Government/Legal	<input checked="" type="checkbox"/> Society/Lifestyle
<input checked="" type="checkbox"/> Alcohol/Tobacco	<input checked="" type="checkbox"/> Military	<input checked="" type="checkbox"/> Gay/Lesbian
<input checked="" type="checkbox"/> Illegal/Questionable	<input checked="" type="checkbox"/> Political/Activist Groups	<input type="checkbox"/> Restaurants/Dining/Food
<input checked="" type="checkbox"/> Drugs	<input type="checkbox"/> Health	<input type="checkbox"/> Sports/Recreation/Hobbies
<input checked="" type="checkbox"/> Gambling	<input checked="" type="checkbox"/> Hacking/Proxy Avoidance	<input type="checkbox"/> Travel
<input checked="" type="checkbox"/> Hate/Racism	<input type="checkbox"/> Search Engines/Portals	<input type="checkbox"/> Vehicles
<input checked="" type="checkbox"/> Violence/Hate/Racism	<input type="checkbox"/> Web Page Hosting	<input type="checkbox"/> Humor/Jokes
<input checked="" type="checkbox"/> Weapons	<input type="checkbox"/> Web Communications	<input checked="" type="checkbox"/> Streaming Media/MP3
<input checked="" type="checkbox"/> Abortion	<input checked="" type="checkbox"/> Job Search/Careers	<input checked="" type="checkbox"/> Educational Cheating
<input checked="" type="checkbox"/> Activist/Advocacy Groups	<input type="checkbox"/> News/Media	<input type="checkbox"/> Software Downloads
<input type="checkbox"/> Arts/Entertainment	<input checked="" type="checkbox"/> Personals/Dating	<input checked="" type="checkbox"/> Pay to Surf
<input type="checkbox"/> Business/Economy	<input type="checkbox"/> Recreation and Hobbies	<input checked="" type="checkbox"/> Glamour
<input checked="" type="checkbox"/> Cult/Occult	<input type="checkbox"/> Reference	<input type="checkbox"/> For Kids
<input checked="" type="checkbox"/> Illegal Drugs	<input checked="" type="checkbox"/> Chat/Instant Messaging	<input checked="" type="checkbox"/> Web Advertisements
<input type="checkbox"/> Education	<input checked="" type="checkbox"/> Email	<input checked="" type="checkbox"/> Web Hosting
<input type="checkbox"/> Educational Institutions	<input checked="" type="checkbox"/> Newsgroups	<input checked="" type="checkbox"/> Unrated

Select/Deselect all categories

- General ^
- Start
- Logout
- Profile
- Router ^
- WLAN-Settings
- VPN-Settings
- Email ^
- Spam Protection
- Virus Protection
- Firewall ^
- System Policies
- Parental Control ^
- URL filtering

**SYSTEMS AND METHODS FOR REMOTELY  
MAINTAINING VIRTUAL PRIVATE  
NETWORKS**

CROSS-REFERENCE TO RELATED  
APPLICATIONS

This application is a divisional of application Ser. No. 11/057,860, filed Feb. 14, 2005, now U.S. Pat. No. 7,373,661 entitled Systems and Methods for Automatically Configuring and Managing Network Devices and Virtual Private Networks, the entire disclosure of which is incorporated herein by reference.

COPYRIGHT NOTICE

A portion of the disclosure of this patent document contains material which is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the Patent and Trademark Office patent file or records, but otherwise reserves all copyright whatsoever.

BACKGROUND OF THE INVENTION

Embodiments of the present invention relate to the field of network devices. More specifically, the present invention relates to systems and methods for automatically configuring and managing network devices such as broadband routers and virtual private networks.

Many systems and methods have been created to provide communication between individual computers of a centralized, single site organization through a private network. Computers may be interconnected through telephone lines, coaxial cables, optical fibers, radio or microwave communication links, earth-orbiting satellites, or other means. Such communications can include electronic mail, file sharing and transferring, and database sharing.

The most commonly used network is the local area network ("LAN"). LANs consist of interconnected computers that provide different functions such as a host or server. A host computer sends and receives information of the network in forms of packets of data. A server distributes the data to network users along with the host computer. These computers are interconnected through the use of bridges, switches, routers, and gateways. A bridge is a device that is connected to at least two LANs and transmits data between the LANs. A router provides similar services, but also determines the optimum path for the data by using network identifiers. LANs provide a high level of security when they are properly managed and configured since all information transfer occurs within a single site.

Other systems have been created to provide communication between several single site organizations. For example, this may be performed using a wide area network ("WAN"). WANs interconnect offices or various organizational sites via private communication connections such as leased lines. WANs are virtually identically to LANs with the exception of the spatially extended interconnections. Although these systems can be expensive due to the lease cost of the leased lines and the additional administrative cost of managing a network encompassing a large geographic area, they also provide an adequate amount of security when they are properly managed.

In recent years, technical advancement and declining prices have made it commonplace for workplaces to provide

Internet access via a local Internet Service Provider ("ISP") to some or all of their employees. Besides providing a vast amount of informational resources, the Internet provides electronic communication to any computer also connected to the Internet. This innovation provides a relatively easy method for members of an organization to communicate with members of their organization who are traveling, working from home, or are located at other geographic locations. However, a large disadvantage of using the Internet for communications is accessibility of the Internet to the general public. Since the exact route of the data is indeterminable, an Internet user risks eavesdropping and information theft. An even greater risk is that communications can be intercepted and altered before reaching their intended recipient. Due to these risks, many organizations are unwilling to expose their associates' and employees' communications to public network space such as the Internet.

With these security issues in mind, many systems and methods have been created to provide more secure communication between private computer networks over a public network such as institutional intranets and the Internet. One of the first systems to arise was the VPN. A VPN has the characteristics of a private network but provides connectivity via a shared public network infrastructure. VPNs include intranet VPNs, remote access VPNs, and extranet VPNs. A VPN incorporates access control, encryption technologies, and tunneling to achieve the security inherent in private networks while taking advantage of the infrastructure, economies of scale, and established management resources of public networks. However, a downfall of VPNs exists in large organizations in which the size of the VPN may cause maintenance of the VPN to become an increasingly complex task often causing extended time periods to perform necessary updates.

To alleviate the expense of maintaining a VPN, many third party service providers such as ISPs offer managed VPNs to organizations desiring complex VPNs having increased levels of communication security. Typically, the service provider has a network operations center that controls and maintains the VPN remotely and locally based on the requirements provided by the organization.

Increased levels of security may be obtained using a variety of methods. For example, cryptography systems may be employed to minimize theft of data by an unauthorized third party. Such systems encrypt transmitted data such that only the intended recipient's system can interpret the encryption. With these systems, unintended parties may receive the data, however, they are unable to interpret the encrypted data with their system.

Once such commonly employed cryptography system is public key cryptography. In public key cryptography, also known as asymmetric encryption, a public and a private key exist for each user in the communication network. The encryption key is a code or number that can only be read by its respective encryption algorithm. Two users communicate data only by knowing each other's public code. One user's public key, which is known to all users of the network and is generally accessible from one location, is decoded by the other user's private key, which is only known by the owner of the key. Since only the intended recipient has the private key, only that user can decode and access the data. In addition to the relationship defined by the users' keys, the sender encodes the data with its private key to indicate to the user that the sender is authentic.

Typically, the user's keys are generated and maintained by a certification authority. The user's private key is delivered to the user via electronic mail, regular mail, or a data storage

device such as a compact disc (“CD”). The user’s private keys are stored only (i.e., they cannot be downloaded), while the user’s public keys can be downloaded from the certification authority when needed by another sender. The certification authority generates “certificates” or signed messages that specify the name of the user as well as the user’s public key to verify the user’s identity.

Secure Sockets Layer (“SSL”) is a commonly employed security protocol that may be implemented in conjunction with a cryptography system such as public key cryptography. This protocol is widely used for transmission of sensitive data via the Internet, such as credit card data, to a vendor’s Internet web site. When an SSL session is initiated, the web site’s server sends a digital certificate to the user’s Internet browser (e.g., Internet Explorer®). The browser receives the digital certificate, which is used to authenticate the web site accessed by the user. The browser maintains an inventory of the certificates issued by public certificate authorities and is able to contact the respective authority to ensure that the received digital certificate has not been revoked. After verification that the digital certificate is valid, the user’s browser uses the public key received from the web site to encrypt a random number, which it transmits to the Web site. This random number may be used as sent or may be modified to create a secret session key for subsequent exchange of private information between the user’s system and the web site.

Another commonly used security protocol is IP Security Protocol (“IPsec”). IPsec was created by the Internet Engineering Task Force to provide authentication and encryption for data transmitted via the Internet. An advantage of IPsec in comparison to SSL is that IPsec provides services at layer three and secures all applications in the network unlike SSL, which provides services at layer four and only secures two applications. IPsec can access both Internet and non-Internet applications. Although IPsec provides a higher level of security, IPsec requires more maintenance. For example, IPsec requires an installation at the client (e.g., a user’s personal computer) whereas SSL is typically a component of a standard web browser.

#### BRIEF SUMMARY OF THE INVENTION

Briefly stated, in one aspect of the present invention, a method for remotely maintaining a VPN is provided. This method includes the steps of: transmitting maintenance data to at least one management device; creating at least one of the group consisting of a device configuration file, a VPN configuration file, and combinations thereof at the management device; automatically establishing a communication between the management device and at least one of the network devices via at least one network connection of at least one network; and transmitting at least one of the group consisting of the device configuration file, the VPN configuration file, and combinations thereof from the management device to the network device via the network connection; wherein at least one parameter of at least one of the network device, the VPN, and combinations thereof is automatically configured upon local processing of at least one of the group consisting of the device configuration file, the VPN configuration file, and combinations thereof.

#### BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

A further understanding of the present invention can be obtained by reference to the embodiments set forth in the illustrations of the accompanying drawings. Although the

illustrated embodiments are exemplary of systems for carrying out the present invention, both the organization and method of operation of the invention, in general, together with further objectives and advantages thereof, may be more easily understood by reference to the drawings and the following description. The drawings are not intended to limit the scope of this invention, which is set forth with particularity in the claims as appended or as subsequently amended, but merely to clarify and exemplify the invention.

FIG. 1 depicts a schematic view of a network environment in accordance with an embodiment of the present invention including, inter alia, a management center, management portal, firewall, master server, regional servers, the Internet, a router, network connections, network devices, local networks, and local network devices.

FIG. 2 depicts a schematic view of one embodiment of a VPN created using the systems and methods of the present invention including, inter alia, the Internet, a router, network connections, network devices, local networks, and local network devices.

FIG. 3 depicts a flowchart of the steps in one embodiment of a process for user configuration to initiate automatic creation of a VPN.

FIG. 4 depicts a flowchart of the steps in one embodiment of a process for automatic device configuration for the creation of a VPN.

FIG. 5 depicts a flowchart of the steps in one embodiment of a process for updating external network address changes within a VPN.

FIG. 6 depicts a GUI screen for initial creation of a VPN according to one embodiment of the present invention.

FIG. 7 depicts a GUI screen for addition of a second member of a VPN according to one embodiment of the present invention.

FIG. 8 depicts a GUI screen for editing or deleting a VPN according to one embodiment of the present invention.

FIG. 9 depicts a GUI screen for editing or deleting an existing VPN member according to one embodiment of the present invention.

FIG. 10 depicts a flowchart of the steps in one embodiment of a process for initial configuration of a network device according to one embodiment of the present invention.

FIG. 11 depicts a flowchart of the steps in one embodiment of a process for user configuration to initiate the automatic modification of a network device configuration.

FIG. 12 depicts a flowchart of the steps in one embodiment of a process for automatic modification of a network device configuration.

FIG. 13 depicts a GUI screen for the start menu for changing network device configurations according to one embodiment of the present invention.

FIG. 14 depicts a GUI screen for configuration of a profile according to one embodiment of the present invention.

FIG. 15 depicts a GUI screen for configuration of a WLAN according to one embodiment of the present invention.

FIG. 16 depicts a GUI screen for the configuration of spam protection according to one embodiment of the present invention.

FIG. 17 depicts a GUI screen for the configuration of virus protection according to one embodiment of the present invention.

FIG. 18 depicts a GUI screen for the configuration of system policies according to one embodiment of the present invention.

FIG. 19 depicts a GUI screen for the configuration of URL filtering according to one embodiment of the present invention.

## DETAILED DESCRIPTION OF THE INVENTION

Referring first to FIG. 1, depicted is network environment **100** in accordance with one embodiment of the present invention. In this embodiment, network environment **100** includes management center **102**, management portal **104**, firewall **106**, master server **108**, management servers **110**, Internet **112**, router **114**, network connections **116**, network devices **118**, local networks **120**, and local network devices **122**.

In one embodiment of the present invention, network device **118** is a broadband device such as a cable or Digital Subscriber Line (“DSL”) modem having one or more features such as wireless gateways (e.g., an 802.11 gateway, a Bluetooth® gateway, an Infrared Data Association (“IrDA”) gateway, etc.), voice over Internet Protocol (“VoIP”), multi-port switching, VPN, firewalls, anti-virus protection, spam control, content filtering, etc. However, the present invention is not so limited. Network device may be virtually any device having a network connection to at least one other network device regardless of its features.

Managed network devices **118** may be incorporated in some embodiments of the present invention. In these embodiments, network devices **118** are managed and maintained remotely. That is, maintenance functions such as updates to virus definitions, block lists, policies, and firmware are performed from a remote management center such as management center **102** and its associated management portal **104**, master server **108**, and management servers **110a-110b**, via a network connected to both management center **102** and the managed network device **118** (e.g., Internet **112**).

In preferred embodiments of the present invention, management center **102** and one or more of its associated devices are protected by firewall **106**. However, alternate embodiments are envisioned in which no firewall, or more than one firewall, is incorporated. Also, although management servers **110a-110b** are a part of the management center infrastructure, such devices may be hosted by a third party such as an ISP. In these embodiments, all management servers and master servers have identical copies of the authoritative database and a change to any management server database is automatically updated in the databases of other management servers and the master server via database replication. Additionally, the present invention may include any combination of managed and unmanaged network devices **118** without departing from the scope of the present invention.

In some embodiments of the present invention, the master and management server databases are formed of a plurality of tables. For example, such tables may include network device configuration parameter tables, web content filtering software parameter tables, channel tables, customer information tables, ISP tables, ISP rights tables, navigation tables, policy tables, user tables, VPN tables, and the like.

In some embodiments, network device **118** includes a multi-port switch, such as an Ethernet switch, and/or a wireless gateway that allows local devices to communicate with each other and network device **118** in a local area network (“LAN”) configuration. For example, local device **122a** is a personal computer connected to network device **118a** via a hardwired or wireless connection to form local network **120a**. Similarly, local devices **122b** and **122c** are personal computers connected to network device **118b** via hardwired or wireless connections to form local network **120b**. In yet another example, local devices **122d** and **122e** are a network-compatible printer and personal computer, respectively, connected to network device **118d** via hardwired or wireless connections to form local network **120d**.

In some embodiments of the present invention, network device **118** includes a DHCP server. This server may be hardware or software configured to automatically assign network addresses such as Internet Protocol (“IP”) addresses, subnet masks, and related IP information to local devices **122** upon such log in of such devices to local network **120**. Related IP information may include, but is not limited to, default gateways and network addresses for Domain Name System (“DNS”) servers. However, alternative embodiments may be created in which users manually assign permanent network addresses, subnet masks, and related IP information to local devices **122**. In yet other embodiments, such parameters may be automatically assigned by hardware or software other than a DHCP server.

During standalone operation, network devices **118a-118d** connect local networks **120a-120d**, respectively, to Internet **112** via internal hardware such as a modem including, but not limited to, a cable or DSL modem. In turn, this internal modem is typically coupled to network connections **116** such as a telephone line, cable, etc. For example, network connections **116a** and **116b** are cables such as coaxial cables typically wired from a cable television company’s existing wiring infrastructure to the location of network device **118**. Similarly, network connections **116c** and **116d** are xDSL and T1 cabling such as telephone-grade conductors wired from a telephone company’s existing wiring infrastructure to the location of network device **118**. However, other varieties of network connections or wireless connections may also be incorporated without departing from the scope of the present invention.

Network connections **116**, or wireless connections, typically connect network devices **118** to the equipment of a third party ISP. This equipment facilitates network device **118**’s access of Internet **112**. Such connections allow each local device **122** connected to the respective local network **120** to also access the Internet for services such as, but not limited to, electronic mail, surfing the Internet, etc. via network device **118**’s access to Internet **112**.

It is envisioned that a user of a first network device such as network device **118a** and its associated local network **120a** may wish to add a remote local network such as local network **120d**, and its associated local devices **122d** and **122e**, to local network **120a**. However, since local network **120d** may be located at a relatively far distance from local network **120a**, it may be cumbersome or expensive to connect local networks **120a** and **120d** via a physical or wireless connection. In this scenario, a user may implement the systems and methods of the present invention to automatically create a VPN.

Referring now to FIG. 2, depicted is one embodiment of a VPN created using the systems and methods of the present invention. VPN **200** includes many of the devices included in network embodiment **100**. More specifically, VPN **200** includes Internet **112**, router **114**, network connections **116**, network devices **118**, local networks **120**, and local network devices **122**.

After creation of the VPN as discussed herein, network devices **118a** and **118d** are connected to each other via the same hardwired and wireless connections present prior to creation of the VPN. In addition, each of the network devices **118a** and **118d** has the same external network address. That is, each of the network devices **118a** and **118d** may still be accessed by devices that are not members of the VPN via the Internet through the same external network address. However, after creation of the VPN, each of network devices **118a** and **118d** may communicate with local devices **122** coupled to the local network **120** of other VPN members using the local device **122**’s internal network address as if the network



device **118** is connected directly to the respective local network **120**. That is, the VPN is transparent to the user and the user operates as if all devices are a part of the same local network.

To initiate automatic creation of a VPN, a user performs a process similar to, but not limited to, user configuration process **300** illustrated in FIG. **3**. User configuration process **300** begins at **302** at a point in which a user decides to create a VPN. At **304**, the user logs in to a management portal such as management portal **104** using a local device **122** residing on the same local network **120** as a network device such as network device **118**. For example, a user may use a local device **122a** such as a personal computer to log in to management portal **104** through Internet **112** via network device **118a**'s connection of local device **122b** to Internet **112**. After the user logs in to the management portal, user configuration process **300** proceeds to **306**.

At **306**, the management portal to which the user is connected provides a GUI to the user's local device **122** in the form of an Internet web page. From the main screen of the GUI, a user clicks on the "VPN Configuration" tab causing the VPN configuration screen to be displayed at local device **122**. User configuration process **300** then proceeds to **308**, at which the user clicks on the "Create VPN" button on the VPN Configuration screen of the GUI. Once the user clicks the "Create VPN" button, user configuration process **300** proceeds to **310**, at which the user is prompted to assign a name to the VPN. Typically, this name identifies the use of the VPN such as its corresponding business or individual owner. However, any name may be assigned without departing from the scope of the present invention.

Once a name has been assigned to the VPN such as VPN **200**, user configuration process **300** proceeds to **312**. At **312**, a VPN Setting screen is displayed to the user such as VPN Setting screen **600** depicted in FIG. **6**. At this screen, the user is prompted to enter a description for network device **118** in description field **606**, as well as the existing customer ID and password for network device **118** in customer ID and password fields **602** and **604**, respectively. That is, the user is prompted to enter the existing customer ID and password for network device **118** that is coupled to the same local network **120** as the user's local device **118**. After entry of the data, the user clicks add button **608** to proceed to **314**.

Once the user enters the username and password via the local GUI, this data is transmitted via Internet **112** to the management portal, which verifies the network device's password information at **314**. In one embodiment, the management portal accesses the master server's database to determine if the inputted password matches the password information contained in the username's associated data records. In another embodiment of the present invention, management portal accesses a management server's database for this information. However, alternate embodiments of password verification may be incorporated without departing from the scope of the present invention. If, at **314**, the entered username and password are incorrect, user configuration process **300** returns to **312** and allows the user to re-enter the information. However, if at **314**, the username and password information are verified, user configuration process **300** proceeds to **316**.

At **316**, the management portal queries a master or management database to determine if the network device is enabled for VPN operation. This option may be enabled or disabled by a local network device user. If the network device is enabled for VPN operation, user configuration process **300** proceeds to **318**. However, if VPN operation is not enabled,

user configuration process **300** returns to **312**, at which a user may attempt to add a different, VPN-enabled network device.

At **318**, network device **118** is added to a list of network devices **118** that are members of the VPN under creation. The management service assigns network device **118** a position on the list based upon the information contained in the database of a master or management server. Also, each network device **118** is assigned a unique numerical identifier based upon its order of entry to the VPN. That is, each network device **118** in the VPN shall be assigned a unique numerical identifier. For example, network device **118** having the same local network **120** as the local device **122** from which the user logged in to the management portal will be the first network device added to the list and is therefore assigned a numerical identifier of one. The second network device **118** added to the VPN as per the method discussed below shall be assigned a numerical identifier of two, the third network device **118** added to the VPN shall be assigned a numerical identifier of three, and this process of assigning numerical identifiers shall continue until all network devices **118** to be included in the VPN have been assigned an identifier.

In an embodiment of the present invention, the management portal transmits the list data including numerical identifiers to a master or management server. Upon receipt, the server updates its database with the list information. All other databases are then updated via database replication.

Database replication occurs continuously within the systems and methods of the present invention. Upon a change to any master or management server database, all other databases are immediately updated, thereby creating and maintaining backup management servers. In embodiments that include a master server, the master server does not manage any network devices, but rather retains the master, authoritative database for all network devices and VPNS. That is, if a management server database is damaged, the management server receives a new copy of the authoritative database from the master server. However, alternate embodiments are envisioned that do not include a master server. In these embodiments, the failed management server receives a new copy of the current database from one of the other management servers. In either embodiment, since all management servers have identical copies of the current database, each network device has a designated backup server to handle its requests, as described herein, if it is not able to communicate with or receive information from its primary management server.

User configuration process **300** then proceeds to **320**, at which an internal network address is assigned to network device **118** based upon its numerical identifier. For example, network device **118** having a numerical identifier of one may be assigned an internal network address of 192.168.1.0/24, wherein network device **118**'s numerical identifier is the third number of the dotted decimal notation and /24 indicates that the size of the network is 24 network bits. In this scenario, all additional network devices **118** will have network addresses having the same first and second numbers of the dotted decimal notation (i.e., **192** and **168**), however, the third number for each of the network device **118**'s network address will vary as it will also equal the numerical identifier of the corresponding network device **118**.

At **322**, the customer ID, description, and internal network address of network device **118** added to the VPN are displayed to the user. In one embodiment, this display is similar to VPN setting screen **700** as depicted in FIG. **7**. The customer ID, description, and internal network address of the added network device **118** are displayed in customer ID, description, and internal network address display fields **710**, **712**, and **714**, respectively. In this screen, customer ID, password, and

description fields **702**, **704**, and **706**, respectively, are cleared to allow a second VPN member to be added to the VPN.

At **324**, the user decides whether an additional member will be added to the VPN. If an additional member will be added, user configuration process **300** returns to **312** at which point the user enters a customer ID, description, and password. In the embodiment depicted in FIG. 7, the customer ID, password, and description are entered in customer ID, passwords, and description fields **702**, **704**, and **706**, respectively. Thereafter, steps **312** through **322** are repeated until all members have been added to the VPN. However, if at **324**, the user indicates to the management portal that there are no additional members to be added, user configuration process **300** proceeds to **326**. Optionally, at **326**, the user is notified that every network device **118** and every local device **122** including personal computers, network printers, network copiers, etc. to be connected to the new VPN may require rebooting. User configuration process **300** then proceeds to **328**, at which user configuration process **300** ends.

Upon completion of the user configuration process such as user configuration process **300**, automatic device configuration occurs using a process similar to device configuration process **400** as depicted in FIG. 4. Device configuration process **400** begins at **402** at a point after which a user has finished the user configuration process. At **404**, the management portal to which the user logged in to for entry of the configuration parameters for the new VPN transmits the new VPN data to the management server(s) responsible for managing the network devices designated as members of the VPN. Preferably, such transmission occurs internally within a private network connecting the management portal to the management servers. However, embodiments are envisioned in which the management portal communicates with the management servers via a public network such as the Internet.

In one embodiment of the present invention, the management servers may be regional management servers. That is, each management server may be responsible for managing all network devices located in a particular region (e.g., one regional management server per country, one regional management server per state, etc.). However, other non-regional embodiments are envisioned without departing from the scope of the present invention. For example, in lieu of individual management servers, one master management server may be substituted. In fact, embodiments of the present invention are envisioned in which one high-powered server performs all of the functions of the management portal, master server, and all management servers. However, preferably, the management servers are located outside of the management center firewall (e.g., firewall **106**), whereas the management portal and master server are located inside the management center firewall.

Once the management server(s) receive the VPN data, device configuration process **400** proceeds to **406**. The VPN data may be transmitted directly to the management server from the management portal or indirectly via database replication. At **406**, management server configuration transfer tools located on board each of the management server(s) create, encode, and encrypt the configuration data and transmit it as a network device configuration file to the respective network device. The management server configuration transfer tools secure an authenticated communication channel prior to transmitting the data via this channel to the respective network device. Typically, the channel is an Internet channel. The databases of the master server and all other management servers, if any, are updated via database replication.

Virtually any method of encoding the files may be incorporated without departing from the scope of the present

invention. In one embodiment, the encoding method is based upon the World Meteorological Organization's GRIB encoding format. The encoding method analyzes and reduces the data such that its representation uses the least number of bits. The bitgroups are then concatenated and divided into bytes. The sequential order of the multibyte information strings may also be varied to further increase security of the transmitted data. When this latter aspect is incorporated, the network device and management server configuration transfer tools are programmed with the information required to decode the varied sequential order of the data.

In some embodiments of the present invention, the management server creates network device and VPN configuration files using scripting language. A specific scripting language may be chosen for compatibility with the type of database resident on the management server. For example, the PHP Hypertext Preprocessor ("PHP") scripting language may be incorporated for use with management servers having SQL databases, MySQL databases, or any other type of relational databases. However, alternate databases or alternate scripting languages such as Practical Extraction Report Language ("Perl"), Active Server Page ("ASP"), Digital Command Language ("DCL"), etc. may also be incorporated without departing from the scope of the present invention.

Various algorithms may be incorporated for creation of network device configuration files. In an embodiment of the present invention, a network device configuration file is created through execution of scripting language code that performs the following steps: verifies the current directory; retrieves a filename for the network device configuration file; establishes a connection to the management server database; retrieves the server name; retrieves current data relating to the network device from the management server database; and writes the retrieved data to the network device configuration file. The created network device configuration file is then transmitted to the respective network device.

Similarly, various algorithms may also be used to create VPN configuration files. In one efficient embodiment of the present invention, a VPN configuration file is created through execution of scripting language code that performs the following steps: establishes a connection to the management server database by providing a host, username, and password; retrieves current data relating to all network devices that are a member of a VPN from the management server database; retrieves current data relating to all network devices having the same VPN mesh identifier from the data retrieved in the previous step; sets a configuration file path; writes the VPN member data to a file in the configuration file path; and copies the VPN member data to a VPN configuration file.

Request for network device or VPN configuration files may be received by a management server from a master server, management server, or a management portal. Such requests may be transmitted in a variety of forms such as shell commands or batch files without departing from the scope of the present invention. For example, in an embodiment incorporating shell commands, a shell command may execute a shell that changes the directory to the desired directory and executes the scripting language code that generates one or more of the desired configuration files.

After the network device configuration file is transmitted to the network device, device configuration process **400** proceeds to **408**. At **408**, the network device configuration transfer tool receives, decrypts, and decodes the network device configuration file. Next, this tool writes the extracted data to designated storage areas within the network device. Also, the network device configuration transfer tool analyzes the extracted data to determine whether a VPN configuration or

reconfiguration is required (e.g., a user wishes to create a VPN, a user wishes to delete a VPN, etc.).

The network device configuration file received by the network device includes a variety of configuration parameters including, but not limited to: MAC address of the network device; the name of the network device's primary management server; spam filter settings such as off, mark, or drop; quantity of memory reserved to retain potential spam; a forwarding address for spam; antivirus enable/disable; antivirus handling parameters such as drop or pass; the network address of the host that provides the antivirus daemon with updates to the antivirus engine and signature files; the time interval at which the antivirus daemon should check for updates; HTTP proxy server enable/disable setting; the URL of the policy file; network address of the NTP server; network address of the client that made the last change; the beginning and ending of the range of network address that the DHCP daemon may assign to clients; the network address of the DHCP server lease information; WLAN enable/disable; WLAN identifier information; WLAN broadcast beacon enable/disable; WEP encryption method of WLAN; the key for encryption and decryption of WLAN data packet; WLAN channel; VPN enable/disable; the VPN numeric identifier; network device username; network device password; authentication method; and the network device encoding method.

If the respective network device determines that a VPN configuration, or reconfiguration, is not required, device configuration process **400** proceeds to **422**. Reconfiguration is not required, for example, when a member is deleted from the VPN. Referring to FIG. 2, if network device **118b** is deleted, the remaining network devices **118a** and **118c-118d** will retain their existing local network addresses. In other words, to conserve computing resources and speed of the system or method as a whole, these network devices will not be renumbered to account for the elimination of the second network device. Also, the numerical identifier associated with the deleted network device **118b** will not be made available to future VPN members, thereby eliminating any confusion regarding the identity of future VPN members.

However, if reconfiguration is required, device configuration process **400** proceeds to **410**. In one embodiment of the present invention, reconfiguration will be required if the VPN variable(s) in the network device configuration file vary from those configured at the network device. For example, comparison of one or more VPN variables in the network device configuration file to the network device's current VPN variable(s) may indicate that the VPN enable/disable setting has changed, that the network device has been added to a VPN, that the VPN mesh identifier has been changed, etc. In one such embodiment of the present invention, a VPN mesh identifier of zero indicates that the network device is not currently assigned to a VPN. Therefore, changing the VPN mesh identifier from zero to another number indicates to the network device that it has been added to a VPN and, therefore, configuration is required. In another embodiment of the present invention, the network device configuration transfer tool requests a VPN configuration file whenever the VPN mesh identifier does not equal zero.

If such a configuration is required, the network device configuration transfer tool requests a VPN configuration file from the respective management server configuration transfer tool at **410**. At **410**, the management server configuration transfer tool creates a VPN configuration file as discussed in greater detail above. The management server configuration transfer tool then parses the VPN configuration file, adds the authentication data, encodes the configuration and authorization data, and encrypts the resulting encoded data. Next, at

**412**, the management server configuration transfer tool transmits the augmented VPN configuration file to the respective network device via an authenticated communication channel secured by the management server configuration transfer tool prior to transmission of the data.

At **414**, the network device configuration transfer tool receives, decrypts, and decodes the respective VPN configuration file, and writes the received data to the designated storage areas. This data is retrieved from such storage areas by the respective daemons, which reconfigure the network device with the new VPN data contained in the VPN configuration file. For example, the DHCP server may be reconfigured to reserve and assign the static internal network address created for the network device and displayed to the user during the user configuration process. Additionally, other parameters such as scope, address pool, exclusion range, and lease parameters may also be configured.

At **416**, the network device configuration transfer tool extracts the current internal and external network addresses of the other VPN members and writes the data to the respective storage locations. Device configuration process **400** then proceeds to **418**, at which, a VPN tunnel is created between all VPN members using commonly known methods. That is, the internal routing parameters of each network device are altered such that encrypted connections are established between all network devices having local network addresses.

In one embodiment of the present invention, the VPN tunnel is created using an IPsec protocol. The IPsec protocol authenticates and encrypts all data transmitted via the VPN. However, alternate protocols such as Secure Sockets Layer ("SSL") may be substituted without departing from the scope of the present invention. However, IPsec and similar higher-security protocols are preferred as they provide services at layer three, thereby securing all data on the VPN.

Device configuration process **400** then proceeds to **420** at which an authentication system is implemented. Such a system verifies the integrity of information received from another device. Almost any authentication system may be incorporated without departing from the scope of the present invention including, but not limited to, passwords, digital certificates, smart cards, biometrics, and dynamic biometrics.

The authentication system is implemented by the network device configuration transfer tool. This tool extracts the authentication data after decrypting and decoding the VPN configuration file and writes the extracted data to predetermined storage locations within the network device. Whenever data is transmitted between VPN members, the VPN client daemon is responsible for establishing a secure communication link between the VPN members prior to data transmission. During this process, the VPN client daemon accesses the authentication data stored in the respective storage locations to authenticate the link. Consequently, authentication is implemented or updated whenever a VPN configuration file is received at the network device.

Passwords and digital certificates may be managed solely via software, whereas smart cards, biometrics, and dynamic biometrics typically require both software and hardware located at the network device such as network device **118** or the local device such as local device **122**. However, whenever an authentication scheme is implemented, each network device requires additional configuration and setup during the VPN creation process. Via the systems and methods of the present invention, such configuration and setup is performed automatically without user intervention.

Either or both of the network device and VPN configuration files received by each VPN member from its respective management server may contain the necessary authentication

information and related information required for proper local configuration of the authentication scheme as discussed above. For example, in some embodiments, if password protection is implemented, such configuration files will contain the usernames and passwords for each VPN member. Upon a change in a VPN member's username or password information, each of the other VPN members are notified of such change in the same manner in which they are notified of an external network address change. That is, the process to update the VPN members with new username and password information for a particular VPN member is a process such as address change process **500**, as discussed in further detail below with respect to FIG. **5**.

In other embodiments, such configuration files contain digital certificate information such as keys or secrets, user information, and certification authority information. In some embodiments, such keys or secrets are generated and maintained by a third-party certification authority, however, such keys and secrets may also be maintained internal to one or more of the VPN members, management servers, master server, and management center without departing from the scope of the present invention. In either scenario, the digital certificates specify the name of the device as well as its key or secret such that the identity of the sender may be verified.

In yet other embodiments, hardware located at either or both of the network devices and local devices, such as network devices **118** and local devices **122**, respectively, receive information used for verification purposes such as biometric information or smart card information. For example, in a smart card embodiment, the hardware may be a smart card reader into which a smart card is inserted. Such a reader may be a drive in a local device such as a personal computer. The information read from the smart card is read and compared to stored data to verify the identity of the user.

Similarly, in biometric embodiments, biometric readers such as fingerprint readers, signature readers, iris readers, and the like may be incorporated. For example, in one embodiment, a biometric mouse is connected to the local devices for fingerprint recognition purposes. Similar to the smart card embodiments, such biometric information is compared to stored data to verify the identity of a user.

After the authentication scheme is implemented, device configuration process **400** proceeds to **422** at which the user may now access any device coupled to the VPN. For example, in the VPN depicted in FIG. **2**, a user at local device **122a** may access any device coupled to any of the local networks **120a-120d** including local devices **122b-122e**. At **424**, the device configuration ends.

Upon completion of the automatic device configuration process such as automatic device configuration process **400**, a VPN has been created between all network devices **118** selected by the user during the user configuration process. An example of a resultant VPN is depicted in FIG. **2**.

However, after creation of the VPN, reconfiguration of the VPN will be required if there is a change in the external network address of any VPN member. Such a change may occur, for example, if a member of the VPN changes hosting companies or an existing hosting company changes the assigned external network address. Or, if the external network address is dynamic, it may change due to a timeout from the ISP, removing power from network device **118**, or on a regular basis set by the ISP (e.g., every 24 hours). When such a change occurs, the VPN performs a process similar to, but not limited to, external network address change process **500** as illustrated in FIG. **5**. This process updates all members of the VPN with the new external network address information.

At **502**, external network address change process **500** begins. At **504**, the external network address of a VPN member changes and, consequently, the VPN member loses communication with the other VPN members (i.e., it is no longer operating as a member of the VPN). At **506**, the VPN member such as network device **118a-118d** notifies its respective management server, such as management server **110a** or **110b**, of its new external network address and requests a new VPN configuration file. This information is transmitted from the network device through a network, such as the Internet, to the respective management server. Once the management server receives the notification, address change process **500** proceeds to **507**.

At **507**, the VPN member receives an updated VPN configuration file from its management server and is automatically reconfigured as discussed above with respect to FIG. **4**. At this point, the reconfigured VPN member re-established communication with the VPN. At **508**, the management server updates its database with the new external network address information. At **510**, the databases in the master server and other management servers are then updated via database replication or direct transmission of the data between the master and management servers. At **512**, each management server configuration transfer tool creates a new VPN configuration file for all of its respective network devices that are VPN members. The newly created VPN configuration files, including the new external network address information, are then transmitted to the respective network devices. Upon receipt, the respective network device configuration transfer tool receives, decrypts, and decodes the VPN configuration file and writes the configuration data to its respective storage locations. Thereafter, one or more daemons retrieve the newly stored data and reconfigure the network device. At **514**, all VPN members have received the new external network address information, all components of the VPN have been reconfigured as necessary, and the external network address changes process **500** terminates.

Turning next to FIG. **8**, depicted is VPN edit screen **800** as per one embodiment of the present invention. Such a screen may be accessed after a VPN has been created and all VPN members have been added. The description, customer ID, network address, and subnet mask for each network device **118** in the VPN are listed in columns **801**, **803**, **805**, and **807**, respectively. A user may now edit or delete the VPN by clicking edit or delete buttons, **809** and **811**, respectively. Clicking edit button **809** allows the user to edit or delete individual VPN members, as discussed in greater detail below with respect to FIG. **9**. Clicking delete button **811** deletes the entire VPN. That is, each network device **118** reverts to standalone operation and the VPN tunnels are eliminated. The screen depicted in FIG. **8**, as well as those depicted in FIGS. **6**, **7**, and **9**, may be accessed in the same manner as the VPN creation screen, as discussed in detail herein.

Referring next to FIG. **9**, depicted is VPN edit screen **900** as per an embodiment of the present invention. This, as well as all other screens discussed herein or depicted in FIGS. **6**, **7**, and **8**, are intended to be exemplary only. That is, other screens may be substituted for these screens without departing from the scope of the present invention. Similar to VPN edit screen **800**, the customer ID, description, and network address for each network device **118** in the VPN are listed in columns **901**, **903**, and **905**, respectively. However, the subnet mask column is replaced with individual edit and delete buttons **909** and **911**, respectively. Clicking edit button **909**, allows the user to edit the individual VPN member. For example, the description may be modified. Alternatively, a user may click delete button **911** to delete the VPN member.

## 15

Turning next to FIG. 10, depicted is network device initial configuration process 1000 as per one embodiment of the present invention. Typically, this process is performed whenever a user receives a new or replacement network device such as network device 118. Network device initial configuration process 1000 begins at 1001, at which a user receives a new network device. At 1002, the user connects the network device to power, a hardwired or wireless network connection, and a user interface. The power connection is typically achieved by plugging a first end of a power cable into the network device and a second end of the power cable into a typical house of office receptacle. Network connections may be made via any commonly available method (e.g., connection to one or more telephone lines via one or more telephone cables, connection to a cable network via a coaxial cable, etc.). User interfaces may be connected to the network interface via a wireless or hardwired connection. Such interfaces may include any interface having a display and means for (e.g., PDAs, personal computers such as local device 122a, etc.).

Network device initial configuration process 1000 then continues to 1004 at which, via the user interface, the user will attempt to initiate a connection to the Internet by a method such as opening an Internet browser. At 1006, the network device automatically redirects the Internet browser from the current HTML page to an HTML setup page stored in the network device. Upon display of the HTML setup page to the user via the user interface, the user is prompted to input a minimal amount of data such as username, password, and the type of network connection coupled to the network device. Upon entry of such data at 1008, network device initial configuration process 1000 proceeds to 1010.

At 1010, the network device automatically configures the network connection based upon the data input by the user, and network device initial configuration process 1000 proceeds to 1011. At 1011, the network device automatically establishes communication with the Internet via the network connection. At 1012, if a connection with the Internet is established, network device initial configuration process 1000 proceeds to 1013. If an Internet connection is not established, network device initial configuration process 1000 returns to 1008.

At 1013, the network device automatically establishes communication with a master server such as master server 108 via the network connection. At 1014, the master server analyzes the data provided by the network device and assigns and directs the network device to one of the management servers such as management servers 110. After terminating communication with the master server, network device initial configuration process 1000 proceeds to 1016, at which the network device establishes communication with its assigned management server. At 1018, the network device requests a network device configuration file from the management server, and process 1000 proceeds to 1020. At 1020, the management server configuration transfer tool transmits a generic encoded and encrypted network device configuration file to the network device.

At 1022, the network device configuration transfer tool decrypts and decodes the generic network device configuration file. Then, this tool extracts the configuration data and writes it to its respective storage locations within the network device. Thereafter, all daemons executed by the network device retrieve their respective data from the configuration data storage locations, thereby performing an initial generic configuration of the network device. Upon completion of its initial configuration, the network device terminates the configuration process 1024. After network device initial configuration process 1000 is complete, the user shall be enabled for

## 16

basic functions such as, but not limited to, web surfing, electronic mail, etc. Thereafter, a user may customize the network device configuration using the remote management systems and methods of the present invention as described in greater detail with respect to FIGS. 11-19.

After an initial generic configuration of the network device, a user may customize the configuration by performing a process similar to, but not limited to, user configuration process 1100 as illustrated in FIG. 11. User configuration process 1100 begins at 1102 at which a user decides to alter the network device configuration. At 1104, the user logs in to a management portal such as management portal 104 using a user interface such as local device 122 coupled to the network device. In one embodiment, the user interface may reside on the same local network (e.g., local network 120) as the network device (e.g., network device 118). In another embodiment, a user may use a user interface such as a personal computer to log in to the management portal through the Internet via the network device's connection of the user interface to the Internet. After the user logs in to the management portal, user configuration process 1100 proceeds to 1106.

At 1106, the management portal to which the user is connected provides a GUI to the user interface. In one embodiment, the GUI is in the form of an Internet web page. At this web page, the user is prompted to enter a customer ID and password. That is, the user is prompted to enter the existing customer ID and password for the network device. Once the user enters the customer ID and password, this data is transmitted via the Internet to the management portal, which verifies the network device's customer ID and password information at 1108. In one embodiment, the management portal accesses the master server's database to determine if the inputted password matches the password information contained in the customer ID's associated data records. In another embodiment of the present invention, management portal accesses a management server's database for this information. However, alternate embodiments of password verification may be incorporated without departing from the scope of the present invention. If, at 1108, the entered customer ID and password are incorrect, user configuration process 1100 returns to 1106 and allows the user to re-enter the information. However, if at 1108, the customer ID and password information are verified, user configuration process 1100 proceeds to 1114.

At 1114, a start screen is displayed to the user such as start screen 1300 depicted in FIG. 13. Start screen 1300 contains easy-to-understand and user-friendly instructions 1302. The user clicks on the desired configuration tab of configurations tabs 1306a-1306e located on the left side of start screen 1300, and process 1100 proceeds to 1116. Although start screen 1300 only depicts five configuration tabs 1306a-1306e for general, router, e-mail, firewall and parental control options, respectively, additional options may be included without departing from the scope of the present invention.

At 1116, the user clicks on the desired configuration parameter 1308a-1308i. Based upon the user's selected configuration parameter, a preferences screen such as one of the preference screens 1400, 1500, 1600, 1700, 1800, or 1900 as depicted in FIGS. 14-19 may be displayed at 1118. For example, in the embodiment depicted in FIG. 13, if the user chooses the spam protection parameter 1308f listed below electronic mail configuration tab 1306c, preference screen 1600, as depicted in FIG. 16, is displayed. The user then selects the desired preference via radio buttons 1602a-1602e and user configuration process 1100 proceeds to 1120. At 1120, the user clicks the save button such as save button 1604, and, at 1122, the user receives verification that the configu-

ration parameter has been successfully updated. Thereafter, at **1124**, user configuration process **1100** ends.

However, if the user chooses a configuration parameter other than **1308f**, such as **1308c**, **1308d**, **1308g**, **1308h**, or **1308i**, preference screens such as preference screens **1400**, **1500**, **1700**, **1800**, or **1900** may be displayed. After being redirected to the requested preference screens, the user simply makes a selection by clicking radio buttons, checkmarks, and the like. When all selections are made for the given configuration parameter, the user clicks the save button as per **1120** of user configuration process **1100** depicted in FIG. **11**, and the process completes as described above.

FIGS. **14-19** are provided to demonstrate the simplistic nature of configuring a network device as per the systems and methods of the present invention. However, it should be noted that the format of these displays may be altered without departing from the scope of the present invention. Also, displays depicting configuration parameters other than those included herein may also be added or substituted without departing from the scope of the present invention.

Upon completion of the user configuration process such as user configuration process **1100**, automatic network device configuration occurs using a process similar to network device configuration process **1200** as depicted in FIG. **12**. Network device configuration process **1200** begins at **1202** at which a user has finished the user configuration process. At **1204**, the management portal to which the user logged in to for entry of the configuration parameters for the network device transmits the new network device configuration data to the management server such as management server **110** responsible for managing the network device. Preferably, such transmission occurs internally within a private network connecting the management portal to the management servers. However, embodiments are envisioned in which the management portal communicates with the management servers via a public network such as the Internet.

Once the management server receives the network device configuration data, network device configuration process **1200** proceeds to **1206**. The network device data may be transmitted directly to the management server from the management portal or indirectly via database replication.

At **1206**, management server configuration transfer tools located on board each of the management server(s) create, encode, and encrypt the configuration data and transmit it as a network device configuration file to the respective network device as discussed in detail above with respect to FIG. **4**. The management server configuration transfer tools secure an authenticated communication channel prior to transmitting the data via this channel to the respective network device. Typically, the channel is an Internet channel.

After the network device configuration file is transmitted to the network device, network device configuration process **1200** proceeds to **1208**. At **1208**, the network device configuration transfer tool network device **118** receives, decrypts, and decodes the network device configuration file. Next, this tool writes the extracted data to designated storage areas within the network device. Also, the network device configuration transfer tool, decrypts it if required, and analyzes the extracted data to determine whether a VPN configuration or reconfiguration is required (e.g., a user wishes to create a VPN, a user wishes to delete a VPN, etc.).

After the configuration data is written to the respective storage locations, process **1200** proceeds to **1212**. At **1212**, daemons read the stored data thereby reconfiguring the network devices. At **1214**, network device configuration process **1200** ends.

While the present invention has been described with reference to one or more preferred embodiments, which embodiments have been set forth in considerable detail for the purposes of making a complete disclosure of the invention, such embodiments are merely exemplary and are not intended to be limiting or represent an exhaustive enumeration of all aspects of the invention. The scope of the invention, therefore, shall be defined solely by the following claims. Further, it will be apparent to those of skill in the art that techniques, systems and operating structures in accordance with the present invention may be embodied in a wide variety of forms and modes, some of which may be quite different from those in the disclosed embodiments, without departing from the spirit and the principles of the invention.

The invention claimed is:

1. A method for remotely maintaining a VPN configured using VPN data input by a user at a portal comprising the steps of:

transmitting maintenance data to at least one management device from a first network device in the VPN through a management portal;

creating (i) a VPN configuration file or (ii) a VPN configuration file and a device configuration file, each at the at least one management device;

automatically establishing a communication between the at least one management device and at least one network device, which may be the same or different than the first network device, via at least one connection of at least one network; and

transmitting at least one of the VPN configuration file or the VPN configuration file and the device configuration file from the at least one management device to the at least one network device via the network connection;

wherein at least one parameter of the at least one network device, the VPN, and combinations thereof is automatically configured upon local processing of the VPN configuration file or the VPN configuration file and the device configuration file.

2. A method according to claim **1**, wherein the maintenance data is at least one of the group consisting of virus definitions, block lists, policies, and firmware.

3. A method according to claim **1**, wherein the at least one network device is at least one of the group consisting of a broadband device, a router, a modem, a switch, a wireless gateway, and combinations thereof.

4. A method according to claim **1**, further comprising the steps of:

encoding the VPN configuration file or the VPN configuration file and the device configuration file, and

encrypting the VPN configuration file or the VPN configuration file and the device configuration file,

wherein the encoding and the encrypting occur prior to transmission of the VPN configuration file or the VPN configuration file and the device configuration file via the at least one network.

5. A method according to claim **1**, wherein the network connection is at least one of the group consisting of a wireless connection, a cable connection, a digital subscriber line, a telephone line, and combinations thereof.

6. A method according to claim **1**, wherein the network is at least one of the group consisting of an Internet, a wide area network, and combinations thereof.

7. A method according to claim **1**, wherein a configuration transfer tool integral to the at least one management device creates and transmits the VPN configuration file or the VPN configuration file and the device configuration file to the at least one network device.

## 19

8. A method according to claim 1, wherein the local processing of the VPN configuration file or the VPN configuration file and the device configuration file, includes the sub-steps of:

extracting configuration data from the VPN configuration 5  
file or the VPN configuration file and the device configuration file, and

writing the configuration data to at least one storage location of the at least one network device;

wherein at least one daemon executed by each of the at least 10  
one network device retrieves and processes at least a portion of the configuration data contained in each of the storage locations.

9. A method according to claim 1, wherein the local processing of the VPN configuration file or the VPN configuration 15  
file and the device configuration file includes the sub-steps of:

decrypting the VPN configuration file or the VPN configuration file and the device configuration file,

decoding the VPN configuration file or the VPN configuration 20  
file and the device configuration file,

extracting configuration data from the VPN configuration file or the VPN configuration file and the device configuration file and

writing the configuration data to at least one storage location 25  
of the at least one network device;

wherein at least one daemon executed by each of the at least one network device retrieves and processes at least a portion of the configuration data contained in each of the storage locations.

## 20

10. A method according to claim 1, wherein the transmitting maintenance data to the at least one management device includes the sub-steps of:

transmitting the maintenance data to a master device; and  
transmitting the maintenance data from the master device to the at least one management device.

11. A method according to claim 1, wherein the maintenance data is input via a user interface coupled to the network device in the VPN.

12. A method according to claim 11, wherein the user interface is at least one of the group consisting of a personal computer, a personal data assistant, and a network-equipped appliance.

13. A method according to claim 11, wherein the coupling of the user interface to the network device in the VPN is at least one of the group consisting of a cable, an Ethernet cable, a wireless connection, a local area network, a wide area network, an Internet connection, and combinations thereof.

14. A method according to claim 1, further comprising the step of:

authenticating a communication channel prior to the establishing of the communication between the at least one management device and the at least one network device.

15. A method according to claim 14, wherein the authenticating is performed using at least one of the group consisting of IP security, secure sockets layer, passwords, digital certificates, smart cards, biometrics, dynamic biometrics, and combinations thereof.

\* \* \* \* \*