

US008156459B1

(12) **United States Patent**
Ou et al.

(10) **Patent No.:** **US 8,156,459 B1**
(45) **Date of Patent:** **Apr. 10, 2012**

(54) **DETECTING DIFFERENCES BETWEEN HIGH LEVEL BLOCK DIAGRAM MODELS**

(75) Inventors: **Jingzhao Ou**, San Jose, CA (US); **Chi Bun Chan**, San Jose, CA (US)

(73) Assignee: **Xilinx, Inc.**, San Jose, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 315 days.

(21) Appl. No.: **12/615,415**

(22) Filed: **Nov. 10, 2009**

(51) **Int. Cl.**
G06F 17/50 (2006.01)
G06F 9/455 (2006.01)

(52) **U.S. Cl.** **716/107**; 716/102; 716/103; 716/104; 716/106; 716/132; 716/136; 716/139; 703/2; 703/6; 703/7; 703/14

(58) **Field of Classification Search** 716/102, 716/103, 104, 106, 107, 132, 136, 139
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,493,507	A *	2/1996	Shinde et al.	703/14
5,995,736	A *	11/1999	Aleksic et al.	716/103
6,321,369	B1 *	11/2001	Heile et al.	716/102
6,385,617	B1 *	5/2002	Malik	707/693
6,848,084	B1 *	1/2005	Pandey et al.	716/107
7,007,261	B1 *	2/2006	Ballagh et al.	716/103
7,093,224	B2 *	8/2006	Wheeler et al.	716/102
7,099,809	B2 *	8/2006	Dori	703/6

7,178,112	B1 *	2/2007	Ciolfi et al.	703/2
7,194,705	B1 *	3/2007	Deepak et al.	716/103
7,222,317	B1 *	5/2007	Mathur et al.	716/107
7,346,486	B2 *	3/2008	Ivancic et al.	703/22
7,383,166	B2 *	6/2008	Ashar et al.	703/14
7,418,680	B2 *	8/2008	Clarke et al.	716/107
7,437,700	B2 *	10/2008	Wang et al.	716/104
7,480,877	B2 *	1/2009	Acuna et al.	716/136
7,523,433	B1 *	4/2009	Anderson	716/139
7,539,602	B2 *	5/2009	Willis	703/2
7,681,151	B2 *	3/2010	Ciolfi et al.	716/116
7,685,545	B2 *	3/2010	Chapman et al.	716/136
7,698,668	B2 *	4/2010	Balasubramanian et al.	716/106
7,707,014	B2 *	4/2010	Kodosky et al.	703/2
7,890,198	B1 *	2/2011	Gahinet	700/31
7,974,823	B1 *	7/2011	Aldrich	703/7
7,992,111	B1 *	8/2011	Ma et al.	716/103
7,996,799	B2 *	8/2011	Farkash et al.	716/106

* cited by examiner


Primary Examiner — Helen Rossoshek

(74) *Attorney, Agent, or Firm* — LeRoy D. Maunu

(57) **ABSTRACT**

A method of detecting differences between high level block diagram models using text based analysis. Previous methods of determining differences between high level block diagram models derive differences through traversal of the block hierarchy which is complex and cannot compare differences between models created with third party design environments. The present invention increases interoperability and capabilities of existing circuit design environments, and achieves an advance in the art, by converting high level block diagram models to a user readable text-based format and performing a text-based differential analysis on the converted models to determine differences.

16 Claims, 7 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

1**DETECTING DIFFERENCES BETWEEN
HIGH LEVEL BLOCK DIAGRAM MODELS**

FIELD OF THE INVENTION

The present invention generally relates to tools for creating electronic circuit designs.

BACKGROUND

Electronic circuit designs may be prepared using any of a variety of approaches. In one approach, the designer creates a graphical high level block diagram model of the system using a tool such as the System Generator for DSP from XILINX®, Inc., which enables use of the SIMULINK® model-based environment from The MATHWORKS®. These types of tools provide a graphical user interface (GUI) for preparing, simulating, and even implementing a circuit design. Basic building blocks are instantiated, connected, and combined into larger blocks of the design via the GUI. Each block generally has at least one input signal, at least one output signal, and an equation that defines the relationship between the input and output signals.

In another approach, a design can be specified in a hardware description language (HDL) such as VHDL or Verilog. In an HDL approach the designer has a greater level of control over the eventual implementation. However, when using an HDL the designer may sacrifice the benefits associated with the ability to abstract the design at a high level as provided by a GUI approach.

A scripting language such as MATLAB provides a higher level of abstraction for creating a design than does an HDL. A scripting language supports flexible parameterization through which, for example, components of a design may be easily scaled for different applications. However, scripting languages may be cumbersome for quickly assembling components of a circuit design. Other high-level programming languages such as JAVA™, JAVASCRIPT™, C++, and TCL (Tool Command Language), are also sometimes used to create circuit designs. However, developing circuit designs using these languages has the same drawbacks as using MATLAB.

A GUI-based modeling system allows a designer to easily abstract and assemble different parts of a design. However, for designs that contain hundreds to thousands of blocks, and for designs in which the number of blocks and connections change subject to design parameters, it may be more straightforward for the designer to specify the design and define the parameters that control the numbers of blocks and connections with a script-based specification rather than with a GUI-based system.

Furthermore, designs are often prepared with the collaboration of several designers preparing different components of the overall design. Different designers may use different design systems or design on different levels of abstraction. Because changes to one component can adversely affect the operation of others, it is desirable to compare and track changes between various design tools.

SUMMARY

In one of the various contemplated embodiments of the invention, a process is provided for detecting differences between high level block diagram models using text based analysis. First and second block diagram models are converted into respective first and second text based models. Differences between the first and second text based models are identified. Identified differences are then displayed.

2

In another embodiment of the invention, a system is provided for identifying and displaying differences between two block diagram models. The system includes a processor, a bus coupled to the processor, a memory unit coupled to the bus, and a storage unit coupled to the bus. The processor and the memory are configured to convert the block diagram models into respective first and second text based models. The processor and memory are further configured to identify differences between the first and second text-based models and display the identified differences.

In yet another of the various embodiments of the invention, an article of manufacture is provided. The article of manufacture is characterized by instructions which, when executed by a processor, cause the processor to convert first and second block diagram models into respective first and second text-based models. The executed instructions further cause the processor to identify differences between the first and second text-based models and store the identified differences.

It will be appreciated that various other embodiments are set forth in the Detailed Description and Claims, which follow.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a block diagram of the process of converting two models into a text-based format and identifying differences in accordance with several embodiments of the invention;

FIG. 2 illustrates a GUI interface and an example modularized circuit design which is translated from a high level block diagram model into a high level language program in accordance with various embodiments of the invention;

FIG. 3 illustrates a block diagram of a second process of converting a high level block diagram model into a user readable text format in accordance with various embodiments of the invention;

FIG. 4 illustrates a block diagram of the process of comparing two models to identify differences and determine whether a module has been added, deleted, or modified in accordance with various embodiments of the invention;

FIG. 5 illustrates, as an example, an implementation of the difference calculation in accordance with various embodiments of the invention;

FIG. 6 illustrates a block diagram of the process of converting two models into a text-based format, identifying differences, and displaying differences as a high level block diagram in accordance with various embodiments of the invention; and

FIG. 7 illustrates a block diagram of a general purpose processor computing arrangement for implementing a difference utility in accordance with various embodiments of the invention.

DETAILED DESCRIPTION

The present invention increases interoperability and capabilities of existing circuit design environments, and achieves an advance in the art, by converting high level block diagram models to a user readable text-based format and performing a text-based differential analysis on the converted models. High level block diagram models are often encoded in special formats. These model files may contain information unrelated to the functionality of the designs, such as time stamps or formatting information for a diagram. The conversion of high level block diagram models to text based models places the compared models in a format in which the models can be compared for character differences without identifying char-

acter differences unrelated to the design functionality. In this manner, false positives identifying a block as changed when there has been no substantive functional change, are prevented. The conversion of the models into a common plain-text format further increases interoperability between designs that have been converted and modified in different models. In converting to text, the user is able to utilize inexpensive text-based solutions rather than more complex, high-level block diagram solutions. Additionally, the text conversion places the models to be viewed in a more user readable format. There is no need for users to install high level modeling systems in order to see the differences between the high level models.

FIG. 1 shows a block diagram of the process of converting two models into a text-based format and identifying differences in accordance with several embodiments of the invention. The process takes two high level block diagram models **100** and **104** as input. Each model is converted into a text based format at steps **102** and **106**. The converted models are compared for differences at step **108** and identified differences **110** are output in plain text format.

Various embodiments of the invention perform the conversion to a text-based format differently. For example, a high level block diagram model may be converted to an HDL such as Verilog, an HLL such as C or C++, a MATLAB script, or other plaintext representation of the circuit design.

FIG. 2 shows a GUI interface and an example modularized circuit design outer subsystem and inner subsystem which are translated from a high level block diagram model into an HLL program. The example user interface window **202** includes a design pane in which a portion of an example electronic circuit design is displayed. The portion of the example design is shown as having graphical objects **204**, **206**, and **208**. Graphical object **206** is used to illustrate the translation of an underlying graphical model into an HLL program.

In the description below, the following terminology is employed. A "graphical object" refers to the graphical rendering of a component of a design as displayed to a designer. An abstract view of the circuit design is that the design is comprised of functional or logic "blocks," each performing the designated function. A "graphical model" refers to the stored data that defines a block of the design in a high level block diagram model, including data for rendering a graphical object. The function of a block may be provided by one or more blocks nested within that block. If the details of the nested blocks are not important to the designer, the designer may choose to view the block containing the nested blocks without viewing the nested blocks. The term "outer subsystem" refers to a block that contains nested blocks, and each nested block may be an "inner subsystem" of the outer subsystem. A block is a subsystem if it contains any nested blocks, and a leaf block if it does not contain any nested blocks. "Block" may sometimes be used as shorthand to reference a graphical object, the underlying graphical model, a subsystem, or a leaf.

The graphical object **206** depicts an outer subsystem as defined by graphical model **206'** in storage **212**, and the graphical object(s) **208** depicts an inner subsystem as defined by the graphical model **208'**. The graphical model **206'** is part of graphical model **210**, which includes other parts of the overall electronic circuit design. Each graphical model **206'** and **208'** includes a set of attributes that define the model. The attributes include parameters, initialization commands, ports, blocks, and connectivity. For graphical model **206'**, the attributes are shown as parameters **222**, initialization commands **224**, ports **226**, blocks **228**, and connectivity **230**.

Parameter attributes **222** are used in configuring the graphical model **206'**. For example, the parameter attributes may

include variable names and values which are evaluated at the time the graphical model is compiled into a simulation model. Example parameters include values for constants used in the function specified by the graphical model.

The initialization attributes **224** include commands which are optionally established by a designer. The commands may be used to establish an initial state for the graphical model when that model is opened for simulation.

The ports attributes **226** specify characteristics of the ports of the block specified by the graphical model **206'**. Such characteristics include the names and directions (input or output) of the ports.

The block attributes **228** specify each block that is nested within graphical model **206'**. In the example, the block **206** is shown as including one or more blocks **208**. The nested block **208** provides some part of the overall function of block **206**. Thus, the block attributes **228** of graphical model **206'** specify that block **208** is nested within block **206**. It will be appreciated that graphical model **206'** specifies that block **206** is an inner subsystem of the block defined by graphical model **210**. Thus, the block (not shown) defined by graphical model **210** is an outer subsystem relative to block **206'**.

The connectivity attributes **230** specify the connections between the blocks specified by the blocks attributes **228** as well as the connections to the ports specified by the ports attributes **226**. Values for the parameters and the initialization commands may be specified by a designer using editing windows such as the examples shown in FIGS. 2 and 3.

Graphical model **208'** specifies the attributes of block **208**, which is nested within block **206**. The nested relationship is shown as graphical model **208'** being contained by graphical model **206'**.

The graphical model **208'** includes parameter attributes **232**, initialization attributes **234**, ports attributes **236**, block attributes **238**, and connectivity attributes **240** as described above for the graphical model **206'**.

According to embodiments of the inventions, in response to a designer selecting a particular graphical model and invoking a translator **242**, the selected graphical model is read from storage **212** and translated into an HLL program **244**. The HLL may be a scripting language or a language for which program code is typically interpreted or compiled and executed. The generated HLL program **242** has a structure that corresponds to the hierarchical relationship between the components of the translated model. For example, the graphical model **206'**, which contains the graphical model **208'**, is translated into a function in the HLL program which begins with the function declaration **206"**. The function specification **206"** includes parameter declarations **222'** for the parameter attributes **222** of the graphical model **206'**, initialization statements **224'** that implement the initialization commands **224**, port and connectivity statements **226'** that implement the port attributes **226** and connectivity attributes **230**, and a statement **228'** that invokes a function corresponding to the block **208**, which is specified by the block attributes **228**.

The graphical model **208'** is translated into a function that is specified within the scope of function **206"** in the HLL program **244**. The specification of the function for graphical model **208'** begins with the function declaration **208"** and includes statements **232'**, **234'**, **236'**, and **238'**, which correspond to the attributes of graphical model **208** and are similar to the statements in function **206"**.

In the example program **244**, function **208"** is shown as being declared within the scope of function **206"** by way of it being specified before the end **206"** statement. Parameters referenced by function **206"** can be referenced by function

5

208", which reflects the scope of parameter attributes 222 of graphical model 206' being visible within graphical model 208'.

The HLL program code in Example 1 below illustrates an example translation of a graphical model. The example code is a script in the MATLAB language. There are elements in the example script that correspond to code that would be generated from the graphical model 206' of FIG. 2. However, it will be recognized that the script in Example 1 reflects characteristics of a graphical model beyond those of graphical model 206'. In particular, the declared inner_subsystem invokes the xBlock function twice for instantiating two constant multipliers, with the output of the first constant multiplier connected to the input of the second constant multiplier.

```
function outer_subsystem(a, b)
    % initialization commands
    c=a+b;
    in=xInport('in');
    out=xOutput('out');
    xBlock(str2func('inner_subsystem'), {a, b});
function inner_subsystem(a, b)
    % mask initialization
    d1=c*2+a;
    d2=c*3+b;
    in=xInport('in');
    out=xOutput('out');
    % create a signal object which can
    % connect two blocks
    sig=xSignal( );
    % create a const mult,
    % connect subsystem input port 'in'
    % to the input port of const mult
    % connect signal 'sig'
    % to the output port of const mult
    xBlock('Constant Multiplier', ...
        {'const', d1}, ...
        {in}, ...
        {sig});
    % create another const mult 2,
    % connect signal 'sig'
    % to the input port of const mult 2
    % connect subsystem input port 'out'
    % with the output port of const mult
    xBlock('Constant Multiplier', ...
        {'const', d2}, ...
        {sig}, ...
        {out});
end % function inner_subsystem
end % function outer_subsystem
```

EXAMPLE 1

The outer_subsystem function corresponds to graphical model 206'. The inner_subsystem function is declared and defined within the definition of the outer_subsystem function (before the "end" statement for the outer_subsystem). Thus, the inner_subsystem function is nested within the outer_subsystem function, much as function 208" is nested within function 206" in FIG. 2, which allows the inner_subsystem function to reference parameters of the outer_subsystem function. For example, parameters a, b, and c, which are declared in the outer_subsystem function, are referenced in the inner_subsystem function.

For a scripting language, such as MATLAB, type declaration is not required for the variables. However, those skilled in the art will recognize that if the target HLL is strongly typed, as are C++ and Java, each variable would be declared with a

6

type. In a strongly-typed language, the "in" in Example 1 would be declared as a type xInport, "out" would be declared as a type xOutput, "sig" would be declared as a type xSignal, and parameters a and b would be the type double. The types, xInport, xOutput, and xSignal would be custom defined for use in generating the desired model from the executed program.

The comments in the script designate the initialization commands for the outer_subsystem and for the inner_subsystem. The following statements:

```
in=xInport('in');
out=xOutput('out');
```

are generated from the port attributes of the graphical model. Note that the outer_subsystem and the inner_subsystem both have these port statements.

The statement, xBlock(str2func('inner_subsystem'), {a, b}); invokes the inner_subsystem function and is generated based on the block attributes of the graphical model of the outer_subsystem. That is, the block attributes of the outer_subsystem will identify the inner_subsystem as a constituent block of the outer_subsystem.

A block that does not contain any nested blocks is a leaf block, as noted above. The function that is specified for a leaf block is that which generates a graphical model of that same leaf block when that function is invoked in executing the HLL program. The following HLL statement from Example 1 is that generated from a leaf block in a graphical model:

```
xBlock('Constant Multiplier', ...
    {'const', d1}, ...
    {in}, ...
    {sig});
```

When the xBlock function is called with values for the specified parameters, the output is a graphical model for the constant multiplier block. Thus, the predefined xBlock function instantiates a leaf block in the graphical model, with the leaf block being a constant multiplier as specified with the parameter to xBlock. The xBlock function is programmed to generate a graphical model that is compliant with the underlying graphical modeling system, for example, SIMULINK.

Based on the connectivity attributes of the graphical model corresponding to the inner_subsystem function, the function is specified with a statement to instantiate the signal (sig=xSignal()). The signal named sig, connects the output of the first constant multiplier to an input of the second constant multiplier, where the constant multipliers are instantiated with the calls to xBlock('Constant Multiplier', ...).

The generated HLL program is distinguished from the graphical model in that the graphical model does not support parameterization of the model by way of adding programmatic control flow. For example, the script in Example 1 could be supplemented with a for loop which contains the xBlock ('Constant Multiplier', ...) statement, where the for loop iterates some number of times based on an input parameter value. When the supplemented script is executed with the parameter value of the for loop, a chain of constant multipliers is instantiated in the design. Whereas, with the GUI interface the designer would have to manually instantiate and connect the desired number constant multipliers in the chain, with the supplemented script the designer need only input the desired parameter value.

In converting a high level block diagram model into a plain-text format, several embodiments of the present invention increase user readability of the converted file by removing operations and objects that are non-functional. FIG. 3 illustrates a flowchart of an example process for converting a high level block diagram model into a user readable text format in accordance with various embodiments of the inven-

FIG. 6 shows a flowchart of an example process of converting two models into a text-based format, identifying differences between them, and displaying the differences as a high level block diagram. The process takes two high level block diagram models as input, 602 and 606. Each model is converted into a text based format at steps 604 and 608. The converted models are compared for differences at 610. The process is similar to that in FIG. 1, except the identified differences are used to generate a high level block diagram model 612 which is displayed to the user at steps 614 and 616. If the hierarchy of the models is preserved as in FIG. 4, the hierarchy is used to generate the graphical display model 612. Otherwise, the text-based model must be parsed to determine hierarchy of each block (not shown). After the model is generated, the whole model may be displayed with changed blocks indicated as added, deleted, or modified at step 614, or changed blocks may be displayed separate from the entire model at step 616. The additions, deletions, and modifications may be delineated with different block colors or shading, for example.

FIG. 7 is a block diagram of an example computing arrangement on which the processes described herein may be implemented using a general purpose processor. Those skilled in the art will appreciate that various alternative computing arrangements, including one or more processors and a memory arrangement configured with program code, would be suitable for hosting the processes and data structures and implementing the algorithms of the different embodiments of the present invention. The computer code comprising the processes of the present invention, encoded in a processor executable format, may be stored and provided via a variety of computer-readable storage media or delivery channels such as magnetic or optical disks or tapes, electronic storage devices, or as application services over a network.

Processor computing arrangement 700 includes one or more processors 702, a clock signal generator 704, a memory unit 706, a storage unit 708, and an input/output control unit 710, all coupled to host bus 712. The arrangement 700 may be implemented with separate components on a circuit board or may be implemented internally within an integrated circuit. When implemented internally within an integrated circuit, the processor computing arrangement is otherwise known as a microcontroller.

The architecture of the computing arrangement depends on implementation requirements, as would be recognized by those skilled in the art. The processor 702 may be one or more general purpose processors, or a combination of one or more general purpose processors and suitable co-processors, or one or more specialized processors (e.g., RISC, CISC, pipelined, etc.), for example.

The memory arrangement 706 typically includes multiple levels of cache memory, and a main memory. The storage arrangement 708 may include local and/or remote persistent storage such as provided by magnetic disks (not shown), flash, EPROM, or other non-volatile data storage. The storage unit may be read or read/write capable. Further, the memory 706 and storage 708 may be combined in a single arrangement.

The processor arrangement 702 executes the software in storage 708 and/or memory 706 arrangements, reads data from and stores data to the storage 708 and/or memory 706 arrangements, and communicates with external devices through the input/output control arrangement 710. These functions are synchronized by the clock signal generator 704. The resources of the computing arrangement may be managed by either an operating system (not shown), or a hardware control unit (not shown).

The present invention is thought to be applicable to a variety of systems for detecting differences between high level block diagram models. Other aspects and embodiments of the present invention will be apparent to those skilled in the art from consideration of the specification and practice of the invention disclosed herein. It is intended that the specification and illustrated embodiments be considered as examples only, with a true scope and spirit of the invention being indicated by the following claims.

What is claimed is:

1. A method of detecting differences between high level block diagram models using text based analysis, comprising: converting a first block diagram-based model and a second block diagram-based model to a first text-based model and a second text-based model, respectively; on a processor, identifying differences between the first text-based model and the second text-based model; merging identified differences into a third block diagram model which has been converted to a plain text format; and displaying the identified differences on a graphical user interface.
2. The method of claim 1, further comprising indentifying blocks of text within the first and second text-based models which correspond to blocks of the high level block diagram-based model.
3. The method of claim 2, further comprising: identifying each block that has been added, modified, or deleted; and storing data indicating each block that has been added, modified, or deleted.
4. The method of claim 3, wherein the converting includes preserving in the first and second text-based models, hierarchical relationships between blocks as specified in the first and second block diagram-based models.
5. The method of claim 4, further comprising: generating a block diagram from the first and second text-based models of blocks identified as added, modified, or deleted; and displaying the generated block diagram in a manner that graphically indicates each block that has been added, modified, or deleted.
6. The method of claim 4, further comprising: generating a block diagram from the first and second text-based models; and displaying the generated block diagram in a manner that graphically indicates each block that has been added, modified, or deleted.
7. The method of claim 1, wherein the text-based model converted to is a hardware description language based model.
8. The method of claim 1, wherein the identifying of differences comprises: determining a longest common subsequence of characters in the first text-based model and the second text-based model; and identifying portions of the first and second text-based models that are not part of the longest common subsequence.
9. The method of claim 1, further comprising: converting merged file to a high-level block diagram format.
10. A system for identifying and displaying differences between two block diagram models, comprising: a processor; a bus coupled to the processor; a memory unit coupled to the bus; and a storage unit coupled to the bus; wherein the processor and the memory are configured to:

11

convert the block diagram models to respective first and second text-based models;

identify differences between the first and second text-based models;

merge identified differences into a third block diagram model which has been converted to a plain text format; and

display the identified differences on a graphical user interface.

11. The method of claim **10**, wherein the processor and the memory are further configured to: identify blocks of text within the first and second text-based models which correspond to blocks of the high level block diagram-based model.

12. The method of claim **11**, wherein the processor and the memory are further configured to:

identify each block that has been added, modified, or deleted; and

store data indicating each block that has been added, modified, or deleted.

13. An article of manufacture, comprising:

a processor-readable non-transitory storage medium configured with processor-executable instructions, the instructions when executed by a processor causing the processor to:

convert first and second block diagram models into respective first and second text-based models;

12

identify differences between the first and second text-based models;

merge identified differences into a third block diagram model which has been converted to a plain text format;

and

store the identified differences in an electronic storage device.

14. The article of manufacture of claim **13**, wherein the instructions further cause the processor to:

identify blocks of text within the first and second text-based models which correspond to blocks of the high level block diagram-based model.

15. The article of manufacture of claim **13**, wherein the instructions further cause the processor to:

identify each block that has been added, modified, or deleted; and

store data indicating each block that has been added, modified, or deleted.

16. The article of manufacture of claim **13**, wherein the instructions further cause the processor to:

determine a longest common subsequence of characters in the first text-based model and the second text-based model; and

identify portions of the first and second text-based models that are not part of the longest common subsequence.

* * * * *