



US008170909B2

(12) **United States Patent**  
**Brown et al.**

(10) **Patent No.:** **US 8,170,909 B2**  
(45) **Date of Patent:** **May 1, 2012**

(54) **SYSTEM AND METHOD FOR MONITORING  
RETAIL STORE PERFORMANCE**

(56) **References Cited**

(75) Inventors: **Robert Kruger Brown**, Edina, MN  
(US); **Gregory Allen McDonald**,  
Shakopee, MN (US); **Caroline Louise  
Slettedahl**, Roseville, MN (US); **Robert  
Francis Foster**, Ramsey, MN (US);  
**Richard Scott Post**, Little Canada, MN  
(US)

U.S. PATENT DOCUMENTS  
5,097,328 A 3/1992 Boyette  
5,111,291 A 5/1992 Erickson et al.  
5,390,107 A \* 2/1995 Nelson et al. .... 705/7.13  
5,455,561 A 10/1995 Brown  
5,551,021 A 8/1996 Harada et al.  
5,581,625 A 12/1996 Connell  
5,974,219 A 10/1999 Fujita et al.  
6,011,537 A 1/2000 Slotznick  
6,016,139 A 1/2000 Terasawa et al.

(73) Assignee: **Target Brands, Inc.**, Minneapolis, MN  
(US)

(Continued)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 290 days.

FOREIGN PATENT DOCUMENTS  
JP 09-295698 11/1997  
(Continued)

(21) Appl. No.: **12/616,078**

(22) Filed: **Nov. 10, 2009**

OTHER PUBLICATIONS  
"Connecticut Department of Transportation," <http://www.dotct.state.ct.us/trafficcam.aspx?dotNav=>>, publicly available at least as early as Nov. 3, 2004, 1 page

(65) **Prior Publication Data**  
US 2010/0131340 A1 May 27, 2010

(Continued)

**Related U.S. Application Data**

(63) Continuation of application No. 10/980,574, filed on  
Nov. 3, 2004, now abandoned.

*Primary Examiner* — Lynda Jasmin  
*Assistant Examiner* — Sujay Koneru  
(74) *Attorney, Agent, or Firm* — Nixon & Vanderhye P.C.

(51) **Int. Cl.**  
**G06Q 10/00** (2006.01)  
**H04N 7/18** (2006.01)  
**G06K 9/00** (2006.01)


(57) **ABSTRACT**

A system for monitoring the performance of at least one task associated with operation of a retail store. The system includes at least one monitoring device positioned and adapted to provide images of at least one location within the retail store, with each image showing at least one factor related to performance of the at least one task. A controller is adapted to obtain and store images from the at least one monitoring device. An interface is adapted to enable a user to selectively view stored images and to manually analyze the at least one factor shown in the viewed images to evaluate the performance of the at least one task.

(52) **U.S. Cl.** ..... **705/7.42**; 705/7.11; 705/7.12;  
705/7.13; 705/7.15; 705/7.16; 705/7.17; 348/149;  
348/150; 348/156; 382/100

(58) **Field of Classification Search** ..... None  
See application file for complete search history.

**19 Claims, 6 Drawing Sheets**



# US 8,170,909 B2

Page 2

## U.S. PATENT DOCUMENTS

6,195,121 B1 2/2001 Huang et al.  
6,714,236 B1 3/2004 Wada et al.  
6,788,333 B1 9/2004 Uyttendaele et al.  
6,980,088 B2 \* 12/2005 Stambaugh ..... 340/286.09  
7,286,158 B1 \* 10/2007 Griebenow ..... 348/156  
7,792,256 B1 \* 9/2010 Arledge et al. .... 379/102.01  
2002/0016971 A1 \* 2/2002 Berezowski et al. .... 725/105  
2003/0098910 A1 \* 5/2003 Kim ..... 348/150  
2003/0107649 A1 \* 6/2003 Flickner et al. .... 348/150  
2003/0197782 A1 \* 10/2003 Ashe et al. .... 348/150  
2003/0212567 A1 11/2003 Shintani et al.  
2004/0203878 A1 \* 10/2004 Thomson ..... 455/456.1  
2005/0038695 A1 \* 2/2005 Matsko ..... 705/10  
2005/0073585 A1 4/2005 Ettinger et al.  
2006/0004581 A1 \* 1/2006 Claudatos et al. .... 704/275  
2006/0053342 A1 3/2006 Bazakos et al.  
2007/0152810 A1 \* 7/2007 Livingston et al. .... 340/539.1  
2008/0059274 A1 3/2008 Holliday

## FOREIGN PATENT DOCUMENTS

JP 2003-242587 8/2003  
JP 2003-244506 8/2003

## OTHER PUBLICATIONS

“Maidenhead Rowing Club River Thomas Web Camera-About the View,” [http://www.maidenheadrec.org.uk/webcam/things\\_to\\_spot.htm](http://www.maidenheadrec.org.uk/webcam/things_to_spot.htm), publicly available at least as early as Nov. 3, 2004, 5 pages.

“Today-Okoboji Live-Okoboji Online,” <http://www.okoboji.com/live/today/>, publicly available at least as early as Nov. 3, 2004, 4 pages.

“Web Cam: Iowa State University,” <http://www.iastate.edu/webcam.html>, publicly available at least as early as Nov. 3, 2004, 1 page.

\* cited by examiner




Fig. 1




Fig. 2




Fig. 3






Fig. 4A

Fig. 4B





Fig. 5



**Fig. 6**



## 1

## SYSTEM AND METHOD FOR MONITORING RETAIL STORE PERFORMANCE

### CROSS-REFERENCE TO RELATED APPLICATION

This application is a continuation of and claims priority under 35 U.S.C. §120 to U.S. patent application Ser. No. 10/980,574, filed Nov. 3, 2004, which is incorporated herein in its entirety.

### BACKGROUND OF THE INVENTION

As the retail industry continues to become more competitive, customer satisfaction is of paramount importance in establishing and maintaining customers. Customer satisfaction depends on a variety of factors such as a customer's perception of price, product availability, well-stocked shelves, ease of finding products within a retail store, cleanliness of the store, and friendliness of employees.

However, perhaps the most important factor regarding customer satisfaction is customer service. Of primary concern with regard to customer service is the amount of time a customer must wait when requiring assistance from a store employee. This includes, for example, time spent waiting for assistance at a customer service counter, at a merchandise counter and, of course, time spent waiting in check-out lanes. Generally speaking, the less time spent waiting for assistance, the more satisfied the customer.

### SUMMARY OF THE INVENTION

One embodiment of the present invention relates to a system for monitoring the performance of at least one task associated with operation of a retail store. The system comprises at least one monitoring device positioned and adapted to provide images of at least one location within the retail store, with each image showing at least one factor related to performance of the at least one task. The system further includes a controller and an interface. The controller is adapted to obtain and store images from the at least one monitoring device. The interface is configured to enable a user to selectively view stored images and to manually analyze the at least one factor shown in the viewed images to evaluate the performance of the at least one task.

### BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments of the invention will be described with respect to the figures, in which like reference numerals denote like elements, and in which:

FIG. 1 is block diagram illustrating one embodiment of a performance monitoring system according to the present invention.

FIG. 2 is a block diagram illustrating one embodiment of a performance monitoring system according to the present invention.

FIG. 3 is a block diagram illustrating one embodiment of a performance monitoring system according to the present invention.

FIG. 4A is an illustration of a graphical user interface for use with one embodiment of a performance monitoring system according to the present invention.

FIG. 4B illustrates in greater detail a portion of the graphical user interface of illustrated in FIG. 4A.

## 2

FIG. 5 is a flow diagram illustrating one embodiment of a process for monitoring the performance of a retail store according to the present invention.

FIG. 6 is a flow diagram illustrating another embodiment of a process for determining staffing requirements of a retail store according to the present invention.

### DETAILED DESCRIPTION

FIG. 1 is a block diagram generally illustrating one embodiment of a performance monitoring system 10 according to the present invention for monitoring the performance of at least one task associated with operation of a retail store 12. Performance monitoring system 10 includes a plurality of monitoring devices 14, each positioned to view a corresponding location 16 within retail store 12 and adapted to provide images of the corresponding location 16, each image showing at least one factor related to performance of at the at least one task. In one embodiment, monitoring devices 14 comprise cameras. In one embodiment, monitoring devices 14 comprise analog video cameras adapted to provide analog video of corresponding locations 16. In one embodiment, monitoring devices 14 comprise digital video cameras adapted to provide digital video of corresponding locations 16. As illustrated, analog video cameras 14a through 14f respectively correspond to store locations indicated as checkout lanes 14a, customer service desk 14b, electronics counter 14c, jewelry counter 14d, stockroom 14e, and receiving area 14f. Although illustrated as having analog video cameras 14a through 14f, monitoring system 10 can include more or fewer cameras 14 at locations other than locations 16 indicated by FIG. 1. Additionally, multiple cameras may be used to monitor a single store location, such as check lanes 16a.

Performance monitoring system 10 further includes a controller 18 and an interface 20. Controller 18 is adapted to automatically obtain and store still images from each of the monitoring devices 14 at selectable intervals. In one embodiment, controller 18 is adapted to obtain still images in a digital format, such as JPG format, for example, from analog video cameras 14 at selected intervals. In one embodiment, the selectable intervals are regular intervals, such as every fifteen minutes, for example.

Interface 20 is adapted to enable a user, such as a store manager, to selectively view the stored images and to manually analyze the at least one factor shown in the viewed images to evaluate the performance of the at least one task. Examples of such factors include number of employees and an amount of unloading time required when evaluating the task of unloading an incoming shipment of products at receiving dock 16f, and a number of customers awaiting service when evaluating the tasks of processing customers at check lanes 16a or assisting customers at customer service area 16b, electronics counter 16c, and jewelry counter 16d. Any number of other tasks associated with operation of retail store 12 can be similarly monitored by providing and positioning cameras 14 at other locations within retail store 12 as required.

By providing monitoring of selected areas of a retail store, performance monitoring system 10 enables a user, such as a store manager, to evaluate performance of selected tasks associated with the operation of the retail store. Based on such evaluations, performance of certain tasks can be adjusted to improve the store's performance. For example, staffing requirements at certain store locations, particularly at check lanes, can be evaluated and adjusted in order to minimize customer wait times and thereby likely improve customer satisfaction. Furthermore, by storing the images, monitoring



system **10** enables a user, such as a store manager, to evaluate the performance of tasks at any suitable time and does not require real-time monitoring.

Components of the present invention can be implemented in hardware via a microprocessor, programmable logic, or state machine, in firmware, or in software with a given device. In one aspect, at least a portion of the software programming is web-based and written in HTML and JAVA programming languages, including links to user interfaces, such as a Windows based operating system, and each of the main components may communicate via a network using a communication protocol. For example, the present invention may or may not use a TCP/IP protocol for data transport. Other programming languages and communication protocols suitable for use with the present invention will become apparent to those skilled in the art after reading the present application. Components of the present invention may also reside in software on one or more computer-readable mediums, which is defined herein to include any kind of memory, volatile or non-volatile, such as floppy disks, hard drives, read-only memory (ROM), CD-ROMs, flash memory, and random access memory (RAM).

FIG. 2 is a block and schematic diagram illustrating one embodiment of performance monitoring system **10** for retail store **12** as illustrated generally by FIG. 1. Performance monitoring system **10** includes a plurality of analog video cameras **14**, such as analog video cameras **14a** through **14e**. Each camera **14** is coupled to a digital video recorder (DVR) **30** via a corresponding link **32**. Each camera **14** is configured as a unique channel and provides an analog video signal of its associated store location **16** via corresponding link **32** to DVR **30**. DVR **30** includes an analog-to-digital converter (A/D) **34** which converts the analog video signal of each camera (or channel) **14** to a corresponding digital video having a digital video format, such as AVI, for example. DVR **30** is configured to store a predetermined amount of the digital video for each camera **14**. In one embodiment, for example, DVR **30** stores a day's worth of digital video for each camera **14**, with the stored digital video being replaced with the digital video for each subsequent day.

A server **40** is coupled to DVR **30** via a link **42**. In one embodiment, controller **18** comprises a monitoring system application (MSA) comprising an electronically readable code which is installed and operating on server **40**. In one embodiment, in addition to MSA **18**, store server **40** includes various other applications **44** related to operation of retail store **12**. MSA **18** is adapted to automatically retrieve digital still images for each camera **14** at regular intervals from DVR **30** via link **42**. In one embodiment, MSA **18** is adapted to retrieve the digital still images for each camera by selecting a single frame from a selectable time period of the digital video of each camera stored in DVR **30** and by converting the selected digital video frame from a digital video from, such as AVI, to a digital still picture format, such as JPG. In one embodiment, MSA **18** stores the retrieved digital still images for each camera in a memory **46** according to a directory and file naming convention. In an alternate embodiment, MSA **18** stores the retrieved digital still images in a database **48**. Although illustrated as being within server **40**, in other embodiments, database **48** could be located external to server **40**.

In one embodiment, interface **20** comprises a graphical user interface (GUI) adapted to display the digital still photos stored in database **46** and which is viewable via a personal computer (PC) **50** coupled to server **40** via a link **52**. Although illustrated as being viewed via PC **50**, in other embodiments,

GUI **20** may be viewed via other electronic viewing devices, such as a personal digital assistant (PDA) or Blackberry device, for example.

In one embodiment, DVR **30** comprises a portion of a security system **60** which further includes a plurality of analog video cameras **62** providing surveillance video of retail store **12** for purposes of assets protection. Surveillance system **60** is controlled by a security system application (SSA) **64** comprising a computer readable code which is installed and operating on store server **40**. In one embodiment, analog video cameras **16** are dedicated for use as surveillance cameras for assets protection and analog video cameras **14** are employed both as surveillance cameras by security system **60** and as monitoring cameras by performance monitoring system **10**. Security system **60** utilizes the entire video signal of analog video cameras **14** and **62** stored in DVR **30**, while performance monitoring system **10** utilizes the digital images obtained by controller **18** and stored in database **46**.

In one embodiment, security system **60** represents an existing surveillance system within retail store **12**. If analog video cameras **62** of security system **60** are already positioned or can be repositioned to view all locations desired to be monitored by performance monitoring system **10** (e.g., locations **16** as illustrated by FIG. 1), analog video cameras **14** are not required and MSA **18** of performance monitoring system **10** can obtain images as necessary from existing analog video cameras **62**. However, if analog video cameras **62** of security system **60** are not, or cannot, be positioned to view all desired store locations **16**, analog video cameras **14** are added to security system **60** and positioned to view the otherwise non-observed areas. In such a scenario, while the primary function of analog video cameras **14** is to provide images for performance monitoring system **10**, analog video signals provided by analog video cameras **14** via links **32** can also be utilized for assets protection purposes by security system **60**.

In one embodiment, in lieu of a digital recording device, recording device **30** comprises some type of analog recording device, such as one or more video tape recording devices adapted to record the analog video signals received via links **32** from each camera, or channel. In such an embodiment, performance monitoring system **10** further includes a "frame grabber" (FG) **70** adapted to capture at regular intervals a single frame of the analog video signal provided by each camera **14** prior to the analog video signal being recorded by the analog recording device, and to convert the single frame to a digital still image which is subsequently stored in memory **46**.

In one embodiment, cameras **14** comprise digital still cameras configured to provide digital still images of store locations **16** at intervals as directed by MSA **18**. In this embodiment, digital still images from cameras **14** can be stored directly to database **46** as directed by MSA **18**. As such, recording device **30** is not required in this embodiment.

FIG. 3 is a block diagram illustrating one embodiment of a performance monitoring system **110** according to the present invention configured as a network system distributed across a plurality of retail stores **112** and a headquarters facility **113** of a retail corporation. In one embodiment, as illustrated, each retail store **112a** through **112n** respectively includes a monitoring system **110a** to **110n**. In one embodiment, monitoring systems **110** are similar to monitoring system **10** of retail store **12** described above by FIG. 2, with each monitoring system **110** including a plurality of digital video cameras and a digital recording device (indicated generally at **114**), and an MSA **118** and database **146** installed and operating on a server **140**. Each monitoring system **110** further includes a GUI **120** viewable via an electronic viewing device, such as PC **150**.



Headquarters facility **113** includes a server **140x** and at least one electronic viewing device, such as PC **150x**, for viewing GUI **120x**.

Monitoring systems **110a** to **110n** are respectively coupled to a network communications link **180** via communications links **176a** to **176n** and headquarters facility **113** is coupled to network communications link **180** via communications link **176x**. Network communication link **180**, as employed herein, includes an Internet communications link, an intranet communication link, or similar high-speed communication link. In one embodiment, network communication link **18** includes an Internet communications link **182**. Internet communications link permits communication between performance monitoring systems **110** of stores **112** and between performance monitoring systems **110** of stores **110** and headquarters facility **113**.

In one embodiment, network communications link **180** includes an Intranet communications link **184** linking retail stores **112** and headquarters facility **113** by means of Internet communications link **182**. Intranet communications link **184** provides a controlled-access communications link between stores **112** and headquarters facility **113** which is accessible via a password or other user-recognition mechanism.

MSA **118** of monitoring system **110** of each retail store **112** is configured to obtain and store digital images of desired locations within retail store **112** (e.g. locations **16** as illustrated by FIG. **1**) in memory **146** of server **140** of corresponding retail store **112**. In other embodiments, in lieu of monitoring systems **110** storing digital images in a memory **146** local to each retail store **112**, monitoring systems **110** store digital images obtained from corresponding camera and recording devices **114** in a central data base, such as database **192** within server **140x** of headquarters facility **113** or database **194** coupled to network communications link **180** via a communications link **196**.

In one embodiment, the digital images obtained by MSAs **118** are viewable by users via GUIs **120** which access the digital images stored in data bases **146** of servers **140** via a website **190** located on server **140x** of headquarters facility **113** and network communications link **180**. Although illustrated as being located on server **140x**, in other embodiments, website **190** could be located on any server coupled to network communications link **180**.

In one embodiment, as described briefly above, intranet communications link **184** comprises a controlled-access communications link between stores **112** and headquarters facility **113**. In one embodiment, to access the digital photos stored in memories **146**, a user, such as a manager of retail store **112a**, enters the URL (Uniform Resource Location), or address, of website **190** into a Web browser located on PC **150a** which subsequently locates website **190** via intranet connection **186**. To access website **190**, the user enters a username and password. Upon entering a valid username and password, the user can access and view selected stored digital images via GUI **120a** which is displayed by PC **150a**. Although described as being accessed via PC **150**, website **190** can be accessed via other types of electronic viewing devices, such as a PDA, for example, and from any location that provides a communication link to intranet **184**.

In one embodiment, access to viewing stored images is limited based on a user's logon ID. For instance, in one embodiment, based on the user's unique logon ID, a user associated with a given retail store **112** can access only stored images corresponding to the given retail store **112**. For example, a manager of retail store **112a** can access only images of locations within retail store **112a** which are stored within memory **146a**, and cannot access images of other retail

stores, such as retail store **112b**. In other embodiments, other users, such as certain employees associated with headquarters facility **113**, can access images of all retail stores **112a** to **112n** respectively stored in memories **146a** to **146n**. In one embodiment, access to viewing stored images is limited based a location from which access is initiated. For example, in one embodiment, each PC, or workstation, **150** has unique hardware identifier which corresponds, at least in part, to the retail store **112** in which PC **150** is located. As such, a user accessing stored images via PC **150a**, for example, is limited to viewing only those images stored in memory **146a** corresponding to retail store **112a**.

FIG. **4A** is an illustrative example of GUI **120** for accessing and viewing digital images provided by performance monitoring systems **110** via website **190** as described above by FIG. **3**. GUI **120** includes an options menu **200**, an image selection menu **202**, and an image display area **204**. Options menu **200** includes a pull-down menu **206** that enables a user to select a retail store **112** from which the user would like to view digital images provided by the store's performance monitoring system **110**. In one embodiment, pull-down menu **206** comprises a list of unique identification numbers corresponding to each retail store **112** (for example, "RS**123**" as illustrated in FIG. **4**) from which the user can select, such as by selecting the identification number corresponding to the desired retail store with a mouse. Similarly, options menu **200** includes a pull-down menu **208** that enables a user to select a desired date from which the user would like to view images for the desired retail store **112** as selected via pull-down menu **206**.

As described above, in one embodiment, access of images is limited based on a user's unique logon ID or location. As such, in one embodiment, pull-down menu **206** comprises the unique identification numbers of only those retail stores **112** to which the user is allowed access as based on the user's password. Thus, for a user having access to only one retail store **112**, options menu **200** will include only pull-down menu **208** enabling the user to select a desired date from which to view images of only the retail store **112** with which the user is associated. In lieu of pull-down menu **206**, only the unique identification number of the store with which the user is associated will be displayed.

Image selection menu comprises a column **210** of descriptions of monitored locations within the selected retail store (e.g. locations **16** of retail store **12** as illustrated by FIG. **1**). Each description of column **210** is followed by a row **212** of icons **214** representative of stored images corresponding to the described location within the selected retail store. In one embodiment, each row comprises 24 icons with each icon representative of images acquired during one hour of the day selected via pull-down menu **208**. In one embodiment, as indicated at **216**, the columns of icons are labeled as columns "01" through "23" with the icons in the column labeled "00" representative of digital images acquired between 12:00 am and 1:00 am, the icons in the column labeled "01" representative of digital images acquired between 1:00 am and 2:00 am, and so on.

In one embodiment, wherein images of desired locations within a retail store are obtained on 15-minute intervals, each icon **214** is partitioned into four areas **214a** through **214d**, with each area being representative of one of the four photos acquired during the corresponding hour. For example, as illustrated by the enlarged view of FIG. **4B**, icon **214** is representative of images of a first group of check lanes ("check lanes **1**") acquired during time period "23", wherein time period "23" corresponds to the time period between 11:00 pm to 12:00 am. As such, areas **214a**, **214b**, **214c** and



214*d* respectively represent images of the first group of check lanes acquired at 11:00 pm, 11:15 pm, 11:30 pm and 11:45 pm.

After selecting a desired store and a desired date via pull-down menus 206 and 208, a user chooses an image to be viewed by selecting one of the icons 214. In one embodiment, a user selects a desired icon, or desired area of an icon, by mouse-clicking the desired icon 214. Upon selecting a desired image, the image is displayed within image viewing area 204. In one embodiment, image viewing area 204 includes a title field 218 displaying the description of the store location from column 210 corresponding to the selected image (i.e. the camera from which the selected image originated) and an indication of a time frame 220 corresponding to the selected image.

FIG. 5 is a flow diagram illustrating one embodiment of a process 250 according to the present invention for monitoring performance of at least one task associated with operation of a retail store. Process 250 begins at step 252 where cameras are provided at desired locations within the retail store where certain tasks which are desired to be monitored are performed, such as positions 16 illustrated by FIG. 1. In one embodiment, as described above, the cameras may be analog video cameras providing analog video signals which are converted into digital video format. In one embodiment, the cameras may be digital video cameras providing a digital video signal. In one embodiment, the cameras may be digital still cameras providing digital still photos. In one embodiment, the cameras may comprise a portion of an existing security surveillance system.

At step 254, images are obtained at selectable intervals from the cameras positioned at step 252. In one embodiment, the images are obtained at regular intervals, such as, for example, 15-minute intervals. In one embodiment, wherein the cameras are analog video cameras, digital still photos are extracted from the digital video signals obtained from the cameras' analog video signals, wherein the extracted images comprise digital still photos of the corresponding areas monitored by the cameras. At step 254, the images obtained at step 254 are stored in a memory. In one embodiment, the obtained images are stored in a database.

At step 258, a user, such as a store manager, views selected images obtained and stored via steps 254 and 256. At step 260, the user manually analyzes at least one factor shown in the viewed images that is related to the performance of a given task in order to evaluate how well the given task was performed. For example, a user may select images of a given location provided by one or more cameras over a certain time period to evaluate the performance of a task that is carried out at that location. For example, a user may select one or more cameras positioned at receiving dock 16*f* to monitor how long it takes to unload an incoming shipment of products. In this instance, factors related to the unloading of the incoming shipment may include the number of employees engaged in unloading the truck, the size of packages being unloaded, and the time required to unload the truck. From the images, the store manager can evaluate generally the number of employees engaged in unloading the truck and from the time interval of the images selected, estimate how long it took to unload the truck.

At step 262, based on the evaluation of the images at step 260, the user may determine that performance of the task needs to be improved. For example, if the truck took too long to unload, more employees may be assigned to this task for future shipments. Also, if from the images it appeared that

there were too many employees assigned to unload the truck, fewer employees may be assigned to unload future shipments.

FIG. 6 is a flow diagram illustrating one embodiment of a process 270 according to the present invention for determining staffing requirements at one or more check lanes of a retail store. Process 270 begins at step 272 where still images of the one or more check lanes are provided. In one embodiment, the still images are digital images. At step 274, the still images are stored in a storage device.

At step 276, a user, such as a store manager, selects for viewing one or more images of the one or more check lanes corresponding to a desired time interval. In one embodiment, the digital still images are viewed via an electronic viewing device, such as via the display of a personal computer or a personal digital assistant (PDA). At step 278, the user manually analyzes the one or more selected images to assess generally the customer conditions at the one or more check lanes. If the images permit, a store manager may thoroughly assess customer conditions by manually counting a number of customers awaiting service at the one or more check lanes. The user may also determine a number of cashiers on duty and estimate a length of time customers wait before being served.

At step 278, the store manager may adjust the number of cashiers on duty at that time of the day based on the conditions shown in the images viewed during step 276. For example, with reference to FIG. 1, a store manager may view images obtained from camera 14*a* during a selected time interval, such as between 4 pm and 5 pm on a given date, to evaluate the performance of check lanes 16*a*. For instance, if controller 18 obtains images from camera 14*a* at fifteen minute intervals, the store manager can view the five images (i.e., 4:00, 4:15, 4:30, 4:45 and 5:00) to determine the number of check lanes open (i.e., staffed with a cashier) and the number of customers at each open check lane in order to determine whether more or fewer check lanes should be open during that time of the day. Also, a store manager may view images of a same time period each day over an extended time period (e.g., a week, a month, etc.) to determine trends in customer patterns in order to predict how many cashiers should be available and how many check lanes should be open at a given time.

One aspect of the present invention, as described briefly above with respect to FIG. 2, relates to retrofitting a retail store's existing security system to provide a performance monitoring system according to the present invention, wherein the existing security system includes a plurality of video cameras each providing a video signal of a corresponding location within the retail store. The retrofitting process includes evaluating the positions of the existing video cameras and to select those existing video cameras that provide images of store locations desired to be monitored. If all desired store locations are not adequately monitored, the process includes adding one or more video cameras to the existing security system in order to adequately monitor such store locations.

The process further includes providing a controller adapted to capture digital images from the video signals of selected existing video cameras and newly added video cameras. The process further includes providing a storage device in which to store the captured digital images and providing an interface adapted to enable a user to selectively view the stored digital images in order to evaluate performance of one or more operations taking place at the one or more locations viewed in the digital images.

Although the invention has been described with respect to particular embodiments, such embodiments are for illustrative purposes only and should not be considered to limit the



invention. Various alternatives and changes will be apparent to those of ordinary skill in the art.

What is claimed is:

1. A method for actively monitoring activities in a retail store enterprise, the method comprising:
  - capturing, with a plurality of image capture devices positioned at a first plurality of positions at a first retail store location, a first plurality of images reflecting activities occurring at the first retail store location, wherein the first plurality of positions include at least customer checkout lanes, a customer service desk and a receiving area of the first retail store location;
  - capturing, with a plurality of image capture devices positioned at a second plurality of positions at a second retail store location, a second plurality of images reflecting activities occurring at the second enterprise location, wherein the second plurality of positions include at least customer checkout lanes, a customer service desk and a receiving area of the second retail store location;
  - associating each of the images with a unique identifier comprising time, position and location data;
  - receiving user access credentials and selectively presenting, at a terminal positioned at a location remote from said first and second retail store locations, a user interface including a first region and a second region based on permissions associated with the credentials, the first region including an array of input areas each associated with at least a time and at least one of the first or second pluralities of positions, the second region including an output area to display an image;
  - receiving user input selecting a location and one of the input areas;
  - simultaneously displaying i) in the second region, in response to the user input, one or more output images associated with the selected location and the time and the at least one position associated with the selected input area, and ii) in the first region, the array of input areas, the output images showing at least one factor relating to employee performance of at least one task associated with operation of the first or second retail store;
  - analyzing the at least one factor and evaluating the employee performance of the at least one task, the at least one factor including one of a number of employees and an amount of unloading time required when unloading an incoming shipment received at the receiving area, a number of customers in the customer checkout lanes, a length of time customers wait before being served, and a number of customers at the customer service desk; and
  - adjusting the employee performance of the at least one task based on the step of analyzing the at least one factor, the adjusting being practiced at least by adjusting staffing requirements at a corresponding one of the first or second plurality of positions, the adjusting comprising adjusting a number of cashiers on duty at a specific time of day based on the number of customers in the customer checkout lanes at said specific time of day or based on the length of time customers wait before being served at said specific time of day.
2. The method of claim 1, wherein the location remote from said first and second retail store locations comprises an enterprise headquarters.
3. The method of claim 1, further comprising:
  - presenting, at a terminal positioned at the first retail store location, a user interface including said first region and said second region;
  - receiving user input selecting one of the input areas; and

simultaneously displaying in the user interface located at the first retail store location i) in the second region, in response to the user input, one or more output images associated with the time and position associated with the selected input area, and ii) in the first region, the array of input areas.

4. The method of claim 1, wherein the user interface further includes a third region that includes one or more user selection input areas to receive input selecting a date and a retail store location.

5. The method of claim 4, wherein said one or more user selection input areas are displayed simultaneously with the output image and the array of input areas.

6. The method of claim 1, further comprising receiving, at the remote location, user credentials and authenticating said credentials to determine the images to which a user has access.

7. The method of claim 1, further comprising determining permissions to retrieve and view stored images based on the retail store location from which access is initiated.

8. The method of claim 1, wherein the displayed images are frames of video.

9. The method of claim 1, wherein the user interface comprises a secure website.

10. An enterprise monitoring system comprising:
 

- video monitoring devices located at a plurality of locations within each of a plurality of retail stores in a retail enterprise, at least some of the locations having fields of view covering areas in which retail point of sale activity occurs, the plurality of locations including at least customer checkout lanes, a customer service desk and a receiving area;

a local video management system at a first retail store operatively coupled to the respective video monitoring devices, wherein the local video management system transmits video for storage at predetermined time intervals;

a local display device at the first retail store operatively coupled to the local video management system, wherein the local display device selectively displays video based on access credentials for a local user of the local video management system and wherein the display device presents a user interface that simultaneously displays a collection of user selectable input regions associated with a plurality of different times and locations and a video area to display one or more frames of a video associated with a selected input region; and

an enterprise video management system remote from and communicatively coupled to the local video management system, wherein the enterprise video management system receives users' access credentials and selectively displays the one or more video frames from one or more of the plurality of retail stores based on permissions associated with the credentials, the one or more video frames showing at least one factor relating to employee performance of at least one task associated with operation of the plurality of retail stores, and each of the plurality of retail stores being identified by a unique identification number,

wherein the enterprise video management system locally presents a user interface that simultaneously includes a collection of user selectable input regions associated with a plurality of different times and locations and a video area to display one or more frames of a video associated with a selected input region, wherein each of the user selectable input regions is associated with one of a plurality of predefined time periods, and wherein each



**11**

of the predefined time periods is associated with a plurality of video frames over time intervals within the respective time period,

the enterprise video management system enabling an analysis of the at least one factor and evaluating the employee performance of the at least one task, the at least one factor including one of a number of employees and an amount of unloading time required when unloading an incoming shipment received at the receiving area, a number of customers in the customer checkout lanes, a length of time customers wait before being served, and a number of customers at the customer service desk, and the enterprise video management system further enabling adjustment of the employee performance of the at least one task based on the analysis, the adjusting comprising adjusting staffing requirements at a corresponding one of the plurality of locations, and the adjusting comprising adjusting a number of cashiers on duty at a specific time of day based on the number of customers in the customer checkout lanes at said specific time of day or based on the length of time customers wait before being served at said specific time of day.

**11.** The system of claim **10**, further comprising a local video management system at a second retail store and a local display device at the second retail store that selectively displays video based on access credentials of a local user, wherein the display device at the second retail store presents a user interface that simultaneously includes a collection of user selectable input regions associated with a plurality of

**12**

different times and locations and a video area to display one or more frames of a video associated with a selected input region.

**12.** The system of claim **10**, wherein each of the input regions comprises an icon that is uniquely associated with video taken at a predetermined time at a particular location within a given retail store.

**13.** The system of claim **12**, wherein the display presents video in response to a user's selection of an icon.

**14.** The system of claim **10**, wherein the video captured by the video monitoring devices is stored at a central repository communicatively coupled to the enterprise video management system.

**15.** The system of claim **14**, wherein frames of video accessed for display at the user interface at the first retail store are transmitted from the central repository under the control of the enterprise video management system.

**16.** The system of claim **10**, wherein access permissions for a user are determined based on enterprise level credentials.

**17.** The system of claim **11**, wherein access for users at the first and second retail stores is restricted to video taken at the respective stores.

**18.** The system of claim **10**, wherein access for users at the enterprise video management system includes substantially all stores in the retail enterprise.

**19.** The system of claim **10**, wherein the video monitoring devices capture still images at predetermined intervals.

\* \* \* \* \*