



US008175681B2

(12) **United States Patent**
Hartmann et al.

(10) **Patent No.:** **US 8,175,681 B2**
(45) **Date of Patent:** **May 8, 2012**

(54) **COMBINATION OF ELECTROMAGNETIC AND ELECTROPOTENTIAL LOCALIZATION**

(75) Inventors: **Steven L. Hartmann**, Superior, CO (US); **Andrew Bzostek**, Erie, CO (US); **Bradley A. Jascob**, Broomfield, CO (US)

(73) Assignee: **Medtronic Navigation Inc.**, Louisville, CO (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 635 days.

(21) Appl. No.: **12/336,085**

(22) Filed: **Dec. 16, 2008**

(65) **Prior Publication Data**

US 2010/0152571 A1 Jun. 17, 2010

(51) **Int. Cl.**
A61B 5/05 (2006.01)
A61B 19/00 (2006.01)

(52) **U.S. Cl.** **600/424; 600/427; 128/899**

(58) **Field of Classification Search** **600/424, 600/407, 427; 128/899; 607/122**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,576,781 A	3/1926	Phillips
1,735,726 A	11/1929	Bornhardt
2,407,845 A	9/1946	Nemeyer
2,650,588 A	9/1953	Drew
2,697,433 A	12/1954	Sehnder
3,016,899 A	1/1962	Stenvall
3,017,887 A	1/1962	Heyer
3,061,936 A	11/1962	Dobbeleer
3,073,310 A	1/1963	Mocarski
3,109,588 A	11/1963	Polhemus et al.

3,294,083 A	12/1966	Alderson
3,367,326 A	2/1968	Frazier
3,439,256 A	4/1969	Kahne
3,577,160 A	5/1971	White
3,614,950 A	10/1971	Rabey
3,644,825 A	2/1972	Davis, Jr. et al.
3,674,014 A	7/1972	Tillander
3,702,935 A	11/1972	Carey et al.
3,704,707 A	12/1972	Halloran
3,821,469 A	6/1974	Whetstone et al.
3,837,347 A	9/1974	Tower
3,868,565 A	2/1975	Kuipers
3,941,127 A	3/1976	Froning
3,983,474 A	9/1976	Kuipers
3,995,623 A	12/1976	Blake et al.
4,017,858 A	4/1977	Kuipers
4,037,592 A	7/1977	Kronner
4,052,620 A	10/1977	Brunnett
4,054,881 A	10/1977	Raab
4,117,337 A	9/1978	Staats

(Continued)

FOREIGN PATENT DOCUMENTS

CA 964149 A1 3/1975

(Continued)

OTHER PUBLICATIONS

“Prestige Cervical Disc System Surgical Technique”, 12 pgs.

(Continued)


Primary Examiner — Michael Rozanski

(74) *Attorney, Agent, or Firm* — Harness, Dickey

(57) **ABSTRACT**

A navigation system or combination of navigation systems can be used to provide two or more types of navigation or modalities of navigation to navigate a single instrument. The single instrument can be positioned within the patient and tracked. For example, both an Electromagnetic (EM) and Electropotential (EP) navigation system can be used to navigate an instrument within a patient.

29 Claims, 8 Drawing Sheets



US 8,175,681 B2

Page 2

U.S. PATENT DOCUMENTS					
4,173,228	A	11/1979	Van Steenwyk et al.	4,779,212	A 10/1988 Levy
4,182,312	A	1/1980	Mushabac	4,782,239	A 11/1988 Hirose et al.
4,202,349	A	5/1980	Jones	4,788,481	A 11/1988 Niwa
4,228,799	A	10/1980	Anichkov et al.	4,791,934	A 12/1988 Brunnett
4,256,112	A	3/1981	Kopf et al.	4,793,355	A 12/1988 Crum et al.
4,262,306	A	4/1981	Renner	4,794,262	A 12/1988 Sato et al.
4,287,809	A	9/1981	Egli et al.	4,797,907	A 1/1989 Anderton
4,298,874	A	11/1981	Kuipers	4,801,297	A 1/1989 Mueller
4,314,251	A	2/1982	Raab	4,803,976	A 2/1989 Frigg et al.
4,317,078	A	2/1982	Weed et al.	4,804,261	A 2/1989 Kirschen
4,319,136	A	3/1982	Jinkins	4,805,615	A 2/1989 Carol
4,328,548	A	5/1982	Crow et al.	4,809,694	A 3/1989 Ferrara
4,328,813	A	5/1982	Ray	4,821,200	A 4/1989 Oberg
4,339,953	A	7/1982	Iwasaki	4,821,206	A 4/1989 Arora
4,341,220	A	7/1982	Perry	4,821,731	A 4/1989 Martinelli et al.
4,346,384	A	8/1982	Raab	4,822,163	A 4/1989 Schmidt
4,358,856	A	11/1982	Stivender et al.	4,825,091	A 4/1989 Breyer et al.
4,368,536	A	1/1983	Pfeiler	4,829,373	A 5/1989 Leberl et al.
4,396,885	A	8/1983	Constant	4,836,778	A 6/1989 Baumrind et al.
4,396,945	A	8/1983	DiMatteo et al.	4,838,265	A 6/1989 Cosman et al.
4,403,321	A	9/1983	Kruger	4,841,967	A 6/1989 Chang et al.
4,418,422	A	11/1983	Richter et al.	4,845,771	A 7/1989 Wislocki et al.
4,419,012	A	12/1983	Stephenson et al.	4,849,692	A 7/1989 Blood
4,422,041	A	12/1983	Lienau	4,860,331	A 8/1989 Williams et al.
4,431,005	A	2/1984	McCormick	4,862,893	A 9/1989 Martinelli
4,485,815	A	12/1984	Amplatz et al.	4,869,247	A 9/1989 Howard, III et al.
4,506,676	A	3/1985	Duska	4,875,165	A 10/1989 Fencil et al.
4,506,680	A	3/1985	Stokes	4,875,478	A 10/1989 Chen
4,543,959	A	10/1985	Sepponen	4,884,566	A 12/1989 Mountz et al.
4,548,208	A	10/1985	Niemi	4,889,526	A 12/1989 Rauscher et al.
4,571,834	A	2/1986	Fraser et al.	4,896,673	A 1/1990 Rose et al.
4,572,198	A	2/1986	Codrington	4,905,698	A 3/1990 Strohl, Jr. et al.
4,583,538	A	4/1986	Onik et al.	4,923,459	A 5/1990 Nambu
4,584,577	A	4/1986	Temple	4,931,056	A 6/1990 Ghajar et al.
4,608,977	A	9/1986	Brown	4,945,305	A 7/1990 Blood
4,613,866	A	9/1986	Blood	4,945,914	A 8/1990 Allen
4,617,925	A	10/1986	Laitinen	4,951,653	A 8/1990 Fry et al.
4,618,978	A	10/1986	Cosman	4,955,891	A 9/1990 Carol
4,619,246	A	10/1986	Molgaard-Nielsen et al.	4,961,422	A 10/1990 Marchosky et al.
4,621,628	A	11/1986	Brudermann	4,977,655	A 12/1990 Martinelli
4,625,718	A	12/1986	Olerud et al.	4,989,608	A 2/1991 Ratner
4,638,798	A	1/1987	Shelden et al.	4,991,579	A 2/1991 Allen
4,642,786	A	2/1987	Hansen	5,002,058	A 3/1991 Martinelli
4,645,343	A	2/1987	Stockdale et al.	5,005,592	A 4/1991 Cartmell
4,649,504	A	3/1987	Krouglicof et al.	5,013,317	A 5/1991 Cole et al.
4,651,732	A	3/1987	Frederick	5,016,639	A 5/1991 Allen
4,653,509	A	3/1987	Oloff et al.	5,017,139	A 5/1991 Mushabac
4,659,971	A	4/1987	Suzuki et al.	5,027,818	A 7/1991 Bova et al.
4,660,970	A	4/1987	Ferrano	5,030,196	A 7/1991 Inoue
4,673,352	A	6/1987	Hansen	5,030,222	A 7/1991 Calandrucchio et al.
4,688,037	A	8/1987	Krieg	5,031,203	A 7/1991 Trecha
4,696,304	A	9/1987	Chin	5,035,246	A 7/1991 Heuvelmans et al.
4,701,049	A	10/1987	Beckman et al.	5,042,486	A 8/1991 Pfeiler et al.
4,705,395	A	11/1987	Hageniers	5,047,036	A 9/1991 Koutrouvelis
4,705,401	A	11/1987	Addleman et al.	5,050,608	A 9/1991 Watanabe et al.
4,706,665	A	11/1987	Gouda	5,054,492	A 10/1991 Scribner et al.
4,709,156	A	11/1987	Murphy et al.	5,057,095	A 10/1991 Fabian
4,710,708	A	12/1987	Rorden et al.	5,059,789	A 10/1991 Salcudean
4,719,419	A	1/1988	Dawley	5,076,285	A 12/1991 Hess et al.
4,722,056	A	1/1988	Roberts et al.	5,078,140	A 1/1992 Kwoh
4,722,336	A	2/1988	Kim et al.	5,078,714	A 1/1992 Katims
4,723,544	A	2/1988	Moore et al.	5,079,699	A 1/1992 Tuy et al.
4,727,565	A	2/1988	Ericson	5,086,401	A 2/1992 Glassman et al.
RE32,619	E	3/1988	Damadgian	5,094,241	A 3/1992 Allen
4,733,969	A	3/1988	Case et al.	5,097,839	A 3/1992 Allen
4,737,032	A	4/1988	Addleman et al.	5,098,426	A 3/1992 Sklar et al.
4,737,794	A	4/1988	Jones	5,099,845	A 3/1992 Besz et al.
4,737,921	A	4/1988	Goldwasser et al.	5,099,846	A 3/1992 Hardy
4,742,356	A	5/1988	Kuipers	5,105,829	A 4/1992 Fabian et al.
4,742,815	A	5/1988	Ninan et al.	5,107,839	A 4/1992 Houdek et al.
4,743,770	A	5/1988	Lee	5,107,843	A 4/1992 Aarnio et al.
4,743,771	A	5/1988	Sacks et al.	5,107,862	A 4/1992 Fabian et al.
4,745,290	A	5/1988	Frankel et al.	5,109,194	A 4/1992 Cantaloube
4,750,487	A	6/1988	Zanetti	5,119,817	A 6/1992 Allen
4,753,528	A	6/1988	Hines et al.	5,142,930	A 9/1992 Allen et al.
4,761,072	A	8/1988	Pryor	5,143,076	A 9/1992 Hardy et al.
4,764,016	A	8/1988	Johansson	5,152,288	A 10/1992 Hoenig et al.
4,771,787	A	9/1988	Wurster et al.	5,160,337	A 11/1992 Cosman
				5,161,536	A 11/1992 Vilkomerson et al.

US 8,175,681 B2

5,167,239 A	12/1992	Cohen et al.	5,391,199 A	2/1995	Ben-Haim
5,178,164 A	1/1993	Allen	5,394,457 A	2/1995	Leibinger et al.
5,178,621 A	1/1993	Cook et al.	5,394,875 A	3/1995	Lewis et al.
5,186,174 A	2/1993	Schlondorff et al.	5,397,329 A	3/1995	Allen
5,187,475 A	2/1993	Wagener et al.	5,398,684 A	3/1995	Hardy
5,188,126 A	2/1993	Fabian et al.	5,399,146 A	3/1995	Nowacki et al.
5,190,059 A	3/1993	Fabian et al.	5,400,384 A	3/1995	Fernandes et al.
5,193,106 A	3/1993	DeSena	5,402,801 A	4/1995	Taylor
5,197,476 A	3/1993	Nowacki et al.	5,408,409 A	4/1995	Glassman et al.
5,197,965 A	3/1993	Cherry et al.	5,413,573 A	5/1995	Koivukangas
5,198,768 A	3/1993	Keren	5,417,210 A	5/1995	Funda et al.
5,198,877 A	3/1993	Schulz	5,419,325 A	5/1995	Dumoulin et al.
5,207,688 A	5/1993	Carol	5,423,334 A	6/1995	Jordan
5,211,164 A	5/1993	Allen	5,425,367 A	6/1995	Shapiro et al.
5,211,165 A	5/1993	Dumoulin et al.	5,425,382 A	6/1995	Golden et al.
5,211,176 A	5/1993	Ishiguro et al.	5,426,683 A	6/1995	O'Farrell, Jr. et al.
5,212,720 A	5/1993	Landi et al.	5,426,687 A	6/1995	Goodall et al.
5,214,615 A	5/1993	Bauer	5,427,097 A	6/1995	Depp
5,219,351 A	6/1993	Teubner et al.	5,429,132 A	7/1995	Guy et al.
5,222,499 A	6/1993	Allen et al.	5,433,198 A	7/1995	Desai
5,224,049 A	6/1993	Mushabac	RE35,025 E	8/1995	Anderton
5,228,442 A	7/1993	Imran	5,437,277 A	8/1995	Dumoulin et al.
5,230,338 A	7/1993	Allen et al.	5,443,066 A	8/1995	Dumoulin et al.
5,230,623 A	7/1993	Guthrie et al.	5,443,489 A	8/1995	Ben-Haim
5,233,990 A	8/1993	Barnea	5,444,756 A	8/1995	Pai et al.
5,237,996 A	8/1993	Waldman et al.	5,445,144 A	8/1995	Wodicka et al.
5,249,581 A	10/1993	Horbal et al.	5,445,150 A	8/1995	Dumoulin et al.
5,251,127 A	10/1993	Raab	5,445,166 A	8/1995	Taylor
5,251,635 A	10/1993	Dumoulin et al.	5,446,548 A	8/1995	Gerig et al.
5,253,647 A	10/1993	Takahashi et al.	5,447,154 A	9/1995	Cinquin et al.
5,255,680 A	10/1993	Darrow et al.	5,448,610 A	9/1995	Yamamoto et al.
5,257,636 A	11/1993	White	5,453,686 A	9/1995	Anderson
5,257,998 A	11/1993	Ota et al.	5,456,718 A	10/1995	Szymaitis
5,261,404 A	11/1993	Mick et al.	5,457,641 A	10/1995	Zimmer et al.
5,265,610 A	11/1993	Darrow et al.	5,458,718 A	10/1995	Venkitachalam
5,265,611 A	11/1993	Hoening et al.	5,464,446 A	11/1995	Dreessen et al.
5,265,622 A	11/1993	Barbere	5,469,847 A	11/1995	Zinreich et al.
5,269,759 A	12/1993	Hernandez et al.	5,478,341 A	12/1995	Cook et al.
5,271,400 A	12/1993	Dumoulin et al.	5,478,343 A	12/1995	Ritter
5,273,025 A	12/1993	Sakiyama et al.	5,480,422 A	1/1996	Ben-Haim
5,274,551 A	12/1993	Corby, Jr.	5,480,439 A	1/1996	Bisek et al.
5,279,309 A	1/1994	Taylor et al.	5,483,961 A	1/1996	Kelly et al.
5,285,787 A	2/1994	Machida	5,485,849 A	1/1996	Panescu et al.
5,291,199 A	3/1994	Overman et al.	5,487,391 A	1/1996	Panescu
5,291,889 A	3/1994	Kenet et al.	5,487,729 A	1/1996	Avellanet et al.
5,295,483 A	3/1994	Nowacki et al.	5,487,757 A	1/1996	Truckai et al.
5,297,549 A	3/1994	Beatty et al.	5,490,196 A	2/1996	Rudich et al.
5,299,253 A	3/1994	Wessels	5,494,034 A	2/1996	Schlondorff et al.
5,299,254 A	3/1994	Dancer et al.	5,503,416 A	4/1996	Aoki et al.
5,299,288 A	3/1994	Glassman et al.	5,512,920 A	4/1996	Gibson
5,300,080 A	4/1994	Clayman et al.	5,513,637 A	5/1996	Twiss et al.
5,305,091 A	4/1994	Gelbart et al.	5,514,146 A	5/1996	Lam et al.
5,305,203 A	4/1994	Raab	5,515,160 A	5/1996	Schulz et al.
5,306,271 A	4/1994	Zinreich et al.	5,517,990 A	5/1996	Kalfas et al.
5,307,072 A	4/1994	Jones, Jr.	5,522,874 A	6/1996	Gates
5,309,913 A	5/1994	Kormos et al.	5,531,227 A	7/1996	Schneider
5,315,630 A	5/1994	Sturm et al.	5,531,520 A	7/1996	Grimson et al.
5,316,024 A	5/1994	Hirschi et al.	5,542,938 A	8/1996	Avellanet et al.
5,318,025 A	6/1994	Dumoulin et al.	5,543,951 A	8/1996	Moehrmann
5,320,111 A	6/1994	Livingston	5,546,940 A	8/1996	Panescu et al.
5,325,728 A	7/1994	Zimmerman et al.	5,546,949 A	8/1996	Frazin et al.
5,325,873 A	7/1994	Hirschi et al.	5,546,951 A	8/1996	Ben-Haim
5,329,944 A	7/1994	Fabian et al.	5,551,429 A	9/1996	Fitzpatrick et al.
5,330,485 A	7/1994	Clayman et al.	5,558,091 A	9/1996	Acker et al.
5,333,168 A	7/1994	Fernandes et al.	5,566,681 A	10/1996	Manwaring et al.
5,342,295 A	8/1994	Imran	5,568,384 A	10/1996	Robb et al.
5,353,795 A	10/1994	Souza et al.	5,568,809 A	10/1996	Ben-haim
5,353,800 A	10/1994	Pohndorf et al.	5,571,083 A	11/1996	Lemelson
5,353,807 A	10/1994	DeMarco	5,572,999 A	11/1996	Funda et al.
5,359,417 A	10/1994	Muller et al.	5,573,533 A	11/1996	Strul
5,368,030 A	11/1994	Zinreich et al.	5,575,794 A	11/1996	Walus et al.
5,371,778 A	12/1994	Yanof et al.	5,575,798 A	11/1996	Koutrouvelis
5,375,596 A	12/1994	Twiss et al.	5,583,909 A	12/1996	Hanover
5,377,678 A	1/1995	Dumoulin et al.	5,588,430 A	12/1996	Bova et al.
5,383,454 A	1/1995	Bucholz	5,590,215 A	12/1996	Allen
5,385,146 A	1/1995	Goldreyer	5,592,939 A	1/1997	Martinelli
5,385,148 A	1/1995	Lesh et al.	5,595,193 A	1/1997	Walus et al.
5,386,828 A	2/1995	Owens et al.	5,596,228 A	1/1997	Anderton et al.
5,389,101 A	2/1995	Heilbrun et al.	5,600,330 A	2/1997	Blood

US 8,175,681 B2

5,603,318 A	2/1997	Heilbrun et al.	5,803,089 A	9/1998	Ferre et al.
5,611,025 A	3/1997	Lorensen et al.	5,807,252 A	9/1998	Hassfeld et al.
5,617,462 A	4/1997	Spratt	5,810,008 A	9/1998	Dekel et al.
5,617,857 A	4/1997	Chader et al.	5,810,728 A	9/1998	Kuhn
5,619,261 A	4/1997	Anderton	5,810,735 A	9/1998	Halperin et al.
5,622,169 A	4/1997	Golden et al.	5,820,553 A	10/1998	Hughes
5,622,170 A	4/1997	Schulz	5,823,192 A	10/1998	Kalend et al.
5,627,873 A	5/1997	Hanover et al.	5,823,958 A	10/1998	Truppe
5,628,315 A	5/1997	Vilsmeier et al.	5,828,725 A	10/1998	Levinson
5,630,431 A	5/1997	Taylor	5,828,770 A	10/1998	Leis et al.
5,636,644 A	6/1997	Hart et al.	5,829,444 A	11/1998	Ferre et al.
5,638,819 A	6/1997	Manwaring et al.	5,831,260 A	11/1998	Hansen
5,639,276 A	6/1997	Weinstock et al.	5,833,608 A	11/1998	Acker
5,640,170 A	6/1997	Anderson	5,834,759 A	11/1998	Glossop
5,642,395 A	6/1997	Anderton et al.	5,836,954 A	11/1998	Heilbrun et al.
5,643,268 A	7/1997	Vilsmeier et al.	5,840,024 A	11/1998	Taniguchi et al.
5,645,065 A	7/1997	Shapiro et al.	5,840,025 A	11/1998	Ben-Haim
5,646,524 A	7/1997	Gilboa	5,843,076 A	12/1998	Webster, Jr. et al.
5,647,361 A	7/1997	Damadian	5,848,967 A	12/1998	Cosman
5,662,111 A	9/1997	Cosman	5,851,183 A	12/1998	Bucholz
5,664,001 A	9/1997	Tachibana et al.	5,865,846 A	2/1999	Bryan et al.
5,674,296 A	10/1997	Bryan et al.	5,868,674 A	2/1999	Glowinski et al.
5,676,673 A	10/1997	Ferre et al.	5,868,675 A	2/1999	Henrion et al.
5,681,260 A	10/1997	Ueda et al.	5,871,445 A	2/1999	Bucholz
5,682,886 A	11/1997	Delp et al.	5,871,455 A	2/1999	Ueno
5,682,890 A	11/1997	Kormos et al.	5,871,487 A	2/1999	Warner et al.
5,690,108 A	11/1997	Chakeres	5,873,822 A	2/1999	Ferre et al.
5,694,945 A	12/1997	Ben-Haim	5,882,304 A	3/1999	Ehnholm et al.
5,695,500 A	12/1997	Taylor et al.	5,884,410 A	3/1999	Prinz
5,695,501 A	12/1997	Carol et al.	5,889,834 A	3/1999	Vilsmeier et al.
5,696,500 A	12/1997	Diem	5,891,034 A	4/1999	Bucholz
5,697,377 A	12/1997	Wittkamp	5,891,157 A	4/1999	Day et al.
5,702,406 A	12/1997	Vilsmeier et al.	5,904,691 A	5/1999	Barnett et al.
5,711,299 A	1/1998	Manwaring et al.	5,907,395 A	5/1999	Schulz et al.
5,713,946 A	2/1998	Ben-Haim	5,913,820 A	6/1999	Bladen et al.
5,715,822 A	2/1998	Watkins et al.	5,916,193 A	6/1999	Stevens et al.
5,715,836 A	2/1998	Kliegis et al.	5,920,395 A	7/1999	Schulz
5,718,241 A	2/1998	Ben-Haim et al.	5,921,992 A	7/1999	Costales et al.
5,727,552 A	3/1998	Ryan	5,923,727 A	7/1999	Navab
5,727,553 A	3/1998	Saad	5,928,248 A	7/1999	Acker
5,729,129 A	3/1998	Acker	5,935,160 A	8/1999	Auricchio et al.
5,730,129 A	3/1998	Darrow et al.	5,938,603 A	8/1999	Ponzi
5,730,130 A	3/1998	Fitzpatrick et al.	5,938,694 A	8/1999	Jaraczewski et al.
5,732,703 A	3/1998	Kalfas et al.	5,944,022 A	8/1999	Nardella et al.
5,735,278 A	4/1998	Hoult et al.	5,947,980 A	9/1999	Jensen et al.
5,738,096 A	4/1998	Ben-Haim	5,947,981 A	9/1999	Cosman
5,740,802 A	4/1998	Nafis et al.	5,950,629 A	9/1999	Taylor et al.
5,740,808 A	4/1998	Panescu et al.	5,951,475 A	9/1999	Gueziec et al.
5,741,214 A	4/1998	Ouchi et al.	5,951,571 A	9/1999	Audette
5,742,394 A	4/1998	Hansen	5,954,647 A	9/1999	Bova et al.
5,744,953 A	4/1998	Hansen	5,954,796 A	9/1999	McCarty et al.
5,748,767 A	5/1998	Raab	5,957,844 A	9/1999	Dekel et al.
5,749,362 A	5/1998	Funda et al.	5,964,796 A	10/1999	Imran
5,749,835 A	5/1998	Glantz	5,967,980 A	10/1999	Ferre et al.
5,752,513 A	5/1998	Acker et al.	5,967,982 A	10/1999	Barnett
5,755,725 A	5/1998	Druais	5,968,047 A	10/1999	Reed
RE35,816 E	6/1998	Schulz	5,971,997 A	10/1999	Guthrie et al.
5,758,667 A	6/1998	Slettenmark	5,976,156 A	11/1999	Taylor et al.
5,762,064 A	6/1998	Polvani	5,980,535 A	11/1999	Barnett et al.
5,767,669 A	6/1998	Hansen et al.	5,983,126 A	11/1999	Wittkamp
5,767,699 A	6/1998	Bosnyak et al.	5,987,349 A	11/1999	Schulz
5,767,960 A	6/1998	Orman	5,987,960 A	11/1999	Messner et al.
5,769,789 A	6/1998	Wang et al.	5,999,837 A	12/1999	Messner et al.
5,769,843 A	6/1998	Abela et al.	5,999,840 A	12/1999	Grimson et al.
5,769,861 A	6/1998	Vilsmeier	6,001,130 A	12/1999	Bryan et al.
5,772,594 A	6/1998	Barrick	6,004,269 A	12/1999	Crowley et al.
5,775,322 A	7/1998	Silverstein et al.	6,006,126 A	12/1999	Cosman
5,776,064 A	7/1998	Kalfas et al.	6,006,127 A	12/1999	Van Der Brug et al.
5,782,765 A	7/1998	Jonkman	6,009,349 A	12/1999	Mouchawar et al.
5,787,886 A	8/1998	Kelly et al.	6,013,087 A	1/2000	Adams et al.
5,792,055 A	8/1998	McKinnon	6,014,580 A	1/2000	Blume et al.
5,795,294 A	8/1998	Luber et al.	6,016,439 A	1/2000	Acker
5,797,849 A	8/1998	Vesely et al.	6,019,725 A	2/2000	Vesely et al.
5,799,055 A	8/1998	Peshkin et al.	6,024,695 A	2/2000	Taylor et al.
5,799,099 A	8/1998	Wang et al.	6,050,267 A	4/2000	Nardella et al.
5,800,352 A	9/1998	Ferre et al.	6,050,724 A	4/2000	Schmitz et al.
5,800,407 A	9/1998	Eldor	6,059,718 A	5/2000	Taniguchi et al.
5,800,535 A	9/1998	Howard, III	6,063,022 A	5/2000	Ben-Haim
5,802,719 A	9/1998	O'Farrell, Jr. et al.	6,071,288 A	6/2000	Carol et al.

US 8,175,681 B2

6,073,043 A	6/2000	Schneider	6,569,160 B1	5/2003	Goldin et al.
6,076,008 A	6/2000	Bucholz	6,574,498 B1	6/2003	Gilboa
6,088,527 A	7/2000	Rybczynski	6,584,174 B2	6/2003	Schubert et al.
6,090,105 A	7/2000	Zepeda et al.	6,593,884 B1	7/2003	Gilboa et al.
6,096,050 A	8/2000	Audette	6,595,989 B1	7/2003	Schaer
6,104,944 A	8/2000	Martinelli	6,602,271 B2	8/2003	Adams et al.
6,112,111 A	8/2000	Glantz	6,609,022 B2	8/2003	Vilsmeier et al.
6,118,845 A	9/2000	Simon et al.	6,611,141 B1	8/2003	Schulz et al.
6,122,538 A	9/2000	Sliwa, Jr. et al.	6,611,700 B1	8/2003	Vilsmeier et al.
6,122,541 A	9/2000	Cosman et al.	6,640,128 B2	10/2003	Vilsmeier et al.
6,122,552 A	9/2000	Tockman et al.	6,694,162 B2	2/2004	Hartlep
6,131,396 A	10/2000	Duerr et al.	6,701,176 B1	3/2004	Halperin et al.
6,139,183 A	10/2000	Graumann	6,701,179 B1	3/2004	Martinelli et al.
6,147,480 A	11/2000	Osadchy et al.	6,711,429 B1	3/2004	Gilboa et al.
6,149,592 A	11/2000	Yanof et al.	6,714,806 B2	3/2004	Iaizzo et al.
6,152,946 A	11/2000	Broome et al.	6,725,080 B2	4/2004	Melkent et al.
6,156,067 A	12/2000	Bryan et al.	6,868,195 B2	3/2005	Fujita
6,161,032 A	12/2000	Acker	6,888,623 B2	5/2005	Clements
6,165,181 A	12/2000	Heilbrun et al.	6,892,090 B2	5/2005	Verard et al.
6,167,296 A	12/2000	Shahidi	6,892,091 B1	5/2005	Ben-Haim et al.
6,172,499 B1	1/2001	Ashe	6,950,689 B1	9/2005	Willis et al.
6,175,756 B1	1/2001	Ferre et al.	6,990,370 B1	1/2006	Beatty et al.
6,178,345 B1	1/2001	Vilsmeier et al.	7,020,522 B1	3/2006	Hoijer et al.
6,183,444 B1	2/2001	Glines et al.	7,047,073 B2	5/2006	Hoijer et al.
6,192,280 B1	2/2001	Sommer et al.	7,130,700 B2	10/2006	Gardeski et al.
6,194,639 B1	2/2001	Botella et al.	7,189,208 B1	3/2007	Beatty et al.
6,196,230 B1	3/2001	Hall et al.	7,207,989 B2	4/2007	Pike, Jr. et al.
6,201,387 B1	3/2001	Govari	7,215,430 B2	5/2007	Kacyra et al.
6,203,493 B1	3/2001	Ben-Haim	7,263,397 B2	8/2007	Hauck et al.
6,203,497 B1	3/2001	Dekel et al.	7,305,121 B2	12/2007	Kaufmann et al.
6,207,111 B1	3/2001	Weinberg	7,369,901 B1	5/2008	Morgan et al.
6,210,362 B1	4/2001	Ponzi	7,421,300 B2	9/2008	Smits et al.
6,211,666 B1	4/2001	Acker	7,479,141 B2	1/2009	Kleen et al.
6,213,995 B1	4/2001	Steen et al.	7,570,791 B2	8/2009	Frank et al.
6,216,027 B1	4/2001	Willis et al.	7,599,730 B2	10/2009	Hunter et al.
6,223,067 B1	4/2001	Vilsmeier et al.	7,697,972 B2	4/2010	Verard et al.
6,226,543 B1	5/2001	Gilboa et al.	7,715,604 B2	5/2010	Sun et al.
6,233,476 B1	5/2001	Strommer et al.	7,988,639 B2	8/2011	Starks
6,236,875 B1	5/2001	Bucholz et al.	2001/0007918 A1	7/2001	Vilsmeier et al.
6,236,886 B1	5/2001	Cherepenin et al.	2001/0031920 A1	10/2001	Kaufman et al.
6,246,231 B1	6/2001	Ashe	2001/0036245 A1	11/2001	Kienzle et al.
6,246,468 B1	6/2001	Dimsdale	2002/0045810 A1	4/2002	Ben-Haim
6,253,770 B1	7/2001	Acker et al.	2002/0049375 A1	4/2002	Strommer et al.
6,256,121 B1	7/2001	Lizotte et al.	2002/0077544 A1	6/2002	Shahidi
6,259,942 B1	7/2001	Westermann et al.	2002/0077568 A1	6/2002	Haddock
6,273,896 B1	8/2001	Franck et al.	2002/0095081 A1	7/2002	Vilsmeier et al.
6,285,902 B1	9/2001	Kienzle, III et al.	2002/0111662 A1	8/2002	Iaizzo et al.
6,298,262 B1	10/2001	Franck et al.	2002/0128565 A1	9/2002	Rudy
6,301,498 B1	10/2001	Greenberg et al.	2002/0147488 A1	10/2002	Doan et al.
6,314,310 B1	11/2001	Ben-Haim et al.	2002/0183817 A1	12/2002	Van Venrooij et al.
6,330,356 B1	12/2001	Sundareswaran et al.	2002/0193686 A1	12/2002	Gilboa
6,332,089 B1	12/2001	Acker et al.	2003/0018251 A1	1/2003	Solomon
6,341,231 B1	1/2002	Ferre et al.	2003/0028118 A1	2/2003	Dupree et al.
6,351,659 B1	2/2002	Vilsmeier	2003/0055324 A1	3/2003	Wasserman
6,379,302 B1	4/2002	Kessman et al.	2003/0074011 A1	4/2003	Gilboa et al.
6,381,485 B1	4/2002	Hunter et al.	2003/0078494 A1	4/2003	Panescu et al.
6,389,187 B1	5/2002	Greenaway et al.	2003/0108853 A1	6/2003	Chosack et al.
6,423,009 B1	7/2002	Downey et al.	2003/0114908 A1	6/2003	Flach
6,424,856 B1	7/2002	Vilsmeier et al.	2003/0225434 A1	12/2003	Glantz et al.
6,427,314 B1	8/2002	Acker	2003/0231789 A1	12/2003	Willis et al.
6,428,547 B1	8/2002	Vilsmeier et al.	2004/0001075 A1	1/2004	Balakrishnan et al.
6,434,415 B1	8/2002	Foley et al.	2004/0024309 A1	2/2004	Ferre et al.
6,437,567 B1	8/2002	Schenck et al.	2004/0044295 A1	3/2004	Reinert et al.
6,445,943 B1	9/2002	Ferre et al.	2004/0064159 A1	4/2004	Hoijer et al.
6,447,504 B1	9/2002	Ben-Haim et al.	2004/0068312 A1	4/2004	Sigg et al.
6,470,205 B2	10/2002	Bosselmann et al.	2004/0070582 A1	4/2004	Smith et al.
6,470,207 B1	10/2002	Simon et al.	2004/0097805 A1	5/2004	Verard et al.
6,474,341 B1	11/2002	Hunter et al.	2004/0097806 A1	5/2004	Hunter et al.
6,478,802 B2	11/2002	Kienzle, III et al.	2004/0162599 A1	8/2004	Kurth
6,484,049 B1	11/2002	Seeley et al.	2004/0215298 A1	10/2004	Richardson et al.
6,490,475 B1	12/2002	Seeley et al.	2004/0228453 A1	11/2004	Dobbs et al.
6,493,573 B1	12/2002	Martinelli et al.	2004/0236395 A1	11/2004	Iaizzo et al.
6,493,575 B1	12/2002	Kesten et al.	2004/0249281 A1	12/2004	Olstad
6,498,944 B1	12/2002	Ben-Haim et al.	2004/0249430 A1	12/2004	Martinez et al.
6,499,488 B1	12/2002	Hunter et al.	2004/0254437 A1	12/2004	Hauck et al.
6,516,046 B1	2/2003	Frohlich et al.	2005/0018888 A1	1/2005	Zonneveld
6,527,443 B1	3/2003	Vilsmeier et al.	2005/0119550 A1	6/2005	Serra et al.
6,546,270 B1	4/2003	Goldin et al.	2005/0143651 A1	6/2005	Verard et al.
6,551,325 B2	4/2003	Neubauer et al.	2005/0177151 A1	8/2005	Coen et al.

WO	WO-9929253	A1	6/1999
WO	WO-9933406	A1	7/1999
WO	WO-9937208	A1	7/1999
WO	WO-9938449	A1	8/1999
WO	WO-9952094	A1	10/1999
WO	WO-9960939	A1	12/1999
WO	WO-0006701	A1	2/2000
WO	WO-0035531	A1	6/2000
WO	WO-0130437	A1	5/2001
WO	WO-0134050	A2	5/2001
WO	WO-0187136	A2	11/2001
WO	WO-02064011	A2	8/2002
WO	WO-02064040	A2	8/2002
WO	WO-2005112836	A2	12/2005
WO	WO-2006042039	A2	4/2006
WO	WO-2006117773	A1	11/2006
WO	WO-2007067945		6/2007
WO	WO-2007111542	A1	10/2007
WO	WO-2007136451	A2	11/2007
WO	WO-2008108901		9/2008
WO	WO-2008147961	A1	12/2008
WO	WO-2009126575	A1	10/2009
WO	WO-2009129477	A1	10/2009
WO	WO-2010074986	A1	7/2010

OTHER PUBLICATIONS

“Vital Images Receives 510(k) Clearance to Market VScore(TM) With AutoGate(TM); Breakthrough in Cardiac CT Imaging Simplifies Screening for Heart Disease,” Press Release. Vital Images, Inc., Feb. 6, 2001 (4 pages).

Adams et al., “Orientation Aid for Head and Neck Surgeons,” *Innov. Tech. Biol. Med.*, vol. 13, No. 4, 1992, pp. 409-424.

Adams et al., Computer-Assisted Surgery, *IEEE Computer Graphics & Applications*, pp. 43-51, (May 1990).

Barrick et al., “Prophylactic Intramedullary Fixation of the Tibia for Stress Fracture in a Professional Athlete,” *Journal of Orthopaedic Trauma*, vol. 6, No. 2, pp. 241-244 (1992).

Barrick et al., “Technical Difficulties with the Brooker-Wills Nail in Acute Fractures of the Femur,” *Journal of Orthopaedic Trauma*, vol. 6, No. 2, pp. 144-150 (1990).

Barrick, “Distal Locking Screw Insertion Using a Cannulated Drill Bit: Technical Note,” *Journal of Orthopaedic Trauma*, vol. 7, No. 3, 1993, pp. 248-251.

Batnitzky et al., “Three-Dimensional Computer Reconstructions of Brain Lesions from Surface Contours Provided by Computed Tomography: A Prospectus,” *Neurosurgery*, vol. 11, No. 1, Part 1, 1982, pp. 73-84.

Benzel et al., “Magnetic Source Imaging: a Review of the Magnes System of Biomagnetic Technologies Incorporated,” *Neurosurgery*, vol. 33, No. 2 (Aug. 1993), pp. 252-259.

Bergstrom et al. Stereotaxic Computed Tomography, *Am. J. Roentgenol*, vol. 127 pp. 167-170 (1976).

Bouazza-Marouf et al.; “Robotic-Assisted Internal Fixation of Femoral Fractures,” *IMECHE.*, pp. 51-58 (1995).

Brack et al., “Accurate X-ray Based Navigation in Computer-Assisted Orthopedic Surgery,” *CAR '98*, pp. 716-722.

Brown, R., M.D., A Stereotactic Head Frame for Use with CT Body Scanners, *Investigative Radiology*. COPYRIGHT. J.B. Lippincott Company, pp. 300-304 (Jul.-Aug. 1979).

Bryan, “Bryan Cervical Disc System Single Level Surgical Technique,” *Spinal Dynamics*, 2002, pp. 1-33.

Bucholz et al., “Variables affecting the accuracy of stereotactic localization using computerized tomography,” *Journal of Neurosurgery*, vol. 79, Nov. 1993, pp. 667-673.

Bucholz, R.D., et al. Image-guided surgical techniques for infections and trauma of the central nervous system, *Neurosurg. Clinics of N.A.*, vol. 7, No. 2, pp. 187-200 (1996).

Bucholz, R.D., et al., A Comparison of Sonic Digitizers Versus Light Emitting Diode-Based Localization, *Interactive Image-Guided Neurosurgery*, Chapter 16, pp. 179-200 (1993).

Bucholz, R.D., et al., Intraoperative localization using a three dimensional optical digitizer, *SPIE—The Intl. Soc. for Opt. Eng.*, vol. 1894, pp. 312-322 (Jan. 17-19, 1993).

Bucholz, R.D., et al., Intraoperative Ultrasonic Brain Shift Monitor and Analysis, *Stealth Station Marketing Brochure* (2 pages) (undated).

Bucholz, R.D., et al., The Correction of Stereotactic Inaccuracy Caused by Brain Shift Using an Intraoperative Ultrasound Device, *First Joint Conference, Computer Vision, Virtual Reality and Robotics in Medicine and Medical Robotics and Computer-Assisted Surgery*, Grenoble, France, pp. 459-466 (Mar. 19-22, 1997).

Champleboux et al., “Accurate Calibration of Cameras and Range Imaging Sensors: the NPBS Method,” *IEEE International Conference on Robotics and Automation*, Nice, France, May 1992.

Champleboux, “Utilisation de Fonctions Splines pour la Mise au Point D’un Capteur Tridimensionnel sans Contact,” *Quelques Applications Medicales*, Jul. 1991.

Cinquin et al., “Computer Assisted Medical Interventions,” *IEEE Engineering in Medicine and Biology*, May/June 1995, pp. 254-263.

Cinquin et al., “Computer Assisted Medical Interventions,” *International Advanced Robotics Programme*, Sep. 1989, pp. 63-65.

Clarysse et al., “A Computer-Assisted System for 3-D Frameless Localization in Stereotaxic MRI,” *IEEE Transactions on Medical Imaging*, vol. 10, No. 4, Dec. 1991, pp. 523-529.

Cutting M.D. et al., Optical Tracking of Bone Fragments During Craniofacial Surgery, *Second Annual International Symposium on Medical Robotics and Computer Assisted Surgery*, pp. 221-225, (Nov. 1995).

European Search Report completed Mar. 1, 2004 for European application EP03024327, claiming benefit of U.S. Appl. No. 10/299,969, filed Nov. 19, 2002.

European Search Report completed Sep. 29, 2004 for European application EP04016056, claiming benefit of U.S. Appl. No. 10/619,216, filed Jul. 14, 2003.

Feldmar et al., “3D-2D Projective Registration of Free-Form Curves and Surfaces,” *Rapport de recherche (Inria Sophia Antipolis)*, 1994, pp. 1-44.

Foley et al., “Fundamentals of Interactive Computer Graphics,” *The Systems Programming Series*, Chapter 7, Jul. 1984, pp. 245-266.

Foley et al., “Image-guided Intraoperative Spinal Localization,” *Intraoperative Neuroprotection*, Chapter 19, 1996, pp. 325-340.

Foley, “The SteathStation: Three-Dimensional Image-Interactive Guidance for the Spine Surgeon,” *Spinal Frontiers*, Apr. 1996, pp. 7-9.

Friets, E.M., et al. A Frameless Stereotaxic Operating Microscope for Neurosurgery, *IEEE Trans. on Biomed. Eng.*, vol. 36, No. 6, pp. 608-617 (Jul. 1989).

Gallen, C.C., et al., Intracranial Neurosurgery Guided by Functional Imaging, *Surg. Neurol.*, vol. 42, pp. 523-530 (1994).

Galloway, R.L., et al., Interactive Image-Guided Neurosurgery, *IEEE Trans. on Biomed. Eng.*, vol. 89, No. 12, pp. 1226-1231 (1992).

Galloway, R.L., Jr. et al, Optical localization for interactive, image-guided neurosurgery, *SPIE*, vol. 2164 (May 1, 1994) pp. 137-145.

Germano, “Instrumentation, Technique and Technology”, *Neurosurgery*, vol. 37, No. 2, Aug. 1995, pp. 348-350.

Gildenberg et al., “Calculation of Stereotactic Coordinates from the Computed Tomographic Scan,” *Neurosurgery*, vol. 10, No. 5, May 1982, pp. 580-586.

Gomez, C.R., et al., Transcranial Doppler Ultrasound Following Closed Head Injury: Vasospasm or Vasoparalysis?, *Surg. Neurol.*, vol. 35, pp. 30-35 (1991).

Gonzalez, “Digital Image Fundamentals,” *Digital Image Processing*, Second Edition, 1987, pp. 52-54.

Gottesfeld Brown et al., “Registration of Planar Film Radiographs with Computer Tomography,” *Proceedings of MMBIA*, Jun. '96, pp. 42-51.

Grimson, W.E.L., An Automatic Registration Method for Frameless Stereotaxy, *Image Guided Surgery, and enhanced Reality Visualization*, IEEE, pp. 430-436 (1994).

Grimson, W.E.L., et al., Virtual-reality technology is giving surgeons the equivalent of x-ray vision helping them to remove tumors more effectively, to minimize surgical wounds and to avoid damaging critical tissues, *Sci. Amer.*, vol. 280, No. 6, pp. 62-69 (Jun. 1999).

Guezic et al., “Registration of Computed Tomography Data to a Surgical Robot Using Fluoroscopy: A Feasibility Study,” *Computer Science/Mathematics*, Sep. 27, 1996, 6 pages.

- Guthrie, B.L., *Graphic-Interactive Cranial Surgery: The Operating Arm System*, Handbook of Stereotaxy Using the CRW Apparatus, Chapter 13 (1994) pp. 193-211.
- Hamadeh et al., "Kinematic Study of Lumbar Spine Using Functional Radiographies and 3D/2D Registration," TIMC UMR 5525—IMAG (1997).
- Hamadeh et al., "Automated 3-Dimensional Computed Tomographic and Fluoroscopic Image Registration," *Computer Aided Surgery* (1998), 3:11-19.
- Hamadeh et al., "Towards Automatic Registration Between CT and X-ray Images: Cooperation Between 3D/2D Registration and 2D Edge Detection," MRCAS '95, pp. 39-46.
- Hardy, T., M.D., et al., CASS: A Program for Computer Assisted Stereotaxic Surgery, The Fifth Annual Symposium on Computer Applications in Medical Care, Proceedings, Nov. 1-4, 1981, IEEE, pp. 1116-1126, (1981).
- Hatch, "Reference-Display System for the Integration of CT Scanning and the Operating Microscope," Thesis, Thayer School of Engineering, Oct. 1984, pp. 1-189.
- Hatch, et al., "Reference-Display System for the Integration of CT Scanning and the Operating Microscope", Proceedings of the Eleventh Annual Northeast Bioengineering Conference, Mar. 14-15, 1985, pp. 252-254.
- Heilbrun et al., "Preliminary experience with Brown-Roberts-Wells (BRW) computerized tomography stereotaxic guidance system," *Journal of Neurosurgery*, vol. 59, Aug. 1983, pp. 217-222.
- Heilbrun, M.D., *Progressive Technology Applications, Neurosurgery for the Third Millennium*, Chapter 15, J. Whitaker & Sons, Ltd., Amer. Assoc. of Neurol. Surgeons, pp. 191-198 (1992).
- Heilbrun, M.P., *Computed Tomography—Guided Stereotactic Systems*, *Clinical Neurosurgery*, Chapter 31, pp. 564-581 (1983).
- Heilbrun, M.P., et al., *Stereotactic Localization and Guidance Using a Machine Vision Technique*, *Stereotact & Funct. Neurosurg.*, Proceed. of the Mtg. of the Amer. Soc. for Sterot. and Funct. Neurosurg. (Pittsburgh, PA) vol. 58, pp. 94-98 (1992).
- Henderson et al., "An Accurate and Ergonomic Method of Registration for Image-guided Neurosurgery," *Computerized Medical Imaging and Graphics*, vol. 18, No. 4, Jul.-Aug. 1994, pp. 273-277.
- Hoerenz, "The Operating Microscope I. Optical Principles, Illumination Systems, and Support Systems," *Journal of Microsurgery*, vol. 1, 1980, pp. 364-369.
- Hofstetter et al., "Fluoroscopy Based Surgical Navigation—Concept and Clinical Applications," *Computer Assisted Radiology and Surgery*, 1997, pp. 956-960.
- Horner et al., "A Comparison of CT-Stereotaxic Brain Biopsy Techniques," *Investigative Radiology*, Sep.-Oct. 1984, pp. 367-373.
- Hounsfield, "Computerized transverse axial scanning (tomography): Part 1. Description of system," *British Journal of Radiology*, vol. 46, No. 552, Dec. 1973, pp. 1016-1022.
- Intracardiac Echocardiographic Guidance & Monitoring During Percutaneous Endomyocardial Gene Injection in Porcine Heart, Seung, et al. (*Human Gene Therapy* 12:893-903 May 20, 2001).
- Jacob, Al, et al., "A Whole-Body Registration-Free Navigation System for Image-Guided Surgery and Interventional Radiology," *Investigative Radiology*, vol. 35 No. 5 (May 2000) pp. 279-288.
- Jacques et al., "A Computerized Microstereotactic Method to Approach, 3-Dimensionally Reconstruct, Remove and Adjuvantly Treat Small CNS Lesions," *Applied Neurophysiology*, vol. 43, 1980, pp. 176-182.
- Jacques et al., "Computerized three-dimensional stereotaxic removal of small central nervous system lesion in patients," *J. Neurosurg.*, vol. 53, Dec. 1980, pp. 816-820.
- Joskowicz et al., "Computer-Aided Image-Guided Bone Fracture Surgery: Concept and Implementation," *CAR '98*, pp. 710-715.
- Kall, B., *The Impact of Computer and Imaging Technology on Stereotactic Surgery*, Proceedings of the Meeting of the American Society for Stereotactic and Functional Neurosurgery, pp. 10-22 (1987).
- Kato, A., et al., A frameless, armless navigational system for computer-assisted neurosurgery, *J. Neurosurg.*, vol. 74, pp. 845-849 (May 1991).
- Kelly et al., "Computer-assisted stereotaxic laser resection of intra-axial brain neoplasms," *Journal of Neurosurgery*, vol. 64, Mar. 1986, pp. 427-439.
- Kelly et al., "Precision Resection of Intra-Axial CNS Lesions by CT-Based Stereotactic Craniotomy and Computer Monitored CO.sub.2 Laser," *Acta Neurochirurgica*, vol. 68, 1983, pp. 1-9.
- Kelly, P.J., *Computer Assisted Stereotactic Biopsy and Volumetric Resection of Pediatric Brain Tumors*, *Brain Tumors in Children*, *Neurologic Clinics*, vol. 9, No. 2, pp. 317-336 (May 1991).
- Kelly, P.J., *Computer-Directed Stereotactic Resection of Brain Tumors*, *Neurologica Operative Atlas*, vol. 1, No. 4, pp. 299-313 (1991).
- Kelly, P.J., et al., Results of Computed Tomography-based Computer-assisted Stereotactic Resection of Metastatic Intracranial Tumors, *Neurosurgery*, vol. 22, No. 1, Part 1, 1988, pp. 7-17 (Jan. 1988).
- Kelly, P.J., *Stereotactic Imaging, Surgical Planning and Computer-Assisted Resection of Intracranial Lesions: Methods and Results*, *Advances and Technical Standards in Neurosurgery*, vol. 17, pp. 78-118, (1990).
- Kim, W.S. et al., A Helmet Mounted Display for Telerobotics, IEEE, pp. 543-547 (1988).
- Klimek, L., et al., Long-Term Experience with Different Types of Localization Systems in Skull-Base Surgery, *Ear, Nose & Throat Surgery*, Chapter 51 (1996) pp. 635-638.
- Kosugi, Y., et al., An Articulated Neurosurgical Navigation System Using MRI and CT Images, *IEEE Trans. on Biomed. Eng.* vol. 35, No. 2, pp. 147-152 (Feb. 1988).
- Krybus, W., et al., Navigation Support for Surgery by Means of Optical Position Detection, *Computer Assisted Radiology Proceed. of the Intl. Symp. Car '91 Computed Assisted Radiology*, pp. 362-366 (Jul. 3-6, 1991).
- Kwoh, Y.S., Ph.D., et al., A New Computerized Tomographic-Aided Robotic Stereotaxis System, *Robotics Age*, vol. 7, No. 6, pp. 17-22 (Jun. 1985).
- Laitinen et al., "An Adapter for Computed Tomography-Guided, Stereotaxis," *Surg. Neurol.*, 1985, pp. 559-566.
- Laitinen, "Noninvasive multipurpose stereoadapter," *Neurological Research*, Jun. 1987, pp. 137-141.
- Lavallee et al., "Matching 3-D Smooth Surfaces with their 2-D Projections using 3-D Distance Maps," *SPIE*, vol. 1570, *Geometric Methods in Computer Vision*, 1991, pp. 322-336.
- Lavallee et al., "Computer Assisted Driving of a Needle into the Brain," *Proceedings of the International Symposium CAR '89, Computer Assisted Radiology*, 1989, pp. 416-420.
- Lavallee et al., "Computer Assisted Interventionist Imaging: The Instance of Stereotactic Brain Surgery," *North-Holland MEDINFO 89, Part 1*, 1989, pp. 613-617.
- Lavallee et al., "Computer Assisted Spine Surgery: A Technique for Accurate Transpedicular Screw Fixation Using CT Data and a 3-D Optical Localizer," TIMC, Faculte de Medecine de Grenoble. (1995).
- Lavallee et al., "Image guided operating robot: a clinical application in stereotactic neurosurgery," *Proceedings of the 1992 IEEE International Conference on Robotics and Automation*, May 1992, pp. 618-624.
- Lavallee et al., "Matching of Medical Images for Computed and Robot Assisted Surgery," *IEEE EMBS, Orlando*, 1991.
- Lavallee, "A New System for Computer Assisted Neurosurgery," *IEEE Engineering in Medicine & Biology Society 11.sup.th Annual International Conference*, 1989, pp. 0926-0927.
- Lavallee, "VI Adaption de ja Methodologie a Quelques Applications Cliniques," *Chapitre VI*, pp. 133-148.
- Lavallee, S., et al., Computer Assisted Knee Anterior Cruciate Ligament Reconstruction First Clinical Tests, *Proceedings of the First International Symposium on Medical Robotics and Computer Assisted Surgery*, pp. 11-16 (Sep. 1994).
- Lavallee, S., et al., *Computer Assisted Medical Interventions*, NATO ASI Series, vol. F 60, *3d Imaging in Medic.*, pp. 301-312 (1990).
- Leavitt, D.D., et al., Dynamic Field Shaping to Optimize Stereotactic Radiosurgery, *I.J. Rad. Onc. Biol. Physc.*, vol. 21, pp. 1247-1255 (1991).
- Leksell et al., "Stereotaxis and Tomography—A Technical Note," *ACTA Neurochirurgica*, vol. 52, 1980, pp. 1-7.

- Lemieux et al., "A Patient-to-Computed-Tomography Image Registration Method Based on Digitally Reconstructed Radiographs," *Med. Phys.* 21 (11), Nov. 1994, pp. 1749-1760.
- Levin et al., "The Brain: Integrated Three-dimensional Display of MR and PET Images," *Radiology*, vol. 172, No. 3, Sep. 1989, pp. 783-789.
- Maurer, Jr., et al., Registration of Head CT Images to Physical Space Using a Weighted Combination of Points and Surfaces, *IEEE Trans. on Med. Imaging*, vol. 17, No. 5, pp. 753-761 (Oct. 1998).
- Mazier et al., "Computer-Assisted Interventionist Imaging: Application to the Vertebral Column Surgery," *Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, vol. 12, No. 1, 1990, pp. 0430-0431.
- Mazier et al., Chirurgie de la Cotonne Vertebrale Assiste par Ordinateur: Application au Vissage Pediculaire, *Innov. Tech. Biol. Med.*, vol. 11, No. 5, 1990, pp. 559-566.
- McGirr, S., M.D., et al., Stereotactic Resection of Juvenile Pilocytic Astrocytomas of the Thalamus and Basal Ganglia, *Neurosurgery*, vol. 20, No. 3, pp. 447-452, (1987).
- Merloz, et al. "Computer Assisted Spine Surgery", *Clinical Assisted Spine Surgery*, No. 337, pp. 86-96, (Apr. 1997).
- Muschlitz, Lin, "Ultrasound in the OR suite is providing more detailed information to allow less invasive surgeries." *Technology—Ultra Sound Surgical Partners* (Sep. 2003) *Medical Imaging*. http://www.imagingeconomics.com/issues/articles/M1_2003-09_03.asp (accessed on Aug. 12, 2010).
- Ng, W.S. et al., Robotic Surgery—A First-Hand Experience in Transurethral Resection of the Prostate Surgery, *IEEE Eng. in Med. and Biology*, pp. 120-125 (Mar. 1993).
- Partial European Search Report completed Mar. 1, 2004 for European application EP03024327, claiming benefit of U.S. Appl. No. 10/299,969, filed Nov. 19, 2002.
- Pelizzari et al., "Accurate Three-Dimensional Registration of CT, PET, and/or MR Images of the Brain," *Journal of Computer Assisted Tomography*, Jan./Feb. 1989, pp. 20-26.
- Pelizzari et al., "Interactive 3D Patient-Image Registration," *Information Processing in Medical Imaging*, 12^{sup.th} International Conference, IPMI '91, Jul. 7-12, 136-141 (A.C.F. Colchester et al. eds. 1991).
- Pelizzari et al., No. 528—"Three Dimensional Correlation of PET, CT and MRI Images," *The Journal of Nuclear Medicine*, vol. 28, No. 4, Apr. 1987, p. 682.
- Penn, R.D., et al., Stereotactic Surgery with Image Processing of Computerized Tomographic Scans, *Neurosurgery*, vol. 3, No. 2, pp. 157-163 (Sep.-Oct. 1978).
- Phillips et al., "Image Guided Orthopaedic Surgery Design and Analysis," *Trans Inst. MC*, vol. 17, No. 5, 1995, pp. 251-264.
- Pixsys, 3-D Digitizing Accessories, by Pixsys (marketing brochure)(undated) (2 pages).
- Potamianos et al., "Intra-Operative Imaging Guidance for Keyhole Surgery Methodology and Calibration," *First International Symposium on Medical Robotics and Computer Assisted Surgery*, Sep. 22-24, 1994, pp. 98-104.
- Reinhardt et al., "CT-Guided 'Real Time' Stereotaxy," *ACTA Neurochirurgica*, 1989.
- Reinhardt, H., et al., A Computer-Assisted Device for Intraoperative CT-Correlated Localization of Brain Tumors, pp. 51-58 (1988).
- Reinhardt, H.F. et al., Sonic Stereometry in Microsurgical Procedures for Deep-Seated Brain Tumors and Vascular Malformations, *Neurosurgery*, vol. 32, No. 1, pp. 51-57 (Jan. 1993).
- Reinhardt, H.F., et al., Mikrochirurgische Entfernung tiefliegender Gefa.beta.mi.beta.bildungen mit Hilfe der Sonar-Stereometrie (Microsurgical Removal of Deep-Seated Vascular Malformations Using Sonar Stereometry). *Ultraschall in Med.* 12, pp. 80-83(1991).
- Reinhardt, Hans. F., *Neuronavigation: A Ten-Year Review*, *Neurosurgery* (1996) pp. 329-341.
- Roberts et al., "A frameless stereotaxic integration of computerized tomographic imaging and the operating microscope," *J. Neurosurg.*, vol. 65, Oct. 1986, pp. 545-549.
- Rosenbaum et al., "Computerized Tomography Guided Stereotaxis: A New Approach," *Applied Neurophysiology*, vol. 43, No. 3-5, 1980, pp. 172-173.
- Sautot, "Vissage Pediculaire Assiste Par Ordinateur," Sep. 20, 1994.
- Schueler et al., "Correction of Image Intensifier Distortion for Three-Dimensional X-Ray Angiography," *SPIE Medical Imaging* 1995, vol. 2432, pp. 272-279.
- Selvik et al., "A Roentgen Stereophotogrammetric System," *Acta Radiologica Diagnosis*, 1983, pp. 343-352.
- Shelden et al., "Development of a computerized microstereotaxic method for localization and removal of minute CNS lesions under direct 3-D vision," *J. Neurosurg.*, vol. 52, 1980, pp. 21-27.
- Simon, D.A., Accuracy Validation in Image-Guided Orthopaedic Surgery, *Second Annual Intl. Symp. on Med. Rob. and Comp-Assisted surgery*, *MRCAS* (1995) pp. 185-192.
- Smith et al., "Computer Methods for Improved Diagnostic Image Display Applied to Stereotactic Neurosurgery," *Automedical*, vol. 14, 1992, pp. 371-382.
- Smith et al., "The Neurostation.TM.—A Highly Accurate, Minimally Invasive Solution to Frameless Stereotactic Neurosurgery," *Computerized Medical Imaging and Graphics*, vol. 18, Jul.-Aug. 1994, pp. 247-256.
- Smith, K.R., et al. Multimodality Image Analysis and Display Methods for Improved Tumor Localization in Stereotactic Neurosurgery, *Annul Intl. Conf. of the IEEE Eng. in Med. and Biol. Soc.*, vol. 13, No. 1, p. 210 (1991).
- Tan, K., Ph.D., et al., A frameless stereotactic approach to neurosurgical planning based on retrospective patient-image registration, *J Neurosuroy*, vol. 79, pp. 296-303 (Aug. 1993).
- The Laitinen Stereotactic System, E2-E6.
- Thompson, et al., A System for Anatomical and Functional Mapping of the Human Thalamus, *Computers and Biomedical Research*, vol. 10, pp. 9-24 (1977).
- Trobraugh, J.W., et al.; *Frameless Stereotactic Ultrasonography: Method and Applications*, *Computerized Medical Imaging and Graphics*, vol. 18, No. 4, pp. 235-246 (1994).
- Viant et al., "A Computer Assisted Orthopaedic System for Distal Locking of Intramedullary Nails," *Proc. of MediMEC '95*, Bristol, 1995, pp. 86-91.
- Von Hanwhr et al., Foreword, *Computerized Medical Imaging and Graphics*, vol. 18, No. 4, pp. 225-228, (Jul.-Aug. 1994).
- Wang, M.Y., et al., An Automatic Technique for Finding and Localizing Externally Attached Markers in CT and MR vol. Images of the Head, *IEEE Trans. on Biomed. Eng.*, vol. 43, No. 6, pp. 627-637 (Jun. 1996).
- Watanabe et al., "Three-Dimensional Digitizer (Neuronavigator): New Equipment for Computed Tomography-Guided Stereotaxic Surgery," *Surgical Neurology*, vol. 27, No. 6, Jun. 1987, pp. 543-547.
- Watanabe, "Neuronavigator," *Igaku-no-Ayumi*, vol. 137, No. 6, May 10, 1986, pp. 1-4.
- Watanabe, E., M.D., et al., Open Surgery Assisted by the Neuronavigator, a Stereotactic, Articulated, Sensitive Arm, *Neurosurgery*, vol. 28, No. 6, pp. 792-800 (1991).
- Weese et al., "An Approach to 2D/3D Registration of a Vertebra in 2D X-ray Fluoroscopies with 3D CT Images," (1997) pp. 119-128.
- "EnSite NavX™ Navigation & Visualization Technology." 3 pages, St. Jude Medical. <http://www.sjmprofessional.com/Products/US/Mapping-and-Visualization/EnSite-NavX-Navigation-and-Visualization-Technology.aspx> Web. Accessed Jun. 19, 2009.
- "Local Lisa® Intracardiac Navigation System Model 9670000/9670025." Technical Manual Version 1.2, Chapter 1, pp. 1-19. 2004.
- Brenner, David J., Ph.D., "Computed Tomography—An Increasing Source of Radiation Exposure", *The New England Journal of Medicine* (Nov. 29, 2007), pp. 2277-2284.
- Gepstein, Lior, M.D., "A Novel Method for Nonfluoroscopic Catheter-Based Electroanatomical Mapping of the Heart, In Vitro and In Vivo Accuracy Results", *American Heart Association, Learn and Live, Circulation* (1997), <http://circ.ahajournals.org/cgi/content/abstract/95/6/1611> printed Oct. 2, 2008.
- International Preliminary Report on Patentability and Written Opinion for PCT/US2009/040998 mailed Oct. 28, 2010, 2009 claiming benefit of U.S. Appl. No. 12/421,332, filed Apr. 9, 2009; which claims priority to U.S. Appl. No. 61/105,957, filed Oct. 16, 2008; U.S. Appl. No. 12/117549, filed May 8, 2008.
- International Preliminary Report on Patentability and Written Opinion for PCT/US2009/0400984 mailed Oct. 28, 2010, claiming benefit of U.S. Appl. No. 12/117,549, filed May 8, 2008.

- International Preliminary Report on Patentability and Written Opinion for PCT/US2009/040979 mailed Oct. 28, 2010 claiming benefit of U.S. Appl. No. 12/117,537, filed May 8, 2008.
- International Preliminary Report on Patentability and Written Opinion mailed Oct. 29, 2009 for PCT/US2007/089087, of which U.S. Appl. No. 12/492,906 filed Jun. 26, 2009 claims benefit.
- International Search Report and Written Opinion for PCT/US2008/088189 mailed Apr. 3, 2009, claiming benefit of U.S. Appl. No. 12/183,796, filed Jul. 31, 2008; and claims priority to U.S. Appl. No. 11/966382, filed Dec. 28, 2007.
- International Search Report and Written Opinion for PCT/US2009/0400984 mailed Sep. 21, 2009, claiming benefit of U.S. Appl. No. 12/117,549, filed May 8, 2008.
- International Search Report and Written Opinion for PCT/US2009/040998 mailed Jul. 29, 2009 claiming benefit of U.S. Appl. No. 12/421,332, filed Apr. 9, 2009; which claims priority to U.S. Appl. No. 61/105,957, filed Oct. 16, 2008; U.S. Appl. No. 12/117,549, filed May 8, 2008.
- International Search Report and Written Opinion for PCT/US2009/067486 mailed May 4, 2010, claiming benefit of U.S. Appl. No. 12/336,085, filed Dec. 16, 2008.
- International Search Report and Written Opinion mailed Dec. 6, 2010 for PCT/US2010/051248, which claims benefit of U.S. Appl. No. 12/609,734 filed Oct. 30, 2009.
- International Search Report and Written Opinion for PCT/US2009/040979 mailed Sep. 21, 2009 claiming benefit of U.S. Appl. No. 12/117,537, filed May 8, 2008.
- International Search Report for PCT/US2007/089087 mailed Jul. 9, 2008, of which U.S. Appl. No. 12/492,906 filed Jun. 26, 2009 claims benefit.
- Invitation to Pay Additional Fees for PCT/US2009/0400984 mailed Jul. 30, 2009, claiming benefit of U.S. Appl. No. 12/117,549, filed May 8, 2008.
- Invitation to Pay Additional Fees for PCT/US2009/040979 mailed Jul. 30, 2009 claiming benefit of U.S. Appl. No. 12/117,537, filed May 8, 2008.
- Invitation to Pay Additional Fees for PCT/US2009/067486 mailed Mar. 5, 2010, claiming benefit of U.S. Appl. No. 12/336,085, filed Dec. 16, 2008.
- Invitation to Pay Additional Fees for PCT/US2010/047241 mailed Jan. 10, 2011, claiming benefit of U.S. Appl. No. 12/844,065, filed Jul. 27, 2010.
- Invitation to Pay Additional Fees mailed Jul. 7, 2010 for PCT/US2010/030534 claiming benefit of U.S. Appl. No. 12/421,375, filed Apr. 9, 2009.
- Jiang, Yuan. "An Impedance-Based Catheter Positioning System for Cardiac Mapping and Navigation." IEEE Transactions on Biomedical Engineering, (Aug. 2009) pp. 1963-1970, vol. 56, No. 8.
- Markowitz, Toby, et al., "Unleaded: The Fluoroless 3D Lead Implant", Presented at Heart Rhythm Society, Denver, CO, (May 2007) 1 pg.
- Markowitz, Toby, et al., Abstract Submission, "Unleaded: The Fluoroless 3D Lead Implant", Mar. 2007 2 pgs.
- Milstein, S. et al., "Initial Clinical Results of Non-Fluoroscopic Pacemaker Lead Implantation." (pre-presentation abstract) May 14-17, 2008. 2 pgs.
- Milstein, S. et al., "Initial Clinical Results of Non-Fluoroscopic Pacemaker Lead Implantation." (poster presentation) May 14-17, 2008. 1 pg.
- Nelder, J.A., et al. "A simplex method for function minimization." vol. 7, Issue 4, (1965) pp. 308-313. The Computer Journal.
- Savage, George, M.D., "Electric Tomography (ET)—A Novel Method for Assessing Myocardial Motion and Cardiac Performance", Heart Rhythm Society, Denver, CO (May 9-12, 2007) 1 pg.
- Wittkamp, Fred, H.M., et al., "LocaLisa: New Technique for Real-Time 3-Dimensional Localization of Regular Intracardiac Electrodes." Circulation Journal of the American Heart Association, 1999; 99; 13-12-1317.
- Wittkamp, Fred., H.M., et al. "Accuracy of the LocaLisa System in Catheter Ablation Procedures." Journal of Electrocardiology vol. 32 Supplement (1999). Heart Lung Institute, University Hospital Utrecht, The Netherlands.
- International Search Report and Written Opinion mailed May 4, 2010 for PCT/US2009/067486 claiming benefit of U.S. Appl. No. 12/336,085 filed Dec. 16, 2008.
- Invitation to Pay Additional Fees mailed Mar. 5, 2010 for PCT/US2009/067486 claiming benefit of U.S. Appl. No. 12/336,085, filed Dec. 16, 2008.
- Birkfellner, Wolfgang, et al. "Calibration of Tracking Systems in a Surgical Environment," IEEE Transactions on Medical Imaging, IEEE Service Center, Piscataway, NJ, US, vol. 17, No. 5. (Oct. 1, 1998) XP011035767. ISSN: 0278-0062 the whole document.
- Hubert-Tremblay, Vincent, et al. "Octree indexing of DICOM images for voxel number reduction and improvement of Monte Carlo simulation computing efficiency," Medical Physics, AIP, Melville, NY, US, vol. 33, No. 8, (Jul. 21, 2006) pp. 2819-2831, XP012092212, ISSN: 0094-2405, DOI: 10.1118/1.2214305 pp. 2820-2821.
- International Preliminary Report on Patentability mailed Oct. 11, 2011 for PCT/US2010/030534 claiming benefit of U.S. Appl. No. 12/421,375, filed Apr. 9, 2009.
- International Search Report and Written Opinion mailed Jul. 25, 2011 for PCT/US2010/047241 claiming benefit of U.S. Appl. No. 12/844,065, filed Jul. 27, 2010.
- International Search Report mailed Sep. 13, 2010 for PCT/US2010/030534 claiming benefit of U.S. Appl. No. 12/421,375, filed Apr. 9, 2009.
- Invitation to Pay Additional Fees mailed Jul. 7, 2010 for PCT/US2010/030534 claiming benefit of U.S. Appl. No. 12/421,375, filed Apr. 9, 2009.




Fig-1




Fig-2A




Fig-2B





Fig-3






Fig-5




Fig-7A




Fig-6




Fig-7B




Fig-7C




Fig-8

1

COMBINATION OF ELECTROMAGNETIC AND ELECTROPOTENTIAL LOCALIZATION

FIELD

The present disclosure relates generally to a system for localizing a tracked instrument, and particularly to a localization system using two or more modalities for localizing the instrument within a volume.

BACKGROUND

This section provides background information related to the present disclosure which is not necessarily prior art.

A navigation system can be used to track and navigate an instrument within a volume. For example, a navigation system can be used to track an instrument during a procedure, such as a surgical procedure. Various systems can be used to track instruments including electromagnetic systems, optical systems, acoustic systems, and other appropriate systems.

Tracking an instrument can allow for determination of a position of the instrument relative to the patient without directly viewing the instrument within the patient. Various methods can be used to achieve this result, such as directly tracking a particular portion of the instrument exterior to the patient or tracking a distal point of the instrument within the patient.

Differing navigation systems can be used to track different instruments within a patient. For example, a long substantially rigid instrument can be tracked with an optical navigation system that can track a proximal and/or end of the instrument that is external to the patient. Based on determinations, a position of a distal tip or an end of the instrument within the patient can be made. Additionally, navigation systems can use fields, such as electromagnetic fields, to track and navigate a distal portion of an instrument that is within a patient.

SUMMARY

This section provides a general summary of the disclosure, and is not a comprehensive disclosure of its full scope or all of its features.

A navigation system or combination of navigation systems can be used to provide two or more types of navigation or modalities of navigation to navigate a single instrument. The single instrument can be positioned within the patient and tracked. For example, both an Electromagnetic (EM) and Electropotential (EP) tracking systems can be used to navigate an instrument within a patient.

A navigation system can generally include a localizer and a tracking sensor. One skilled in the art will understand that the localizer can either transmit or receive a signal and the tracking sensor can also transmit or receive a signal to allow for a determination of a location of the tracking sensor associated with the surgical instrument. A surgical instrument can have associated therewith two or more tracking sensors that can be used in two or more modalities of navigation. For example, a surgical instrument may include an electrode that can be used with an EP tracking system and can also be associated or moved relative to a tracking sensor that includes an EM coil to be used with an EM tracking system.

An instrument can include one or more tracking sensors to be used with two or more navigation systems during a single procedure. In addition, a method can be used to register the two navigation systems during a single procedure. The registration of the two navigation systems can allow all or a selected number of points within one navigational domain to

2

be coordinated or correlated to all or selected points in a second navigational domain. For example, a surgical instrument can include a single tracking sensor that can be tracked within two navigation modalities. Also, a surgical instrument with a single tracking sensor can be moved relative to a second tracking sensor, where each of the tracking sensors are tracked in different navigation modalities. According to various embodiments, when a first tracking sensor is positioned at a known location relative to a second tracking sensor, a navigation volume or domain of the first navigation system can be registered to a navigation volume or domain of a second navigation system. In this way, a first and second navigation system can be registered for navigating a tracking sensor or a surgical instrument within the two navigation modalities.

Further areas of applicability will become apparent from the description provided herein. The description and specific examples in this summary are intended for purposes of illustration only and are not intended to limit the scope of the present disclosure.

DRAWINGS

The drawings described herein are for illustrative purposes only of selected embodiments and not all possible implementations, and are not intended to limit the scope of the present disclosure.

FIG. 1 is an environmental view of a navigation system;

FIG. 2A is a detailed cross-section view of an instrument, according to various embodiments;

FIG. 2B is a detailed cross-section and environmental view of an instrument, according to various embodiments;

FIG. 3 is a detailed cross-section view of an instrument, according to various embodiments;

FIG. 4 is an environmental view of a navigation system, according to various embodiments;

FIG. 5 is a flow chart of a method of registering two navigation systems;

FIG. 6 is a view of image data and icons displayed relative to the image data, according to various embodiments;

FIG. 7A-7C are detailed flowcharts of registration of two tracking systems; and

FIG. 8 is a detailed view of navigating a registered instrument.

Corresponding reference numerals indicate corresponding parts throughout the several views of the drawings.

DETAILED DESCRIPTION

Example embodiments will now be described more fully with reference to the accompanying drawings.

A surgical navigation system **20** is illustrated in FIG. 1. A first tracking system can include an electropotential (EP) tracking system **22**. A second tracking system can include an electromagnetic (EM) tracking system **24**. Appropriate tracking systems can include those disclosed in U.S. patent application Ser. No. 12/117,537, filed on May 8, 2008 and U.S. Patent Publication No. 2004/0097805, published on May 20, 2004, both incorporated herein by reference. The first and second tracking systems **22**, **24** can be used to track a surgical instrument **26**. The surgical instrument **26** can be any appropriate instrument, including a lead used as a part of an implantable medical device (IMD) for heart rhythm treatment, neurological treatment, or other appropriate purposes.

The surgical navigation system **20** can also include other components, such as an imaging system **30**. The imaging system **30** can be any appropriate imaging system and is exemplarily illustrated as a fluoroscopic C-arm system **32**.

Other imaging systems can include computed tomography (CT) imaging systems, magnetic resonance imaging (MRI) systems, and positron emission tomography (PET) imaging systems. The imaging systems **30** can be used by a surgeon **34** to image a patient **36** prior to (preoperatively), during (intra-operatively), or after (postoperatively) a procedure. Imaging the patient **36** can create image data that can be viewed on a display device **38** or a display device **40**. The display device **38, 40** can be provided alone, such as on a stand **42** or with a processing system as a part of a workstation or processing system **44**. The image data can be transferred from the imaging system **30** through a data transmission system **46**, such as a wired or wireless transmission system, to the display devices **38, 40**.

The navigation system **20**, also including the tracking systems **22, 24** can be incorporated or connected to the processor system **44**. The processor system **44** can include human input devices such as a keyboard **48**, a joystick or mouse **50**, a foot pedal **52** or any other appropriate human input device. Each of the human input devices **48-52** can be connected with the processor system **44** or other systems, such as the imaging system **30**, for control or actuation thereof.

The EP tracking system **22** can include components to generate a current in the patient **36**. The EP tracking system can include or be based on the Localisa™ intracardiac tracking system sold by Medtronic, Inc. have a place of business in Minneapolis, Minn. The EP tracking system **22** can also include portions disclosed in U.S. Pat. Nos. 5,697,377 or 5,983,126 to Wittkamp, incorporated herein by reference

Briefly, the EP tracking system **22** can include a pair of axis electrodes, which can also be referred to as a localizer, operable to generate a current within a volume, such as the patient **36**. The axis electrodes can include three pairs of axis electrodes to generate three substantially orthogonal axes of current within the patient **26** (also see FIG. 4). The axis electrodes can include a first pair **60a, 60b**, a second pair **62a, 62b**, and a third pair **64a, 64b**. The axis can be defined by an alternating current that is generated between any pair of the axis electrodes. For example, the first pair of axis electrodes **60a** and **60b** can be positioned on a left and right side of the patient **36** to define an X-axis when a current is generated between the two axis electrodes **60a** and **60b**.

The substantially orthogonal axis of current can be used to determine or calculate a location of a tracking device **70**. The tracking device **70** can include a first or EP tracking device **70a** and a second or EM tracking device **70b**. The EP tracking system **22** can be used to track the EP tracking device **70a**. The first tracking device **70a** can sense a voltage in the patient **36** based upon the induced current between any pair of the axis electrodes **60a-64b**. The voltage can be related to a position of the first tracking device **70a** in the patient **36**.

The pairs of axis electrodes **60a-64b** can be driven with a generator in a controller **72** that is connected via wires or wirelessly with the axis electrodes **60a-64b**. The generator can provide the power to generate the alternating current in the patient **36** between the respective the axis electrodes **60a-64b**. The controller **72** can also include a connection for the instrument **26** to communicate a signal from the tracking device **70** to the controller. The connection with the instrument **26** can be wired or wireless, according to various embodiments. In addition, the controller **72** can include a processor portion or simply be a transmitter to transmit signals from the tracking device **70**. Signals can be transmitted from the controller **72** to the processor system **44** with a transmission system **74**. The transmission system **74** can be a wired or wireless transmission system.

The EM tracking system **24** can also be associated with the controller **72** or can be provided with a separate controller system. It will be understood that various separate circuitry portions may be provided in the controller **72** to generate or operate the EP tracking system **22** or the EM tracking system **24**.

The EM tracking system **24** includes an EM localizer **76** that can be positioned relative to the patient **36**. The EM tracking system can include the AxiEM™ electromagnetic tracking system sold by Medtronic Navigation, Inc. having a place of business in Colorado, USA. The localizer **76** can generate an electromagnetic field that is sensed by the EM tracking device **70b**. Alternatively, the EM tracking device **70b** can generate a field that is sensed by the localizer **76**.

A localizer can be used as a part of a tracking system to determine the location of the tracking device **70**. For example, the localizer **76** can be interconnected with the controller **72** to transmit a signal to the processor system **44** regarding the position of the EM tracking device **70b**. The axis electrodes **60a-64b** can be a localizer that induces axes of current in the patient **36** to localize the EP tracking device **70a**. Accordingly, the localizer can refer to a portion of the tracking system which can be exterior to the volume, such as the patient **36**, that is used to determine a position of the tracking device **70**.

According to various embodiments, the localizer devices, including the EM localizer **76** and the axis electrodes **60a-64b**, can be used to define a navigation domain in a patient space of the patient **36**. Patient space can be the physical space that is being operated on during the operative procedure. The patient space can also include the navigated space through which the surgical instrument **26** is being navigated. Image space can be defined by image data **80** that is displayed on the display devices **38, 40**. Image data **80** can include any appropriate image data, such as image data of a heart **84** (FIG. 4) of the patient **36**. the image data **80** displayed on the display devices **38, 40** can also include atlas data. Atlas data can include statistical or historical data. The atlas data can be registered or morphed to the patient image data or patient space. It will be understood that atlas data may be used in an imageless navigation system. For example, an imageless navigation system may not require the acquisition of image data of the patient **36**.

The patient space can be registered to the image space of the image data **80** according to any appropriate technique, including those discussed herein. Generally, however, the patient space is registered to the image data **80** to allow for displaying or a super imposing an icon or representation of a tracked device, for example the surgical instrument **26**, over the image data **80** on the display device **38, 40**. Registration generally allows for a transformation of the image data to the patient space. Various registration techniques can include contour matching, fiducial or point matching, automatic registration, or any other appropriate registration. For example, various landmarks or fiducials can be identified in the image data **80** and the same fiducials or landmarks can be identified in the patient **36**, such as within the heart **84**. The image data **80** can then be transformed to the patient space of the patient **36** so that a proper location of a superimposed icon **26i** can be shown relative to the image data **80** of the heart **84**. Registration techniques can include those discussed in the U.S. patent applications incorporated above. In addition, as discussed herein, the EP tracking system **22** can be registered to the EM tracking system **24**. The registration of the EP tracking system **22** to the EM tracking system **24** can allow navigation of the EP tracking device **70a** with the image data **80**.

5

Turning to FIGS. 2A and 2B, the tracking device 70 can include the two tracking devices 70a and 70b. The first tracking device 70a can be a single electrode or a tip electrode 90 or ring electrode (not illustrated) of a lead assembly 92. The lead assembly 92 can be a lead for any appropriate device, such as a pacing or defibrillator system. The lead assembly 92 can be positioned or delivered within a sheath 94 according to generally known lead assemblies, such as the Attain family of catheters sold by Medtronic Inc., having a place of business in Minneapolis, Minn.

The lead assembly 92 can be positioned within the patient 36, such as relative to the heart 84, with a catheter assembly 100. The catheter assembly 100 can be any appropriate configuration. The catheter 100 can include a body molded to substantially define a cannula. The catheter assembly 100 can include the second tracking device 70b. The second tracking device 70b can include a first coil 102 and a second coil 104, or any appropriate number of coils, as part of the EM tracking device 70b. The coils can be coiled with any appropriate configuration, such as around substantially orthogonal axes to one another. The second tracking device 70b, however, can sense an electromagnetic field generated with the localizer 76 or generate an electromagnetic field that is sensed by the localizer 76.

The two tracking devices 70a, 70b can be used with respective tracking systems 22, 24. The first tracking device 70a can sense a voltage or determine bioimpedance (such as an impedance of a tissue of the patient 36) because of the induced current from the axis electrodes 60a-64b. The inducement of the current generates a voltage that can be sensed with the EP tracking device 70a. The voltage sensed by the EP tracking device 70a can be transmitted to the controller 72 with an appropriate communication line, such as a conductor 106. The conductor 106 can be conductively coupled to the EP tracking device 70a. It will be understood that although the EP tracking device 70a is illustrated as the tip electrode 90 of the lead assembly 92, that the EP tracking device 70a can also include an alternative EP tracking device 70a' formed as a part of the sheath 94. Regardless of the position of the EP tracking device 70a, its contact (e.g. by removal of a portion of insulation around the electrode) with a conductive medium or electrolyte of the patient 36 can increase and provide efficiency of detecting an appropriate voltage. The voltage sensed by the EP tracking device 70a can be used to determine the position of the EP tracking device 70a as discussed further herein and also described in the above incorporated U.S. patent applications and patents.

The second tracking device 70b, according to various embodiments, can sense an electromagnetic field generated by the localizer 76. For example, a current can be induced in one or more of the coils 102, 104 that is dependent upon the position of the coils 102, 104 in a portion of the electromagnetic field. The generated current can be sent as a signal along a transmission line 108 to the controller 72.

As discussed further herein, and illustrated in FIG. 2B, the lead assembly 92 can be moved relative to tissue of the heart 84 to position the distal tip electrode 90 into the heart 84. When positioning the distal tip electrode 90 into the heart 84, the sheath 94 and the tip 90, which can include the first tracking device 70a, can move relative to the catheter assembly 100. Moving the first tracking device 70a relative to the catheter assembly 100 moves the first tracking device 70a relative to the second tracking device 70b. As discussed herein, this can be used to determine the location of the first tracking device 70a relative to the second tracking device 70b for registration of the EP tracking system 22 and the EM

6

tracking system 24. This determination can be used to track the first tracking device 70a relative to the patient 36 and with the registered image data 80.

In addition, the tracking devices 70a and 70b could be the same coil of wire or conductive material provided with different insulation characteristics. For example, the loops or turns of the tracking device 70a can be electrically separated from the loops or turns of wire for the second tracking device 70b. Both sets of loops can be of the same length of wire over top one another. The conductive media or loops of the first tracking device 70a can be external and exposed to the patient to sense or measure the voltage in the patient. The second portion of the loops can be isolated from the patient and insulated, but they can, along with the first portion, sense the field of the EM tracking system 24.

Turning to FIG. 3, an instrument 120, according to various embodiments, is illustrated. The instrument 120 can include a lead assembly 121 substantially similar to the lead assembly 92 discussed above, including a tip electrode 90 and a sheath 94. The instrument 120 can also include a catheter assembly 122. The lead assembly 121, including the distal tip 90 and the sheath 94 can be moved relative to the catheter assembly 122.

The catheter assembly 122 can include the tracking device 70' as a single unit or device including an EP tracking device 70a' and one or more windings of an EM tracking device 70b'. The EM tracking device 70b' can be positioned substantially over or around the EP tracking device 70a'. The EP tracking device 70a' can include an annular ring that is molded into or formed with the catheter assembly 122. The EP tracking device 70a' can be used with the EP tracking system 22 similar to the distal tip electrode 90 of the lead assembly 92. The EM tracking device 70b' can be used with the EM tracking system 24 similar to the windings 102, 104 of the EM tracking device 70b. Nevertheless, the EP tracking device 70a' and the EM tracking device 70b' can be positioned substantially atop one another. This allows for the tracked position of the EP tracking device 70a' and the tracked position of the EM tracking device 70b' to be substantially coincident throughout a tracked procedure. A signal from either of the EP tracking device 70a' or the EM tracking device 70b' can be transmitted along or with a communication system 124, which can include a wired or wireless transmission system.

Again, it will be understood, that the tracking device 70' can be tracked with the two tracking systems 22, 24. As discussed above, the electrode of the EP tracking device 70a' can sense a voltage within the patient 36. The EM tracking device 70b' can sense a magnetic field or electromagnetic field. Accordingly, the single tracking device 70' can be used with two or more tracking systems 22, 24 to determine a location of the tracking device 70' and the catheter and lead assembly 120. It will be further understood that the tip electrode 90 of the lead assembly 121 can also be used as the EP tracking device with the EP tracking system 22.

With reference to FIG. 4, a tracking device 70'' can include an EP tracking device 70a'' and an EM tracking device 70b''. The EP tracking device 70a'' can be positioned on a first instrument portion 26a and the EM tracking device 70b'' can be positioned on a second instrument portion 26b. The two instrument portions 26a, 26b can be positioned within the patient 36. Alternately, one of the two instrument portions 26 can be positioned relative to the patient 36 in any appropriate manner. For example, the second instrument portion 26b including the EM tracking device 70b'' can be positioned on an exterior surface of the patient 36 or be implanted as a fiducial or dynamic reference frame in the patient 36, such as fixed relative to the heart 84.

The two tracking devices **70a**" and **70b**" can be moved relative to one another during an operative procedure. For example, if both of the tracking devices **70a**" and **70b**" are positioned on two separate and moveable instruments **26a**, **26b** they can be moved to a known position relative to one another within the patient **36** during an operative procedure. Alternatively, if the second instrument **26b** is positioned at a fixed location relative to the patient **36**, the first instrument portion **26a** can be moved to a known position relative to the second instrument portion **26b** during an operative procedure. For example, fluoroscopic or ultrasound imaging, such as with the imaging system **30**, can be used to confirm or determine the known position of the first surgical instrument **26a** and the second instrument **26b**. Accordingly, during a second procedure, a position of the EP tracking device **70a**" and the EM tracking device **70b**" can be determined.

A location of the EP tracking device **70a**" can be determined with the EP tracking system **22**. The EM tracking system **24** can be used to determine the location of the EM tracking device **70b**". As discussed further herein, the determined location of the two tracking devices **70a**", **70b**" can be used to register the EP tracking system **22** and the EM tracking system **24**. The tracked position of the two instruments **26a**, **26b** can be used for illustration of an icon representing one or both of the instruments **26a**, **26b** on the display devices **38**, **40** relative to the image data **80**.

Turning reference to FIG. **5**, a flow chart or navigation method for registering or coordinating a dual tracking system **130** is illustrated. The navigation method **130** is illustrated briefly in FIG. **5** and further detailed in FIGS. **7A-7C** and **8**. The method of using a two tracking system navigation system will be discussed in an exemplary embodiment herein. It will be understood, however, that a navigation system including two or more tracking systems can be used according to various embodiments, including those discussed above. The assembly **92**, however, is discussed as an exemplary embodiment.

The navigation method **130**, as discussed in detail herein, allows for registration of the EP tracking system **22** to the EM tracking system **24** and further to the image data **80**. The EM tracking system **24** can be registered to the image data **80**, as discussed herein, including registering the navigation domain of the EM tracking system **24** with the image space. The EP tracking system **22**, including the navigation domain of the EP tracking system **22**, can be registered to the EM tracking system **24**, including the EM navigation domain, according to various embodiments, such as using the devices discussed above. The registration of the EP tracking system **22** to the EM tracking system **24** can allow the EP tracking system **22** to be registered to the image data **80**.

The navigation method **130** can include starting in start block **132**. The image data **80** can then be acquired in block **134**. In addition, with reference to FIG. **6**, the image data **80** can be displayed on the display device **40**. As discussed above, an icon **92i** can be superimposed on the image data **80** to represent a location of an appropriate instrument, such as the surgical instrument **26**. The image data **80** can include three dimensional or two dimensional image data that is acquired for representation or illustration of a portion of the patient **36**. It will be further understood that the image data **80** acquired in block **134** can be image data that is acquired preoperatively, intraoperatively, or at any appropriate time. It may also include a combination of preoperative and intraoperative image data. For example, preoperative image data can be merged or registered with intraoperative image data according to any appropriate technique. For example, 2D to

3D image registration can occur as described in U.S. patent application Ser. No. 10/644,680 filed Aug. 20, 2003, incorporated herein by reference.

The acquired image data can be stored or transferred to the processor system **44** which is a part of the navigation system **20** for use in illustrating a tracked location of the surgical instrument **26** relative to the patient **36**. To assist in illustrating the correct location of the surgical instrument **26** relative to the patient **36**, the patient space generally defined by the tracking system **22**, **24**, can be registered to the image data **80** or image space in block **136**. The registration of the image data **80** to the patient space can be with any appropriate method, as discussed above.

The registration of the image data **80** to the patient space can be performed with the EM tracking system **24**. The EM tracking system **24**, including the localizer **76**, can generate a field and navigation space which can be substantially known and definable Euclidean coordinates. The known navigation space can be efficiently and directly registered to Euclidean coordinates of the image data **80**. The known field of the EM localizer **76** allows a detected change in the field generated with the EM localizer **76** to be directly related to a distinct position or movement in the field at substantially all points in the field. In other words, a detected change of movement of the EM tracking device **70b** generally equals a selected known movement of the EM tracking device **70b** within the field regardless of the position of the EM tracking device **70b** within the field generated by the EM localizer **76**. Also, every space in the EM navigation domain is known due to the uniform electromagnetic field. Accordingly, a coordinate system identified or defined by the EM tracking system **24** can be substantially known and efficiently applied to the coordinate system of the image data **80**.

The registration of the image data **80** to the patient space identified with the EM tracking system **24** can be performed in any appropriate manner. As discussed above, point, contour, or any other appropriate registration processes can be used. For example, the EM tracking device **70b** can be positioned relative to known fiducials or landmarks within the patient **36** and similar or correlated landmarks or fiducials can be identified in the image data **80**. The processor system **44**, or any appropriate processor system, can then be used to register or correlate the points in the image data **80** to the points of the patient space. Once the registration has occurred, the image data **80** is registered to the patient space identified or within the navigation space defined by the EM tracking system **24**.

The EM tracking system **24** can be registered to the EP tracking system **22** in block **138**. The registration or coordination between the EM tracking system **24** and the EP tracking system **22** can occur at any appropriate time, such as before or after the EM tracking system **24** is registered to the image data in block **136**. The EP tracking system **22** can be registered to the EM tracking system **24** in block **138** in any appropriate manner. As discussed further herein, exemplary registration systems **138a**, **138b**, and **138c** are illustrated and described in greater detail in relation to FIGS. **7A-7C**. Once the EP tracking system **22** is registered with the EM tracking system **24**, navigation of the instrument **26** with only the EP tracking device **70a** can be done in block **140**. The navigation with the EP tracking device **70a** can be done and a position of the instrument **26** including the tracking device **70a** can be navigated relative to the image data **80** due to the registration of the EP tracking system **22** and the EM tracking system **24** in block **138**. Accordingly, navigation using only the EP tracking system **22** can occur in block **140**.

With continuing reference to FIGS. **5** and **6** and additional reference to FIG. **7A**, registration of the EM tracking system

and the EP tracking system, according to various embodiments, is illustrated in block **138a**. As discussed above, the lead assembly **92** can include the EP tracking device **70a** that can be defined by the tip electrode **90** of the lead **92**. The catheter **100** can include one or more coils **102, 104** of the EM tracking device **70b**. As illustrated in FIG. 6, the EM tracking device **70b** can be used to register the image data **80** to the patient space of the patient **36**.

Once the registration has occurred in block **136**, then the EP tracking system **22** can be registered with the EM tracking system **24** in block **138a**, illustrated in FIG. 7A. A lead or instrument including an EP electrode can be provided in block **152**. The EP electrode can be a distal tip electrode of the lead or can be provided in any other portion, such as in the sheath **94**. For example, as illustrated in FIG. 2A, the alternative EP tracking device **70a'** can be provided in the sheath **94**. Regardless of the position of the electrode it can be used as the EP tracking device **70a** and it can be positioned relative to the EM tracking device **70b** that is positioned within the catheter **100**. In addition, as illustrated in FIG. 2B, the lead including the EP tracking device **70a** can be moved relative to the catheter **100** in block **154**.

When moving the lead relative to the catheter **100**, it can be determined when the EP tracking device **70a** moves past or is near the coils **102, 104** of the EM tracking device **70b** in block **156**. Various mechanisms can be used to determine when the EP electrode **70a** moves past the EM tracking device **70b**. For example, a change in impedance, measured voltage, or other determinations can be used to determine when the EP electrode is next to or immediately past the EM tracking device **70b**.

When the determination is made that the EP tracking device **70a** has been positioned relative to the EM tracking device **70b**, such as substantially in the same position, a registration of the EM tracking system **24** and the EP tracking system **22** can occur in block **158**. The registration can occur by substantially coordinating or registering the EP tracking system **22** and the EM tracking system **24**. In other words, because the EP tracking system **22** can be used to determine the position of the EP tracking device **70a** and the EM tracking system **24** can be used to determine the position of the EM tracking device **70b** these two positions or points in patient space can be identified as the same. Accordingly, the navigation space of the EP tracking system **22** can be overlaid or registered with the navigation space of the EM tracking system **24**.

The coordination or registration between the EP tracking system **22** and the EM tracking system **24** can be performed by acquiring a selected number of points that are identical or at known locations relative to one another, as discussed above, with both of the tracking systems. For example, at least three corresponding points may be acquired though more points may be used to actually model or characterize the non-orthogonal or known navigation space defined by the EP tracking system **22**. Less information may be necessary in a local or small region than would be needed for a larger space, such as an entire navigation space. Once points with both of the tracking systems have been acquired a curvature model, such as a spline model, can be used to model the EP tracking system **22** coordinate system or navigation space. Other appropriate modeling calculations could also be used to computationally coordinate the EP tracking system **22** and the EM tracking system **24**.

Once the EM tracking system **24** and the EP tracking system **22** have been registered, movement of the EP tracking device **70a** within the patient space of the patient **36** can be illustrated superimposed on the image data **80**. As illustrated

in FIG. 6, icons illustrating the first tracking device **70ai** and second tracking device **70bi** can be illustrated and superimposed on the image data **80**. Once registration has occurred, however, the EP tracking device icon **70ai**, illustrating the position of the EP tracking device **70a**, can be illustrated separate from the EM tracking device icon **70bi**, representing the position of the EM tracking device **70b**, but correctly related to the image data **80**. It will be understood that an icon **92i** can represent generally the surgical instrument **26**, or any portion thereof, and not only the tracking devices. The position of the surgical instrument, however, can be identified or determined based upon the tracked position of the tracking device **70**.

Registration of the EP tracking system **22** with of the second navigation space, such as that of the EM tracking system **24**, can allow for image navigation of the instrument **26** tracked with only the EP tracking system **22**. The navigation space of the EP tracking system **22** may not be substantially uniform or strictly aligned with the image data **80**. For example, the tissue of the patient **36** may not be substantially uniform impedance. For example, the impedance of muscle tissue may be substantially different from the impedance of blood or other electrolyte. Accordingly, a particular change in voltage may not always be related to a single physical movement amount of the EP tracking device **70a**. Movement of the EP tracking device **70a** within the patient **36**, however, can be measured using the EP tracking system **22** once it is registered with a tracking system, such as the EM tracking system **24**, which can be registered to the image data **80**. A registered position of the EP tracking device **70a** can be superimposed on the image data **80**. Therefore, a position of the EP tracking device **70a** can be superimposed on the image data **80** even if a non-uniform navigation space is generated with the EP tracking system **22**.

Returning reference to FIG. 7B, registering the EP tracking system **22** and the EM tracking system **24** can be achieved with registration method **138b**. According to the registration method **138b**, a catheter can be provided with an EP electrode as the EP tracking device **70a** in block **170**. A lead assembly can be provided with the EM tracking device **70b** in block **172**. The lead can then be moved relative to the catheter in block **174**. A determination can be made when the EM tracking device **70b** is aligned with or at a selected and known position relative to the EP tracking device **70a** in block **176**. A registration of the EM tracking system **24** and the EP tracking system **22** can then occur in block **178**. The registration method **138b** can be substantially similar to the registration method **138a** (illustrated in FIG. 7A) save that the EP electrode is positioned in the catheter **100** and the EM tracking device **70b** is positioned on the lead. Therefore, registration can occur in substantially the same way and tracking of the EP tracking device **70a** can occur and superimposition of a position of the EP tracking device **70a** can be illustrated relative to the image data **80**.

Turning to FIG. 7C, a registration method **138c** is illustrated. The registration method **138c** can include positioning the EM tracking device **70b** at a known location in the patient **36** or other navigable space in block **184**. The EM tracking device **70b** can be any appropriate device, for example the second tracked instrument **26b** illustrated in FIG. 4. The second tracked device **26b** can be a second instrument moved relative to the patient **36**, a dynamic reference frame fixed relative to the patient **36**, or any appropriate device including the EM tracking device **70b**. For example, the DRF **26b'** can be positioned relative to the patient **36** at a fixed and known location. The known location of the DRF **26b'** can be determined in any appropriate manner. For example, a registration

probe (not illustrated) can be moved relative to the DRF **26b'** to determine the location of the DRF **26b'**. In addition, the DRF **26b'** can be positioned or include a fiducial that is identified in the image data **80** to allow for identification and registration to the image data **80**. Alternatively, if the second instrument **26b** is a moveable instrument, it can be moved to a landmark that can also be identified within the image data **80**.

When the second tracked device **26b, 26b'** is identified relative to the image data **80** and the EM tracking system **24** is registered to the image data **80**, the first tracked instrument **26a** including the EP tracking device **70a** can be moved relative to the second tracked device **26b, 26b'**. For example, the first instrument **26a**, illustrated in FIG. 4, can move to the location of the DRF **26b'** in block **186**. Once the first tracked instrument **26a** is at the same position as the DRF **26b'**, registration of the EM tracking system **24** and the EP tracking system **22** can occur in block **188**. As discussed above, the location of the two tracking devices **70a, 70b** can be determined to be substantially identical when they are positioned next to each other to allow for registration of the two tracking systems **22, 24**.

It will be further understood that when two tracked instruments **26a, 26b** are provided, they can be positioned at a known position and orientation relative to one another to allow for registration to occur in block **188**. For example, it will be understood, the first tracked instrument **26a** can be positioned at a known position and orientation relative to the DRF **26b'** and registration can occur. In other words, knowing a position and orientation of the DRF **26b'** and position and orientation of the EP tracking device **70a** can allow for registration of the two tracking systems **22, 24** even if the two tracking devices **70a, 70b** are not in substantially identical locations. As discussed above, imaging systems can be used to determine or identify the known locations of the two tracking devices **70a, 70b**.

Registration of the EP tracking system **22** and the EM tracking system, **24** can also occur by providing the EP tracking device **70a** and the EM tracking device **70b** substantially at the same position on the tracked instrument **26**, as illustrated with the instrument **120** in FIG. 3. When the tracking device **70** has substantially only one location for both the EP tracking system **22** and the EM tracking system **24** a determination of registration is not otherwise required, including positioning the EP tracking device **70a** relative to the EM tracking device **70b**. Rather, the tracked position of the EM tracking device **70b** with the EM tracking system **24** can be used to correlate the position of the EP tracking device **70a** inherently since all positions determined with the EM tracking device **70b** are inherently registered with the EP tracking device **70a**. Therefore, the coordinate system of the EM tracking system **24** can be used to illustrate a position of the EP tracking device **70a** on the image data **80** at all times. This can allow or be used to acquire more than one point that is the same position with both of the tracking devices **70a** and **70b**. This can assist in registration of the EP tracking system **22** and the EM tracking system **24**. It will be understood, however, that the two tracking devices **70a** and **70b** need not be the same device to acquire more than one point that is at the same position with both of the tracking devices **70a** and **70b**.

Even when the two tracking devices **70a, 70b** are the same device or formed to be at the same or fixed relative positions, a third tracking device can be provided. For example, the tip electrode **92** can also be interconnected with the controller **72**. Thus, the position of the tip electrode **92** can be tracked once it has exited the catheter **122**.

In addition, or alternatively, it will be understood that the EP tracking device **70a** and the EM tracking device **70b** need not be positioned on top of one another, but can be positioned substantially at a known fixed location relative to one another or next to each other with a selected assembly. For example, an electrode of the EP tracking device **70a** can be positioned substantially abutting coils of wire defining the EM tracking device **70b**. They can also be positioned a distance from one another at a substantially known location, at least when a device is at a known configuration. The known relationship or relative positions of the EP tracking device **70a** and the EM tracking device **70b** can be used to register the EP tracking system **22** and the EM tracking system **24** even if the EP tracking device **70a** and the EM tracking device **70b** are not at the same location.

Turning to FIG. 8, navigating the EP tracking device **70a** in block **140** is described in further detail. Movement of the EP tracking device **70a** can be determined in block **200**. The movements of the EP tracking device **70a** can then be registered to the coordinates of the EM tracking system **24** in block **202**. As discussed above, registration of the EP tracking system **22** and the EM tracking system **24** allow for a registration of a coordinate in the EM tracking system **24** with a determined position of the EP tracking device **70a** in the EP tracking system **22**.

Because of the registration of the EP tracking system **22** and the EM tracking system **24**, a position of the EP tracking device **70a** can be illustrated or displayed on the display device **38, 40** in block **204**. As discussed above regarding FIG. 6, a tracked position of just the EP tracking device **70a** with the EP tracking system **22** can be displayed on the display device **40** relative to the image data **80**. For example, the icon **70ai** representing a position of the instrument tracked with the EP tracking device **70a** can be displayed on the image data **80**.

Merging preoperative acquired image data, such as the image data **80**, can be done to intraoperative acquired image data in block **206**. The merging of the image data can occur in any appropriate manner. One appropriate method can include contour merging, which matches contours in the preoperative acquired image data and intraoperative acquired image data. For example, if image data of a vertebra is acquired preoperatively and contours of a vertebra is acquired intraoperatively they can be matched. The contours can be manually or automatically determined in the image data and matched between image data sets.

Additionally, tracking the EP tracking device **70a** can be used to create point clouds for various organs. For example, a point cloud or point cloud map can be generated for a portion of the heart **84**. The point cloud can then be matched, such as with contour matching or landmark matching, with preoperative acquired image data. Point cloud matching or generation includes identifying one or more points with the tracking device **70**, such as with the EP tracking device **70a** to generate a surface of a volume. Appropriate cloud mapping techniques include those described in U.S. patent application Ser. No. 12/117,537, filed on May 8, 2008, incorporated herein by reference. It will be understood, however, that the generation of the point cloud can be made with either the EP tracking device **70a** or the EM tracking device **70b**. However, the EP tracking device **70a**, which can include an electrode, can be provided at a selected size, such as one that will easily maneuver within the heart **84** to allow for an efficient generation of the cloud map by identifying a plurality of points. Accordingly, a selected one of the tracking devices **70a, 70b** can be

efficiently used to generate a selected type of data, such as a landmark or cloud map, for merging of intraoperative and preoperative image data.

In addition, the electrode **92** of the lead **90** can be used as the EP tracking device **70a**. The tip electrode **92** can be implanted in the heart **84**. Accordingly, image data **80**, which can be pre- or intra-operatively acquired, can be used to identify or suggest a selected location of the lead tip **92**. By correlating the EM tracking system **24** and the EP tracking system **22** a selected location identified relative to the image data **80** can be used to guide the electrode **92** to an appropriate or selected location for implantation. An additional tracking device, such as the EM tracking device **70b**, is not required to track the electrode **92** to a selected location within the heart **84** with the image data **80** because of the registration of the EM tracking system **24** and the EP tracking system **22**. Suggesting a placement of a lead tip can be based on any appropriate information, such as historical data, statistical data, or atlas models. Exemplary suggestion systems include those disclosed in U.S. Patent Application Publication No. 2002/0097806, published on May 20, 2004, incorporated herein by reference.

Providing registered tracking systems can be used for various purposes. As discussed above, the EM tracking system **24** and the EP tracking system **22** can be used for different tracking purposes or in different locations. In addition, the EP tracking system **22** may not generate an appropriate signal in various portions of the patient **36**. For example, if the EP tracking device **70a** is not positioned within a portion of the patient **36** that includes an electrolyte or appropriately conducted material, a voltage may not be generated relative to the EP tracking device **70a** when a current is induced in the patient **36**. Therefore, the EM tracking device **70b** can be used to track the position of the instrument **26** relative to the patient **36**.

According to various embodiments, the EP tracking device **70a** can be substantially smaller than the EM tracking device **70b**. For example, the EP tracking device **70a** may only include a single wire or small conductive member to act as an electrode. The small dimensions of the electrode of the EP tracking device **70a** can allow it to move to selected locations, such as within the heart **84**, which may not be accessible with a larger tracking device, such as the EM tracking device **70b**. Therefore, providing the EP Tracking system **22** and the EM tracking system **24** can allow for tracking the surgical device **26**, or any appropriate device, with more than one modality.

The EP tracking system **22** can be used to track the lead electrode **90** as the EP tracking device **70a**. Accordingly, the EP tracking system **22** can be used to track the location of the lead electrode **90** to its intended implantation site or location with the EP tracking device **70a**. The tracked position can then be displayed on the display devices **38**, **40** for viewing by the surgeon **34**.

The EP tracking system **22**, however, may not be directly registerable to the image data **80**. As discussed above, varying impedances of tissue of the patient **36** may inhibit registration of the EP tracking system **22** with the image data **80**. Lack of registration with the image data **80** can reduce effectiveness of image navigation.

The EM tracking system **24**, however, can be registered with the image data **80**. The EM tracking system **24**, including the more uniform navigation domain, can be registered to the image data **80**. In determining one or more points, also referred to as identity points, in both the EP tracking system **22** navigation domain and the EM tracking system **24** navigation domain the two tracking systems can be registered.

This can allow the EP tracking system **22** to be registered to the image data **80**. Registration can also allow the use of pre-acquired image data that can be registered to intraoperative image data or other appropriate image data for navigation of the instrument **26** with the EP tracking device **70a**.

In addition, the two tracking systems **22**, **24** can be used for complimentary purposes. For example, the EM tracking system **24** may have a higher accuracy than the EP tracking system **22**. Therefore the EM tracking system **24** can be used to determine locations of various landmarks for registration, while the EP tracking system **22** is used for navigation of the instrument **26** for implantation. Also, if location and size permits, the EM tracking system **24** can be used to confirm a location of the instrument **26** after implantation.

Further, the EM tracking system **24** can track the tracking device **70b** in the absence of a conductive material. Thus, the EP tracking device **70a** can be used to track the instrument when a conductive medium and current is present (e.g. within the heart **84**) and the EM tracking device **70b** can be used to track the instrument **26** when the conductive medium is not present (e.g. exterior to the heart **84**).

It will be further understood that the tracking systems **22**, **24** can be used to track any appropriate device relative to any appropriate volume. For example, positioning a device within an enclosed volume may be selected for building, manufacturing, or repairing various workpieces in selected workspaces. For example, a device can be moved relative to an enclosed volume, such as within an airplane, robot, or other enclosed areas without requiring open visualization or access within the volume. The enclosed volume of the workpiece or workspace, may also include more than one type of environment. Accordingly, having multiple tracking systems using differing tracking modalities can be used to track a single instrument or two parts of the single instrument within any appropriate volume.

The foregoing description of the embodiments has been provided for purposes of illustration and description. It is not intended to be exhaustive or to limit the invention. Individual elements or features of a particular embodiment are generally not limited to that particular embodiment, but, where applicable, are interchangeable and can be used in a selected embodiment, even if not specifically shown or described. The same may also be varied in many ways. Such variations are not to be regarded as a departure from the invention, and all such modifications are intended to be included within the scope of the invention.

What is claimed is:

1. A system for tracking an instrument within a volume, comprising:
 - a first electromagnetic tracking system including a first tracking device operable to determine a position of the first tracking device within a first tracking domain;
 - a second electropotential tracking system including:
 - a plurality of current electrodes operable to induce a current into the volume to form a second tracking domain;
 - a second tracking device operable to sense a voltage at the second tracking device based upon the induced current;
 - an instrument having a first portion connected to the first tracking device and a second portion connected to the second tracking device to allow tracking of the instrument with at least one of the first tracking system or the second tracking system, wherein the second portion is operable to move relative to the first portion to place the second tracking device at a known position relative to the first tracking device;

15

a controller in communication with the first electromagnetic tracking system and the second electropotential tracking system;
 wherein the controller is operable to determine a registration of the first tracking domain and the second tracking domain based on at least the position of the first tracking device relative to the second tracking device within the volume;
 wherein the registration is operable to allow tracking of the instrument with either of the first electromagnetic tracking system or the second electropotential tracking system in the volume.

2. The system of claim 1, further comprising:
 an imaging system operable to acquire image data of the volume;
 wherein the first electromagnetic tracking system is operable to generate an electromagnetic field defining a tracking volume domain of a determined uniformity within the volume allowing the first tracking domain to be registered to the image data.

3. The system of claim 2, wherein the first electromagnetic tracking system includes a localizer;
 wherein either of the localizer or the first tracking device is operable to generate the electromagnetic field and the other of the localizer or the first tracking device is operable to sense the electromagnetic field;
 wherein the electromagnetic field defines the first tracking domain.

4. The system of claim 2, wherein the imaging system is operable to acquire image data of the first tracking device and the second tracking device to determine the position of the first tracking device and the second tracking device relative to each other within the volume.

5. The system of claim 1, wherein the instrument having the first portion and the second portion includes:
 an outer member as the first portion and an inner member as the second portion, wherein the outer member and the inner member are operable to move relative to one another;
 wherein the outer member is connected to the first tracking device and the second inner member is connected to the second tracking device.

6. The system of claim 1, wherein the first tracking device is configured to be fixedly associated with the volume;
 wherein the second tracking device is moveable to a known position relative to the first tracking device;
 wherein when the second tracking device is at the known position, the controller is operable to correlate the position of the first tracking device relative to the second tracking device and correlate the first tracking domain relative to the second tracking domain.

7. The system of claim 1, wherein the instrument is a catheter and lead assembly;
 wherein the catheter includes a first tracking device and the lead includes the second tracking device.

8. The system of claim 7, wherein the first tracking device is one or more coils of wire and the second tracking device includes an electrode.

9. The system of claim 1, wherein the first tracking device and the second tracking device are formed as a single device operable to be tracked within both of the first electromagnetic tracking system and the second electropotential tracking system.

10. The system of claim 9, wherein the single device includes a first portion defining an electrode to sense a voltage and a second portion operable to sense or generate a field.

16

11. The system of claim 1, wherein the instrument includes both the first tracking device and the second tracking device operable to be positioned at a known position relative to one another in at least a first orientation of the instrument.

12. The system of claim 1, wherein the instrument includes a lead having an electrode;
 wherein the electrode of the lead is the second tracking device.

13. A method of tracking an instrument using at least a first tracking system and a second tracking system, comprising:
 providing the first tracking system to determine a position of a first tracking device, including:
 generating an electromagnetic field to define a first navigation space in a volume;
 determining a first position of the first tracking device with the generated electromagnetic field;
 providing the second tracking system to determine a position of a second tracking device, including:
 generating a current in the volume to define a second navigation space;
 sensing a voltage with the second tracking device;
 determining a second position of the second tracking device based upon the sensed voltage;
 registering the first tracking system and the second tracking system based upon moving the second tracking device to a known position relative to the first tracking device; and
 tracking the second tracking device with the second tracking system and illustrating on a display device a position of the second tracking device based upon the registration of the first tracking system and the second tracking system.

14. The method of claim 13, further comprising:
 providing image data of the volume;
 registering the image data to the first navigation space; and
 illustrating on the display device the determined first position of the first tracking device.

15. The method of claim 14, wherein moving the second tracking device to a known position relative to the first tracking device includes:
 positioning the first tracking device on a tube;
 moving the second tracking device through the tube; and
 measuring a signal change when the second tracking device moves past the first tracking device.

16. The method of claim 14, wherein registering the first tracking system and the second tracking system, includes:
 determining a first identity position in the volume with the first tracking device in the first navigation space;
 determining a second identity position in the volume with the second tracking device in the second navigation space;
 relating a selected plurality of points in the second navigation space with a selected plurality of points in the first navigation space based upon the known first identity position and the second identity position;
 calculating a position with the second tracking system of the second tracking device once the second tracking device is no longer at the identity position; and
 displaying a tracked position of the second tracking device on the display device relative to the image data.

17. The method of claim 16, wherein determining the first identity position includes determining a plurality of first identity positions and determining a second identity position includes determining a plurality of second identity positions; and

17

registering the first tracking system and the second tracking system based on the determined plurality of first identity positions and plurality of second identity positions.

18. The method of claim **17**, wherein determining a first identity position includes positioning the first tracking device at substantially the same location as the second tracking device.

19. The method of claim **16**, wherein determining the first position of the first tracking device and the second position of the second tracking device includes:

acquiring image data of the first tracking device and the second tracking device; and

determining spatial positions of both the first tracking device and the second tracking device in the image data.

20. The method of claim **16**, further comprising:

selecting a position to implant a lead; and navigating a lead with the image data based upon the tracked position of the second tracking device alone.

21. The method of claim **16**, further comprising:

illustrating a selected position of implantation for a lead on the image data; and

navigating a lead to the selected position while substantially only tracking the position of the second tracking device.

22. The method of claim **13**, further comprising:

providing a catheter including the first tracking device; and providing a lead including the second tracking device.

23. The method of claim **13**, further comprising:

providing a lead including the second tracking device; wherein the lead includes an electrode as the second tracking device.

24. A system for tracking an instrument including a tracking device operable to be tracked within a volume, comprising:

a tracking device including:

a tip electrode,

an annular ring electrode, and

a coil of conductive material wrapped relative to a surface of the annular ring; and

a first electromagnetic tracking system for determining a position of the coil of conductive material within a first tracking domain;

a second electropotential tracking system including:

a plurality of current electrodes operable to induce a current into the volume to form a second tracking domain;

wherein the tip electrode and the annular ring electrode are operable to sense a voltage based upon the induced current;

18

a communication system interconnecting the tip electrode, the annular ring and the coil of conductive material with both the first tracking system and the second tracking system;

an instrument having a first portion connected to the tip electrode and a second portion connected to the annular ring electrode and the coil of conductive material to allow tracking of the instrument with at least the second tracking system, wherein the second portion is operable to move relative to the first portion to place the annular ring electrode at a known position relative to the tip electrode;

a controller in communication with the first electromagnetic tracking system and the second electropotential tracking system;

wherein the controller is operable to determine a registration of the first tracking domain and the second tracking domain based on at least the position of the annular ring relative to the coil of conductive material within the volume;

wherein the registration is operable to allow tracking of the first portion with the second electropotential tracking system in the volume.

25. The system of claim **24**, wherein the first electromagnetic tracking system includes:

a first localizer operable to generate an electromagnetic field or sense an electromagnetic field;

wherein the coil of conductive material is operable to generate an electromagnetic field or sense an electromagnetic field.

26. The system of claim **24**, further comprising:

a display device;

wherein the first or second tracking system is in communication with the display device and operable to display a represented position of the annular ring, the coil of conductive material, or combinations thereof.

27. The system of claim **26**, wherein image data is operable to be displayed on the display device relative to the representation of the annular ring and the coil of conductive material.

28. The system of claim **24**, further comprising:

wherein the second portion defines a cannula and the annular ring and coil of conductive material are positioned around the cannula.

29. The system of claim **28**, wherein the instrument includes at least one of a catheter, an implantable lead, or combinations thereof.

* * * * *