



US008186191B2

(12) **United States Patent**
Bacon

(10) **Patent No.:** **US 8,186,191 B2**
(45) **Date of Patent:** **May 29, 2012**

(54) **REMOTELY OPERATED LOCKING PADDLE HANDLE LATCH ASSEMBLY FOR CLOSURES AND THE LIKE**

(75) Inventor: **Bruce C. Bacon**, Rockford, MI (US)

(73) Assignee: **Bauer Products, Inc.**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **12/952,230**

(22) Filed: **Nov. 23, 2010**

(65) **Prior Publication Data**

US 2011/0126598 A1 Jun. 2, 2011

Related U.S. Application Data

(60) Provisional application No. 61/264,935, filed on Nov. 30, 2009.

(51) **Int. Cl.**

B60R 25/02 (2006.01)
B62H 5/04 (2006.01)
E05B 13/10 (2006.01)
F16C 3/00 (2006.01)
G05G 5/00 (2006.01)

(52) **U.S. Cl.** **70/208; 70/256; 70/257; 70/277; 70/279.1; 70/283.1; 292/DIG. 31; 292/40; 292/201; 292/216**

(58) **Field of Classification Search** **70/208, 70/256, 257, 277, 279.1, 283.1; 292/DIG. 31, 292/40, 201, 216**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,677,834 A * 7/1987 Hicks 70/279.1
4,892,338 A * 1/1990 Weinerman et al. 292/35

4,986,576 A * 1/1991 Anderson 292/40
5,127,686 A 7/1992 Gleason et al.
5,595,076 A * 1/1997 Weinerman et al. 70/208
5,606,882 A * 3/1997 Larsen et al. 70/369
5,927,773 A 7/1999 Larsen et al.
6,409,234 B1 * 6/2002 Larsen et al. 292/173
6,513,353 B1 * 2/2003 Weinerman et al. 70/208
6,651,467 B1 11/2003 Weinerman et al.
D485,155 S * 1/2004 Bacon D8/338
6,685,240 B2 2/2004 Bacon
6,701,761 B1 * 3/2004 Chang et al. 70/337
6,708,537 B1 * 3/2004 Eschweiler et al. 70/208
6,758,503 B2 7/2004 Sadler
6,845,641 B2 * 1/2005 Hsieh 70/257
6,854,304 B2 2/2005 Linares
6,857,298 B2 2/2005 Linares
6,962,375 B2 11/2005 Linares
7,237,812 B2 * 7/2007 Tweedy 292/40
2007/0056338 A1 * 3/2007 Sabo et al. 70/257
2008/0258867 A1 * 10/2008 Harris et al. 340/5.64
2010/0300162 A1 * 12/2010 Cappuccio et al. 70/257

* cited by examiner

Primary Examiner — Suzanne Barrett


Assistant Examiner — David E Sosnowski

(74) *Attorney, Agent, or Firm* — Price Heneveld LLP

(57) **ABSTRACT**

A locking paddle handle assembly for closures has a housing with a paddle handle pivotally mounted therein, a latch which latches and unlatches the closure upon rotation of the paddle handle, and an exterior key lock with a movable member that shifts between locked and unlocked positions. A deadbolt lock selectively engages the closure frame in the locked position to positively retain the closure closed. The deadbolt lock is operably connected with the movable key lock member, such that movement of the latter between the latched and unlatched positions contemporaneously shifts the deadbolt lock between the locked and unlocked positions. A remotely operable controller is operably connected with the deadbolt lock to power shift the same between the locked and unlocked positions from a remote location.

7 Claims, 6 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

1

**REMOTELY OPERATED LOCKING PADDLE
HANDLE LATCH ASSEMBLY FOR
CLOSURES AND THE LIKE**

CROSS-REFERENCE TO RELATED
APPLICATIONS AND CLAIM TO PRIORITY

The present invention is related to commonly assigned, U.S. patent application Ser. No. 12/639,516, filed Dec. 16, 2009, entitled LOCKING PADDLE HANDLE LATCH ASSEMBLY FOR CLOSURES AND THE LIKE, which is hereby incorporated herein by reference, and claims priority under 35 U.S.C. §119(e) to related provisional U.S. Patent Application Ser. No. 61/264,935, filed Nov. 30, 2009.

BACKGROUND OF THE INVENTION

The present invention relates to latches for movable closures and the like, and in particular to a remotely operated locking paddle handle latch assembly.

Paddle handles are generally well known in the art, and are typically flush mounted on an associated closure or door to facilitate selectively shifting the closure between an open unlatched position and closed latched position. Paddle handle assemblies are used widely on entry doors for recreational vehicles, motor homes and the like, and in such applications, require that the latch mechanism be accessible and operable from both the inside and the outside of the vehicle, and that they include a deadbolt lock for maximum security.

Heretofore, paddle handle assemblies have proven generally effective, although they experience certain drawbacks. For example, such prior art paddle handle assemblies are not particularly adapted for use with remotely operated power actuators, which have become quite popular in the recreational vehicle industry. Hence, a paddle handle assembly which overcomes such drawbacks would clearly be advantageous.

SUMMARY OF THE INVENTION

One aspect of the present invention is a remotely operated locking paddle handle assembly for closures and the like having a housing adapted for mounting in or adjacent an associated closure of the type that can be shifted between an open position and a closed position. A paddle handle is pivotally mounted in an interior portion of the housing for rotation between a retracted position and an extended position. A latch is operably connected with the paddle handle, and configured such that when the paddle handle is in the retracted position, the latch is in the latched position, wherein the closure cannot be unintentionally shifted from the closed position, and when the paddle handle is in the extended position, the latch is in an unlatched position, wherein the closure is free to be shifted from the closed position to the open position. A key lock is mounted on an exterior portion of the housing, and includes a movable key lock member that is selectively moveable between a locked position and an unlocked position. A deadbolt lock is movably mounted in the housing for shifting between a locked position, wherein the closure is positively retained in the closed position, and an unlocked position, wherein the closure is free to be shifted between the open position and closed position. The deadbolt lock is operably connected with the movable key lock member, whereby movement of the movable key lock member between the locked and unlocked positions shifts the deadbolt lock between the locked and unlocked positions. A remotely operated controller is operably connected with the deadbolt

2

lock, and when activated, shifts the deadbolt lock between the locked and unlocked positions from a remote location.

Another aspect of the present invention is a remotely operated paddle handle assembly that has an uncomplicated design which is efficient in use, economical to manufacture, capable of a long operating life, and particularly well adapted for the proposed use.

These and other advantages of the invention will be further understood and appreciated by those skilled in the art by reference to the following written specification, claims and appended drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a front elevational view of a remotely operated locking paddle handle latch assembly embodying the present invention.

FIG. 2 is a rear elevational view of the paddle handle latch assembly.

FIG. 3 is a left-hand side elevational view of the lockable paddle handle latch assembly.

FIG. 4 is a right-hand side elevational view of the lockable paddle handle latch assembly.

FIG. 5 is a bottom elevational view of the lockable paddle handle latch assembly.

FIG. 6 is a rear elevational view of the lockable paddle handle latch assembly, wherein portions thereof have been broken away to reveal internal construction.

FIG. 7 is a perspective view of a deadbolt lock cam portion of the lockable paddle handle latch assembly.

FIG. 8 is a side elevational view of the deadbolt lock cam.

FIG. 9 is a front elevational view of the deadbolt lock cam.

FIG. 10 is another side elevational view of the deadbolt lock cam.

FIG. 11 is a perspective view of the paddle handle latch assembly shown with an associated remotely operated controller.

FIG. 12 is a rear elevational view of the paddle handle latch assembly with portions thereof broken away to reveal internal construction, along with the remotely operated controller.

DETAILED DESCRIPTION OF THE PREFERRED
EMBODIMENTS

For purposes of description herein, the terms “upper”, “lower”, “right”, “left”, “rear”, “front”, “vertical”, “horizontal” and derivatives thereof shall relate to the invention as oriented in FIG. 1. However, it is to be understood that the invention may assume various alternative orientations and step sequences, except where expressly specified to the contrary. It is also to be understood that the specific devices and processes illustrated in the attached drawings, and described in the following specification, are simply exemplary embodiments of the inventive concepts defined in the appended claims. Hence, specific dimensions and other physical characteristics relating to the embodiments disclosed herein are not to be considered as limiting, unless the claims expressly state otherwise.

The reference numeral **1** (FIGS. 1-4) generally designates a remotely operated locking paddle handle latch assembly embodying the present invention. Locking paddle handle latch assembly **1** includes a housing **2** adapted for mounting in or adjacent to an associated closure of the type that can be shifted between an open position and a closed position. A paddle handle **4** is pivotally mounted in an interior portion of housing **2** for rotation between a retracted position and an extended position. A latch **5** is operably connected with

3

paddle handle **4**, and configured such that when paddle handle **4** is in the retracted position, latch **5** is in a latched position, wherein the closure cannot be unintentionally shifted from the closed position, and when paddle handle **4** is in the extended position, latch **5** is in an unlatched position, wherein the closure is free to be shifted from the closed position to the open position. A key lock **6** is mounted on an exterior portion of housing **2**, and includes a movable key lock member **7** that is selectively movable between a locked position and an unlocked position. A deadbolt lock **9** is mounted in housing **2** for shifting between a locked position, wherein the closure is positively retained in the closed position, and an unlocked position, wherein the closure is free to be shifted between the open and closed positions. Deadbolt lock **9** is operably connected with movable key lock member **7**, such that movement of the movable key lock member **7** between the locked and unlocked positions shifts the deadbolt lock **9** between the locked and unlocked positions. A remotely operated controller **11** (FIGS. **11** and **12**) reciprocates between locked and unlocked positions, and is operably connected with deadbolt lock **9** to shift the same between the locked and unlocked positions from a remote location.

As best illustrated in FIGS. **1-5**, the illustrated housing **2** has a two part construction, comprising an exterior plate **22** in which paddle handle **4** is pivotally mounted, and an interior plate **23** which mounts on the interior of the closure and is attached to exterior plate **22** by fasteners. The illustrated exterior plate **22** includes a centrally disposed, bowl-shaped recess **24** located directly behind paddle handle **4** which provides finger access to facilitate rotation of paddle handle **4** between the retracted and extended positions. The bottom wall of recess **24** includes an actuator window through which an actuator tab on paddle handle **4** extends to operate latch **5**. The marginal portion of exterior plate **22** includes a lock aperture **27** in which key lock **6** is mounted.

The inside surface of exterior plate **22** includes a cylindrical-shaped lock boss **34**, the interior of which defines lock aperture **27**. The interior plate **23** of housing **2** includes a marginal portion **40** which engages the interior surface of the closure, as well as fastener bosses **41** and a lock boss **42**. The rearwardmost or interior side edge **48** of interior plate **23** is contoured to define a stationary interior handle **49** which facilitates opening and closing the closure from the interior portion of the vehicle. A release lever **50** is pivotally mounted on the interior surface of interior plate **23**. Release lever **50** includes a forwardly protruding actuator tab which extends through to the latch **5** to selectively shift the same to the unlatched position. An interior lock knob **52** is pivotally received in lock boss **42** on the interior plate **23**, and is operably connected with the deadbolt lock **9** as described below.

In the illustrated example, the moveable key lock member **7** is in the form of a cylindrical lock plug which is received in the lock aperture **27** on the exterior housing plate **22**, and is rotatably mounted in lock boss **34** for rotation between locked and unlocked positions. A multi-arm deadbolt lock cam **74** is pivotally mounted in the interior end of lock boss **34**, and is operably connected with key lock member **7** for rotation therewith. The illustrated deadbolt lock cam **74** has a first crank arm **76** that is operably connected with deadbolt lock **9**. As best illustrated in FIGS. **7-10**, deadbolt lock cam **74** has a cylindrical-shaped base **77** with a recessed end oriented toward exterior housing plate **22** and a faced shaft **78** oriented toward interior housing plate **23**. The shaft **78** on deadbolt lock cam **74** extends through the lock boss **42** in the interior housing plate **23**, and the lock knob **52** is mounted on the interior end thereof, such that rotation of lock knob **52** from

4

the interior of the vehicle rotates deadbolt lock cam **74** between the locked and unlocked positions, and simultaneously shifts the deadbolt lock **9** between the locked and unlocked positions.

The illustrated deadbolt lock **9** includes a deadbolt **80** slidably mounted in the exterior housing plate **22**, and includes an outer end which extends exterior of housing **2** for engagement with an associated strike bolt assembly, and an inner end which extends interior of housing **2**. A link **83** has a first end **84** thereof pivotally connected with the inner end **82** of deadbolt **80**, and a second end **85** thereof pivotally connected with the first crank arm **76** of lock cam **74**, such that rotation of key lock member **7** between the locked and unlocked positions longitudinally shifts the deadbolt **80** between the locked and unlocked positions.

The multi-arm lock cam **74** also includes a second crank arm **130**, which is adapted for operable connection with remotely operable controller **11**, which rotates lock cam **74**, and shifts the deadbolt lock **9** between the locked and unlocked positions. More specifically, crank arm **130** includes an aperture **131** adjacent its outer end into which an actuator rod **133** is received, which is operably connected with remotely operable controller **11**, which is typically mounted in the vehicle door. In the illustrated example, remotely operated controller **11** includes a linear actuating device **15** in the form of a solenoid or the like, which has a plunger portion **13** that shifts or reciprocates longitudinally between locked and unlocked positions in response to a remotely generated signal. The illustrated remotely operable controller **11** also includes a signal receiver portion **12** which actuates the motor upon detection of an appropriate radio frequency signal or the like. Remote actuation of the controller **11** longitudinally shifts the actuator rod **133**, which in turn rotates deadbolt lock cam **74** and shifts deadbolt **80** between the locked and unlocked positions.

In the foregoing description, it will be readily appreciated by those skilled in the art that modifications may be made to the invention without departing from the concepts disclosed herein. Such modifications are to be considered as included in the following claims, unless these claims by their language expressly state otherwise.

The invention claimed is as follows:

1. A remotely operated locking paddle handle latch assembly for closures and the like, comprising:
 - a housing adapted for mounting adjacent an associated closure of the type that can be shifted between an open position and a closed position;
 - a paddle handle pivotally mounted in an exterior portion of said housing for rotation between a retracted position and an extended position;
 - a latch operably connected with said paddle handle, and configured such that when said paddle handle is in said retracted position, said latch is in a latched position, wherein the closure cannot be unintentionally shifted from the closed position, and when said paddle handle is in said extended position, said latch is in an unlatched position, wherein the closure is free to be shifted from the closed position to the open position;
 - a key lock mounted on said exterior portion of said housing, and including a movable key lock member rotatable mounted in said key lock for selectively pivoting between a locked position and an unlocked position;
 - a deadbolt lock movably mounted in said housing for shifting between a locked position, wherein the closure is positively retained in the closed position, and an unlocked position, wherein the closure is free to be shifted between the open and closed positions; said

5

deadbolt lock being operably connected with said movable key lock member, whereby movement of said movable key lock member between said locked and unlocked positions shifts said deadbolt lock between said locked and unlocked positions;

a remotely operable controller operably connected with said deadbolt lock and power shifting the same between said locked and unlocked positions from a remote location; and

a multi-arm lock cam rotatably mounted in said housing and operably connected with said key lock member for rotation therewith; said lock cam having a first crank arm operably connected with said deadbolt lock and a second crank arm operably connected with said remotely operable controller.

2. A remotely operated locking paddle handle latch assembly as set forth in claim 1, wherein:

said deadbolt lock includes a deadbolt having a locked and an unlocked position slidably mounted in said housing with an outer end thereof which extends exterior of said housing, an inner end thereof which extends interior of said housing, and a first link having a first end thereof pivotally connected with said inner end of said deadbolt, and a second end thereof pivotally connected with said first crank arm of said lock cam, such that rotation of said key lock member between said locked and unlocked positions longitudinally shifts said deadbolt between said locked and unlocked positions.

3. A remotely operated locking paddle handle latch assembly as set forth in claim 2, wherein:

6

said remotely operable controller includes a linear actuating device and a signal receiver which actuates said linear actuating device upon detection of a predetermined signal.

4. A remotely operated locking paddle handle latch assembly as set forth in claim 3, wherein:

said linear actuating device includes a reciprocating plunger; and including

an actuator rod having an outer end thereof pivotally connected with an outer end of said plunger and an inner end thereof pivotally connected with said second crank arm of said lock cam, whereby reciprocation of said plunger rotates said lock cam and longitudinally slides said deadbolt between said locked and unlocked positions.

5. A remotely operated locking paddle handle latch assembly as set forth in claim 4, wherein:

said linear actuating device comprises a solenoid.

6. A remotely operated locking paddle handle latch assembly as set forth in claim 5, including:

a fixed handle operably connected with an interior portion of said housing and shaped to facilitate manually shifting the closure between the open and closed positions from an interior side of the closure.

7. A remotely operated locking paddle handle latch assembly as set forth in claim 6, including:

an interior lock actuator mounted on said interior portion of said housing, and operably connected with said lock cam for rotation therewith, such that shifting said interior lock actuator between locked and unlocked positions shifts both said deadbolt lock and said latch lock between said locked and unlocked positions.

* * * * *