



US008192402B2

(12) **United States Patent**
Anderson et al.

(10) **Patent No.:** **US 8,192,402 B2**
(45) **Date of Patent:** **Jun. 5, 2012**

(54) **ACCESS DEVICE**

(75) Inventors: **Janelle Anderson**, New York, NY (US);
Michael Tal, Woodbridge, CT (US);
Steven F. Bierman, Del Mar, CA (US)

(73) Assignee: **Access Scientific, Inc.**, San Diego, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1076 days.

(21) Appl. No.: **12/106,119**

(22) Filed: **Apr. 18, 2008**

(65) **Prior Publication Data**

US 2008/0262430 A1 Oct. 23, 2008

Related U.S. Application Data

(60) Provisional application No. 60/912,645, filed on Apr. 18, 2007, provisional application No. 60/948,136, filed on Jul. 5, 2007.

(51) **Int. Cl.**

A61M 5/178 (2006.01)
A61M 25/16 (2006.01)
A61M 25/18 (2006.01)
A61M 39/00 (2006.01)
A61M 39/10 (2006.01)
A61M 39/02 (2006.01)

(52) **U.S. Cl.** **604/164.1**; 604/164.13; 604/165.03; 604/166.01; 604/535; 604/538

(58) **Field of Classification Search** 604/165.01–165.04, 164.01, 164.04, 604/164.07, 523, 533, 534, 535, 538, 539
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,539,034 A * 11/1970 Tafeen 604/164.09
3,565,074 A 2/1971 Foti et al.
3,995,628 A 12/1976 Gula et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0139091 7/1984
(Continued)

OTHER PUBLICATIONS

Arrow Trauma Products No. TRM-C 12/00 11M, Arrow International.

International Search Report for PCT Application No. PCT/US/2006/011624, mailed Oct. 17, 2007.

International Search Report for PCT Application No. PCT/US/2002/041371, mailed Oct. 2, 2003.

A photograph of various access devices.

Office Action from EP 08746350.1-2310, dated Jun. 17, 2011.

(Continued)

Primary Examiner — Kevin C Sirmons


Assistant Examiner — William Carpenter

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear LLP

(57) **ABSTRACT**

An access device places a medical article within a body space of a patient. The device has a needle that includes a needle body and hub. The device further includes a dilator coaxially disposed and slideable over the needle body and a medical article. A viewing space is disposed between the dilator and the medical article with at least one passageway or conduit connecting the viewing space with the interior bore of the needle body. The passageway is defined at least in part by openings through the sides of the needle and dilator. At least a portion of the conduit or passageway can be defined by one or more grooves between the needle and dilator. The device can further include a guidewire and an interlock between the guidewire and the needle and/or dilator. The device can further include one or more stops disposed between the guidewire and the needle and/or dilator to limit the extent to which the guidewire can be moved (e.g., advanced) relative to the needle or inhibit such relative movement (e.g., backwards movement).

58 Claims, 10 Drawing Sheets



U.S. PATENT DOCUMENTS

4,068,659 A 1/1978 Moorehead
 4,205,675 A 6/1980 Vaillancourt
 4,230,123 A * 10/1980 Hawkins, Jr. 600/435
 4,345,596 A * 8/1982 Young 604/264
 4,411,655 A 10/1983 Schreck
 4,417,886 A 11/1983 Frankhouser et al.
 4,512,351 A * 4/1985 Pohndorf 607/117
 4,525,157 A 6/1985 Vaillancourt
 4,581,019 A * 4/1986 Curelaru et al. 604/164.05
 4,629,450 A 12/1986 Suzuki et al.
 4,655,750 A 4/1987 Vaillancourt
 4,661,300 A 4/1987 Daugherty
 4,772,264 A * 9/1988 Cragg 604/158
 4,791,937 A 12/1988 Wang
 4,850,975 A 7/1989 Furukawa
 4,869,259 A 9/1989 Elkins
 4,894,052 A 1/1990 Crawford
 4,944,728 A 7/1990 Carrell
 4,955,890 A 9/1990 Yamamoto et al.
 4,961,729 A 10/1990 Vaillancourt
 4,978,334 A 12/1990 Toyote et al.
 4,995,866 A 2/1991 Amplatz et al.
 5,066,284 A 11/1991 Mersch et al.
 5,098,392 A * 3/1992 Fleischhacker et al. . 604/164.05
 5,108,374 A 4/1992 Lemieux
 5,112,308 A 5/1992 Olsen et al.
 5,114,401 A 5/1992 Stuart et al.
 5,158,544 A 10/1992 Weinstein
 5,171,218 A 12/1992 Fonger et al.
 5,242,410 A 9/1993 Melker
 5,242,427 A 9/1993 Bilweis
 5,246,426 A 9/1993 Lewis et al.
 5,250,038 A 10/1993 Melker et al.
 5,255,691 A * 10/1993 Otten 607/117
 5,295,969 A 3/1994 Fischell
 5,295,970 A 3/1994 Clinton et al.
 5,306,253 A 4/1994 Brimhall
 5,312,355 A 5/1994 Lee
 5,328,480 A 7/1994 Melker et al.
 5,330,433 A 7/1994 Fonger et al.
 5,336,191 A * 8/1994 Davis et al. 604/165.01
 5,342,315 A 8/1994 Rowe et al.
 5,366,441 A 11/1994 Crawford
 5,380,290 A 1/1995 Makower et al.
 5,391,178 A 2/1995 Yapor
 5,512,052 A * 4/1996 Jesch 604/158
 5,542,932 A 8/1996 Daugherty
 5,589,120 A 12/1996 Khan et al.
 5,676,689 A 10/1997 Kensery et al.
 5,685,856 A * 11/1997 Lehrer 604/164.1
 5,688,249 A 11/1997 Chang et al.
 5,704,914 A 1/1998 Stocking et al.
 5,712,229 A 1/1998 Hopkins et al.
 5,728,132 A 3/1998 Van Tassel et al.
 5,795,339 A 8/1998 Erskine
 5,810,780 A 9/1998 Brimhall et al.
 5,820,596 A 10/1998 Rosen et al.
 5,827,202 A 10/1998 Miraki et al.
 5,830,190 A 11/1998 Howell
 5,833,662 A 11/1998 Stevens
 5,858,002 A 1/1999 Jesch
 5,885,217 A 3/1999 Gisselberg et al.
 5,885,253 A 3/1999 Liu
 5,904,657 A 5/1999 Unsworth et al.
 5,910,132 A 6/1999 Schultz
 5,919,160 A 7/1999 Sanfilippo
 5,935,110 A 8/1999 Brimhall
 5,954,708 A * 9/1999 Lopez et al. 604/533
 6,027,480 A 2/2000 Davis et al.
 6,046,143 A 4/2000 Khan et al.
 6,074,377 A 6/2000 Sanfilippo
 6,080,141 A 6/2000 Castro et al.
 6,120,494 A 9/2000 Jonkman
 6,156,010 A 12/2000 Kuracina et al.
 6,159,179 A 12/2000 Simonson
 6,179,813 B1 1/2001 Ballow et al.
 6,210,366 B1 4/2001 Sanfilippo

6,273,871 B1 8/2001 Davis et al.
 6,277,100 B1 8/2001 Raulerson
 6,336,914 B1 * 1/2002 Gillespie, III 604/165.01
 6,436,070 B1 8/2002 Botich et al.
 6,461,362 B1 10/2002 Halseth et al.
 6,475,207 B1 11/2002 Maginot
 6,488,662 B2 12/2002 Sirimanne
 6,500,152 B1 12/2002 Illi
 6,524,277 B1 2/2003 Chang
 6,607,511 B2 8/2003 Halseth et al.
 6,626,868 B1 9/2003 Prestidge et al.
 6,641,564 B1 * 11/2003 Kraus 604/164.1
 6,692,462 B2 2/2004 Mackenzie et al.
 6,692,482 B2 2/2004 Heller et al.
 6,695,816 B2 2/2004 Cassidy
 6,726,659 B1 4/2004 Stocking et al.
 6,808,520 B1 10/2004 Fourkas
 6,836,687 B2 12/2004 Kelley
 6,905,481 B2 6/2005 Sirimanne
 6,994,693 B2 2/2006 Tal
 7,001,396 B2 2/2006 Glazier et al.
 7,025,746 B2 4/2006 Tal
 7,182,755 B2 2/2007 Tal
 7,192,433 B2 * 3/2007 Osypka et al. 606/108
 7,270,649 B2 9/2007 Fitzgerald
 7,503,596 B2 * 3/2009 Rome et al. 285/384
 7,556,617 B2 7/2009 Voorhees, Jr. et al.
 7,722,567 B2 * 5/2010 Tal 604/164.01
 7,922,696 B2 4/2011 Tal et al.
 2002/0072712 A1 6/2002 Nool et al.
 2003/0032927 A1 2/2003 Halseth et al.
 2003/0088212 A1 5/2003 Tal
 2003/0171718 A1 9/2003 DeLegge
 2003/0199827 A1 10/2003 Thorne
 2003/0216771 A1 11/2003 Osypka et al.
 2004/0092879 A1 5/2004 Kraus et al.
 2004/0171988 A1 9/2004 Moretti
 2004/0193112 A1 * 9/2004 Glazier et al. 604/164.1
 2007/0282300 A1 12/2007 Attawia et al.
 2008/0262431 A1 10/2008 Anderson et al.
 2009/0221961 A1 9/2009 Tal et al.
 2011/0009827 A1 1/2011 Bierman et al.
 2011/0021994 A1 1/2011 Anderson et al.

FOREIGN PATENT DOCUMENTS

EP 0502714 11/1995
 EP 806221 11/1997
 KR 20050027359 3/2005
 WO WO 02/36179 A2 5/2002
 WO WO/03057272 7/2003
 WO WO/2007/046850 4/2007
 WO WO 2010/048449 4/2010
 WO WO 2010/056906 5/2010
 WO WO 2010/083467 7/2010
 WO WO 2010/132608 11/2010

OTHER PUBLICATIONS

Photos of a peripheral emergency infusion device Applicant believes to be produced by Arrow International Inc.
 Photos of a splittable catheter design.
 Photos of an infusion device Applicant believes to be produced by B. Braun Medical Inc.
 Results of Preliminary Report of PCT/US2008/060914 filed Apr. 18, 2008, mailed Oct. 29, 2009.
 Examination Report for European Application No. 02806219.8-2310 dated Sep. 18, 2007.
 Examination Report for European Application No. 02806219.8-2310 dated May 16, 2008.
 Results of Partial International Search for PCT Application No. PCT/US/2008/060930, mailed Oct. 29, 2008.
 Results of Partial International Search for PCT Application No. PCT/US/2008/060914, mailed Oct. 29, 2008.
 International Search Report for PCT Application No. PCT/US/2008/051950, mailed Oct. 22, 2008.

* cited by examiner




FIG. 1




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4B




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16

1**ACCESS DEVICE****CROSS-REFERENCE TO RELATED
APPLICATIONS**

This application is related to and claims the benefit under 35 U.S.C. §119(e) to U.S. Provisional Patent Application Ser. No. 60/912,645 (filed Apr. 18, 2007) and 60/948,136 (filed Jul. 5, 2007), all of which are hereby expressly incorporated by reference in their entireties.

BACKGROUND**1. Field of the Invention**

This invention is generally directed to access devices for introducing and/or delivering a medical article (such as, for example, a catheter, cannula, sheath, etc.) into a body space, such as, for example, an artery, vein, vessel, body cavity, or drainage site.

2. Description of the Related Art

A preferred non-surgical method for inserting a catheter or vascular sheath into a blood vessel involves the use of the Seldinger or a modified Seldinger technique, which includes an access needle that is inserted into a patient's blood vessel. A guidewire is inserted through the needle and into the vessel. The needle is removed, and a dilator and sheath in combination or separately are then inserted over the guidewire. The dilator and sheath, together or separately, are then inserted a short distance through the tissue into the vessel, after which the dilator and guidewire are removed and discarded. A catheter or other medical article may then be inserted through the sheath into the vessel to a desired location, or the sheath may simply be left in the vessel.

A number of vascular access devices are known. U.S. Pat. Nos. 4,241,019, 4,289,450, 4,756,230, 4,978,334, 5,124,544, 5,424,410, 5,312,355, 5,212,052, 5,558,132, 5,885,217, 6,120,460, 6,179,823, 6,210,332, 6,726,659 and 7,025,746 disclose examples of such devices. None of these devices, however, has the ease and safety of use that physicians and other healthcare providers would prefer. Thus, there exists a need for an easier-to-use and safer vascular access device, especially one that would clearly and promptly indicate when a blood vessel has been punctured and one that would reduce accidental needle sticks and other attendant risks of over-wire vascular access.

SUMMARY

Embodiments of the present invention involve several features for an access device useful for the delivery of a catheter or sheath into a space within a patient's body, such as, for example, a blood vessel or drainage site. Without limiting the scope of this invention, its more prominent features will be discussed briefly. After considering this discussion, and particularly after reading the Detailed Description of the Preferred Embodiments section below in combination with this section, one will understand how the features and aspects of this invention provide several advantages over prior access devices.

One aspect of the present invention involves an access device for placing a medical article within a body space. The device includes a needle having a needle body and a dilator coaxially disposed about the needle body and having a dilator shaft. The device further includes a medical article coaxially disposed about the dilator and a plurality of openings extending through a side of at least one of the needle body and the dilator shaft. The device further includes at least one opening

2

in the other one of the needle body and dilator shaft. The plurality of openings are spaced about the one of the needle body or dilator shaft so that at least one of the plurality of openings at least partially overlaps the at least one opening in the other one of the needle body and dilator shaft when the needle body is rotationally clocked relative to the dilator shaft in a first position and in a second position. The second position is different than the first position. The device further includes a viewing space disposed between the dilator and the medical article and at least one passageway connecting the viewing space with an interior bore of the needle body. The passageway is defined at least in part by the plurality of openings and the at least one opening.

In some embodiments, these side openings are aligned or are overlapped to permit the flow of blood or other body fluid from the needle to the viewing space. In other embodiments, the side openings can be configured to overlap regardless of the rotational orientation of the dilator relative to the needle. For example, by irregularly spacing and/or slotting the side openings in one or both of the needle and the dilator, one or more passageways through the side walls of the needle and dilator can be provided.

In some embodiments, the conduit or passageway is (although need not be) formed between the side openings in the dilator and the needle to connect the interior bore of the needle body with the viewing space. At least a portion of the conduit or passageway can be defined by one or more grooves that are formed (e.g., by scoring) on an outer side surface of the needle, on an inner side surface of the dilator surface, or on both the needle outer side surface and the dilator inner side surface. In this latter form, the grooves can oppose each other or can overlap at one or more points to define a portion of the passageway.

In additional embodiments, the conduit or passageway that places the side openings in communication can be formed by incongruous shapes (e.g., incongruous radial cross-sectional shapes) between the needle outer surface and the dilator inner surface. For example, the needle outer surface can have a circular shape and the dilator inner surface can have an oval shape with a minor dimension of the oval substantially equals the diameter to the circle, or vice versa. The needle outer surface and the dilator inner surface also can have other incongruous shapes, such as, but without limitation, a triangle and a circle, a square and a circle, and a square and a triangle, where the needle supports the dilator at least at two points.

The viewing space, which occurs between an inner surface of the sheath and an outer surface of the dilator, can have an annular shape and can have an axial length that is almost coextensive with the length of the sheath. In other embodiments, the annular space can be significantly smaller than the elongated annular space just described. For example, but without limitation, the space can take the form of one or more annular grooves (or a fraction(s) of such an annular groove(s)) that is or are disposed at a distal, mid and/or proximal portion(s) of the sheath. For example, but without limitation, a groove can be formed on an outer surface the dilator with the side opening extending from a bottom of the groove through the side of the dilator. The space alternatively can have a linear, curved or spiral shape along an axial length of the sheath or can be formed by a plurality of such shapes. For example, one or more axial and/or spiral grooves can be formed (e.g., by scoring) on an outer side surface of the dilator, on an inner side surface of the sheath, or on both the dilator outer side surface and the sheath inner side surface. In this latter form, the grooves can oppose each other or can overlap at one or more points to define the passageway.

Another aspect of the present invention involves an access device for placing a medical article within a body space. The device includes a needle that has a needle body, a dilator coaxially disposed about the needle body and that has a dilator shaft. The device further includes a guidewire and an interlock between the guidewire and at least one of the needle and the dilator.

The interconnection or interlock may comprise an attachment connecting the guidewire to at least one area on the needle body, needle hub, and/or dilator hub. Additionally, the interconnection or interlock may comprise an attachment to the guidewire so that the guidewire cannot be totally retracted into the bevel tip or inadvertently advanced too far, resulting in intravascular guidewire loss.

The interlock or interconnection can be configured to maintain a guidewire length beyond the needle tip when advanced. The length of guidewire extension beyond the bevel tip is sufficient to prevent unwanted or accidental punctures and injury, both inside and outside the patient's body. Additionally, the interlock or interconnection can be configured to retain the guidewire to the access device so that the guidewire is not misplaced or lost in the patient's body.

The interlock or interconnection can comprise a release member adapted to engage a lock member on either the needle and/or dilator. The lock member releasably locks the needle and dilator hubs together. When the guidewire is advanced by a sufficient extent, the release member cooperates with and releases the lock member to release the dilator hub from the needle hub. Once the lock member is released, the dilator (and possibly the medical article) can be advanced over the needle.

Another aspect of the invention involves an access device for placing a medical article within a body space. The device includes a needle that has a needle body and a dilator coaxially disposed about the needle body. The device further includes a lock member configured to move between a lock state and an unlock state. The lock member connects the needle to the dilator so as to inhibit at least relative axial movement between at least a portion of the needle and at least a portion of the dilator when the lock member is in at least the lock state. The device further includes a guidewire configured to be coaxially disposed within at least a portion of the needle body and a release member configured to engage with the lock member so as to at least move the lock member from the lock state to the unlock state.

Another aspect of the present invention involves a method of locking a guidewire to an access device. The method includes releasably locking a dilator to a needle so as to inhibit at least relative axial movement between at least a portion of the needle and at least a portion of the dilator. The method further includes sliding a release member and guidewire in a distal direction relative to the locked dilator and needle, the guidewire being attached to the release member and engaging the release member with at least one of the dilator and needle so as to unlock the dilator from the needle and inhibit at least relative axial movement between at least a portion of the guidewire and at least a portion of the needle.

Another aspect of the present invention involves an access device for placing a medical article within a body space. The device includes a needle having a needle body, a dilator coaxially disposed about the needle body and having a dilator shaft, a guidewire, and one or more stops disposed between the guidewire and at least one of the needle and the dilator.

In some embodiments, the one or more stops (which can be adjustable) limit the extent to which the guidewire can be moved (e.g., advanced) relative to the needle or inhibit such relative movement (e.g., backwards movement). In some

modes, a stop can be disposed at the proximal end of the guidewire to inhibit the proximal end from slipping into the proximal end of the needle (e.g., into the needle hub). In other modes, the stop can be positioned just proximal to the needle hub to help regulate the length of guidewire that can be advanced from the needle tip. In still other modes, the stop can be slid along the guidewire and set in a position thereon (e.g., near the needle hub). Preferably, an interaction (e.g., interference, friction, mechanical coupling, adhesion, etc.) exists between the guidewire and the stop to inhibit relative movement between these components.

Another aspect of the present invention involves an access device that has a releasable interlock. The interlock inhibits relative rotational movement between a needle and a dilator, at least when the needle is inserted into a patient. By inhibiting such relative rotational movement, side openings in the needle and dilator can be held in alignment to provide a simplified passageway through which the blood or fluid may flow. Thus, when the needle enters a blood vessel or drainage site in the patient, blood or other body fluid quickly flows into a passageway. The resulting blood or fluid flash is visible through the medical article (sheath or catheter) to indicate that the needle tip has entered the vessel or drainage site.

For example, but without limitation, the dilator can comprise, in some embodiments, a dilator hub and dilator having one or more side openings. The dilator hub may have a luer connection and a releasable locking mechanism. The releasable locking mechanism can be configured to releasably engage and secure the dilator to another part, such as the needle hub. When the needle hub and the dilator hub are releasably locked to prevent rotation therebetween, one or more of the side openings in the dilator are aligned with one or more side openings in the needle. The locking mechanism can also be configured to inhibit unintentional relative axial movement between the needle and the dilator.

These and other aspects of the present invention will become readily apparent to those skilled in the art from the following detailed description of the preferred embodiments, which refers to the attached figures. The invention is not limited, however, to the particular embodiments that are disclosed.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other features, aspects, and advantages of the invention disclosed herein are described below with reference to the drawings of preferred embodiments, which are intended to illustrate and not to limit the invention. Additionally, from figure to figure, the same reference numerals have been used to designate the same components of an illustrated embodiment. The following is a brief description of each of the drawings.

FIG. 1 is a perspective view of a preferred embodiment of an access device configured in accordance with the present invention and shows coaxially aligned needle, dilator, medical article, and guidewire.

FIG. 2A is side view of a needle of the embodiment depicted in FIG. 1.

FIG. 2B is a cross-sectional view of the needle of the embodiment depicted in FIG. 2A taken along line A-A.

FIG. 3A is a side view of the dilator portion of the embodiment depicted in FIG. 1.

FIG. 3B is a proximal end view of the dilator portion of FIG. 3A.

FIG. 3C is a cross-sectional view of the dilator portion of the embodiment depicted in FIG. 3A, taken along line B-B.

5

FIG. 4A is a side view of a sheath of the embodiment from FIG. 1.

FIG. 4B is a proximal end view of the sheath of FIG. 4A.

FIG. 5 is a side view of the access device of FIG. 1.

FIG. 6 is an enlarged cross-sectional view of a portion the embodiment illustrated in FIG. 5 which is circled by line C-C.

FIG. 7 is a similar cross-sectional view of a portion of an access device which is configured in accordance with another preferred embodiment of present invention.

FIG. 8 is a similar cross-sectional view of a portion of an access device which is configured in accordance with an additional preferred embodiment of present invention.

FIG. 9 is an enlarged cross-sectional view of a needle hub with a guidewire extending therethrough, wherein the needle hub and the guidewire are configured in accordance with another preferred embodiment of the present invention.

FIG. 10 is an enlarged cross-sectional view of a needle hub with a guidewire extending therethrough, wherein the needle hub and the guidewire are configured in accordance with a further preferred embodiment of the present invention.

FIG. 11 is an enlarged cross-sectional view of a needle hub with a guidewire extending therethrough, wherein the needle hub and the guidewire are configured in accordance with an additional preferred embodiment of the present invention.

FIG. 12 is an enlarged view of a section of a guidewire configured in accordance with a further preferred embodiment of the present invention.

FIG. 13 is an enlarged view of a section of a guidewire configured in accordance with another preferred embodiment of the present invention.

FIG. 14 is an enlarged side view of a proximal end of an access device, including a guidewire with a release mechanism, which are configured in accordance with an additional embodiment of the present invention.

FIG. 15 is an enlarged side view of a proximal end of an access device that is configured in accordance with another embodiment of the present invention.

FIG. 16 is a side view of a guidewire configured in accordance with another embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present disclosure provides an access device for the delivery of a medical article, for example a catheter or sheath, to a blood vessel or drainage site that overcomes possible disadvantages associated with conventional non-surgical catheter insertion techniques.

The present disclosure provides an access device for the delivery of a medical article (e.g., catheter or sheath) to a blood vessel or drainage site. FIG. 1 illustrates an access device 102 that is configured to be inserted into a blood vessel (e.g., a vein or an artery) in accordance with a preferred embodiment of the present invention. While the access device is described below in this context (i.e., for vascular access), the access device also can be used to access and place a medical article (e.g., catheter or sheath) into other locations within a patient's body (e.g., a drainage site) and for other purposes (e.g., for draining an abscess).

The present embodiment of the access device is disclosed in the context of placing an exemplary single-piece, tubular medical article into a body space within a patient. Once placed, the tubular article can then be used to receive other medical articles (e.g., catheters, guidewires, etc.) to provide access into the body space, and/or used to provide a passage way for introducing fluids into the body space or removing (e.g., draining) fluids from the body space. In the illustrated

6

embodiment, the tubular medical article is a sheath or catheter that is configured primarily to provide a fluid passage into a vein. The principles of the present invention, however, are not limited to the placement of single piece sheaths or catheters, or to the subsequent insertion of a medical article via the sheath or catheter. Instead, it will be understood by one of skill in this art, in light of the present disclosure, that the access device disclosed herein also can be successfully utilized in connection with placing one or more other types of medical articles, including other types of sheaths, fluid drainage and delivery tubes, and single or multi-lumen catheters directly in the patient or indirectly via another medical article.

For example, but without limitation, the access device disclosed herein can also be configured to directly or indirectly place central venous catheters, peripherally inserted central catheters, hemodialysis catheters, surgical drainage tubes, tear-away sheaths, multi-piece sheaths, scopes, as well as electrical conduit for wires or cables connected to external or implanted electronic devices or sensors. As explained above, the medical articles listed above may be directly placed in the patient via the dilator, needle, and guidewire of the access device or subsequently placed within the patient via a medical article that was placed within the patient via the dilator, needle, and guidewire of the access device.

Further, the embodiments disclosed herein are not limited to co-axial insertion of a single medical article. For example, two catheters may be inserted in the patient via an inserted sheath or a second catheter may be inserted in the patient via an inserted first catheter. Further, in addition to providing a conduit or passageway into the vessel or other body space, the medical article inserted via the dilator, needle, and guidewire can form a lumen that is in addition to the lumen(s) of the subsequently inserted medical article. One skilled in the art can also find additional applications for the devices and systems disclosed herein. Thus, the illustration and description of the access device in connection with a sheath (e.g., for micro puncture applications) is merely exemplary of one possible application of the access device.

The access device 102 comprises a needle 20, a dilator 28, a sheath (e.g., catheter or cannula) 58, and a guidewire 120. In preferred embodiments, the dilator 28 is coaxially mounted on the needle 20, and the sheath 58 is coaxially mounted on the dilator 28.

In the illustrated embodiment, the needle 20, dilator 28, and sheath 58 are releasably interlocked at the proximal end 110 of the access device 102. In some embodiments, the releasable interlock between the needle 20, dilator 28, and sheath 58 is a linear interlock where the dilator 28 is locked to the needle 20 at interface 101 and the sheath 58 is locked to the dilator 28 at interface 103. Preferably, the needle 20 locks to the dilator 28 via a lock mechanism 26. The lock mechanism 26 may comprise an engaging mechanism such as hinged clips 27 with clip sides 29. The hinged clips 27 may releasably engage and secure the dilator 28 to the needle 20. In some embodiments, the clip sides 29 engage and secure the dilator 28 by clipping to the outer lip of a luer connection 33 on the dilator 28. Although hinged clips 27 are shown, the lock member 26 may comprise any suitable engaging mechanism known in the art. In the illustrated embodiment, as best seen in FIG. 3B, the portions of the outer lip onto which the hinge clips 27 engage are flats to inhibit rotation of the needle hub 21 relative to the dilator hub 32 after a certain degree of relative rotation (e.g., 180 degrees) between the needle hub 21 and the dilator hub 32.

Similarly, the sheath 58 is secured to the dilator 28 through a lock member 59. The sheath 58 may, preferably, comprise a twist lock member 59 so that the user may releasably engage

and secure the dilator **28** to the sheath **58**. In some preferred embodiments, the dilator **28** comprises teeth or prongs that are configured to mate or attach to corresponding areas on the sheath **58**. Preferably, the needle **20**, dilator **28** and sheath **58** are releasably locked so that a physician or user may remove sections or portions of the access device as needed for treatment.

FIGS. **2A** and **2B** depict the needle **20** of the preferred embodiment shown in FIG. **1**. FIG. **2A** shows a side view of the needle **20** and FIG. **2B** provides a cross-sectional view of the needle **20**. As shown in both FIGS. **2A** and **2B**, the needle **20** has a needle body **22**, distal end **106**, and proximal portion **24**. Preferably, the proximal portion **24** has a needle hub **21** and the lock member **26**.

The needle body **22** preferably has an elongated tubular shape having a circular, constant-diameter inner bore and a circular, constant-diameter exterior surface. In other embodiments, however, the needle body **22** can have other bore and exterior shapes (such as, for example, but without limitation, an oval cross-sectional shape).

The needle body **22** has a sufficiently long length to access a targeted subcutaneous body space and has a sufficient gauge size to withstand the insertion forces when accessing the body space without causing undue trauma. For many applications, the needle body can have a length between 3-20 cm, and more preferably between 3-10 cm. For example, to access a body space (e.g., a vessel) in the thorax of an adult human, the needle body **22** preferably has a length of 7 cm or greater, and more preferably has a length of 9 cm or greater, and most preferably has a length of 9 to 10 cm. The size of the needle preferably is 18 gauge or smaller, and more preferably between 18-26 gauge, and most preferably between 18-26 gauge. For applications with a neonate, the length and gauge of the needle body **22** should be shorter and smaller, for example preferably between 3-4 cm and between 26-28 gauge.

As best seen in FIGS. **2A** and **2B**, the needle body **22** includes at least one fenestration or opening **34** near a distal end of the needle body **22**. The fenestration **34** extends through the wall of the needle body **22**. In addition, the needle body **22** can have a bevel tip **108** disposed on the distal portion **106**.

The needle hub **21** may also include locking structures at the proximal portion and distal portion of the needle hub **21**. These locking structures may be a luer-thread-type or another type of connections. In the illustrated embodiment, a luer connection **35**, such a luer lock or slip, is disposed at the proximal portion **24** of the needle **20**. This allows the physician or healthcare provider, for example, to introduce a guidewire **120** through the hollow portion of the luer connection **35**, through the needle body **22**, and into a punctured vessel. Additionally, a physician or healthcare provider may also attach a syringe to the luer connection **35** to perform other procedures as desired.

As discussed above, in preferred embodiments, the needle hub **21** comprises the lock member **26**. The lock member **26** may be configured to lock or secure another part such as, for example, the dilator **28** or the sheath **58**, to the needle **20**. As shown in FIG. **2A**, the lock member **26** can comprise an engaging mechanism such as a pair of hinged clips **27**, although other types of locking mechanisms comprising tabs and/or slots can also be used. Preferably, the clip sides **29** of the hinged clips **27** can engage a lipped surface such as the outer lip **37** of a luer connection **33** to the dilator **28**, shown in FIG. **1**. Once engaged, the clip sides **29** prevent the locked part from undesired slipping or releasing. In certain embodiments, the clips **27** are hinged to provide a bias towards the

center of the needle hub **21**. Preferably, the bias prevents the secured part from slipping or disengaging from the hinged clips **27**. More preferably, the bias of the hinged clips **27** can be overcome by simultaneously applying pressure to or squeezing the sides **29** of the clips **27** to release, for example, a luer connection to the luer connection **33** from the needle hub **21**. To apply the appropriate releasing pressure, a physician or healthcare provider may, for example, place an index finger and thumb on the sides **29** of the hinged clips **27** and apply squeezing pressure to overcome the hinge bias. The hinged clips **27** will, preferably, release only when sufficient releasing pressure is applied to both clip sides **29**.

The needle proximal portion **24** may have color coding, words, or other indicia, such as a pivot or notch, to indicate to the operator the position of the bevel tip **108** relative to the dilator **28** or the sheath **58**. Also, there may be a mechanical fit between the dilator **28** and the needle body **22** so that the physician or healthcare provider would sense by feel or sound (e.g., by a click) when the needle body **22** has been rotated to change the position of the bevel tip **108**. The needle body **22** can be rotated relative to the dilator **28** and sheath **58**, so that the bevel tip **108** can be inserted into the blood vessel with bevel tip up, and can be rotated **180** degrees so that the bevel tip **108** is down after successful insertion. When the bevel tip **108** is in this position, it may be less likely that movement of the needle body **22** will cause injury to the blood vessel.

FIGS. **3A**, **3B**, and **3C** provide a side view of an entire dilator **28**, a side view of the dilator hub **32** from the proximal end **45**, and a cross-sectional view of a dilator **28**, respectively, for the embodiment described in FIG. **1**. As shown, the dilator **28** may comprise a dilator shaft **30** and a dilator hub **32**. The dilator shaft **30** may further comprise one or more side openings or fenestrations **111**. The dilator hub **32** preferably comprises a luer connection **33** with an outer lip **37**. In some embodiments, the outer lip **37** can be configured to engage to a lock member **26** on the needle **20**.

Additionally, the dilator shaft **30** may be coaxially mounted to the needle body **22** by slipping the hollow section **113** of the dilator shaft **30** over the needle body **22** and releasably securing the dilator hub **32** to the needle hub **21**. Preferably, the proximal end **45** of the dilator hub **32** is configured to mechanically fit and interlock with the needle lock member **26** to inhibit some rotational and axial motion. More preferably, the dilator shaft **30** is releasably mounted to the needle body **22** so that the dilator shaft **30** can be mounted and released, or vice versa, from a coaxial position relative to the needle body **22**.

In some embodiments, the dilator hub **32** further comprises a locking mechanism **39**. In FIG. **3A**, the locking mechanism **39** comprises posts, teeth, or prongs projecting from the dilator hub **32**. These teeth **39** can be configured to mate or attach to corresponding receiving areas disposed on another part such as the sheath **58** or the needle hub **21**. This locking mechanism **39** will be explained in greater detail in the following section.

FIGS. **4A** and **4B** show side views of the medical article or sheath **58** illustrated in FIG. **1**. FIG. **4B** provides a side view from the proximal end **57**. The medical article preferably, but not necessarily, includes a sheath **58**. In preferred embodiments, the sheath **58** comprises a sheath body **54** and a sheath hub **53**. The sheath body **54** may be made partially or completely from a clear, translucent, semi-opaque, or transparent material. Such transparent, translucent, semi-opaque and clear materials allow a clinician the ability to see when blood or other body fluids flows into the needle, through the needle side opening(s), through the side dilator opening(s), and into the viewing space between the dilator and sheath.

The sheath body **54** may be a single piece sheath through which a catheter or other medical article (e.g., a guidewire) is inserted into the vessel. In such an embodiment, the sheath body **54** forms a conduit for insertion of the catheter or other medical article (e.g., a guidewire). In addition to providing a conduit, the sheath or a portion of the sheath can form a lumen that is in addition to the lumen(s) of the catheter. For example, an equivalent to a triple lumen catheter can be formed by inserting a dual lumen catheter through the sheath body **54** with the sheath body **54** itself forming a third lumen. The sheath hub **53** may further comprise winged ends **55** and a lock member **59**.

Preferably, the lock member **59** may comprise a locking or attaching structure that mates or engages with a corresponding structure. For example, the lock member **59** may comprise indentations, bumps, or grooves designed to engage and secure the teeth **39** on the dilator hub **32** described above in FIG. **2A**. The sheath hub **53**, as best seen in FIGS. **4A** and **4B**, preferably is designed so that the teeth **39** of the dilator hub **32** can enter the sheath hub **53** substantially unobstructed. However, in use, once the sheath hub **53** is placed at a desired location over the dilator shaft **30**, the physician or healthcare provider can twist the sheath hub **53** and disengage the locking member **59**. The locking member **59** can be, for example, a protruding bump, dent, etc., that creates a mechanical fit so that the dilator hub **32** and the sheath hub **53** are releasably interlocked. In the illustrated embodiment, the locking member **59** of the sheath hub **53** comprises a pair of axial arranged grooves which extend from an end of the sheath hub **53** and terminate at a protruding bump, dent, etc. Preferably, the locked position can be disengaged by twisting the dilator hub **32** relative to the sheath hub **53**. Additionally, the sheath hub may comprise wings **55** or handle structures to allow for easy release and removal of the sheath body **54** from other parts.

In some applications, the wings **55** are sized to provide the healthcare provider with leverage for breaking apart the sheath hub **53**. For example, the sheath hub **53** may comprise a thin membrane **61** connecting the halves of the sheath hub **53**. The membrane **61** is sized to keep the halves of the sheath hub **53** together until the healthcare provider decides to remove the sheath hub **53** from the access device. The healthcare provider manipulates the wings **55** to break the membrane **61** and separate the sheath hub **53** into removable halves.

It may be advantageous to remove a portion or the entire sheath body **54** depending on the type of catheter or medical article that is to be inserted into the vessel after employing the access device **102**. For example, after the catheter or other medical article is inserted into the vessel, a portion of the sheath body **54** can be separated or peeled-away and removed. A peel-away sheath can include perforations, serrations, or other material structure to allow the physician or healthcare provider to easily remove a portion or the entire sheath body **54**.

FIG. **5** depicts a side view of the assembled access device **102** in which the needle **20**, dilator **28**, and sheath **58** are interlocked together. In the assembly, as noted above the needle **20**, dilator **28** and sheath **58** are coaxially disposed about a common longitudinal axis.

FIG. **6** depicts a partial cross-sectional view of the assembled unit. As noted above, the needle body **22**, preferably, comprises one or more side openings **34** in its side wall. Additionally, the dilator may comprise one or more side openings **111**. FIG. **6**, however, illustrates the alignment between only one set of corresponding side openings. Other

sets of side openings can also be aligned or be misaligned depending upon the relative orientations of the needle **20** and the dilator **28**.

Preferably the dilator shaft **30** may be coaxially positioned to minimize the annular space **36** between the needle body **22** and the dilator shaft **30**. The inner surface **38** of the dilator shaft **30** need not, though it can, lie directly against the outer-surface **40** of the needle body **22**. Preferably, the annular interface **36** between the outer-surface **40** of the needle body **22** and the inner surface **38** of the dilator shaft **30** is minimized to inhibit the flow of blood or its constituents (or other bodily fluids) into the annular interface **36** between the dilator shaft **30** and needle body **22**. Advantageously, this feature minimizes the blood's exposure to multiple external surfaces and reduces the risk of contamination, infection, and clotting.

The sheath body **54** is made partially or completely from clear, semi-opaque, translucent, or transparent material so that when blood flows into the needle body **22**, (1) through the needle side opening **34**, (2) through the dilator side opening **111**, and (3) into an annular space **60** between the dilator shaft **30** and the sheath body **54**, the physician or healthcare provider can see the blood. This will indicate to the physician or healthcare provider that the bevel tip **108** of the needle body **22** has punctured a blood vessel.

More preferably, the dilator shaft **30** can be coaxially mounted to the needle body **22** such that at least one side opening **34** disposed on the needle body **22** is rotationally aligned with at least one side opening **111** on the dilator shaft **30**. In some embodiments, the needle body **22** and dilator shaft **30** may (both) have multiple side openings **34**, **111** where some or all of these side openings **34**, **111** can be rotationally aligned. Preferably, the needle body **22** and dilator shaft **30** maintain rotational alignment so that blood flows substantially unobstructed through the needle side opening **34** and dilator side opening **111**.

In some embodiments, the dilator shaft **30** and needle body **22** maintain releasable rotational alignment where the user may transition the dilator shaft **30** and needle body **22** from a first annular position to a second annular position about the longitudinal axis relative to the needle body **22**. The transition from a first to second position may align or misalign the respective side openings on the needle body **22** and dilator shaft **30**. This feature allows the user to change the needle body **22** to a desired orientation before and/or after puncturing the blood vessel. For example, as discussed above, generally, it is preferred that the bevel tip **108** enter the vessel with bevel tip **108** up. However, once the needle body **22** is in the vessel, rotating the bevel tip **108** 180 degrees prevents risk of unwanted injury to the vessel. In preferred embodiments, the physician or healthcare provider can alter the rotational alignment between the dilator shaft **30** and needle body **22** according to his/her needs.

FIG. **7** depicts a cross-sectional view of another preferred embodiment of the present invention. Additionally or alternatively, the annular space **60** between the dilator shaft **30** and sheath body **54** may be minimized to reduce the flow of blood into this space **60**. Preferably, a passageway or conduit **62** is provided that channels blood flow to a view space **43**. A groove formed (e.g., by scoring) on either the outer side of the dilator shaft **30** or the inner side of the sheath body **54** can define at least a portion of the passageway or conduit **62**. In the illustrated embodiment, the passageway or conduit **62** and the view space **43** reduce the open space in the annular space **60** into which the blood or fluid can flow.

FIG. **8** depicts a cross-sectional view of another preferred embodiment of the present invention. In some embodiments, the annular space **60** can be substantially restricted so that

blood or its constituents cannot flow into the annular space between the sheath body **54** and the dilator shaft **30**. The sheath, preferably, comprises a view space **43** that allows some blood to flow into a substantially reduced space between the dilator shaft **30** and sheath body **54**. Preferably, blood cannot flow from the view space **43** or side openings **34**, **111** into the annular space **60**. The portion of the sheath body **54** above the view space **43** can be made from a clear, semi-opaque, translucent, or transparent material so that when blood flows into the needle body **22**, through the needle side opening **34**, through the dilator side opening **111**, and into the view space **43**, the physician or healthcare provider can see the blood. Most preferably, the dilator side opening **111**, needle side opening **34**, and the view space **43** are rotationally aligned so that the blood can flow through the needle side opening **34**, through the dilator side opening **111**, and into the view space **43** without any substantial obstruction. In some embodiments, the sheath may comprise more than one view space **43**.

While the side openings **34**, **111** in the needle **20** and the dilator shaft **30** are aligned in the embodiments illustrated in FIGS. **6**, **7** and **8**, the side openings alternatively can overlap with each other or can be connected via a passageway or conduit **62**. The passageway or conduit **62** can be formed between the side openings **111**, **34** in the dilator and the needle. In some embodiments of the access device, the passageway or conduit **62** is defined by one or more grooves that are formed (e.g., by scoring) on an outer side surface of the needle, on an inner side surface of the dilator, or on both the needle outer side surface and the dilator inner side surface. In this latter form, the grooves can oppose each other or can overlap at one or more points to define a portion of the passageway. In additional embodiments, the passageway or conduit **62** that places the side openings in communication can be formed by incongruous shapes (e.g., incongruous radial cross-sectional shapes) between the needle outer surface and the dilator inner surface. For example, the needle outer surface can have a circular shape and the dilator inner surface can have an oval shape with a minor dimension of the oval substantially equals the diameter to the circle, or vice versa. The needle outer surface and the dilator inner surface also can have other incongruous shapes, such as, but without limitation, a triangle and a circle, a square and a circle, and a square and a triangle, where the needle supports the dilator at least at two points.

In accordance with another aspect of the present invention, there is provided an interlock or interconnection between the guidewire and at least one of the following components of the access device: (1) the needle body; (2) the needle hub; and (3) the dilator hub. The interlock or interconnection inhibits the proximal end of the guidewire from being advanced too far into the needle (and risk the possibility of intravascular guidewire loss), as well as allows the needle, the dilator and the guidewire to be generally withdrawn simultaneously. Additionally, by inhibiting the withdrawal of the advanced guidewire back into the needle, the risk of shearing off the distal end of the guidewire and having a guidewire embolus is reduced. The interlock or interconnection can also ensure that the distal end of the guidewire remains extended beyond the distal end of the needle to protect the needle tip, thereby inhibiting an accidental needle stick.

FIG. **9** illustrates an embodiment of an interconnection suitable to couple the guidewire **120** with the needle hub **21** once a healthcare provider has advanced the guidewire **120** to its fully deployed position (i.e., to a position where the guidewire **120** extends well beyond the distal end **108** of the needle body **22** into the vessel). In the illustrated embodi-

ment, the interconnection comprises a female luer or inner bore **130** defined by the inner bore of the needle hub **21** and a male luer **122** disposed on the guidewire **120**. The male luer **122** preferably resided at the proximal end of the guidewire **120**; however, it can be formed at other locations along the guidewire's length, provided a sufficient length of guidewire **120** extends into the vascular lumen (or other body cavity, lumen or space) when the male luer **122** engages the female luer **130**.

The male luer **122** can be molded (e.g., inserted molded), crimped, adhered or otherwise attached onto or to the end of the guidewire **120** or can be formed in a unitary manner with the guidewire **120**. For example, the male luer body **122** can be molded as a separate piece with a hole passing through the luer body **122**. The hole can be created in the molding process or can be created thereafter. The luer body **122** is then threaded over the guidewire **120**. The proximal end of the guidewire can be crimped, kinked, or enlarged by the addition of other material to inhibit the luer body **122** from slipping off the proximal end of the guidewire **120**. The guidewire **120** can be similarly modified at a point distal of the luer body **122** to inhibit the luer body **122** from sliding distally and ease the use of the device; however, such further modification is unnecessary in order to interconnect together the needle hub **21** and guidewire **120** when the guidewire **120** is fully deployed.

The male and female luer connection illustrated in FIG. **9** is but one example of the types of cooperating structure that can be included to interconnect or interlock the guidewire **120** with the needle hub **21**. Other types of interengaging structure can also be used for this purpose. For example, but without limitation, the guidewire **120** can include one or more enlarged beads at or near its proximal end and the needle hub **21** can include one or more annular grooves defined about its conical inner bore **130**. When advancing the guidewire **120** to its fully extended position, the bead snaps into the corresponding annular groove to interlock the guidewire **120** to the needle hub **21**.

The engagement between the guidewire **120** and the needle hub **21** can occur through simple axial movement of the guidewire **120** relative to the needle hub **21**, as understood from the embodiments described above. It can also occur through relative rotational movement between the guidewire **120** and the needle hub **21**, or through a combination of both axial and rotational movements. For example, the male luer **122**, which is included on the end of the guidewire **120**, can include one or more projecting structures (e.g., an external thread) that engage one or more spiral grooves (e.g., an internal thread) formed within the needle hub **21**. A combined axial and rotational movement of the guidewire **120** relative to the needle hub **21** will interengage these cooperating structures to interlock the guidewire **120** and the needle hub **21**.

FIG. **10** illustrates another interlock formed between the guidewire **120** and the needle hub **21**. In this embodiment, the proximal end of the guidewire **120** is shaped as a clip **140**, which is configured to engage structure on the needle hub **21**. In the illustrated embodiment, the clip **140** has a two-dimensional shape; however, in other embodiments, the clip can take a three-dimensional shape.

As shown in FIG. **10**, the clip **140** is preferably configured to engage an annular flange **142** disposed at the end of the needle hub **21**. For this purpose, the clip **140** includes a transverse section **144** that extends outwardly from a longitudinal axis of the guidewire **120** and lies generally normal to the longitudinal axis; however, the transverse section **144** can extend at an acute or oblique angle relative to the longitudinal

13

axis of the guidewire 120. The length of the transverse section preferably is slightly larger than half of the diameter across the hub flange 142.

The clip 140 also includes a spring clip 146 that extends distally from the transverse section 144. The spring clip 146 includes a generally V-shaped end that is configured to deflect outwardly and ride over the hub flange 142 when the guidewire 120 is advanced distally and then to spring back toward the guidewire 120 and into a groove or space provided on a distal side of the hub flange 142. While not illustrated, the spring clip 146 can include an abutment surface on an inner side of the spring clip 146, which extends generally normal to the longitudinal axis and is disposed to abut against a distal side of the hub flange 142 to resist proximal movement of the guidewire 120 relative to the needle hub 21.

FIG. 11 illustrates an example of an interlock formed between the guidewire 120 and the needle body 22. The interlock is formed in part by a hole 150 through the needle body 22. In the illustrated embodiment, hub material on either side of the through hole 150 is also omitted; however, such a relief may not be included in other embodiments. Additionally, the hole 150 need not extend through the needle body 22.

The guidewire 120 includes a protuberance 152 (e.g., a bead) formed along its length which is deformable and is slightly larger than the inner diameter of the needle body 22. The protuberance 152 may be integral with the guidewire 120 or be attached to the guidewire 120. The protuberance 152 can also take the form of a deflectable barb that projects proximally from the guidewire 120 to inhibit proximal movement once it engages with the through hole 150. Additional protuberances are depicted in FIGS. 12 and 13. In FIG. 12, the protuberance 152*b* is formed by flattening a section of the guidewire 120. In FIG. 13, the protuberance 152*c* is formed by a pair of nubs 154 formed on opposite sides of the guidewire 120. The guidewire is split to a point distal of the nubs and plastically deformed so as to spread the nubs 154 apart. The split ends 156 of the guidewire 120 act as leaf springs that bias the nubs 154 outwardly, away from a longitudinal axis of the guidewire 120.

With reference back to FIG. 11, the protuberance 152 is sized and located on the guidewire 120 to interact with the through hole 150 once the guidewire 120 has been advanced into the vessel by a desired length. At this point, the protuberance 152 snaps or springs into one or both sides of the through hole 150 to hold the guidewire 120 relative to the needle body 22. The guidewire 120 can also include a plurality of protuberances so as to provide multiple extension lengths for the guidewire 120 from the needle body 22 and/or to interact with a plurality of through holes to provide enhanced or redundant interengagement between the guidewire 120 and the needle body 22.

FIG. 14 illustrates a further embodiment of an interlock between the guidewire 120 and the needle hub 21 with the addition of a release mechanism that unlocks the dilator shaft 30 (and the sheath body 54 in the illustrated embodiment) from the needle hub 21. The proximal end of the guidewire 120 is attached to an end cap 160 that interacts with the needle hub 21 in any of the variety of ways described above. The end cap 160 additionally includes a pair of cam arms 162. The cam arms 162, when the end cap 160 is engaged with the needle hub 21, cause the clip sides 29 to depress inward and release the hinged clips 27 from the flange 33 of the dilator hub 32. In this position, the guidewire 120 is interlocked or interconnected with the needle hub 21, while the dilator shaft 30 is free to be advanced over the needle body 22.

FIG. 15 illustrates a further embodiment of an access device that includes an interconnection between the

14

guidewire 120 and the needle hub 21, which also helps support a length of guidewire 120 before insertion into the needle body 22. In this embodiment, a support rod 170 extends proximally from the needle hub 21. In some embodiments, the length of the rod 170 can generally equal the length of the guidewire 120 and in other embodiments it can be significantly shorter (e.g., 25%-50% of the guidewire's length). The guidewire 120 includes a loop 172 formed at or near its proximal end which slides over the rod 170 as the guidewire 120 is advanced into the needle body 22. The interaction between the loop 172 and the rod support 170 supports the proximal end of the guidewire 120. This same interaction inhibits withdrawal of the guidewire 120 from the needle 20 once the guidewire 120 is fully advanced. In another embodiment, the loop can be part of the rod and the guidewire is placed within that loop, reducing the likelihood that the wire will fall out of the device before or during the procedure.

FIG. 16 illustrates another embodiment of a guidewire 120 that can be used with one or more of the above-described embodiments of the access device. The guidewire 120 has one or more movable positioners or stops 180 that can be slid along the guidewire shaft 120 as desired to limit the forward advancement or backward movement of the guidewire 120 within the assembly of the needle 20, the dilator 28, and the sheath 58. In the illustrated embodiment, the stops 180 are silicone balls. The stop(s) of course can have other shapes as well such as, for example, but without limitation, a hollow cylindrical shape or a hollow truncated conical shape (e.g., substantially matching the shape of the needle hub inner bore), and can be made of other types of materials as well.

Each ball 180 in the illustrated embodiment has a bore 182 passing through the ball 180. The bore 182 has a diameter approximately equal to the diameter of the guidewire 120. The compressible nature of the silicone balls 180 allows them to be slid under force to a desired location along the guidewire's length. Once a sufficient sliding force is no longer applied, the interference and resulting friction between the balls 180 and the guidewire 120 inhibits the balls 180 from sliding over the guidewire 120. Additionally, one or more of the stops 180 can be split along its length (e.g., by a groove, slit, or elongated opening) that permits the stop to be attached and detached from the guidewire 120 without passing over an end of the guidewire 120. This configuration thus allows the stop(s) 180 to be removed from guidewires with outwardly-extending proximal structure (e.g., the guidewires 120 shown in FIGS. 9, 10, 14 and 15) without passing over either the proximal or distal ends of the guidewire.

The outer diameter of the balls 180 is sized to be larger than the proximal opening into the needle body 22. In the illustrated embodiment, the outer size of the ball 180 is larger than an inner bore 130 of the needle hub 21; however, in other embodiments, the ball 180 can be sized to fit within the inner bore 130 but not to fit into the needle body 22. The resulting interference between the stop 180 and the needle hub 21 and/or the needle body 22 limits the forward advancement of the guidewire 120 into the needle 20, as well as inhibits retraction (backwards movement) of the guidewire 120 from the needle body 22. The balls 180 also support the guidewire 120 when the access device 102 is placed in its packaging, and inhibit the guidewire 120 from moving relative to the needle/dilator/sheath assembly during sterilization, transport and storage, prior to use.

The embodiments herein described are comprised of conventional, biocompatible materials. For example, the needle preferably consists of a rigid polymer or a metal such as stainless steel, nitinol, or the like. The other elements can be formed of suitable polymeric materials, such as polycarbon-

15

ate, nylon, polyethylene, high-density polyethylene, polypropylene, fluoropolymers and copolymers such as perfluoro (ethylene-propylene) copolymer, polyurethane polymers or co-polymers.

As noted above, the present access device can be used to place a catheter at other locations within a patient's body. Thus, for example, but without limitation, the access device can be used as or with a variety of catheters to drain fluids from abscesses, to drain air from a pneumothorax, and to access the peritoneal cavity. In such applications, body fluids flow into the viewing space to indicate when the needle has been properly placed.

Although this invention has been disclosed in the context of certain preferred embodiments and examples, it will be understood by those skilled in the art that the present invention extends beyond the specifically disclosed embodiments to other alternative embodiments and/or uses of the invention and obvious modifications and equivalents thereof. In addition, while a number of variations of the invention have been shown and described in detail, other modifications, which are within the scope of this invention, will be readily apparent to those of skill in the art based upon this disclosure. It is also contemplated that various combinations or sub-combinations of the specific features and aspects of the embodiments may be made and still fall within the scope of the invention. Accordingly, it should be understood that various features and aspects of the disclosed embodiments can be combined with or substituted for one another in order to form varying modes of the disclosed invention. Thus, it is intended that the scope of the present invention herein disclosed should not be limited by the particular disclosed embodiments described above, but should be determined only by a fair reading of the disclosure and the claims that follow.

What is claimed is:

1. An access device for placing a medical article within a body space, comprising:

- a needle having a needle body and an interior bore;
- a dilator coaxially disposed about the needle body and having a dilator shaft;
- a medical article coaxially disposed about the dilator;
- a plurality of openings extending through a side of at least one of the needle body and the dilator shaft;
- at least one opening in the other one of the needle body and dilator shaft, the plurality of openings being spaced about the one of the needle body or dilator shaft so that at least one of the plurality of openings at least partially overlaps the at least one opening in the other one of the needle body and dilator shaft when the needle body is rotationally clocked relative to the dilator shaft in a first position and in a second position, the second position being different than the first position;
- a viewing space disposed between the dilator and the medical article;
- at least one passageway connecting the viewing space with the interior bore of the needle body, the passageway being defined at least in part by the plurality of openings and the at least one opening;
- a lock member configured to move between a lock state and an unlock state, the lock member connecting the needle to the dilator so as to inhibit at least relative axial movement between at least a portion of the needle and at least a portion of the dilator when the lock member is in at least the lock state; and
- a guidewire configured to be coaxially disposed within at least a portion of the needle body, the guidewire comprising a release member separable from the lock member and configured to engage with the lock member so as

16

to at least move the lock member from the lock state to the unlock state when the guidewire is coaxially advanced within the needle body.

2. The access device of claim **1**, wherein the medical article is a catheter.

3. The access device of claim **1**, wherein the medical article is a sheath.

4. The access device of claim **3**, wherein the sheath comprises a body and a hub.

5. The access device of claim **3**, wherein at least a portion of the sheath is clear.

6. The access device of claim **3**, wherein at least a portion of the sheath is translucent.

7. The access device of claim **3**, wherein at least a portion of the sheath is semi-opaque.

8. The access device of claim **3**, wherein at least a portion of the sheath is transparent so as to provide a visual indication when blood or other body fluids flow into the needle body, through the plurality of openings and the at least one opening, and into the viewing space.

9. The access device of claim **1**, wherein at least one of the plurality of openings at least partially overlaps the at least one opening in the other one of the needle body and dilator shaft regardless of a rotational orientation of the dilator shaft relative to the needle body.

10. The access device of claim **1**, wherein the plurality of openings is irregularly spaced about the one of the needle body or dilator shaft.

11. The access device of claim **1**, wherein the at least one opening and the plurality of openings define a plurality of passageways, each passageway connecting the viewing space with an interior bore of the needle body.

12. The access device of claim **1**, wherein the at least one passageway has an incongruous shape between the needle outer surface and the dilator inner surface, the incongruous shape being a radial cross-sectional shape.

13. The access device of claim **12**, wherein an inner side surface of the dilator shaft has an oval shape and an outer side surface of the needle body has a circular shape.

14. The access device of claim **1**, wherein the viewing space is disposed at a distal portion of the medical article.

15. The access device of claim **1**, wherein at least a portion of the viewing space has a linear shape along at least a portion of an axial length of the medical article.

16. The access device of claim **1**, wherein at least a portion of the viewing space has a curved shape along at least a portion of an axial length of the medical article.

17. The access device of claim **1**, wherein at least a portion of the viewing space has a spiral shape along at least a portion of an axial length of the medical article.

18. The access device of claim **1**, wherein the viewing space has an annular shape.

19. The access device of claim **18**, wherein an axial length of the viewing space is substantially coextensive with a length of the medical article.

20. The access device of claim **18**, wherein an axial length of the viewing space is substantially less than a length of the medical article.

21. An access device for placing a medical article within a body space, comprising:

- a needle having a needle body;
- a dilator coaxially disposed about the needle body and having a dilator shaft;
- a lock member configured to move between a lock state and an unlock state, the lock member connecting the needle to the dilator so as to inhibit at least relative axial move-

17

ment between at least a portion of the needle and at least a portion of the dilator when the lock member is in at least the lock state;

a guidewire configured to be coaxially disposed within at least a portion of the needle body, the guidewire comprising a release member separable from the lock member and configured to engage with the lock member so as to at least move the lock member from the lock state to the unlock state when the guidewire is coaxially advanced within the needle body; and
an interlock between the guidewire and at least one of the needle and the dilator.

22. The access device of claim 21, wherein the interlock is configured to retain the guidewire to the access device.

23. The access device of claim 21 further comprising a medical article coaxially disposed about the dilator.

24. The access device of claim 21, wherein the interlock comprises an attachment connecting the guidewire to at least one area of at least one of the needle and the dilator.

25. The access device of claim 24, wherein the one area is a surface on the needle body.

26. The access device of claim 24, wherein the needle includes a needle hub, the one area being a surface on the needle hub.

27. The access device of claim 24, wherein the dilator includes a dilator hub, the one area being a surface on the dilator hub.

28. The access device of claim 24, wherein the attachment connects the guidewire to at least two areas, the two areas being on one of the needle, the dilator, and the needle and the dilator.

29. The access device of claim 24, wherein the attachment is disposed relative to the guidewire so that the guidewire does not have a full range of motion in at least one direction when moving axially relative to the needle body.

30. The access device of claim 24, wherein the attachment is disposed relative to the guidewire so that the guidewire is limited in moving in a proximal direction so as to prevent the guidewire from completely retracting into the needle body.

31. The access device of claim 24, wherein the attachment is disposed relative to the guidewire so that the guidewire is limited in moving in a distal direction so as to prevent the guidewire from completely exiting the needle body.

32. The access device of claim 24, wherein the attachment is disposed relative to the guidewire so that the guidewire is limited in moving in a distal direction so as to maintain a minimum length of the guidewire beyond a tip of the needle.

33. An access device for placing a medical article within a body space, comprising:

a needle having a needle body;

a dilator coaxially disposed about the needle body;

a lock member configured to move between a lock state and an unlock state, the lock member connecting the needle to the dilator so as to inhibit at least relative axial movement between at least a portion of the needle and at least a portion of the dilator when the lock member is in at least the lock state; and

a guidewire configured to be coaxially disposed within at least a portion of the needle body, the guidewire comprising a release member separable from the lock member and configured to engage with the lock member so as to at least move the lock member from the lock state to the unlock state when the guidewire is coaxially advanced within the needle body.

34. The access device of claim 33, wherein the release member is configured so that as the release member is moved from a separated position to engage with the lock member to

18

move the lock member to the unlock state, the guidewire simultaneously moves with the release member.

35. The access device of claim 33, wherein the release member is configured so that when the release member engages with the lock member and moves the lock member to the unlock state, at least relative axial movement between at least a portion of the guidewire and at least a portion of at least one of the needle and the dilator is inhibited.

36. The access device of claim 33, wherein the lock member is attached to the needle and releasably attaches to the dilator.

37. The access device of claim 33, wherein the lock member is attached to the dilator and releasably attaches to the needle.

38. The access device of claim 33, wherein each of the needle and the dilator comprises a hub, the lock member connecting the hubs.

39. The access device of claim 33, wherein the guidewire comprises an end cap, the end cap comprising the release member.

40. An access device for placing a medical article within a body space, comprising:

a needle having a needle body;

a dilator coaxially disposed about the needle body and having a dilator shaft;

a lock member configured to move between a lock state and an unlock state, the lock member connecting the needle to the dilator so as to inhibit at least relative axial movement between at least a portion of the needle and at least a portion of the dilator when the lock member is in at least the lock state;

a guidewire configured to be coaxially disposed within at least a portion of the needle body, the guidewire comprising a release member separable from the lock member and configured to engage with the lock member so as to at least move the lock member from the lock state to the unlock state when the guidewire is coaxially advanced within the needle body; and

one or more stops disposed between the guidewire and at least one of the needle and the dilator.

41. The access device of claim 40, wherein the one or more stops have a maximum circumference that is greater than a minimum circumference of the guidewire.

42. The access device of claim 40, wherein the one or more stops comprise silicon.

43. The access device of claim 40, wherein the one or more stops have a generally round shape.

44. The access device of claim 40, wherein the one or more stops contacts an inner surface on the needle body at least when the guidewire is slid in a distal direction.

45. The access device of claim 40, wherein the one or more stops is disposed so as to connect the guidewire to at least an area of one of the needle and the dilator.

46. The access device of claim 40, wherein the one or more stops is disposed on the guidewire so that the guidewire does not have a full range of motion in at least one direction when moving axially relative to the needle body.

47. The access device of claim 40, wherein the one or more stops is disposed on the guidewire so that the guidewire is limited in moving in a proximal direction to prevent the guidewire from completely retracting into the needle body.

48. The access device of claim 40, wherein the one or more stops is disposed on the guidewire so that the guidewire is limited in moving in a distal direction to prevent the guidewire from completely exiting the needle body.

49. The access device of claim 40, wherein the one or more stops is disposed on the guidewire so that the guidewire is

19

limited in moving in a distal direction to maintain a minimum length of the guidewire beyond a tip of the needle.

50. The access device of claim 40 further comprising a medical article coaxially disposed about the dilator.

51. The access device of claim 40, wherein the one or more stops are attached to the guidewire. 5

52. The access device of claim 51, wherein the one or more stops are movable along a length of the guidewire.

53. The access device of claim 51, wherein the one or more stops are inhibited from moving along the length of the guidewire. 10

54. The access device of claim 51, wherein an interference fit exists between the one or more stops and the guidewire.

55. The access device of claim 51, wherein a friction fit exists between the one or more stops and the guidewire. 15

56. The access device of claim 51, wherein the one or more stops are mechanically coupled to the guidewire.

57. The access device of claim 51, wherein the one or more stops are adhered to the guidewire. 20

58. An access device for placing a medical article within a body space, comprising:

20

a needle having a needle body;

a dilator coaxially disposed about the needle body;

a lock member configured to move between a lock state and an unlock state, the lock member connecting the needle to the dilator so as to inhibit at least relative axial movement between at least a portion of the needle and at least a portion of the dilator when the lock member is in at least the lock state; and

a guidewire configured to be coaxially disposed within at least a portion of the needle body, the guidewire comprising a release member separable from the lock member and configured to engage with the lock member so as to at least move the lock member from the lock state to the unlock state when the guidewire is coaxially advanced within the needle body

wherein the lock member comprises hinged clips that releasably attach to at least one of the needle and dilator, and the release member is configured to engage the hinged clips to rotate the clips and cause them to release the at least one of the needle and the dilator.

* * * * *