

US008238963B1

(12) **United States Patent**
Fujisaki

(10) **Patent No.:** **US 8,238,963 B1**
(45) **Date of Patent:** ***Aug. 7, 2012**

(54) **COMMUNICATION DEVICE**

(76) Inventor: **Iwao Fujisaki**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/026,210**

(22) Filed: **Feb. 12, 2011**

Related U.S. Application Data

(63) Continuation of application No. 12/344,306, filed on Dec. 26, 2008, now Pat. No. 7,917,167, which is a continuation of application No. 10/905,836, filed on Jan. 22, 2005, now abandoned, which is a continuation of application No. 10/711,265, filed on Sep. 7, 2004, now abandoned.

(60) Provisional application No. 60/481,695, filed on Nov. 22, 2003.

(51) **Int. Cl.**
H04M 1/00 (2006.01)

(52) **U.S. Cl.** **455/550.1**; 455/556.1; 455/557; 455/419; 455/412; 455/420

(58) **Field of Classification Search** 455/418-420, 455/566, 550.1, 575.1, 90.3

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,934,773 A 6/1990 Becker
4,937,570 A 6/1990 Matsukawa et al.
5,113,427 A 5/1992 Ryoichi et al.
5,272,638 A 12/1993 Martin et al.

5,345,272 A 9/1994 Ersoz et al.
5,353,376 A 10/1994 Oh et al.
5,388,147 A 2/1995 Grimes
5,404,579 A 4/1995 Obayashi et al.
5,405,152 A 4/1995 Katanics et al.
5,414,461 A 5/1995 Kishi et al.
5,438,357 A 8/1995 McNelley
5,446,904 A 8/1995 Belt et al.
5,479,476 A 12/1995 Finke-Anlauff
5,530,472 A 6/1996 Bregman et al.
5,532,741 A 7/1996 Tsutsumi
5,542,557 A 8/1996 Koyama et al.
5,543,789 A 8/1996 Behr et al.
5,550,754 A 8/1996 McNelley et al.
5,559,554 A 9/1996 Uekane et al.
5,625,675 A 4/1997 Katsumaru et al.
5,629,741 A 5/1997 Hopper
5,648,768 A 7/1997 Bouve
5,675,630 A 10/1997 Beatty
5,687,331 A 11/1997 Volk et al.
5,732,383 A 3/1998 Foladare et al.

(Continued)

FOREIGN PATENT DOCUMENTS

JP H11/195137 A1 7/1999
JP 2005/216149 A1 8/2005
WO WO03001457 1/2003

OTHER PUBLICATIONS

HI Corporation's company history (<http://www.hicorp.co.jp/english/corporate/history.html>).


(Continued)

Primary Examiner — Sharad Rampuria

(57) **ABSTRACT**

The mobile phone, wherein a list of controllers, such as battery controller, CCD unit controller, microphone controller, speaker controller, and vibrator controller, are displayed, and the controller selected from the list is updated by utilizing the mobile phone updating data received via antenna.

18 Claims, 1 Drawing Sheet



U.S. PATENT DOCUMENTS							
5,758,280	A	5/1998	Kimura	6,567,984	B1	5/2003	Allport
5,772,586	A	6/1998	Heinonen et al.	6,600,975	B2	7/2003	Moriguchi et al.
5,778,304	A	7/1998	Grube et al.	6,606,504	B1	8/2003	Mooney et al.
5,786,846	A	7/1998	Hiroaki	6,611,753	B1	8/2003	Millington
5,802,460	A	9/1998	Parvulescu et al.	6,615,186	B1	9/2003	Kolls
5,805,672	A	9/1998	Barkat et al.	6,618,704	B2	9/2003	Kanevsky et al.
5,812,930	A	9/1998	Zavrel	6,622,018	B1	9/2003	Erekson
5,825,408	A	10/1998	Yuyama et al.	6,630,958	B2	10/2003	Tanaka et al.
5,844,824	A	12/1998	Newman et al.	6,631,271	B1	10/2003	Logan
5,902,349	A	5/1999	Endo et al.	6,647,251	B1	11/2003	Siegle et al.
5,916,024	A	6/1999	Von Kohorn	6,650,877	B1	11/2003	Tarbouriech et al.
5,918,180	A	6/1999	Dimino	6,650,894	B1	11/2003	Berstis et al.
5,959,661	A	9/1999	Isono	6,658,272	B1	12/2003	Lenchik et al.
6,009,336	A	12/1999	Harris et al.	6,658,461	B1	12/2003	Mazo
6,011,973	A	1/2000	Valentine et al.	6,662,023	B1	12/2003	Helle
6,034,715	A	3/2000	Ishida et al.	6,681,120	B1	1/2004	Kim
6,043,752	A	3/2000	Hisada et al.	6,690,932	B1	2/2004	Barnier et al.
6,073,034	A	6/2000	Jacobsen et al.	6,701,148	B1	3/2004	Wilson et al.
6,081,265	A	6/2000	Nakayama et al.	6,707,942	B1	3/2004	Cortopassi et al.
6,115,597	A	9/2000	Kroll et al.	6,711,399	B1	3/2004	Granier
6,128,594	A	10/2000	Gulli et al.	6,725,022	B1	4/2004	Clayton et al.
6,144,848	A	11/2000	Walsh et al.	6,728,531	B1	4/2004	Lee et al.
6,148,212	A	11/2000	Park et al.	6,738,643	B1	5/2004	Harris
6,161,134	A	12/2000	Wang et al.	6,738,711	B2	5/2004	Ohmura et al.
6,167,283	A	12/2000	Korpela et al.	6,763,226	B1	7/2004	McZeal, Jr.
6,192,343	B1	2/2001	Morgan et al.	6,772,174	B1	8/2004	Pettersson
6,198,942	B1	3/2001	Hayashi et al.	6,775,361	B1	8/2004	Arai et al.
6,202,060	B1	3/2001	Tran	6,779,030	B1	8/2004	Dugan et al.
6,216,013	B1	4/2001	Moore et al.	6,788,928	B2	9/2004	Kohinata et al.
6,216,158	B1	4/2001	Luo et al.	6,795,715	B1	9/2004	Kubo et al.
6,222,482	B1	4/2001	Gueziec	6,812,954	B1	11/2004	Priestman et al.
6,223,029	B1	4/2001	Stenman et al.	6,819,939	B2	11/2004	Masamura
6,225,944	B1	5/2001	Hayes	6,820,055	B2	11/2004	Saindon et al.
6,236,832	B1	5/2001	Ito	6,836,654	B2	12/2004	Decotignie
6,243,039	B1	6/2001	Elliot	6,850,209	B2	2/2005	Mankins et al.
6,249,720	B1	6/2001	Kubota et al.	6,865,372	B2	3/2005	Mauney et al.
6,253,075	B1	6/2001	Beghtol et al.	6,870,828	B1	3/2005	Giordano, III
6,265,988	B1	7/2001	LeMense et al.	6,883,000	B1	4/2005	Gropper
6,285,317	B1	9/2001	Ong	6,891,525	B2	5/2005	Ogoro
6,285,757	B1	9/2001	Carroll et al.	6,895,084	B1	5/2005	Saylor et al.
6,292,666	B1	9/2001	Siddiqui et al.	6,895,256	B2	5/2005	Harma
6,292,747	B1	9/2001	Amro et al.	6,895,259	B1	5/2005	Blank nee Keller et al.
6,311,011	B1	10/2001	Kuroda	6,898,321	B1	5/2005	Knee et al.
6,311,077	B1	10/2001	Bien	6,898,765	B2	5/2005	Matthews, III et al.
6,332,122	B1	12/2001	Ortega et al.	6,901,383	B1	5/2005	Ricketts et al.
6,333,684	B1	12/2001	Kang	6,904,298	B2	6/2005	Arai et al.
6,363,320	B1	3/2002	Chou	6,912,544	B1	6/2005	Weiner
6,366,651	B1	4/2002	Griffith et al.	6,922,630	B2	7/2005	Maruyama et al.
6,366,782	B1	4/2002	Fumarolo et al.	6,937,868	B2	8/2005	Himmel et al.
6,374,221	B1	4/2002	Haimi-Cohen	6,947,728	B2	9/2005	Tagawa et al.
6,385,466	B1	5/2002	Hirai et al.	6,954,645	B2	10/2005	Tsai et al.
6,385,541	B1	5/2002	Blumberg et al.	6,958,675	B2	10/2005	Maeda et al.
6,385,654	B1	5/2002	Tanaka	6,961,559	B1	11/2005	Chow et al.
6,405,033	B1	6/2002	Kennedy, III et al.	6,968,184	B2	11/2005	Criss et al.
6,411,198	B1	6/2002	Hirai et al.	6,968,206	B1	11/2005	Whitsey-Anderson
6,411,822	B1	6/2002	Kraft	6,970,178	B2	11/2005	Tanioka et al.
6,415,138	B2	7/2002	Sirola et al.	6,970,703	B2	11/2005	Fuchs et al.
6,421,470	B1	7/2002	Nozaki et al.	6,992,699	B1	1/2006	Vance et al.
6,421,602	B1	7/2002	Bullock et al.	6,999,757	B2	2/2006	Bates et al.
6,430,498	B1	8/2002	Maruyama et al.	6,999,802	B2	2/2006	Kim
6,438,380	B1	8/2002	Bi et al.	7,003,598	B2	2/2006	Kavanagh
6,442,404	B1	8/2002	Sakajiri	7,007,239	B1	2/2006	Hawkins et al.
6,445,802	B1	9/2002	Dan	7,012,999	B2	3/2006	Ruckart
6,477,387	B1	11/2002	Jackson et al.	7,019,770	B1	3/2006	Katz
6,486,867	B1	11/2002	Kopp et al.	7,028,077	B2	4/2006	Toshimitsu et al.
6,487,422	B1	11/2002	Lee	7,030,880	B2	4/2006	Tanioka et al.
6,512,919	B2	1/2003	Ogasawara	7,035,666	B2	4/2006	Silberfenig
6,518,956	B1	2/2003	Sato	7,058,356	B2	6/2006	Slotznick
6,519,566	B1	2/2003	Boyer	7,076,052	B2	7/2006	Yoshimura
6,526,293	B1	2/2003	Matsuo	7,081,832	B2	7/2006	Nelson et al.
6,529,742	B1	3/2003	Yang	7,085,578	B2	8/2006	Barclay et al.
6,532,035	B1	3/2003	Saari et al.	7,085,739	B1	8/2006	Winter et al.
6,538,558	B2	3/2003	Sakazume et al.	7,089,298	B2	8/2006	Nyman et al.
6,542,750	B2	4/2003	Hendrey et al.	7,106,846	B2	9/2006	Nguyen et al.
6,542,814	B2	4/2003	Polidi et al.	7,107,081	B1	9/2006	Fujisaki
6,553,309	B2 *	4/2003	Uchida et al. 701/409	7,117,152	B1	10/2006	Mukherji et al.
6,553,310	B1	4/2003	Lopke	7,117,504	B2	10/2006	Smith et al.
6,567,745	B2	5/2003	Fuchs et al.	7,126,951	B2	10/2006	Belcea et al.
				7,127,238	B2	10/2006	Vandermeijden et al.

US 8,238,963 B1


7,127,271	B1	10/2006	Fujisaki	2002/0085700	A1	7/2002	Metcalf
7,130,630	B1	10/2006	Enzmann et al.	2002/0094806	A1	7/2002	Kamimura
7,142,810	B2	11/2006	Oesterling	2002/0097984	A1	7/2002	Abecassis
7,142,890	B2	11/2006	Irimajiri et al.	2002/0098857	A1	7/2002	Ishii
7,190,880	B2	3/2007	Cookson et al.	2002/0102960	A1	8/2002	Lechner
7,218,916	B2	5/2007	Nonami	2002/0103872	A1	8/2002	Watanabe
7,224,851	B2	5/2007	Kinjo	2002/0110246	A1	8/2002	Gosior et al.
7,224,987	B1	5/2007	Bhela et al.	2002/0115469	A1	8/2002	Rekimoto et al.
7,233,781	B2	6/2007	Hunter et al.	2002/0120589	A1	8/2002	Aoki
7,233,795	B1	6/2007	Ryden	2002/0120718	A1	8/2002	Lee
7,239,742	B2	7/2007	Ohtani et al.	2002/0123336	A1	9/2002	Kamada
7,251,255	B1	7/2007	Young	2002/0127997	A1	9/2002	Karlstedt et al.
7,254,408	B2	8/2007	Kim	2002/0133342	A1	9/2002	McKenna
7,260,416	B2	8/2007	Shippee	2002/0137470	A1	9/2002	Baron et al.
7,266,186	B1	9/2007	Henderson	2002/0137503	A1	9/2002	Roderique
7,274,952	B2	9/2007	Hayashi	2002/0137526	A1	9/2002	Shinohara
7,277,711	B2	10/2007	Nyu	2002/0142763	A1	10/2002	Kolsky
7,321,783	B2	1/2008	Kim et al.	2002/0147645	A1	10/2002	Alao et al.
7,346,373	B2	3/2008	Kim	2002/0151326	A1	10/2002	Awada et al.
7,372,447	B1	5/2008	Jacobsen et al.	2002/0151327	A1	10/2002	Levitt
7,383,067	B2	6/2008	Phillips et al.	2002/0154632	A1	10/2002	Wang et al.
7,426,264	B1	9/2008	Henderson	2002/0157101	A1	10/2002	Schrader et al.
7,433,845	B1	10/2008	Flitcroft et al.	2002/0164996	A1	11/2002	Dorenbosch
7,444,168	B2 *	10/2008	Nakagawa et al. 455/557	2002/0165850	A1	11/2002	Roberts et al.
7,450,709	B2	11/2008	Gonzalez et al.	2002/0168959	A1	11/2002	Noguchi et al.
7,489,768	B1	2/2009	Strietzel	2002/0173344	A1	11/2002	Cupps et al.
7,532,879	B1	5/2009	Fujisaki	2002/0177407	A1	11/2002	Mitsumoto
7,551,899	B1	6/2009	Nicolas et al.	2002/0178009	A1	11/2002	Firman
7,657,252	B2	2/2010	Futami	2002/0178225	A1	11/2002	Madenberg et al.
7,707,592	B2	4/2010	Wesslen et al.	2002/0183045	A1	12/2002	Emmerson et al.
7,707,602	B2	4/2010	Cragun et al.	2002/0191951	A1	12/2002	Sodeyama et al.
7,769,364	B2	8/2010	Logan et al.	2002/0196378	A1	12/2002	Slobodin et al.
7,787,857	B2	8/2010	Peterman	2002/0198813	A1	12/2002	Patterson et al.
7,787,887	B2	8/2010	Gupta et al.	2002/0198936	A1	12/2002	McIntyre et al.
7,853,295	B1	12/2010	Fujisaki	2003/0003967	A1	1/2003	Ito
7,853,297	B1	12/2010	Fujisaki	2003/0006879	A1	1/2003	Kang et al.
7,873,349	B1	1/2011	Smith et al.	2003/0007556	A1	1/2003	Oura et al.
7,899,410	B2	3/2011	Rakshani et al.	2003/0013483	A1	1/2003	Ausems et al.
7,917,167	B1 *	3/2011	Fujisaki 455/550.1	2003/0014286	A1	1/2003	Cappellini
7,941,141	B2	5/2011	Shoykhet et al.	2003/0016189	A1	1/2003	Abe et al.
7,953,439	B2	5/2011	Rofougaran	2003/0017857	A1	1/2003	Kitson et al.
2001/0000249	A1	4/2001	Oba et al.	2003/0018744	A1	1/2003	Johanson et al.
2001/0005826	A1	6/2001	Shibuya	2003/0018748	A1	1/2003	McKenna
2001/0011293	A1	8/2001	Murakami et al.	2003/0032389	A1	2/2003	Kinnear et al.
2001/0029425	A1	10/2001	Myr	2003/0032406	A1	2/2003	Miner et al.
2001/0035829	A1	11/2001	Yu et al.	2003/0033214	A1	2/2003	Mikkelsen et al.
2001/0037191	A1	11/2001	Furuta et al.	2003/0038800	A1	2/2003	Kawahara
2001/0041590	A1	11/2001	Silberfenig et al.	2003/0045301	A1	3/2003	Wollrab
2001/0049470	A1	12/2001	Mault et al.	2003/0045311	A1	3/2003	Larikka et al.
2002/0002044	A1	1/2002	Naruse et al.	2003/0045329	A1	3/2003	Kinoshita
2002/0002705	A1	1/2002	Byrnes et al.	2003/0045996	A1	3/2003	Yamazaki et al.
2002/0004701	A1	1/2002	Nakano	2003/0050776	A1	3/2003	Blair
2002/0006804	A1	1/2002	Mukai et al.	2003/0052964	A1	3/2003	Priestman et al.
2002/0009978	A1	1/2002	Dukach et al.	2003/0054830	A1	3/2003	Williams et al.
2002/0016724	A1	2/2002	Yang et al.	2003/0055994	A1	3/2003	Herrmann et al.
2002/0019225	A1	2/2002	Miyashita	2003/0061606	A1	3/2003	Hartwig et al.
2002/0026348	A1	2/2002	Fowler et al.	2003/0063732	A1	4/2003	Mcknight
2002/0028690	A1	3/2002	McKenna et al.	2003/0065784	A1	4/2003	Herrod
2002/0031120	A1	3/2002	Rakib	2003/0065805	A1	4/2003	Barnes, Jr.
2002/0034292	A1	3/2002	Tuoriniemi et al.	2003/0069693	A1	4/2003	Snapp et al.
2002/0036231	A1	3/2002	Monaghan et al.	2003/0073432	A1	4/2003	Meade, II
2002/0036642	A1	3/2002	Kwon et al.	2003/0083055	A1	5/2003	Riordan et al.
2002/0038219	A1	3/2002	Yanay et al.	2003/0083873	A1	5/2003	Ross et al.
2002/0039914	A1	4/2002	Hama et al.	2003/0084121	A1	5/2003	De Boor et al.
2002/0041262	A1	4/2002	Mukai et al.	2003/0093503	A1	5/2003	Yamaki et al.
2002/0047787	A1	4/2002	Mikkola et al.	2003/0093790	A1	5/2003	Logan et al.
2002/0049742	A1	4/2002	Chan et al.	2003/0099367	A1	5/2003	Okamura
2002/0054068	A1	5/2002	Ellis et al.	2003/0100326	A1	5/2003	Grube et al.
2002/0055350	A1	5/2002	Gupte et al.	2003/0107580	A1	6/2003	Egawa et al.
2002/0058497	A1	5/2002	Jeong	2003/0109251	A1	6/2003	Fujito et al.
2002/0058531	A1	5/2002	Terasaki et al.	2003/0114191	A1	6/2003	Nishimura
2002/0065037	A1	5/2002	Messina et al.	2003/0115240	A1	6/2003	Cho
2002/0065604	A1	5/2002	Sekiyama	2003/0117316	A1	6/2003	Tischer
2002/0066115	A1	5/2002	Wendelrup	2003/0119479	A1	6/2003	Arima et al.
2002/0068558	A1	6/2002	Janik	2003/0119485	A1	6/2003	Ogasawara
2002/0068585	A1	6/2002	Chan et al.	2003/0119562	A1	6/2003	Kokubo
2002/0068599	A1	6/2002	Rodriguez et al.	2003/0120784	A1	6/2003	Johnson et al.
2002/0072395	A1	6/2002	Miramontes	2003/0122779	A1	7/2003	Martin et al.
2002/0082059	A1	6/2002	Nariai et al.	2003/0125008	A1	7/2003	Shimamura

2003/0132928	A1	7/2003	Kori	2005/0113080	A1	5/2005	Nishimura
2003/0135563	A1	7/2003	Bodin et al.	2005/0120225	A1	6/2005	Kirsch et al.
2003/0137970	A1	7/2003	Odman	2005/0136949	A1	6/2005	Barnes et al.
2003/0142957	A1	7/2003	Young et al.	2005/0153681	A1	7/2005	Hanson
2003/0144024	A1	7/2003	Luo	2005/0153745	A1	7/2005	Smethers
2003/0148772	A1	8/2003	Ben-Ari	2005/0159189	A1	7/2005	Iyer
2003/0153364	A1	8/2003	Osann, Jr.	2005/0164684	A1	7/2005	Chen et al.
2003/0155413	A1	8/2003	Kovesdi et al.	2005/0165871	A1	7/2005	Barrs et al.
2003/0157929	A1	8/2003	Janssen et al.	2005/0166242	A1	7/2005	Matsumoto et al.
2003/0166399	A1	9/2003	Tokkonen et al.	2005/0186954	A1	8/2005	Kenney
2003/0169329	A1	9/2003	Parker et al.	2005/0191969	A1	9/2005	Mousseau
2003/0171113	A1	9/2003	Choi	2005/0235312	A1	10/2005	Karaoguz et al.
2003/0174685	A1	9/2003	Hasebe	2005/0257149	A1	11/2005	Kamiya et al.
2003/0181201	A1	9/2003	Bomze et al.	2005/0261945	A1	11/2005	Mougin et al.
2003/0204562	A1	10/2003	Hwang	2005/0272504	A1	12/2005	Eguchi et al.
2003/0208541	A1	11/2003	Musa	2005/0282582	A1	12/2005	Slotznick et al.
2003/0220835	A1	11/2003	Barnes, Jr.	2006/0003813	A1	1/2006	Seligmann et al.
2003/0222762	A1	12/2003	Beigl et al.	2006/0015819	A1	1/2006	Hawkins et al.
2003/0222982	A1	12/2003	Hamdan et al.	2006/0031407	A1	2/2006	Dispensa et al.
2003/0224760	A1	12/2003	Day	2006/0033809	A1	2/2006	Farley
2003/0227570	A1	12/2003	Kim et al.	2006/0041923	A1	2/2006	McQuaide, Jr.
2003/0229900	A1	12/2003	Reisman	2006/0052100	A1	3/2006	Almgren
2003/0236866	A1	12/2003	Light	2006/0059038	A1	3/2006	Iuchi et al.
2004/0003307	A1	1/2004	Tsuji	2006/0073820	A1	4/2006	Craswell et al.
2004/0029640	A1	2/2004	Masuyama et al.	2006/0114100	A1	6/2006	Ghabra et al.
2004/0033795	A1	2/2004	Walsh et al.	2006/0133590	A1	6/2006	Jiang
2004/0034692	A1	2/2004	Eguchi et al.	2006/0140173	A1	6/2006	Hoover
2004/0072595	A1	4/2004	Anson et al.	2006/0140387	A1	6/2006	Boldt
2004/0082321	A1	4/2004	Kontianinen	2006/0143655	A1	6/2006	Ellis et al.
2004/0092255	A1*	5/2004	Ji et al. 455/419	2006/0166650	A1	7/2006	Berger et al.
2004/0103303	A1	5/2004	Yamauchi et al.	2006/0199571	A1	9/2006	Chin et al.
2004/0107072	A1	6/2004	Dietrich et al.	2006/0206913	A1	9/2006	Jerding et al.
2004/0114732	A1	6/2004	Choe et al.	2006/0229114	A2	10/2006	Kim, II
2004/0117108	A1	6/2004	Nemeth	2006/0234693	A1	10/2006	Isidore et al.
2004/0128359	A1	7/2004	Horvitz et al.	2006/0234758	A1	10/2006	Parupudi et al.
2004/0132445	A1	7/2004	Rogalski et al.	2006/0284732	A1	12/2006	Brock-Fisher
2004/0137893	A1	7/2004	Muthuswamy et al.	2007/0015550	A1	1/2007	Kayanuma
2004/0137983	A1	7/2004	Kerr et al.	2007/0050832	A1	3/2007	Wright et al.
2004/0139208	A1	7/2004	Tuli	2007/0061845	A1	3/2007	Barnes, Jr.
2004/0142678	A1	7/2004	Krasner	2007/0109262	A1	5/2007	Oshima et al.
2004/0157664	A1	8/2004	Link	2007/0121596	A1	5/2007	Kurapati et al.
2004/0166832	A1	8/2004	Portman et al.	2007/0135145	A1	6/2007	Lee et al.
2004/0166879	A1	8/2004	Meadows et al.	2007/0135150	A1	6/2007	Ushiki et al.
2004/0174863	A1	9/2004	Caspi et al.	2007/0142047	A1	6/2007	Heeschen
2004/0183937	A1	9/2004	Viinikanoja et al.	2007/0190944	A1	8/2007	Doan et al.
2004/0198374	A1	10/2004	Bajikar	2007/0204014	A1	8/2007	Greer et al.
2004/0203490	A1	10/2004	Kaplan	2007/0216760	A1	9/2007	Kondo et al.
2004/0203520	A1	10/2004	Schirtzinger et al.	2007/0218891	A1	9/2007	Cox
2004/0203577	A1	10/2004	Forman et al.	2007/0260456	A1	11/2007	Proux et al.
2004/0203904	A1	10/2004	Gwon et al.	2007/0262848	A1	11/2007	Berstis et al.
2004/0203909	A1	10/2004	Koster	2007/0293240	A1	12/2007	Drennan et al.
2004/0204035	A1	10/2004	Raghuram et al.	2008/0014917	A1	1/2008	Rhoads et al.
2004/0204126	A1	10/2004	Reyes et al.	2008/0016526	A1	1/2008	Asmussen
2004/0204821	A1	10/2004	Tu	2008/0016534	A1	1/2008	Ortiz et al.
2004/0204848	A1	10/2004	Matsuo et al.	2008/0058005	A1	3/2008	Zicker et al.
2004/0209649	A1	10/2004	Lord	2008/0194273	A1	8/2008	Kansal et al.
2004/0216037	A1	10/2004	Hishida et al.	2008/0242271	A1	10/2008	Schmidt et al.
2004/0218738	A1	11/2004	Arai et al.	2008/0242283	A1	10/2008	Ruckart
2004/0219951	A1	11/2004	Holder	2008/0250459	A1	10/2008	Roman
2004/0222988	A1	11/2004	Donnelly	2008/0299989	A1	12/2008	King et al.
2004/0235513	A1	11/2004	O'Connell	2009/0047972	A1	2/2009	Neeraj
2004/0235520	A1	11/2004	Cadiz et al.	2009/0153490	A1	6/2009	Nymark et al.
2004/0242240	A1	12/2004	Lin	2009/0186628	A1	7/2009	Yonker et al.
2004/0242269	A1	12/2004	Fadell	2009/0197641	A1	8/2009	Rofougaran et al.
2004/0248586	A1	12/2004	Patel et al.	2009/0290369	A1	11/2009	Schofield et al.
2004/0252197	A1	12/2004	Fraley et al.	2010/0030557	A1	2/2010	Molloy et al.
2004/0257208	A1	12/2004	Huang et al.	2010/0062740	A1	3/2010	Ellis et al.
2004/0267628	A1	12/2004	Stillman	2010/0099457	A1	4/2010	Kim
2005/0004749	A1	1/2005	Park	2010/0145700	A1	6/2010	Kennewick et al.
2005/0020301	A1	1/2005	Lee				
2005/0026629	A1	2/2005	Contractor				
2005/0036509	A1	2/2005	Acharya et al.				
2005/0046584	A1	3/2005	Breed				
2005/0048987	A1	3/2005	Glass				
2005/0070257	A1	3/2005	Saarinen et al.				
2005/0090768	A1	4/2005	Brattesani et al.				
2005/0097038	A1	5/2005	Yu et al.				
2005/0107119	A1	5/2005	Lee et al.				

OTHER PUBLICATIONS

Audiovox, "POcket PC Phone User Manual", published on Mar. 19, 2004.
 Gamespot, "Super Mario Bros. 3", Feb 12, 1990, <<http://www.gamespot.com/nes/action/supermariobros3/index.html?tag=tabs%3Bsummary>>.

* cited by examiner



1**COMMUNICATION DEVICE****CROSS REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. Ser. No. 12/344,306, filed Dec. 26, 2008, which is a continuation of U.S. Ser. No. 10/905,836, filed Jan. 22, 2005, which is a continuation of U.S. Ser. No. 10/711,265, filed Sep. 7, 2004, which claims the benefit of U.S. Provisional Application Ser. No. 60/481,695, filed Nov. 22, 2003, all of which are hereby incorporated herein by reference in their entirety.

BACKGROUND OF INVENTION

The invention relates to communication device and more particularly to the communication device which is capable to communicate with another communication device in a wireless fashion.

U.S. Patent Publication No. 20030013483 is introduced as prior art of the present invention of which the summary is the following: "A user interface includes a main screen segregated into various screen areas. At least one of the screen areas is devoted to a system application for displaying status icons, and another of the screen areas is devoted to an interface page which may or may not link to other interface pages which are used for displaying current or recent application information for respective user applications, which user applications may be accessed through interaction with the interface page. The application information may be application status information, recent communication messages (such as e-mail messages, SMS messages, or instant messaging messages) and/or one or more upcoming events or to do items for a user. The user interaction may occur through selection with a pointing device such as a stylus, a fingertip stylus, a finger, or one or more buttons, or even through voice commands. The user interface may also include an area reserved for displaying advertisements." However, this prior art does not disclose the mobile phone, wherein a list of controllers, such as battery controller, CCD unit controller, microphone controller, speaker controller, and vibrator controller, are displayed, and the controller selected from the list is updated by utilizing the mobile phone updating data received via antenna.

For the avoidance of doubt, the number of the prior arts introduced herein (and/or in IDS) may be of a large one, however, applicant has no intent to hide the more relevant prior art(s) in the less relevant ones.

SUMMARY OF INVENTION

It is an object of the present invention to provide a device capable to implement a plurality of functions.

It is another object of the present invention to provide merchandise to merchants attractive to the customers in the U.S.

It is another object of the present invention to provide mobility to the users of communication device.

It is another object of the present invention to provide more convenience to the customers in the U.S.

It is another object of the present invention to provide more convenience to the users of communication device or any tangible thing in which the communication device is fixedly or detachably (i.e., removably) installed.

It is another object of the present invention to overcome the shortcomings associated with the foregoing prior art.

2

The present invention introduces the mobile phone, wherein a list of controllers, such as battery controller, CCD unit controller, microphone controller, speaker controller, and vibrator controller, are displayed, and the controller selected from the list is updated by utilizing the mobile phone updating data received via antenna.

BRIEF DESCRIPTION OF DRAWINGS

The above and other aspects, features, and advantages of the invention will be better understood by reading the following more particular description of the invention, presented in conjunction with the following drawing, wherein:

FIG. 1 is a block diagram illustrating an exemplary embodiment of the present invention.

DETAILED DESCRIPTION

Paragraph [0020]—The following description is of the best presently contemplated mode of carrying out the present invention. This description is not to be taken in a limiting sense but is made merely for the purpose of describing the general principles of the invention. For example, each description of random access memory in this specification illustrate(s) only one function or mode in order to avoid complexity in its explanation, however, such description does not mean that only one function or mode can be implemented at a time. In other words, more than one function or mode can be implemented simultaneously by way of utilizing the same random access memory. In addition, the FIGURE number is cited after the elements in parenthesis in a manner for example 'RAM 206 (FIG. 1)'. It is done so merely to assist the readers to have a better understanding of this specification, and must not be used to limit the scope of the claims in any manner since the FIGURE numbers cited are not exclusive. There are only few data stored in each storage area described in this specification. This is done so merely to simplify the explanation and, thereby, to enable the reader of this specification to understand the content of each function with less confusion. Therefore, more than few data (hundreds and thousands of data, if necessary) of the same kind, not to mention, are preferred to be stored in each storage area to fully implement each function described herein. The scope of the invention should be determined by referencing the appended claims.

Paragraph [0021]—FIG. 1 is a simplified block diagram of the Communication Device 200 utilized in the present invention. Referring to FIG. 1, Communication Device 200 includes CPU 211 which controls and administers the overall function and operation of Communication Device 200. CPU 211 uses RAM 206 to temporarily store data and/or to perform calculation to perform its function, and to implement the present invention, modes, functions, and systems explained hereinafter. Video Processor 202 generates analog and/or digital video signals which are displayed on LCD 201. ROM 207 stores the data and programs which are essential to operate Communication Device 200. Wireless signals are received by Antenna 218 and processed by Signal Processor 208. Input signals are input by Input Device 210, such as a dial pad, a joystick, and/or a keypad, and the signals are transferred via Input Interface 209 and Data Bus 203 to CPU 211. Indicator 212 is an LED lamp which is designed to output different colors (e.g., red, blue, green, etc). Analog audio data is input to Microphone 215. A/D 213 converts the analog audio data into a digital format. Speaker 216 outputs analog audio data which is converted into an analog format from digital format by D/A 204. Sound Processor 205 produces digital audio

signals that are transferred to D/A **204** and also processes the digital audio signals transferred from A/D **213**. CCD Unit **214** captures video image which is stored in RAM **206** in a digital format. Vibrator **217** vibrates the entire device by the command from CPU **211**.

Paragraph [0022]—As another embodiment, LCD **201** or LCD **201**/Video Processor **202** may be separated from the other elements described in FIG. **1**, and be connected in a wireless fashion to be wearable and/or head-mountable.

Paragraph [0023]—When Communication Device **200** is in the voice communication mode, the analog audio data input to Microphone **215** is converted to a digital format by A/D **213** and transmitted to another device via Antenna **218** in a wireless fashion after being processed by Signal Processor **208**, and the wireless signal representing audio data which is received via Antenna **218** is output from Speaker **216** after being processed by Signal Processor **208** and converted to analog signal by D/A **204**. For the avoidance of doubt, the definition of Communication Device **200** in this specification includes so-called ‘PDA’. The definition of Communication Device **200** also includes in this specification any device which is mobile and/or portable and which is capable to send and/or receive audio data, text data, image data, video data, and/or other types of data in a wireless fashion via Antenna **218**. The definition of Communication Device **200** further includes any micro device embedded or installed into devices and equipments (e.g., VCR, TV, tape recorder, heater, air conditioner, fan, clock, micro wave oven, dish washer, refrigerator, oven, washing machine, dryer, door, window, automobile, motorcycle, and modem) to remotely control these devices and equipments. The size of Communication Device **200** is irrelevant. Communication Device **200** may be installed in houses, buildings, bridges, boats, ships, submarines, airplanes, and spaceships, and firmly fixed therein.

Paragraph [0024]—This Paragraph [0024] illustrate(s) the elements of Communication Device **200**. The elements of Communication Device **200** described in this Paragraph [0024] is identical to the ones described in FIG. **1**, except Communication Device **200** has new element, i.e., LED **219**. Here, LED **219** receives infra red signals from other wireless devices, which are transferred to CPU **211** via Data Bus **203**. LED **219** also sends infra red signals in a wireless fashion which are composed by CPU **211** and transferred via Data Bus **203**. As the second embodiment, LED **219** may be connected to Signal Processor **208**. Here, LED **219** transfers the received infra red signals to Signal Processor **208**, and Signal Processor **208** processes and converts the signals to a CPU readable format which are transferred to CPU **211** via Data Bus **203**. The data produced by CPU **211** are processed by Signal Processor **208** and transferred to another device via LED **219** in a wireless fashion. The task of LED **219** is as same as that of Antenna **218** described in FIG. **1** except that LED **219** utilizes infra red signals for implementing wireless communication in the second embodiment. For the avoidance of doubt, the reference to FIG. **1** (e.g., referring to FIG. **1** in parenthesis) automatically refers to this Paragraph [0024] in this specification.

Paragraph [0025]—This Paragraph [0025] illustrate(s) the data stored in Host H. In the present embodiment, Host H includes Host Information Storage Area **H00a** which stores various types of data to assist and/or co-operate with Communication Device **200** to implement all modes, functions, and systems described in this specification. As another embodiment, Host H may be composed of a plurality of computers, i.e., one master computer and a plurality of slave computers, wherein the master computer is connected to the plurality of slave computers. As another embodiment, Host H

may also be composed of a plurality of master computers by way of utilizing peer-to-peer connection.

Paragraph [0026]—<<Multiple Language Displaying Function>>

Paragraph [0027]—Paragraph [0028] through Paragraph [0076] illustrate the multiple language displaying function wherein a language is selected from a plurality of languages, such as English, Japanese, French, and German, which is utilized to operate Communication Device **200**.

Paragraph [0028]—This Paragraph [0028] illustrates the storage area included in RAM **206** (FIG. **1**). In the present embodiment, RAM **206** includes Multiple Language Displaying Info Storage Area **20654a** of which the data and the software programs stored therein are described in Paragraph [0030].

Paragraph [0029]—The data and/or the software programs stored in Multiple Language Displaying Info Storage Area **20654a** (Paragraph [0028]) may be downloaded from Host H (Paragraph [0025]).

Paragraph [0030]—This Paragraph [0030] illustrates the storage areas included in Multiple Language Displaying Info Storage Area **20654a** (Paragraph [0028]). In the present embodiment, Multiple Language Displaying Info Storage Area **20654a** includes Multiple Language Displaying Data Storage Area **20654b** and Multiple Language Displaying Software Storage Area **20654c**. Multiple Language Displaying Data Storage Area **20654b** stores the data necessary to implement the present function, such as the ones described in Paragraph [0031] through Paragraph [0039]. Multiple Language Displaying Software Storage Area **20654c** stores the software programs necessary to implement the present function, such as the ones described in Paragraph [0040].

Paragraph [0031]—This Paragraph [0031] illustrates the storage areas included in Multiple Language Displaying Data Storage Area **20654b** (Paragraph [0030]). In the present embodiment, Multiple Language Displaying Data Storage Area **20654b** includes Language Tables Storage Area **20654b1**, Language Type Data Storage Area **20654b2**, Language Item Data Storage Area **20654b3**, and Selected Language Table ID Storage Area **20654b4**. Language Tables Storage Area **20654b1** stores the data described in Paragraph [0032]. Language Type Data Storage Area **20654b2** stores the data described in Paragraph [0038]. Language Item Data Storage Area **20654b3** stores the data described in Paragraph [0039]. Selected Language Table ID Storage Area **20654b4** stores the language table ID selected in S4s of Paragraph [0042], Paragraph [0051], Paragraph [0060], and Paragraph [0069].

Paragraph [0032]—This Paragraph [0032] illustrates the storage areas included in Language Tables Storage Area **20654b1** (Paragraph [0031]). In the present embodiment, Language Tables Storage Area **20654b1** includes Language Table#1 Storage Area **20654b1a**, Language Table#2 Storage Area **20654b1b**, Language Table#3 Storage Area **20654b1c**, and Language Table#4 Storage Area **20654b1d**. Language Table#1 Storage Area **20654b1a** stores the data described in Paragraph [0033]. Language Table#2 Storage Area **20654b1b** stores the data described in Paragraph [0035]. Language Table#3 Storage Area **20654b1c** stores the data described in Paragraph [0036]. Language Table#4 Storage Area **20654b1d** stores the data described in Paragraph [0037].

Paragraph [0033]—This Paragraph [0033] illustrates the data stored in Language Table#1 Storage Area **20654b1a** (Paragraph [0032]). In the present embodiment, Language Table#1 Storage Area **20654b1a** comprises two columns, i.e., ‘Language Item ID’ and ‘Language Text Data’. Column ‘Lan-

5

language Item ID' stores the language item IDs, and each language item ID represents the identification of the corresponding language text data.

Paragraph [0034]—Column 'Language Text Data' stores the language text data, and each language text data represents the English text data displayed on LCD 201 (FIG. 1). In the present embodiment, Language Table#1 Storage Area 20654b1a stores the following data: the language item ID 'Language Item#1' and the corresponding language text data 'Open file'; the language item ID 'Language Item#2' and the corresponding language text data 'Close file'; the language item ID 'Language Item#3' and the corresponding language text data 'Delete'; the language item ID 'Language Item#4' and the corresponding language text data 'Copy'; the language item ID 'Language Item#5' and the corresponding language text data 'Cut'; the language item ID 'Language Item#6' and the corresponding language text data 'Paste'; the language item ID 'Language Item#7' and the corresponding language text data 'Insert'; the language item ID 'Language Item#8' and the corresponding language text data 'File'; the language item ID 'Language Item#9' and the corresponding language text data 'Edit'; the language item ID 'Language Item#10' and the corresponding language text data 'View'; the language item ID 'Language Item#11' and the corresponding language text data 'Format'; the language item ID 'Language Item#12' and the corresponding language text data 'Tools'; the language item ID 'Language Item#13' and the corresponding language text data 'Window'; the language item ID 'Language Item#14' and the corresponding language text data 'Help'; the language item ID 'Language Item#15' and the corresponding language text data 'My Network'; the language item ID 'Language Item#16' and the corresponding language text data 'Trash'; the language item ID 'Language Item#17' and the corresponding language text data 'Local Disk'; the language item ID 'Language Item#18' and the corresponding language text data 'Save'; the language item ID 'Language Item#19' and the corresponding language text data 'Yes'; the language item ID 'Language Item#20' and the corresponding language text data 'No'; and the language item ID 'Language Item#21' and the corresponding language text data 'Cancel'.

Paragraph [0035]—This Paragraph [0035] illustrates the data stored in Language Table#1 Storage Area 20654b1b (Paragraph [0032]). In the present embodiment, Language Table#1 Storage Area 20654b1b comprises two columns, i.e., 'Language Item ID' and 'Language Text Data'. Column 'Language Item ID' stores the language item IDs, and each language item ID represents the identification of the corresponding language text data. Column 'Language Text Data' stores the language text data, and each language text data represents the Japanese text data displayed on LCD 201 (FIG. 1). In the present embodiment, Language Table#1 Storage Area 20654b1b stores the following data: the language item ID 'Language Item#1' and the corresponding language text data meaning 'Open file' in Japanese; the language item ID 'Language Item#2' and the corresponding language text data meaning 'Close file' in Japanese; the language item ID 'Language Item#3' and the corresponding language text data meaning 'Delete' in Japanese; the language item ID 'Language Item#4' and the corresponding language text data meaning 'Copy' in Japanese; the language item ID 'Language Item#5' and the corresponding language text data meaning 'Cut' in Japanese; the language item ID 'Language Item#6' and the corresponding language text data meaning 'Paste' in Japanese; the language item ID 'Language Item#7' and the corresponding language text data meaning 'Insert' in Japanese; the language item ID 'Language Item#8' and the corre-

6

sponding language text data meaning 'File' in Japanese; the language item ID 'Language Item#9' and the corresponding language text data meaning 'Edit' in Japanese; the language item ID 'Language Item#10' and the corresponding language text data meaning 'View' in Japanese; the language item ID 'Language Item#11' and the corresponding language text data meaning 'Format' in Japanese; the language item ID 'Language Item#12' and the corresponding language text data meaning 'Tools' in Japanese; the language item ID 'Language Item#13' and the corresponding language text data meaning 'Window' in Japanese; the language item ID 'Language Item#14' and the corresponding language text data meaning 'Help' in Japanese; the language item ID 'Language Item#15' and the corresponding language text data meaning 'My Network' in Japanese; the language item ID 'Language Item#16' and the corresponding language text data meaning 'Trash' in Japanese; the language item ID 'Language Item#17' and the corresponding language text data meaning 'Local Disk' in Japanese; the language item ID 'Language Item#18' and the corresponding language text data meaning 'Save' in Japanese; the language item ID 'Language Item#19' and the corresponding language text data meaning 'Yes' in Japanese; the language item ID 'Language Item#20' and the corresponding language text data meaning 'No' in Japanese; and the language item ID 'Language Item#21' and the corresponding language text data meaning 'Cancel' in Japanese.

Paragraph [0036]—This Paragraph [0036] illustrates the data stored in Language Table#1 Storage Area 20654b1c (Paragraph [0032]). In the present embodiment, Language Table#1 Storage Area 20654b1c comprises two columns, i.e., 'Language Item ID' and 'Language Text Data'. Column 'Language Item ID' stores the language item IDs, and each language item ID represents the identification of the corresponding language text data. Column 'Language Text Data' stores the language text data, and each language text data represents the French text data displayed on LCD 201 (FIG. 1). In the present embodiment, Language Table#1 Storage Area 20654b1c stores the following data: the language item ID 'Language Item#1' and the corresponding language text data 'French#1' meaning 'Open file' in French; the language item ID 'Language Item#2' and the corresponding language text data 'French#2' meaning 'Close file' in French; the language item ID 'Language Item#3' and the corresponding language text data 'French#3' meaning 'Delete' in French; the language item ID 'Language Item#4' and the corresponding language text data 'French#4' meaning 'Copy' in French; the language item ID 'Language Item#5' and the corresponding language text data 'French#5' meaning 'Cut' in French; the language item ID 'Language Item#6' and the corresponding language text data 'French#6' meaning 'Paste' in French; the language item ID 'Language Item#7' and the corresponding language text data 'French#7' meaning 'Insert' in French; the language item ID 'Language Item#8' and the corresponding language text data 'French#8' meaning 'File' in French; the language item ID 'Language Item#9' and the corresponding language text data 'French#9' meaning 'Edit' in French; the language item ID 'Language Item#10' and the corresponding language text data 'French#10' meaning 'View' in French; the language item ID 'Language Item#11' and the corresponding language text data 'French#11' meaning 'Format' in French; the language item ID 'Language Item#12' and the corresponding language text data 'French#12' meaning 'Tools' in French; the language item ID 'Language Item#13' and the corresponding language text data 'French#13' meaning 'Window' in French; the language item ID 'Language Item#14' and the corresponding language text data 'French#14' meaning 'Help' in French; the language item ID

‘Language Item#15’ and the corresponding language text data ‘French#15’ meaning ‘My Network’ in French; the language item ID ‘Language Item#16’ and the corresponding language text data ‘French#16’ meaning ‘Trash’ in French; the language item ID ‘Language Item#17’ and the corresponding language text data ‘French#17’ meaning ‘Local Disk’ in French; the language item ID ‘Language Item#18’ and the corresponding language text data ‘French#18’ meaning ‘Save’ in French; the language item ID ‘Language Item#19’ and the corresponding language text data ‘French#19’ meaning ‘Yes’ in French; the language item ID ‘Language Item#20’ and the corresponding language text data ‘French#20’ meaning ‘No’ in French; and the language item ID ‘Language Item#21’ and the corresponding language text data ‘French#21’ meaning ‘Cancel’ in French.

Paragraph [0037]—This Paragraph [0037] illustrates the data stored in Language Table#1 Storage Area **20654b1d** (Paragraph [0032]). In the present embodiment, Language Table#1 Storage Area **20654b1d** comprises two columns, i.e., ‘Language Item ID’ and ‘Language Text Data’. Column ‘Language Item ID’ stores the language item IDs, and each language item ID represents the identification of the corresponding language text data. Column ‘Language Text Data’ stores the language text data, and each language text data represents the German text data displayed on LCD **201** (FIG. 1). In the present embodiment, Language Table#1 Storage Area **20654b1d** stores the following data: the language item ID ‘Language Item#1’ and the corresponding language text data ‘German#1’ meaning ‘Open file’ in German; the language item ID ‘Language Item#2’ and the corresponding language text data ‘German#2’ meaning ‘Close file’ in German; the language item ID ‘Language Item#3’ and the corresponding language text data ‘German#3’ meaning ‘Delete’ in German; the language item ID ‘Language Item#4’ and the corresponding language text data ‘German#4’ meaning ‘Copy’ in German; the language item ID ‘Language Item#5’ and the corresponding language text data ‘German#5’ meaning ‘Cut’ in German; the language item ID ‘Language Item#6’ and the corresponding language text data ‘German#6’ meaning ‘Paste’ in German; the language item ID ‘Language Item#7’ and the corresponding language text data ‘German#7’ meaning ‘Insert’ in German; the language item ID ‘Language Item#8’ and the corresponding language text data ‘German#8’ meaning ‘File’ in German; the language item ID ‘Language Item#9’ and the corresponding language text data ‘German#9’ meaning ‘Edit’ in German; the language item ID ‘Language Item#10’ and the corresponding language text data ‘German#10’ meaning ‘View’ in German; the language item ID ‘Language Item#11’ and the corresponding language text data ‘German#11’ meaning ‘Format’ in German; the language item ID ‘Language Item#12’ and the corresponding language text data ‘German#12’ meaning ‘Tools’ in German; the language item ID ‘Language Item#13’ and the corresponding language text data ‘German#13’ meaning ‘Window’ in German; the language item ID ‘Language Item#14’ and the corresponding language text data ‘German#14’ meaning ‘Help’ in German; the language item ID ‘Language Item#15’ and the corresponding language text data ‘German#15’ meaning ‘My Network’ in German; the language item ID ‘Language Item#16’ and the corresponding language text data ‘German#16’ meaning ‘Trash’ in German; the language item ID ‘Language Item#17’ and the corresponding language text data ‘German#17’ meaning ‘Local Disk’ in German; the language item ID ‘Language Item#18’ and the corresponding language text data ‘German#18’ meaning ‘Save’ in German; the language item ID ‘Language Item#19’ and the corresponding language text data

‘German#19’ meaning ‘Yes’ in German; the language item ID ‘Language Item#20’ and the corresponding language text data ‘German#20’ meaning ‘No’ in German; and the language item ID ‘Language Item#21’ and the corresponding language text data ‘German#21’ meaning ‘Cancel’ in German.

Paragraph [0038]—This Paragraph [0038] illustrates data stored in Language Type Data Storage Area **20654b2** (Paragraph [0031]). In the present embodiment, Language Type Data Storage Area **20654b2** comprises two columns, i.e., ‘Language Table ID’ and ‘Language Type Data’. Column ‘Language Table ID’ stores the language table ID, and each language table ID represents the identification of the storage areas included in Language Tables Storage Area **20654b1** (Paragraph [0032]). Column ‘Language Type Data’ stores the language type data, and each language type data represents the type of the language utilized in the language table of the corresponding language table ID. In the present embodiment, Language Type Data Storage Area **20654b2** stores the following data: the language table ID ‘Language Table#1’ and the corresponding language type data ‘English’; the language table ID ‘Language Table#2’ and the corresponding language type data ‘Japanese’; the language table ID ‘Language Table#3’ and the corresponding language type data ‘French’; and the language table ID ‘Language Table#4’ and the corresponding language type data ‘German’. Here, the language table ID ‘Language Table#1’ is an identification of Language Table#1 Storage Area **20654b1a** (Paragraph [0033]); the language table ID ‘Language Table#2’ is an identification of Language Table#2 Storage Area **20654b1b** (Paragraph [0035]); the language table ID ‘Language Table#3’ is an identification of Language Table#3 Storage Area **20654b1c** (Paragraph [0036]); and the language table ID ‘Language Table#4’ is an identification of Language Table#4 Storage Area **20654b1d** (Paragraph [0037]).

Paragraph [0039]—This Paragraph [0039] illustrates the data stored in Language Item Data Storage Area **20654b3** (Paragraph [0031]). In the present embodiment, Language Item Data Storage Area **20654b3** comprises two columns, i.e., ‘Language Item ID’ and ‘Language Item Data’. Column ‘Language Item ID’ stores the language item IDs, and each language item ID represents the identification of the corresponding language item data. Column ‘Language Item Data’ stores the language item data, and each language item data represents the content and/or the meaning of the language text data displayed on LCD **201** (FIG. 1). In the present embodiment, Language Item Data Storage Area **20654b3** stores the following data: the language item ID ‘Language Item#1’ and the corresponding language item data ‘Open file’; the language item ID ‘Language Item#2’ and the corresponding language item data ‘Close file’; the language item ID ‘Language Item#3’ and the corresponding language item data ‘Delete’; the language item ID ‘Language Item#4’ and the corresponding language item data ‘Copy’; the language item ID ‘Language Item#5’ and the corresponding language item data ‘Cut’; the language item ID ‘Language Item#6’ and the corresponding language item data ‘Paste’; the language item ID ‘Language Item#7’ and the corresponding language item data ‘Insert’; the language item ID ‘Language Item#8’ and the corresponding language item data ‘File’; the language item ID ‘Language Item#9’ and the corresponding language item data ‘Edit’; the language item ID ‘Language Item#10’ and the corresponding language item data ‘View’; the language item ID ‘Language Item#11’ and the corresponding language item data ‘Format’; the language item ID ‘Language Item#12’ and the corresponding language item data ‘Tools’; the language item ID ‘Language Item#13’ and the corresponding language item data ‘Window’; the language item ID ‘Language

Item#14' and the corresponding language item data 'Help'; the language item ID 'Language Item#15' and the corresponding language item data 'My Network'; the language item ID 'Language Item#16' and the corresponding language item data 'Trash'; the language item ID 'Language Item#17' and the corresponding language item data 'Local Disk'; the language item ID 'Language Item#18' and the corresponding language item data 'Save'; the language item ID 'Language Item#19' and the corresponding language item data 'Yes'; the language item ID 'Language Item#20' and the corresponding language item data 'No'; and the language item ID 'Language Item#21' and the corresponding language item data 'Cancel'. Primarily, the data stored in column 'Language Item Data' are same as the ones stored in column 'Language Text Data' of Language Table#1 Storage Area 20654b1a (Paragraph [0033]).

Paragraph [0040]—This Paragraph [0040] illustrates the software program stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0030]). In the present embodiment, Multiple Language Displaying Software Storage Area 20654c stores Language Selecting Software 20654c1, Selected Language Displaying Software 20654c2, Language Text Data Displaying Software For Word Processor 20654c3a, Language Text Data Displaying Software For Word Processor 20654c3b, and Language Text Data Displaying Software For Explorer 20654c4. Language Selecting Software 20654c1 is the software program described in Paragraph [0042], Paragraph [0051], Paragraph [0060], and Paragraph [0069]. Selected Language Displaying Software 20654c2 is the software program described in Paragraph [0043], Paragraph [0052], Paragraph [0061], and Paragraph [0070]. Language Text Data Displaying Software For Word Processor 20654c3a is the software program described in Paragraph [0044], Paragraph [0053], Paragraph [0062], and Paragraph [0071]. Language Text Data Displaying Software For Word Processor 20654c3b is the software program described in Paragraph [0046], Paragraph [0055], Paragraph [0064], and Paragraph [0073]. Language Text Data Displaying Software For Explorer 20654c4 is the software program described in Paragraph [0048], Paragraph [0057], Paragraph [0066], and Paragraph [0075].

Paragraph [0041]—<<Multiple Language Displaying Function—Utilizing English>>

Paragraph [0042]—This Paragraph [0042] illustrates Language Selecting Software 20654c1 stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which selects the language utilized to operate Communication Device 200 from a plurality of languages. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 retrieves the language type data from Language Type Data Storage Area 20654b2 (Paragraph [0038]) (S1), and Displays a list of available languages on LCD 201 (FIG. 1) (S2). In the present example, the following languages are displayed on LCD 201: English, Japanese, French, and German. A certain language is selected therefrom by utilizing Input Device 210 (FIG. 1) or via voice recognition system (S3). Assume that 'English' is selected in S3. CPU 211 then identifies the language table ID corresponding to the language type data in Language Type Data Storage Area 20654b2 (Paragraph [0038]), and stores the language table ID (Language Table#1) in Selected Language Table ID Storage Area 20654b4 (Paragraph [0031]) (S4).

Paragraph [0043]—This Paragraph [0043] illustrates Selected Language Displaying Software 20654c2 stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which displays and operates with the language selected in S3 of Paragraph [0042] (i.e.,

English). In the present embodiment, when Communication Device 200 is powered on (S1), CPU 211 (FIG. 1) of Communication Device 200 retrieves the selected language table ID (Language Table#1) from Selected Language Table ID Storage Area 20654b4 (Paragraph [0031]) (S2). CPU 211 then identifies the storage area corresponding to the language table ID selected in S2 (Language Table#1 Storage Area 20654b1a (Paragraph [0033])) in Language Tables Storage Area 20654b1 (Paragraph [0032]) (S3). Language text data displaying process is initiated thereafter of which the details are described hereinafter (S4).

Paragraph [0044]—This Paragraph [0044] illustrates Language Text Data Displaying Software For Word Processor 20654c3a stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which displays the language text data at the time a word processor, such as MS Word and WordPerfect is executed. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 executes a word processor in response to the signal input by the user of Communication Device 200 indicating to activate and execute the word processor (S1). In the process of displaying the word processor on LCD 201 (FIG. 1), the following steps of S2 through S8 are implemented. Namely, CPU 211 identifies the language item ID 'Language Item#8' in Language Table#1 Storage Area 20654b1a (Paragraph [0033]) and displays the corresponding language text data 'File' at the predetermined location in the word processor (S2). CPU 211 identifies the language item ID 'Language Item#9' in Language Table#1 Storage Area 20654b1a (Paragraph [0033]) and displays the corresponding language text data 'Edit' at the predetermined location in the word processor (S3). CPU 211 identifies the language item ID 'Language Item#10' in Language Table#1 Storage Area 20654b1a (Paragraph [0033]) and displays the corresponding language text data 'View' at the predetermined location in the word processor (S4). CPU 211 identifies the language item ID 'Language Item#11' in Language Table#1 Storage Area 20654b1a (Paragraph [0033]) and displays the corresponding language text data 'Format' at the predetermined location in the word processor (S5). CPU 211 identifies the language item ID 'Language Item#12' in Language Table#1 Storage Area 20654b1a (Paragraph [0033]) and displays the corresponding language text data 'Tools' at the predetermined location in the word processor (S6). CPU 211 identifies the language item ID 'Language Item#13' in Language Table#1 Storage Area 20654b1a (Paragraph [0033]) and displays the corresponding language text data 'Window' at the predetermined location in the word processor (S7). CPU 211 identifies the language item ID 'Language Item#14' in Language Table#1 Storage Area 20654b1a (Paragraph [0033]) and displays the corresponding language text data 'Help' at the predetermined location in the word processor (S8). Alphanumeric data is input to the word processor by utilizing Input Device 210 (FIG. 1) or via voice recognition system thereafter (S9).

Paragraph [0045]—This Paragraph [0045] illustrates the data displayed on LCD 201 (FIG. 1) of Communication Device 200 at the time Language Text Data Displaying Software For Word Processor 20654c3a (Paragraph [0044]) is implemented. In the present embodiment, the word processor described in Paragraph [0044] is primarily composed of Menu Bar 20154MB and Alphanumeric Data Input Area 20154ADIA wherein the language text data described in S2 through S8 of Paragraph [0044] are displayed on Menu Bar 20154MB and alphanumeric data are input in Alphanumeric Data Input Area 20154ADIA. In the present embodiment, 20154MBF is the language text data processed in S2 of the previous paragraph; 20154MBE is the language text data

processed in **S3** of the previous paragraph; **20154MBV** is the language text data processed in **S4** of the previous paragraph; **20154MBF** is the language text data processed in **S5** of the previous paragraph; **20154MBT** is the language text data processed in **S6** of the previous paragraph; **20154MBW** is the language text data processed in **S7** of the previous paragraph; and **20154MBH** is the language text data processed in **S8** of the previous paragraph.

Paragraph [0046]—This Paragraph [0046] illustrates Language Text Data Displaying Software For Word Processor **20654c3b** stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which displays a prompt on LCD **201** (FIG. 1) at the time a word processor is closed. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** initiates the closing process of the word processor in response to the signal input by the user of Communication Device **200** indicating to close the word processor (**S1**). In the process of closing the word processor, the following steps of **S2** through **S5** are implemented. Namely, CPU **211** identifies the language item ID ‘Language Item#18’ in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data ‘Save’ at the predetermined location in the word processor (**S2**). CPU **211** identifies the language item ID ‘Language Item#19’ in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data ‘Yes’ at the predetermined location in the word processor (**S3**). CPU **211** identifies the language item ID ‘Language Item#20’ in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data ‘No’ at the predetermined location in the word processor (**S4**). CPU **211** identifies the language item ID ‘Language Item#21’ in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data ‘Cancel’ at the predetermined location in the word processor (**S5**). The save signal indicating to save the alphanumeric data input in **S9** of Paragraph [0044] is input by utilizing Input Device **210** (FIG. 1) or via voice recognition system, assuming that the user of Communication Device **200** intends to save the data (**S6**), and the data are saved in a predetermined location in RAM **206** (FIG. 1) (**S7**). The word processor is closed thereafter (**S8**).

Paragraph [0047]—This Paragraph [0047] illustrates the data displayed on LCD **201** (FIG. 1) of Communication Device **200** at the time Language Text Data Displaying Software For Word Processor **20654c3b** (Paragraph [0046]) is implemented. In the present embodiment, Prompt **20154Pr** is displayed on LCD **201** (FIG. 1) at the time Language Text Data Displaying Software For Word Processor **20654c3a** (Paragraph [0044]) is closed. In the present embodiment, Prompt **20154Pr** is primarily composed of **20154PrS**, **20154PrY**, **20154PrN**, and **20154PrC**. In the present embodiment, **20154PrS** is the language text data processed in **S2** of the previous paragraph; **20154PrY** is the language text data processed in **S3** of the previous paragraph; **20154PrN** is the language text data processed in **S4** of the previous paragraph; and **20154PrC** is the language text data processed in **S5** of the previous paragraph.

Paragraph [0048]—This Paragraph [0048] illustrates Language Text Data Displaying Software For Explorer **20654c4** stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which displays the language text data at the time a Windows Explorer like software program which displays folders and/or directories and the structures thereof is executed. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** executes Windows Explorer like software program in response to the signal

input by the user of Communication Device **200** indicating to activate and execute the software program (**S1**). In the process of displaying the Windows Explorer like software program on LCD **201** (FIG. 1), the steps of **S2** through **S4** are implemented. Namely, CPU **211** identifies the language item ID ‘Language Item#15’ in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data ‘My Network’ at the predetermined location in the Windows Explorer like software program (**S2**). CPU **211** identifies the language item ID ‘Language Item#16’ in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data ‘Trash’ at the predetermined location in the Windows Explorer like software program (**S3**). CPU **211** identifies the language item ID ‘Language Item#17’ in Language Table#1 Storage Area **20654b1a** (Paragraph [0033]) and displays the corresponding language text data ‘Local Disk’ at the predetermined location in the Windows Explorer like software program (**S4**).

Paragraph [0049]—This Paragraph [0049] illustrates the data displayed on LCD **201** (FIG. 1) of Communication Device **200** at the time Language Text Data Displaying Software For Explorer **20654c4** (Paragraph [0048]) is executed. In the present embodiment, **20154LD**, **20154MN**, and **20154Tr** are displayed on LCD **201** (FIG. 1) at the time Language Text Data Displaying Software For Explorer **20654c4** is executed. In the present embodiment, **20154LD** is the language text data processed in **S4** of the previous paragraph; **20154MN** is the language text data processed in **S2** of the previous paragraph; and **20154Tr** is the language text data processed in **S3** of the previous paragraph.

Paragraph [0050]—<<Multiple Language Displaying Function—Utilizing Japanese>>

Paragraph [0051]—This Paragraph [0051] illustrates Language Selecting Software **20654c1** stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which selects the language utilized to operate Communication Device **200** from a plurality of languages. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves the language type data from Language Type Data Storage Area **20654b2** (Paragraph [0038]) (**S1**), and Displays a list of available languages on LCD **201** (FIG. 1) (**S2**). In the present example, the following languages are displayed on LCD **201**: English, Japanese, French, and German. A certain language is selected therefrom by utilizing Input Device **210** (FIG. 1) or via voice recognition system (**S3**). Assume that ‘Japanese’ is selected in **S3**. CPU **211** then identifies the language table ID corresponding to the language type data in Language Type Data Storage Area **20654b2** (Paragraph [0038]), and stores the language table ID (Language Table#2) in Selected Language Table ID Storage Area **20654b4** (Paragraph [0031]) (**S4**).

Paragraph [0052]—This Paragraph [0052] illustrates Selected Language Displaying Software **20654c2** stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which displays and operates with the language selected in **S3** of Paragraph [0051] (i.e., Japanese). In the present embodiment, when Communication Device **200** is powered on (**S1**), CPU **211** (FIG. 1) of Communication Device **200** retrieves the selected language table ID (Language Table#2) from Selected Language Table ID Storage Area **20654b4** (Paragraph [0031]) (**S2**). CPU **211** then identifies the storage area corresponding to the language table ID selected in **S2** (Language Table#2 Storage Area **20654b1b** (Paragraph [0035])) in Language Tables Storage Area **20654b1** (Paragraph [0032]) (**S3**). Language text data

displaying process is initiated thereafter of which the details are described hereinafter (S4).

Paragraph [0053]—This Paragraph [0053] illustrates Language Text Data Displaying Software For Word Processor **20654c3a** stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which displays the language text data at the time a word processor, such as MS Word and WordPerfect is executed. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** executes a word processor in response to the signal input by the user of Communication Device **200** indicating to activate and execute the word processor (S1). In the process of displaying the word processor on LCD **201** (FIG. 1), the following steps of S2 through S8 are implemented. Namely, CPU **211** identifies the language item ID ‘Language Item#8’ in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating ‘File’ in Japanese at the predetermined location in the word processor (S2). CPU **211** identifies the language item ID ‘Language Item#9’ in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating ‘Edit’ in Japanese at the predetermined location in the word processor (S3). CPU **211** identifies the language item ID ‘Language Item#10’ in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating ‘View’ in Japanese at the predetermined location in the word processor (S4). CPU **211** identifies the language item ID ‘Language Item#11’ in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating ‘Format’ in Japanese at the predetermined location in the word processor (S5). CPU **211** identifies the language item ID ‘Language Item#12’ in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating ‘Tools’ in Japanese at the predetermined location in the word processor (S6). CPU **211** identifies the language item ID ‘Language Item#13’ in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating ‘Window’ in Japanese at the predetermined location in the word processor (S7). CPU **211** identifies the language item ID ‘Language Item#14’ in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating ‘Help’ in Japanese at the predetermined location in the word processor (S8). Alphanumeric data is input to the word processor by utilizing Input Device **210** (FIG. 1) or via voice recognition system thereafter (S9).

Paragraph [0054]—This Paragraph [0054] illustrates the data displayed on LCD **201** (FIG. 1) of Communication Device **200** at the time Language Text Data Displaying Software For Word Processor **20654c3a** (Paragraph [0053]) is implemented. In the present embodiment, the word processor described in Paragraph [0053] is primarily composed of Menu Bar **20154MB** and Alphanumeric Data Input Area **20154ADIA** wherein the language text data described in S2 through S8 of Paragraph [0053] are displayed on Menu Bar **20154MB** and alphanumeric data are input in Alphanumeric Data Input Area **20154ADIA**. In the present embodiment, **20154MBF** is the language text data processed in S2 of the previous paragraph; **20154MBE** is the language text data processed in S3 of the previous paragraph; **20154MBV** is the language text data processed in S4 of the previous paragraph; **20154MBF** is the language text data processed in S5 of the previous paragraph; **20154MBT** is the language text data processed in S6 of the previous paragraph; **20154MBW** is the

language text data processed in S7 of the previous paragraph; and **20154MBH** is the language text data processed in S8 of the previous paragraph.

Paragraph [0055]—This Paragraph [0055] illustrates Language Text Data Displaying Software For Word Processor **20654c3b** stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which displays a prompt on LCD **201** (FIG. 1) at the time a word processor is closed. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** initiates the closing process of the word processor in response to the signal input by the user of Communication Device **200** indicating to close the word processor (S1). In the process of closing the word processor, the following steps of S2 through S5 are implemented. Namely, CPU **211** identifies the language item ID ‘Language Item#18’ in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating ‘Save’ in Japanese at the predetermined location in the word processor (S2). CPU **211** identifies the language item ID ‘Language Item#19’ in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating ‘Yes’ in Japanese at the predetermined location in the word processor (S3). CPU **211** identifies the language item ID ‘Language Item#20’ in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating ‘No’ in Japanese at the predetermined location in the word processor (S4). CPU **211** identifies the language item ID ‘Language Item#21’ in Language Table#2 Storage Area **20654b1b** (Paragraph [0035]) and displays the corresponding language text data indicating ‘Cancel’ in Japanese at the predetermined location in the word processor (S5). The save signal indicating to save the alphanumeric data input in S9 of Paragraph [0053] is input by utilizing Input Device **210** (FIG. 1) or via voice recognition system, assuming that the user of Communication Device **200** intends to save the data (S6), and the data are saved in a predetermined location in RAM **206** (FIG. 1) (S7). The word processor is closed thereafter (S8).

Paragraph [0056]—This Paragraph [0056] illustrates the data displayed on LCD **201** (FIG. 1) of Communication Device **200** at the time Language Text Data Displaying Software For Word Processor **20654c3b** (Paragraph [0055]) is implemented. In the present embodiment, Prompt **20154Pr** is displayed on LCD **201** (FIG. 1) at the time Language Text Data Displaying Software For Word Processor **20654c3a** (Paragraph [0053]) is closed. In the present embodiment, Prompt **20154Pr** is primarily composed of **20154PrS**, **20154PrY**, **20154PrN**, and **20154PrC**. In the present embodiment, **20154PrS** is the language text data processed in S2 of the previous paragraph; **20154PrY** is the language text data processed in S3 of the previous paragraph; **20154PrN** is the language text data processed in S4 of the previous paragraph; and **20154PrC** is the language text data processed in S5 of the previous paragraph.

Paragraph [0057]—This Paragraph [0057] illustrates Language Text Data Displaying Software For Explorer **20654c4** stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which displays the language text data at the time a Windows Explorer like software program which displays folders and/or directories and the structures thereof is executed. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** executes Windows Explorer like software program in response to the signal input by the user of Communication Device **200** indicating to activate and execute the software program (S1). In the process of displaying the Windows Explorer like software program on

LCD 201 (FIG. 1), the following steps of S2 through S4 are implemented. Namely, CPU 211 identifies the language item ID 'Language Item#15' in Language Table#2 Storage Area 20654b1b (Paragraph [0035]) and displays the corresponding language text data indicating 'My Network' in Japanese at the predetermined location in the Windows Explorer like software program (S2). CPU 211 identifies the language item ID 'Language Item#16' in Language Table#2 Storage Area 20654b1b (Paragraph [0035]) and displays the corresponding language text data indicating 'Trash' in Japanese at the predetermined location in the Windows Explorer like software program (S3). CPU 211 identifies the language item ID 'Language Item#17' in Language Table#2 Storage Area 20654b1b (Paragraph [0035]) and displays the corresponding language text data indicating 'Local Disk' in Japanese at the predetermined location in the Windows Explorer like software program (S4).

Paragraph [0058]—This Paragraph [0058] illustrates the data displayed on LCD 201 (FIG. 1) of Communication Device 200 at the time Language Text Data Displaying Software For Explorer 20654c4 (Paragraph [0057]) is executed. In the present embodiment, 20154LD, 20154MN, and 20154Tr are displayed on LCD 201 (FIG. 1) at the time Language Text Data Displaying Software For Explorer 20654c4 is executed. In the present embodiment, 20154LD is the language text data processed in S4 of the previous paragraph; 20154MN is the language text data processed in S2 of the previous paragraph; and 20154Tr is the language text data processed in S3 of the previous paragraph.

Paragraph [0059]—<<Multiple Language Displaying Function—Utilizing French>>

Paragraph [0060]—This Paragraph [0060] illustrates Language Selecting Software 20654c1 stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which selects the language utilized to operate Communication Device 200 from a plurality of languages. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 retrieves the language type data from Language Type Data Storage Area 20654b2 (Paragraph [0038]) (S1), and Displays a list of available languages on LCD 201 (FIG. 1) (S2). In the present example, the following languages are displayed on LCD 201: English, Japanese, French, and German. A certain language is selected therefrom by utilizing Input Device 210 (FIG. 1) or via voice recognition system (S3). Assume that 'French' is selected in S3. CPU 211 then identifies the language table ID corresponding to the language type data in Language Type Data Storage Area 20654b2 (Paragraph [0038]), and stores the language table ID (Language Table#3) in Selected Language Table ID Storage Area 20654b4 (Paragraph [0031]) (S4).

Paragraph [0061]—This Paragraph [0061] illustrates Selected Language Displaying Software 20654c2 stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which displays and operates with the language selected in S3 of Paragraph [0060] (i.e., French). In the present embodiment, when Communication Device 200 is powered on (S1), CPU 211 (FIG. 1) of Communication Device 200 retrieves the selected language table ID (Language Table#3) from Selected Language Table ID Storage Area 20654b4 (Paragraph [0031]) (S2). CPU 211 then identifies the storage area corresponding to the language table ID selected in S2 (Language Table#3 Storage Area 20654b1c (Paragraph [0036])) in Language Tables Storage Area 20654b1 (Paragraph [0032]) (S3). Language text data displaying process is initiated thereafter of which the details are described hereinafter (S4).

Paragraph [0062]—This Paragraph [0062] illustrates Language Text Data Displaying Software For Word Processor 20654c3a stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which displays the language text data at the time a word processor, such as MS Word and WordPerfect is executed. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 executes a word processor in response to the signal input by the user of Communication Device 200 indicating to activate and execute the word processor (S1). In the process of displaying the word processor on LCD 201 (FIG. 1), the following steps of S2 through S8 are implemented. Namely, CPU 211 identifies the language item ID 'Language Item#8' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#8' indicating 'File' in French at the predetermined location in the word processor (S2). CPU 211 identifies the language item ID 'Language Item#9' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#9' indicating 'Edit' in French at the predetermined location in the word processor (S3). CPU 211 identifies the language item ID 'Language Item#10' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#10' indicating 'View' in French at the predetermined location in the word processor (S4). CPU 211 identifies the language item ID 'Language Item#11' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#11' indicating 'Format' in French at the predetermined location in the word processor (S5). CPU 211 identifies the language item ID 'Language Item#12' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#12' indicating 'Tools' in French at the predetermined location in the word processor (S6). CPU 211 identifies the language item ID 'Language Item#13' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#13' indicating 'Window' in French at the predetermined location in the word processor (S7). CPU 211 identifies the language item ID 'Language Item#14' in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data 'French#14' indicating 'Help' in French at the predetermined location in the word processor (S8). Alphanumeric data is input to the word processor by utilizing Input Device 210 (FIG. 1) or via voice recognition system thereafter (S9).

Paragraph [0063]—This Paragraph [0063] illustrates the data displayed on LCD 201 (FIG. 1) of Communication Device 200 at the time Language Text Data Displaying Software For Word Processor 20654c3a (Paragraph [0062]) is implemented. In the present embodiment, the word processor described in Paragraph [0062] is primarily composed of Menu Bar 20154MB and Alphanumeric Data Input Area 20154ADIA wherein the language text data described in S2 through S8 of Paragraph [0062] are displayed on Menu Bar 20154MB and alphanumeric data are input in Alphanumeric Data Input Area 20154ADIA. In the present embodiment, 20154MBF is the language text data processed in S2 of the previous paragraph; 20154MBE is the language text data processed in S3 of the previous paragraph; 20154MBV is the language text data processed in S4 of the previous paragraph; 20154MBF is the language text data processed in S5 of the previous paragraph; 20154MBT is the language text data processed in S6 of the previous paragraph; 20154MBW is the

language text data processed in S7 of the previous paragraph; and 20154MBH is the language text data processed in S8 of the previous paragraph.

Paragraph [0064]—This Paragraph [0064] illustrates Language Text Data Displaying Software For Word Processor 20654c3b stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which displays a prompt on LCD 201 (FIG. 1) at the time a word processor is closed. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 initiates the closing process of the word processor in response to the signal input by the user of Communication Device 200 indicating to close the word processor (S1). In the process of closing the word processor, the following steps of S2 through S5 are implemented. Namely, CPU 211 identifies the language item ID ‘Language Item#18’ in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data ‘French#18’ indicating ‘Save’ in French at the predetermined location in the word processor (S2). CPU 211 identifies the language item ID ‘Language Item#19’ in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data ‘French#19’ indicating ‘Yes’ in French at the predetermined location in the word processor (S3). CPU 211 identifies the language item ID ‘Language Item#20’ in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data ‘French#20’ indicating ‘No’ in French at the predetermined location in the word processor (S4). CPU 211 identifies the language item ID ‘Language Item#21’ in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data ‘French#21’ indicating ‘Cancel’ in French at the predetermined location in the word processor (S5). The save signal indicating to save the alphanumeric data input in S9 of Paragraph [0062] is input by utilizing Input Device 210 (FIG. 1) or via voice recognition system, assuming that the user of Communication Device 200 intends to save the data (S6), and the data are saved in a predetermined location in RAM 206 (FIG. 1) (S7). The word processor is closed thereafter (S8).

Paragraph [0065]—This Paragraph [0065] illustrates the data displayed on LCD 201 (FIG. 1) of Communication Device 200 at the time Language Text Data Displaying Software For Word Processor 20654c3b (Paragraph [0064]) is implemented. In the present embodiment, Prompt 20154Pr is displayed on LCD 201 (FIG. 1) at the time Language Text Data Displaying Software For Word Processor 20654c3a (Paragraph [0062]) is closed. In the present embodiment, Prompt 20154Pr is primarily composed of 20154PrS, 20154PrY, 20154PrN, and 20154PrC. In the present embodiment, 20154PrS is the language text data processed in S2 of the previous paragraph; 20154PrY is the language text data processed in S3 of the previous paragraph; 20154PrN is the language text data processed in S4 of the previous paragraph; and 20154PrC is the language text data processed in S5 of the previous paragraph.

Paragraph [0066]—This Paragraph [0066] illustrates Language Text Data Displaying Software For Explorer 20654c4 stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which displays the language text data at the time a Windows Explorer like software program which displays folders and/or directories and the structures thereof is executed. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 executes Windows Explorer like software program in response to the signal input by the user of Communication Device 200 indicating to activate and execute the software program (S1). In the process of displaying the Windows Explorer like software program on

LCD 201 (FIG. 1), the following steps of S2 through S4 are implemented. Namely, CPU 211 identifies the language item ID ‘Language Item#15’ in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data ‘French#15’ indicating ‘My Network’ in French at the predetermined location in the Windows Explorer like software program (S2). CPU 211 identifies the language item ID ‘Language Item#16’ in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data ‘French#16’ indicating ‘Trash’ in French at the predetermined location in the Windows Explorer like software program (S3). CPU 211 identifies the language item ID Language Item#17’ in Language Table#3 Storage Area 20654b1c (Paragraph [0036]) and displays the corresponding language text data ‘French#17’ indicating ‘Local Disk’ in French at the predetermined location in the Windows Explorer like software program (S4).

Paragraph [0067]—This Paragraph [0067] illustrates the data displayed on LCD 201 (FIG. 1) of Communication Device 200 at the time Language Text Data Displaying Software For Explorer 20654c4 (Paragraph [0066]) is executed. In the present embodiment, 20154LD, 20154MN, and 20154Tr are displayed on LCD 201 (FIG. 1) at the time Language Text Data Displaying Software For Explorer 20654c4 is executed. In the present embodiment, 20154LD is the language text data processed in S4 of the previous paragraph; 20154MN is the language text data processed in S2 of the previous paragraph; and 20154Tr is the language text data processed in S3 of the previous paragraph.

Paragraph [0068]—<<Multiple Language Displaying Function—Utilizing German>>

Paragraph [0069]—This Paragraph [0069] illustrates Language Selecting Software 20654c1 stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which selects the language utilized to operate Communication Device 200 from a plurality of languages. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 retrieves the language type data from Language Type Data Storage Area 20654b2 (Paragraph [0038]) (S1), and Displays a list of available languages on LCD 201 (FIG. 1) (S2). In the present example, the following languages are displayed on LCD 201: English, Japanese, French, and German. A certain language is selected therefrom by utilizing Input Device 210 (FIG. 1) or via voice recognition system (S3). Assume that ‘German’ is selected in S3. CPU 211 then identifies the language table ID corresponding to the language type data in Language Type Data Storage Area 20654b2 (Paragraph [0038]), and stores the language table ID (Language Table#4) in Selected Language Table ID Storage Area 20654b4 (Paragraph [0031]) (S4).

Paragraph [0070]—This Paragraph [0070] illustrates Selected Language Displaying Software 20654c2 stored in Multiple Language Displaying Software Storage Area 20654c (Paragraph [0040]) which displays and operates with the language selected in S3 of Paragraph [0069] (i.e., German) In the present embodiment, when Communication Device 200 is powered on (S1), CPU 211 (FIG. 1) of Communication Device 200 retrieves the selected language table ID (Language Table#4) from Selected Language Table ID Storage Area 20654b4 (Paragraph [0031]) (S2). CPU 211 then identifies the storage area corresponding to the language table ID selected in S2 (Language Table#4 Storage Area 20654b1d (Paragraph [0037])) in Language Tables Storage Area 20654b1 (Paragraph [0032]) (S3). Language text data displaying process is initiated thereafter of which the details are described hereinafter (S4).

Paragraph [0071]—This Paragraph [0071] illustrates Language Text Data Displaying Software For Word Processor **20654c3a** stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which displays the language text data at the time a word processor, such as MS Word and WordPerfect is executed. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** executes a word processor in response to the signal input by the user of Communication Device **200** indicating to activate and execute the word processor (S1). In the process of displaying the word processor on LCD **201** (FIG. 1), the following steps of S2 through S8 are implemented. Namely, CPU **211** identifies the language item ID ‘Language Item#8’ in Language Table#4 Storage Area **20654b1d** (Paragraph [0037]) and displays the corresponding language text data ‘German#8’ indicating ‘File’ in German at the predetermined location in the word processor (S2). CPU **211** identifies the language item ID ‘Language Item#9’ in Language Table#4 Storage Area **20654b1d** (Paragraph [0037]) and displays the corresponding language text data ‘German#9’ indicating ‘Edit’ in German at the predetermined location in the word processor (S3). CPU **211** identifies the language item ID ‘Language Item#10’ in Language Table#4 Storage Area **20654b1d** (Paragraph [0037]) and displays the corresponding language text data ‘German#10’ indicating ‘View’ in German at the predetermined location in the word processor (S4). CPU **211** identifies the language item ID ‘Language Item#11’ in Language Table#4 Storage Area **20654b1d** (Paragraph [0037]) and displays the corresponding language text data ‘German#11’ indicating ‘Format’ in German at the predetermined location in the word processor (S5). CPU **211** identifies the language item ID ‘Language Item#12’ in Language Table#4 Storage Area **20654b1d** (Paragraph [0037]) and displays the corresponding language text data ‘German#12’ indicating ‘Tools’ in German at the predetermined location in the word processor (S6). CPU **211** identifies the language item ID ‘Language Item#13’ in Language Table#4 Storage Area **20654b1d** (Paragraph [0037]) and displays the corresponding language text data ‘German#13’ indicating ‘Window’ in German at the predetermined location in the word processor (S7). CPU **211** identifies the language item ID ‘Language Item#14’ in Language Table#4 Storage Area **20654b1d** (Paragraph [0037]) and displays the corresponding language text data ‘German#14’ indicating ‘Help’ in German at the predetermined location in the word processor (S8). Alphanumeric data is input to the word processor by utilizing Input Device **210** (FIG. 1) or via voice recognition system thereafter (S9).

Paragraph [0072]—This Paragraph [0072] illustrates the data displayed on LCD **201** (FIG. 1) of Communication Device **200** at the time Language Text Data Displaying Software For Word Processor **20654c3a** (Paragraph [0071]) is implemented. In the present embodiment, the word processor described in Paragraph [0071] is primarily composed of Menu Bar **20154MB** and Alphanumeric Data Input Area **20154ADIA** wherein the language text data described in S2 through S8 of Paragraph [0071] are displayed on Menu Bar **20154MB** and alphanumeric data are input in Alphanumeric Data Input Area **20154ADIA**. In the present embodiment, **20154MBF** is the language text data processed in S2 of the previous paragraph; **20154MBE** is the language text data processed in S3 of the previous paragraph; **20154MBV** is the language text data processed in S4 of the previous paragraph; **20154MBF** is the language text data processed in S5 of the previous paragraph; **20154MBT** is the language text data processed in S6 of the previous paragraph; **20154MBW** is the

language text data processed in S7 of the previous paragraph; and **20154MBH** is the language text data processed in S8 of the previous paragraph.

Paragraph [0073]—This Paragraph [0073] illustrates Language Text Data Displaying Software For Word Processor **20654c3b** stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which displays a prompt on LCD **201** (FIG. 1) at the time a word processor is closed. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** initiates the closing process of the word processor in response to the signal input by the user of Communication Device **200** indicating to close the word processor (S1). In the process of closing the word processor, the following steps of S2 through S5 are implemented. Namely, CPU **211** identifies the language item ID ‘Language Item#18’ in Language Table#4 Storage Area **20654b1d** (Paragraph [0037]) and displays the corresponding language text data ‘German#18’ indicating ‘Save’ in German at the predetermined location in the word processor (S2). CPU **211** identifies the language item ID ‘Language Item#19’ in Language Table#4 Storage Area **20654b1d** (Paragraph [0037]) and displays the corresponding language text data ‘German#19’ indicating ‘Yes’ in German at the predetermined location in the word processor (S3). CPU **211** identifies the language item ID ‘Language Item#20’ in Language Table#4 Storage Area **20654b1d** (Paragraph [0037]) and displays the corresponding language text data ‘German#20’ indicating ‘No’ in German at the predetermined location in the word processor (S4). CPU **211** identifies the language item ID ‘Language Item#21’ in Language Table#4 Storage Area **20654b1d** (Paragraph [0037]) and displays the corresponding language text data ‘German#21’ indicating ‘Cancel’ in German at the predetermined location in the word processor (S5). The save signal indicating to save the alphanumeric data input in S9 of Paragraph [0071] is input by utilizing Input Device **210** (FIG. 1) or via voice recognition system, assuming that the user of Communication Device **200** intends to save the data (S6), and the data are saved in a predetermined location in RAM **206** (FIG. 1) (S7). The word processor is closed thereafter (S8).

Paragraph [0074]—This Paragraph [0074] illustrates the data displayed on LCD **201** (FIG. 1) of Communication Device **200** at the time Language Text Data Displaying Software For Word Processor **20654c3b** (Paragraph [0073]) is implemented. In the present embodiment, Prompt **20154Pr** is displayed on LCD **201** (FIG. 1) at the time Language Text Data Displaying Software For Word Processor **20654c3a** (Paragraph [0071]) is closed. In the present embodiment, Prompt **20154Pr** is primarily composed of **20154PrS**, **20154PrY**, **20154PrN**, and **20154PrC**. In the present embodiment, **20154PrS** is the language text data processed in S2 of the previous paragraph; **20154PrY** is the language text data processed in S3 of the previous paragraph; **20154PrN** is the language text data processed in S4 of the previous paragraph; and **20154PrC** is the language text data processed in S5 of the previous paragraph.

Paragraph [0075]—This Paragraph [0075] illustrates Language Text Data Displaying Software For Explorer **20654c4** stored in Multiple Language Displaying Software Storage Area **20654c** (Paragraph [0040]) which displays the language text data at the time a Windows Explorer like software program which displays folders and/or directories and the structures thereof is executed. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** executes Windows Explorer like software program in response to the signal input by the user of Communication Device **200** indicating to activate and execute the software program (S1). In the process of displaying the Windows Explorer like software program on

LCD **201** (FIG. 1), the following steps of **S2** through **S4** are implemented. Namely, CPU **211** identifies the language item ID 'Language Item#**15**' in Language Table#**4** Storage Area **20654b1d** (Paragraph [0037]) and displays the corresponding language text data 'German#**15**' indicating 'My Network' in German at the predetermined location in the Windows Explorer like software program (**S2**). CPU **211** identifies the language item ID 'Language Item#**16**' in Language Table#**4** Storage Area **20654b1d** (Paragraph [0037]) and displays the corresponding language text data 'German#**16**' indicating 'Trash' in German at the predetermined location in the Windows Explorer like software program (**S3**). CPU **211** identifies the language item ID 'Language Item#**17**' in Language Table#**4** Storage Area **20654b1d** (Paragraph [0037]) and displays the corresponding language text data 'German#**17**' indicating 'Local Disk' in German at the predetermined location in the Windows Explorer like software program (**S4**).

Paragraph [0076]—This Paragraph [0076] illustrates the data displayed on LCD **201** (FIG. 1) of Communication Device **200** at the time Language Text Data Displaying Software For Explorer **20654c4** (Paragraph [0075]) is executed. In the present embodiment, **20154LD**, **20154MN**, and **20154Tr** are displayed on LCD **201** (FIG. 1) at the time Language Text Data Displaying Software For Explorer **20654c4** is executed. In the present embodiment, **20154LD** is the language text data processed in **S4** of the previous paragraph; **20154MN** is the language text data processed in **S2** of the previous paragraph; and **20154Tr** is the language text data processed in **S3** of the previous paragraph.

Paragraph [0077]—<<Multiple Language Displaying Function—Utilizing Other Languages>>

Paragraph [0078]—For the avoidance of doubt, the present function is not limited to select a language, to operate Communication Device **200**, only from the foregoing four languages of English, Japanese, French, and German. The present function is also capable to select a language from Dutch, Chinese, Arabic, Korean, Spanish, Italian, and any other languages existing in this world, in addition to the foregoing four languages.

Paragraph [0079]—<<Caller's Information Displaying Function>>

Paragraph [0080]—Paragraph [0084] through Paragraph [0129] illustrate the Caller's Information displaying function which displays the Information regarding the caller (e.g., name, phone number, email address, and home address, etc.) on LCD **201** (FIG. 1) when Communication Device **200** is utilized as a 'TV phone'.

Paragraph [0081]—Paragraph [0084] through Paragraph [0091] illustrate the data and software programs stored in RAM **206** (FIG. 1) of Caller's Device, a Communication Device **200**, utilized by the caller.

Paragraph [0082]—Paragraph [0092] through Paragraph [0099] illustrate the data and software programs stored in RAM **206** (FIG. 1) of Callee's Device, a Communication Device **200**, utilized by the callee.

Paragraph [0083]—Paragraph [0100] through Paragraph [0103] illustrate the data and software programs stored in Host H (Paragraph [0025]).

Paragraph [0084]—This Paragraph [0084] illustrates the storage area included in RAM **206** (FIG. 1) of Caller's Device. In the present embodiment, RAM **206** of Caller's Device includes Caller's Information Displaying Information Storage Area **20655a** of which the data and the software programs stored therein are described in Paragraph [0085].

Paragraph [0085]—This Paragraph [0085] illustrates the storage areas included in Caller's Information Displaying Information Storage Area **20655a** (Paragraph [0084]). In the

present embodiment, Caller's Information Displaying Information Storage Area **20655a** includes Caller's Information Displaying Data Storage Area **20655b** and Caller's Information Displaying Software Storage Area **20655c**. Caller's Information Displaying Data Storage Area **20655b** stores the data necessary to implement the present function on the side of Caller's Device, such as the ones described in Paragraph [0086] through Paragraph [0090]. Caller's Information Displaying Software Storage Area **20655c** stores the software programs necessary to implement the present function on the side of Caller's Device, such as the ones described in Paragraph [0091].

Paragraph [0086]—This Paragraph [0086] illustrates the storage areas included in Caller's Information Displaying Data Storage Area **20655b**. In the present embodiment, Caller's Information Displaying Data Storage Area **20655b** includes Caller's Audiovisual Data Storage Area **20655b1**, Callee's Audiovisual Data Storage Area **20655b2**, Caller's Personal Data Storage Area **20655b3**, Callee's Personal Data Storage Area **20655b4**, Caller's Calculated GPS Data Storage Area **20655b5**, Callee's Calculated GPS Data Storage Area **20655b6**, Caller's Map Data Storage Area **20655b7**, Callee's Map Data Storage Area **20655b8**, and Work Area **20655b9**. Caller's Audiovisual Data Storage Area **20655b1** stores the data described in Paragraph [0087]. Callee's Audiovisual Data Storage Area **20655b2** stores the data described in Paragraph [0088]. Caller's Personal Data Storage Area **20655b3** stores the data described in Paragraph [0089]. Callee's Personal Data Storage Area **20655b4** stores the data described in Paragraph [0090]. Caller's Calculated GPS Data Storage Area **20655b5** stores the caller's calculated GPS data which represents the current geographic location of Caller's Device in (x, y, z) format. Callee's Calculated GPS Data Storage Area **20655b6** stores the callee's calculated GPS data which represents the current geographic location of Callee's Device in (x, y, z) format. Caller's Map Data Storage Area **20655b7** stores the map data representing the surrounding area of the location indicated by the caller's calculated GPS data. Callee's Map Data Storage Area **20655b8** stores the map data representing the surrounding area of the location indicated by the callee's calculated GPS data. Work Area **20655b9** is a storage area utilized to perform calculation and to temporarily store data.

Paragraph [0087]—This Paragraph [0087] illustrates the storage areas included in Caller's Audiovisual Data Storage Area **20655b1** (Paragraph [0086]). In the present embodiment, Caller's Audiovisual Data Storage Area **20655b1** includes Caller's Audio Data Storage Area **20655b1a** and Caller's Visual Data Storage Area **20655b1b**. Caller's Audio Data Storage Area **20655b1a** stores the caller's audio data which represents the audio data input via Microphone **215** (FIG. 1) of Caller's Device. Caller's Visual Data Storage Area **20655b1b** stores the caller's visual data which represents the visual data input via CCD Unit **214** (FIG. 1) of Caller's Device.

Paragraph [0088]—This Paragraph [0088] illustrates the storage areas included in Callee's Audiovisual Data Storage Area **20655b2** (Paragraph [0086]). In the present embodiment, Callee's Audiovisual Data Storage Area **20655b2** includes Callee's Audio Data Storage Area **20655b2a** and Callee's Visual Data Storage Area **20655b2b**. Callee's Audio Data Storage Area **20655b2a** stores the callee's audio data which represents the audio data sent from Callee's Device. Callee's Visual Data Storage Area **20655b2b** stores the callee's visual data which represents the visual data sent from Callee's Device.

Paragraph [0089]—This Paragraph [0089] illustrates the data stored in Caller's Personal Data Storage Area **20655b3** (Paragraph [0086]). In the present embodiment, Caller's Personal Data Storage Area **20655b3** comprises two columns, i.e., 'Caller's Personal Data' and 'Permitted Caller's Personal Data Flag'. Column 'Caller's Personal Data' stores the caller's personal data which represent the personal data of the caller. Column 'Permitted Caller's Personal Data Flag' stores the permitted caller's personal data flag and each permitted caller's personal data flag represents whether the corresponding caller's personal data is permitted to be displayed on Callee's Device. The permitted caller's personal data flag is represented by either '1' or '0' wherein '1' indicates that the corresponding caller's personal data is permitted to be displayed on Callee's Device, and '0' indicates that the corresponding caller's personal data is not permitted to be displayed on Callee's Device. In the present embodiment, Caller's Personal Data Storage Area **20655b3** stores the following data: the caller's name and the corresponding permitted caller's personal data flag '1'; the caller's phone number and the corresponding permitted caller's personal data flag '1'; the caller's email address and the corresponding permitted caller's personal data flag '1'; the caller's home address and the corresponding permitted caller's personal data flag '1'; the caller's business address and the corresponding permitted caller's personal data flag '0'; the caller's title and the corresponding permitted caller's personal data flag '0'; the caller's hobby and the corresponding permitted caller's personal data flag '0'; the caller's blood type and the corresponding permitted caller's personal data flag '0'; the caller's gender and the corresponding permitted caller's personal data flag '0'; the caller's age and the corresponding permitted caller's personal data flag '0'; and caller's date of birth and the corresponding permitted caller's personal data flag '0'.

Paragraph [0090]—This Paragraph [0090] illustrates the data stored in Callee's Personal Data Storage Area **20655b4** (Paragraph [0086]). In the present embodiment, Callee's Personal Data Storage Area **20655b4** stores the callee's personal data which represent the personal data of the callee which are displayed on LCD **201** (FIG. 1) of Caller's Device. In the present embodiment, Callee's Personal Data Storage Area **20655b4** stores the callee's name and phone number.

Paragraph [0091]—This Paragraph [0091] illustrates the software programs stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0085]). In the present embodiment, Caller's Information Displaying Software Storage Area **20655c** stores Permitted Caller's Personal Data Selecting Software **20655c1**, Dialing Software **20655c2**, Caller's Device Pin-pointing Software **20655c3**, Map Data Sending/Receiving Software **20655c4**, Caller's Audiovisual Data Collecting Software **20655c5**, Caller's Information Sending/Receiving Software **20655c6**, Callee's Information Sending/Receiving Software **20655c6a**, Permitted Callee's Personal Data Displaying Software **20655c7**, Map Displaying Software **20655c8**, Callee's Audio Data Outputting Software **20655c9**, and Callee's Visual Data Displaying Software **20655c10**. Permitted Caller's Personal Data Selecting Software **20655c1** is the software program described in Paragraph [0105]. Dialing Software **20655c2** is the software program described in Paragraph [0106]. Caller's Device Pin-pointing Software **20655c3** is the software program described in Paragraph [0107] and Paragraph [0108]. Map Data Sending/Receiving Software **20655c4** is the software program described in Paragraph [0109]. Caller's Audiovisual Data Collecting Software **20655c5** is the software program described in Paragraph [0110]. Caller's Information Sending/Receiving Software **20655c6** is the software pro-

gram described in Paragraph [0111]. Callee's Information Sending/Receiving Software **20655c6a** is the software program described in Paragraph [0125]. Permitted Callee's Personal Data Displaying Software **20655c7** is the software program described in Paragraph [0126]. Map Displaying Software **20655c8** is the software program described in Paragraph [0127]. Callee's Audio Data Outputting Software **20655c9** is the software program described in Paragraph [0128]. Callee's Visual Data Displaying Software **20655c10** is the software program described in Paragraph [0129].

Paragraph [0092]—This Paragraph [0092] illustrates the storage area included in RAM **206A** (FIG. 1) of Callee's Device. In the present embodiment, RAM **206A** of Callee's Device includes Callee's Information Displaying Information Storage Area **20655aA** of which the data and the software programs stored therein are described in Paragraph [0093].

Paragraph [0093]—This Paragraph [0093] illustrates the storage areas included in Callee's Information Displaying Information Storage Area **20655aA** (Paragraph [0092]). In the present embodiment, Callee's Information Displaying Information Storage Area **20655aA** includes Callee's Information Displaying Data Storage Area **20655bA** and Callee's Information Displaying Software Storage Area **20655cA**. Callee's Information Displaying Data Storage Area **20655bA** stores the data necessary to implement the present function on the side of Callee's Device, such as the ones described in Paragraph [0094] through Paragraph [0098]. Callee's Information Displaying Software Storage Area **20655cA** stores the software programs necessary to implement the present function on the side of Callee's Device, such as the ones described in Paragraph [0099].

Paragraph [0094]—This Paragraph [0094] illustrates the storage areas included in Callee's Information Displaying Data Storage Area **20655bA**. In the present embodiment, Callee's Information Displaying Data Storage Area **20655bA** includes Caller's Audiovisual Data Storage Area **20655b1A**, Callee's Audiovisual Data Storage Area **20655b2A**, Caller's Personal Data Storage Area **20655b3A**, Callee's Personal Data Storage Area **20655b4A**, Caller's Calculated GPS Data Storage Area **20655b5A**, Callee's Calculated GPS Data Storage Area **20655b6A**, Caller's Map Data Storage Area **20655b7A**, Callee's Map Data Storage Area **20655b8A**, and Work Area **20655b9A**. Caller's Audiovisual Data Storage Area **20655b1A** stores the data described in Paragraph [0095]. Callee's Audiovisual Data Storage Area **20655b2A** stores the data described in Paragraph [0096]. Caller's Personal Data Storage Area **20655b3A** stores the data described in Paragraph [0097]. Callee's Personal Data Storage Area **20655b4A** stores the data described in Paragraph [0098]. Caller's Calculated GPS Data Storage Area **20655b5A** stores the caller's calculated GPS data which represents the current geographic location of Caller's Device in (x, y, z) format. Callee's Calculated GPS Data Storage Area **20655b6A** stores the callee's calculated GPS data which represents the current geographic location of Callee's Device in (x, y, z) format. Caller's Map Data Storage Area **20655b7A** stores the map data representing the surrounding area of the location indicated by the caller's calculated GPS data. Callee's Map Data Storage Area **20655b8A** stores the map data representing the surrounding area of the location indicated by the callee's calculated GPS data. Work Area **20655b9A** is a storage area utilized to perform calculation and to temporarily store data.

Paragraph [0095]—This Paragraph [0095] illustrates the storage areas included in Caller's Audiovisual Data Storage Area **20655b1A** (Paragraph [0094]). In the present embodiment, Caller's Audiovisual Data Storage Area **20655b1A** includes Caller's Audio Data Storage Area **20655b1aA** and

Caller's Visual Data Storage Area **20655b1bA**. Caller's Audio Data Storage Area **20655b1aA** stores the caller's audio data which represents the audio data sent from Caller's Device in a wireless fashion. Caller's Visual Data Storage Area **20655b1bA** stores the caller's visual data which represents the visual data input sent from Caller's Device in a wireless fashion.

Paragraph [0096]—This Paragraph [0096] illustrates the storage areas included in Callee's Audiovisual Data Storage Area **20655b2A** (Paragraph [0094]). In the present embodiment, Callee's Audiovisual Data Storage Area **20655b2A** includes Callee's Audio Data Storage Area **20655b2aA** and Callee's Visual Data Storage Area **20655b2bA**. Callee's Audio Data Storage Area **20655b2aA** stores the callee's audio data which represents the audio data input via Microphone **215** (FIG. 1) of Callee's Device. Callee's Visual Data Storage Area **20655b2bA** stores the callee's visual data which represents the visual data input via CCD Unit **214** (FIG. 1) of Callee's Device.

Paragraph [0097]—This Paragraph [0097] illustrates the data stored in Caller's Personal Data Storage Area **20655b3A** (Paragraph [0094]). In the present embodiment, Caller's Personal Data Storage Area **20655b3A** stores the caller's personal data which represent the personal data of the caller which are displayed on LCD **201** (FIG. 1) of Caller's Device. In the present embodiment, Caller's Personal Data Storage Area **20655b3A** stores the caller's name, phone number, email address, and home address.

Paragraph [0098]—This Paragraph [0098] illustrates the data stored in Callee's Personal Data Storage Area **20655b4A** (Paragraph [0094]). In the present embodiment, Callee's Personal Data Storage Area **20655b4A** comprises two columns, i.e., 'Callee's Personal Data' and 'Permitted Callee's Personal Data Flag'. Column 'Callee's Personal Data' stores the callee's personal data which represent the personal data of the callee. Column 'Permitted Callee's Personal Data Flag' stores the permitted callee's personal data flag and each permitted callee's personal data flag represents whether the corresponding callee's personal data is permitted to be displayed on Caller's Device. The permitted callee's personal data flag is represented by either '1' or '0' wherein '1' indicates that the corresponding callee's personal data is permitted to be displayed on Caller's Device, and '0' indicates that the corresponding callee's personal data is not permitted to be displayed on Caller's Device. In the present embodiment, Callee's Personal Data Storage Area **20655b4A** stores the following data: callee's name and the corresponding permitted callee's personal data flag '1'; the callee's phone number and the corresponding permitted callee's personal data flag '1'; the callee's email address and the corresponding permitted caller's personal data flag '0'; the callee's home address and the corresponding permitted callee's personal data flag '0'; the callee's business address and the corresponding permitted callee's personal data flag '0'; the callee's title and the corresponding permitted callee's personal data flag '0'; the callee's hobby and the corresponding permitted callee's personal data flag '0'; the callee's blood type and the corresponding permitted callee's personal data flag '0'; the callee's gender and the corresponding permitted callee's personal data flag '0'; the callee's age and the corresponding permitted callee's personal data flag '0'; and callee's date of birth and the corresponding permitted callee's personal data flag '0'.

Paragraph [0099]—This Paragraph [0099] illustrates the software programs stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0093]). In the present embodiment, Callee's Information Displaying Software Storage Area **20655cA** stores Permitted Callee's Per-

sonal Data Selecting Software **20655c1A**, Dialing Software **20655c2A**, Callee's Device Pin-pointing Software **20655c3A**, Map Data Sending/Receiving Software **20655c4A**, Callee's Audiovisual Data Collecting Software **20655c5A**, Callee's Information Sending/Receiving Software **20655c6A**, Caller's Information Sending/Receiving Software **20655c6aA**, Permitted Caller's Personal Data Displaying Software **20655c7A**, Map Displaying Software **20655c8A**, Caller's Audio Data Outputting Software **20655c9A**, and Caller's Visual Data Displaying Software **20655c10A**. Permitted Callee's Personal Data Selecting Software **20655c1A** is the software program described in Paragraph [0118]. Dialing Software **20655c2A** is the software program described in Paragraph [0119]. Callee's Device Pin-pointing Software **20655c3A** is the software program described in Paragraph [0120] and Paragraph [0121]. Map Data Sending/Receiving Software **20655c4A** is the software program described in Paragraph [0122]. Callee's Audiovisual Data Collecting Software **20655c5A** is the software program described in Paragraph [0123]. Callee's Information Sending/Receiving Software **20655c6A** is the software program described in Paragraph [0124]. Caller's Information Sending/Receiving Software **20655c6aA** is the software program described in Paragraph [0112]. Permitted Caller's Personal Data Displaying Software **20655c7A** is the software program described in Paragraph [0113]. Map Displaying Software **20655c8A** is the software program described in Paragraph [0114]. Caller's Audio Data Outputting Software **20655c9A** is the software program described in Paragraph [0115]. Caller's Visual Data Displaying Software **20655c10A** is the software program described in Paragraph [0116].

Paragraph [0100]—This Paragraph [0100] illustrates the storage area included in Host H (Paragraph [0025]). In the present embodiment, Host H includes Caller/Callee Information Storage Area **H55a** of which the data and the software programs stored therein are described in Paragraph [0101].

Paragraph [0101]—This Paragraph [0101] illustrates the storage areas included in Caller/Callee Information Storage Area **H55a**. In the present embodiment, Caller/Callee Information Storage Area **H55a** includes Caller/Callee Data Storage Area **H55b** and Caller/Callee Software Storage Area **H55c**. Caller/Callee Data Storage Area **H55b** stores the data necessary to implement the present function on the side of Host H (Paragraph [0025]), such as the ones described in Paragraph [0102]. Caller/Callee Software Storage Area **H55c** stores the software programs necessary to implement the present function on the side of Host H, such as the ones described in Paragraph [0103].

Paragraph [0102]—This Paragraph [0102] illustrates the storage areas included in Caller/Callee Data Storage Area **H55b**. In the present embodiment, Caller/Callee Data Storage Area **H55b** includes Caller's Information Storage Area **H55b1**, Callee's Information Storage Area **H55b2**, Map Data Storage Area **H55b3**, Work Area **H55b4**, Caller's Calculated GPS Data Storage Area **H55b5**, and Callee's Calculated GPS Data Storage Area **H55b6**. Caller's Information Storage Area **H55b1** stores the Caller's Information received from Caller's Device. Callee's Information Storage Area **H55b2** stores the Callee's Information received from Callee's Device. Map Data Storage Area **H55b3** stores the map data received from Caller's Device and Callee's Device. Work Area **H55b4** is a storage area utilized to perform calculation and to temporarily store data. Caller's Calculated GPS Data Storage Area **H55b5** stores the caller's calculated GPS data. Callee's Calculated GPS Data Storage Area **H55b6** stores the callee's calculated GPS data.

Paragraph [0103]—This Paragraph [0103] illustrates the software programs stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]). In the present embodiment, Caller/Callee Software Storage Area **H55c** stores Dialing Software **H55c2**, Caller's Device Pin-pointing Software **H55c3**, Callee's Device Pin-pointing Software **H55c3a**, Map Data Sending/Receiving Software **H55c4**, Caller's Information Sending/Receiving Software **H55c6**, and Callee's Information Sending/Receiving Software **H55c6a**. Dialing Software **H55c2** is the software program described in Paragraph [0106] and Paragraph [0119]. Caller's Device Pin-pointing Software **H55c3** is the software program described in Paragraph [0107]. Callee's Device Pin-pointing Software **H55c3a** is the software program described in Paragraph [0120]. Map Data Sending/Receiving Software **H55c4** is the software program described in Paragraph [0109] and Paragraph [0122]. Caller's Information Sending/Receiving Software **H55c6** is the software program described in Paragraph [0111]. Callee's Information Sending/Receiving Software **H55c6a** is the software program described in Paragraph [0124] and Paragraph [0125].

Paragraph [0104]—Paragraph [0105] through Paragraph [0116] primarily illustrate the sequence to output the Caller's Information (which is defined hereinafter) from Callee's Device.

Paragraph [0105]—This Paragraph [0105] illustrates Permitted Caller's Personal Data Selecting Software **20655c1** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which selects the permitted caller's personal data to be displayed on LCD **201** (FIG. 1) of Callee's Device. In the present embodiment, CPU **211** (FIG. 1) of Caller's Device retrieves all of the caller's personal data from Caller's Personal Data Storage Area **20655b3** (Paragraph [0089]) (S1). CPU **211** then displays a list of caller's personal data on LCD **201** (FIG. 1) (S2). The caller selects, by utilizing Input Device **210** (FIG. 1) or via voice recognition system, the caller's personal data permitted to be displayed on Callee's Device (S3). The permitted caller's personal data flag of the data selected in S3 is registered as '1' (S4).

Paragraph [0106]—This Paragraph [0106] illustrates Dialing Software **H55c2** stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]), Dialing Software **20655c2** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, and Dialing Software **20655c2A** stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0099]) of Callee's Device, which enables to connect between Caller's Device and Callee's Device via Host H (Paragraph [0025]) in a wireless fashion. In the present embodiment, a connection is established between Caller's Device and Host H (S1). Next, a connection is established between Host H and Callee's Device (S2). As a result, Caller's Device and Callee's Device are able to exchange audiovisual data, text data, and various types of data with each other. The connection is maintained until Caller's Device, Host H, or Callee's Device terminates the connection.

Paragraph [0107]—This Paragraph [0107] illustrates Caller's Device Pin-pointing Software **H55c3** (Paragraph [0103]) stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]) and Caller's Device Pin-pointing Software **20655c3** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which identifies the current geographic location of Caller's Device. In the present embodiment, CPU **211** (FIG. 1) of Caller's Device collects

the GPS raw data from the near base stations (S1). CPU **211** sends the raw GPS data to Host H (S2). Upon receiving the raw GPS data (S3), Host H produces the caller's calculated GPS data by referring to the raw GPS data (S4). Host H stores the caller's calculated GPS data in Caller's Calculated GPS Data Storage Area **H55b5** (Paragraph [0102]) (S5). Host H then retrieves the caller's calculated GPS data from Caller's Calculated GPS Data Storage Area **H55b5** (Paragraph [0102]) (S6), and sends the data to Caller's Device (S7). Upon receiving the caller's calculated GPS data from Host H (S8), CPU **211** stores the data in Caller's Calculated GPS Data Storage Area **20655b5** (Paragraph [0086]) (S9). Here, the GPS raw data are the primitive data utilized to produce the caller's calculated GPS data, and the caller's calculated GPS data is the data representing the location of Caller's Device in (x, y, z) format. The sequence described in the present paragraph is repeated periodically.

Paragraph [0108]—This Paragraph [0108] illustrates another embodiment of the sequence described in Paragraph [0107] in which the entire process is performed solely by Caller's Device Pin-pointing Software **20655c3** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device. In the present embodiment, CPU **211** (FIG. 1) of Caller's Device collects the raw GPS data from the near base stations (S1). CPU **211** then produces the caller's calculated GPS data by referring to the raw GPS data (S2), and stores the caller's calculated GPS data in Caller's Calculated GPS Data Storage Area **20655b5** (Paragraph [0086]) (S3). The sequence described in the present paragraph is repeated periodically.

Paragraph [0109]—This Paragraph [0109] illustrates Map Data Sending/Receiving Software **H55c4** stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]) and Map Data Sending/Receiving Software **20655c4** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which sends and receives the map data. In the present embodiment, CPU **211** (FIG. 1) of Caller's Device retrieves the caller's calculated GPS data from Caller's Calculated GPS Data Storage Area **20655b5** (Paragraph [0086]) (S1), and sends the data to Host H (S2). Upon receiving the calculated GPS data from Caller's Device (S3), Host H identifies the map data in Map Data Storage Area **H55b3** (Paragraph [0102]) (S4). Here, the map data represents the surrounding area of the location indicated by the caller's calculated GPS data. Host H retrieves the map data from Map Data Storage Area **H55b3** (Paragraph [0102]) (S5), and sends the data to Caller's Device (S6). Upon receiving the map data from Host H (S7), Caller's Device stores the data in Caller's Map Data Storage Area **20655b7** (Paragraph [0086]) (S8). The sequence described in the present paragraph is repeated periodically.

Paragraph [0110]—This Paragraph [0110] illustrates Caller's Audiovisual Data Collecting Software **20655c5** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which collects the audiovisual data of the caller to be sent to Callee's Device via Antenna **218** (FIG. 1) thereof. CPU **211** (FIG. 1) of Caller's Device retrieves the caller's audiovisual data from CCD Unit **214** and Microphone **215** (S1). CPU **211** then stores the caller's audio data in Caller's Audio Data Storage Area **20655b1a** (Paragraph [0087]) (S2), and the caller's visual data in Caller's Visual Data Storage Area **20655b1b** (Paragraph [0087]) (S3). The sequence described in the present paragraph is repeated periodically.

Paragraph [0111]—This Paragraph [0111] illustrates Caller's Information Sending/Receiving Software **H55c6** stored

in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]) and Caller's Information Sending/Receiving Software **20655c6** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which sends and receives the Caller's Information (which is defined hereinafter) between Caller's Device and Host H. In the present embodiment, CPU **211** (FIG. 1) of Caller's Device retrieves the permitted caller's personal data from Caller's Personal Data Storage Area **20655b3** (Paragraph [0089]) (S1). CPU **211** retrieves the caller's calculated GPS data from Caller's Calculated GPS Data Storage Area **20655b5** (Paragraph [0086]) (S2). CPU **211** retrieves the map data from Caller's Map Data Storage Area **20655b7** (Paragraph [0086]) (S3). CPU **211** retrieves the caller's audio data from Caller's Audio Data Storage Area **20655b1a** (Paragraph [0087]) (S4). CPU **211** retrieves the caller's visual data from Caller's Visual Data Storage Area **20655b1b** (Paragraph [0087]) (S5). CPU **211** then sends the data retrieved in S1 through S5 (collectively defined as the 'Caller's Information' hereinafter) to Host H (S6). Upon receiving the Caller's Information from Caller's Device (S7), Host H stores the Caller's Information in Caller's Information Storage Area **H55b1** (Paragraph [0102]) (S8). The sequence described in the present paragraph is repeated periodically.

Paragraph [0112]—This Paragraph [0112] illustrates Caller's Information Sending/Receiving Software **H55c6** stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]) and Caller's Information Sending/Receiving Software **20655c6aA** (Paragraph [0099]) stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which sends and receives the Caller's Information between Host H and Callee's Device. In the present embodiment, Host H retrieves the Caller's Information from Caller's Information Storage Area **H55b1** (Paragraph [0102]) (S1), and sends the Caller's Information to Callee's Device (S2). CPU **211** (FIG. 1) of Callee's Device receives the Caller's Information from Host H (S3). CPU **211** stores the permitted caller's personal data in Caller's Personal Data Storage Area **20655b3A** (Paragraph [0097]) (S4). CPU **211** stores the caller's calculated GPS data in Caller's Calculated GPS Data Storage Area **20655b5A** (Paragraph [0094]) (S5). CPU **211** stores the map data in Caller's Map Data Storage Area **20655b7A** (Paragraph [0094]) (S6). CPU **211** stores the caller's audio data in Caller's Audio Data Storage Area **20655b1aA** (Paragraph [0095]) (S7). CPU **211** stores the caller's visual data in Caller's Visual Data Storage Area **20655b1bA** (Paragraph [0095]) (S8). The sequence described in the present paragraph is repeated periodically.

Paragraph [0113]—This Paragraph [0113] illustrates Permitted Caller's Personal Data Displaying Software **20655c7A** stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0099]) of Callee's Device, which displays the permitted caller's personal data on LCD **201** (FIG. 1) of Callee's Device. In the present embodiment, CPU **211** (FIG. 1) of Callee's Device retrieves the permitted caller's personal data from Caller's Personal Data Storage Area **20655b3A** (Paragraph [0097]) (S1). CPU **211** then displays the permitted caller's personal data on LCD **201** (FIG. 1) (S2). The sequence described in the present paragraph is repeated periodically.

Paragraph [0114]—This Paragraph [0114] illustrates Map Displaying Software **20655c8A** stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0099]) of Callee's Device, which displays the map representing the surrounding area of the location indicated by the

caller's calculated GPS data. In the present embodiment, CPU **211** (FIG. 1) of Callee's Device retrieves the caller's calculated GPS data from Caller's Calculated GPS Data Storage Area **20655b5A** (Paragraph [0094]) (S1). CPU **211** then retrieves the map data from Caller's Map Data Storage Area **20655b7A** (Paragraph [0094]) (S2), and arranges on the map data the caller's current location icon in accordance with the caller's calculated GPS data (S3). Here, the caller's current location icon is an icon which represents the location of Caller's Device in the map data. The map with the caller's current location icon is displayed on LCD **201** (FIG. 1) (S4). The sequence described in the present paragraph is repeated periodically.

Paragraph [0115]—This Paragraph [0115] illustrates Caller's Audio Data Outputting Software **20655c9A** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which outputs the caller's audio data from Speaker **216** (FIG. 1) of Callee's Device. In the present embodiment, CPU **211** (FIG. 1) of Callee's Device retrieves the caller's audio data from Caller's Audio Data Storage Area **20655b1aA** (Paragraph [0095]) (S1). CPU **211** then outputs the caller's audio data from Speaker **216** (FIG. 1) (S2). The sequence described in the present paragraph is repeated periodically.

Paragraph [0116]—This Paragraph [0116] illustrates Caller's Visual Data Displaying Software **20655c10A** stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0099]) of Callee's Device, which displays the caller's visual data on LCD **201** (FIG. 1) of Callee's Device. In the present embodiment, CPU **211** (FIG. 1) of Callee's Device retrieves the caller's visual data from Caller's Visual Data Storage Area **20655b1bA** (Paragraph [0095]) (S1). CPU **211** then displays the caller's visual data on LCD **201** (FIG. 1) (S2). The sequence described in the present paragraph is repeated periodically.

Paragraph [0117]—Paragraph [0118] through Paragraph [0129] primarily illustrate the sequence to output the Callee's Information (which is defined hereinafter) from Caller's Device.

Paragraph [0118]—This Paragraph [0118] illustrates Permitted Callee's Personal Data Selecting Software **20655c1A** stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0099]) of Callee's Device, which selects the permitted callee's personal data to be displayed on LCD **201** (FIG. 1) of Caller's Device. In the present embodiment, CPU **211** (FIG. 1) of Callee's Device retrieves all of the callee's personal data from Callee's Personal Data Storage Area **20655b4A** (Paragraph [0098]) (S1). CPU **211** then displays a list of callee's personal data on LCD **201** (FIG. 1) (S2). The callee selects, by utilizing Input Device **210** (FIG. 1) or via voice recognition system, the callee's personal data permitted to be displayed on Caller's Device (S3). The permitted callee's personal data flag of the data selected in S3 is registered as '1' (S4).

Paragraph [0119]—This Paragraph [0119] illustrates Dialing Software **H55c2** stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]), Dialing Software **20655c2A** stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0099]) of Callee's Device, and Dialing Software **20655c2** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which enables to connect between Callee's Device and Caller's Device via Host H (Paragraph [0025]) in a wireless fashion. In the present embodiment, a connection is established between Callee's Device and Host H (S1). Next, a connection is established between Host H and Caller's Device (S2). As a

result, Callee's Device and Caller's Device are able to exchange audiovisual data, text data, and various types of data with each other. The sequence described in the present paragraph is not necessarily implemented if the connection between Caller's Device and Callee's Device is established as described in Paragraph [0106]. The sequence described in the present paragraph may be implemented if the connection is accidentally terminated by Callee's Device and the connection process is initiated by Callee's Device.

Paragraph [0120]—This Paragraph [0120] illustrates Callee's Device Pin-pointing Software **H55c3a** stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]) and Callee's Device Pin-pointing Software **20655c3A** stored in Callee's Information Displaying Software Storage Area **20655cA** of Callee's Device, which identifies the current geographic location of Callee's Device. In the present embodiment, CPU **211** (FIG. 1) of Callee's Device collects the GPS raw data from the near base stations (S1). CPU **211** sends the raw GPS data to Host H (S2). Upon receiving the raw GPS data (S3), Host H produces the callee's calculated GPS data by referring to the raw GPS data (S4). Host H stores the callee's calculated GPS data in Callee's Calculated GPS Data Storage Area **H55b6** (Paragraph [0102]) (S5). Host H then retrieves the callee's calculated GPS data from Callee's Calculated GPS Data Storage Area **H55b6** (Paragraph [0102]) (S6), and sends the data to Callee's Device (S7). Upon receiving the callee's calculated GPS data from Host H (S8), CPU **211** stores the data in Callee's Calculated GPS Data Storage Area **20655b6A** (Paragraph [0094]) (S9). Here, the GPS raw data are the primitive data utilized to produce the callee's calculated GPS data, and the callee's calculated GPS data is the data representing the location of Callee's Device in (x, y, z) format. The sequence described in the present paragraph is repeated periodically.

Paragraph [0121]—This Paragraph [0121] illustrates another embodiment of the sequence described in Paragraph [0120] in which the entire process is performed solely by Callee's Device Pin-pointing Software **20655c3A** stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0099]) of Callee's Device. In the present embodiment, CPU **211** (FIG. 1) of Callee's Device collects the raw GPS data from the near base stations (S1). CPU **211** then produces the callee's calculated GPS data by referring to the raw GPS data (S2), and stores the callee's calculated GPS data in Callee's Calculated GPS Data Storage Area **20655b6A** (Paragraph [0094]) (S3). The sequence described in the present paragraph is repeated periodically.

Paragraph [0122]—This Paragraph [0122] illustrates Map Data Sending/Receiving Software **H55c4** stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]) and Map Data Sending/Receiving Software **20655c4A** stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0099]) of Callee's Device, which sends and receives the map data. In the present embodiment, CPU **211** (FIG. 1) of Callee's Device retrieves the callee's calculated GPS data from Callee's Calculated GPS Data Storage Area **20655b6A** (Paragraph [0094]) (S1), and sends the data to Host H (S2). Upon receiving the calculated GPS data from Callee's Device (S3), Host H identifies the map data in Map Data Storage Area **H55b3** (Paragraph [0102]) (S4). Here, the map data represents the surrounding area of the location indicated by the callee's calculated GPS data. Host H retrieves the map data from Map Data Storage Area **H55b3** (Paragraph [0102]) (S5), and sends the data to Callee's Device (S6). Upon receiving the map data from Host H (S7), Callee's Device stores the data in Callee's Map Data Storage Area **20655b8A** (Para-

graph [0094]) (S8). The sequence described in the present paragraph is repeated periodically.

Paragraph [0123]—This Paragraph [0123] illustrates Callee's Audiovisual Data Collecting Software **20655c5A** stored in Callee's Information Displaying Software Storage Area **20655cA** (Paragraph [0099]) of Callee's Device, which collects the audiovisual data of the callee to be sent to Caller's Device via Antenna **218** (FIG. 1) thereof. CPU **211** (FIG. 1) of Callee's Device retrieves the callee's audiovisual data from CCD Unit **214** and Microphone **215** (S1). CPU **211** then stores the callee's audio data in Callee's Audio Data Storage Area **20655b2aA** (Paragraph [0096]) (S2), and the callee's visual data in Callee's Visual Data Storage Area **20655b2bA** (Paragraph [0096]) (S3). The sequence described in the present paragraph is repeated periodically.

Paragraph [0124]—This Paragraph [0124] illustrates Callee's Information Sending/Receiving Software **H55c6a** (Paragraph [0103]) stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]) and Callee's Information Sending/Receiving Software **20655c6A** (Paragraph [0099]) stored in Callee's Information Displaying Software Storage Area **20655cA** of Callee's Device, which sends and receives the Callee's Information (which is defined hereinafter) between Callee's Device and Host H. In the present embodiment, CPU **211** (FIG. 1) of Callee's Device retrieves the permitted callee's personal data from Callee's Personal Data Storage Area **20655b4A** (Paragraph [0098]) (S1). CPU **211** retrieves the callee's calculated GPS data from Callee's Calculated GPS Data Storage Area **20655b6A** (Paragraph [0094]) (S2). CPU **211** retrieves the map data from Callee's Map Data Storage Area **20655b8A** (Paragraph [0094]) (S3). CPU **211** retrieves the callee's audio data from Callee's Audio Data Storage Area **20655b2aA** (Paragraph [0096]) (S4). CPU **211** retrieves the callee's visual data from Callee's Visual Data Storage Area **20655b2bA** (Paragraph [0096]) (S5). CPU **211** then sends the data retrieved in S1 through S5 (collectively defined as the 'Callee's Information' hereinafter) to Host H (S6). Upon receiving the Callee's Information from Callee's Device (S7), Host H stores the Callee's Information in Callee's Information Storage Area **H55b2** (Paragraph [0102]) (S8). The sequence described in the present paragraph is repeated periodically.

Paragraph [0125]—This Paragraph [0125] illustrates Callee's Information Sending/Receiving Software **H55c6a** stored in Caller/Callee Software Storage Area **H55c** (Paragraph [0103]) of Host H (Paragraph [0025]) and Callee's Information Sending/Receiving Software **20655c6a** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which sends and receives the Callee's Information between Host H and Caller's Device. In the present embodiment, Host H retrieves the Callee's Information from Callee's Information Storage Area **H55b2** (Paragraph [0102]) (S1), and sends the Callee's Information to Caller's Device (S2). CPU **211** (FIG. 1) of Caller's Device receives the Callee's Information from Host H (S3). CPU **211** stores the permitted callee's personal data in Callee's Personal Data Storage Area **20655b4** (Paragraph [0090]) (S4). CPU **211** stores the callee's calculated GPS data in Callee's Calculated GPS Data Storage Area **20655b6** (Paragraph [0086]) (S5). CPU **211** stores the map data in Callee's Map Data Storage Area **20655b8** (Paragraph [0086]) (S6). CPU **211** stores the callee's audio data in Callee's Audio Data Storage Area **20655b2a** (Paragraph [0088]) (S7). CPU **211** stores the callee's visual data in Callee's Visual Data

Storage Area **20655b2b** (Paragraph [0088]) (S8). The sequence described in the present paragraph is repeated periodically.

Paragraph [0126]—This Paragraph [0126] illustrates Permitted Callee's Personal Data Displaying Software **20655c7** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which displays the permitted callee's personal data on LCD **201** (FIG. 1) of Caller's Device. In the present embodiment, CPU **211** (FIG. 1) of Caller's Device retrieves the permitted callee's personal data from Callee's Personal Data Storage Area **20655b4** (Paragraph [0090]) (S1). CPU **211** then displays the permitted callee's personal data on LCD **201** (FIG. 1) (S2). The sequence described in the present paragraph is repeated periodically.

Paragraph [0127]—This Paragraph [0127] illustrates Map Displaying Software **20655c8** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which displays the map representing the surrounding area of the location indicated by the callee's calculated GPS data. In the present embodiment, CPU **211** (FIG. 1) of Caller's Device retrieves the callee's calculated GPS data from Callee's Calculated GPS Data Storage Area **20655b6** (Paragraph [0086]) (S1). CPU **211** then retrieves the map data from Callee's Map Data Storage Area **20655b8** (Paragraph [0086]) (S2), and arranges on the map data the callee's current location icon in accordance with the callee's calculated GPS data (S3). Here, the callee's current location icon is an icon which represents the location of Callee's Device in the map data. The map with the callee's current location icon is displayed on LCD **201** (FIG. 1) (S4). The sequence described in the present paragraph is repeated periodically.

Paragraph [0128]—This Paragraph [0128] illustrates Callee's Audio Data Outputting Software **20655c9** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which outputs the callee's audio data from Speaker **216** (FIG. 1) of Caller's Device. In the present embodiment, CPU **211** (FIG. 1) of Caller's Device retrieves the callee's audio data from Callee's Audio Data Storage Area **20655b2a** (Paragraph [0088]) (S1). CPU **211** then outputs the caller's audio data from Speaker **216** (FIG. 1) (S2). The sequence described in the present paragraph is repeated periodically.

Paragraph [0129]—This Paragraph [0129] illustrates Callee's Visual Data Displaying Software **20655c10** stored in Caller's Information Displaying Software Storage Area **20655c** (Paragraph [0091]) of Caller's Device, which displays the callee's visual data on LCD **201** (FIG. 1) of Caller's Device. In the present embodiment, CPU **211** (FIG. 1) of Caller's Device retrieves the callee's visual data from Callee's Visual Data Storage Area **20655b2b** (Paragraph [0088]) (S1). CPU **211** then displays the callee's visual data on LCD **201** (FIG. 1) (S2). The sequence described in the present paragraph is repeated periodically.

Paragraph [0130]—<<Communication Device Remote Controlling Function (by Phone)>>

Paragraph [0131]—Paragraph [0132] through Paragraph [0155] illustrate the communication device remote controlling function (by phone) which enables the user of Communication Device **200** to remotely control Communication Device **200** via conventional telephone Phone PH (not shown).

Paragraph [0132]—This Paragraph [0132] illustrates the storage areas included in Host H (Paragraph [0025]). In the present embodiment, Host H includes Communication Device Controlling Information Storage Area **H57a** of which

the data and the software programs stored therein are described in Paragraph [0133].

Paragraph [0133]—This Paragraph [0133] illustrates the storage areas included in Communication Device Controlling Information Storage Area **H57a** (Paragraph [0132]). In the present embodiment, Communication Device Controlling Information Storage Area **H57a** includes Communication Device Controlling Data Storage Area **H57b** and Communication Device Controlling Software Storage Area **H57c**. Communication Device Controlling Data Storage Area **H57b** stores the data necessary to implement the present function on the side of Host H (Paragraph [0025]), such as the ones described in Paragraph [0134] through Paragraph [0137]. Communication Device Controlling Software Storage Area **H57c** stores the software programs necessary to implement the present function on the side of Host H, such as the ones described in Paragraph [0138].

Paragraph [0134]—This Paragraph [0134] illustrates the storage areas included in Communication Device Controlling Data Storage Area **H57b** (Paragraph [0133]). In the present embodiment, Communication Device Controlling Data Storage Area **H57b** includes Password Data Storage Area **H57b1**, Phone Number Data Storage Area **H57b2**, Audio Data Storage Area **H57b3**, and Work Area **H57b4**. Password Data Storage Area **H57b1** stores the data described in Paragraph [0135]. Phone Number Data Storage Area **H57b2** stores the data described in Paragraph [0136]. Audio Data Storage Area **H57b3** stores the data described in Paragraph [0137]. Work Area **H57b4** is utilized as a work area to perform calculation and to temporarily store data.

Paragraph [0135]—This Paragraph [0135] illustrates the data stored in Password Data Storage Area **H57b1** (Paragraph [0134]). In the present embodiment, Password Data Storage Area **H57b1** comprises two columns, i.e., 'User ID' and 'Password Data'. Column 'User ID' stores the user IDs, and each user ID represents the identification of the user of Communication Device **200**. Column 'Password Data' stores the password data, and each password data represents the password set by the user of the corresponding user ID. Here, each password data is composed of alphanumeric data. In the present embodiment, Password Data Storage Area **H57b1** stores the following data: the user ID 'User#1' and the corresponding password data 'Password Data#1'; the user ID 'User#2' and the corresponding password data 'Password Data#2'; the user ID 'User#3' and the corresponding password data 'Password Data#3'; the user ID 'User#4' and the corresponding password data 'Password Data#4'; and the user ID 'User#5' and the corresponding password data 'Password Data#5'.

Paragraph [0136]—This Paragraph [0136] illustrates the data stored in Phone Number Data Storage Area **H57b2** (Paragraph [0134]). In the present embodiment, Phone Number Data Storage Area **H57b2** comprises two columns, i.e., 'User ID' and 'Phone Number Data'. Column 'User ID' stores the user IDs, and each user ID represents the identification of the user of Communication Device **200**. Column 'Phone Number Data' stores the phone number data, and each phone number data represents the phone number of the user of the corresponding user ID. Here, each phone number data is composed of numeric data. In the present embodiment, Phone Number Data Storage Area **H57b2** stores the following data: the user ID 'User#1' and the corresponding phone number data 'Phone Number Data#1'; the user ID 'User#2' and the corresponding phone number data 'Phone Number Data#2'; the user ID 'User#3' and the corresponding phone number data 'Phone Number Data#3'; the user ID 'User#4' and the corre-

sponding phone number data 'Phone Number Data#4'; and the user ID 'User#5' and the corresponding phone number data 'Phone Number Data#5'.

Paragraph [0137]—This Paragraph [0137] illustrates the data stored in Audio Data Storage Area H57b3 (Paragraph [0134]). In the present embodiment, Audio Data Storage Area H57b3 comprises two columns, i.e., 'Audio ID' and 'Audio Data'. Column 'Audio ID' stores the audio IDs, and each audio ID represents the identification of the audio data stored in column 'Audio Data'. Column 'Audio Data' stores the audio data, and each audio data represents a message output from a conventional telephone Phone PH. In the present embodiment, Audio Data Storage Area H57b3 stores the following data: the audio ID 'Audio#0' and the corresponding audio data 'Audio Data#0'; the audio ID 'Audio#1' and the corresponding audio data 'Audio Data#1'; the audio ID 'Audio#2' and the corresponding audio data 'Audio Data#2'; the audio ID 'Audio#3' and the corresponding audio data 'Audio Data#3'; the audio ID 'Audio#4' and the corresponding audio data 'Audio Data#4'; the audio ID 'Audio#5' and the corresponding audio data 'Audio Data#5'; and the audio ID 'Audio#6' and the corresponding audio data 'Audio Data#6'. 'Audio Data#0' represents the message: 'To deactivate manner mode, press 1. To deactivate manner mode and ring your mobile phone, press 2. To ring your mobile phone, press 3. To change password of your mobile phone, press 4. To lock your mobile phone, press 5. To power off your mobile phone, press 6.' 'Audio Data#1' represents the message: 'The manner mode has been deactivated.' 'Audio Data#2' represents the message: 'The manner mode has been deactivated and your mobile phone has been rung.' 'Audio Data#3' represents the message: 'Your mobile phone has been rung.' 'Audio Data#4' represents the message: 'The password of your mobile phone has been changed.' 'Audio Data#5' represents the message: 'Your mobile phone has been changed.' 'Audio Data#6' represents the message: 'Your mobile phone has been power-offed.' The foregoing audio data may be recorded in either male's voice or female's voice.

Paragraph [0138]—This Paragraph [0138] illustrates the software programs stored in Communication Device Controlling Software Storage Area H57c (Paragraph [0133]). In the present embodiment, Communication Device Controlling Software Storage Area H57c stores User Authenticating Software H57c1, Menu Introducing Software H57c2, Line Connecting Software H57c3, Manner Mode Deactivating Software H57c4, Manner Mode Deactivating & Ringing Software H57c5, Ringing Software H57c6, Password Changing Software H57c7, Device Locking Software H57c8, and Power Off Software H57c9. User Authenticating Software H57c1 is the software program described in Paragraph [0147]. Menu Introducing Software H57c2 is the software program described in Paragraph [0148]. Line Connecting Software H57c3 is the software program described in Paragraph [0149]. Manner Mode Deactivating Software H57c4 is the software program described in Paragraph [0150]. Manner Mode Deactivating & Ringing Software H57c5 is the software program described in Paragraph [0151]. Ringing Software H57c6 is the software program described in Paragraph [0152]. Password Changing Software H57c7 is the software program described in Paragraph [0153]. Device Locking Software H57c8 is the software program described in Paragraph [0154]. Power Off Software H57c9 is the software program described in Paragraph [0155].

Paragraph [0139]—This Paragraph [0139] illustrates the storage area included in RAM 206 (FIG. 1). In the present embodiment, RAM 206 includes Communication Device

Controlling Information Storage Area 20657a of which the data and the software programs stored therein are described in Paragraph [0140].

Paragraph [0140]—This Paragraph [0140] illustrates the storage areas included in Communication Device Controlling Information Storage Area 20657a (Paragraph [0139]). In the present embodiment, Communication Device Controlling Information Storage Area 20657a includes Communication Device Controlling Data Storage Area 20657b and Communication Device Controlling Software Storage Area 20657c. Communication Device Controlling Data Storage Area 20657b stores the data necessary to implement the present function on the side of Communication Device 200, such as the ones described in Paragraph [0142] through Paragraph [0144]. Communication Device Controlling Software Storage Area 20657c stores the software programs necessary to implement the present function on the side of Communication Device 200, such as the ones described in Paragraph [0145].

Paragraph [0141]—The data and/or the software programs stored in Communication Device Controlling Information Storage Area 20657a (Paragraph [0140]) may be downloaded from Host H (Paragraph [0025]).

Paragraph [0142]—This Paragraph [0142] illustrates the storage areas included in Communication Device Controlling Data Storage Area 20657b (Paragraph [0140]). In the present embodiment, Communication Device Controlling Data Storage Area 20657b includes Password Data Storage Area 20657b1 and Work Area 20657b4. Password Data Storage Area 20657b1 stores the data described in Paragraph [0143]. Work Area 20657b4 is utilized as a work area to perform calculation and to temporarily store data.

Paragraph [0143]—This Paragraph [0143] illustrates the data stored in Password Data Storage Area 20657b1 (Paragraph [0142]). In the present embodiment, Password Data Storage Area 20657b1 comprises two columns, i.e., 'User ID' and 'Password Data'. Column 'User ID' stores the user ID which represents the identification of the user of Communication Device 200. Column 'Password Data' stores the password data set by the user of Communication Device 200. Here, the password data is composed of alphanumeric data. Assuming that the user ID of Communication Device 200 is 'User#1'. In the present embodiment, Password Data Storage Area H57b1 stores the following data: the user ID 'User#1' and the corresponding password data 'Password Data#1'.

Paragraph [0144]—This Paragraph [0144] illustrates the data stored in Phone Number Data Storage Area 20657b2 (Paragraph [0142]). In the present embodiment, Phone Number Data Storage Area 20657b2 comprises two columns, i.e., 'User ID' and 'Phone Number Data'. Column 'User ID' stores the user ID of the user of Communication Device 200. Column 'Phone Number Data' stores the phone number data which represents the phone number of Communication Device 200. Here, the phone number data is composed of numeric data. In the present embodiment, Phone Number Data Storage Area H57b2 stores the following data: the user ID 'User#1' and the corresponding phone number data 'Phone Number Data#1'.

Paragraph [0145]—This Paragraph [0145] illustrates the software programs stored in Communication Device Controlling Software Storage Area 20657c (Paragraph [0140]). In the present embodiment, Communication Device Controlling Software Storage Area 20657c stores Line Connecting Software 20657c3, Manner Mode Deactivating Software 20657c4, Manner Mode Deactivating & Ringing Software 20657c5, Ringing Software 20657c6, Password Changing Software 20657c7, Device Locking Software 20657c8, and

Power Off Software **20657c9**. Line Connecting Software **20657c3** is the software program described in Paragraph [0149]. Manner Mode Deactivating Software **20657c4** is the software program described in Paragraph [0150]. Manner Mode Deactivating & Ringing Software **20657c5** is the software program described in Paragraph [0151]. Ringing Software **20657c6** is the software program described in Paragraph [0152]. Password Changing Software **20657c7** is the software program described in Paragraph [0153]. Device Locking Software **20657c8** is the software program described in Paragraph [0154]. Power Off Software **20657c9** is the software program described in Paragraph [0155].

Paragraph [0146]—Paragraph [0147] through Paragraph [0155] illustrate the software programs which enables the user of Communication Device **200** to remotely control Communication Device **200** via conventional telephone Phone PH.

Paragraph [0147]—This Paragraph [0147] illustrates User Authenticating Software **H57c1** (Paragraph [0138]) stored in Communication Device Controlling Software Storage Area **H57c** of Host H (Paragraph [0025]), which authenticates the user of Communication Device **200** to implement the present function via Phone PH. In the present embodiment, Phone PH calls Host H by dialing the predetermined phone number of Host H (S1). Upon receiving the call from Phone PH (S2) and the line is connected therebetween (S3), the user, by utilizing Phone PH, inputs both his/her password data (S4) and the phone number data of Communication Device **200** (S5). Host H initiates the authentication process by referring to Password Data Storage Area **H57b1** (Paragraph [0135]) and Phone Number Data Storage Area **H57b2** (Paragraph [0136]) (S6). The authentication process is completed (and the sequences described hereafter are enabled thereafter) if the password data and the phone number data described in S4 and S5 match with the data stored in Password Data Storage Area **H57b1** and Phone Number Data Storage Area **H57b2**.

Paragraph [0148]—This Paragraph [0148] illustrates Menu Introducing Software **H57c2** (Paragraph [0138]) stored in Communication Device Controlling Software Storage Area **H57c** of Host H (Paragraph [0025]), which introduces the menu via Phone PH. In the present embodiment, Host H retrieves Audio Data#0 from Audio Data Storage Area **H57b3** (Paragraph [0137]) (S1), and sends the data to Phone PH (S2). Upon receiving Audio Data#0 from Host H (S3), Phone PH outputs Audio Data#0 from its speaker (S4). The user presses one of the keys of '1' through '6' wherein the sequences implemented thereafter are described in Paragraph [0149] through Paragraph [0155] (S5).

Paragraph [0149]—This Paragraph [0149] illustrates Line Connecting Software **H57c3** (Paragraph [0138]) stored in Communication Device Controlling Software Storage Area **H57c** of Host H (Paragraph [0025]) and Line Connecting Software **20657c3** (Paragraph [0145]) stored in Communication Device Controlling Software Storage Area **20657c** of Communication Device **200**, which connect line between Host H and Communication Device **200**. In the present embodiment, Host H calls Communication Device **200** by retrieving the corresponding phone number data from Phone Number Data Storage Area **H57b2** (Paragraph [0136]) (S1). Upon Communication Device **200** receiving the call from Host H (S2), the line is connected therebetween (S3). For the avoidance of doubt, the line is connected between Host H and Communication Device **200** merely to implement the present function, and a voice communication between human beings is not enabled thereafter.

Paragraph [0150]—This Paragraph [0150] illustrates Manner Mode Deactivating Software **H57c4** (Paragraph [0138])

stored in Communication Device Controlling Software Storage Area **H57c** of Host H (Paragraph [0025]) and Manner Mode Deactivating Software **20657c4** (Paragraph [0145]) stored in Communication Device Controlling Software Storage Area **20657c** of Communication Device **200**, which deactivate the manner mode of Communication Device **200**. Here, Communication Device **200** activates Vibrator **217** (FIG. 1) when Communication Device **200** is in the manner mode and outputs a ringing sound from Speaker **216** (FIG. 1) when Communication Device **200** is not in the manner mode, upon receiving an incoming call. Assume that the user presses key '1' of Phone PH (S1). In response, Phone PH sends the corresponding signal to Host H (S2). Host H, upon receiving the signal described in S2, sends a manner mode deactivating command to Communication Device **200** (S3). Upon receiving the manner mode deactivating command from Host H (S4), Communication Device **200** deactivates the manner mode (S5). Host H retrieves Audio Data#1 from Audio Data Storage Area **H57b3** (Paragraph [0137]) and sends the data to Phone PH (S6). Upon receiving Audio Data#1 from Host H, Phone PH outputs the data from its speaker (S7). Normally the purpose to output the ringing sound from Speaker **216** is to give a notification to the user that Communication Device **200** has received an incoming call, and a voice communication is enabled thereafter upon answering the call. In contrast, the purpose to output the ringing sound from Speaker **216** by executing Manner Mode Deactivating & Ringing Software **H57c5** and Manner Mode Deactivating & Ringing Software **20657c5** is merely to let the user to identify the location of Communication Device **200**. Therefore, a voice communication between human beings is not enabled thereafter.

Paragraph [0151]—This Paragraph [0151] illustrates Manner Mode Deactivating & Ringing Software **H57c5** (Paragraph [0138]) stored in Communication Device Controlling Software Storage Area **H57c** of Host H (Paragraph [0025]) and Manner Mode Deactivating & Ringing Software **20657c5** (Paragraph [0145]) stored in Communication Device Controlling Software Storage Area **20657c** of Communication Device **200**, which deactivate the manner mode of Communication Device **200** and outputs a ringing sound thereafter. Assume that the user presses key '2' of Phone PH (S1). In response, Phone PH sends the corresponding signal to Host H (S2). Host H, upon receiving the signal described in S2, sends a manner mode deactivating & device ringing command to Communication Device **200** (S3). Upon receiving the manner mode deactivating & device ringing command from Host H (S4), Communication Device **200** deactivates the manner mode (S5) and outputs a ring data from Speaker **216** (S6). Host H retrieves Audio Data#2 from Audio Data Storage Area **H57b3** (Paragraph [0137]) and sends the data to Phone PH (S7). Upon receiving Audio Data#2 from Host H, Phone PH outputs the data from its speaker (S8). Normally the purpose to output the ringing sound from Speaker **216** is to give a notification to the user that Communication Device **200** has received an incoming call, and a voice communication is enabled thereafter upon answering the call. In contrast, the purpose to output the ringing sound from Speaker **216** by executing Manner Mode Deactivating & Ringing Software **H57c5** and Manner Mode Deactivating & Ringing Software **20657c5** is merely to let the user to identify the location of Communication Device **200**. Therefore, a voice communication between human beings is not enabled thereafter by implementing the present function.

Paragraph [0152]—This Paragraph [0152] illustrates Ringing Software **H57c6** (Paragraph [0138]) stored in Communication Device Controlling Software Storage Area **H57c** of Host H (Paragraph [0025]) and Ringing Software **20657c6**

(Paragraph [0145]) stored in Communication Device Controlling Software Storage Area **20657c** of Communication Device **200**, which output a ringing sound from Speaker **216** (FIG. 1). Assume that the user presses key '3' of Phone PH (S1). In response, Phone PH sends the corresponding signal to Host H (S2). Host H, upon receiving the signal described in S2, sends a device ringing command to Communication Device **200** (S3). Upon receiving the device ringing command from Host H (S4), Communication Device **200** outputs a ring data from Speaker **216** (S5). Host H retrieves Audio Data#3 from Audio Data Storage Area **H57b3** (Paragraph [0137]) and sends the data to Phone PH (S6). Upon receiving Audio Data#3 from Host H, Phone PH outputs the data from its speaker (S7). Normally the purpose to output the ringing sound from Speaker **216** is to give a notification to the user that Communication Device **200** has received an incoming call, and a voice communication is enabled thereafter upon answering the call. In contrast, the purpose to output the ringing sound from Speaker **216** by executing Ringing Software **H57c6** and Ringing Software **20657c6** is merely to let the user to identify the location of Communication Device **200**. Therefore, a voice communication between human beings is not enabled thereafter by implementing the present function.

Paragraph [0153]—This Paragraph [0153] illustrates Password Changing Software **H57c7** (Paragraph [0138]) stored in Communication Device Controlling Software Storage Area **H57c** of Host H (Paragraph [0025]) and Password Changing Software **20657c7** (Paragraph [0145]) stored in Communication Device Controlling Software Storage Area **20657c** of Communication Device **200**, which change the password necessary to operate Communication Device **200**. Assume that the user presses key '4' of Phone PH (S1). In response, Phone PH sends the corresponding signal to Host H (S2). The user then enters a new password data by utilizing Phone PH (S3), which is sent to Communication Device **200** by Host H (S4). Upon receiving the new password data from Host H (S5), Communication Device **200** stores the new password data in Password Data Storage Area **20657b1** (Paragraph [0143]) and the old password data is erased (S6). Host H retrieves Audio Data#4 from Audio Data Storage Area **H57b3** (Paragraph [0137]) and sends the data to Phone PH (S7). Upon receiving Audio Data#4 from Host H, Phone PH outputs the data from its speaker (S8).

Paragraph [0154]—This Paragraph [0154] illustrates Device Locking Software **H57c8** (Paragraph [0138]) stored in Communication Device Controlling Software Storage Area **H57c** of Host H (Paragraph [0025]) and Device Locking Software **20657c8** (Paragraph [0145]) stored in Communication Device Controlling Software Storage Area **20657c** of Communication Device **200**, which lock Communication Device **200**, i.e., nullify any input signal input via Input Device **210** (FIG. 1). Assume that the user presses key '5' of Phone PH (S1). In response, Phone PH sends the corresponding signal to Host H (S2). Host H, upon receiving the signal described in S2, sends a device locking command to Communication Device **200** (S3). Upon receiving the device locking command from Host H (S4), Communication Device **200** is locked thereafter, i.e., any input via Input Device **210** is nullified unless a password data matching to the one stored in Password Data Storage Area **20657b1** (Paragraph [0143]) is entered (S5). Host H retrieves Audio Data#5 from Audio Data Storage Area **H57b3** (Paragraph [0137]) and sends the data to Phone PH (S6). Upon receiving Audio Data#5 from Host H, Phone PH outputs the data from its speaker (S7).

Paragraph [0155]—This Paragraph [0155] illustrates Power Off Software **H57c9** (Paragraph [0138]) stored in

Communication Device Controlling Software Storage Area **H57c** of Host H (Paragraph [0025]) and Power Off Software **20657c9** (Paragraph [0145]) stored in Communication Device Controlling Software Storage Area **20657c** of Communication Device **200**, which turn off the power of Communication Device **200**. Assume that the user presses key '6' of Phone PH (S1). In response, Phone PH sends the corresponding signal to Host H (S2). Host H, upon receiving the signal described in S2, sends a power off command to Communication Device **200** (S3). Upon receiving the power off command from Host H (S4), Communication Device **200** turns off the power of itself (S5). Host H retrieves Audio Data#6 from Audio Data Storage Area **H57b3** (Paragraph [0137]) and sends the data to Phone PH (S6). Upon receiving Audio Data#6 from Host H, Phone PH outputs the data from its speaker (S7).

Paragraph [0156]—<<Communication Device Remote Controlling Function (by Web)>>

Paragraph [0157]—Paragraph [0158] through Paragraph [0181] illustrate the communication device remote controlling function (by web) which enables the user of Communication Device **200** to remotely control Communication Device **200** by an ordinary personal computer (Personal Computer PC) via the Internet, i.e., by accessing a certain web site. Here, Personal Computer PC may be any type of personal computer, including a desktop computer, lap top computer, and PDA.

Paragraph [0158]—This Paragraph [0158] illustrates the storage areas included in Host H (Paragraph [0025]). In the present embodiment, Host H includes Communication Device Controlling Information Storage Area **H58a** of which the data and the software programs stored therein are described in Paragraph [0159].

Paragraph [0159]—This Paragraph [0159] illustrates the storage areas included in Communication Device Controlling Information Storage Area **H58a** (Paragraph [0158]). In the present embodiment, Communication Device Controlling Information Storage Area **H58a** includes Communication Device Controlling Data Storage Area **H58b** and Communication Device Controlling Software Storage Area **H58c**. Communication Device Controlling Data Storage Area **H58b** stores the data necessary to implement the present function on the side of Host H (Paragraph [0025]), such as the ones described in Paragraph [0160] through Paragraph [0163]. Communication Device Controlling Software Storage Area **H58c** stores the software programs necessary to implement the present function on the side of Host H, such as the ones described in Paragraph [0164].

Paragraph [0160]—This Paragraph [0160] illustrates the storage areas included in Communication Device Controlling Data Storage Area **H58b** (Paragraph [0159]). In the present embodiment, Communication Device Controlling Data Storage Area **H58b** includes Password Data Storage Area **H58b1**, Phone Number Data Storage Area **H58b2**, Web Display Data Storage Area **H58b3**, and Work Area **H58b4**. Password Data Storage Area **H58b1** stores the data described in Paragraph [0161]. Phone Number Data Storage Area **H58b2** stores the data described in Paragraph [0162]. Web Display Data Storage Area **H58b3** stores the data described in Paragraph [0163]. Work Area **H58b4** is utilized as a work area to perform calculation and to temporarily store data.

Paragraph [0161]—This Paragraph [0161] illustrates the data stored in Password Data Storage Area **H58b1** (Paragraph [0160]). In the present embodiment, Password Data Storage Area **H58b1** comprises two columns, i.e., 'User ID' and 'Password Data'. Column 'User ID' stores the user IDs, and each user ID represents the identification of the user of Com-

munication Device **200**. Column 'Password Data' stores the password data, and each password data represents the password set by the user of the corresponding user ID. Here, each password data is composed of alphanumeric data. In the present embodiment, Password Data Storage Area **H58b1** stores the following data: the user ID 'User#1' and the corresponding password data 'Password Data#1'; the user ID 'User#2' and the corresponding password data 'Password Data#2'; the user ID 'User#3' and the corresponding password data 'Password Data#3'; the user ID 'User#4' and the corresponding password data 'Password Data#4'; and the user ID 'User#5' and the corresponding password data 'Password Data#5'.

Paragraph [0162]—This Paragraph [0162] illustrates the data stored in Phone Number Data Storage Area **H58b2** (Paragraph [0160]). In the present embodiment, Phone Number Data Storage Area **H58b2** comprises two columns, i.e., 'User ID' and 'Phone Number Data'. Column 'User ID' stores the user IDs, and each user ID represents the identification of the user of Communication Device **200**. Column 'Phone Number Data' stores the phone number data, and each phone number data represents the phone number of the user of the corresponding user ID. Here, each phone number data is composed of numeric data. In the present embodiment, Phone Number Data Storage Area **H58b2** stores the following data: the user ID 'User#1' and the corresponding phone number data 'Phone Number Data#1'; the user ID 'User#2' and the corresponding phone number data 'Phone Number Data#2'; the user ID 'User#3' and the corresponding phone number data 'Phone Number Data#3'; the user ID 'User#4' and the corresponding phone number data 'Phone Number Data#4'; and the user ID 'User#5' and the corresponding phone number data 'Phone Number Data#5'.

Paragraph [0163]—This Paragraph [0163] illustrates the data stored in Web Display Data Storage Area **H58b3** (Paragraph [0160]). In the present embodiment, Web Display Data Storage Area **H58b3** comprises two columns, i.e., 'Web Display ID' and 'Web Display Data'. Column 'Web Display ID' stores the web display IDs, and each web display ID represents the identification of the web display data stored in column 'Web Display Data'. Column 'Web Display Data' stores the web display data, and each web display data represents a message displayed on Personal Computer PC. In the present embodiment, Web Display Data Storage Area **H58b3** stores the following data: the web display ID 'Web Display#0' and the corresponding web display data 'Web Display Data#0'; the web display ID 'Web Display#1' and the corresponding web display data 'Web Display Data#1'; the web display ID 'Web Display#2' and the corresponding web display data 'Web Display Data#2'; the web display ID 'Web Display#3' and the corresponding web display data 'Web Display Data#3'; the web display ID 'Web Display#4' and the corresponding web display data 'Web Display Data#4'; the web display ID 'Web Display#5' and the corresponding web display data 'Web Display Data#5'; and the web display ID 'Web Display#6' and the corresponding web display data 'Web Display Data#6'. 'Web Display Data#0' represents the message: 'To deactivate manner mode, press **1**. To deactivate manner mode and ring your mobile phone, press **2**. To ring your mobile phone, press **3**. To change password of your mobile phone, press **4**. To lock your mobile phone, press **5**. To power off your mobile phone, press **6**.' 'Web Display Data#1' represents the message: 'The manner mode has been deactivated.' Web Display Data#2' represents the message: 'The manner mode has been deactivated and your mobile phone has been rung.' 'Web Display Data#3' represents the message: 'Your mobile phone has been rung.' Web Display

Data#4' represents the message: 'The password of your mobile phone has been changed.' Web Display Data#5' represents the message: 'Your mobile phone has been changed.' Web Display Data#6' represents the message: 'Your mobile phone has been power-offed.' Paragraph [0163] illustrates the display of Personal Computer PC. In the present embodiment, Home Page **20158HP**, i.e., a home page to implement the present function is displayed on Personal Computer PC. Home Page **20158HP** is primarily composed of Web Display Data#0 (Paragraph [0163]) and six buttons, i.e., Buttons **1** through **6**. Following the instruction described in Web Display Data#0, the user may select one of the buttons to implement the desired function as described hereinafter.

Paragraph [0164]—This Paragraph [0164] illustrates the software programs stored in Communication Device Controlling Software Storage Area **H58c** (Paragraph [0159]). In the present embodiment, Communication Device Controlling Software Storage Area **H58c** stores User Authenticating Software **H58c1**, Menu Introducing Software **H58c2**, Line Connecting Software **H58c3**, Manner Mode Deactivating Software **H58c4**, Manner Mode Deactivating & Ringing Software **H58c5**, Ringing Software **H58c6**, Password Changing Software **H58c7**, Device Locking Software **H58c8**, and Power Off Software **H58c9**. User Authenticating Software **H58c1** is the software program described in Paragraph [0173]. Menu Introducing Software **H58c2** is the software program described in Paragraph [0174]. Line Connecting Software **H58c3** is the software program described in Paragraph [0175]. Manner Mode Deactivating Software **H58c4** is the software program described in Paragraph [0176]. Manner Mode Deactivating & Ringing Software **H58c5** is the software program described in Paragraph [0177]. Ringing Software **H58c6** is the software program described in Paragraph [0178]. Password Changing Software **H58c7** is the software program described in Paragraph [0179]. Device Locking Software **H58c8** is the software program described in Paragraph [0180]. Power Off Software **H58c9** is the software program described in Paragraph [0181].

Paragraph [0165]—This Paragraph [0165] illustrates the storage area included in RAM **206** (FIG. 1). In the present embodiment, RAM **206** includes Communication Device Controlling Information Storage Area **20658a** of which the data and the software programs stored therein are described in Paragraph [0166].

Paragraph [0166]—This Paragraph [0166] illustrates the storage areas included in Communication Device Controlling Information Storage Area **20658a** (Paragraph [0165]). In the present embodiment, Communication Device Controlling Information Storage Area **20658a** includes Communication Device Controlling Data Storage Area **20658b** and Communication Device Controlling Software Storage Area **20658c**. Communication Device Controlling Data Storage Area **20658b** stores the data necessary to implement the present function on the side of Communication Device **200**, such as the ones described in Paragraph [0168] through Paragraph [0170]. Communication Device Controlling Software Storage Area **20658c** stores the software programs necessary to implement the present function on the side of Communication Device **200**, such as the ones described in Paragraph [0171].

Paragraph [0167]—The data and/or the software programs stored in Communication Device Controlling Information Storage Area **20658a** (Paragraph [0166]) may be downloaded from Host H (Paragraph [0025]).

Paragraph [0168]—This Paragraph [0168] illustrates the storage areas included in Communication Device Controlling Data Storage Area **20658b** (Paragraph [0166]). In the present

embodiment, Communication Device Controlling Data Storage Area **20658b** includes Password Data Storage Area **20658b1** and Work Area **20658b4**. Password Data Storage Area **20658b1** stores the data described in Paragraph [0169]. Work Area **20658b4** is utilized as a work area to perform calculation and to temporarily store data.

Paragraph [0169]—This Paragraph [0169] illustrates the data stored in Password Data Storage Area **20658b1** (Paragraph [0168]). In the present embodiment, Password Data Storage Area **20658b1** comprises two columns, i.e., ‘User ID’ and ‘Password Data’. Column ‘User ID’ stores the user ID which represents the identification of the user of Communication Device **200**. Column ‘Password Data’ stores the password data set by the user of Communication Device **200**. Here, the password data is composed of alphanumeric data. Assuming that the user ID of Communication Device **200** is ‘User#1’. In the present embodiment, Password Data Storage Area **H58b1** stores the following data: the user ID ‘User#1’ and the corresponding password data ‘Password Data#1’.

Paragraph [0170]—This Paragraph [0170] illustrates the data stored in Phone Number Data Storage Area **20658b2** (Paragraph [0168]). In the present embodiment, Phone Number Data Storage Area **20658b2** comprises two columns, i.e., ‘User ID’ and ‘Phone Number Data’. Column ‘User ID’ stores the user ID of the user of Communication Device **200**. Column ‘Phone Number Data’ stores the phone number data which represents the phone number of Communication Device **200**. Here, the phone number data is composed of numeric data. In the present embodiment, Phone Number Data Storage Area **H58b2** stores the following data: the user ID ‘User#1’ and the corresponding phone number data ‘Phone Number Data#1’.

Paragraph [0171]—This Paragraph [0171] illustrates the software programs stored in Communication Device Controlling Software Storage Area **20658c** (Paragraph [0166]). In the present embodiment, Communication Device Controlling Software Storage Area **20658c** stores Line Connecting Software **20658c3**, Manner Mode Deactivating Software **20658c4**, Manner Mode Deactivating & Ringing Software **20658c5**, Ringing Software **20658c6**, Password Changing Software **20658c7**, Device Locking Software **20658c8**, and Power Off Software **20658c9**. Line Connecting Software **20658c3** is the software program described in Paragraph [0175]. Manner Mode Deactivating Software **20658c4** is the software program described in Paragraph [0176]. Manner Mode Deactivating & Ringing Software **20658c5** is the software program described in Paragraph [0177]. Ringing Software **20658c6** is the software program described in Paragraph [0178]. Password Changing Software **20658c7** is the software program described in Paragraph [0179]. Device Locking Software **20658c8** is the software program described in Paragraph [0180]. Power Off Software **20658c9** is the software program described in Paragraph [0181].

Paragraph [0172]—Paragraph [0173] through Paragraph [0181] illustrate the software programs which enables the user of Communication Device **200** to remotely control Communication Device **200** by Personal Computer PC.

Paragraph [0173]—This Paragraph [0173] illustrates User Authenticating Software **H58c1** (Paragraph [0164]) stored in Communication Device Controlling Software Storage Area **H58c** of Host H (Paragraph [0025]), which authenticates the user of Communication Device **200** to implement the present function via Personal Computer PC. In the present embodiment, Personal Computer PC sends an access request to Host H via the Internet (S1). Upon receiving the request from Personal Computer PC (S2) and the line is connected therebetween (S3), the user, by utilizing Personal Computer PC,

inputs both his/her password data (S4) and the phone number data of Communication Device **200** (S5). Host H initiates the authentication process by referring to Password Data Storage Area **H58b1** (Paragraph [0161]) and Phone Number Data Storage Area **H58b2** (Paragraph [0162])) (S6). The authentication process is completed (and the sequences described hereafter are enabled thereafter) if the password data and the phone number data described in S4 and S5 match with the data stored in Password Data Storage Area **H58b1** and Phone Number Data Storage Area **H58b2**.

Paragraph [0174]—This Paragraph [0174] illustrates Menu Introducing Software **H58c2** (Paragraph [0164]) stored in Communication Device Controlling Software Storage Area **H58c** of Host H (Paragraph [0025]), which introduces the menu on Personal Computer PC. In the present embodiment, Host H retrieves Web Display Data#0 from Web Display Data Storage Area **H58b3** (Paragraph [0163]) (S1), and sends the data to Personal Computer PC (S2). Upon receiving Web Display Data#0 from Host H (S3), Personal Computer PC displays Web Display Data#0 on its display (S4). The user selects from one of the buttons of ‘1’ through ‘6’ wherein the sequences implemented thereafter are described in Paragraph [0175] through Paragraph [0181] (S5).

Paragraph [0175]—This Paragraph [0175] illustrates Line Connecting Software **H58c3** (Paragraph [0164]) stored in Communication Device Controlling Software Storage Area **H58c** of Host H (Paragraph [0025]) and Line Connecting Software **20658c3** (Paragraph [0171]) stored in Communication Device Controlling Software Storage Area **20658c** of Communication Device **200**, which connect line between Host H and Communication Device **200**. In the present embodiment, Host H calls Communication Device **200** by retrieving the corresponding phone number data from Phone Number Data Storage Area **H58b2** (Paragraph [0162]) (S1). Upon Communication Device **200** receiving the call from Host H (S2), the line is connected therebetween (S3). For the avoidance of doubt, the line is connected between Host H and Communication Device **200** merely to implement the present function, and a voice communication between human beings is not enabled thereafter.

Paragraph [0176]—This Paragraph [0176] illustrates Manner Mode Deactivating Software **H58c4** (Paragraph [0164]) stored in Communication Device Controlling Software Storage Area **H58c** of Host H (Paragraph [0025]) and Manner Mode Deactivating Software **20658c4** (Paragraph [0171]) stored in Communication Device Controlling Software Storage Area **20658c** of Communication Device **200**, which deactivate the manner mode of Communication Device **200**. Here, Communication Device **200** activates Vibrator **217** (FIG. 1) when Communication Device **200** is in the manner mode and outputs a ringing sound from Speaker **216** (FIG. 1) when Communication Device **200** is not in the manner mode, upon receiving an incoming call. Assume that the user selects button ‘1’ displayed on Personal Computer PC (S1). In response, Personal Computer PC sends the corresponding signal to Host H via the Internet (S2). Host H, upon receiving the signal described in S2, sends a manner mode deactivating command to Communication Device **200** (S3). Upon receiving the manner mode deactivating command from Host H (S4), Communication Device **200** deactivates the manner mode (S5). Host H retrieves Web Display Data#1 from Web Display Data Storage Area **H58b3** (Paragraph [0163]) and sends the data to Personal Computer PC (S6). Upon receiving Web Display Data#1 from Host H, Personal Computer PC displays the data (S7). Normally the purpose to output the ringing sound from Speaker **216** is to give a notification to the user that Communication Device **200** has received an incoming call, and a

voice communication is enabled thereafter upon answering the call. In contrast, the purpose to output the ringing sound from Speaker **216** by executing Manner Mode Deactivating & Ringing Software **H58c5** and Manner Mode Deactivating & Ringing Software **20658c5** is merely to let the user to identify the location of Communication Device **200**. Therefore, a voice communication between human beings is not enabled thereafter.

Paragraph [0177]—This Paragraph [0177] illustrates Manner Mode Deactivating & Ringing Software **H58c5** (Paragraph [0164]) stored in Communication Device Controlling Software Storage Area **H58c** of Host H (Paragraph [0025]) and Manner Mode Deactivating & Ringing Software **20658c5** (Paragraph [0171]) stored in Communication Device Controlling Software Storage Area **20658c** of Communication Device **200**, which deactivate the manner mode of Communication Device **200** and outputs a ringing sound thereafter. Assume that the user selects button ‘**2**’ displayed on Personal Computer PC (**S1**). In response, Personal Computer PC sends the corresponding signal to Host H via the Internet (**S2**). Host H, upon receiving the signal described in **S2**, sends a manner mode deactivating & device ringing command to Communication Device **200** (**S3**). Upon receiving the manner mode deactivating & device ringing command from Host H (**S4**), Communication Device **200** deactivates the manner mode (**S5**) and outputs a ring data from Speaker **216** (**S6**). Host H retrieves Web Display Data#**2** from Web Display Data Storage Area **H58b3** (Paragraph [0163]) and sends the data to Personal Computer PC (**S7**). Upon receiving Web Display Data#**2** from Host H, Personal Computer PC displays the data (**S8**). Normally the purpose to output the ringing sound from Speaker **216** is to give a notification to the user that Communication Device **200** has received an incoming call, and a voice communication is enabled thereafter upon answering the call. In contrast, the purpose to output the ringing sound from Speaker **216** by executing Manner Mode Deactivating & Ringing Software **H58c5** and Manner Mode Deactivating & Ringing Software **20658c5** is merely to let the user to identify the location of Communication Device **200**. Therefore, a voice communication between human beings is not enabled thereafter by implementing the present function.

Paragraph [0178]—This Paragraph [0178] illustrates Ringing Software **H58c6** (Paragraph [0164]) stored in Communication Device Controlling Software Storage Area **H58c** of Host H (Paragraph [0025]) and Ringing Software **20658c6** (Paragraph [0171]) stored in Communication Device Controlling Software Storage Area **20658c** of Communication Device **200**, which output a ringing sound from Speaker **216** (FIG. 1). Assume that the user selects button ‘**3**’ displayed on Personal Computer PC (**S1**). In response, Personal Computer PC sends the corresponding signal to Host H via the Internet (**S2**). Host H, upon receiving the signal described in **S2**, sends a device ringing command to Communication Device **200** (**S3**). Upon receiving the device ringing command from Host H (**S4**), Communication Device **200** outputs a ring data from Speaker **216** (**S5**). Host H retrieves Web Display Data#**3** from Web Display Data Storage Area **H58b3** (Paragraph [0163]) and sends the data to Personal Computer PC (**S6**). Upon receiving Web Display Data#**3** from Host H, Personal Computer PC displays the data (**S7**). Normally the purpose to output the ringing sound from Speaker **216** is to give a notification to the user that Communication Device **200** has received an incoming call, and a voice communication is enabled thereafter upon answering the call. In contrast, the purpose to output the ringing sound from Speaker **216** by executing Ringing Software **H58c6** and Ringing Software **20658c6** is merely to let the user to identify the location of

Communication Device **200**. Therefore, a voice communication between human beings is not enabled thereafter by implementing the present function.

Paragraph [0179]—This Paragraph [0179] illustrates Password Changing Software **H58c7** (Paragraph [0164]) stored in Communication Device Controlling Software Storage Area **H58c** of Host H (Paragraph [0025]) and Password Changing Software **20658c7** (Paragraph [0171]) stored in Communication Device Controlling Software Storage Area **20658c** of Communication Device **200**, which change the password necessary to operate Communication Device **200**. Assume that the user selects button ‘**4**’ displayed on Personal Computer PC (**S1**). In response, Personal Computer PC sends the corresponding signal to Host H via the Internet (**S2**). The user then enters a new password data by utilizing Personal Computer PC (**S3**), which is sent to Communication Device **200** by Host H (**S4**). Upon receiving the new password data from Host H (**S5**), Communication Device **200** stores the new password data in Password Data Storage Area **20658b1** (Paragraph [0169]) and the old password data is erased (**S6**). Host H retrieves Web Display Data#**4** from Web Display Data Storage Area **H58b3** (Paragraph [0163]) and sends the data to Personal Computer PC (**S7**). Upon receiving Web Display Data#**4** from Host H, Personal Computer PC displays the data (**S8**).

Paragraph [0180]—This Paragraph [0180] illustrates Device Locking Software **H58c8** (Paragraph [0164]) stored in Communication Device Controlling Software Storage Area **H58c** of Host H (Paragraph [0025]) and Device Locking Software **20658c8** (Paragraph [0171]) stored in Communication Device Controlling Software Storage Area **20658c** of Communication Device **200**, which lock Communication Device **200**, i.e., nullify any input signal input via Input Device **210** (FIG. 1). Assume that the user selects button ‘**5**’ displayed on Personal Computer PC (**S1**). In response, Personal Computer PC sends the corresponding signal to Host H via the Internet (**S2**). Host H, upon receiving the signal described in **S2**, sends a device locking command to Communication Device **200** (**S3**). Upon receiving the device locking command from Host H (**S4**), Communication Device **200** is locked thereafter, i.e., any input via Input Device **210** is nullified unless a password data matching to the one stored in Password Data Storage Area **20658b1** (Paragraph [0169]) is entered (**S5**). Host H retrieves Web Display Data#**5** from Web Display Data Storage Area **H58b3** (Paragraph [0163]) and sends the data to Personal Computer PC (**S6**). Upon receiving Web Display Data#**5** from Host H, Personal Computer PC displays the data (**S7**).

Paragraph [0181]—This Paragraph [0181] illustrates Power Off Software **H58c9** (Paragraph [0164]) stored in Communication Device Controlling Software Storage Area **H58c** of Host H (Paragraph [0025]) and Power Off Software **20658c9** (Paragraph [0171]) stored in Communication Device Controlling Software Storage Area **20658c** of Communication Device **200**, which turn off the power of Communication Device **200**. Assume that the user selects button ‘**6**’ displayed on Personal Computer PC (**S1**). In response, Personal Computer PC sends the corresponding signal to Host H via the Internet (**S2**). Host H, upon receiving the signal described in **S2**, sends a power off command to Communication Device **200** (**S3**). Upon receiving the power off command from Host H (**S4**), Communication Device **200** turns off the power of itself (**S5**). Host H retrieves Web Display Data#**6** from Web Display Data Storage Area **H58b3** (Paragraph [0163]) and sends the data to Personal Computer PC (**S6**). Upon receiving Web Display Data#**6** from Host H, Personal Computer PC displays the data (**S7**).

Paragraph [0182]—<<OS Updating Function>>

Paragraph [0183]—Paragraph [0184] through Paragraph [0244] illustrate the OS updating function which updates the operating system of Communication Device **200** in a wireless fashion. In other words, Communication Device **200** down-loads the portion of the operating system of the latest version from Host H (Paragraph [0025]) via Antenna **218** (FIG. 1).

Paragraph [0184]—This Paragraph [0184] illustrates the storage areas included in RAM **206** (FIG. 1). In the present embodiment, RAM **206** includes Operating System **20663OS** of which the data stored therein are described in Paragraph [0185], and OS Updating Information Storage Area **20663a** of which the data and the software programs stored therein are described in Paragraph [0186].

Paragraph [0185]—This Paragraph [0185] illustrates the data stored in Operating System **20663OS** (Paragraph [0184]). In the present embodiment, Operating System **20663OS** includes Battery Controller **20663OSa**, CCD Unit Controller **20663OSb**, Flash Light Unit Controller **20663OSc**, Indicator Controller **20663OSd**, Input Device Controller **20663OSe**, LCD Controller **20663OSf**, LED Controller **20663OSg**, Memory Card Interface Controller **20663OSh**, Microphone Controller **20663OSi**, Photometer Controller **20663OSj**, RAM Controller **20663OSk**, ROM Controller **20663OSl**, Signal Processor Controller **20663OSm**, Signal Processor Controller **20663OSn**, Solar Panel Controller **20663OSo**, Speaker Controller **20663OSp**, Vibrator Controller **20663OSq**, Video Processor Controller **20663OSr**, Wireless Receiver Controller **20663OSs**, Wireless Receiver Controller **20663OSt**, Wireless Receiver Controller **20663OSu**, Wireless Transmitter Controller **20663OSv**, Wireless Transmitter Controller **20663OSw**, and Wireless Transmitter Controller **20663OSx**. Battery Controller **20663OSa** is a controller which controls Battery **230** (not shown). CCD Unit Controller **20663OSb** is a controller which controls CCD Unit **214** (not shown). Flash Light Unit Controller **20663OSc** is a controller which controls Flash Light Unit **220** (not shown). Indicator Controller **20663OSd** is a controller which controls Indicator **212** (not shown). Input Device Controller **20663OSe** is a controller which controls Input Device **210** (not shown). LCD Controller **20663OSf** is a controller which controls LCD **201** (not shown). LED Controller **20663OSg** is a controller which controls LED **219** (not shown). Memory Card Interface Controller **20663OSh** is a controller which controls Memory Card Interface **221** (not shown). Microphone Controller **20663OSi** is a controller which controls Microphone **215** (not shown). Photometer Controller **20663OSj** is a controller which controls Photometer **232** (not shown). RAM Controller **20663OSk** is a controller which controls RAM **206** (not shown). ROM Controller **20663OSl** is a controller which controls ROM **207** (not shown). Signal Processor Controller **20663OSm** is a controller which controls Signal Processor **205** (not shown). Signal Processor Controller **20663OSn** is a controller which controls Signal Processor **208** (not shown). Solar Panel Controller **20663OSo** is a controller which controls Solar Panel **229** (not shown). Speaker Controller **20663OSp** is a controller which controls Speaker **216L** (not shown). Vibrator Controller **20663OSq** is a controller which controls Vibrator **217** (not shown). Video Processor Controller **20663OSr** is a controller which controls Video Processor **202** (not shown). Wireless Receiver Controller **20663OSs** is a controller which controls Wireless Receiver **224** (not shown). Wireless Receiver Controller **20663OSt** is a controller which controls Wireless Receiver **225** (not shown). Wireless Receiver Controller **20663OSu** is a controller which controls Wireless Receiver **226** (not shown). Wireless Transmitter

Controller **20663OSv** is a controller which controls Wireless Transmitter **222** (not shown). Wireless Transmitter Controller **20663OSw** is a controller which controls Wireless Transmitter **223** (not shown). Wireless Transmitter Controller **20663OSx** is a controller which controls Wireless Transmitter **227** (not shown). For the avoidance of doubt, the data stored in Operating System **20663OS** are illustrative, and other types of data, which are updated by implementing the present function, are also stored therein, such as DLLs, drivers, security implementing program.

Paragraph [0186]—This Paragraph [0186] illustrates the storage areas included in OS Updating Information Storage Area **20663a** (Paragraph [0184]). In the present embodiment, OS Updating Information Storage Area **20663a** includes OS Updating Data Storage Area **20663b** and OS Updating Software Storage Area **20663c**. OS Updating Data Storage Area **20663b** stores the data necessary to implement the present function on the side of Communication Device **200**, such as the ones described in Paragraph [0188]. OS Updating Software Storage Area **20663c** stores the software programs necessary to implement the present function on the side of Communication Device **200**, such as the ones described in Paragraph [0190].

Paragraph [0187]—The data and/or the software programs stored in OS Updating Software Storage Area **20663c** (Paragraph [0186]) may be downloaded from Host H (Paragraph [0025]).

Paragraph [0188]—This Paragraph [0188] illustrates the storage area included in OS Updating Data Storage Area **20663b** (Paragraph [0186]). In the present embodiment, OS Updating Data Storage Area **20663b** includes OS Version Data Storage Area **20663b1**. OS Version Data Storage Area **20663b1** stores the data described in Paragraph [0189].

Paragraph [0189]—This Paragraph [0189] illustrates the data stored in OS Version Data Storage Area **20663b1** (Paragraph [0188]). In the present embodiment, OS Version Data Storage Area **20663b1** includes Battery Controller Version Data **20663b1a**, CCD Unit Controller Version Data **20663b1b**, Flash Light Unit Controller Version Data **20663b1c**, Indicator Controller Version Data **20663b1d**, Input Device Controller Version Data **20663b1e**, LCD Controller Version Data **20663b1f**, LED Controller Version Data **20663b1g**, Memory Card Interface Controller Version Data **20663b1h**, Microphone Controller Version Data **20663b1i**, Photometer Controller Version Data **20663b1j**, RAM Controller Version Data **20663b1k**, ROM Controller Version Data **20663b1l**, Signal Processor Controller Version Data **20663b1m**, Signal Processor Controller Version Data **20663b1n**, Solar Panel Controller Version Data **20663b1o**, Speaker Controller Version Data **20663b1p**, Vibrator Controller Version Data **20663b1q**, Video Processor Controller Version Data **20663b1r**, Wireless Receiver Controller Version Data **20663b1s**, Wireless Receiver Controller Version Data **20663b1t**, Wireless Receiver Controller Version Data **20663b1u**, Wireless Transmitter Controller Version Data **20663b1v**, Wireless Transmitter Controller Version Data **20663b1w**, and Wireless Transmitter Controller Version Data **20663b1x**. Battery Controller Version Data **20663b1a** is the version data representing the current version of Battery Controller **20663OSa** (Paragraph [0185]). CCD Unit Controller Version Data **20663b1b** is the version data representing the current version of CCD Unit Controller **20663OSb** (Paragraph [0185]). Flash Light Unit Controller Version Data **20663b1c** is the version data representing the current version of Flash Light Unit Controller **20663OSc** (Paragraph [0185]). Indicator Controller Version Data **20663b1d** is the version data representing the current version of Indicator Controller

20663OSd (Paragraph [0185]). Input Device Controller Version Data 20663b1e is the version data representing the current version of Input Device Controller 20663OSe (Paragraph [0185]). LCD Controller Version Data 20663b1f is the version data representing the current version of LCD Controller 20663OSf (Paragraph [0185]). LED Controller Version Data 20663b1g is the version data representing the current version of LED Controller 20663OSg (Paragraph [0185]). Memory Card Interface Controller Version Data 20663b1h is the version data representing the current version of Memory Card Interface Controller 20663OSh (Paragraph [0185]). Microphone Controller Version Data 20663b1i is the version data representing the current version of Microphone Controller 20663OSi (Paragraph [0185]). Photometer Controller Version Data 20663b1j is the version data representing the current version of Photometer Controller 20663OSj (Paragraph [0185]). RAM Controller Version Data 20663b1k is the version data representing the current version of RAM Controller 20663OSk (Paragraph [0185]). ROM Controller Version Data 20663b1l is the version data representing the current version of ROM Controller 20663OSl (Paragraph [0185]). Signal Processor Controller Version Data 20663b1m is the version data representing the current version of Signal Processor Controller 20663OSm (Paragraph [0185]). Signal Processor Controller Version Data 20663b1n is the version data representing the current version of Signal Processor Controller 20663OSn (Paragraph [0185]). Solar Panel Controller Version Data 20663b1o is the version data representing the current version of Solar Panel Controller 20663OSo (Paragraph [0185]). Speaker Controller Version Data 20663b1p is the version data representing the current version of Speaker Controller 20663OSp (Paragraph [0185]). Vibrator Controller Version Data 20663b1q is the version data representing the current version of Vibrator Controller 20663OSq (Paragraph [0185]). Video Processor Controller Version Data 20663b1r is the version data representing the current version of Video Processor Controller 20663OSr (Paragraph [0185]). Wireless Receiver Controller Version Data 20663b1s is the version data representing the current version of Wireless Receiver Controller 20663OSs (Paragraph [0185]). Wireless Receiver Controller Version Data 20663b1t is the version data representing the current version of Wireless Receiver Controller 20663OSt (Paragraph [0185]). Wireless Receiver Controller Version Data 20663b1u is the version data representing the current version of Wireless Receiver Controller 20663OSu (Paragraph [0185]). Wireless Transmitter Controller Version Data 20663b1v is the version data representing the current version of Wireless Transmitter Controller 20663OSv (Paragraph [0185]). Wireless Transmitter Controller Version Data 20663b1w is the version data representing the current version of Wireless Transmitter Controller 20663OSw (Paragraph [0185]). Wireless Transmitter Controller Version Data 20663b1x is the version data representing the current version of Wireless Transmitter Controller 20663OSx (Paragraph [0185]). Here, the version data is composed of numeric data, such as '1', '2', and '3', wherein '1' represents version '1.0', '2' represents version '2.0', and '3' represents version '3.0'.

Paragraph [0190]—This Paragraph [0190] illustrates the software programs stored in OS Updating Software Storage Area 20663c (Paragraph [0186]). In the present embodiment, OS Updating Software Storage Area 20663c stores Battery Controller Updating Software 20663c1a, CCD Unit Controller Updating Software 20663c1b, Flash Light Unit Controller Updating Software 20663c1c, Indicator Controller Updating Software 20663c1d, Input Device Controller Updating Software 20663c1e, LCD Controller Updating Software 20663c1f, LED Controller Updating Software 20663c1g,

Memory Card Interface Controller Updating Software 20663c1h, Microphone Controller Updating Software 20663c1i, Photometer Controller Updating Software 20663c1j, RAM Controller Updating Software 20663c1k, ROM Controller Updating Software 20663c1l, Signal Processor Controller Updating Software 20663c1m, Signal Processor Controller Updating Software 20663c1n, Solar Panel Controller Updating Software 20663c1o, Speaker Controller Updating Software 20663c1p, Vibrator Controller Updating Software 20663c1q, Video Processor Controller Updating Software 20663c1r, Wireless Receiver Controller Updating Software 20663c1s, Wireless Receiver Controller Updating Software 20663c1t, Wireless Receiver Controller Updating Software 20663c1u, Wireless Transmitter Controller Updating Software 20663c1v, Wireless Transmitter Controller Updating Software 20663c1w, and Wireless Transmitter Controller Updating Software 20663c1x. Battery Controller Updating Software 20663c1a is the software program described in Paragraph [0197] and Paragraph [0198]. CCD Unit Controller Updating Software 20663c1b is the software program described in Paragraph [0199] and Paragraph [0200]. Flash Light Unit Controller Updating Software 20663c1c is the software program described in Paragraph [0201] and Paragraph [0202]. Indicator Controller Updating Software 20663c1d is the software program described in Paragraph [0203] and Paragraph [0204]. Input Device Controller Updating Software 20663c1e is the software program described in Paragraph [0205] and Paragraph [0206]. LCD Controller Updating Software 20663c1f is the software program described in Paragraph [0207] and Paragraph [0208]. LED Controller Updating Software 20663c1g is the software program described in Paragraph [0209] and Paragraph [0210]. Memory Card Interface Controller Updating Software 20663c1h is the software program described in Paragraph [0211] and Paragraph [0212]. Microphone Controller Updating Software 20663c1i is the software program described in Paragraph [0213] and Paragraph [0214]. Photometer Controller Updating Software 20663c1j is the software program described in Paragraph [0215] and Paragraph [0216]. RAM Controller Updating Software 20663c1k is the software program described in Paragraph [0217] and Paragraph [0218]. ROM Controller Updating Software 20663c1l is the software program described in Paragraph [0219] and Paragraph [0220]. Signal Processor Controller Updating Software 20663c1m is the software program described in Paragraph [0221] and Paragraph [0222]. Signal Processor Controller Updating Software 20663c1n is the software program described in Paragraph [0223] and Paragraph [0224]. Solar Panel Controller Updating Software 20663c1o is the software program described in Paragraph [0225] and Paragraph [0226]. Speaker Controller Updating Software 20663c1p is the software program described in Paragraph [0227] and Paragraph [0228]. Vibrator Controller Updating Software 20663c1q is the software program described in Paragraph [0229] and Paragraph [0230]. Video Processor Controller Updating Software 20663c1r is the software program described in Paragraph [0231] and Paragraph [0232]. Wireless Receiver Controller Updating Software 20663c1s is the software program described in Paragraph [0233] and Paragraph [0234]. Wireless Receiver Controller Updating Software 20663c1t is the software program described in Paragraph [0235] and Paragraph [0236]. Wireless Receiver Controller Updating Software 20663c1u is the software program described in Paragraph [0237] and Paragraph [0238]. Wireless Transmitter Controller Updating Software 20663c1v is the software program described in Paragraph [0239] and Paragraph [0240]. Wireless Transmitter Controller Updating

Software **20663c1w** is the software program described in Paragraph [0241] and Paragraph [0242]. Wireless Transmitter Controller Updating Software **20663c1x** is the software program described in Paragraph [0243] and Paragraph [0244].

Paragraph [0191]—This Paragraph [0191] illustrates the storage areas included in Host H (Paragraph [0025]). In the present embodiment, Host H includes Operating System **H63OS** of which the data stored therein are described in Paragraph [0192], and OS Updating Information Storage Area **H63a** of which the data and the software programs stored therein are described in Paragraph [0193].

Paragraph [0192]—This Paragraph [0192] illustrates the data stored in Operating System **H63OS** (Paragraph [0191]). In the present embodiment, Operating System **H63OS** includes Battery Controller **H63OSa**, CCD Unit Controller **H63OSb**, Flash Light Unit Controller **H63OSc**, Indicator Controller **H63OSd**, Input Device Controller **H63OSE**, LCD Controller **H63OSf**, LED Controller **H63OSg**, Memory Card Interface Controller **H63OSh**, Microphone Controller **H63OSi**, Photometer Controller **H63OSj**, RAM Controller **H63OSk**, ROM Controller **H63OSl**, Signal Processor Controller **H63OSm**, Signal Processor Controller **H63OSn**, Solar Panel Controller **H63OSo**, Speaker Controller **H63OSp**, Vibrator Controller **H63OSq**, Video Processor Controller **H63OSr**, Wireless Receiver Controller **H63OSs**, Wireless Receiver Controller **H63OSt**, Wireless Receiver Controller **H63OSu**, Wireless Transmitter Controller **H63OSv**, Wireless Transmitter Controller **H63OSw**, and Wireless Transmitter Controller **H63OSx**. Battery Controller **H63OSa** is the controller of the latest version which controls Battery **230** (not shown). CCD Unit Controller **H63OSb** is the controller of the latest version which controls CCD Unit **214** (not shown). Flash Light Unit Controller **H63OSc** is the controller of the latest version which controls Flash Light Unit **220** (not shown). Indicator Controller **H63OSd** is the controller of the latest version which controls Indicator **212** (not shown). Input Device Controller **H63OSE** is the controller of the latest version which controls Input Device **210** (not shown). LCD Controller **H63OSf** is the controller of the latest version which controls LCD **201** (not shown). LED Controller **H63OSg** is the controller of the latest version which controls LED **219** (not shown). Memory Card Interface Controller **H63OSh** is the controller of the latest version which controls Memory Card Interface **221** (not shown). Microphone Controller **H63OSi** is the controller of the latest version which controls Microphone **215** (not shown). Photometer Controller **H63OSj** is the controller of the latest version which controls Photometer **232** (not shown). RAM Controller **H63OSk** is the controller of the latest version which controls Host H (not shown). ROM Controller **H63OSl** is the controller of the latest version which controls ROM **207** (not shown). Signal Processor Controller **H63OSm** is the controller of the latest version which controls Signal Processor **205** (not shown). Signal Processor Controller **H63OSn** is the controller of the latest version which controls Signal Processor **208** (not shown). Solar Panel Controller **H63OSo** is the controller of the latest version which controls Solar Panel **229** (not shown). Speaker Controller **H63OSp** is the controller of the latest version which controls Speaker **216L** (not shown). Vibrator Controller **H63OSq** is the controller of the latest version which controls Vibrator **217** (not shown). Video Processor Controller **H63OSr** is the controller of the latest version which controls Video Processor **202** (not shown). Wireless Receiver Controller **H63OSs** is the controller of the latest version which controls Wireless Receiver **224** (not shown). Wireless Receiver Controller **H63OSt** is the controller of the

latest version which controls Wireless Receiver **225** (not shown). Wireless Receiver Controller **H63OSu** is the controller of the latest version which controls Wireless Receiver **226** (not shown). Wireless Transmitter Controller **H63OSv** is the controller of the latest version which controls Wireless Transmitter **222** (not shown). Wireless Transmitter Controller **H63OSw** is the controller of the latest version which controls Wireless Transmitter **223** (not shown). Wireless Transmitter Controller **H63OSx** is the controller of the latest version which controls Wireless Transmitter **227** (not shown). The data stored in Operating System Storage Area **H63OS** are updated periodically. For the avoidance of doubt, the data stored in Operating System **H63OS** are illustrative, and other types of data, which are utilized to update Operating System **H63OS** of Communication Device **200** by implementing the present function, are also stored therein, such as DLLs, drivers, security implementing program. The data stored in Operating System **H63OS** are updated periodically thereby the data are always of the latest version.

Paragraph [0193]—This Paragraph [0193] illustrates the storage areas included in OS Updating Information Storage Area **H63a** (Paragraph [0191]). In the present embodiment, OS Updating Information Storage Area **H63a** includes OS Updating Data Storage Area **H63b** and OS Updating Software Storage Area **H63c**. OS Updating Data Storage Area **H63b** stores the data necessary to implement the present function on the side of Host H (Paragraph [0025]), such as the ones described in Paragraph [0194]. OS Updating Software Storage Area **H63c** stores the software programs necessary to implement the present function on the side of Host H, such as the ones described in Paragraph [0196].

Paragraph [0194]—This Paragraph [0194] illustrates the storage area included in OS Updating Data Storage Area **H63b** (Paragraph [0193]). In the present embodiment, OS Updating Data Storage Area **H63b** includes OS Version Data Storage Area **H63b1**. OS Version Data Storage Area **H63b1** stores the data described in Paragraph [0195].

Paragraph [0195]—This Paragraph [0195] illustrates the data stored in OS Version Data Storage Area **H63b1** (Paragraph [0194]). In the present embodiment, OS Version Data Storage Area **H63b1** includes Battery Controller Version Data **H63b1a**, CCD Unit Controller Version Data **H63b1b**, Flash Light Unit Controller Version Data **H63b1c**, Indicator Controller Version Data **H63b1d**, Input Device Controller Version Data **H63b1e**, LCD Controller Version Data **H63b1f**, LED Controller Version Data **H63b1g**, Memory Card Interface Controller Version Data **H63b1h**, Microphone Controller Version Data **H63b1i**, Photometer Controller Version Data **H63b1j**, RAM Controller Version Data **H63b1k**, ROM Controller Version Data **H63b1l**, Signal Processor Controller Version Data **H63b1m**, Signal Processor Controller Version Data **H63b1n**, Solar Panel Controller Version Data **H63b1o**, Speaker Controller Version Data **H63b1p**, Vibrator Controller Version Data **H63b1q**, Video Processor Controller Version Data **H63b1r**, Wireless Receiver Controller Version Data **H63b1s**, Wireless Receiver Controller Version Data **H63b1t**, Wireless Receiver Controller Version Data **H63b1u**, Wireless Transmitter Controller Version Data **H63b1v**, Wireless Transmitter Controller Version Data **H63b1w**, and Wireless Transmitter Controller Version Data **H63b1x**. Battery Controller Version Data **H63b1a** is the version data representing the latest version of Battery Controller **H63OSa** (Paragraph [0192]). CCD Unit Controller Version Data **H63b1b** is the version data representing the latest version of CCD Unit Controller **H63OSb** (Paragraph [0192]). Flash Light Unit Controller Version Data **H63b1c** is the version data representing the latest version of Flash Light Unit Controller **H63OSc**

(Paragraph [0192]). Indicator Controller Version Data H63b1d is the version data representing the latest version of Indicator Controller H63OSd (Paragraph [0192]). Input Device Controller Version Data H63b1e is the version data representing the latest version of Input Device Controller H63OSe (Paragraph [0192]). LCD Controller Version Data H63b1f is the version data representing the latest version of LCD Controller H63OSf (Paragraph [0192]). LED Controller Version Data H63b1g is the version data representing the latest version of LED Controller H63OSg (Paragraph [0192]). Memory Card Interface Controller Version Data H63b1h is the version data representing the latest version of Memory Card Interface Controller H63OSh (Paragraph [0192]). Microphone Controller Version Data H63b1i is the version data representing the latest version of Microphone Controller H63OSi (Paragraph [0192]). Photometer Controller Version Data H63b1j is the version data representing the latest version of Photometer Controller H63OSj (Paragraph [0192]). RAM Controller Version Data H63b1k is the version data representing the latest version of RAM Controller H63OSk (Paragraph [0192]). ROM Controller Version Data H63b1l is the version data representing the latest version of ROM Controller H63OSl (Paragraph [0192]). Signal Processor Controller Version Data H63b1m is the version data representing the latest version of Signal Processor Controller H63OSm (Paragraph [0192]). Signal Processor Controller Version Data H63b1n is the version data representing the latest version of Signal Processor Controller H63OSn (Paragraph [0192]). Solar Panel Controller Version Data H63b1o is the version data representing the latest version of Solar Panel Controller H63OSo (Paragraph [0192]). Speaker Controller Version Data H63b1p is the version data representing the latest version of Speaker Controller H63OSp (Paragraph [0192]). Vibrator Controller Version Data H63b1q is the version data representing the latest version of Vibrator Controller H63OSq (Paragraph [0192]). Video Processor Controller Version Data H63b1r is the version data representing the latest version of Video Processor Controller H63OSr (Paragraph [0192]). Wireless Receiver Controller Version Data H63b1s is the version data representing the latest version of Wireless Receiver Controller H63OSs (Paragraph [0192]). Wireless Receiver Controller Version Data H63b1t is the version data representing the latest version of Wireless Receiver Controller H63OSt (Paragraph [0192]). Wireless Receiver Controller Version Data H63b1u is the version data representing the latest version of Wireless Receiver Controller H63OSu (Paragraph [0192]). Wireless Transmitter Controller Version Data H63b1v is the version data representing the latest version of Wireless Transmitter Controller H63OSv (Paragraph [0192]). Wireless Transmitter Controller Version Data H63b1w is the version data representing the latest version of Wireless Transmitter Controller H63OSw (Paragraph [0192]). Wireless Transmitter Controller Version Data H63b1x is the version data representing the latest version of Wireless Transmitter Controller H63OSx (Paragraph [0192]). Here, the version data is composed of numeric data, such as '1', '2', and '3', wherein '1' represents version '1.0', '2' represents version '2.0', and '3' represents version '3.0'. The data stored in OS Version Data Storage Area H63b1 are updated periodically.

Paragraph [0196]—This Paragraph [0196] illustrates the software programs stored in OS Updating Software Storage Area H63c (Paragraph [0193]). In the present embodiment, OS Updating Software Storage Area H63c stores Battery Controller Updating Software H63c1a, CCD Unit Controller Updating Software H63c1b, Flash Light Unit Controller Updating Software H63c1c, Indicator Controller Updating

Software H63c1d, Input Device Controller Updating Software H63c1e, LCD Controller Updating Software H63c1f, LED Controller Updating Software H63c1g, Memory Card Interface Controller Updating Software H63c1h, Microphone Controller Updating Software H63c1i, Photometer Controller Updating Software H63c1j, RAM Controller Updating Software H63c1k, ROM Controller Updating Software H63c1l, Signal Processor Controller Updating Software H63c1m, Signal Processor Controller Updating Software H63c1n, Solar Panel Controller Updating Software H63c1o, Speaker Controller Updating Software H63c1p, Vibrator Controller Updating Software H63c1q, Video Processor Controller Updating Software H63c1r, Wireless Receiver Controller Updating Software H63c1s, Wireless Receiver Controller Updating Software H63c1t, Wireless Receiver Controller Updating Software H63c1u, Wireless Transmitter Controller Updating Software H63c1v, Wireless Transmitter Controller Updating Software H63c1w, and Wireless Transmitter Controller Updating Software H63c1x. Battery Controller Updating Software H63c1a is the software program described in Paragraph [0197] and Paragraph [0198]. CCD Unit Controller Updating Software H63c1b is the software program described in Paragraph [0199] and Paragraph [0200]. Flash Light Unit Controller Updating Software H63c1c is the software program described in Paragraph [0201] and Paragraph [0202]. Indicator Controller Updating Software H63c1d is the software program described in Paragraph [0203] and Paragraph [0204]. Input Device Controller Updating Software H63c1e is the software program described in Paragraph [0205] and Paragraph [0206]. LCD Controller Updating Software H63c1f is the software program described in Paragraph [0207] and Paragraph [0208]. LED Controller Updating Software H63c1g is the software program described in Paragraph [0209] and Paragraph [0210]. Memory Card Interface Controller Updating Software H63c1h is the software program described in Paragraph [0211] and Paragraph [0212]. Microphone Controller Updating Software H63c1i is the software program described in Paragraph [0213] and Paragraph [0214]. Photometer Controller Updating Software H63c1j is the software program described in Paragraph [0215] and Paragraph [0216]. RAM Controller Updating Software H63c1k is the software program described in Paragraph [0217] and Paragraph [0218]. ROM Controller Updating Software H63c1l is the software program described in Paragraph [0219] and Paragraph [0220]. Signal Processor Controller Updating Software H63c1m is the software program described in Paragraph [0221] and Paragraph [0222]. Signal Processor Controller Updating Software H63c1n is the software program described in Paragraph [0223] and Paragraph [0224]. Solar Panel Controller Updating Software H63c1o is the software program described in Paragraph [0225] and Paragraph [0226]. Speaker Controller Updating Software H63c1p is the software program described in Paragraph [0227] and Paragraph [0228]. Vibrator Controller Updating Software H63c1q is the software program described in Paragraph [0229] and Paragraph [0230]. Video Processor Controller Updating Software H63c1r is the software program described in Paragraph [0231] and Paragraph [0232]. Wireless Receiver Controller Updating Software H63c1s is the software program described in Paragraph [0233] and Paragraph [0234]. Wireless Receiver Controller Updating Software H63c1t is the software program described in Paragraph [0235] and Paragraph [0236]. Wireless Receiver Controller Updating Software H63c1u is the software program described in Paragraph [0237] and Paragraph [0238]. Wireless Transmitter Controller Updating Software H63c1v is the software program described in Para-

graph [0239] and Paragraph [0240]. Wireless Transmitter Controller Updating Software **H63c1w** is the software program described in Paragraph [0241] and Paragraph [0242]. Wireless Transmitter Controller Updating Software **H63c1x** is the software program described in Paragraph [0243] and Paragraph [0244]. The foregoing software programs are automatically implemented periodically or implemented manually by utilizing Input Device **210** (FIG. 1) or via voice recognition system.

Paragraph [0197]—This Paragraph [0197] illustrates Battery Controller Updating Software **H63c1a** (Paragraph [0196]) of Host H (Paragraph [0025]) and Battery Controller Updating Software **20663c1a** (Paragraph [0190]) of Communication Device **200**, which update Battery Controller **20663OSa** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Battery Controller Version Data **20663b1a** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Battery Controller Version Data **20663b1a** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Battery Controller Version Data **20663b1a** (Paragraph [0189]) with Battery Controller Version Data **H63b1a** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Battery Controller Version Data **20663b1a** of Communication Device **200** is of an old version. Host H retrieves Battery Controller **H63OSa**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Battery Controller **H63OSa** from Host H (S5), CPU **211** stores Battery Controller **H63OSa** as Battery Controller **20663OSa** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Battery Controller **20663OSa** (Paragraph [0185]) is deleted.

Paragraph [0198]—This Paragraph [0198] illustrates another embodiment of Battery Controller Updating Software **H63c1a** (Paragraph [0196]) of Host H (Paragraph [0025]) and Battery Controller Updating Software **20663c1a** (Paragraph [0190]) of Communication Device **200**, which update Battery Controller **20663OSa** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Battery Controller Update Request, which is received by Host H (S1). Here, the Battery Controller Update Request is a request to send Battery Controller Version Data **H63b1a** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Battery Controller Version Data **H63b1a** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Battery Controller Version Data **H63b1a** from Host H (S3), CPU **211** compares Battery Controller Version Data **H63b1a** with Battery Controller Version Data **20663b1a** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Battery Controller Version Data **20663b1a** of Communication Device **200** is of an old version. CPU **211** sends a New Battery Controller Sending Request, which is received by Host H (S5). Here, the New Battery Controller Sending Request is a request to send Battery Controller **H63OSa** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Battery Controller **H63OSa** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communica-

tion Device **200** (S6). Upon receiving Battery Controller **H63OSa** from Host H (S7), CPU **211** stores Battery Controller **H63OSa** as Battery Controller **20663OSa** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Battery Controller **20663OSa** (Paragraph [0185]) is deleted.

Paragraph [0199]—This Paragraph [0199] illustrates CCD Unit Controller Updating Software **H63c1b** (Paragraph [0196]) of Host H (Paragraph [0025]) and CCD Unit Controller Updating Software **20663c1b** (Paragraph [0190]) of Communication Device **200**, which update CCD Unit Controller **20663OSb** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves CCD Unit Controller Version Data **20663b1b** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving CCD Unit Controller Version Data **20663b1b** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares CCD Unit Controller Version Data **20663b1b** (Paragraph [0189]) with CCD Unit Controller Version Data **H63b1b** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that CCD Unit Controller Version Data **20663b1b** of Communication Device **200** is of an old version. Host H retrieves CCD Unit Controller **H63OSb**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving CCD Unit Controller **H63OSb** from Host H (S5), CPU **211** stores CCD Unit Controller **H63OSb** as CCD Unit Controller **20663OSb** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of CCD Unit Controller **20663OSb** (Paragraph [0185]) is deleted.

Paragraph [0200]—This Paragraph [0200] illustrates another embodiment of CCD Unit Controller Updating Software **H63c1b** (Paragraph [0196]) of Host H (Paragraph [0025]) and CCD Unit Controller Updating Software **20663c1b** (Paragraph [0190]) of Communication Device **200**, which update CCD Unit Controller **20663OSb** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a CCD Unit Controller Update Request, which is received by Host H (S1). Here, the CCD Unit Controller Update Request is a request to send CCD Unit Controller Version Data **H63b1b** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves CCD Unit Controller Version Data **H63b1b** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving CCD Unit Controller Version Data **H63b1b** from Host H (S3), CPU **211** compares CCD Unit Controller Version Data **H63b1b** with CCD Unit Controller Version Data **20663b1b** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that CCD Unit Controller Version Data **20663b1b** of Communication Device **200** is of an old version. CPU **211** sends a New CCD Unit Controller Sending Request, which is received by Host H (S5). Here, the New CCD Unit Controller Sending Request is a request to send CCD Unit Controller **H63OSb** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves CCD Unit Controller **H63OSb** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving CCD Unit Controller **H63OSb** from Host H (S7), CPU **211** stores CCD Unit Controller **H63OSb** as CCD

Unit Controller **20663OSb** in Operating System **20663OS** (Paragraph [0185]) (**S8**). The old version of CCD Unit Controller **20663OSb** (Paragraph [0185]) is deleted.

Paragraph [0201]—This Paragraph [0201] illustrates Flash Light Unit Controller Updating Software **H63c1c** (Paragraph [0196]) of Host H (Paragraph [0025]) and Flash Light Unit Controller Updating Software **20663c1c** (Paragraph [0190]) of Communication Device **200**, which update Flash Light Unit Controller **20663OSc** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Flash Light Unit Controller Version Data **20663b1c** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (**S1**). Upon receiving Flash Light Unit Controller Version Data **20663b1c** (Paragraph [0189]) from Communication Device **200** (**S2**), Host H compares Flash Light Unit Controller Version Data **20663b1c** (Paragraph [0189]) with Flash Light Unit Controller Version Data **H63b1c** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (**S3**). Assuming that Host H detects in **S3** that Flash Light Unit Controller Version Data **20663b1c** of Communication Device **200** is of an old version. Host H retrieves Flash Light Unit Controller **H63OSc**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (**S4**). Upon receiving Flash Light Unit Controller **H63OSc** from Host H (**S5**), CPU **211** stores Flash Light Unit Controller **H63OSc** as Flash Light Unit Controller **20663OSc** in Operating System **20663OS** (Paragraph [0185]) (**S6**). The old version of Flash Light Unit Controller **20663OSc** (Paragraph [0185]) is deleted.

Paragraph [0202]—This Paragraph [0202] illustrates another embodiment of Flash Light Unit Controller Updating Software **H63c1c** (Paragraph [0196]) of Host H (Paragraph [0025]) and Flash Light Unit Controller Updating Software **20663c1c** (Paragraph [0190]) of Communication Device **200**, which update Flash Light Unit Controller **20663OSc** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Flash Light Unit Controller Update Request, which is received by Host H (**S1**). Here, the Flash Light Unit Controller Update Request is a request to send Flash Light Unit Controller Version Data **H63b1c** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Flash Light Unit Controller Version Data **H63b1c** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (**S2**). Upon receiving Flash Light Unit Controller Version Data **H63b1c** from Host H (**S3**), CPU **211** compares Flash Light Unit Controller Version Data **H63b1c** with Flash Light Unit Controller Version Data **20663b1c** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (**S4**). Assuming that CPU **211** detects in **S4** that Flash Light Unit Controller Version Data **20663b1c** of Communication Device **200** is of an old version. CPU **211** sends a New Flash Light Unit Controller Sending Request, which is received by Host H (**S5**). Here, the New Flash Light Unit Controller Sending Request is a request to send Flash Light Unit Controller **H63OSc** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Flash Light Unit Controller **H63OSc** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (**S6**). Upon receiving Flash Light Unit Controller **H63OSc** from Host H (**S7**), CPU **211** stores Flash

Light Unit Controller **H63OSc** as Flash Light Unit Controller **20663OSc** in Operating System **20663OS** (Paragraph [0185]) (**S8**). The old version of Flash Light Unit Controller **20663OSc** (Paragraph [0185]) is deleted.

Paragraph [0203]—This Paragraph [0203] illustrates Indicator Controller Updating Software **H63c1d** (Paragraph [0196]) of Host H (Paragraph [0025]) and Indicator Controller Updating Software **20663c1d** (Paragraph [0190]) of Communication Device **200**, which update Indicator Controller **20663OSd** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Indicator Controller Version Data **20663b1d** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (**S1**). Upon receiving Indicator Controller Version Data **20663b1d** (Paragraph [0189]) from Communication Device **200** (**S2**), Host H compares Indicator Controller Version Data **20663b1d** (Paragraph [0189]) with Indicator Controller Version Data **H63b1d** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (**S3**). Assuming that Host H detects in **S3** that Indicator Controller Version Data **20663b1d** of Communication Device **200** is of an old version. Host H retrieves Indicator Controller **H63OSd**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (**S4**). Upon receiving Indicator Controller **H63OSd** from Host H (**S5**), CPU **211** stores Indicator Controller **H63OSd** as Indicator Controller **20663OSd** in Operating System **20663OS** (Paragraph [0185]) (**S6**). The old version of Indicator Controller **20663OSd** (Paragraph [0185]) is deleted.

Paragraph [0204]—This Paragraph [0204] illustrates another embodiment of Indicator Controller Updating Software **H63c1d** (Paragraph [0196]) of Host H (Paragraph [0025]) and Indicator Controller Updating Software **20663c1d** (Paragraph [0190]) of Communication Device **200**, which update Indicator Controller **20663OSd** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Indicator Controller Update Request, which is received by Host H (**S1**). Here, the Indicator Controller Update Request is a request to send Indicator Controller Version Data **H63b1d** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Indicator Controller Version Data **H63b1d** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (**S2**). Upon receiving Indicator Controller Version Data **H63b1d** from Host H (**S3**), CPU **211** compares Indicator Controller Version Data **H63b1d** with Indicator Controller Version Data **20663b1d** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (**S4**). Assuming that CPU **211** detects in **S4** that Indicator Controller Version Data **20663b1d** of Communication Device **200** is of an old version. CPU **211** sends a New Indicator Controller Sending Request, which is received by Host H (**S5**). Here, the New Indicator Controller Sending Request is a request to send Indicator Controller **H63OSd** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Indicator Controller **H63OSd** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (**S6**). Upon receiving Indicator Controller **H63OSd** from Host H (**S7**), CPU **211** stores Indicator Controller **H63OSd** as Indicator Controller **20663OSd** in Operating System **20663OS**

(Paragraph [0185]) (S8). The old version of Indicator Controller **20663OSd** (Paragraph [0185]) is deleted.

Paragraph [0205]—This Paragraph [0205] illustrates Input Device Controller Updating Software **H63c1e** (Paragraph [0196]) of Host H (Paragraph [0025]) and Input Device Controller Updating Software **20663c1e** (Paragraph [0190]) of Communication Device **200**, which update Input Device Controller **20663OSe** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Input Device Controller Version Data **20663b1e** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Input Device Controller Version Data **20663b1e** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Input Device Controller Version Data **20663b1e** (Paragraph [0189]) with Input Device Controller Version Data **H63b1e** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Input Device Controller Version Data **20663b1e** of Communication Device **200** is of an old version. Host H retrieves Input Device Controller **H63OSe**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Input Device Controller **H63OSe** from Host H (S5), CPU **211** stores Input Device Controller **H63OSe** as Input Device Controller **20663OSe** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Input Device Controller **20663OSe** (Paragraph [0185]) is deleted.

Paragraph [0206]—This Paragraph [0206] illustrates another embodiment of Input Device Controller Updating Software **H63c1e** (Paragraph [0196]) of Host H (Paragraph [0025]) and Input Device Controller Updating Software **20663c1e** (Paragraph [0190]) of Communication Device **200**, which update Input Device Controller **20663OSe** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Input Device Controller Update Request, which is received by Host H (S1). Here, the Input Device Controller Update Request is a request to send Input Device Controller Version Data **H63b1e** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Input Device Controller Version Data **H63b1e** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Input Device Controller Version Data **H63b1e** from Host H (S3), CPU **211** compares Input Device Controller Version Data **H63b1e** with Input Device Controller Version Data **20663b1e** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Input Device Controller Version Data **20663b1e** of Communication Device **200** is of an old version. CPU **211** sends a New Input Device Controller Sending Request, which is received by Host H (S5). Here, the New Input Device Controller Sending Request is a request to send Input Device Controller **H63OSe** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Input Device Controller **H63OSe** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Input Device Controller **H63OSe** from Host H (S7), CPU **211** stores Input Device Controller **H63OSe** as Input Device Controller

20663OSe in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Input Device Controller **20663OSe** (Paragraph [0185]) is deleted.

Paragraph [0207]—This Paragraph [0207] illustrates LCD Controller Updating Software **H63c1f** (Paragraph [0196]) of Host H (Paragraph [0025]) and LCD Controller Updating Software **20663c1f** (Paragraph [0190]) of Communication Device **200**, which update LCD Controller **20663OSf** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves LCD Controller Version Data **20663b1f** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving LCD Controller Version Data **20663b1f** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares LCD Controller Version Data **20663b1f** (Paragraph [0189]) with LCD Controller Version Data **H63b1f** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that LCD Controller Version Data **20663b1f** of Communication Device **200** is of an old version. Host H retrieves LCD Controller **H63OSf**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving LCD Controller **H63OSf** from Host H (S5), CPU **211** stores LCD Controller **H63OSf** as LCD Controller **20663OSf** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of LCD Controller **20663OSf** (Paragraph [0185]) is deleted.

Paragraph [0208]—This Paragraph [0208] illustrates another embodiment of LCD Controller Updating Software **H63c1f** (Paragraph [0196]) of Host H (Paragraph [0025]) and LCD Controller Updating Software **20663c1f** (Paragraph [0190]) of Communication Device **200**, which update LCD Controller **20663OSf** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a LCD Controller Update Request, which is received by Host H (S1). Here, the LCD Controller Update Request is a request to send LCD Controller Version Data **H63b1f** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves LCD Controller Version Data **H63b1f** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving LCD Controller Version Data **H63b1f** from Host H (S3), CPU **211** compares LCD Controller Version Data **H63b1f** with LCD Controller Version Data **20663b1f** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that LCD Controller Version Data **20663b1f** of Communication Device **200** is of an old version. CPU **211** sends a New LCD Controller Sending Request, which is received by Host H (S5). Here, the New LCD Controller Sending Request is a request to send LCD Controller **H63OSf** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves LCD Controller **H63OSf** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving LCD Controller **H63OSf** from Host H (S7), CPU **211** stores LCD Controller **H63OSf** as LCD Controller **20663OSf** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of LCD Controller **20663OSf** (Paragraph [0185]) is deleted.

Paragraph [0209]—This Paragraph [0209] illustrates LED Controller Updating Software **H63c1g** (Paragraph [0196]) of Host H (Paragraph [0025]) and LED Controller Updating

61

Software **20663c1g** (Paragraph [0190]) of Communication Device **200**, which update LED Controller **20663OSg** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves LED Controller Version Data **20663b1g** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving LED Controller Version Data **20663b1g** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares LED Controller Version Data **20663b1g** (Paragraph [0189]) with LED Controller Version Data **H63b1g** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that LED Controller Version Data **20663b1g** of Communication Device **200** is of an old version. Host H retrieves LED Controller **H63OSg**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving LED Controller **H63OSg** from Host H (S5), CPU **211** stores LED Controller **H63OSg** as LED Controller **20663OSg** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of LED Controller **20663OSg** (Paragraph [0185]) is deleted.

Paragraph [0210]—This Paragraph [0210] illustrates another embodiment of LED Controller Updating Software **H63c1g** (Paragraph [0196]) of Host H (Paragraph [0025]) and LED Controller Updating Software **20663c1g** (Paragraph [0190]) of Communication Device **200**, which update LED Controller **20663OSg** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a LED Controller Update Request, which is received by Host H (S1). Here, the LED Controller Update Request is a request to send LED Controller Version Data **H63b1g** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves LED Controller Version Data **H63b1g** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving LED Controller Version Data **H63b1g** from Host H (S3), CPU **211** compares LED Controller Version Data **H63b1g** with LED Controller Version Data **20663b1g** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that LED Controller Version Data **20663b1g** of Communication Device **200** is of an old version. CPU **211** sends a New LED Controller Sending Request, which is received by Host H (S5). Here, the New LED Controller Sending Request is a request to send LED Controller **H63OSg** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves LED Controller **H63OSg** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving LED Controller **H63OSg** from Host H (S7), CPU **211** stores LED Controller **H63OSg** as LED Controller **20663OSg** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of LED Controller **20663OSg** (Paragraph [0185]) is deleted.

Paragraph [0211]—This Paragraph [0211] illustrates Memory Card Interface Controller Updating Software **H63c1h** (Paragraph [0196]) of Host H (Paragraph [0025]) and Memory Card Interface Controller Updating Software **20663c1h** (Paragraph [0190]) of Communication Device **200**, which update Memory Card Interface Controller **20663OSh** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device

62

200 retrieves Memory Card Interface Controller Version Data **20663b1h** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Memory Card Interface Controller Version Data **20663b1h** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Memory Card Interface Controller Version Data **20663b1h** (Paragraph [0189]) with Memory Card Interface Controller Version Data **H63b1h** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Memory Card Interface Controller Version Data **20663b1h** of Communication Device **200** is of an old version. Host H retrieves Memory Card Interface Controller **H63OSh**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Memory Card Interface Controller **H63OSh** from Host H (S5), CPU **211** stores Memory Card Interface Controller **H63OSh** as Memory Card Interface Controller **20663OSh** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Memory Card Interface Controller **20663OSh** (Paragraph [0185]) is deleted.

Paragraph [0212]—This Paragraph [0212] illustrates another embodiment of Memory Card Interface Controller Updating Software **H63c1h** (Paragraph [0196]) of Host H (Paragraph [0025]) and Memory Card Interface Controller Updating Software **20663c1h** (Paragraph [0190]) of Communication Device **200**, which update Memory Card Interface Controller **20663OSh** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Memory Card Interface Controller Update Request, which is received by Host H (S1). Here, the Memory Card Interface Controller Update Request is a request to send Memory Card Interface Controller Version Data **H63b1h** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Memory Card Interface Controller Version Data **H63b1h** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Memory Card Interface Controller Version Data **H63b1h** from Host H (S3), CPU **211** compares Memory Card Interface Controller Version Data **H63b1h** with Memory Card Interface Controller Version Data **20663b1h** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Memory Card Interface Controller Version Data **20663b1h** of Communication Device **200** is of an old version. CPU **211** sends a New Memory Card Interface Controller Sending Request, which is received by Host H (S5). Here, the New Memory Card Interface Controller Sending Request is a request to send Memory Card Interface Controller **H63OSh** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Memory Card Interface Controller **H63OSh** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Memory Card Interface Controller **H63OSh** from Host H (S7), CPU **211** stores Memory Card Interface Controller **H63OSh** as Memory Card Interface Controller **20663OSh** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Memory Card Interface Controller **20663OSh** (Paragraph [0185]) is deleted.

Paragraph [0213]—This Paragraph [0213] illustrates Microphone Controller Updating Software **H63c1i** (Paragraph [0196]) of Host H (Paragraph [0025]) and Microphone

Controller Updating Software **20663c1i** (Paragraph [0190]) of Communication Device **200**, which update Microphone Controller **20663OSi** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Microphone Controller Version Data **20663b1i** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Microphone Controller Version Data **20663b1i** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Microphone Controller Version Data **20663b1i** (Paragraph [0189]) with Microphone Controller Version Data **H63b1i** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Microphone Controller Version Data **20663b1i** of Communication Device **200** is of an old version. Host H retrieves Microphone Controller **H63OSi**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Microphone Controller **H63OSi** from Host H (S5), CPU **211** stores Microphone Controller **H63OSi** as Microphone Controller **20663OSi** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Microphone Controller **20663OSi** (Paragraph [0185]) is deleted.

Paragraph [0214]—This Paragraph [0214] illustrates another embodiment of Microphone Controller Updating Software **H63c1i** (Paragraph [0196]) of Host H (Paragraph [0025]) and Microphone Controller Updating Software **20663c1i** (Paragraph [0190]) of Communication Device **200**, which update Microphone Controller **20663OSi** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Microphone Controller Update Request, which is received by Host H (S1). Here, the Microphone Controller Update Request is a request to send Microphone Controller Version Data **H63b1i** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Microphone Controller Version Data **H63b1i** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Microphone Controller Version Data **H63b1i** from Host H (S3), CPU **211** compares Microphone Controller Version Data **H63b1i** with Microphone Controller Version Data **20663b1i** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Microphone Controller Version Data **20663b1i** of Communication Device **200** is of an old version. CPU **211** sends a New Microphone Controller Sending Request, which is received by Host H (S5). Here, the New Microphone Controller Sending Request is a request to send Microphone Controller **H63OSi** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Microphone Controller **H63OSi** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Microphone Controller **H63OSi** from Host H (S7), CPU **211** stores Microphone Controller **H63OSi** as Microphone Controller **20663OSi** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Microphone Controller **20663OSi** (Paragraph [0185]) is deleted.

Paragraph [0215]—This Paragraph [0215] illustrates Photometer Controller Updating Software **H63c1j** (Paragraph [0196]) of Host H (Paragraph [0025]) and Photometer Controller Updating Software **20663c1j** (Paragraph [0190]) of

Communication Device **200**, which update Photometer Controller **20663OSj** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Photometer Controller Version Data **20663b1j** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Photometer Controller Version Data **20663b1j** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Photometer Controller Version Data **20663b1j** (Paragraph [0189]) with Photometer Controller Version Data **H63b1j** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Photometer Controller Version Data **20663b1j** of Communication Device **200** is of an old version. Host H retrieves Photometer Controller **H63OSj**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Photometer Controller **H63OSj** from Host H (S5), CPU **211** stores Photometer Controller **H63OSj** as Photometer Controller **20663OSj** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Photometer Controller **20663OSj** (Paragraph [0185]) is deleted.

Paragraph [0216]—This Paragraph [0216] illustrates another embodiment of Photometer Controller Updating Software **H63c1j** (Paragraph [0196]) of Host H (Paragraph [0025]) and Photometer Controller Updating Software **20663c1j** (Paragraph [0190]) of Communication Device **200**, which update Photometer Controller **20663OSj** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Photometer Controller Update Request, which is received by Host H (S1). Here, the Photometer Controller Update Request is a request to send Photometer Controller Version Data **H63b1j** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Photometer Controller Version Data **H63b1j** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Photometer Controller Version Data **H63b1j** from Host H (S3), CPU **211** compares Photometer Controller Version Data **H63b1j** with Photometer Controller Version Data **20663b1j** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Photometer Controller Version Data **20663b1j** of Communication Device **200** is of an old version. CPU **211** sends a New Photometer Controller Sending Request, which is received by Host H (S5). Here, the New Photometer Controller Sending Request is a request to send Photometer Controller **H63OSj** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Photometer Controller **H63OSj** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Photometer Controller **H63OSj** from Host H (S7), CPU **211** stores Photometer Controller **H63OSj** as Photometer Controller **20663OSj** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Photometer Controller **20663OSj** (Paragraph [0185]) is deleted.

Paragraph [0217]—This Paragraph [0217] illustrates RAM Controller Updating Software **H63c1k** (Paragraph [0196]) of Host H (Paragraph [0025]) and RAM Controller Updating Software **20663c1k** (Paragraph [0190]) of Communication Device **200**, which update RAM Controller

20663OSk stored in Operating System 20663OS (Paragraph [0185]) of Communication Device 200. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 retrieves RAM Controller Version Data 20663b1k from OS Version Data Storage Area 20663b1 (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving RAM Controller Version Data 20663b1k (Paragraph [0189]) from Communication Device 200 (S2), Host H compares RAM Controller Version Data 20663b1k (Paragraph [0189]) with RAM Controller Version Data H63b1k stored in OS Version Data Storage Area H63b1 (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that RAM Controller Version Data 20663b1k of Communication Device 200 is of an old version. Host H retrieves RAM Controller H63OSk, which is of the latest version, from Operating System Storage Area H63OS (Paragraph [0192]), and sends the controller to Communication Device 200 (S4). Upon receiving RAM Controller H63OSk from Host H (S5), CPU 211 stores RAM Controller H63OSk as RAM Controller 20663OSk in Operating System 20663OS (Paragraph [0185]) (S6). The old version of RAM Controller 20663OSk (Paragraph [0185]) is deleted.

Paragraph [0218]—This Paragraph [0218] illustrates another embodiment of RAM Controller Updating Software H63c1k (Paragraph [0196]) of Host H (Paragraph [0025]) and RAM Controller Updating Software 20663c1k (Paragraph [0190]) of Communication Device 200, which update RAM Controller 20663OSk stored in Operating System 20663OS (Paragraph [0185]) of Communication Device 200. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 sends a RAM Controller Update Request, which is received by Host H (S1). Here, the RAM Controller Update Request is a request to send RAM Controller Version Data H63b1k (Paragraph [0195]) stored in Host H to Communication Device 200. In response to the request, Host H retrieves RAM Controller Version Data H63b1k from OS Version Data Storage Area H63b1 (Paragraph [0195]), and sends the data to Communication Device 200 (S2). Upon receiving RAM Controller Version Data H63b1k from Host H (S3), CPU 211 compares RAM Controller Version Data H63b1k with RAM Controller Version Data 20663b1k stored in OS Version Data Storage Area 20663b1 (Paragraph [0189]) of Communication Device 200 (S4). Assuming that CPU211 detects in S4 that RAM Controller Version Data 20663b1k of Communication Device 200 is of an old version. CPU 211 sends a New RAM Controller Sending Request, which is received by Host H (S5). Here, the New RAM Controller Sending Request is a request to send RAM Controller H63OSk (Paragraph [0192]) stored in Host H to Communication Device 200. Host H retrieves RAM Controller H63OSk (Paragraph [0192]), which is of the latest version, from Operating System Storage Area H63OS (Paragraph [0192]), and sends the controller to Communication Device 200 (S6). Upon receiving RAM Controller H63OSk from Host H (S7), CPU 211 stores RAM Controller H63OSk as RAM Controller 20663OSk in Operating System 20663OS (Paragraph [0185]) (S8). The old version of RAM Controller 20663OSk (Paragraph [0185]) is deleted.

Paragraph [0219]—This Paragraph [0219] illustrates ROM Controller Updating Software H63c1l (Paragraph [0196]) of Host H (Paragraph [0025]) and ROM Controller Updating Software 20663c1l (Paragraph [0190]) of Communication Device 200, which update ROM Controller 20663OSl stored in Operating System 20663OS (Paragraph [0185]) of Communication Device 200. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 retrieves ROM Controller Version Data 20663b1l from

OS Version Data Storage Area 20663b1 (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving ROM Controller Version Data 20663b1l (Paragraph [0189]) from Communication Device 200 (S2), Host H compares ROM Controller Version Data 20663b1l (Paragraph [0189]) with ROM Controller Version Data H63b1l stored in OS Version Data Storage Area H63b1 (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that ROM Controller Version Data 20663b1l of Communication Device 200 is of an old version. Host H retrieves ROM Controller H63OSl, which is of the latest version, from Operating System Storage Area H63OS (Paragraph [0192]), and sends the controller to Communication Device 200 (S4). Upon receiving ROM Controller H63OSl from Host H (S5), CPU 211 stores ROM Controller H63OSl as ROM Controller 20663OSl in Operating System 20663OS (Paragraph [0185]) (S6). The old version of ROM Controller 20663OSl (Paragraph [0185]) is deleted.

Paragraph [0220]—This Paragraph [0220] illustrates another embodiment of ROM Controller Updating Software H63c1l (Paragraph [0196]) of Host H (Paragraph [0025]) and ROM Controller Updating Software 20663c1l (Paragraph [0190]) of Communication Device 200, which update ROM Controller 20663OSl stored in Operating System 20663OS (Paragraph [0185]) of Communication Device 200. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 sends a ROM Controller Update Request, which is received by Host H (S1). Here, the ROM Controller Update Request is a request to send ROM Controller Version Data H63b1l (Paragraph [0195]) stored in Host H to Communication Device 200. In response to the request, Host H retrieves ROM Controller Version Data H63b1l from OS Version Data Storage Area H63b1 (Paragraph [0195]), and sends the data to Communication Device 200 (S2). Upon receiving ROM Controller Version Data H63b1l from Host H (S3), CPU 211 compares ROM Controller Version Data H63b1l with ROM Controller Version Data 20663b1l stored in OS Version Data Storage Area 20663b1 (Paragraph [0189]) of Communication Device 200 (S4). Assuming that CPU211 detects in S4 that ROM Controller Version Data 20663b1l of Communication Device 200 is of an old version. CPU 211 sends a New ROM Controller Sending Request, which is received by Host H (S5). Here, the New ROM Controller Sending Request is a request to send ROM Controller H63OSl (Paragraph [0192]) stored in Host H to Communication Device 200. Host H retrieves ROM Controller H63OSl (Paragraph [0192]), which is of the latest version, from Operating System Storage Area H63OS (Paragraph [0192]), and sends the controller to Communication Device 200 (S6). Upon receiving ROM Controller H63OSl from Host H (S7), CPU 211 stores ROM Controller H63OSl as ROM Controller 20663OSl in Operating System 20663OS (Paragraph [0185]) (S8). The old version of ROM Controller 20663OSl (Paragraph [0185]) is deleted.

Paragraph [0221]—This Paragraph [0221] illustrates Signal Processor Controller Updating Software H63c1m (Paragraph [0196]) of Host H (Paragraph [0025]) and Signal Processor Controller Updating Software 20663c1m (Paragraph [0190]) of Communication Device 200, which update Signal Processor Controller 20663OSm stored in Operating System 20663OS (Paragraph [0185]) of Communication Device 200. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 retrieves Signal Processor Controller Version Data 20663b1m from OS Version Data Storage Area 20663b1 (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Signal Processor Controller Version Data 20663b1m (Paragraph [0189]) from Communication Device 200 (S2), Host H compares Signal Processor Control-

ler Version Data **20663b1m** (Paragraph [0189]) with Signal Processor Controller Version Data **H63b1m** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (**S3**). Assuming that Host H detects in **S3** that Signal Processor Controller Version Data **20663b1m** of Communication Device **200** is of an old version. Host H retrieves Signal Processor Controller **H63OSm**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (**S4**). Upon receiving Signal Processor Controller **H63OSm** from Host H (**S5**), CPU **211** stores Signal Processor Controller **H63OSm** as Signal Processor Controller **20663OSm** in Operating System **20663OS** (Paragraph [0185]) (**S6**). The old version of Signal Processor Controller **20663OSm** (Paragraph [0185]) is deleted.

Paragraph [0222]—This Paragraph [0222] illustrates another embodiment of Signal Processor Controller Updating Software **H63c1m** (Paragraph [0196]) of Host H (Paragraph [0025]) and Signal Processor Controller Updating Software **20663c1m** (Paragraph [0190]) of Communication Device **200**, which update Signal Processor Controller **20663OSm** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Signal Processor Controller Update Request, which is received by Host H (**S1**). Here, the Signal Processor Controller Update Request is a request to send Signal Processor Controller Version Data **H63b1m** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Signal Processor Controller Version Data **H63b1m** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (**S2**). Upon receiving Signal Processor Controller Version Data **H63b1m** from Host H (**S3**), CPU **211** compares Signal Processor Controller Version Data **H63b1m** with Signal Processor Controller Version Data **20663b1m** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (**S4**). Assuming that CPU **211** detects in **S4** that Signal Processor Controller Version Data **20663b1m** of Communication Device **200** is of an old version. CPU **211** sends a New Signal Processor Controller Sending Request, which is received by Host H (**S5**). Here, the New Signal Processor Controller Sending Request is a request to send Signal Processor Controller **H63OSm** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Signal Processor Controller **H63OSm** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (**S6**). Upon receiving Signal Processor Controller **H63OSm** from Host H (**S7**), CPU **211** stores Signal Processor Controller **H63OSm** as Signal Processor Controller **20663OSm** in Operating System **20663OS** (Paragraph [0185]) (**S8**). The old version of Signal Processor Controller **20663OSm** (Paragraph [0185]) is deleted.

Paragraph [0223]—This Paragraph [0223] illustrates Signal Processor Controller Updating Software **H63c1n** (Paragraph [0196]) of Host H (Paragraph [0025]) and Signal Processor Controller Updating Software **20663c1n** (Paragraph [0190]) of Communication Device **200**, which update Signal Processor Controller **20663OSn** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Signal Processor Controller Version Data **20663b1n** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (**S1**). Upon receiving Signal Processor Controller Version

Data **20663b1n** (Paragraph [0189]) from Communication Device **200** (**S2**), Host H compares Signal Processor Controller Version Data **20663b1n** (Paragraph [0189]) with Signal Processor Controller Version Data **H63b1n** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (**S3**). Assuming that Host H detects in **S3** that Signal Processor Controller Version Data **20663b1n** of Communication Device **200** is of an old version. Host H retrieves Signal Processor Controller **H63OSn**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (**S4**). Upon receiving Signal Processor Controller **H63OSn** from Host H (**S5**), CPU **211** stores Signal Processor Controller **H63OSn** as Signal Processor Controller **20663OSn** in Operating System **20663OS** (Paragraph [0185]) (**S6**). The old version of Signal Processor Controller **20663OSn** (Paragraph [0185]) is deleted.

Paragraph [0224]—This Paragraph [0224] illustrates another embodiment of Signal Processor Controller Updating Software **H63c1n** (Paragraph [0196]) of Host H (Paragraph [0025]) and Signal Processor Controller Updating Software **20663c1n** (Paragraph [0190]) of Communication Device **200**, which update Signal Processor Controller **20663OSn** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Signal Processor Controller Update Request, which is received by Host H (**S1**). Here, the Signal Processor Controller Update Request is a request to send Signal Processor Controller Version Data **H63b1n** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Signal Processor Controller Version Data **H63b1n** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (**S2**). Upon receiving Signal Processor Controller Version Data **H63b1n** from Host H (**S3**), CPU **211** compares Signal Processor Controller Version Data **H63b1n** with Signal Processor Controller Version Data **20663b1n** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (**S4**). Assuming that CPU **211** detects in **S4** that Signal Processor Controller Version Data **20663b1n** of Communication Device **200** is of an old version. CPU **211** sends a New Signal Processor Controller Sending Request, which is received by Host H (**S5**). Here, the New Signal Processor Controller Sending Request is a request to send Signal Processor Controller **H63OSn** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Signal Processor Controller **H63OSn** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (**S6**). Upon receiving Signal Processor Controller **H63OSn** from Host H (**S7**), CPU **211** stores Signal Processor Controller **H63OSn** as Signal Processor Controller **20663OSn** in Operating System **20663OS** (Paragraph [0185]) (**S8**). The old version of Signal Processor Controller **20663OSn** (Paragraph [0185]) is deleted.

Paragraph [0225]—This Paragraph [0225] illustrates Solar Panel Controller Updating Software **H63c1o** (Paragraph [0196]) of Host H (Paragraph [0025]) and Solar Panel Controller Updating Software **20663c1o** (Paragraph [0190]) of Communication Device **200**, which update Solar Panel Controller **20663OSo** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Solar Panel Controller Version Data **20663b1o** from OS Version Data Storage Area **20663b1**

(Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Solar Panel Controller Version Data **20663b1o** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Solar Panel Controller Version Data **20663b1o** (Paragraph [0189]) with Solar Panel Controller Version Data **H63b1o** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3).

Assuming that Host H detects in S3 that Solar Panel Controller Version Data **20663b1o** of Communication Device **200** is of an old version. Host H retrieves Solar Panel Controller **H63OSo**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Solar Panel Controller **H63OSo** from Host H (S5), CPU **211** stores Solar Panel Controller **H63OSo** as Solar Panel Controller **20663OSo** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Solar Panel Controller **20663OSo** (Paragraph [0185]) is deleted.

Paragraph [0226]—This Paragraph [0226] illustrates another embodiment of Solar Panel Controller Updating Software **H63c1o** (Paragraph [0196]) of Host H (Paragraph [0025]) and Solar Panel Controller Updating Software **20663c1o** (Paragraph [0190]) of Communication Device **200**, which update Solar Panel Controller **20663OSo** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Solar Panel Controller Update Request, which is received by Host H (S1). Here, the Solar Panel Controller Update Request is a request to send Solar Panel Controller Version Data **H63b1o** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Solar Panel Controller Version Data **H63b1o** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Solar Panel Controller Version Data **H63b1o** from Host H (S3), CPU **211** compares Solar Panel Controller Version Data **H63b1o** with Solar Panel Controller Version Data **20663b1o** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Solar Panel Controller Version Data **20663b1o** of Communication Device **200** is of an old version. CPU **211** sends a New Solar Panel Controller Sending Request, which is received by Host H (S5). Here, the New Solar Panel Controller Sending Request is a request to send Solar Panel Controller **H63OSo** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Solar Panel Controller **H63OSo** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Solar Panel Controller **H63OSo** from Host H (S7), CPU **211** stores Solar Panel Controller **H63OSo** as Solar Panel Controller **20663OSo** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Solar Panel Controller **20663OSo** (Paragraph [0185]) is deleted.

Paragraph [0227]—This Paragraph [0227] illustrates Speaker Controller Updating Software **H63c1p** (Paragraph [0196]) of Host H (Paragraph [0025]) and Speaker Controller Updating Software **20663c1p** (Paragraph [0190]) of Communication Device **200**, which update Speaker Controller **20663OSp** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Speaker Controller Version Data **20663b1p** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving

Speaker Controller Version Data **20663b1p** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Speaker Controller Version Data **20663b1p** (Paragraph [0189]) with Speaker Controller Version Data **H63b1p** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Speaker Controller Version Data **20663b1p** of Communication Device **200** is of an old version. Host H retrieves Speaker Controller **H63OSp**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Speaker Controller **H63OSp** from Host H (S5), CPU **211** stores Speaker Controller **H63OSp** as Speaker Controller **20663OSp** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Speaker Controller **20663OSp** (Paragraph [0185]) is deleted.

Paragraph [0228]—This Paragraph [0228] illustrates another embodiment of Speaker Controller Updating Software **H63c1p** (Paragraph [0196]) of Host H (Paragraph [0025]) and Speaker Controller Updating Software **20663c1p** (Paragraph [0190]) of Communication Device **200**, which update Speaker Controller **20663OSp** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Speaker Controller Update Request, which is received by Host H (S1). Here, the Speaker Controller Update Request is a request to send Speaker Controller Version Data **H63b1p** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Speaker Controller Version Data **H63b1p** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Speaker Controller Version Data **H63b1p** from Host H (S3), CPU **211** compares Speaker Controller Version Data **H63b1p** with Speaker Controller Version Data **20663b1p** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Speaker Controller Version Data **20663b1p** of Communication Device **200** is of an old version. CPU **211** sends a New Speaker Controller Sending Request, which is received by Host H (S5). Here, the New Speaker Controller Sending Request is a request to send Speaker Controller **H63OSp** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Speaker Controller **H63OSp** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Speaker Controller **H63OSp** from Host H (S7), CPU **211** stores Speaker Controller **H63OSp** as Speaker Controller **20663OSp** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Speaker Controller **20663OSp** (Paragraph [0185]) is deleted.

Paragraph [0229]—This Paragraph [0229] illustrates Vibrator Controller Updating Software **H63c1q** (Paragraph [0196]) of Host H (Paragraph [0025]) and Vibrator Controller Updating Software **20663c1q** (Paragraph [0190]) of Communication Device **200**, which update Vibrator Controller **20663OSq** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Vibrator Controller Version Data **20663b1q** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Vibrator Controller Version Data **20663b1q** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Vibrator Controller Version Data **20663b1q** (Paragraph

[0189]) with Vibrator Controller Version Data **H63b1q** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Vibrator Controller Version Data **20663b1q** of Communication Device **200** is of an old version. Host H retrieves Vibrator Controller **H63OSq**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Vibrator Controller **H63OSq** from Host H (S5), CPU **211** stores Vibrator Controller **H63OSq** as Vibrator Controller **20663OSq** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Vibrator Controller **20663OSq** (Paragraph [0185]) is deleted.

Paragraph [0230]—This Paragraph [0230] illustrates another embodiment of Vibrator Controller Updating Software **H63c1q** (Paragraph [0196]) of Host H (Paragraph [0025]) and Vibrator Controller Updating Software **20663c1q** (Paragraph [0190]) of Communication Device **200**, which update Vibrator Controller **20663OSq** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Vibrator Controller Update Request, which is received by Host H (S1). Here, the Vibrator Controller Update Request is a request to send Vibrator Controller Version Data **H63b1q** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Vibrator Controller Version Data **H63b1q** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Vibrator Controller Version Data **H63b1q** from Host H (S3), CPU **211** compares Vibrator Controller Version Data **H63b1q** with Vibrator Controller Version Data **20663b1q** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Vibrator Controller Version Data **20663b1q** of Communication Device **200** is of an old version. CPU **211** sends a New Vibrator Controller Sending Request, which is received by Host H (S5). Here, the New Vibrator Controller Sending Request is a request to send Vibrator Controller **H63OSq** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Vibrator Controller **H63OSq** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Vibrator Controller **H63OSq** from Host H (S7), CPU **211** stores Vibrator Controller **H63OSq** as Vibrator Controller **20663OSq** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Vibrator Controller **20663OSq** (Paragraph [0185]) is deleted.

Paragraph [0231]—This Paragraph [0231] illustrates Video Processor Controller Updating Software **H63c1r** (Paragraph [0196]) of Host H (Paragraph [0025]) and Video Processor Controller Updating Software **20663c1r** (Paragraph [0190]) of Communication Device **200**, which update Video Processor Controller **20663OSr** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Video Processor Controller Version Data **20663b1r** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Video Processor Controller Version Data **20663b1r** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Video Processor Controller Version Data **20663b1r** (Paragraph [0189]) with Video Processor Controller Version Data **H63b1r** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H

(S3). Assuming that Host H detects in S3 that Video Processor Controller Version Data **20663b1r** of Communication Device **200** is of an old version. Host H retrieves Video Processor Controller **H63OSr**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Video Processor Controller **H63OSr** from Host H (S5), CPU **211** stores Video Processor Controller **H63OSr** as Video Processor Controller **20663OSr** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Video Processor Controller **20663OSr** (Paragraph [0185]) is deleted.

Paragraph [0232]—This Paragraph [0232] illustrates another embodiment of Video Processor Controller Updating Software **H63c1r** (Paragraph [0196]) of Host H (Paragraph [0025]) and Video Processor Controller Updating Software **20663c1r** (Paragraph [0190]) of Communication Device **200**, which update Video Processor Controller **20663OSr** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Video Processor Controller Update Request, which is received by Host H (S1). Here, the Video Processor Controller Update Request is a request to send Video Processor Controller Version Data **H63b1r** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Video Processor Controller Version Data **H63b1r** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Video Processor Controller Version Data **H63b1r** from Host H (S3), CPU **211** compares Video Processor Controller Version Data **H63b1r** with Video Processor Controller Version Data **20663b1r** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Video Processor Controller Version Data **20663b1r** of Communication Device **200** is of an old version. CPU **211** sends a New Video Processor Controller Sending Request, which is received by Host H (S5). Here, the New Video Processor Controller Sending Request is a request to send Video Processor Controller **H63OSr** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Video Processor Controller **H63OSr** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Video Processor Controller **H63OSr** from Host H (S7), CPU **211** stores Video Processor Controller **H63OSr** as Video Processor Controller **20663OSr** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Video Processor Controller **20663OSr** (Paragraph [0185]) is deleted.

Paragraph [0233]—This Paragraph [0233] illustrates Wireless Receiver Controller Updating Software **H63c1s** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Receiver Controller Updating Software **20663c1s** (Paragraph [0190]) of Communication Device **200**, which update Wireless Receiver Controller **20663OSs** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Wireless Receiver Controller Version Data **20663b1s** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Wireless Receiver Controller Version Data **20663b1s** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Wireless Receiver Controller Version Data **20663b1s** (Paragraph [0189]) with Wireless Receiver Controller Version Data **H63b1s** stored in OS

Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Wireless Receiver Controller Version Data **20663b1s** of Communication Device **200** is of an old version. Host H retrieves Wireless Receiver Controller **H63OSs**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Wireless Receiver Controller **H63OSs** from Host H (S5), CPU **211** stores Wireless Receiver Controller **H63OSs** as Wireless Receiver Controller **20663OSs** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Wireless Receiver Controller **20663OSs** (Paragraph [0185]) is deleted.

Paragraph [0234]—This Paragraph [0234] illustrates another embodiment of Wireless Receiver Controller Updating Software **H63c1s** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Receiver Controller Updating Software **20663c1s** (Paragraph [0190]) of Communication Device **200**, which update Wireless Receiver Controller **20663OSs** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Wireless Receiver Controller Update Request#1, which is received by Host H (S1). Here, the Wireless Receiver Controller Update Request#1 is a request to send Wireless Receiver Controller Version Data **H63b1s** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Wireless Receiver Controller Version Data **H63b1s** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Wireless Receiver Controller Version Data **H63b1s** from Host H (S3), CPU **211** compares Wireless Receiver Controller Version Data **H63b1s** with Wireless Receiver Controller Version Data **20663b1s** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Wireless Receiver Controller Version Data **20663b1s** of Communication Device **200** is of an old version. CPU **211** sends a New Wireless Receiver Controller Sending Request#1, which is received by Host H (S5). Here, the New Wireless Receiver Controller Sending Request#1 is a request to send Wireless Receiver Controller **H63OSs** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Wireless Receiver Controller **H63OSs** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Wireless Receiver Controller **H63OSs** from Host H (S7), CPU **211** stores Wireless Receiver Controller **H63OSs** as Wireless Receiver Controller **20663OSs** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Wireless Receiver Controller **20663OSs** (Paragraph [0185]) is deleted.

Paragraph [0235]—This Paragraph [0235] illustrates Wireless Receiver Controller Updating Software **H63c1t** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Receiver Controller Updating Software **20663c1t** (Paragraph [0190]) of Communication Device **200**, which update Wireless Receiver Controller **20663OST** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Wireless Receiver Controller Version Data **20663b1t** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Wireless Receiver Controller Version Data **20663b1t** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Wireless Receiver Con-

troller Version Data **20663b1t** (Paragraph [0189]) with Wireless Receiver Controller Version Data **H63b1t** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Wireless Receiver Controller Version Data **20663b1t** of Communication Device **200** is of an old version. Host H retrieves Wireless Receiver Controller **H63OST**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Wireless Receiver Controller **H63OST** from Host H (S5), CPU **211** stores Wireless Receiver Controller **H63OST** as Wireless Receiver Controller **20663OST** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Wireless Receiver Controller **20663OST** (Paragraph [0185]) is deleted.

Paragraph [0236]—This Paragraph [0236] illustrates another embodiment of Wireless Receiver Controller Updating Software **H63c1t** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Receiver Controller Updating Software **20663c1t** (Paragraph [0190]) of Communication Device **200**, which update Wireless Receiver Controller **20663OST** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Wireless Receiver Controller Update Request#2, which is received by Host H (S1). Here, the Wireless Receiver Controller Update Request#2 is a request to send Wireless Receiver Controller Version Data **H63b1t** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Wireless Receiver Controller Version Data **H63b1t** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Wireless Receiver Controller Version Data **H63b1t** from Host H (S3), CPU **211** compares Wireless Receiver Controller Version Data **H63b1t** with Wireless Receiver Controller Version Data **20663b1t** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Wireless Receiver Controller Version Data **20663b1t** of Communication Device **200** is of an old version. CPU **211** sends a New Wireless Receiver Controller Sending Request#2, which is received by Host H (S5). Here, the New Wireless Receiver Controller Sending Request#2 is a request to send Wireless Receiver Controller **H63OST** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Wireless Receiver Controller **H63OST** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Wireless Receiver Controller **H63OST** from Host H (S7), CPU **211** stores Wireless Receiver Controller **H63OST** as Wireless Receiver Controller **20663OST** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Wireless Receiver Controller **20663OST** (Paragraph [0185]) is deleted.

Paragraph [0237]—This Paragraph [0237] illustrates Wireless Receiver Controller Updating Software **H63c1u** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Receiver Controller Updating Software **20663c1u** (Paragraph [0190]) of Communication Device **200**, which update Wireless Receiver Controller **20663OSu** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Wireless Receiver Controller Version Data **20663b1u** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Wireless Receiver Controller Version

Data **20663b1u** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Wireless Receiver Controller Version Data **20663b1u** (Paragraph [0189]) with Wireless Receiver Controller Version Data **H63b1u** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Wireless Receiver Controller Version Data **20663b1u** of Communication Device **200** is of an old version. Host H retrieves Wireless Receiver Controller **H63OSu**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Wireless Receiver Controller **H63OSu** from Host H (S5), CPU **211** stores Wireless Receiver Controller **H63OSu** as Wireless Receiver Controller **20663OSu** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Wireless Receiver Controller **20663OSu** (Paragraph [0185]) is deleted.

Paragraph [0238]—This Paragraph [0238] illustrates another embodiment of Wireless Receiver Controller Updating Software **H63c1u** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Receiver Controller Updating Software **20663c1u** (Paragraph [0190]) of Communication Device **200**, which update Wireless Receiver Controller **20663OSu** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Wireless Receiver Controller Update Request#3, which is received by Host H (S1). Here, the Wireless Receiver Controller Update Request#3 is a request to send Wireless Receiver Controller Version Data **H63b1u** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Wireless Receiver Controller Version Data **H63b1u** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Wireless Receiver Controller Version Data **H63b1u** from Host H (S3), CPU **211** compares Wireless Receiver Controller Version Data **H63b1u** with Wireless Receiver Controller Version Data **20663b1u** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Wireless Receiver Controller Version Data **20663b1u** of Communication Device **200** is of an old version. CPU **211** sends a New Wireless Receiver Controller Sending Request#3, which is received by Host H (S5). Here, the New Wireless Receiver Controller Sending Request#3 is a request to send Wireless Receiver Controller **H63OSu** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Wireless Receiver Controller **H63OSu** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Wireless Receiver Controller **H63OSu** from Host H (S7), CPU **211** stores Wireless Receiver Controller **H63OSu** as Wireless Receiver Controller **20663OSu** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Wireless Receiver Controller **20663OSu** (Paragraph [0185]) is deleted.

Paragraph [0239]—This Paragraph [0239] illustrates Wireless Transmitter Controller Updating Software **H63c1v** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Transmitter Controller Updating Software **20663c1v** (Paragraph [0190]) of Communication Device **200**, which update Wireless Transmitter Controller **20663OSv** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Wireless

Transmitter Controller Version Data **20663b1v** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Wireless Transmitter Controller Version Data **20663b1v** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Wireless Transmitter Controller Version Data **20663b1v** (Paragraph [0189]) with Wireless Transmitter Controller Version Data **H63b1v** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Wireless Transmitter Controller Version Data **20663b1v** of Communication Device **200** is of an old version. Host H retrieves Wireless Transmitter Controller **H63OSv**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Wireless Transmitter Controller **H63OSv** from Host H (S5), CPU **211** stores Wireless Transmitter Controller **H63OSv** as Wireless Transmitter Controller **20663OSv** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Wireless Transmitter Controller **20663OSv** (Paragraph [0185]) is deleted.

Paragraph [0240]—This Paragraph [0240] illustrates another embodiment of Wireless Transmitter Controller Updating Software **H63c1v** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Transmitter Controller Updating Software **20663c1v** (Paragraph [0190]) of Communication Device **200**, which update Wireless Transmitter Controller **20663OSv** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Wireless Transmitter Controller Update Request#1, which is received by Host H (S1). Here, the Wireless Transmitter Controller Update Request#1 is a request to send Wireless Transmitter Controller Version Data **H63b1v** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Wireless Transmitter Controller Version Data **H63b1v** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Wireless Transmitter Controller Version Data **H63b1v** from Host H (S3), CPU **211** compares Wireless Transmitter Controller Version Data **H63b1v** with Wireless Transmitter Controller Version Data **20663b1v** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Wireless Transmitter Controller Version Data **20663b1v** of Communication Device **200** is of an old version. CPU **211** sends a New Wireless Transmitter Controller Sending Request#1, which is received by Host H (S5). Here, the New Wireless Transmitter Controller Sending Request#1 is a request to send Wireless Transmitter Controller **H63OSv** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Wireless Transmitter Controller **H63OSv** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Wireless Transmitter Controller **H63OSv** from Host H (S7), CPU **211** stores Wireless Transmitter Controller **H63OSv** as Wireless Transmitter Controller **20663OSv** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Wireless Transmitter Controller **20663OSv** (Paragraph [0185]) is deleted.

Paragraph [0241]—This Paragraph [0241] illustrates Wireless Transmitter Controller Updating Software **H63c1w** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Transmitter Controller Updating Software **20663c1w** (Paragraph [0190]) of Communication Device **200**, which

update Wireless Transmitter Controller **20663OSw** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Wireless Transmitter Controller Version Data **20663b1w** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Wireless Transmitter Controller Version Data **20663b1w** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Wireless Transmitter Controller Version Data **20663b1w** (Paragraph [0189]) with Wireless Transmitter Controller Version Data **H63b1w** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Wireless Transmitter Controller Version Data **20663b1w** of Communication Device **200** is of an old version. Host H retrieves Wireless Transmitter Controller **H63OSw**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Wireless Transmitter Controller **H63OSw** from Host H (S5), CPU **211** stores Wireless Transmitter Controller **H63OSw** as Wireless Transmitter Controller **20663OSw** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Wireless Transmitter Controller **20663OSw** (Paragraph [0185]) is deleted.

Paragraph [0242]—This Paragraph [0242] illustrates another embodiment of Wireless Transmitter Controller Updating Software **H63c1w** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Transmitter Controller Updating Software **20663c1w** (Paragraph [0190]) of Communication Device **200**, which update Wireless Transmitter Controller **20663OSw** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Wireless Transmitter Controller Update Request#2, which is received by Host H (S1). Here, the Wireless Transmitter Controller Update Request#2 is a request to send Wireless Transmitter Controller Version Data **H63b1w** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Wireless Transmitter Controller Version Data **H63b1w** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Wireless Transmitter Controller Version Data **H63b1w** from Host H (S3), CPU **211** compares Wireless Transmitter Controller Version Data **H63b1w** with Wireless Transmitter Controller Version Data **20663b1w** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Wireless Transmitter Controller Version Data **20663b1w** of Communication Device **200** is of an old version. CPU **211** sends a New Wireless Transmitter Controller Sending Request#2, which is received by Host H (S5). Here, the New Wireless Transmitter Controller Sending Request#2 is a request to send Wireless Transmitter Controller **H63OSw** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Wireless Transmitter Controller **H63OSw** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Wireless Transmitter Controller **H63OSw** from Host H (S7), CPU **211** stores Wireless Transmitter Controller **H63OSw** as Wireless Transmitter Controller **20663OSw** in Operating System **20663OS** (Paragraph [0185]) (S8). The old version of Wireless Transmitter Controller **20663OSw** (Paragraph [0185]) is deleted.

Paragraph [0243]—This Paragraph [0243] illustrates Wireless Transmitter Controller Updating Software **H63c1x** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Transmitter Controller Updating Software **20663c1x** (Paragraph [0190]) of Communication Device **200**, which update Wireless Transmitter Controller **20663OSx** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves Wireless Transmitter Controller Version Data **20663b1x** from OS Version Data Storage Area **20663b1** (Paragraph [0189]) and sends the data to Host H (S1). Upon receiving Wireless Transmitter Controller Version Data **20663b1x** (Paragraph [0189]) from Communication Device **200** (S2), Host H compares Wireless Transmitter Controller Version Data **20663b1x** (Paragraph [0189]) with Wireless Transmitter Controller Version Data **H63b1x** stored in OS Version Data Storage Area **H63b1** (Paragraph [0195]) of Host H (S3). Assuming that Host H detects in S3 that Wireless Transmitter Controller Version Data **20663b1x** of Communication Device **200** is of an old version. Host H retrieves Wireless Transmitter Controller **H63OSx**, which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S4). Upon receiving Wireless Transmitter Controller **H63OSx** from Host H (S5), CPU **211** stores Wireless Transmitter Controller **H63OSx** as Wireless Transmitter Controller **20663OSx** in Operating System **20663OS** (Paragraph [0185]) (S6). The old version of Wireless Transmitter Controller **20663OSx** (Paragraph [0185]) is deleted.

Paragraph [0244]—This Paragraph [0244] illustrates another embodiment of Wireless Transmitter Controller Updating Software **H63c1x** (Paragraph [0196]) of Host H (Paragraph [0025]) and Wireless Transmitter Controller Updating Software **20663c1x** (Paragraph [0190]) of Communication Device **200**, which update Wireless Transmitter Controller **20663OSx** stored in Operating System **20663OS** (Paragraph [0185]) of Communication Device **200**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** sends a Wireless Transmitter Controller Update Request#3, which is received by Host H (S1). Here, the Wireless Transmitter Controller Update Request#3 is a request to send Wireless Transmitter Controller Version Data **H63b1x** (Paragraph [0195]) stored in Host H to Communication Device **200**. In response to the request, Host H retrieves Wireless Transmitter Controller Version Data **H63b1x** from OS Version Data Storage Area **H63b1** (Paragraph [0195]), and sends the data to Communication Device **200** (S2). Upon receiving Wireless Transmitter Controller Version Data **H63b1x** from Host H (S3), CPU **211** compares Wireless Transmitter Controller Version Data **H63b1x** with Wireless Transmitter Controller Version Data **20663b1x** stored in OS Version Data Storage Area **20663b1** (Paragraph [0189]) of Communication Device **200** (S4). Assuming that CPU **211** detects in S4 that Wireless Transmitter Controller Version Data **20663b1x** of Communication Device **200** is of an old version. CPU **211** sends a New Wireless Transmitter Controller Sending Request#3, which is received by Host H (S5). Here, the New Wireless Transmitter Controller Sending Request#3 is a request to send Wireless Transmitter Controller **H63OSx** (Paragraph [0192]) stored in Host H to Communication Device **200**. Host H retrieves Wireless Transmitter Controller **H63OSx** (Paragraph [0192]), which is of the latest version, from Operating System Storage Area **H63OS** (Paragraph [0192]), and sends the controller to Communication Device **200** (S6). Upon receiving Wireless Transmitter Controller **H63OSx** from Host H (S7), CPU **211** stores Wireless

Transmitter Controller H63OSx as Wireless Transmitter Controller 20663OSx in Operating System 20663OS (Paragraph [0185]) (S8). The old version of Wireless Transmitter Controller 20663OSx (Paragraph [0185]) is deleted.

Paragraph [0245]—As another embodiment, each and all data and software programs described in this specification stored in Communication Device 200 may be updated in the manner described hereinbefore.

Paragraph [0246]—For the avoidance of doubt, the present function may be utilized to repair the operating system of Communication Device 200, i.e., Operating System 20663OS (Paragraph [0185]) in the form of downloading updates.

Paragraph [0247]—<<Automobile Controlling Function>>

Paragraph [0248]—Paragraph [0249] through Paragraph [0290] illustrate the automobile controlling function which enables Communication Device 200 to remotely control an automobile in a wireless fashion via Antenna 218 (FIG. 1).

Paragraph [0249]—This Paragraph [0249] illustrates the storage area included in Automobile 835, i.e., an automobile or a car. In the present embodiment, Automobile 835 includes Automobile Controlling Information Storage Area 83565a of which the data and the software programs stored therein are described in Paragraph [0251].

Paragraph [0250]—The data and/or the software programs stored in Automobile Controlling Information Storage Area 83565a (Paragraph [0249]) may be downloaded from Host H (Paragraph [0025]).

Paragraph [0251]—This Paragraph [0251] illustrates the storage areas included in Automobile Controlling Information Storage Area 83565a (Paragraph [0249]). In the present embodiment, Automobile Controlling Information Storage Area 83565a includes Automobile Controlling Data Storage Area 83565b and Automobile Controlling Software Storage Area 83565c. Automobile Controlling Data Storage Area 83565b stores the data necessary to implement the present function on the side of Automobile 835 (Paragraph [0249]), such as the ones described in Paragraph [0252] through Paragraph [0258]. Automobile Controlling Software Storage Area 83565c stores the software programs necessary to implement the present function on the side of Automobile 835, such as the ones described in Paragraph [0259].

Paragraph [0252]—This Paragraph [0252] illustrates the storage areas included in Automobile Controlling Data Storage Area 83565b (Paragraph [0251]). In the present embodiment, Automobile Controlling Data Storage Area 83565b includes User Access Data Storage Area 83565b1, Window Data Storage Area 83565b2, Door Data Storage Area 83565b3, Radio Channel Data Storage Area 83565b4, TV Channel Data Storage Area 83565b5, Blinker Data Storage Area 83565b6, and Work Area 83565b7. User Access Data Storage Area 83565b1 stores the data described in Paragraph [0253]. Window Data Storage Area 83565b2 stores the data described in Paragraph [0254]. Door Data Storage Area 83565b3 stores the data described in Paragraph [0255]. Radio Channel Data Storage Area 83565b4 stores the data described in Paragraph [0256]. TV Channel Data Storage Area 83565b5 stores the data described in Paragraph [0257]. Blinker Data Storage Area 83565b6 stores the data described in Paragraph [0258]. Work Area 83565b7 is utilized as a work area to perform calculation and temporarily store data. The data stored in Automobile Controlling Data Storage Area 83565b excluding the ones stored in User Access Data Storage Area 83565b1 and Work Area 83565b7 are primarily utilized for reinstallation, i.e., to reinstall the data to Communication

Device 200 as described hereinafter in case the data stored in Communication Device 200 are corrupted or lost.

Paragraph [0253]—This Paragraph [0253] illustrates the data stored in User Access Data Storage Area 83565b1 (Paragraph [0252]). In the present embodiment, User Access Data Storage Area 83565b1 comprises two columns, i.e., ‘User ID’ and ‘Password Data’. Column ‘User ID’ stores the user IDs, and each user ID is an identification of the user of Communication Device 200 authorized to implement the present function. Column ‘Password Data’ stores the password data, and each password data represents the password set by the user of the corresponding user ID. The password data is composed of alphanumeric data. In the present embodiment, User Access Data Storage Area 83565b1 stores the following data: the user ID ‘User#1’ and the corresponding password data ‘Password Data#1’; the user ID ‘User#2’ and the corresponding password data ‘Password Data#2’; the user ID ‘User#3’ and the corresponding password data ‘Password Data#3’; and the user ID ‘User#4’ and the corresponding password data ‘Password Data#4’. According to the present example, the users represented by User#1 through #4 are authorized to implement the present function.

Paragraph [0254]—This Paragraph [0254] illustrates the data stored in Window Data Storage Area 83565b2 (Paragraph [0252]). In the present embodiment, Window Data Storage Area 83565b2 comprises two columns, i.e., ‘Window ID’ and ‘Window Data’. Column ‘Window ID’ stores the window IDs, and each window ID is an identification of the window (not shown) of Automobile 835 (Paragraph [0249]). Column ‘Window Data’ stores the window data, and each window data is the image data designed to be displayed on LCD 201 (FIG. 1) which represents the position of the window (not shown) of the corresponding window ID. In the present embodiment, Window Data Storage Area 83565b2 stores the following data: the window ID ‘Window#1’ and the corresponding window data ‘Window Data#1’; the window ID ‘Window#2’ and the corresponding window data ‘Window Data#2’; the window ID ‘Window#3’ and the corresponding window data ‘Window Data#3’; and the window ID ‘Window#4’ and the corresponding window data ‘Window Data#4’. Four windows of Automobile 835 which are represented by the window IDs, ‘Window#1’ through ‘Window#4’, are remotely controllable by implementing the present function.

Paragraph [0255]—This Paragraph [0255] illustrates the data stored in Door Data Storage Area 83565b3 (Paragraph [0252]). In the present embodiment, Door Data Storage Area 83565b3 comprises two columns, i.e., ‘Door ID’ and ‘Door Data’. Column ‘Door ID’ stores the door IDs, and each door ID is an identification of the door (not shown) of Automobile 835 (Paragraph [0249]). Column ‘Door Data’ stores the door data, and each door data is the image data designed to be displayed on LCD 201 (FIG. 1) which represents the position of the door (not shown) of the corresponding door ID. In the present embodiment, Door Data Storage Area 83565b3 stores the following data: the door ID ‘Door#1’ and the corresponding door data ‘Door Data#1’; the door ID ‘Door#2’ and the corresponding door data ‘Door Data#2’; the door ID ‘Door#3’ and the corresponding door data ‘Door Data#3’; and the door ID ‘Door#4’ and the corresponding door data ‘Door Data#4’. Four doors of Automobile 835 which are represented by the door IDs, ‘Door#1’ through ‘Door#4’, are remotely controllable by implementing the present function.

Paragraph [0256]—This Paragraph [0256] illustrates the data stored in Radio Channel Data Storage Area 83565b4 (Paragraph [0252]). In the present embodiment, Radio Channel Data Storage Area 83565b4 comprises two columns, i.e.,

81

‘Radio Channel ID’ and ‘Radio Channel Data’. Column ‘Radio Channel ID’ stores the radio channel IDs, and each radio channel ID is an identification of the radio channel (not shown) playable by the radio (not shown) installed in Automobile **835** (Paragraph [0249]). Column ‘Radio Channel Data’ stores the radio channel data, and each radio channel data is the image data designed to be displayed on LCD **201** (FIG. 1) which represents the radio channel (not shown) of the corresponding radio channel ID. In the present embodiment, Radio Channel Data Storage Area **83565b4** stores the following data: the radio channel ID ‘Radio Channel#1’ and the corresponding radio channel data ‘Radio Channel Data#1’; the radio channel ID ‘Radio Channel#2’ and the corresponding radio channel data ‘Radio Channel Data#2’; the radio channel ID ‘Radio Channel#3’ and the corresponding radio channel data ‘Radio Channel Data#3’; and the radio channel ID ‘Radio Channel#4’ and the corresponding radio channel data ‘Radio Channel Data#4’. Four radio channels which are represented by the radio channel IDs, ‘Radio Channel#1’ through ‘Radio Channel#4’, are remotely controllable by implementing the present invention.

Paragraph [0257]—This Paragraph [0257] illustrates the data stored in TV Channel Data Storage Area **83565b5** (Paragraph [0252]). In the present embodiment, TV Channel Data Storage Area **83565b5** comprises two columns, i.e., ‘TV Channel ID’ and ‘TV Channel Data’. Column ‘TV Channel ID’ stores the TV channel IDs, and each TV channel ID is an identification of the TV channel (not shown) playable by the TV (not shown) installed in Automobile **835** (Paragraph [0249]). Column ‘TV Channel Data’ stores the TV channel data, and each TV channel data is the image data designed to be displayed on LCD **201** (FIG. 1) which represents the TV channel (not shown) of the corresponding TV channel ID. In the present embodiment, TV Channel Data Storage Area **83565b5** stores the following data: the TV channel ID ‘TV Channel#1’ and the corresponding TV channel data ‘TV Channel Data#1’; the TV channel ID ‘TV Channel#2’ and the corresponding TV channel data ‘TV Channel Data#2’; the TV channel ID ‘TV Channel#3’ and the corresponding TV channel data ‘TV Channel Data#3’; and the TV channel ID ‘TV Channel#4’ and the corresponding TV channel data ‘TV Channel Data#4’. Four TV channels which are represented by the TV channel IDs, ‘TV Channel#1’ through ‘TV Channel#4’, are remotely controllable by implementing the present invention.

Paragraph [0258]—This Paragraph [0258] illustrates the data stored in Blinker Data Storage Area **83565b6** (Paragraph [0252]). In the present embodiment, Blinker Data Storage Area **83565b6** comprises two columns, i.e., ‘Blinker ID’ and ‘Blinker Data’. Column ‘Blinker ID’ stores the blinker IDs, and each blinker ID is an identification of the blinker (not shown) of Automobile **835** (Paragraph [0249]). Column ‘Blinker Data’ stores the blinker data, and each blinker data is the image data designed to be displayed on LCD **201** (FIG. 1) which represents the blinker (not shown) of the corresponding blinker ID. In the present embodiment, Blinker Data Storage Area **83565b6** stores the following data: the blinker ID ‘Blinker#1’ and the corresponding blinker data ‘Blinker Data#1’; and the blinker ID ‘Blinker#2’ and the corresponding blinker data ‘Blinker Data#2’. Two blinkers which are represented by the blinker IDs, ‘Blinker#1’ and ‘Blinker#2’, are remotely controllable by implementing the present invention. Here, the blinker (not shown) represented by ‘Blinker#1’ is the right blinker and the blinker (not shown) represented by ‘Blinker#2’ is the left blinker.

Paragraph [0259]—This Paragraph [0259] illustrates the storage areas included in Automobile Controlling Software

82

Storage Area **83565c** (Paragraph [0251]). In the present embodiment, Automobile Controlling Software Storage Area **83565c** includes Automobile Controller Storage Area **83565c1** and Remote Controlling Software Storage Area **83565c2**. Automobile Controller Storage Area **83565c1** stores the controllers described in Paragraph [0260]. Remote Controlling Software Storage Area **83565c2** stores the software programs described in Paragraph [0261].

Paragraph [0260]—This Paragraph [0260] illustrates the controllers stored in Automobile Controller Storage Area **83565c1** (Paragraph [0259]). In the present embodiment, Automobile Controller Storage Area **83565c1** stores Engine Controller **83565c1a**, Direction Controller **83565c1b**, Speed Controller **83565c1c**, Window Controller **83565c1d**, Door Controller **83565c1e**, Radio Controller **83565c1f**, TV Controller **83565c1g**, Radio Channel Selector **83565c1h**, TV Channel Selector **83565c1i**, Blinker Controller **83565c1j**, Emergency Lamp Controller **83565c1k**, Cruise Control Controller **83565c1l**, and Speaker Volume Controller **83565c1m**. Engine Controller **83565c1a** is the controller which controls the engine (not shown) of Automobile **835** (Paragraph [0249]). Direction Controller **83565c1b** is the controller which controls the steering wheel (not shown) of Automobile **835**. Speed Controller **83565c1c** is the controller which controls the accelerator (not shown) of Automobile **835**. Window Controller **83565c1d** is the controller which controls the windows (not shown) of Automobile **835**. Door Controller **83565c1e** is the controller which controls the doors (not shown) of Automobile **835**. Radio Controller **83565c1f** is the controller which controls the radio (not shown) of Automobile **835**. TV Controller **83565c1g** is the controller which controls the TV (not shown) of Automobile **835**. Radio Channel Selector **83565c1h** is the controller which controls the radio channels (not shown) of the radio (not shown) installed in Automobile **835**. TV Channel Selector **83565c1i** is the controller which controls the radio channels (not shown) of the radio (not shown) installed in Automobile **835**. Blinker Controller **83565c1j** is the controller which controls the blinkers (not shown) of Automobile **835**. Emergency Lamp Controller **83565c1k** is the controller which controls the emergency lamp (not shown) of Automobile **835**. Cruise Control Controller **83565c1l** is the controller which controls the cruise control (not shown) of Automobile **835**. Speaker Volume Controller **83565c1m** is the controller which controls the speaker (not shown) of Automobile **835**. As another embodiment, the foregoing controllers may be in the form of hardware instead of software.

Paragraph [0261]—This Paragraph [0261] illustrates the software programs stored in Remote Controlling Software Storage Area **83565c2** (Paragraph [0259]). In the present embodiment, Remote Controlling Software Storage Area **83565c2** stores Engine Controlling Software **83565c2a**, Direction Controlling Software **83565c2b**, Speed Controlling Software **83565c2c**, Window Controlling Software **83565c2d**, Door Controlling Software **83565c2e**, Radio Controlling Software **83565c2f**, TV Controlling Software **83565c2g**, Radio Channel Selecting Software **83565c2h**, TV Channel Selecting Software **83565c2i**, Blinker Controlling Software **83565c2j**, Emergency Lamp Controlling Software **83565c2k**, Cruise Control Controlling Software **83565c2l**, Speaker Volume Controlling Software **83565c2m**, Controller Reinstalling Software **83565c2n**, Data Reinstalling Software **83565c2o**, and User Access Authenticating Software **83565c2p**. Engine Controlling Software **83565c2a** is the software program described in Paragraph [0276]. Direction Controlling Software **83565c2b** is the software program described in Paragraph [0277]. Speed Controlling Software

83565c2c is the software program described in Paragraph [0278]. Window Controlling Software **83565c2d** is the software program described in Paragraph [0279]. Door Controlling Software **83565c2e** is the software program described in Paragraph [0280]. Radio Controlling Software **83565c2f** is the software program described in Paragraph [0281]. TV Controlling Software **83565c2g** is the software program described in Paragraph [0282]. Radio Channel Selecting Software **83565c2h** is the software program described in Paragraph [0283]. TV Channel Selecting Software **83565c2i** is the software program described in Paragraph [0284]. Blinker Controlling Software **83565c2j** is the software program described in Paragraph [0285]. Emergency Lamp Controlling Software **83565c2k** is the software program described in Paragraph [0286]. Cruise Control Controlling Software **83565c2l** is the software program described in Paragraph [0287]. Speaker Volume Controlling Software **83565c2m** is the software program described in Paragraph [0288]. Controller Reinstalling Software **83565c2n** is the software program described in Paragraph [0289]. Data Reinstalling Software **83565c2o** is the software program described in Paragraph [0290]. User Access Authenticating Software **83565c2p** is the software program described in Paragraph [0275]. The controllers stored in Automobile Controller Storage Area **83565c1** primarily functions as directly controlling Automobile **835** in the manner described in Paragraph [0260], and the software programs stored in Remote Controlling Software Storage Area **83565c2** controls the controllers stored in Automobile Controller Storage Area **83565c1**, by cooperating with the software programs stored in Remote Controlling Software Storage Area **20665c2** (Paragraph [0274]) of Communication Device **200**, in a wireless fashion via Antenna **218** (FIG. 1).

Paragraph [0262]—This Paragraph [0262] illustrates the storage area included in RAM **206** (FIG. 1) of Communication Device **200**. In the present embodiment, RAM **206** includes Automobile Controlling Information Storage Area **20665a** of which the data and the software programs stored therein are described in Paragraph [0264].

Paragraph [0263]—The data and/or the software programs stored in Automobile Controlling Information Storage Area **20665a** (Paragraph [0262]) may be downloaded from Host H (Paragraph [0025]).

Paragraph [0264]—This Paragraph [0264] illustrates the storage areas included in Automobile Controlling Information Storage Area **20665a** (Paragraph [0262]). In the present embodiment, Automobile Controlling Information Storage Area **20665a** includes Automobile Controlling Data Storage Area **20665b** and Automobile Controlling Software Storage Area **20665c**. Automobile Controlling Data Storage Area **20665b** stores the data necessary to implement the present function on the side of Communication Device **200**, such as the ones described in Paragraph [0265] through Paragraph [0271]. Automobile Controlling Software Storage Area **20665c** stores the software programs necessary to implement the present function on the side of Communication Device **200**, such as the ones described in Paragraph [0272].

Paragraph [0265]—This Paragraph [0265] illustrates the storage areas included in Automobile Controlling Data Storage Area **20665b** (Paragraph [0264]). In the present embodiment, Automobile Controlling Data Storage Area **20665b** includes User Access Data Storage Area **20665b1**, Window Data Storage Area **20665b2**, Door Data Storage Area **20665b3**, Radio Channel Data Storage Area **20665b4**, TV Channel Data Storage Area **20665b5**, Blinker Data Storage Area **20665b6**, and Work Area **20665b7**. User Access Data Storage Area **20665b1** stores the data described in Paragraph

[0266]. Window Data Storage Area **20665b2** stores the data described in Paragraph [0267]. Door Data Storage Area **20665b3** stores the data described in Paragraph [0268]. Radio Channel Data Storage Area **20665b4** stores the data described in Paragraph [0269]. TV Channel Data Storage Area **20665b5** stores the data described in Paragraph [0270]. Blinker Data Storage Area **20665b6** stores the data described in Paragraph [0271]. Work Area **20665b7** is utilized as a work area to perform calculation and temporarily store data.

Paragraph [0266]—This Paragraph [0266] illustrates the data stored in User Access Data Storage Area **20665b1** (Paragraph [0265]). In the present embodiment, User Access Data Storage Area **20665b1** comprises two columns, i.e., ‘User ID’ and ‘Password Data’. Column ‘User ID’ stores the user ID which is an identification of the user of Communication Device **200**. Column ‘Password Data’ stores the password data which represents the password set by the user of Communication Device **200**. The password data is composed of alphanumeric data. In the present embodiment, User Access Data Storage Area **20665b1** stores the following data: the user ID ‘User#1’ and the corresponding password data ‘Password Data#1’.

Paragraph [0267]—This Paragraph [0267] illustrates the data stored in Window Data Storage Area **20665b2** (Paragraph [0265]). In the present embodiment, Window Data Storage Area **20665b2** comprises two columns, i.e., ‘Window ID’ and ‘Window Data’. Column ‘Window ID’ stores the window IDs, and each window ID is an identification of the window (not shown) of Automobile **835** (Paragraph [0249]). Column ‘Window Data’ stores the window data, and each window data is the image data designed to be displayed on LCD **201** (FIG. 1) which represents the position of the window (not shown) of the corresponding window ID. In the present embodiment, Window Data Storage Area **20665b2** stores the following data: the window ID ‘Window#1’ and the corresponding window data ‘Window Data#1’; the window ID ‘Window#2’ and the corresponding window data ‘Window Data#2’; the window ID ‘Window#3’ and the corresponding window data ‘Window Data#3’; and the window ID ‘Window#4’ and the corresponding window data ‘Window Data#4’. Four windows of Automobile **835** which are represented by the window IDs, ‘Window#1’ through ‘Window#4’, are remotely controllable by implementing the present function.

Paragraph [0268]—This Paragraph [0268] illustrates the data stored in Door Data Storage Area **20665b3** (Paragraph [0265]). In the present embodiment, Door Data Storage Area **20665b3** comprises two columns, i.e., ‘Door ID’ and ‘Door Data’. Column ‘Door Data’ stores the door data, and each door data is the image data designed to be displayed on LCD **201** (FIG. 1) which represents the position of the door (not shown) of the corresponding door ID. In the present embodiment, Door Data Storage Area **20665b3** stores the following data: the door ID ‘Door#1’ and the corresponding door data ‘Door Data#1’; the door ID ‘Door#2’ and the corresponding door data ‘Door Data#2’; the door ID ‘Door#3’ and the corresponding door data ‘Door Data#3’; and the door ID ‘Door#4’ and the corresponding door data ‘Door Data#4’. Four doors of Automobile **835** (Paragraph [0249]) which are represented by the door IDs, ‘Door#1’ through ‘Door#4’, are remotely controllable by implementing the present function.

Paragraph [0269]—This Paragraph [0269] illustrates the data stored in Radio Channel Data Storage Area **20665b4** (Paragraph [0265]). In the present embodiment, Radio Channel Data Storage Area **20665b4** comprises two columns, i.e., ‘Radio Channel ID’ and ‘Radio Channel Data’. Column ‘Radio Channel ID’ stores the radio channel IDs, and each

radio channel ID is an identification of the radio channel (not shown) playable by the radio (not shown) installed in Automobile **835** (Paragraph [0249]). Column 'Radio Channel Data' stores the radio channel data, and each radio channel data is the image data designed to be displayed on LCD **201** (FIG. 1) which represents the radio channel (not shown) of the corresponding radio channel ID. In the present embodiment, Radio Channel Data Storage Area **20665b4** stores the following data: the radio channel ID 'Radio Channel#1' and the corresponding radio channel data 'Radio Channel Data#1'; the radio channel ID 'Radio Channel#2' and the corresponding radio channel data 'Radio Channel Data#2'; the radio channel ID 'Radio Channel#3' and the corresponding radio channel data 'Radio Channel Data#3'; and the radio channel ID 'Radio Channel#4' and the corresponding radio channel data 'Radio Channel Data#4'. Four radio channels which are represented by the radio channel IDs, 'Radio Channel#1' through 'Radio Channel#4', are remotely controllable by implementing the present invention.

Paragraph [0270]—This Paragraph [0270] illustrates the data stored in TV Channel Data Storage Area **20665b5** (Paragraph [0265]). In the present embodiment, TV Channel Data Storage Area **20665b5** comprises two columns, i.e., 'TV Channel ID' and 'TV Channel Data'. Column 'TV Channel ID' stores the TV channel IDs, and each TV channel ID is an identification of the TV channel (not shown) playable by the TV (not shown) installed in Automobile **835** (Paragraph [0249]). Column 'TV Channel Data' stores the TV channel data, and each TV channel data is the image data designed to be displayed on LCD **201** (FIG. 1) which represents the TV channel (not shown) of the corresponding TV channel ID. In the present embodiment, TV Channel Data Storage Area **20665b5** stores the following data: the TV channel ID 'TV Channel#1' and the corresponding TV channel data 'TV Channel Data#1'; the TV channel ID 'TV Channel#2' and the corresponding TV channel data 'TV Channel Data#2'; the TV channel ID 'TV Channel#3' and the corresponding TV channel data 'TV Channel Data#3'; and the TV channel ID 'TV Channel#4' and the corresponding TV channel data 'TV Channel Data#4'. Four TV channels which are represented by the TV channel IDs, 'TV Channel#1' through 'TV Channel#4', are remotely controllable by implementing the present invention.

Paragraph [0271]—This Paragraph [0271] illustrates the data stored in Blinker Data Storage Area **20665b6** (Paragraph [0265]). In the present embodiment, Blinker Data Storage Area **20665b6** comprises two columns, i.e., 'Blinker ID' and 'Blinker Data'. Column 'Blinker ID' stores the blinker IDs, and each blinker ID is an identification of the blinker (not shown) of Automobile **835** (Paragraph [0249]). Column 'Blinker Data' stores the blinker data, and each blinker data is the image data designed to be displayed on LCD **201** (FIG. 1) which represents the blinker (not shown) of the corresponding blinker ID. In the present embodiment, Blinker Data Storage Area **20665b6** stores the following data: the blinker ID 'Blinker#1' and the corresponding blinker data 'Blinker Data#1'; and the blinker ID 'Blinker#2' and the corresponding blinker data 'Blinker Data#2'. Two blinkers which are represented by the blinker IDs, 'Blinker#1' and 'Blinker#2', are remotely controllable by implementing the present invention. Here, the blinker (not shown) represented by 'Blinker#1' is the right blinker and the blinker (not shown) represented by 'Blinker#2' is the left blinker.

Paragraph [0272]—This Paragraph [0272] illustrates the storage areas included in Automobile Controlling Software Storage Area **20665c** (Paragraph [0264]). In the present embodiment, Automobile Controlling Software Storage Area

20665c includes Automobile Controller Storage Area **20665c1** and Remote Controlling Software Storage Area **20665c2**. Automobile Controller Storage Area **20665c1** stores the controllers described in Paragraph [0273]. Remote Controlling Software Storage Area **20665c2** stores the software programs described in Paragraph [0274].

Paragraph [0273]—This Paragraph [0273] illustrates the controllers stored in Automobile Controller Storage Area **20665c1** (Paragraph [0272]). In the present embodiment, Automobile Controller Storage Area **20665c1** stores Engine Controller **20665c1a**, Direction Controller **20665c1b**, Speed Controller **20665c1c**, Window Controller **20665c1d**, Door Controller **20665c1e**, Radio Controller **20665c1f**, TV Controller **20665c1g**, Radio Channel Selector **20665c1h**, TV Channel Selector **20665c1i**, Blinker Controller **20665c1j**, Emergency Lamp Controller **20665c1k**, Cruise Control Controller **20665c1l**, and Speaker Volume Controller **20665c1m**. Engine Controller **20665c1a** is the controller which controls the engine (not shown) of Automobile **206**. Direction Controller **20665c1b** is the controller which controls the steering wheel (not shown) of Automobile **206**. Speed Controller **20665c1c** is the controller which controls the accelerator (not shown) of Automobile **206**. Window Controller **20665c1d** is the controller which controls the windows (not shown) of Automobile **206**. Door Controller **20665c1e** is the controller which controls the doors (not shown) of Automobile **206**. Radio Controller **20665c1f** is the controller which controls the radio (not shown) of Automobile **206**. TV Controller **20665c1g** is the controller which controls the TV (not shown) of Automobile **206**. Radio Channel Selector **20665c1h** is the controller which controls the radio channels (not shown) of the radio (not shown) installed in Automobile **206**. TV Channel Selector **20665c1i** is the controller which controls the radio channels (not shown) of the radio (not shown) installed in Automobile **206**. Blinker Controller **20665c1j** is the controller which controls the blinkers (not shown) of Automobile **206**. Emergency Lamp Controller **20665c1k** is the controller which controls the emergency lamp (not shown) of Automobile **206**. Cruise Control Controller **20665c1l** is the controller which controls the cruise control (not shown) of Automobile **206**. Speaker Volume Controller **20665c1m** is the controller which controls the speaker (not shown) of Automobile **206**. As another embodiment, the foregoing controllers may be in the form of hardware instead of software. The data stored in Automobile Controller Storage Area **20665c1** are primarily utilized for reinstallation, i.e., to reinstall the data to Automobile **835** (Paragraph [0249]) as described hereinafter in case the data stored in Automobile **835** are corrupted or lost.

Paragraph [0274]—This Paragraph [0274] illustrates the software programs stored in Remote Controlling Software Storage Area **20665c2** (Paragraph [0264]). In the present embodiment, Remote Controlling Software Storage Area **20665c2** stores Engine Controlling Software **20665c2a**, Direction Controlling Software **20665c2b**, Speed Controlling Software **20665c2c**, Window Controlling Software **20665c2d**, Door Controlling Software **20665c2e**, Radio Controlling Software **20665c2f**, TV Controlling Software **20665c2g**, Radio Channel Selecting Software **20665c2h**, TV Channel Selecting Software **20665c2i**, Blinker Controlling Software **20665c2j**, Emergency Lamp Controlling Software **20665c2k**, Cruise Control Controlling Software **20665c2l**, Speaker Volume Controlling Software **20665c2m**, Controller Reinstalling Software **20665c2n**, Data Reinstalling Software **20665c2o**, and User Access Authenticating Software **20665c2p**. Engine Controlling Software **20665c2a** is the software program described in Paragraph [0276]. Direction Controlling Software **20665c2b** is the software program

described in Paragraph [0277]. Speed Controlling Software **20665c2c** is the software program described in Paragraph [0278]. Window Controlling Software **20665c2d** is the software program described in Paragraph [0279]. Door Controlling Software **20665c2e** is the software program described in Paragraph [0280]. Radio Controlling Software **20665c2f** is the software program described in Paragraph [0281]. TV Controlling Software **20665c2g** is the software program described in Paragraph [0282]. Radio Channel Selecting Software **20665c2h** is the software program described in Paragraph [0283]. TV Channel Selecting Software **20665c2i** is the software program described in Paragraph [0284]. Blinker Controlling Software **20665c2j** is the software program described in Paragraph [0285]. Emergency Lamp Controlling Software **20665c2k** is the software program described in Paragraph [0286]. Cruise Control Controlling Software **20665c2l** is the software program described in Paragraph [0287]. Speaker Volume Controlling Software **20665c2m** is the software program described in Paragraph [0288]. Controller Reinstalling Software **20665c2n** is the software program described in Paragraph [0289]. Data Reinstalling Software **20665c2o** is the software program described in Paragraph [0290]. User Access Authenticating Software **20665c2p** is the software program described in Paragraph [0275]. The controllers stored in Automobile Controller Storage Area **83565c1** primarily functions as directly controlling Automobile **835** in the manner described in Paragraph [0260], and the software programs stored in Remote Controlling Software Storage Area **83565c2** (Paragraph [0274]) controls the controllers stored in Automobile Controller Storage Area **83565c1** (Paragraph [0260]), by cooperating with the software programs stored in Remote Controlling Software Storage Area **83565c2** (Paragraph [0261]) of Automobile **835**, in a wireless fashion via Antenna **218** (FIG. 1).

Paragraph [0275]—This Paragraph [0275] illustrates User Access Authenticating Software **83565c2p** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and User Access Authenticating Software **20665c2p** (Paragraph [0274]) of Communication Device **200**, which determine whether Communication Device **200** in question is authorized to remotely control Automobile **835** by implementing the present function. In the present embodiment, the user of Communication Device **200** inputs the user ID and the password data by utilizing Input Device **210** (FIG. 1) or via voice recognition system. The user ID and the password data are temporarily stored in User Access Data Storage Area **20665b1** (Paragraph [0266]) from which the two data are sent to Automobile **835** (S1). Assume that the user input ‘User#1’ as the user ID and ‘Password Data#1’ as the password data. Upon receiving the user ID and the password data (in the present example, User#1 and Password Data#1) from Communication Device **200**, Automobile **835** stores the two data in Work Area **83565b7** (Paragraph [0252]) (S2). Automobile **835** then initiates the authentication process to determine whether Communication Device **200** in question is authorized to remotely control Automobile **835** by referring to the data stored in User Access Data Storage Area **83565b1** (Paragraph [0253]) (S3). Assume that the authenticity of Communication Device **200** in question is cleared. Automobile **835** permits Communication Device **200** in question to remotely control Automobile **835** in the manner described hereinafter (S4).

Paragraph [0276]—This Paragraph [0276] illustrates Engine Controlling Software **83565c2a** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Engine Controlling Software **20665c2a** (Paragraph [0274]) of Communica-

tion Device **200**, which ignite or turn off the engine (not shown) of Automobile **835**. In the present embodiment, the user of Communication Device **200** inputs an engine controlling signal by utilizing Input Device **210** (FIG. 1) or via voice recognition system. The signal is sent to Automobile **835** (S1). Here, the engine controlling signal indicates either to ignite the engine or turn off the engine. Upon receiving the engine controlling signal from Communication Device **200**, Automobile **835** stores the signal in Work Area **83565b7** (Paragraph [0252]) (S2). Automobile **835** controls the engine (not shown) via Engine Controller **83565c1a** (Paragraph [0260]) in accordance with the engine controlling signal (S3).

Paragraph [0277]—This Paragraph [0277] illustrates Direction Controlling Software **83565c2b** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Direction Controlling Software **20665c2b** (Paragraph [0274]) of Communication Device **200**, which control the direction of Automobile **835**. In the present embodiment, the user of Communication Device **200** inputs a direction controlling signal by utilizing Input Device **210** (FIG. 1) or via voice recognition system. The signal is sent to Automobile **835** (S1). Here, the direction controlling signal indicates either to move forward, back, left, or right Automobile **835**. Upon receiving the direction controlling signal from Communication Device **200**, Automobile **835** stores the signal in Work Area **83565b7** (Paragraph [0252]) (S2). Automobile **835** controls the direction via Direction Controller **83565c1b** (Paragraph [0260]) in accordance with the direction controlling signal (S3).

Paragraph [0278]—This Paragraph [0278] illustrates Speed Controlling Software **83565c2c** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Speed Controlling Software **20665c2c** (Paragraph [0274]) of Communication Device **200**, which control the speed of Automobile **835**. In the present embodiment, the user of Communication Device **200** inputs a speed controlling signal by utilizing Input Device **210** (FIG. 1) or via voice recognition system. The signal is sent to Automobile **835** (S1). Here, the speed controlling signal indicates either to increase speed or decrease speed of Automobile **835**. Upon receiving the speed controlling signal from Communication Device **200**, Automobile **835** stores the signal in Work Area **83565b7** (Paragraph [0252]) (S2). Automobile **835** controls the speed via Speed Controller **83565c1c** (Paragraph [0260]) in accordance with speed controlling signal (S3).

Paragraph [0279]—This Paragraph [0279] illustrates Window Controlling Software **83565c2d** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Window Controlling Software **20665c2d** (Paragraph [0274]) of Communication Device **200**, which control the window (not shown) of Automobile **835**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves all window data from Window Data Storage Area **20665b2** (Paragraph [0267]) and displays the data on LCD **201** (FIG. 1) (S1). The user of Communication Device **200** selects one of the window data (for example, Window Data#1), and CPU **211** identifies the corresponding window ID (for example, Window#1) by referring to Window Data Storage Area **20665b2** (Paragraph [0267]) (S2). The user further inputs a window controlling signal by utilizing Input Device **210** (FIG. 1) or via voice recognition system (S3). Here, the window controlling signal indicates either to open the window or to close the window. CPU **211** sends the window ID and the window controlling signal to Automobile **835** (S4). Upon receiving the window ID and the window controlling signal from Communication Device **200**, Automobile **835** stores both data in Work Area **83565b7** (Paragraph [0252]) (S5). Automobile **835** controls the window identified by the window ID via Window Con-

troller **83565c1d** (Paragraph [0260]) in accordance with the window controlling signal (S6).

Paragraph [0280]—This Paragraph [0280] illustrates Door Controlling Software **83565c2e** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Door Controlling Software **20665c2e** (Paragraph [0274]) of Communication Device **200**, which control the door (not shown) of Automobile **835**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves all door data from Door Data Storage Area **20665b3** (Paragraph [0268]) and displays the data on LCD **201** (FIG. 1) (S1). The user of Communication Device **200** selects one of the door data (for example, Door Data#1), and CPU **211** identifies the corresponding door ID (for example, Door#1) by referring to Door Data Storage Area **20665b3** (Paragraph [0268]) (S2). The user further inputs a door controlling signal by utilizing Input Device **210** (FIG. 1) or via voice recognition system. Here, the door controlling signal indicates either to open the door or to close the door (S3). CPU **211** sends the door ID and the door controlling signal to Automobile **835** (S4). Upon receiving the door ID and the door controlling signal from Communication Device **200**, Automobile **835** stores both data in Work Area **83565b7** (Paragraph [0252]) (S5). Automobile **835** controls the door identified by the door ID via Door Controller **83565c1e** (Paragraph [0260]) in accordance with the door controlling signal (S6).

Paragraph [0281]—This Paragraph [0281] illustrates Radio Controlling Software **83565c2f** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Radio Controlling Software **20665c2f** (Paragraph [0274]) of Communication Device **200**, which turn on or turn off the radio (not shown) installed in Automobile **835**. In the present embodiment, the user of Communication Device **200** inputs a radio controlling signal, and CPU **211** sends the signal to Automobile **835** (S1). Here, the radio controlling signal indicates either to turn on the radio or to turn off the radio. Upon receiving the radio controlling signal from Communication Device **200**, Automobile **835** stores the signal in Work Area **83565b7** (Paragraph [0252]) (S2). Automobile **835** controls the radio via Radio Controller **83565c1f** (Paragraph [0260]) in accordance with the radio controlling signal (S3).

Paragraph [0282]—This Paragraph [0282] illustrates TV Controlling Software **83565c2g** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and TV Controlling Software **20665c2g** (Paragraph [0274]) of Communication Device **200**, which turn on or turn off the TV (not shown) installed in Automobile **835**. In the present embodiment, the user of Communication Device **200** inputs a TV controlling signal, and CPU **211** (FIG. 1) sends the signal to Automobile **835** (S1). Here, the TV controlling signal indicates either to turn on the TV or to turn off the TV. Upon receiving the TV controlling signal from Communication Device **200**, Automobile **835** stores the signal in Work Area **83565b7** (Paragraph [0252]) (S2). Automobile **835** controls the TV via TV Controller **83565c1g** (Paragraph [0260]) in accordance with the TV controlling signal (S3).

Paragraph [0283]—This Paragraph [0283] illustrates Radio Channel Selecting Software **83565c2h** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Radio Channel Selecting Software **20665c2h** (Paragraph [0274]) of Communication Device **200**, which select the channel of the radio (not shown) installed in Automobile **835**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves all radio channel data from Radio Channel Data Storage Area **20665b4** (Paragraph [0269]) and Displays the data on LCD **201** (FIG. 1) (S1). The user of Communication Device **200** selects one of the radio channel data (for example,

Radio Channel Data#1), and CPU **211** identifies the corresponding radio channel ID (for example, Radio Channel#1) by referring to Radio Channel Data Storage Area **20665b4** (Paragraph [0269]) (S2). CPU **211** sends the radio channel ID and the radio channel controlling signal to Automobile **835** (S3). Here, the radio channel controlling signal indicates to change the radio channel to the one identified by the radio channel ID. Upon receiving the radio channel ID and the radio channel controlling signal from Communication Device **200**, Automobile **835** stores both data in Work Area **83565b7** (Paragraph [0252]) (S4). Automobile **835** controls the radio channel of the radio via Radio Channel Selector **83565c1h** (Paragraph [0260]) in accordance with the Radio Channel Controlling Signal (S5).

Paragraph [0284]—This Paragraph [0284] illustrates TV Channel Selecting Software **83565c2i** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and TV Channel Selecting Software **20665c2i** (Paragraph [0274]) of Communication Device **200**, which select the channel of the TV (not shown) installed in Automobile **835**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves all TV channel data from TV Channel Data Storage Area **20665b5** (Paragraph [0270]) and displays the data on LCD **201** (FIG. 1) (S1). The user of Communication Device **200** selects one of the TV channel data, and CPU **211** identifies the corresponding TV channel ID (for example, TV Channel#1) by referring to TV Channel Data Storage Area **20665b5** (Paragraph [0270]) (S2). CPU **211** sends the TV channel ID and the TV channel controlling signal to Automobile **835** (S3). Here, the TV channel controlling signal indicates to change the TV channel to the one identified by the TV channel ID. Upon receiving the TV channel ID and the TV channel controlling signal from Communication Device **200**, Automobile **835** stores both data in Work Area **83565b7** (Paragraph [0252]) (S4). Automobile **835** controls the TV Channel via TV Channel Selector **83565c1i** (Paragraph [0260]) in accordance with the TV channel controlling signal (S5).

Paragraph [0285]—This Paragraph [0285] illustrates Blinker Controlling Software **83565c2j** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Blinker Controlling Software **20665c2j** (Paragraph [0274]) of Communication Device **200**, which turn on or turn off the blinker (not shown) of Automobile **835**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves all blinker data from Blinker Data Storage Area **20665b6** (Paragraph [0271]) and displays the data on LCD **201** (FIG. 1) (S1). The user of Communication Device **200** selects one of the blinker data, and CPU **211** identifies the corresponding blinker ID (for example Blinker#1) by referring to Blinker Data Storage Area **20665b6** (Paragraph [0271]) (S2). CPU **211** sends the blinker ID and the blinker controlling signal to Automobile **835** (S3). Here, the blinker controlling signal indicates either to turn on or turn off the blinker identified by the blinker ID. Upon receiving the blinker ID and the blinker controlling signal from Communication Device **200**, Automobile **835** stores both data in Work Area **83565b7** (Paragraph [0252]) (S4). Automobile **835** controls the blinker via Blinker Controller **20665c1j** in accordance with the blinker controlling signal (S5).

Paragraph [0286]—This Paragraph [0286] illustrates Emergency Lamp Controlling Software **83565c2k** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Emergency Lamp Controlling Software **20665c2k** (Paragraph [0274]) of Communication Device **200**, which turn on or turn off the emergency lamp (not shown) installed in Automobile **835**. In the present embodiment, the user of Commu-

nication Device **200** inputs an emergency lamp controlling signal, and CPU **211** (FIG. 1) sends the signal to Automobile **835** (S1). Here, the emergency lamp controlling signal indicates either to turn on the emergency lamp or to turn off the emergency lamp. Upon receiving the emergency lamp controlling signal from Communication Device **200**, Automobile **835** stores the signal in Work Area **83565b7** (Paragraph [0252]) (S2). Automobile **835** controls the emergency lamp via Emergency Lamp Controller **83565c1k** (Paragraph [0260]) in accordance with the emergency lamp controlling signal (S3).

Paragraph [0287]—This Paragraph [0287] illustrates Cruise Control Controlling Software **83565c2l** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Cruise Control Controlling Software **20665c2l** (Paragraph [0274]) of Communication Device **200**, which turn on or turn off the cruise control (not shown) of Automobile **835**. In the present embodiment, the user of Communication Device **200** inputs a cruise control controlling signal, and CPU **211** (FIG. 1) sends the signal to Automobile **835** (S1). Here, the cruise control controlling signal indicates either to turn on the cruise control or turn off the cruise control. Upon receiving the cruise control controlling signal from Communication Device **200**, Automobile **835** stores the signal in Work Area **83565b7** (Paragraph [0252]) (S2). Automobile **835** controls the cruise control via Cruise Control Controller **83565c1l** (Paragraph [0260]) in accordance with the cruise control controlling signal (S3).

Paragraph [0288]—This Paragraph [0288] illustrates Speaker Volume Controlling Software **83565c2m** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Speaker Volume Controlling Software **20665c2m** (Paragraph [0274]) of Communication Device **200**, which raise or lower the volume of the speaker (not shown) of Automobile **835**. In the present embodiment, the user of Communication Device **200** inputs a speaker volume controlling signal, and CPU **211** (FIG. 1) sends the signal to Automobile **835** (S1). Here, the speaker volume controlling signal indicates either to raise the volume or lower the volume of the speaker. Upon receiving the speaker volume controlling signal from Communication Device **200**, Automobile **835** stores the signal in Work Area **83565b7** (Paragraph [0252]) (S2). Automobile **835** controls the speaker volume of the speaker via Speaker Volume Controller **83565c1m** (Paragraph [0260]) in accordance with the speaker volume controlling signal (S3).

Paragraph [0289]—This Paragraph [0289] illustrates Controller Reinstalling Software **83565c2n** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Controller Reinstalling Software **20665c2n** (Paragraph [0274]) of Communication Device **200**, which reinstalls the controllers to Automobile Controller Storage Area **83565c1**. In the present embodiment, CPU **211** (FIG. 1) of Communication Device **200** retrieves all controllers from Automobile Controller Storage Area **20665c1**, and sends the controllers to Automobile **835** (S1). Upon receiving the controllers from Communication Device **200**, Automobile **835** stores the controllers in Work Area **83565b7** (Paragraph [0252]) (S2). Automobile **835** then reinstalls the controllers in Automobile Controller Storage Area **83565c1** (S3).

Paragraph [0290]—This Paragraph [0290] illustrates Data Reinstalling Software **83565c2o** (Paragraph [0261]) of Automobile **835** (Paragraph [0249]) and Data Reinstalling Software **20665c2o** (Paragraph [0274]) of Communication Device **200**, which reinstall the data to Automobile Controlling Data Storage Area **20665b**. In the present embodiment, Automobile **835** retrieves all data from Automobile Controlling Data Storage Area **83565b**, and sends the data to Com-

munication Device **200** (S1). Upon receiving the data from Automobile **835**, CPU **211** (FIG. 1) of Communication Device **200** stores the data in Work Area **20665b7** (S2). CPU **211** then reinstalls the data in Automobile Controlling Data Storage Area **20665b** (S3).

Paragraph [0291]—For the avoidance of doubt, Automobile **835** (Paragraph [0249]) is not limited to an automobile or a car; the present function may be implemented with any type of carrier or vehicle, such as airplane, space ship, artificial satellite, space station, train, and motor cycle.

Paragraph [0292]—<<DVD Remote Controlling Function>>

Paragraph [0293]—Paragraph [0294] through Paragraph [0315] illustrate DVD remote controlling function which enables Communication Device **200** to remotely control a DVD player (not shown).

Paragraph [0294]—This Paragraph [0294] illustrates the screen displayed on DVD Monitor DVDM**69**, a monitor which displays the DVD signal received from the DVD player, after both DVD Monitor DVDM**69** and the DVD player are powered on. In the present embodiment, DVD Monitor DVDM**69** displays Main Menu MM**69** of the movie inserted in the DVD player. In the present embodiment, Main Menu MM**69** is composed of the following menu icons: Chapter Menu Icon MM**69a**, Language Menu Icon MM**69b**, Sub-title Menu Icon MM**69c**, and Start Movie Icon MM**69d**. Chapter Menu Icon MM**69a** is the icon which displays the screen described in Paragraph [0295] upon which said icon is selected by the user of Communication Device **200**. Language Menu Icon MM**69b** is the icon which displays the screen described in Paragraph [0296] upon which said icon is selected by the user of Communication Device **200**. Sub-title Menu Icon MM**69c** is the icon which displays the screen described in Paragraph [0297] upon which said icon is selected by the user of Communication Device **200**. Start Movie Icon MM**69d** is the icon which starts the movie inserted in the DVD player (not shown) upon which said icon is selected by the user of Communication Device **200**.

Paragraph [0295]—This Paragraph [0295] illustrates the screen displayed on DVD Monitor DVDM**69** when Chapter Menu Icon MM**69a** is selected from Main Menu MM**69** (Paragraph [0294]). In the present embodiment, DVD Monitor DVDM**69** displays Chapter List CL**69** of the movie inserted in the DVD player. In the present example, Chapter List CL**69** is composed of the following chapter icons: Chapter 1 Icon CL**69a**, Chapter 2 Icon CL**69b**, Chapter 3 Icon CL**69c**, Chapter 4 Icon CL**69d**, Start Movie Icon CL**69e**, and Main Menu Icon CL**69f**. Chapter 1 Icon CL**69a** represents the first chapter of the movie inserted in the DVD player. Chapter 2 Icon CL**69b** represents the second chapter of the movie inserted in the DVD player. Chapter 3 Icon CL**69c** represents the third chapter of the movie inserted in the DVD player. Chapter 4 Icon CL**69d** represents the fourth chapter of the movie inserted in the DVD player. Start Movie Icon CL**69e** is the icon which starts, upon which said icon is selected by the user, the movie inserted in the DVD player (not shown) from the chapter represented by the icon selected by the user of Communication Device **200**. Assume that the user selects Chapter 3 Icon CL**69c** from Chapter List CL**69**. The movie starts from the chapter represented by Chapter 3 Icon CL**69c** thereafter. Main Menu Icon CL**69f** is the icon which displays the screen described in Paragraph [0294] upon which said icon is selected by the user of Communication Device **200**.

Paragraph [0296]—This Paragraph [0296] illustrates the screen displayed on DVD Monitor DVDM**69** when Language Menu Icon MM**69b** is selected from Main Menu MM**69** (Paragraph [0294]). In the present embodiment, DVD Moni-

tor DVDM69 displays Language List LL69 of the movie inserted in the DVD player. In the present embodiment, Language List LL69 is composed of the following language icons: English Icon LL69a, Japanese Icon LL69b, French Icon LL69c, and Main Menu Icon LL69d. English Icon LL69a is the icon which plays the movie inserted in the DVD player (not shown) in English upon which said icon is selected by the user of Communication Device 200. Japanese Icon LL69b is the icon which plays the movie inserted in the DVD player (not shown) in Japanese upon which said icon is selected by the user of Communication Device 200. French Icon LL69c is the icon which plays the movie inserted in the DVD player (not shown) in French upon which said icon is selected by the user of Communication Device 200. Main Menu Icon LL69d is the icon which displays the screen described in Paragraph [0294] upon which said icon is selected by the user of Communication Device 200.

Paragraph [0297]—This Paragraph [0297] illustrates the screen displayed on DVD Monitor DVDM69 when Sub-title Menu Icon MM69c is selected from Main Menu MM69 (Paragraph [0294]). In the present embodiment, DVD Monitor DVDM69 displays Sub-title List StL69 of the movie inserted in the DVD player. In the present embodiment, Sub-title List StL69 is composed of the following sub-title icons: English Icon StL69a, Japanese Icon StL69b, French Icon StL69c, Sub-title OFF Icon StL69d, and Main Menu Icon StL69e. English Icon StL69a is the icon which displays the sub-titles in English while played of the movie inserted in the DVD player (not shown) upon which said icon is selected by the user of Communication Device 200. Japanese Icon StL69b is the icon which displays the sub-titles in Japanese while played of the movie inserted in the DVD player (not shown) upon which said icon is selected by the user of Communication Device 200. French Icon StL69c is the icon which displays the sub-titles in French while played of the movie inserted in the DVD player (not shown) upon which said icon is selected by the user of Communication Device 200. Sub-title OFF Icon StL69d is the icon which displays no sub-title while played of the movie upon which said icon is selected by the user of Communication Device 200. Main Menu Icon StL69e is the icon which displays the screen described in Paragraph [0294] upon which said icon is selected by the user of Communication Device 200.

Paragraph [0298]—This Paragraph [0298] illustrates the storage area included in RAM 206 (FIG. 1) of Communication Device 200. In the present embodiment, RAM 206 includes DVD Remote Controlling Information Storage Area 20669a of which the data and the software programs stored therein are described in Paragraph [0300].

Paragraph [0299]—The data and/or the software programs stored in DVD Remote Controlling Information Storage Area 20669a (Paragraph [0298]) may be downloaded from Host H (Paragraph [0025]).

Paragraph [0300]—This Paragraph [0300] illustrates the storage areas included in DVD Remote Controlling Information Storage Area 20669a (Paragraph [0298]). In the present embodiment, DVD Remote Controlling Information Storage Area 20669a includes DVD Remote Controlling Data Storage Area 20669b and DVD Remote Controlling Software Storage Area 20669c. DVD Remote Controlling Data Storage Area 20669b stores the data necessary to implement the present function, such as the ones described in Paragraph [0301] through Paragraph [0303]. DVD Remote Controlling Software Storage Area 20669c stores the software programs necessary to implement the present function, such as the ones described in Paragraph [0304].

Paragraph [0301]—This Paragraph [0301] illustrates the storage areas included in DVD Remote Controlling Data Storage Area 20669b (Paragraph [0300]). In the present embodiment, DVD Remote Controlling Data Storage Area 20669b includes DVD Player Type Data Storage Area 20669b1 and Work Area 20669b2. DVD Player Type Data Storage Area 20669b1 stores the data described in Paragraph [0302]. Work Area 20669b2 is utilized as a work area to perform calculation and temporarily store data.

Paragraph [0302]—This Paragraph [0302] illustrates the data stored in DVD Player Type Data Storage Area 20669b1 (Paragraph [0301]). In the present embodiment, DVD Player Type Data Storage Area 20669b1 comprises two columns, i.e., ‘DVD Player Type ID’ and ‘DVD Player Type Data’. Column ‘DVD Player Type ID’ stores the DVD player type IDs, and each DVD player ID is an identification of the DVD player type data stored in column ‘DVD Player Type Data’. Each DVD player ID is the name of the DVD player manufacturer. Column ‘DVD Player Type Data’ stores the DVD player type data, and each DVD player type data is a package of signals designed to be sent to the DVD player (not shown) in a wireless fashion via Antenna 218 (FIG. 1) or LED 219 (not shown). In the present embodiment, DVD Player Type Data Storage Area 20669b1 stores the following data: DVD player type ID ‘DVD Player Type#1’ and the corresponding DVD player type Data ‘DVD Player Type Data#1’; DVD player type ID ‘DVD Player Type#2’ and the corresponding DVD player type Data ‘DVD Player Type Data#2’; DVD player type ID ‘DVD Player Type#3’ and the corresponding DVD player type Data ‘DVD Player Type Data#3’; and DVD player type ID ‘DVD Player Type#4’ and the corresponding DVD player type Data ‘DVD Player Type Data#4’. Here, DVD Player Type#1 represents Sony; DVD Player Type#2 represents Samsung; DVD Player Type#3 represents NEC; and DVD Player Type#4 represents Mitsubishi. DVD Player Type Data#1 is a package of signals designed to be sent to the DVD player manufactured by Sony in a wireless fashion via Antenna 218 (FIG. 1) or LED 219 (not shown). DVD Player Type Data#2 is a package of signals designed to be sent to the DVD player manufactured by Samsung in a wireless fashion via Antenna 218 (FIG. 1) or LED 219 (not shown). DVD Player Type Data#3 is a package of signals designed to be sent to the DVD player manufactured by NEC in a wireless fashion via Antenna 218 (FIG. 1) or LED 219 (not shown). DVD Player Type Data#4 is a package of signals designed to be sent to the DVD player manufactured by Mitsubishi in a wireless fashion via Antenna 218 (FIG. 1) or LED 219 (not shown). Each DVD player type data includes the following data: power on signal, power off signal, main menu displaying signal, main menu selecting signal, chapter menu selecting signal, chapter selecting signal, movie starting signal, sound menu selecting signal, sound selecting signal, sub-title menu selecting signal, and sub-title selecting signal. The details of each signal is described in the next paragraph.

Paragraph [0303]—This Paragraph [0303] illustrates the signals included in DVD Player Type Data#1 stored in DVD Player Type Data Storage Area 20669b1 (Paragraph [0302]), for example. As described in the present paragraph, DVD Player Type Data#1 includes Power ON Signal#1, Power OFF Signal#1, Main Menu Displaying Signal#1, Chapter Menu Selecting Signal#1, Chapter Selecting Signal#1, Movie Starting Signal#1, Language Menu Selecting Signal#1, Language Selecting Signal#1, Sub-title Menu Selecting Signal#1, and Sub-title Selecting Signal#1. Power ON Signal#1 is the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to turn on its power. Power OFF Signal#1 is the wireless signal

which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to turn off its power. Main Menu Displaying Signal#1 is the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to display Main Menu MM69 (Paragraph [0294]). Chapter Menu Selecting Signal#1 is the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select Chapter Menu Icon MM69a (Paragraph [0294]) and display Chapter List CL69 (Paragraph [0295]). Chapter Selecting Signal#1 is the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select one of the chapter icons from Chapter List CL69 (Paragraph [0295]). Movie Starting Signal#1 is the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to start the movie from the chapter represented by the chapter icon identified by Chapter Selecting Signal#1. Language Menu Selecting Signal#1 is the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select Language Menu Icon MM69b (Paragraph [0294]) and display Language List LL69 (Paragraph [0296]). Language Selecting Signal#1 is the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select one of the sound icons from Language List LL69 (Paragraph [0296]). Sub-title Menu Selecting Signal#1 is the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select Sub-title Menu Icon MM69c (Paragraph [0294]) and display Sub-title List StL69 (Paragraph [0297]). Sub-title Selecting Signal#1 is the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select one of the sub-title icons from Sub-title List StL69 (Paragraph [0297]).

Paragraph [0304]—This Paragraph [0304] illustrates the software programs stored in DVD Remote Controlling Software Storage Area 20669c (Paragraph [0300]). In the present embodiment, DVD Remote Controlling Software Storage Area 20669c stores DVD Player Type Selecting Software 20669c1, DVD Power ON Software 20669c2, DVD Power OFF Software 20669c3, Main Menu Displaying Software 20669c4, Chapter Menu Selecting Software 20669c5, Chapter Selecting Software 20669c6, Movie Starting Software 20669c7, Language Menu Selecting Software 20669c8, Language Selecting Software 20669c9, Sub-title Menu Selecting Software 20669c10. DVD Player Type Selecting Software 20669c1 is the software program described in Paragraph [0305]. DVD Power ON Software 20669c2 is the software program described in Paragraph [0306]. DVD Power OFF Software 20669c3 is the software program described in Paragraph [0307]. Main Menu Displaying Software 20669c4 is the software program described in Paragraph [0308]. Chapter Menu Selecting Software 20669c5 is the software program described in Paragraph [0309]. Chapter Selecting Software 20669c6 is the software program described in Paragraph [0310]. Movie Starting Software 20669c7 is the software program described in Paragraph [0311]. Language Menu Selecting Software 20669c8 is the software program described in Paragraph [0312]. Language Selecting Software 20669c9 is the software program described in Paragraph [0313]. Sub-title Menu Selecting Software 20669c10 is the software program described in Paragraph [0314]. Sub-title Selecting Software 20669c11 is the software program described in Paragraph [0315].

Paragraph [0305]—This Paragraph [0305] illustrates DVD Player Type Selecting Software 20669c1 (Paragraph [0304]) of Communication Device 200, which selects the DVD player type of the DVD player. In the present embodiment, CPU 211 (FIG. 1) of Communication Device 200 retrieves all DVD

Player Type IDs from DVD Player Type Data Storage Area 20669b1 (Paragraph [0302]) (S1), and displays a list of DVD player type IDs on LCD 201 (FIG. 1) (S2). The user of Communication Device 200 selects a DVD player type ID by utilizing Input Device 210 (FIG. 1) or via voice recognition system (S3). CPU 211 retrieves the corresponding DVD player type data, and stores the data in Work Area 20669b2 (Paragraph [0301]) (S4). Assume that the DVD player ID selected in S3 is DVD Player Type#1 (i.e., Sony) and DVD Player Type Data#1 is stored in Work Area 20669b2 in S4 for purposes of explaining the software programs hereinafter.

Paragraph [0306]—This Paragraph [0306] illustrates DVD Power ON Software 20669c2 (Paragraph [0304]) of Communication Device 200, which sends Power ON Signal#1, i.e., the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to turn on its power. In the present embodiment, the user of Communication Device 200 inputs a power ON command by utilizing Input Device 210 (FIG. 1) or via voice recognition system (S1). CPU 211 (FIG. 1) retrieves Power ON Signal#1 from Work Area 20669b2 (Paragraph [0301]) (S2), and sends Power ON Signal#1 to the DVD player (S3).

Paragraph [0307]—This Paragraph [0307] illustrates DVD Power OFF Software 20669c3 (Paragraph [0304]) of Communication Device 200, which sends Power OFF Signal#1, i.e., the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to turn off its power. In the present embodiment, the user of Communication Device 200 inputs a power OFF command by utilizing Input Device 210 (FIG. 1) or via voice recognition system (S1). CPU 211 (FIG. 1) retrieves Power OFF Signal#1 from Work Area 20669b2 (Paragraph [0301]) (S2), and sends Power OFF Signal#1 to the DVD player (S3).

Paragraph [0308]—This Paragraph [0308] illustrates Main Menu Displaying Software 20669c4 (Paragraph [0304]) of Communication Device 200, which sends Main Menu Displaying Signal#1, i.e., the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to display Main Menu MM69 (Paragraph [0294]). In the present embodiment, the user of Communication Device 200 inputs a main menu displaying command by utilizing Input Device 210 (FIG. 1) or via voice recognition system (S1). CPU 211 (FIG. 1) retrieves Main Menu Displaying Signal#1 from Work Area 20669b2 (Paragraph [0301]) (S2), and sends Main Menu Displaying Signal#1 to the DVD player (S3).

Paragraph [0309]—This Paragraph [0309] illustrates Chapter Menu Selecting Software 20669c5 (Paragraph [0304]) of Communication Device 200, which sends Chapter Menu Selecting Signal#1, i.e., the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select Chapter Menu Icon MM69a (Paragraph [0294]) and display Chapter List CL69 (Paragraph [0295]). In the present embodiment, the user of Communication Device 200 inputs a chapter menu selecting command by utilizing Input Device 210 (FIG. 1) or via voice recognition system (S1). CPU 211 (FIG. 1) retrieves Chapter Menu Selecting Signal#1 from Work Area 20669b2 (Paragraph [0301]) (S2), and sends Chapter Menu Selecting Signal#1 to the DVD player (S3).

Paragraph [0310]—This Paragraph [0310] illustrates Chapter Selecting Software 20669c6 (Paragraph [0304]) of Communication Device 200, which sends Chapter Selecting Signal#1, i.e., the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select one of the chapter icons from Chapter List LL69 (Paragraph [0295]). In the present embodiment, the user of Communication Device 200 inputs a chapter selecting command

by utilizing Input Device **210** (FIG. 1) or via voice recognition system (S1). CPU **211** (FIG. 1) retrieves Chapter Selecting Signal#1 from Work Area **20669b2** (Paragraph [0301]) (S2), and sends Chapter Selecting Signal#1 to the DVD player (S3).

Paragraph [0311]—This Paragraph [0311] illustrates Movie Starting Software **20669c7** (Paragraph [0304]) of Communication Device **200**, which sends Movie Starting Signal#1, i.e., the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to start the movie from the chapter represented by the chapter icon identified by Chapter Selecting Signal#1. In the present embodiment, the user of Communication Device **200** inputs a movie starting command by utilizing Input Device **210** (FIG. 1) or via voice recognition system (S1). CPU **211** (FIG. 1) retrieves Movie Starting Signal#1 from Work Area **20669b2** (Paragraph [0301]) (S2), and sends Movie Starting Signal#1 to the DVD player (S3).

Paragraph [0312]—This Paragraph [0312] illustrates Language Menu Selecting Software **20669c8** (Paragraph [0304]) of Communication Device **200**, which sends Language Menu Selecting Signal#1, i.e., the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select Language Menu Icon **MM69b** (Paragraph [0294]) and display Language List **LL69** (Paragraph [0296]). In the present embodiment, the user of Communication Device **200** inputs a language menu selecting command by utilizing Input Device **210** (FIG. 1) or via voice recognition system (S1). CPU **211** (FIG. 1) retrieves Language Menu Selecting Signal#1 from Work Area **20669b2** (Paragraph [0301]) (S2), and sends Language Menu Selecting Signal#1 to the DVD player (S3).

Paragraph [0313]—This Paragraph [0313] illustrates Language Selecting Software **20669c9** (Paragraph [0304]) of Communication Device **200**, which sends Language Selecting Signal#1, i.e., the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select one of the sound icons from Language List **LL69** (Paragraph [0296]). In the present embodiment, the user of Communication Device **200** inputs a language selecting command by utilizing Input Device **210** (FIG. 1) or via voice recognition system (S1). CPU **211** (FIG. 1) retrieves Language Selecting Signal#1 from Work Area **20669b2** (Paragraph [0301]) (S2), and sends Language Selecting Signal#1 to the DVD player (S3).

Paragraph [0314]—This Paragraph [0314] illustrates Sub-title Menu Selecting Software **20669c10** (Paragraph [0304]) of Communication Device **200**, which sends Sub-title Menu Selecting Signal#1, i.e., the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select Sub-title Menu Icon **MM69c** (Paragraph [0294]) and display Sub-title List **StL69** (Paragraph [0297]). In the present embodiment, the user of Communication Device **200** inputs a sub-title menu selecting command by utilizing Input Device **210** (FIG. 1) or via voice recognition system (S1). CPU **211** (FIG. 1) retrieves Sub-title Menu Selecting Signal#1 from Work Area **20669b2** (Paragraph [0301]) (S2), and sends Sub-title Menu Selecting Signal#1 to the DVD player (S3).

Paragraph [0315]—This Paragraph [0315] illustrates Sub-title Selecting Software **20669c11** (Paragraph [0304]) of Communication Device **200**, which sends Sub-title Selecting Signal#1, i.e., the wireless signal which instructs the DVD player of the corresponding manufacturer (i.e., Sony) to select one of the sub-title icons from Sub-title List **StL69** (Paragraph [0297]). In the present embodiment, the user of Communication Device **200** inputs a sub-title selecting com-

mand by utilizing Input Device **210** (FIG. 1) or via voice recognition system (S1). CPU **211** (FIG. 1) retrieves Sub-title Selecting Signal#1 from Work Area **20669b2** (Paragraph [0301]) (S2), and sends Sub-title Selecting Signal#1 to the DVD player (S3).

Paragraph [0316]—<<Multiple Mode Implementing Function>>

Paragraph [0317]—Paragraph [0318] through Paragraph [0323] illustrate the multiple mode implementing function of Communication Device **200** which enables to activate and implement a plurality of modes, functions, and/or systems described in this specification simultaneously.

Paragraph [0318]—This Paragraph [0318] illustrates the software programs stored in RAM **206** (FIG. 1) to implement the multiple mode implementing function (FIG. 1). As described in Paragraph [0318], RAM **206** includes Multiple Mode Implementer Storage Area **20690a**. Multiple Mode Implementer Storage Area **20690a** stores Multiple Mode Implementer **20690b**, Mode List Displaying Software **20690c**, Mode Selecting Software **20690d**, Mode Activating Software **20690e**, and Mode Implementation Repeater **20690f**, all of which are software programs. Multiple Mode Implementer **20690b** administers the overall implementation of the present function. One of the major tasks of Multiple Mode Implementer **20690b** is to administer and control the timing and sequence of Mode List Displaying Software **20690c**, Mode Selecting Software **20690d**, Mode Activating Software **20690e**, and Mode Implementation Repeater **20690f**. For example, Multiple Mode Implementer **20690b** executes them in the following order: Mode List Displaying Software **20690c**, Mode Selecting Software **20690d**, Mode Activating Software **20690e**, and Mode Implementation Repeater **20690f**. Mode List Displaying Software **20690c** displays on LCD **201** (FIG. 1) a list of a certain amount or all modes, functions, and/or systems explained in this specification of which the sequence is explained in Paragraph [0319]. Mode Selecting Software **20690d** selects a certain amount or all modes, functions, and/or systems explained in this specification of which the sequence is explained in Paragraph [0320]. Mode Activating Software **20690e** activates a certain amount or all modes, functions, and/or systems selected by the Mode Selecting Software **20690d** of which the sequence is explained in Paragraph [0321]. Mode Implementation Repeater **20690f** executes Multiple Mode Implementer **20690b** which reactivates Mode List Displaying Software **20690c**, Mode Selecting Software **20690d**, Mode Activating Software **20690e** of which the sequence is explained in Paragraph [0322].

Paragraph [0319]—This Paragraph [0319] illustrates the sequence of Mode List Displaying Software **20690c** (Paragraph [0318]). Referring to Paragraph [0319], CPU **211** (FIG. 1), under the command of Mode List Displaying Software **20690c**, displays a list of a certain amount or all modes, functions, and/or systems described in this specification on LCD **201** (FIG. 1).

Paragraph [0320]—This Paragraph [0320] illustrates the sequence of Mode Selecting Software **20690d** (Paragraph [0318]). Referring to Paragraph [0320], the user of Communication Device **200** inputs an input signal by utilizing Input Device **210** (FIG. 1) or via voice recognition system identifying one of the modes, functions, and/or systems displayed on LCD **201** (FIG. 1) (S1), and CPU **211** (FIG. 1), under the command of Mode Selecting Software **20690d**, interprets the input signal and selects the corresponding mode, function, or system (S2).

Paragraph [0321]—This Paragraph [0321] illustrates the sequence of Mode Activating Software **20690e** (Paragraph

[0318]). Referring to Paragraph [0321], CPU **211** (FIG. 1), under the command of Mode Activating Software **20690e**, activates the mode, function, or, system selected in **S2** of Paragraph [0320]. CPU **211** thereafter implements the activated mode, function, or system as described in the relevant paragraphs in this specification.

Paragraph [0322]—This Paragraph [0322] illustrates the sequence of Mode Implementation Repeater **20690f** (Paragraph [0318]). Referring to Paragraph [0322], the user of Communication Device **200** inputs an input signal by utilizing Input Device **210** (FIG. 1) or via voice recognition system (**S1**). Once the activation of the selected mode, function, or system described in Paragraph [0321] hereinbefore is completed, and if the input signal indicates to repeat the process to activate another mode, function, or system (**S2**), CPU **211** (FIG. 1), under the command of Mode Implementation Repeater **20690f**, executes Multiple Mode Implementer **20690b** (Paragraph [0318]), which reactivates Mode List Displaying Software **20690c** (Paragraph [0318]), Mode Selecting Software **20690d** (Paragraph [0318]), and Mode Activating Software **20690e** (Paragraph [0318]) to activate the second mode, function, or system while the first mode, function, or system is implemented by utilizing the method of so-called ‘time sharing’ (**S3**). Mode List Displaying Software **20690c**, Mode Selecting Software **20690d**, and Mode Activating Software **20690e** can be repeatedly executed until all modes, function, and systems displayed on LCD **201** (FIG. 1) are selected and activated. The activation of modes, functions, and/or systems is not repeated if the input signal explained in **S2** so indicates.

Paragraph [0323]—As another embodiment, Multiple Mode Implementer **20690b**, Mode List Displaying Software **20690c**, Mode Selecting Software **20690d**, Mode Activating Software **20690e**, and Mode Implementation Repeater **20690f** described in Paragraph [0318] may be integrated into one software program, Multiple Mode Implementer **20690b**, as described in Paragraph [0323]. Referring to Paragraph [0323], CPU **211** (FIG. 1), first of all, displays a list of a certain amount or all modes, functions, and/or systems described in this specification on LCD **201** (FIG. 1) (**S1**). Next, the user of Communication Device **200** inputs an input signal by utilizing Input Device **210** (FIG. 1) or via voice recognition system identifying one of the modes, functions, and/or systems displayed on LCD **201** (**S2**), and CPU **211** interprets the input signal and selects the corresponding mode, function, or system (**S3**). CPU **211** activates the mode, function, or system selected in **S3**, and thereafter implements the activated mode, function, or system as described in the relevant paragraphs in this specification (**S4**). Once the activation of the selected mode, function, or system described in **S4** is completed, the user of Communication Device **200** inputs an input signal by utilizing Input Device **210** or via voice recognition system (**S5**). If the input signal indicates to repeat the process to activate another mode, function, or system (**S6**), CPU **211** repeats the steps **S1** through **S4** to activate the second mode, function, or system while the first mode, function, or system is implemented by utilizing the method so-called ‘time sharing’. The steps of **S1** through **S4** can be repeatedly executed until all modes, function, and systems displayed on LCD **201** are selected and activated. The activation of modes, functions, and/or systems is not repeated if the input signal explained in **S5** so indicates. As another embodiment, before or at the time one software program is activated, CPU **211** may, either automatically or manually (i.e., by a signal input by the user of Communication Device), terminate the other software programs already activated or prohibit other software programs to be activated while one

software program is implemented in order to save the limited space of RAM **206**, thereby allowing only one software program implemented at a time. For the avoidance of doubt, the meaning of each term ‘mode(s)’, ‘function(s)’, and ‘system(s)’ is equivalent to the others in this specification. Namely, the meaning of ‘mode(s)’ includes and is equivalent to that of ‘function(s)’ and ‘system(s)’, the meaning of ‘function(s)’ includes and is equivalent to that of ‘mode(s)’ and ‘system(s)’, and the meaning of ‘system(s)’ includes and is equivalent to that of ‘mode(s)’ and ‘function(s)’. Therefore, even only mode(s) is expressly utilized in this specification, it impliedly includes function(s) and/or system(s) by its definition.

Paragraph [0324]—<<Incorporation By Reference>>

Paragraph [0325]—All paragraphs and drawings described in U.S. Ser. No. 10/711,265, filed Sep. 7, 2004, are incorporated to this application by reference, particularly the following: the preamble described in paragraph [2149] (no drawings); Communication Device **200** (Voice Communication Mode) described in paragraphs [2150] through [2155] (FIGS. 1 through 2c); Voice Recognition System described in paragraphs [2156] through [2188] (FIGS. 3 through 19); Positioning System described in paragraphs [2189] through [2220] (FIGS. 20a through 32e); Auto Backup System described in paragraphs [2221] through [2230] (FIGS. 33 through 37); Signal Amplifier described in paragraphs [2231] through [2236] (FIG. 38); Audio/Video Data Capturing System described in paragraphs [2237] through [2249] (FIGS. 39 through 44b); Digital Mirror Function (1) described in paragraphs [2250] through [2258] (FIGS. 44c through 44e); Caller ID System described in paragraphs through [2266] (FIGS. 45 through 47); Stock Purchasing Function described in paragraphs [2267] through [2276] (FIGS. 48 through 52); Timer Email Function described in paragraphs [2277] through [2283] (FIGS. 53a and 53b); Call Blocking Function described in paragraphs [2284] through [2297] (FIGS. 54 through 59); Online Payment Function described in paragraphs [2298] through [2307] (FIGS. 60 through 64); Navigation System described in paragraphs [2308] through [2330] (FIGS. 65 through 74a); Remote Controlling System described in paragraphs [2331] through [2349] (FIGS. 75 through 85); Auto Emergency Calling System described in paragraphs [2350] through [2358] (FIGS. 86 and 87); Cellular TV Function described in paragraphs [2359] through [2443] (FIGS. 88 through 135); 3D Video Game Function described in paragraphs [2444] through [2456] (FIGS. 136 through 144); Digital Mirror Function (2) described in paragraphs [2457] through [2466] (FIGS. 145 through 155); Voice Recognition Sys—E-mail (2) described in paragraphs [2467] through [2475] (FIGS. 156 through 160); Positioning System—GPS Search Engine described in paragraphs [2476] through [2518] (FIGS. 161 through 182); Mobile Ignition Key Function described in paragraphs [2519] through [2541] (FIGS. 183 through 201); Voice Print Authentication System described in paragraphs [2542] through [2552] (FIGS. 202 through 211); Fingerprint Authentication System described in paragraphs [2553] through [2565] (FIGS. 212 through 221); Auto Time Adjust Function described in paragraphs [2566] through [2570] (FIGS. 222 through 224); Video/Photo Mode described in paragraphs [2571] through [2599] (FIGS. 225 through 242); Call Taxi Function described in paragraphs [2600] through [2640] (FIGS. 243 through 269); Shooting Video Game Function described in paragraphs [2641] through [2657] (FIGS. 270 through 283); Driving Video Game Function described in paragraphs [2658] through [2671] (FIGS. 284 through 294); Address Book Updating Function described in paragraphs [2672] through [2692]

(FIGS. 295 through 312); Batch Address Book Updating Function—With Host described in paragraphs [2693] through (FIGS. 313 through 329); Batch Address Book Updating Function—Peer-To-Peer Connection described in paragraphs [2715] through [2719] (FIGS. 329a through 329c); Batch Scheduler Updating Function—With Host described in paragraphs [2720] through [2743] (FIGS. 330 through 350); Batch Scheduler Updating Function—Peer-To-Peer Connection described in paragraphs [2744] through (FIGS. 351 and 352); Calculator Function described in paragraphs [2749] through [2754] (FIGS. 353 through 356); Spreadsheet Function described in paragraphs [2755] through [2762] (FIGS. 357 through 360); Word Processing Function described in paragraphs [2763] through [2778] (FIGS. 361 through 373); TV Remote Controller Function described in paragraphs [2779] through [2801] (FIGS. 374 through 394); CD/PC Inter-communicating Function described in paragraphs [2802] through [2826] (FIGS. 413 through 427); PDWR Sound Selecting Function described in paragraphs [2827] through (FIGS. 428 through 456); Start Up Software Function described in paragraphs [2864] through (FIGS. 457 through 466); Another Embodiment Of Communication Device 200 described in paragraphs [2881] through [2885] (FIGS. 467a through 467d); Stereo Audio Data Output Function described in paragraphs [2886] through [2905] (FIGS. 468 through 479); Stereo Visual Data Output Function described in paragraphs [2906] through [2925] (FIGS. 480 through 491); Multiple Signal Processing Function described in paragraphs [2926] through [2998] (FIGS. 492 through 529); Positioning System—Pin-pointing Function described in paragraphs [2999] through [3032] (FIGS. 530 through 553); Artificial Satellite Host described in paragraphs [3033] through [3051] (FIGS. 554 through 567); CCD Bar Code Reader Function described in paragraphs [3052] through [3073] (FIGS. 568 through 579); Online Renting Function described in paragraphs [3074] through [3151] (FIGS. 580 through 633); SOS Calling Function described in paragraphs [3152] through [3172] (FIGS. 634 through 645); Input Device described in paragraphs [3173] through [3178] (FIGS. 646 through 650); PC Remote Controlling Function described in paragraphs [3179] through [3214] (FIGS. 651 through 670); PC Remote Downloading Function described in paragraphs [3215] through [3264] (FIGS. 671 through 701); Audiovisual Playback Function described in paragraphs [3265] through [3290] (FIGS. 702 through 716); Audio Playback Function described in paragraphs [3291] through [3315] (FIGS. 717 through 731); Ticket Purchasing Function described in paragraphs [3316] through [3345] (FIGS. 732 through 753); Remote Data Erasing Function described in paragraphs [3346] through [3375] (FIGS. 754 through 774); Business Card Function described in paragraphs [3376] through [3392] (FIGS. 775 through 783); Game Vibrating Function described in paragraphs [3393] through [3403] (FIGS. 784 through 786); Part-time Job Finding Function described in paragraphs [3404] through [3424] (FIGS. 787 through 801); Parking Lot Finding Function described in paragraphs [3425] through [3464] (FIGS. 802 through 832); Parts Upgradable Communication Device described in paragraphs [3465] through [3490] (FIGS. 833a through 833x); On Demand TV Function described in paragraphs [3491] through [3521] (FIGS. 834 through 855); Inter-communicating TV Function described in paragraphs [3522] through [3556] (FIGS. 856 through 882); Display Controlling Function described in paragraphs [3557] through [3574] (FIGS. 883 through 894); Multiple Party Communicating Function described in paragraphs [3575] through [3608] (FIGS. 894a through 917); Display Brightness Controlling

Function described in paragraphs [3609] through [3618] (FIGS. 918 through 923); Multiple Party Pin-pointing Function described in paragraphs through [3666] (FIGS. 924 through 950f); Digital Camera Function described in paragraphs through [3694] (FIGS. 951 through 968); Phone Number Linking Function described in paragraphs [3695] through [3718] (FIGS. 968a through 983); Multiple Window Displaying Function described in paragraphs [3719] through [3737] (FIGS. 984 through 995); Mouse Pointer Displaying Function described in paragraphs [3738] through [3775] (FIGS. 996 through 1021); House Item Pin-pointing Function described in paragraphs [3776] through [3935] (FIGS. 1022 through 1152); Membership Administrating Function described in paragraphs [3936] through [3978] (FIGS. 1153 through 1188); Keyword Search Timer Recording Function described in paragraphs [3979] through (FIGS. 1189 through 1254); Weather Forecast Displaying Function described in paragraphs through [4112] (FIGS. 1255 through 1288); Multiple Language Displaying Function described in paragraphs [4113] through [4170] (FIGS. 1289 through 1331); Caller's Information Displaying Function described in paragraphs [4171] through [4224] (FIGS. 1332 through 1375); Communication Device Remote Controlling Function (By Phone) described in paragraphs [4225] through [4265] (FIGS. 1394 through 1415); Communication Device Remote Controlling Function (By Web) described in paragraphs through [4306] (FIGS. 1416 through 1437); Shortcut Icon Displaying Function described in paragraphs [4307] through [4334] (FIGS. 1438 through 1455); Task Tray Icon Displaying Function described in paragraphs [4335] through [4357] (FIGS. 1456 through 1470); Multiple Channel Processing Function described in paragraphs [4358] through [4405] (FIGS. 1471 through 1498); Solar Battery Charging Function described in paragraphs [4406] through [4419] (FIGS. 1499 through 1509); OS Updating Function described in paragraphs [4420] through [4487] (FIGS. 1510 through 1575); Device Managing Function described in paragraphs [4488] through [4505] (FIGS. 1576 through 1587); Automobile Controlling Function described in paragraphs [4506] through [4554] (FIGS. 1588 through 1627); OCR Function described in paragraphs [4555] through [4590] (FIGS. 1628 through 1652); Real-time GPS Function described in paragraphs [4591] through [4660] (FIGS. 1653 through 1712); CCD Video Stabilizing Function described in paragraphs [4661] through [4692] (FIGS. 1713 through 1736); DVD Remote Controlling Function described in paragraphs [4693] through [4731] (FIGS. 1737 through 1757); Dual Frame Buffer Implementing Function described in paragraphs [4732] through (FIGS. 1758 through 1767); Mouse Pointer Image Auto Changing Function described in paragraphs [4749] through [4762] (FIGS. 1768 through 1774); Dual CCD Camera Function described in paragraphs [4763] through [4783] (FIGS. 1775a through 1786); Radio Tuner Function described in paragraphs [4784] through [4814] (FIGS. 1787 through 1812); Registered Voice Recognizing Function described in paragraphs [4815] through [4854] (FIGS. 1813 through 1842); Host's TV Resolution Converting Function described in paragraphs [4855] through [4884] (FIGS. 1843 through 1864); Voice Shortcut Recognizing Function described in paragraphs [4885] through [4919] (FIGS. 1865 through 1889); and Vital Sign Monitoring Function described in paragraphs [4920] through [5009] (FIGS. 1890a through 1954).

The invention claimed is:

1. A mobile phone comprising:

an input device;

a display;

a CPU; and

an antenna;

wherein said mobile phone is operable to implement voice communication;

wherein a list of controllers is displayed on said display;

wherein said CPU updates the controller(s) selected from said list via said input device by utilizing a mobile phone updating data received via said antenna; and

wherein the selected controller(s) which is/are updated by said CPU is one or more of the following:

(1) a mobile phone battery controller which controls the mobile phone battery included in said mobile phone,

(2) a mobile phone CCD unit controller which controls the mobile phone CCD unit included in said mobile phone,

(3) a mobile phone microphone controller which controls the mobile phone microphone included in said mobile phone,

(4) a mobile phone speaker controller which controls the mobile phone speaker included in said mobile phone, and

(5) a mobile phone vibrator controller which controls the mobile phone vibrator included in said mobile phone.

2. A mobile phone comprising:

a microphone;

a speaker;

an input device;

a display;

a CPU; and

an antenna;

wherein voice communication is implemented by utilizing said microphone and said speaker;

wherein a list of controllers is displayed on said display;

wherein said CPU updates the controller(s) selected from said list via said input device by utilizing a mobile phone updating data received via said antenna; and

wherein the selected controller(s) which is/are updated by said CPU is one or more of the following:

(1) a mobile phone battery controller which controls the mobile phone battery included in said mobile phone,

(2) a mobile phone CCD unit controller which controls the mobile phone CCD unit included in said mobile phone,

(3) a mobile phone microphone controller which controls the mobile phone microphone included in said mobile phone,

(4) a mobile phone speaker controller which controls the mobile phone speaker included in said mobile phone, and

(5) a mobile phone vibrator controller which controls the mobile phone vibrator included in said mobile phone.

3. A method for updating a mobile phone, comprising:

displaying a list of controllers on a display; and

updating the controller(s) selected from said list via said input device by utilizing a mobile phone updating data received via said antenna;

wherein the selected controller(s) which is/are updated is/are one or more of the following:

(1) a mobile phone battery controller which controls the mobile phone battery included in said mobile phone,

(2) a mobile phone CCD unit controller which controls the mobile phone CCD unit included in said mobile phone,

(3) a mobile phone microphone controller which controls the mobile phone microphone included in said mobile phone,

(4) a mobile phone speaker controller which controls the mobile phone speaker included in said mobile phone, and

(5) a mobile phone vibrator controller which controls the mobile phone vibrator included in said mobile phone.

4. The mobile phone of claim **1**, wherein said mobile phone is a handheld voice communication device which is operable to implement data communication.

5. The mobile phone of claim **1**, wherein said mobile phone is a handheld voice communication device which is operable to implement multiple functions simultaneously together with voice communication.

6. The mobile phone of claim **1**, wherein said mobile phone battery controller, said mobile phone CCD unit controller, said mobile phone microphone controller, said mobile phone speaker controller, and/or said mobile phone vibrator controller is/are updated to the latest version by said mobile phone updating data.

7. The mobile phone of claim **1**, wherein two or more of said mobile phone battery controller, said mobile phone CCD unit controller, said mobile phone microphone controller, said mobile phone speaker controller, and said mobile phone vibrator controller are updated simultaneously.

8. The mobile phone of claim **1**, wherein said mobile phone updating data is received from a host computer.

9. The mobile phone of claim **2**, wherein said mobile phone is a handheld voice communication device which is operable to implement data communication.

10. The mobile phone of claim **2**, wherein said mobile phone is a handheld voice communication device which is operable to implement multiple functions simultaneously together with voice communication.

11. The mobile phone of claim **2**, wherein said mobile phone battery controller, said mobile phone CCD unit controller, said mobile phone microphone controller, said mobile phone speaker controller, and/or said mobile phone vibrator controller is/are updated to the latest version by said mobile phone updating data.

12. The mobile phone of claim **2**, wherein two or more of said mobile phone battery controller, said mobile phone CCD unit controller, said mobile phone microphone controller, said mobile phone speaker controller, and said mobile phone vibrator controller are updated simultaneously.

13. The mobile phone of claim **2**, wherein said mobile phone updating data is received from a host computer.

14. The method of claim **3**, wherein said mobile phone is a handheld voice communication device which is operable to implement data communication.

15. The method of claim **3**, wherein said mobile phone is a handheld voice communication device which is operable to implement multiple functions simultaneously together with voice communication.

16. The method of claim **3**, wherein said mobile phone battery controller, said mobile phone CCD unit controller, said mobile phone microphone controller, said mobile phone speaker controller, and/or said mobile phone vibrator controller is/are updated to the latest version by said mobile phone updating data.

17. The method of claim **3**, wherein two or more of said mobile phone battery controller, said mobile phone CCD unit controller, said mobile phone microphone controller, said mobile phone speaker controller, and said mobile phone vibrator controller are updated simultaneously.

18. The method of claim **3**, wherein said mobile phone updating data is received from a host computer.