

US008244017B2

(12) **United States Patent**
Chun et al.

(10) **Patent No.:** **US 8,244,017 B2**
(45) **Date of Patent:** **Aug. 14, 2012**

(54) **CONSTRUCTING THREE DIMENSIONAL IMAGES USING PANORAMIC IMAGES**

(76) Inventors: **James Jiwen Chun**, Raleigh, NC (US);
Andrew Youngho Chun, Raleigh, NC (US);
Jennifer Miseong Chun, Raleigh, NC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 381 days.

(21) Appl. No.: **12/701,622**

(22) Filed: **Feb. 8, 2010**

(65) **Prior Publication Data**

US 2011/0194787 A1 Aug. 11, 2011

(51) **Int. Cl.**
G06K 9/00 (2006.01)
G06K 9/64 (2006.01)

(52) **U.S. Cl.** **382/131**; 382/154; 382/285

(58) **Field of Classification Search** 382/128,
382/131, 154, 285; 378/21–27, 38, 39, 40;
348/36

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,630,203 A 12/1986 Szirtes
5,214,686 A 5/1993 Webber

5,841,830 A 11/1998 Barni et al.
6,493,415 B1 12/2002 Arai et al.
6,587,541 B2 7/2003 Menhardt
7,317,819 B2 1/2008 Janes
2009/0322856 A1* 12/2009 Duparre 348/36
2009/0323891 A1* 12/2009 Borghese et al. 378/20

* cited by examiner


Primary Examiner — Brian Le

(74) *Attorney, Agent, or Firm* — Ash Tankha; Lipton, Weinberger & Husick

(57) **ABSTRACT**

A computer implemented method and system for constructing a three dimensional (3D) tomographic image from an object's two dimensional (2D) panoramic image are provided. A first geometrical attribute set in a first coordinate system is assigned to one or more focal troughs. A second geometrical attribute set in a second coordinate system is assigned to the 2D panoramic image. Second geometrical attributes are correlated with first geometrical attributes for reconstructing the 2D panoramic image in multiple dimensions. Multiple defocused elements of the object are determined along the 2D panoramic image's horizontal dimension. A transverse dimension is determined for the reconstructed panoramic image by mapping the defocused elements to a translation along the transverse dimension in the first coordinate system on either side of the center of the focal troughs. The multiple dimensions of the reconstructed panoramic image are transformed into an orthogonal coordinate system to generate the 3D tomographic image.

21 Claims, 9 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

CONSTRUCTING THREE DIMENSIONAL IMAGES USING PANORAMIC IMAGES

BACKGROUND

Dentists have been using panoramic dental images for many years to diagnose dental diseases and disorders. Existing panoramic X-ray imaging machines produce high quality images of the entire dental arch. The entire dentition, the maxillary sinuses, the entire mandible, the temporomandibular joints and other oral facial structures are visible on a single resulting X-ray film. Panoramic imaging machines capture X-ray images along a curved cross-sectional focal plane called a focal trough. The resulting image visible on a panoramic radiograph consists largely of the anatomical structures located within the focal trough. Up until now, panoramic images have been solely presented as two-dimensional images. Although some useful information such as the general shape of the dental structures, and the densities of the teeth and supporting bone along the dental arch can be obtained from the panoramic images, the physical dimensions of the dental structures and the spatial relation of these dental structures are not accurate due to the distortions and limitation of the imaging process.

Presently, three dimensional X-ray images are being recognized by more and more dentists as a valuable tool to diagnose dental diseases. Radiographic techniques, such as, cone beam computer tomography scans are known to generate three dimensional images of anatomical structures with high resolutions. However, certain anatomical structures and certain conditions require patients to be exposed to multiple scans or high doses of radiation to obtain good quality images. According to radiation protection in dentistry, a responsible radiologist keeps the radiation exposure as low as reasonably achievable (ALARA). The basis of radiation protection is that the exposure to the patient should be justifiable such that the total potential diagnostic benefits are greater than the individual detriment radiation exposure might cause.

Therefore, there is a need for a computer implemented method and system that constructs three dimensional images of an object using ordinary two dimensional panoramic images that require low doses of radiation for acquiring single scan images of anatomical structures.

SUMMARY OF THE INVENTION

This summary is provided to introduce a selection of concepts in a simplified form that are further described in the detailed description of the invention. This summary is not intended to identify key or essential inventive concepts of the claimed subject matter, nor is it intended for determining the scope of the claimed subject matter.

The computer implemented method and system disclosed herein addresses the above stated need for constructing three dimensional images of an object using ordinary two dimensional panoramic images that require low doses of radiation for image acquisition, thereby enhancing diagnostic and radiographic efficiency. An image processing application assigns a set of first geometrical attributes, herein referred to as a "first geometrical attribute set", in a first coordinate system to one or more focal troughs. The focal troughs define curved multidimensional zones relating to predefined focal planes associated with one or more panoramic imaging machines for imaging, for example, dental arches. The first geometrical attribute set represents a vertical dimension, a rotational dimension, and a transverse dimension in the first coordinate system. The image processing application assigns

a set of second geometrical attributes, herein referred to as a "second geometrical attribute set", in a second coordinate system to a two dimensional panoramic image of the object. The two dimensional panoramic image is a two dimensional projection of the object developed using the panoramic imaging machines. The second geometrical attribute set represents a vertical dimension and a horizontal dimension in the second coordinate system. As used herein, a "geometrical attribute" refers to a scalar, a vector or a combination of a scalar and a vector, and is used to designate points in an n-dimensional space. The image processing application reconstructs the two dimensional panoramic image in multiple dimensions. The multiple dimensions of the reconstructed panoramic image comprise the vertical dimension of the first geometrical attribute set, the rotational dimension of the first geometrical attribute set, and a transverse dimension. The image processing application reconstructs the two dimensional panoramic image as follows: The image processing application correlates one or more of the second geometrical attributes with one or more of the first geometrical attributes. The vertical dimension represented by the second geometrical attribute set corresponds to the vertical dimension represented by the first geometrical attribute set. The horizontal dimension represented by the second geometrical attribute set corresponds to the rotational dimension represented by the first geometrical attribute set. For each of one or more discrete points on the two dimensional panoramic image, the image processing application determines multiple defocused elements of the object along the horizontal dimension of the two dimensional panoramic image. The image processing application determines the transverse dimension for the reconstructed panoramic image by mapping the defocused elements along the horizontal dimension of the two dimensional panoramic image to a translation along the transverse dimension in the first coordinate system on either side of the center of the focal troughs. The image processing application then transforms the multiple dimensions of the reconstructed panoramic image into an orthogonal coordinate system to generate the three dimensional tomographic image of the object.

In an embodiment, for each of the discrete points on the two dimensional panoramic image, the image processing application also determines multiple defocused elements of the object along the vertical dimension of the two dimensional panoramic image. The image processing application generates the three dimensional tomographic image using the orthogonal coordinate system. The orthogonal coordinate system is, for example, a Cartesian coordinate system.

The image processing application also generates a multi-layered three dimensional image by stacking multiple three dimensional tomographic images with thinner focal troughs. Furthermore, the image processing application generates two dimensional cephalometric images using the three dimensional tomographic image. The image processing application obtains a trajectory of the center of rotation of an electromagnetic radiation source, for example, an X-ray source of the panoramic imaging machines that rotates around the object, in the first coordinate system. The trajectory of the center of rotation of the electromagnetic radiation source achieves the predefined focal planes. The image processing application also obtains a measured speed of rotation of the electromagnetic radiation source around the object and a measured speed of rotation of a rotating image film drum of the panoramic imaging machines.

The generated three dimensional tomographic image can be used in, for example, dental implant treatment planning, imaging of maxillary sinus impacted teeth, third molar nerve, foreign body and other pathologies, analyzing temporoman-

dibular joint functions, and orthodontic treatment planning. For example, orthodontists can use the generated three dimensional images to record and understand the shape of the dental arch, amount of arch space needed to align teeth, and a course of root movement during orthodontic treatment. The computer implemented method and system disclosed herein greatly enhances the diagnostic power, with the same doses of radiation required for acquiring two dimensional images, thereby reducing the risk and radiation exposure to as low as reasonably achievable.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing summary, as well as the following detailed description of the invention, is better understood when read in conjunction with the appended drawings. For the purpose of illustrating the invention, exemplary constructions of the invention are shown in the drawings. However, the invention is not limited to the specific methods and instrumentalities disclosed herein.

FIG. 1 illustrates a computer implemented method of constructing a three dimensional tomographic image from a two dimensional panoramic image of an object.

FIG. 2 exemplarily illustrates a logical configuration of a panoramic imaging machine.

FIG. 3A exemplarily illustrates a focal trough.

FIG. 3B exemplarily illustrates geometrical attributes of the focal trough in a first coordinate system.

FIG. 4A exemplarily illustrates the geometric principle in radiography showing points transverse to the focal trough.

FIG. 4B exemplarily illustrates a distribution curve showing the variation of blurriness along a transverse dimension of the focal trough.

FIG. 5 exemplarily illustrates a panoramic image of a dental arch in a second coordinate system.

FIG. 6 exemplarily illustrates a geometrical relationship between an X-ray tube head, the focal trough, and a panoramic film plane of a panoramic imaging machine in a first coordinate space.

FIG. 7 exemplarily illustrates a process flow diagram comprising the steps for reconstructing the panoramic image.

FIG. 8 exemplarily illustrates a computer implemented system for constructing a three dimensional tomographic image from a two dimensional panoramic image of an object.

FIG. 9 exemplarily illustrates the architecture of a computer system used for constructing a three dimensional tomographic image from a two dimensional panoramic image of an object.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 illustrates a computer implemented method of constructing a three dimensional tomographic image from a two dimensional panoramic image of an object, for example, the dental arch of a patient. A set of first geometrical attributes, herein referred to as a "first geometrical attribute set", in a first coordinate system is assigned **101** to one or more focal troughs. As used herein, a focal trough refers to a curved multidimensional zone relating to a predefined focal plane associated with a panoramic imaging machine for imaging the dental arch. The predefined focal plane is also referred to as a focal trough plane. The focal trough of the panoramic imaging machine is a three dimensional curved zone in which images of object structures are reasonably well defined on a panoramic radiograph. The first geometrical attribute set represents a vertical dimension, a rotational dimension, and a transverse dimension in the first coordinate system. As used

herein, the first coordinate system refers to a coordinate system that designates discrete points using tuples in a three dimensional space containing the focal trough. Also, as used herein, a dimension refers to a particular direction with respect to a fixed center or origin and/or angular orientation from a fixed direction for measuring and locating discrete points in a two dimensional space and/or a three dimensional space. For example, a vertical dimension is used to measure and locate discrete points along the vertical direction. A set of second geometrical attributes, herein referred to as a "second geometrical attribute set", in a second coordinate system is assigned **102** to the two dimensional panoramic image of the object. The two dimensional panoramic image is a two dimensional projection of the object developed using one or more panoramic imaging machines. The second geometrical attribute set represents a vertical dimension and a horizontal dimension in the second coordinate system. As used herein, the second coordinate system refers to a coordinate system that designates discrete points using tuples on the panoramic image of the object. Also, as used herein, a "geometrical attribute" refers to a scalar, a vector or a combination of a scalar and a vector of points in the first coordinate system and/or the second coordinate system, and is used to designate points in an n-dimensional space.

The two dimensional panoramic image is reconstructed **103** in multiple dimensions. The multiple dimensions of the reconstructed panoramic image comprise the vertical dimension of the first geometrical attribute set, the rotational dimension of the first geometrical attribute set, and a transverse dimension. One or more second geometrical attributes of the second geometrical attribute set are correlated **103a** with one or more first geometrical attributes of the first geometrical attribute set. The vertical dimension represented by the second geometrical attribute set corresponds to the vertical dimension represented by the first geometrical attribute set. The horizontal dimension represented by the second geometrical attribute set corresponds to the rotational dimension represented by the first geometrical attribute set. For each of one or more discrete points on the two dimensional panoramic image, multiple defocused elements of the object are determined **103b** along the horizontal dimension of the two dimensional panoramic image. A transverse dimension is determined **103c** for the reconstructed panoramic image by mapping the defocused elements along the horizontal dimension of the two dimensional panoramic image to a translation along the transverse dimension in the first coordinate system on either or both sides of the center of the focal troughs. The multiple dimensions of the reconstructed panoramic image are transformed **104** into an orthogonal coordinate system to generate the three dimensional tomographic image of the object.

In an embodiment, for each of the discrete points on the two dimensional panoramic image, multiple defocused elements of the object are also determined along the vertical dimension of the two dimensional panoramic image. An image processing application generates the three dimensional tomographic image using the orthogonal coordinate system. The orthogonal coordinate system is, for example, a Cartesian coordinate system.

FIG. 2 exemplarily illustrates a logical configuration of a panoramic imaging machine **200**. The panoramic imaging machine **200** comprises an X-ray tube head **202** and an image film drum **201**. The X-ray tube head **202** and the image film drum **201** rotate around an object synchronously and in opposite directions. In a normal arrangement, the X-ray tube head **202** and the film plate **201a** are connected through a mechanical linkage **204**, for example, a rod whose pivot point coin-

cides with the focal point of the X-ray tube head **202**. The image created by the points on the focal plane of the rotating X-ray tube head **202** appear sharper, while the images on other points on either side of the focal plane are blurred or distorted. The panoramic imaging machine **200** captures X-ray images of an object, for example, a dental arch along a curved cross-sectional plane of focus called the focal trough **203**. The panoramic images developed are tomographic images of the object along the cross-sectional space defined by the focal trough **203**. The focal trough **203** for a panoramic imaging machine **200** is well defined, making it possible to reconstruct the panoramic images in the three dimensional cross-sectional space defined by the focal trough **203** using three dimensional imaging techniques of the computer implemented method disclosed herein. The three dimensional reconstructed image renders an accurate three dimensional layer of the tomographic image of the object. The three dimensional image contains the three dimensional relationship between the teeth, the upper and lower arches and the bone structures, sinus and nasal cavities, both the upper and lower jaws and the temporomandibular joints.

As illustrated in FIG. 2, the panoramic imaging machine **200** uses the principles of tomography in which images are developed by blurring the image of object structures lying superficial and deep to the focal trough plane. The panoramic images are created by rotating both the X-ray tube head **202** and the film plate **201a** at the same time. When the exposure begins, the X-ray tube head **202** and the film plate **201a** move simultaneously and in opposite directions through the mechanical linkage **204**. The image film drum **201** rotates around its axis and the entire image film drum **201** rotates around the center of the focal trough **203**. The image of a point on an object that coincides with the focal trough plane **302** or the center plane of the focal trough **203** appears sharper, as illustrated in FIGS. 3A-3B. As the point moves farther from the focal trough plane **302**, referred to as defocusing, the blurriness of the image of that point increases. The blurring is also greater if a structure of the object is farther away from the image film, or if the X-ray tube head **202** moves faster. The relation between the speed of the X-ray tube head **202** and the blurring in the developed two dimensional panoramic image is disclosed in the detailed description of FIGS. 4A-4B.

The long axis of the structure relative to the direction of travel for the X-ray tube head **202** can also affect the blurriness. The direction of the travel of the X-ray tube head **202** is parallel to the focal trough **203**. If the long axis of the structure is not parallel to the direction of travel, which is the case for most objects, the relative distance of the structure to the focal trough **203** will be different as well. This causes the blurring of the parts of the structure that are located further away from the focal trough **203**. The normal arrangement of the panoramic imaging machine **200** is modified for imaging the dental arch, since the dental arch does not define a true arc in a perfect circle. Accordingly, multiple centers of rotation are necessary to maintain the dental arch in the focal trough **203** as the panoramic imaging machine **200** rotates around the patient. The trajectory of the center of rotation of the X-ray tube head **202** for imaging a curved dental arch is predefined such that the X-ray beam successively irradiates structures of the dental arch substantially normal to the dental arch.

The created two-dimensional panoramic image contains distortions due to unequal vertical and horizontal magnification or reduction, superimposition due to overlapping of tooth structures, and loss of image sharpness in the imaging process. The structures recorded on the panoramic image are the two dimensional projections of the structures that have relatively high radio opacity and are within or close to the focal

trough **203**. If a structure of the object lies on the focal trough **203**, the image of the structure will have the least blurriness. If the structure lies away from the focal trough **203**, the blurring of the image of the structure is greater.

The degree of blurriness of a structure is a measure of the distance of the structure away from the focal trough **203**. Since the long axis of the object may not lie in the same direction as the vertical axis (Z) of the focal trough **203**, the blurriness varies along the vertical axis (Z). Hence, the structures of the object on the panoramic images can be characterized by their blurriness, which also indicates the distances of the structures away from the focal trough **203**, as a function of their location on the vertical axis. Information regarding distance of the structures away from the focal trough **203** assists in a more accurate approximation of the three dimensional tomography of the object.

The computer implemented method disclosed herein can be divided into three stages, for example, image detection, image reconstruction, and image display. Image detection involves the study and characterization of the focal trough **203** for different types of panoramic imaging machines **200** and numerically constructing the focal trough **203** in the first coordinate system. FIG. 3A exemplarily illustrates a focal trough **203**, showing a contour line **301**. The image of the points lying on the contour line **301** has the least blurriness. FIG. 3B exemplarily illustrates the geometrical attributes of the focal trough **203** in the first coordinate system. Geometrical attributes representing the vertical dimension (Z), the rotational dimension (R) with the center "O" and the transverse dimension (T) are assigned to the focal trough **203**. The rotational center of the X-ray tube head **202** shifts along one or more predefined trajectories. Information such as the centers of the rotation of the image film drum **201**, the diameter of the image film drum **201**, the rotational axis and the rotational velocity of the image film drum **201**, the rotational axis and the rotational velocity of the X-ray tube head **202**, the length of rotational arm of the X-ray tube head **202**, the trajectories of the center of rotation of the X-ray tube head **202**, and other important parameters is collected according to the type of the panoramic imaging machine **200**, and then transformed into the first coordinates system with Z, R, T, O coordinates as illustrated in FIG. 3B. The focal trough **203** of the panoramic imaging machine **200** can be quantitatively defined by a function $F(Z, R, T, O)$ in the first coordinate system. This quantitative data is used to establish the coordinates for the three dimensional reconstruction of the two dimensional panoramic image. Typically, the rotational velocity of the image film drum **201** is about 1.7 mm/s and the thickness of the focal trough **203** is about 10 mm. A higher relative speed between the X-ray tube head **202** and the image film drum **201** results in a thinner focal trough **203**. As disclosed below, multiple tomographic reproductions of the focal trough **203** can be stacked in order to construct multi-layered three dimensional images.

FIG. 4A exemplarily illustrates the geometric principle in radiography showing points transverse to the focal trough **203**. As the X-ray tube head **202** and the film plate **201a** move simultaneously, the projected image of the object at point "C" moves forwards on the film plate **201a**, while the image of the object at "A" moves backwards. As a result, the images of the object at these two points are blurred during the movement. The greater the distances between points "A" and "B" and points "C" and "B" on the object, the longer is the resulting blurring distances A'A" and C'C" on the projected image, respectively. Also, a higher speed of the X-ray tube head **202** relative to the image film drum **201** results in longer blurring distances A'A" and C'C". In a first order approximation, the

equation of motion is of constant speed, and the blurriness of a point is proportional to the distance of the point away from the center of the focal trough **203**, and the relative speed of the X-ray tube head **202** and the image film drum **201**. On the other hand, the projected image for the object at point "B" remains fixed at the same relative location on the film plate **201a** during the movement of the X-ray tube head **202**, retaining its sharpness. The curved plane within which point "B" of the object resides is the focal trough plane **302**. Given the geometry of the X-ray tube head **202** and the film plate **201a**, and the speed of their relative motion, the exact location of the focal trough plane $F(Z_i, R_j, T_l, O)$ **302** can be numerically characterized for each type of panoramic imaging machine **200**. This function $F(Z_i, R_j, T_l, O)$ resembles the function of the contour line **301** illustrated in FIG. 3A. $F(Z_i, R_j, T_l, O)$ is a function of distribution that reflects the blurriness of the panoramic image as a function of Z_i, R_j, T_l, O , with values ranging from one to zero, where "one" indicates the least blurring, and "zero" indicates complete blurring. $F(Z_i, R_j, T_l, O)$ on the contour line **301** has a value of 1 and corresponds to the points on the focal trough **203**. However, the points located away from the focal trough plane **302** correspond to the lighter shades on the projected image, and their values decrease dramatically. Indices i, j , and l in the function $F(Z_i, R_j, T_l, O)$ are the discrete points along the focal trough **203** from the starting point to the end point. "O" is the location of the center of rotation at any instance. The discrete points are chosen to account for the necessary set of points to construct a three dimensional image. $F(Z_i, R_j, T_l, O)$ has a bell shaped curve across the transverse dimension (T) with the peak at the contour line **301** as illustrated in FIG. 4B.

FIG. 4B exemplarily illustrates a distribution curve showing the variation of blurriness along a transverse direction (T) of the focal trough **203**. A wider bell shaped curve corresponds to a lower total blurriness. As illustrated in FIG. 4B, the bell shaped curve becomes narrower when the rotational speed increases and consequently when the blurriness increases, from which it can be inferred that a faster relative speed between the X-ray tube head **202** and the image film drum **201** leads to a narrower focal trough **203**. The resulting blurring manifests in the blurring of the panoramic image along the horizontal dimension (X). As illustrated in FIG. 4A, the relative rotation between the X-ray tube head **202** and the film plate **201a** of the points of C and A, which are positioned away from the focal center B, results in the blurred image of point C as C'C" and point A as A'A" in the horizontal dimension (X) on the film plate **201a**.

Image reconstruction involves the reconstruction of the two dimensional panoramic image data into three dimensional image data. Most panoramic images recorded are usually bitmap data files. Geometrical attributes representing the horizontal dimension (X) and the vertical dimension (Z) from the second coordinate system are assigned to the panoramic image, as illustrated in FIG. 5. FIG. 5 exemplarily illustrates a panoramic image of a dental arch in the second coordinate system. The bitmap data of the panoramic image are converted into numeric data in terms of the X and Y coordinates in the second coordinate system, represented by the tuple $P(Z_m, X_n)$.

FIG. 6 exemplarily illustrates a geometrical relationship between the X-ray tube head **202**, the focal trough **203** and a panoramic film plane **601** of the panoramic imaging machine **200** in a first coordinate space. The horizontal dimension "X" of the panoramic film plane **601** corresponds to the rotational dimension "R" on the focal trough **203**. "Z" is the common vertical axis on the focal trough **203** and the panoramic film plane **601**. Thus, the X and Z dimensional data, for example,

the discrete values of X and Z on the panoramic film plane $P(Z_m, X_n)$ **601** can be readily correlated with the R and Z dimensional data, for example, the discrete values of R and Z of the focal trough plane $F(Z_i, R_j, T_l, O)$ **302**. The correlation between X and Z dimensional data on the panoramic film plane $P(Z_m, X_n)$ **601** and the R and Z dimensional data of the focal trough plane $F(Z_i, R_j, T_l, O)$ **302**, respectively, is represented by equation 1 as follows:

$$I(Z_i, R_j, T_l, O) = F(Z_i, R_j, T_l, O) * P(Z_m, X_n) \quad (\text{Equation 1})$$

The resulting reconstructed image data given by $I(Z_i, R_j, T_l, O)$ has distortions and blurriness due structures that are distant from the focal trough **203**. The reasons for blurriness need to be investigated and properly processed to restore the original image. The distortions and blurriness in the panoramic images occur due to several factors. For example, a penumbra occurs from the size of the focal spot that resulted in non-sharpness near the edge of the panoramic image.

As disclosed in the detailed description of FIGS. 4A-4B, the blurriness along the horizontal dimension (X) on the panoramic image $P(Z_m, X_n)$ may occur due to the relative rotational motion between the image film drum **201** and the X-ray tube head **202**. The rapid rotational motion results in blurry movement of the image data along the horizontal dimension (X) as illustrated in FIGS. 4A and 5. The natural variation of the data from the object structure is replaced by the prolonged repetition of the data superimposed over time. The patterns of this blurring reflect the relative rotational speed and the distance of the structures away from the focal trough **203**, among other factors. Referring to FIG. 4A, the blurriness or defocusing of point C'-C" on the panoramic image is proportional to "BC", the distance between point "C" on the object and point "B" in the focal trough **203**. The length of this blurring C'-C" is a function of the relative speed of the rotation and the distance "BC" of point "C" away from the focal trough **203**. Since the relative rotational speed between the X-ray tube head **202** and the image film drum **201** is well defined, the length of the repetition determines the distance of the structure at point "C" from the center of the focal trough **203**. The length of the blurring quantified or measured in terms of discrete values along the horizontal dimension (X), referred to as a set of defocused elements, is mapped to the transverse dimension (T) represented in the first coordinate system with respect to a discrete point "B" on the center of the focal trough **203**. This mapping of the length of blurring to a length along the transverse dimension (T) is repeated for other sets of defocused elements to construct the transverse dimension (T) with respect to other discrete points along center of the focal trough **203**. The original image of the structure at point "C" is recreated by identifying the center of the repetition, while the distance of the object structure relative to the focal trough **203** is characterized to obtain an approximation of the three dimensional tomography of the object. The panoramic image data reconstructed in three dimensions, namely, the horizontal dimension (Z_i), the rotational dimension (R_j) and the transverse dimension (T_l) provides the image data $I(Z_i, R_j, T_l, O)$ in the three dimensional space around the focal trough **203**. $I(Z_i, R_j, T_l, O)$ resembles the actual physical dimensions of the real object. This set of image data constitutes a narrow band of structures around the focal trough plane **302**.

FIG. 7 exemplarily illustrates a process flow diagram for reconstructing the panoramic image in three dimensions. A panoramic bitmap image file is converted **701** into numeric data labeled as (n, m) for the two dimensions X and Z, yielding $P(Z_m, X_n)$. A three dimensional image processing/viewing application is selected **702**. Data reduction is performed

based on the maximum data density required for three dimensional (3D) viewing. The coordinates X_n are converted **703** into the coordinates R_j on the focal trough **203** based on equation 1 from the positions on the film image to the focal trough **203**. This conversion is given by $P(Z_m, X_n) \rightarrow I(Z_i, R_j, T_l, O)$.

In order to reconstruct the blurriness in the panoramic image, for each discrete value of X_n and Z_m , a series of defocused elements are determined by comparing **704** to check whether the elements $P(Z_m, X_n)$, $P(Z_m, X_{n-k})$, . . . $P(Z_m, X_{n+k-1})$, . . . $P(Z_m, X_{n+k})$, . . . have same values within the noise level, where k is the range index for this series of similar values. The center $P(Z_m, X_n)$ of this series of defocused elements is identified to correct the blurriness, that is, to obtain the correct value for $I(Z_i, R_j, T_l, O)$, where T_l , the translation along the transverse dimension is estimated based on the rotational speeds and the length of blurriness k . When the blurriness in the panoramic image is reconstructed for each discrete value of X_n and Z_m , by mapping the length of the blurriness to a length along the transverse dimension (T_l), the resulting transverse dimensional data establishes one or more new planes on either side of the focal trough plane **302** that can be defined in the Z_i and R_j coordinates. A new three dimensional data $I(Z_i, R_j, T_l, O)$ is thus generated.

In order to ensure the accuracy of the reconstructed image, aluminum calibration guides can be used to calibrate the relative size and location of the panoramic images along the focal trough **203**. These calibration guides are embedded in, for example, a bite guide. Patients are instructed to hold the bite guide between their teeth during the imaging process. Regular shaped objects such a triangular cylinder aluminum rod, circular cylinder aluminum rod, etc. are positioned inside a biting guide between upper and lower teeth. These aluminum rods are semi translucent to X-rays, and hence appear as shadows over the panoramic image. The images of the calibration guides given, for example, by $I_{guide}(Z_i, R_j, T_l, O)$ are compared **705** with their actual physical dimensions. If discrepancies are detected in these images, further investigations are performed to correct these discrepancies. The calibration guides have well-defined radio densities, and hence can be subtracted from the developed image to recover the intended images. The calibration guides also have well-defined radiographic optical density, shape and locations that can be used to calibrate the image density of the structures of the object and the distance of the structures from the focal through.

Among the initial data, for example, centers of the rotation of the image film drum **201**, the relative rotational speed of the image film drum **201** and the X-ray tube head **202**, etc., collected from the panoramic imaging machine **200**, the data that can be altered by mechanical or human error while acquiring the panoramic image, is the relative rotational speed of the image film drum **201** and the X-ray tube head **202**. Thus, special calibration guides can be designed to regain the accuracy of the initial data. Aluminum balls of a small diameter of about 0.5 mm are positioned at various precise distances, for example, 1-5 mm away from a center line of the dental arch, and their images $I_{guide}(Z_i, R_j, T_l, O)$ are analyzed. Although the center line of the dental arch can be arbitrary, the relative distances of these calibration balls from the center are precise. These distances on the image are compared to their actual values. If discrepancies between the image and the actual values are found, corrections to the entire image data are made to ensure the accuracy of $I(Z_i, R_j, T_l, O)$.

Image display involves the selection and configuration of application software for rendering the three dimensional images. A typical three dimensional image processing/view-

ing application requires substantially less discrete data points than that required in the panoramic image. Data reduction is performed either at this stage or in the previous stage where the panoramic image data is reconstructed. The three dimensional image processing/viewing application selected allows a viewer to freely rotate and enlarge the object. The reconstructed image data $I(Z_i, R_j, T_l, O)$ are transformed or converted from data in X-R-T-O space into the data in X-Y-Z Cartesian coordinates, to obtain $V(Z_i, X_j, Y_l)$ in the Cartesian coordinate space. In the Cartesian coordinate space, a center of origin along the mid-line is selected as the common origin. The converted data $V(Z_i, X_j, Y_l)$ are imported into the image processing/viewing application for generating the three dimensional tomographic image of the object. The image processing application incorporates sophisticated algorithms to generate a three dimensional (3D) volumetric data set. The image processing application incorporates basic visual enhancement features, for example, zoom or magnification, window/level, the capability to add annotation, etc. The image processing application also features cursor driven measurement algorithms that provide the viewer or clinician with an interactive capability for real-time dimensional assessment of the generated tomographic image.

In the case of orthodontic diagnosis, most of the important dental and skeletal anatomical features related to the cephalometric landmarks are located near the focal trough **203**. Cephalometric analysis is performed for understanding the dental and skeletal development of a patient. Traditionally, separate cephalometric equipment is required to obtain the cephalometric data. In an embodiment of the computer implemented method disclosed herein, the three dimensional tomographic image data obtained from the panoramic images can also be projected into a two dimensional cephalometric X-ray image for enabling cephalometric analysis of the dental arch.

The three dimensional tomographic image also comprises the three dimensional relation of the temporomandibular joint complex. Multiple three dimensional images can be produced with different bite positions. In this case, the patients are instructed to bite a series of occlusal guides in particular inter-occlusal positions. These three dimensional images can be animated into a three dimensional record of the joint movement. Abnormalities associated with the jaw movement, for example, the temporomandibular joint disorder can be diagnosed from these records.

In an embodiment, a faster relative rotation of the X-ray tube head **202** and the image film drum **201** produces a thinner focal trough plane **302**. Multiple tomographic image layers of thinner focal trough **203** can be stacked together to produce a multi-layered three dimensional image. This multi-layered three dimensional image comprises comprehensive information in the transverse dimension (T), which is useful in implant treatment.

FIG. **8** exemplarily illustrates a computer implemented system **800** for constructing a three dimensional tomographic image from a two dimensional panoramic image of an object. The two dimensional panoramic image is a two dimensional projection of the object developed using a panoramic imaging machine **200**. The computer implemented system **800** disclosed herein comprises one or more panoramic imaging machines **200** having predefined focal trough planes **302**, an image processing application **801a** provided on a computing device **801**, and specific modules that process the data and render a three dimensional view of the object structures, for example, dental structures.

The image processing application **801a** on the computing device **801** comprises a first assignment module **801b**, a second assignment module **801c**, a correlator **801d**, a panoramic

image analyzer **801f**, and a transformation module **801e**. The first assignment module **801b** assigns a first geometrical attribute set in a first coordinate system to one or more focal troughs **203**. The focal troughs **203** define curved multidimensional zones relating to predefined focal trough planes **302** associated with one or more panoramic imaging machines **200**. The first geometrical attribute set represents a vertical dimension, a rotational dimension, and a transverse dimension in the first coordinate system. The second assignment module **801c** assigns a second geometrical attribute set in a second coordinate system to the two dimensional panoramic image of the object. The second geometrical attribute set represents a vertical dimension and a horizontal dimension in the second coordinate system. The correlator **801d** correlates one or more second geometrical attributes with one or more first geometrical attributes for reconstructing the panoramic image in multiple dimensions. The multiple dimensions of the reconstructed panoramic image comprise the vertical dimension represented by the first geometrical attribute set, the rotational dimension of the first geometrical attribute set, and a transverse dimension. The vertical dimension of the second geometrical attribute set corresponds to the vertical dimension of the first geometrical attribute set. The horizontal dimension of the second geometrical attribute set corresponds to the rotational dimension of the first geometrical attribute set.

The panoramic image analyzer **801f** determines, for each of one or more discrete points on the two dimensional panoramic image, multiple defocused elements of the object along the horizontal dimension of the two dimensional panoramic image. The panoramic image analyzer **801f** determines the transverse dimension for the reconstructed panoramic image by mapping the defocused elements along the horizontal dimension to a translation along the transverse dimension in the first coordinate system on either side of the center of the focal troughs **203**. The transformation module **801e** transforms the multiple dimensions of the reconstructed panoramic image into an orthogonal coordinate system to generate the three dimensional tomographic image of the object. The image processing application **801a** generates the three dimensional tomographic image using an orthogonal coordinate system.

In an embodiment, instead of manually feeding the information about the panoramic imaging machine **200** into the computing device **801**, the computer implemented system **800** can include a specially configured panoramic imaging machine **200** interfaced with the computing device **801** such that the computing device **801** can automatically collect configurable information, for example, the centers of rotation of the image film drum **201**, the diameter of the image film drum **201**, the rotational axis and the rotational velocity of the image film drum **201**, the rotational axis and the rotational velocity of the X-ray tube head **202**, the length of rotational arm of the X-ray tube head **202**, the trajectories of center of rotation of the X-ray tube head **202**, etc. from the panoramic imaging machine **200**.

In an embodiment, the panoramic image analyzer **801f** also determines multiple defocused elements of the object along the vertical dimension of the two dimensional panoramic image for each of the discrete points on the two dimensional panoramic image. The image processing application **801a** generates a multi-layered three dimensional image by stacking multiple three dimensional tomographic images with thinner focal troughs **203**. The image processing application **801a** also generates two dimensional cephalometric images using the generated three dimensional tomographic image. In an embodiment, the first assignment module **801b** obtains a

trajectory of the center of rotation of an electromagnetic radiation source, for example, the X-ray source of the panoramic imaging machine **200** that rotates around the object in the first coordinate system. The trajectory of the center of rotation of the X-ray source achieves the predefined focal trough plane **302**. The first assignment module **801b** also obtains a measured speed of rotation of the X-ray source around the object and a measured speed of rotation of the rotating image film drum **201** of the panoramic imaging machine **200**.

In an embodiment, the computer applications and programs, for example, the image processing application **801a** may be operated in a remote location. The image files, for example, the bitmap files can be electronically transmitted to a remote computing device, where web-based viewable images, for example, PNG files are returned to an online user. Information regarding the panoramic imaging machines **200** and calibration guides are required or made available at the remote computing device for an accurate construction of the three dimensional tomographic image.

FIG. 9 exemplarily illustrates the architecture of a computer system **900** used for constructing a three dimensional tomographic image from a two dimensional panoramic image of an object. The computer system **900** comprises a processor **901**, a memory unit **902** for storing programs and data, an input/output (I/O) controller **903**, and a display unit **906** communicating via a data bus **905**. The memory unit **902** comprises a random access memory (RAM) and a read only memory (ROM). The computer system **900** comprises one or more input devices **907**, for example, a keyboard such as an alphanumeric keyboard, a mouse, a joystick, etc. The input/output (I/O) controller **903** controls the input and output actions performed by a user. The computer system **900** communicates with other computer systems through an interface **904**, comprising, for example, a Bluetooth™ interface, an infrared (IR) interface, a WiFi interface, a universal serial bus interface (USB), a local area network (LAN) or wide area network (WAN) interface, etc.

The processor **901** is an electronic circuit that can execute computer programs. The memory unit **902** is used for storing programs, applications, and data. For example, the image processing application **801a** is stored on the memory unit **902** of the computer system **900**. The memory unit **902** is, for example, a random access memory (RAM) or another type of dynamic storage device that stores information and instructions for execution by processor **901**. The memory unit **902** also stores temporary variables and other intermediate information used during execution of the instructions by the processor **901**. The computer system **900** further comprises a read only memory (ROM) or another type of static storage device that stores static information and instructions for the processor **901**. The I/O controller **903** controls the input and output actions performed by the user. The data bus **905** permits communication between the modules, for example, **801b**, **801c**, **801d**, **801e**, and **801f** of the computer implemented system **800** disclosed herein.

Computer applications and programs are used for operating the computer system **900**. The programs are loaded onto the fixed media drive **908** and into the memory unit **902** of the computer system **900** via the removable media drive **909**. In an embodiment, the computer applications and programs may be loaded directly through the network. Computer applications and programs are executed by double clicking a related icon displayed on the display unit **906** using one of the input devices **907**. The user interacts with the computer system **900** using a graphical user interface (GUI) of the display unit **906**.

The computer system **900** employs an operating system for performing multiple tasks. The operating system manages execution of, for example, the image processing application **801a** provided on the computer system **900**. The operating system further manages security of the computer system **900**, peripheral devices connected to the computer system **900**, and network connections. The operating system employed on the computer system **900** recognizes keyboard inputs of a user, output display, files and directories stored locally on the fixed media drive **908**, for example, a hard drive. Different programs, for example, a web browser, an e-mail application, etc., initiated by the user are executed by the operating system with the help of the processor **901**, for example, a central processing unit (CPU). The operating system monitors the use of the processor **901**.

The image processing application **801a** is installed in the computer system **900** and the instructions are stored in the memory unit **902**. The panoramic images are transferred from the panoramic imaging machine **200** to the image processing application **801a** installed in the computer system **900** of the computing device **801** via the interface **904** or a network. A user initiates the execution of the image processing application **801a** by double clicking the icon for the image processing application **801a** on the display unit **906** or the execution of the image processing application **801a** is automatically initiated on installing the image processing application **801a** on the computing device **801**. Instructions for constructing a three dimensional tomographic image are retrieved by the processor **901** from the program memory in the form of signals. The locations of the instructions in the modules, for example, **801b**, **801c**, **801d**, **801e**, and **801f**, are determined by a program counter (PC). The program counter stores a number that identifies the current position in the program of the image processing application **801a**.

The instructions fetched by the processor **901** from the program memory after being processed are decoded. The instructions are placed in an instruction register (IR) in the processor **901**. After processing and decoding, the processor **901** executes the instructions. For example, the first assignment module **801b** defines instructions for assigning a first geometrical attribute set in a first coordinate system to one or more focal troughs **203**. The second assignment module **801c** defines instructions for assigning a second geometrical attribute set in a second coordinate system to the two dimensional panoramic image. The correlator **801d** defines instructions for correlating one or more second geometrical attributes with one or more first geometrical attributes for reconstructing the panoramic image in multiple dimensions. The panoramic image analyzer **801f** defines instructions for determining multiple defocused elements of the object along the horizontal dimension of the two dimensional panoramic image. The panoramic image analyzer **801f** also defines instructions for determining a transverse dimension for the reconstructed panoramic image by mapping the defocused elements along the horizontal dimension to a translation along the transverse dimension in the first coordinate system on either side of the focal trough **203**. The transformation module **801e** defines instructions for transforming the multiple dimensions of the reconstructed panoramic image into an orthogonal coordinate system to generate the three dimensional tomographic image of the object, etc., which are stored in the program memory or received from a remote server.

The processor **901** retrieves the instructions defined by the first assignment module **801b**, the second assignment module **801c**, the correlator **801d**, the panoramic image analyzer **801f**, and the transformation module **801e**, and executes the instructions.

At the time of execution, the instructions stored in the instruction register are examined to determine the operations to be performed. The specified operation is then performed by the processor **901**. The operations include arithmetic and logic operations. The operating system performs multiple routines for performing a number of tasks required to assign input devices **907**, output devices **910**, and memory for execution of the image processing application **801a**. The tasks performed by the operating system comprise assigning memory to the image processing application **801a** and data, moving data between memory **902** and disk units and handling input/output operations. The operating system performs the tasks on request by the operations and after performing the tasks, the operating system transfers the execution control back to the processor **901**. The processor **901** continues the execution to obtain one or more outputs. The outputs of the execution of the image processing application **801a** are displayed to the user on the display unit **906**.

It will be readily apparent that the various methods and algorithms described herein may be implemented in a computer readable medium appropriately programmed for general purpose computers and computing devices. Typically a processor, for example, one or more microprocessors will receive instructions from a memory or like device, and execute those instructions, thereby performing one or more processes defined by those instructions. Further, programs that implement such methods and algorithms may be stored and transmitted using a variety of media, for example, computer readable media in a number of manners. In one embodiment, hard-wired circuitry or custom hardware may be used in place of, or in combination with, software instructions for implementation of the processes of various embodiments. Thus, embodiments are not limited to any specific combination of hardware and software. A "processor" means any one or more microprocessors, central processing unit (CPU) devices, computing devices, microcontrollers, digital signal processors or like devices. The term "computer readable medium" refers to any medium that participates in providing data, for example instructions that may be read by a computer, a processor or a like device. Such a medium may take many forms, including but not limited to, non-volatile media, volatile media, and transmission media. Non-volatile media include, for example, optical or magnetic disks and other persistent memory volatile media include dynamic random access memory (DRAM), which typically constitutes the main memory. Transmission media include coaxial cables, copper wire and fiber optics, including the wires that comprise a system bus coupled to the processor. Common forms of computer readable media include, for example, a floppy disk, a flexible disk, hard disk, magnetic tape, any other magnetic medium, a compact disc-read only memory (CD-ROM), digital versatile disc (DVD), any other optical medium, punch cards, paper tape, any other physical medium with patterns of holes, a random access memory (RAM), a programmable read only memory (PROM), an erasable programmable read only memory (EPROM), an electrically erasable programmable read only memory (EEPROM), a flash memory, any other memory chip or cartridge, a carrier wave as described hereinafter, or any other medium from which a computer can read. In general, the computer readable programs may be implemented in any programming language. Some examples of languages that can be used include C, C++, C#, Perl, Python, or JAVA. The software programs may be stored on or in one or more mediums as an object code. A computer program product comprising computer executable instructions embodied in a computer readable

15

medium comprises computer parsable codes for the implementation of the processes of various embodiments.

The present invention can be configured to work in a network environment including a computer that is in communication, via a communications network, with one or more devices, for example, one or more imaging machines. The computer may communicate with the devices directly or indirectly, via a wired or wireless medium such as the Internet, Local Area Network (LAN), Wide Area Network (WAN) or Ethernet, Token Ring, or via any appropriate communications means or combination of communications means. Each of the devices may comprise computers, such as those based on the Intel® processors, AMD® processors, UltraSPARC® processors, Sun® processors, IBM® processors, etc. that are adapted to communicate with the computer. Any number and type of machines may be in communication with the computer.

The foregoing examples have been provided merely for the purpose of explanation and are in no way to be construed as limiting of the present invention disclosed herein. While the invention has been described with reference to various embodiments, it is understood that the words, which have been used herein, are words of description and illustration, rather than words of limitation. Further, although the invention has been described herein with reference to particular means, materials and embodiments, the invention is not intended to be limited to the particulars disclosed herein; rather, the invention extends to all functionally equivalent structures, methods and uses, such as are within the scope of the appended claims. Those skilled in the art, having the benefit of the teachings of this specification, may effect numerous modifications thereto and changes may be made without departing from the scope and spirit of the invention in its aspects.

We claim:

1. A computer implemented method of constructing a three dimensional tomographic image from a two dimensional panoramic image of an object, comprising:

assigning a set of first geometrical attributes in a first coordinate system to one or more focal troughs, said focal troughs defining curved multidimensional zones relating to predefined focal planes associated with one or more panoramic imaging machines, wherein said set of said first geometrical attributes represents a vertical dimension, a rotational dimension, and a transverse dimension in said first coordinate system;

assigning a set of second geometrical attributes in a second coordinate system to said two dimensional panoramic image of said object, wherein said set of said second geometrical attributes represents a vertical dimension and a horizontal dimension in said second coordinate system;

reconstructing said two dimensional panoramic image in multiple dimensions, wherein said multiple dimensions of said reconstructed panoramic image comprise said vertical dimension of said set of said first geometrical attributes, said rotational dimension of said set of said first geometrical attributes, and a transverse dimension, wherein said reconstruction comprises:

correlating one or more of said second geometrical attributes with one or more of said first geometrical attributes, wherein said vertical dimension of said set of said second geometrical attributes corresponds to said vertical dimension of said set of said first geometrical attributes, and wherein said horizontal dimension of said set of said second geometrical

16

attributes corresponds to said rotational dimension of said set of said first geometrical attributes;

determining, for each of one or more discrete points on said two dimensional panoramic image, a plurality of defocused elements of said object along said horizontal dimension of said two dimensional panoramic image; and

determining said transverse dimension for said reconstructed panoramic image by mapping said defocused elements along said horizontal dimension of said two dimensional panoramic image to a translation along said transverse dimension in said first coordinate system on either side of center of said focal troughs; and transforming said multiple dimensions of said reconstructed panoramic image into an orthogonal coordinate system to generate said three dimensional tomographic image of said object.

2. The computer implemented method of claim **1**, further comprising determining, for said each of said one or more discrete points on said two dimensional panoramic image, a plurality of defocused elements of said object along said vertical dimension of said two dimensional panoramic image.

3. The computer implemented method of claim **1**, wherein said three dimensional tomographic image is generated by an image processing application using said orthogonal coordinate system.

4. The computer implemented method of claim **1**, wherein said two dimensional panoramic image is a two dimensional projection of said object developed using said one or more panoramic imaging machines.

5. The computer implemented method of claim **1**, wherein said orthogonal coordinate system is a Cartesian coordinate system.

6. The computer implemented method of claim **1**, further comprising generating a multi-layered three dimensional image by stacking a plurality of three dimensional tomographic images with thinner focal troughs.

7. The computer implemented method of claim **1**, further comprising generating two dimensional cephalometric images using said generated three dimensional tomographic image.

8. The computer implemented method of claim **1**, further comprising obtaining a trajectory of center of rotation of an electromagnetic radiation source of said one or more panoramic imaging machines that rotates around said object in said first coordinate system, wherein said trajectory of said center of rotation of said electromagnetic radiation source achieves said predefined focal planes.

9. The computer implemented method of claim **8**, further comprising obtaining a measured speed of rotation of said electromagnetic radiation source around said object and a measured speed of rotation of a rotating image film drum of said one or more panoramic imaging machines.

10. A computer implemented system for constructing a three dimensional tomographic image from a two dimensional panoramic image of an object, comprising:

one or more panoramic imaging machines having predefined focal planes;

an image processing application provided on a computing device, said image processing application comprising:

a first assignment module that assigns a set of first geometrical attributes in a first coordinate system to one or more focal troughs, said focal troughs defining curved multidimensional zones relating to said predefined focal planes associated with said one or more panoramic imaging machines, wherein said set of said first geometrical attributes represents a vertical

17

dimension, a rotational dimension, and a transverse dimension in said first coordinate system;

a second assignment module that assigns a set of second geometrical attributes in a second coordinate system to said two dimensional panoramic image of said object, wherein said set of second geometrical attributes represents a vertical dimension and a horizontal dimension in said second coordinate system;

a correlator that correlates one or more of said second geometrical attributes with one or more of said first geometrical attributes for reconstructing said panoramic image in multiple dimensions, wherein said multiple dimensions of said reconstructed panoramic image comprise said vertical dimension of said set of said first geometrical attributes, said rotational dimension of said set of said first geometrical attributes, and a transverse dimension, and wherein said vertical dimension of said set of second geometrical attributes corresponds to said vertical dimension of said set of said first geometrical attributes, and wherein said horizontal dimension of said set of said second geometrical attributes corresponds to said rotational dimension of said set of said first geometrical attributes;

a panoramic image analyzer that determines, for each of one or more discrete points on said two dimensional panoramic image, a plurality of defocused elements of said object along said horizontal dimension of said two dimensional panoramic image;

said panoramic image analyzer that determines said transverse dimension for said reconstructed panoramic image by mapping said defocused elements along said horizontal dimension of said two dimensional panoramic image to a translation along said transverse dimension in said first coordinate system on either side of center of said focal troughs; and

a transformation module that transforms said multiple dimensions of said reconstructed panoramic image into an orthogonal coordinate system to generate said three dimensional tomographic image of said object.

11. The computer implemented system of claim 10, wherein said panoramic image analyzer determines, for said each of said one or more discrete points on said two dimensional panoramic image, a plurality of defocused elements of said object along said vertical dimension of said two dimensional panoramic image.

12. The computer implemented system of claim 10, wherein said image processing application generates said three dimensional tomographic image using said orthogonal coordinate system.

13. The computer implemented system of claim 10, wherein said two dimensional panoramic image is a two dimensional projection of said object developed using said one or more panoramic imaging machines.

14. The computer implemented system of claim 10, wherein said image processing application generates a multi-layered three dimensional image by stacking a plurality of three dimensional tomographic images with thinner focal troughs.

15. The computer implemented system of claim 10, wherein said image processing application generates two dimensional cephalometric images using said generated three dimensional tomographic image.

16. The computer implemented system of claim 10, wherein said first assignment module obtains a trajectory of center of rotation of an electromagnetic radiation source of said one or more panoramic imaging machines that rotates

18

around said object in said first coordinate system, wherein said trajectory of said center of rotation of said electromagnetic radiation source achieves said predefined focal planes.

17. The computer implemented system of claim 16, wherein said first assignment module obtains a measured speed of rotation of said electromagnetic radiation source around said object and a measured speed of rotation of a rotating image film drum of said one or more panoramic imaging machines.

18. A computer program product comprising computer executable instructions embodied in a computer readable storage medium, wherein said computer program product comprises:

a first computer parsable program code for assigning a set of first geometrical attributes in a first coordinate system to one or more focal troughs, said focal troughs defining curved multidimensional zones relating to predefined focal planes associated with one or more panoramic imaging machines, wherein said set of said first geometrical attributes represents a vertical dimension, a rotational dimension, and a transverse dimension in said first coordinate system;

a second computer parsable program code for assigning a set of second geometrical attributes in a second coordinate system to a two dimensional panoramic image of an object, wherein said set of said second geometrical attributes represents a vertical dimension and a horizontal dimension in said second coordinate system;

a third computer parsable program code for correlating one or more of said second geometrical attributes with one or more of said first geometrical attributes for reconstructing said panoramic image in multiple dimensions, wherein said multiple dimensions of said reconstructed panoramic image comprise said vertical dimension of said set of said first geometrical attributes, said rotational dimension of said set of said first geometrical attributes, and a transverse dimension, and wherein said vertical dimension of said set of second geometrical attributes corresponds to said vertical dimension of said set of said first geometrical attributes, and wherein said horizontal dimension of said set of said second geometrical attributes corresponds to said rotational dimension of said set of said first geometrical attributes;

a fourth computer parsable program code for determining, for each of one or more discrete points on said two dimensional panoramic image, a plurality of defocused elements of said object along said horizontal dimension of said two dimensional panoramic image;

a fifth computer parsable program code for determining a transverse dimension for said reconstructed panoramic image by mapping said defocused elements along said horizontal dimension of said two dimensional panoramic image to a translation along said transverse dimension in said first coordinate system on either side of center of said focal troughs; and

a sixth computer parsable program code for transforming said multiple dimensions of said reconstructed panoramic image into an orthogonal coordinate system to generate said three dimensional tomographic image of said object.

19. The computer program product of claim 18, further comprising a seventh computer parsable program code for determining, for said each of said one or more discrete points on said two dimensional panoramic image, a plurality of defocused elements of said object along said vertical dimension of said two dimensional panoramic image.

19

20. The computer program product of claim **18**, further comprising an eighth computer parsable program code for generating said three dimensional tomographic image using said orthogonal coordinate system.

21. The computer program product of claim **18**, further comprising a ninth computer parsable program code for gen-

20

erating a multi-layered three dimensional images by stacking a plurality of three dimensional tomographic images with thinner focal troughs.

* * * * *