

US008262662B2

(12) **United States Patent**  
**Beardsley et al.**

(10) **Patent No.:** **US 8,262,662 B2**  
(45) **Date of Patent:** **Sep. 11, 2012**

(54) **BREAK-OFF SCREW EXTENSIONS**

(75) Inventors: **Timothy Beardsley**, Kingston, MA (US); **Douglas Bireley**, Barrington, RI (US); **James J. Roveda**, North Attleboro, MA (US); **Christopher Sicvol**, Boston, MA (US); **Anthony R. Carlone**, Bristol, RI (US)

6,059,786 A 5/2000 Jackson  
6,183,472 B1 2/2001 Lutz  
6,226,548 B1 5/2001 Foley et al.  
6,235,028 B1 5/2001 Brumfield et al.  
6,258,090 B1\* 7/2001 Jackson ..... 606/916  
6,478,795 B1 11/2002 Gournay et al.  
6,485,491 B1 11/2002 Farris et al.

(Continued)

(73) Assignee: **DePuy Spine, Inc.**, Raynham, MA (US)

FOREIGN PATENT DOCUMENTS

DE 202005007495 8/2005

(Continued)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1419 days.

OTHER PUBLICATIONS

MOSS Miami, Brochure "Polyaxial Reduction Screw", 1998 DePuy AcroMed, Inc.

(Continued)

(21) Appl. No.: **11/561,455**

(22) Filed: **Nov. 20, 2006**

(65) **Prior Publication Data**

US 2008/0119849 A1 May 22, 2008

Primary Examiner — Ellen C Hammond

(74) Attorney, Agent, or Firm — Nutter McClennen & Fish LLP

(51) **Int. Cl.**  
**A61B 17/70** (2006.01)

(52) **U.S. Cl.** ..... **606/86 A**; 606/270

(58) **Field of Classification Search** ..... 606/86 A,  
606/306, 270

See application file for complete search history.

(57) **ABSTRACT**


The present invention provides minimally invasive devices and methods for delivering a spinal connector to one or more spinal anchor sites in a patient's spinal column. In one embodiment, a spinal implant and access device is provided that includes a U-shaped receiver member, a bone-engaging member, and an extension member. The U-shaped receiver member can have a recess formed therein that is adapted to seat a spinal connector. The bone-engaging member can extend distally from the receiver member and it can be adapted to engage bone to thereby mate the receiver member to bone. The extension member can extend proximally from the receiver member and it can include a frangible portion formed thereon that is adapted to break when a predetermined force is applied thereto thereby allowing at least a portion of the extension member to be separated from the receiver member.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,448,191 A 5/1984 Rodnyansky et al.  
5,020,519 A 6/1991 Hayes et al.  
5,242,443 A 9/1993 Kambin  
5,520,689 A 5/1996 Schlapfer et al.  
5,649,963 A 7/1997 McDevitt  
5,720,751 A 2/1998 Jackson  
5,772,661 A 6/1998 Michelson  
5,910,141 A 6/1999 Morrison et al.  
5,984,923 A 11/1999 Breard  
5,989,255 A 11/1999 Pepper et al.  
6,030,388 A 2/2000 Yoshimi et al.

**24 Claims, 15 Drawing Sheets**



U.S. PATENT DOCUMENTS

6,530,929	B1	3/2003	Justis et al.	
6,648,888	B1	11/2003	Shluzas	
6,660,006	B2	12/2003	Markworth et al.	
6,740,086	B2	5/2004	Richelsoph	
6,740,089	B2	5/2004	Haider	
6,743,231	B1	6/2004	Gray et al.	
6,802,844	B2	10/2004	Ferree	
6,821,277	B2	11/2004	Teitelbaum	
6,951,538	B2	10/2005	Ritland	
7,008,422	B2	3/2006	Foley et al.	
7,008,424	B2	3/2006	Teitelbaum	
7,011,660	B2	3/2006	Sherman et al.	
7,160,300	B2	1/2007	Jackson	
7,179,261	B2	2/2007	Sicvol et al.	
7,186,255	B2	3/2007	Baynham et al.	
7,188,626	B2	3/2007	Foley et al.	
7,250,052	B2	7/2007	Landry et al.	
7,261,714	B2	8/2007	Richelsoph	
7,491,218	B2	2/2009	Landry et al.	
7,527,638	B2	5/2009	Anderson et al.	
2002/0087188	A1	7/2002	Pedlick et al.	
2002/0161368	A1	10/2002	Foley et al.	
2003/0060826	A1	3/2003	Foley et al.	
2003/0130659	A1	7/2003	Haider	
2003/0199873	A1	10/2003	Richelsoph	
2003/0199884	A1	10/2003	Davison et al.	
2003/0225408	A1	12/2003	Nichols et al.	
2003/0229347	A1	12/2003	Sherman et al.	
2004/0014326	A1	1/2004	Din	
2004/0039384	A1	2/2004	Boehm et al.	
2004/0049191	A1	3/2004	Markworth et al.	
2004/0138662	A1	7/2004	Landry et al.	
2004/0143265	A1*	7/2004	Landry et al. ....	606/61
2004/0162560	A1	8/2004	Raynor et al.	
2004/0172022	A1	9/2004	Landry et al.	
2004/0193160	A1	9/2004	Richelsoph	
2004/0215190	A1	10/2004	Nguyen et al.	
2004/0267275	A1	12/2004	Cournoyer et al.	
2005/0010219	A1	1/2005	Dalton	
2005/0010221	A1	1/2005	Dalton	
2005/0021031	A1	1/2005	Foley et al.	
2005/0033299	A1	2/2005	Shluzas	
2005/0038434	A1	2/2005	Mathews	
2005/0065517	A1	3/2005	Chin	
2005/0080418	A1	4/2005	Simonson et al.	
2005/0085813	A1	4/2005	Spitler et al.	
2005/0131408	A1*	6/2005	Sicvol et al. ....	606/61
2005/0131421	A1	6/2005	Anderson et al.	
2005/0131422	A1	6/2005	Anderson et al.	
2005/0137594	A1*	6/2005	Doubler et al. ....	606/61
2005/0154389	A1	7/2005	Selover et al.	
2005/0171540	A1*	8/2005	Lim et al. ....	606/61
2005/0182407	A1	8/2005	Dalton	
2005/0182410	A1	8/2005	Jackson	
2005/0192570	A1	9/2005	Jackson	
2005/0192579	A1	9/2005	Jackson	
2005/0192589	A1	9/2005	Raymond et al.	
2005/0215999	A1	9/2005	Birkmeyer et al.	
2005/0228380	A1	10/2005	Moore et al.	
2005/0234449	A1	10/2005	Aferzon	
2005/0261687	A1	11/2005	Garamszegi et al.	
2005/0273101	A1	12/2005	Schumacher	

2005/0277934	A1	12/2005	Vardiman
2005/0283245	A1	12/2005	Gordon et al.
2006/0009777	A1	1/2006	Lim et al.
2006/0025771	A1	2/2006	Jackson
2006/0036244	A1	2/2006	Spitler et al.
2006/0036252	A1	2/2006	Baynham et al.
2006/0036255	A1	2/2006	Pond et al.
2006/0058794	A1	3/2006	Jackson
2006/0069391	A1	3/2006	Jackson
2006/0084980	A1	4/2006	Melkent et al.
2006/0084993	A1	4/2006	Landry et al.
2006/0089643	A1	4/2006	Mujwid
2006/0111712	A1	5/2006	Jackson
2006/0111713	A1	5/2006	Jackson
2006/0111714	A1	5/2006	Foley
2006/0142761	A1	6/2006	Landry et al.
2006/0149238	A1	7/2006	Sherman et al.
2006/0184178	A1	8/2006	Jackson
2006/0200135	A1	9/2006	Sherman et al.
2006/0229614	A1	10/2006	Foley et al.
2006/0247630	A1	11/2006	Iott et al.
2006/0264942	A1	11/2006	Lim et al.
2006/0293664	A1	12/2006	Schumacher
2006/0293680	A1	12/2006	Jackson
2007/0018549	A1	1/2007	Chai et al.
2007/0049931	A1	3/2007	Justis et al.
2007/0106123	A1	5/2007	Gorek et al.
2007/0179502	A1	8/2007	Raynor et al.
2007/0185491	A1	8/2007	Foley et al.
2007/0191840	A1	8/2007	Pond et al.
2007/0198015	A1	8/2007	Foley et al.
2007/0288002	A1	12/2007	Carls et al.
2007/0288026	A1	12/2007	Shluzas
2007/0299443	A1	12/2007	DiPoto et al.
2008/0015584	A1	1/2008	Richelsoph
2008/0082103	A1	4/2008	Hutton et al.
2008/0114403	A1	5/2008	Kuester et al.
2008/0119849	A1	5/2008	Beardsley et al.
2008/0125817	A1	5/2008	Arnett et al.
2008/0262318	A1	10/2008	Gorek et al.
2008/0300638	A1	12/2008	Beardsley et al.

FOREIGN PATENT DOCUMENTS


WO	9311715	A1	6/1993
WO	2005006948	A2	1/2005
WO	2006042189	A2	4/2006

OTHER PUBLICATIONS


- MOSS Miami Spinal System, Brochure "Polyaxial Screw" Dec. 2000.
- SYNTHES Spine, Brochure "USS Fracture System Technique Guide" Sep. 2004.
- International Preliminary Report on Patentability, PCT/US2007/023415, Jun. 15, 2009.
- Zimmer Spine, Silhouette Spinal Fixation System, Catalog, Mar. 2005, 6 pgs.
- International Preliminary Report on Patentability, PCT/US07/023415, Jun. 15, 2009.
- International Search Report for Application No. PCT/US2007/014258 dated Dec. 28, 2007.

\* cited by examiner


**FIG. 1A**




**FIG. 1B**




**FIG. 1C**




**FIG. 1D**




**FIG. 1E**




**FIG. 1F**




**FIG. 2A**




**FIG. 2B**




**FIG. 2C**




**FIG. 3A**



**FIG. 3B**




**FIG. 3C**







**FIG. 4A**




**FIG. 4B**



**FIG. 5A**



**FIG. 5B**



**FIG. 5C**




FIG. 6A




FIG. 6B




FIG. 7B







FIG. 7A



**FIG. 8**




**FIG. 9**





**FIG. 10**



**BREAK-OFF SCREW EXTENSIONS**

## FIELD OF THE INVENTION

The present invention relates to tools for use in spinal surgery, and in particular to minimally invasive methods and devices for introducing a spinal connector to one or more spinal anchor sites within a patient's spine.

## BACKGROUND OF THE INVENTION

For a number of known reasons, spinal fixation devices are used in orthopedic surgery to align and/or fix a desired relationship between adjacent vertebral bodies. Such devices typically include a spinal connector, such as a relatively rigid fixation rod, that is coupled to adjacent vertebrae by attaching the connector to various anchoring devices, such as hooks, bolts, wires, or screws. The connector can have a predetermined contour that has been designed according to the properties of the target implantation site, and once installed, the instrument holds the vertebrae in a desired spatial relationship, either until healing or spinal fusion has taken place, or for some longer period of time.

Spinal connectors can be anchored to specific portions of the vertebrae. Since each vertebra varies in shape and size, a variety of anchoring devices have been developed to facilitate engagement of a particular portion of the bone. Pedicle screw assemblies, for example, have a shape and size that is configured to engage pedicle bone. Such screws typically include a threaded shank that is adapted to be threaded into a vertebra, and a head portion having a receiving element, usually in the form of a U-shaped head. A set-screw, plug, or similar type of fastening mechanism is used to lock the spinal connector, e.g., a spinal rod, into the receiving head of the pedicle screw. In use, the shank portion of each screw is threaded into a vertebra, and once properly positioned, a rod is seated through the receiving member of each screw and the rod is locked in place by tightening a cap or other fastener mechanism to securely interconnect each screw and the spinal rod.

Minimally invasive devices and methods for implanting spinal fixation devices are advantageous because such devices and methods utilize few incisions for introducing and implanting anchoring devices and spinal connectors at a target site within a patient's spine. Such procedures offer advantages over invasive techniques because they reduce the amount of damage to surrounding tissue and muscle and the amount of time required to complete the procedure.

Accordingly, there is a need for improved minimally invasive devices and methods for introducing a spinal connector into a patient's spine.

## SUMMARY OF THE INVENTION

The present invention provides minimally invasive devices and methods for implanting a spinal anchor in bone, for percutaneously delivering various tools and implants to the spinal anchor through an extension coupled thereto, and for removing the extension coupled to the spinal anchor. In one embodiment, a spinal implant and access device is provided that includes a U-shaped receiver member, a bone-engaging member, and an extension member. The U-shaped receiver member can have a recess formed therein that is adapted to seat a spinal connector, such as a spinal rod. In one exemplary embodiment, the receiver member can have a maximum outer diameter that is substantially the same as a maximum outer diameter of the extension member. The bone-engaging member can extend distally from the receiver member and it can be

adapted to engage bone to thereby mate the receiver member to bone. A variety of configurations are available for the bone-engaging member, for example, in one embodiment the bone-engaging member can be a threaded shank such as a bone screw.

As indicated above, the access device can include an extension member. The extension member can extend proximally from the receiver member and it can have a lumen extending therethrough. Although a variety of shapes and sizes are available for the extension member in an exemplary embodiment, the extension member has a length that is adapted to span through a skin surface in a patient to the U-shaped receiver member when the bone engaging member is implanted in a vertebra. The extension member can also include a frangible portion formed thereon that is adapted to break when a predetermined force is applied thereto thereby allowing at least a portion of the extension member to be separated from the receiver member. In one embodiment, the extension member can include a proximal end and a distal end that is coupled to the receiver member. The frangible portion can be formed adjacent to the distal end.

The extension member can also have a variety of configurations. For example, in one embodiment, the extension member can include first and second opposed extension arms that extend proximally from the U-shaped receiver member and that are separated by opposed slots that extend between the arms. The opposed slots can extend from the proximal end to the distal end or the first and second extension arms can be coupled to one another at least one location located proximal to the frangible portion. In another embodiment, the extension member can be a hollow elongate tube. The hollow elongate tube can include opposed slots that extend from a distal end of the tube and that terminate distal to a proximal end of the tube. Various configurations are also available for the frangible portion of the extension member. For example, in one embodiment, the frangible portion can include an annular groove formed around the extension member.

In another embodiment, a removal tool is provided. Although a variety of configurations are available for the removal tool, in an exemplary embodiment the tool can include an elongate member having a proximal portion that is adapted to be positioned adjacent to a skin incision and a distal portion that is adapted to be positioned adjacent to a vertebra and to be received within a lumen formed in an extension member of a spinal anchor. The distal portion can include an engagement mechanism that is adapted to engage an inner surface of the extension member of the spinal anchor and to apply a radially directed force to the extension member disposed therearound to break at least a portion of the extension member apart from the spinal anchor. The engagement mechanism can have a variety of configurations. For example, in one embodiment, the engagement mechanism can be a cam formed on a distal portion of the elongate member. In another embodiment, the engagement mechanism can be a set screw formed on a distal portion of the elongate member. The set screw can have a proximal threaded portion with an outer diameter that is greater than an outer diameter of a distal threaded portion. The removal tool can also include a handle disposed on a proximal portion that is adapted to rotate the elongate member to cause the engagement mechanism to apply a radially directed force to an extension member that is disposed therearound.

Exemplary spinal systems are also provided. In one embodiment, system can include a spinal anchor and a removal tool. The spinal anchor can be adapted to be implanted in bone and it can have a receiver member with a recess formed therein for seating a spinal connector. An

extension member can be frangibly coupled to the receiver member and it can be adapted to span through a skin surface in a patient to the receiver member when the receiver member is coupled to a vertebra. A variety of configurations are available for the extension member and the removal tool, including those discussed above.

Methods for implanting a spinal anchor and removing a percutaneous access device from a spinal anchor are also provided. In one embodiment, the method can include percutaneously delivering a spinal anchor to a vertebra, advancing a spinal connector through an extension member that is frangibly attached to the spinal anchor, and separating the extension member from the spinal anchor. Advancing the spinal connector through the extension member can generally include advancing the connector in a first orientation substantially parallel to a longitudinal axis of the extension member and manipulating the connector to extend in a second orientation angled with respect to the first orientation to position the connector in relation to the spinal anchor. In one embodiment, the spinal connector can extend substantially parallel to a patient's spinal column in the second orientation. A variety of techniques can be used to separate the extension member from the spinal anchor. For example, removing the percutaneous access device from the spinal anchor can generally include inserting an elongate member into a lumen formed through the percutaneous access device and actuating the elongate member to cause the elongate member to apply a radially directed force to an inner surface of the access device to break at least a portion of the device away from the spinal anchor. In one exemplary embodiment, actuating the elongate member can include rotating the elongate member such that an engagement mechanism disposed on a distal portion of the member engages and applies the radially directed force to an inner surface of the access device. The elongate member can be rotated by applying a force to a handle disposed on a proximal end of the elongate member.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be more fully understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

FIG. 1A is a perspective view of a spinal implant and access device having an extension frangibly coupled to a spinal anchor according to one embodiment of the present invention;

FIG. 1B is an enlarged perspective view of the frangible portion of the spinal implant and access device shown in FIG. 1A;

FIG. 1C is a cross-sectional view of a portion of the spinal implant and access device of FIG. 1A;

FIG. 1D is a perspective view of another embodiment of an extension member having a closed configuration for use with a spinal anchor and access device;

FIG. 1E is a perspective view of another embodiment of an extension member having an open configuration for use with a spinal anchor and access device;

FIG. 1F is a perspective view of another embodiment of a proximal end of an extension member having threads formed therein and flats formed on an external surface thereof;

FIG. 2A is a perspective view of a removal tool according to one embodiment of the present invention;

FIG. 2B is an enlarged perspective view of a distal end of the removal tool shown in FIG. 2A;

FIG. 2C is a cross-sectional view of the tool shown in FIG. 2B;

FIG. 3A is a perspective view of a removal tool according to another embodiment of the present invention;

FIG. 3B is a cross-sectional view of the removal tool shown in FIG. 3A disposed within the extension member of the device of FIG. 1A;

FIG. 3C is a cross-sectional view of the removal tool and extension member shown in FIG. 3B showing the tool applying a force to an inner surface of the extension member;

FIG. 4A is a perspective view of another embodiment of a removal tool having first and second breaker arms, showing the tool coupled to the device of FIG. 1A;

FIG. 4B is a perspective view of a distal portion of another embodiment of an extension member;

FIG. 5A is an illustration showing the device of FIG. 1A implanted in adjacent vertebra, and showing a spinal rod about to be inserted therethrough;

FIG. 5B is an illustration showing the spinal rod of FIG. 5A being passed through the slots in the extension members of the devices of FIG. 5A;

FIG. 5C illustrates the rod of FIG. 5B positioned within the spinal anchor of the devices of FIG. 5B;

FIG. 6A is an illustration showing a driver tool being used to apply a fastening element to the spinal anchor of FIG. 5C to lock the rod within the anchor;

FIG. 6B is an illustration of one embodiment of a torque driver and a stabilizer to facilitate tightening of the fastening element of FIG. 6A;

FIG. 7A is an illustration showing another embodiment of a technique for removing the extension arms from the spinal anchor of the device of FIG. 1A, showing a removal tool in an initial position;

FIG. 7B is an illustration showing the removal tool of FIG. 7A in a final position;

FIG. 8 is an illustration showing one embodiment of a jig and a targeting device in use with the spinal anchor and access device of FIG. 1A;

FIG. 9 is an illustration showing one embodiment of a distractor device in use with the spinal anchor and access device of FIG. 1A; and

FIG. 10 is an illustration showing one embodiment of a technique for using the spinal anchor and access device of FIG. 1A to correct a spinal deformity.

#### DETAILED DESCRIPTION OF THE INVENTION

Certain exemplary embodiments will now be described to provide an overall understanding of the principles of the structure, function, manufacture, and use of the devices and methods disclosed herein. One or more examples of these embodiments are illustrated in the accompanying drawings. Those of ordinary skill in the art will understand that the devices and methods specifically described herein and illustrated in the accompanying drawings are non-limiting exemplary embodiments and that the scope of the present invention is defined solely by the claims. The features illustrated or described in connection with one exemplary embodiment may be combined with the features of other embodiments. Such modifications and variations are intended to be included within the scope of the present invention.

The present invention provides minimally invasive methods and devices for introducing a spinal connector into a surgical site in a patient's spinal column. In general, a spinal implant and access device is provided for creating a minimally invasive pathway from a skin incision to a spinal anchor site for delivering various tools and devices to the spinal anchor site. In an exemplary embodiment, the access device can be in the form of an extension member that is mated to or

5

formed on and extends proximally from a spinal anchor. The extension member can be used to implant the spinal anchor, and, once the anchor is implanted, to manipulate the spinal anchor from outside of the patient's body as well as to provide a pathway through a skin surface to the spinal anchor for introducing various tools and spinal system components, such as spinal connectors, fasteners, installation tools, and removal tools. The extension member can also be adapted to be easily detached from or broken off of the spinal anchor once the procedure is complete. Such a configuration eliminates the steps of assembling, disassembling, and cleaning which are currently required for conventional screw extensions.

FIG. 1A illustrates one exemplary embodiment of a spinal implant and access device 10 having an extension member 12 that is mated to a spinal anchor 14. As shown, the anchor 14 includes a U-shaped receiver member 16 and a bone-engaging member 14b that extends distally from the receiver member 16. The U-shaped receiver member 16 can have a recess 16a formed therein that is adapted to seat a spinal connector, such as a spinal rod. The bone-engaging member 14b can extend distally from the receiver member 16 and it can be adapted to engage bone such that it is effective to mate the receiver member 16 to bone. The extension member 12 can include a distal end 12b that is mated to and extends proximally from the receiver member 16. In use, the extension member 12 can define a pathway from a skin incision in a patient to the spinal anchor, which can be implanted in a vertebra of a spine. In an exemplary embodiment, the extension member 12 can be removably mated to the receiver member 16 to allow at least a portion of the extension member 12 to be separated from the receiver member 16.

The anchor can have a variety of configurations. In the embodiment shown in FIG. 1A, the anchor 14 is in the form of a spinal screw. As shown, the spinal screw 14 includes a distal bone-engaging member 14b, e.g., a threaded shank, and a proximal U-shaped receiver member 16 that is adapted to seat a spinal connector, such as a rigid or dynamic spinal rod. The U-shaped receiver member 16 can include opposed arms 16b, 16c having cut-outs 16d, 16e formed therein that define the U-shaped recess 16a. The bone-engaging member 14b can be fixedly attached to the receiver member 16 to form a mono-axial screw, or alternatively the bone-engaging member 14b can be configured as a polyaxial screw that is rotatably disposed through an opening formed in the distal end of the receiver member 16 to allow rotation of the bone-engaging member 14b with respect to the receiver member 16. A variety of techniques known in the art can be used to allow rotation of the receiver member 16 with respect to the bone-engaging member 14b. As shown in FIG. 1C, the U-shaped receiver member 16 can also include a bushing 15 disposed therein. A person skilled in the art will appreciate that a variety of other anchors can be used with the devices and methods of the present invention, including, for example, spinal hooks, bolts, and wires.

The extension member 12 that is coupled to the anchor 14 can also have a variety of configurations. In the illustrated embodiment, the extension member 12 extends proximally from the receiver member 16 and defines a lumen 17 extending therethrough. In particular, a distal end of opposed arms 12c, 12d of the extension member 12 can be mated to or integrally formed with and can extend proximally from a proximal end of the opposed arms 16b, 16c of the receiver member 16. As will be discussed in more detail below, this will allow opposed slots 13a, 13b in the extension member 12 to align with the opposed cut-outs 16d, 16e in the receiver member 16. The inner lumen 17 of the extension member 12

6

can define a longitudinal axis L that extends between proximal and distal ends 12a, 12b of the extension member 12. The size of the extension member 12 can vary depending on the intended use, but in an exemplary embodiment it has a length that allows the proximal end 12a of the extension member 12 to be positioned outside the patient's body, while the distal end 12b of the extension member 12 is coupled to the spinal anchor 14 which is implanted in a vertebra in a patient's spine. More particularly, the extension member 12 can have a length that allows the extension member 12 to span through the skin surface to the receiver member 16 when the bone engaging member is fully implanted in a vertebra, and the receiver member 16 is positioned adjacent to the vertebrae, e.g., the bottom surface of the receiver member 16 is in contact with or within about 1 mm to 2 mm of the vertebra. Such a configuration is particularly advantageous as it allows the extension member 12 to be used to introduce and facilitate positioning of various tools and devices therethrough, and it also allows the extension member 12 to be used to manipulate the anchor from outside of the patient's body. The length  $l_e$  of the extension member 12 is illustrated in FIG. 1A, and is measured from the proximal-most end of the extension member 12 to the proximal end of the receiver member 16, i.e., to a frangible portion 18 that couples the extension member to the U-shaped receiver member 16 as will be discussed in more detail below. In an exemplary embodiment, the length  $l_e$  is greater than about 25 mm, and more preferably is greater than about 55 mm. Thus, in such embodiments, the length of the extension member 12 and the receiver member 16 (which can be approximately 15 mm from the proximal-most end to the bottom or distal end), can be greater than about 40 mm, and more preferably greater than about 70 mm. Exemplary lengths  $l_e$  of the extension member 12 range from 85 mm to 185 mm (100 mm to 200 mm with the receiver member), and more preferably from 135 mm to 175 mm (150 mm to 190 mm with the receiver member). In certain exemplary embodiments, the extension member can have a length  $l_e$  of about 145 mm (160 mm with the receiver member) where the extension member has an open configuration, as will be discussed in more detail below, and a length  $l_e$  of about 165 mm (180 mm with the receiver member) where the extension member has a closed configuration.

The extension member 12 can also be adapted to provide a minimally invasive pathway for the delivery of various implants and devices. In an exemplary embodiment, shown in FIG. 1C, the extension member 12 has inner and outer diameters  $d_i$ ,  $d_o$  that are substantially the same as the inner and outer diameters  $d_{ri}$ ,  $d_{ro}$  of the receiver member 16. The matching inner diameters will allow spinal connectors, fasteners, and other implants and devices to be inserted therethrough and coupled to the receiver member 16, and the matching outer diameters will allow a relatively small incision to be used to introduce the spinal implant and access device 10 into the body. It will also allow the extension member 12 and the anchor 14 to be introduced through a cannula or other access port, if necessary.

As indicated above, the extension member 12 can also include cut-outs or slots to facilitate the introduction of tools, spinal connectors, and other implants therethrough. A variety of configurations are available for the cut-outs. For example, as shown in FIG. 1A, the extension member 12 can include opposed slots 13a, 13b that extend between and separate the first and second opposed extension arms 12c, 12d that extend proximally from the U-shaped receiver member 16. The opposed slots 13a, 13b can extend from the proximal end 12a to the distal end 12b, such that the extension member 12 has an open configuration, or the first and second extension arms

12c, 12d can be coupled to one another at one or more locations along the length thereof, such that the extension member 12 has a closed configuration. FIGS. 1A and 1C illustrate the extension having a closed configuration, in which the first and second extension arms 12c, 12d are coupled to one another by a web or connector 15 located distal to the midpoint of the extensions 12c, 12d and proximal to a frangible portion 18, which will be discussed in more detail below. In use, the slot(s) 13a, 13b can be configured to allow various implants and devices to be passed therethrough. Thus, each slot 13a, 13b preferably has a width that is sufficient to accommodate the size of an implant or device to be passed therethrough. In another embodiment of an extension having a closed configuration, as shown in FIG. 1D, the first and second extension arms 12c', 12d' can be coupled to one another at the proximal end 12a' of the extension member 12'. Such a configuration resembles a hollow elongate tube having slots 13a', 13b' formed in the sidewalls thereof and extending proximally from the distal end 12b' thereof and terminating distal to the proximal end 12a' of the extension member 12'.

Alternatively, the extension member can have an open configuration. This is illustrated in FIG. 1E, which shows an extension member 12'' having first and second extension arms 12c'', 12d'' that are separated by slots 13a'', 13b'' that extend from the distal end 12b'' of the extension member 12'' and that extend through the entire proximal portion of the extension member 12'' such that the proximal end 12a'' of each arm 12c'', 12d'' is separated from one another. Accordingly, the quantity, shape, and size of the slot(s) 13a, 13b can vary. A person skilled in the art will appreciate that the extension member 12 can include any number of sidewall openings having any shape that is sufficient to allow desired implants and devices to be passed therethrough.

The extension member 12 can also include other features to facilitate use of the device. For example, in another embodiment, shown in FIG. 1F, the extension member 12''' includes threads 12t''' formed in a proximal portion of the extension member 12''' for mating with corresponding threads formed on a driver tool, reduction device, or other delivery device. The threads 12t''' will facilitate advancement of the delivery device through the extension member 12'''. For example, the threads 12t''' can mate with corresponding threads on a rod reduction device to allow the rod reduction device to reduce a spinal rod or other spinal connector into the receiver member of the anchor. While FIG. 1F illustrates threads 12t''' formed within the proximal end of the extension member 12''', the threads 12t''' can be formed at any location along the length of the extension member 12'''. For example, threads can be formed within the connector 15 (FIG. 1C) and around the circumference of the inner lumen of the extension member 12. As further shown in FIG. 1F, the extension member 12''' can also or alternatively include one or more flats 12f''' formed on an external surface thereof for use with external devices, such as a rod stabilizer. A person skilled in the art will appreciate that the extension member can have various other configurations to facilitate use with other delivery tools and/or fastening elements.

Referring back to FIGS. 1A-1C, as indicated above the extension member 12 can be removably coupled to the receiver member 16. In an exemplary embodiment, the distal end 12b of the extension member 12 is integrally formed with the receiver member 16, i.e., the extension member 12 and receiver member 16 have a unitary configuration. A frangible portion 18, best shown in FIG. 1A, can be formed on the extension member 12 to allow the extension member 12 to be frangibly separated from the receiver member 16. The frangible portion can be formed at various locations along the

extension member 12, but in an exemplary embodiment the frangible portion 18 is located adjacent to the distal end 12b of the extension member 12. The frangible portion 18 can be adapted to break when a predetermined force is applied thereto thereby allowing at least a portion of the extension member 12 to be separated from the receiver member 16. A variety of techniques can be used to form a frangible portion 18. For example, in one embodiment shown in FIGS. 1A-1B, the frangible portion 18 can be formed by a reduced diameter region or thinned region of material formed between the extension member 12 and the receiver member 16. Other configurations for the frangible portion 18 can include webbing, an annular groove formed in an outer or inner surface of the extension member 12, or other techniques known in the art. A variety of materials, including both plastics and metals, can be used for the frangible portion 18, and the frangible portion 18 need not be made from the same material used for the anchor 14 or extension member 12. By way of non-limiting example, the anchor 14 can be made from a metallic material, such as stainless steel, and the frangible portion 18 and extension member 12 can be formed from a plastic. Such a configuration allows the extension member 12 and frangible portion 18 to act as insulators during neuromonitoring. In use, the frangible portion 18 can provide a weak spot in the extension member 12 to allow the extension member 12 to be separated from the receiver member 16 when a predetermined force is applied thereto.

Several techniques can be used to apply the predetermined force to the frangible portion 18 of the extension member 12. For example, a removal tool 20 can be inserted through a lumen 17 of the percutaneous access device 12 or extension member 12 and it can be actuated to apply a radially directed force to an inner surface 18c of the extension member 12 to break the extension member 12 away from the spinal anchor 14. A variety of configurations are available for the removal tool 20. FIG. 2A illustrates one exemplary removal tool 20 that generally includes an elongate member 22 having a proximal end 22a that is adapted to remain outside the body and a distal end 22b that is adapted to be inserted through the lumen 17 of the extension member 12 and to be positioned adjacent to the spinal anchor 14. The distal portion 22b can include an engagement mechanism 24 that is adapted to engage an inner surface 18c of the extension member 12 and to apply an outward or radially directed force to the extension member 12 disposed therearound to break at least a portion of the extension member 12 apart from the spinal anchor 14. The removal tool 20 can also include a handle 26 disposed on the proximal end 22a of the elongate member 22. The handle 26 can be used to manipulate the device, as will be discussed in more detail below.

The engagement mechanism 24 can have a variety of configurations, and the size and shape of the engagement mechanism 24 can vary depending on the configuration of the extension member 12. For example, in the embodiment shown in FIGS. 2A-2C, the engagement mechanism 24 is in the form of a set screw or other threaded member formed on a distal portion 22b of the elongate member 22 and adapted to engage the complementary threads formed in the distal end of the extension member 12. As shown in FIGS. 2B and 2C, the engagement mechanism 24 has a proximal threaded portion 24a with an outer diameter that is greater than an outer diameter of a distal threaded portion 24b. In other words, the thread on the proximal portion is oversized relative to the thread on the distal portion. The proximal threaded portion 24a can be sized to engage threads formed within the extension member 12, and the distal threaded portion 24b can be configured to engage threads formed in the receiver member 16. FIG. 1B

illustrates threads **12t** formed on inner surface of the extension member **12** just proximal to the frangible portion **18**, and threads **16t** formed on an inner surface of the receiver member **16** just distal to the frangible portion **18**. The proximal threaded portion **24a** on the engagement mechanism **24** can also have a size that is configured to apply a radially directed force to the threads **12t** on the extension member **12** to break the frangible portion **18** and thereby separate the extension member **12** from the receiver member **16**. This can be achieved using various techniques. For example, a distal-most portion of the extension member **12**, i.e., the portion located adjacent to or at the frangible portion **18**, can be tapered such that the threaded portion **24a** will apply a radially directed force thereto to cause the frangible portion **18** to break. Alternatively, the threads on the proximal threaded portion **24a** can have an increasing diameter to cause the proximal threaded portion **24a** to apply a radially directed force to the extension member **12**. The distal threaded portion **24b**, on the other hand, can have threads that complement the threads **16t** within the receiver member **16** to allow the two portions to mate to one another. In use, the distal threaded portion **24b** can thus function as a locking mechanism for locking a spinal connector, such as a spinal rod, within the receiver member **16**.

The engagement mechanism **24**, or a portion thereof, can also optionally be frangibly mated to the distal end **22b** of the elongate member **22**. This will allow the elongate member **22** to be detached from the engagement mechanism **24**, thus allowing the engagement mechanism **24**, or a portion thereof, to remain mated to the receiver member **16** of the anchor **14**. The frangible portion can be formed at various locations on the removal tool **20**. For example, FIG. 2C illustrates a frangible portion **22f** formed within the engagement mechanism **24** at a location that is between the proximal and distal threaded portions **24a**, **24b**. In other embodiments, the proximal and distal threaded portions **24a**, **24b** can be frangibly mated to one another, thus allowing the proximal threaded portion **24a** to be separated from the distal threaded portion **24b** and removed from the body.

In use, the removal tool **20** can be actuated by inserting the elongate member **22** through the extension member **12** to position the engagement mechanism **24** within the distal end **12b** of the extension member **12**. The distal threaded portion **24b** can pass through the threads **12t** formed within the distal end **12b** of the extension member **12**, as they will have a size that is less than a size of the threads **12t** formed within the extension member **12**. The tool **20** can then be rotated with respect to the extension member **12**, using, for example, the handle **26**. As the tool **20** is rotated, the proximal threaded portion **24a** will engage the threads **12t** formed in the extension portion while the distal threaded portion **24b** engages the threads **16t** formed within the receiver member **16**. Continued rotation will cause the proximal threaded portion **24a** to apply a radially directed force to the extension member **12**, thereby breaking the frangible portion **18** formed between the extension member **12** and the receiver member **16**. The extension member **12** can thus be removed from the patient's body, leaving the spinal anchor **14** implanted in bone.

In another embodiment, the engagement mechanism can be in the form of a cam, wedge, or other inclined surface formed on a distal portion of an elongate shaft of a removal tool. FIGS. 3A-3C illustrate a distal end **22b'** of an elongate shaft **22'** of a removal tool having an engagement mechanism **24'** in the form of a cam having first and second fins **30a'**, **30b'** disposed on opposed sides of and extending radially outward from the shaft **22'**. Each fin **30a'**, **30b'** can have a length **1** that is configured to correspond to a width of the slots **13a**, **13b**

formed in the arms **12c**, **12d** of the extension member **12** to allow the fins **30a'**, **30b'** to be slidably received therein during insertion of the removal tool through the extension member **12**. Each fin **30a'**, **30b'** can also have height **h** that increases radially to form a ramped surface such that the fins **30a'**, **30b'** can apply a radially directed force to the arms **12c**, **12d** of the extension member **12**. In particular, after the tool is inserted to position the fins **30a'**, **30b'** within the slots **13a**, **13b** and adjacent to the distal end of the extension member **12**, as shown in FIGS. 3A and 3B, the removal tool can be rotated to cause the fins **30a'**, **30b'** to move in between and into alignment with the arms **12c**, **12d** of the extension member **12**, as shown in FIG. 3C. The increasing height **h** of each fin **30a'**, **30b'** will apply a radially directed force to an inner surface **18c** of each arm **12c**, **12d**, thereby causing the frangible portion to break thereby separating the extension member **12** from the receiver member **16** of the spinal anchor **14**.

In another embodiment, the removal tool shown in FIGS. 3A-3C can include first and second arm members (not shown) that extend along the length of the elongate shaft. The fins can be rotated with respect to the first and second arm members to cause the fins to move in between and into alignment with the arm members. Similar to the removal tool described above, the increasing height of each fin will apply a radially directed force to an inner surface of each arm member, thereby causing the first and second arm members to apply a radially directed force to an inner surface of the extension member. The frangible portion will thus break thereby separating the extension member from the receiver member of the spinal anchor.

In another embodiment, shown in FIG. 4A, the removal tool **20''** can include first and second breaker arms **21a''**, **21b''** that are configured to engage the proximal end of the first and second arms **12c**, **12d** of the extension member **12**. Various techniques can be used to engage the arms **12c**, **12d**, but as shown in FIG. 4A the breaker arms **21a''**, **21b''** each include a U-shaped member for receiving a proximal end of the arms **12c**, **12d** on the extension member **12**. Each breaker arm **21a''**, **21b''** can also include a handle **23a''**, **23b''** formed thereon, and once the breaker arms **21a''**, **21b''** are engaged with the arms **12c**, **12d** on the extension member **12**, the handles **23a''**, **23b''** can be rotated in opposite directions to break the arms **12c**, **12d** of the extension member **12** away from the receiver member **16** of the spinal anchor **14**. In another embodiment, in order to facilitate removal of the arms of the extension member, the arms can have complementary features formed therein that allow the arms to pass through one another. For example, FIG. 4B illustrates a distal end of first and second extension arms **11a**, **11b** having cut-outs **11c** formed therein and offset from one another such that one arm, e.g., arm **11a**, can pass through the other arm, e.g., arm **11b** as the arms **11a**, **11b** are rotated by the breaker arms **21a''**, **21b''**.

Exemplary methods for implanting a spinal anchor **14** and delivering various tools and devices are also provided. In one exemplary embodiment, the procedure can begin by forming a minimally invasive percutaneous incision through tissue located adjacent to a desired implant site. The incision can be a relatively small incision having a length that is less than a diameter or width of the device being inserted therethrough, a spinal anchor and access device. Once the incision is made, a spinal anchor and access device, such as device **10**, can be delivered to the anchor site. In particular, the anchor **14** can be inserted through the incision with the extension member **12** frangibly attached thereto and extending through the skin incision and outside of the patient's body. The bone-engaging member **14b** of the anchor **14** can be driven into bone using a tool, such as a driver, that is passed through the extension member **12**. While not shown, the extension member **12** can

## 11

optionally include threads formed therein for mating with corresponding threads formed on the driver tool, thus facilitating advancement of the driver through the extension member 12 to drive the bone-engaging member 14b into bone. When the spinal anchor 14 is fully implanted, the bone-engaging member 14b will be fully disposed within bone and the receiver member 16 will be located adjacent to the bone such that it is either in contact with the bone or relatively close to the bone, i.e., 1 mm to 2 mm away from the bone. The extension member 12 will extend from the receiver member 16 and through the skin incision, thereby providing a pathway that spans through the skin incision to the anchor 14. Additional spinal anchor and access devices can be implanted in adjacent vertebrae using the same technique, or using other techniques known in the art.

Once the anchor 14 is implanted, the extension member 12 can be used to deliver various spinal connectors, fasteners, and other tools and devices to the implant site. For example, a spinal connector, such as a spinal rod, can be introduced through the extension member and positioned within the spinal anchor 14, and optionally within one or more additional spinal anchors implanted in adjacent vertebrae. FIGS. 5A-5C illustrate one exemplary method for inserting a spinal rod 40. The rod 40 is introduced through the extension member 12 in a first orientation, shown in FIG. 5A, in which the rod 40 is substantially parallel to the longitudinal axis of the extension member 12. The spinal rod 40 can then be manipulated to extend at an angle with respect to the first orientation, such that the rod 40 extends in a direction substantially transverse to the longitudinal axis L of the extension member 12, for example, in a direction that is substantially parallel to the patient's spine, as shown in FIG. 5C. Since the length of the spinal rod 40 will necessarily be greater than the inner diameter of the extension member 12, the slots 13a, 13b in the extension member 12 will allow the spinal rod 40 to pivot and pass therethrough while being transitioned from the first orientation to the second orientation, as shown in FIG. 5B. A person skilled in the art will appreciate that the exact position of the spinal rod 40 with respect to the longitudinal axis L of the extension member 12 will of course vary depending on the configuration of the spinal rod 40 or other spinal connector. As further shown in FIGS. 5A-5C, movement of the spinal rod 40 can be achieved using a manipulator or driver device 50. The manipulator device can have a variety of configurations, but it should be effective to allow controlled movement of the rod 40.

Once the spinal rod 40 is properly positioned and fully seated in the receiver member 16, a closure mechanism or fastener can be inserted through the extension member 12 and applied to lock the rod 40 in place. A variety of closure mechanisms and tools for delivering closure mechanisms are known in the art, and they can be used with the present invention. By way of non-limiting example, FIG. 6A illustrates a driver tool 60 for delivering a set screw 62 to the spinal anchor 14 to lock the spinal rod 40 within the receiver member 16 of the spinal anchor 14. As shown, the set screw 62 is coupled to the distal end of the driver tool 60, which is passed through the inner lumen of the extension member 12. The illustrated driver tool 60 includes threads 60t formed on the shaft thereof for mating with corresponding threads (not shown) formed within the extension member 12. The threaded connection facilitates distal movement or advancement of the driver tool 60 through the extension member 12, thereby allowing the set screw 62 to reduce the rod 50 into the U-shaped recess in the receiver member 16. Final tightening of the set screw 62 can optionally be accomplished using a standard torque driver 64 along with a stabilizer 66 to prevent

## 12

the receiver member 16 from rotating, as shown in FIG. 6B. The stabilizer 66 can interface with flats formed on the external surface of the extension member 12, as previously discussed with respect to FIG. 1F.

While not shown, removal tool 20 previously described herein can optionally be used to deliver the engagement mechanism 24, which includes a distal threaded portion 24b that functions as a set screw. Once the engagement mechanism 24 is mated to the receiver member 16, the elongate member 22, and optionally the proximal threaded portion 24a of the engagement mechanism 24, can be frangibly detached from the distal threaded portion 24b to allow the removal tool 20 to be removed from the extension member 12 while the distal threaded portion 24b remains mated to the receiver member 16. This step can be repeated for adjacent spinal anchor(s). A person skilled in the art will appreciate that the spinal connector does not need to be directly attached to each anchor, and that it can be indirectly attached to the anchors using, for example, a band clamp, a slotted offset connector, or other techniques known in the art.

Where the removal tool is not configured to simultaneously deliver a fastening element while breaking the extension member 12 away from the receiver member 16, the extension member 12 can be detached from the anchor 14 by inserting a removal tool through the extension member 12 to apply a force to the frangible portion 18 formed between the extension member 12 and the spinal anchor 14. FIGS. 7A and 7B illustrate one exemplary method for breaking the extension member 12 away from the receiver member 16 of the spinal anchor 14 using the cam-type engagement mechanism 24' shown in FIGS. 3A-3C. As shown in FIGS. 7A and 7B, the removal tool 20' is passed through the extension member 12 to position the engagement mechanism (not shown) within the distal end of the extension member 12. The first and second fins on the engagement mechanism can be passed through the slots 13a, 13b formed in the extension member 12. The tool 20' is then rotated to cause the fins to pass between the arms 12c, 12d of the extension member 12, thereby applying a radially directed force to the arms 12c, 12d to break the frangible portion 18. The extension member 12 can thus be removed from the patient, leaving the spinal anchor 14 implanted in bone. As further shown in FIGS. 7A and 7B, a stabilizing tool 76 can optionally be passed through at least a portion of the extension member 12 for stabilizing the extension member 12 while the removal tool 20' is rotated.

In other embodiments, one or more spinal anchor and access devices can be implanted in adjacent vertebrae, and the extension member on each device can be used to perform other procedures, such as pedicle targeting, anchor alignment, distraction, deformity correction, etc. For example, the extension member 12 can also be used to manipulate the receiver member 16 coupled thereto. For example, the proximal end 12a of the extension member 12 can be grasped by a user and angularly oriented to thereby move the receiver member 16 relative to the bone-engaging member 14b. Where the anchor 14 is a monoaxial bone screw, movement of the extension member 12 will move the vertebra that the anchor 14 is implanted in. FIG. 8 illustrates a jig 70 mated to one or more extension members implanted in adjacent vertebrae. The jig 70 can be used, for example, to guide a pedicle targeting tool 72 and aid in the alignment of adjacent anchors. In yet another embodiment, as shown in FIG. 9, a distractor 80 can be mated to the extension member to facilitate the distraction of adjacent vertebrae. In another embodiment, shown in FIG. 10, multiple spinal anchor and access devices can be implanted in adjacent vertebrae and they can be used to correct a spinal deformity. For example, as shown in FIG. 10, the

## 13

extension member of each device can aid in the placement of an extra long spinal rod **100**, and insertion of the rod **100** through each extension member can move the extension members to thereby move the adjacent vertebrae into a desired orientation relative to one another. Separate instruments can optionally be used to further distract and/or manipulate the adjacent vertebrae. A person skilled in the art will appreciate that a variety of other tools and devices can be mated to and used in conjunction with the extension member disclosed herein.

One skilled in the art will appreciate further features and advantages of the invention based on the above-described embodiments. Accordingly, the invention is not to be limited by what has been particularly shown and described, except as indicated by the appended claims. All publications and references cited herein are expressly incorporated herein by reference in their entirety.

What is claimed is:

1. A spinal implant and access system, comprising:
  - a U-shaped receiver member having a recess formed therein and adapted to seat a spinal connector;
  - a bone-engaging member extending distally from the receiver member and adapted to engage bone to mate the receiver member to bone;
  - an extension member extending proximally from the receiver member and defining a lumen extending there-through, the extension member having a length that is greater than about 55 mm such that the extension member is adapted to span through a skin surface in a patient to the U-shaped receiver member when the bone engaging member is implanted in a vertebra, and a frangible portion formed thereon and adapted to break when a predetermined force is applied thereto to allow at least a portion of the extension member to be separated from the receiver member; and
  - a removal tool configured to be inserted into the lumen in the extension member and having a threaded engagement member with an increasing thread diameter configured to apply a radially directed force to an inner surface of the extension member to break and separate the extension member from the receiver member.
2. The system of claim 1, wherein the extension member includes a proximal end and a distal end coupled to the receiver member, and wherein the frangible portion is formed adjacent to the distal end of the extension member.
3. The system of claim 1, wherein the receiver member has a maximum outer diameter that is substantially the same as a maximum outer diameter of the extension member.
4. The system of claim 1, wherein the extension member comprises first and second opposed extension arms that extend proximally from the U-shaped receiver member, and that are separated by opposed slots extending therebetween.
5. The system of claim 1, wherein the extension member comprises a hollow elongate tube.
6. The system of claim 5, further comprising opposed slots formed in the hollow elongate tube and extending from a distal end of the hollow elongate tube and terminating distal to a proximal end of the hollow elongate tube.
7. The system of claim 1, wherein the bone-engaging member comprises a threaded shank.
8. The system of claim 1, wherein the frangible portion comprises an annular groove formed around the extension member.
9. The system of claim 1, wherein the removal tool comprises an elongate member and the threaded engagement

## 14

member is configured to be inserted through the lumen in the extension member and positioned adjacent to the U-shaped receiver member.

10. The system of claim 9, wherein the engagement member is configured to engage corresponding threads formed on an inner surface of the extension member.

11. The system of claim 1, wherein the length of the extension member is in the range of about 85 mm to 185 mm.

12. The system of claim 1, further comprising proximal threads formed within the extension member proximal to the frangible portion, and distal threads formed within the receiver member distal to the frangible portion, the proximal and distal threads differing from one another.

13. The system of claim 1, further comprising threads formed within a proximal end of the extension member for threadably mating with the threaded engagement member.

14. A spinal implant and access system, comprising:
 

- a receiver member having a recess formed therein and adapted to seat a spinal connector;
- a bone-engaging member extending distally from the receiver member and adapted to engage bone;
- first and second opposed extension arms extending proximally from the receiver member and frangibly coupled to the receiver member by a break-off region adapted to break upon application of a force to the first and second extension arms for separating the first and second extension arms from the receiver member, the first and second opposed extension arms having a length that is greater than about 55 mm such that the first and second opposed extension arms are adapted to span through a skin surface in a patient to the U-shaped receiver member when the bone engaging member is implanted in a vertebra; and
- a removal tool disposable between the first and second opposed extension arms and configured having a threaded engagement member with an increasing thread diameter to apply a radially directed force to the first and second opposed extension arms to break and separate the extension arms from the receiver member.

15. The system of claim 14, wherein the first and second opposed extension arms include an inner lumen extending therethrough.

16. The system of claim 15, wherein the recess formed in the receiver member has a maximum diameter that is substantially the same as a maximum diameter of the inner lumen extending through the first and second extension arms.

17. The system of claim 14, wherein a portion of the first and second opposed extension arms are coupled to one another to form a hollow elongate tube.

18. The system of claim 14, wherein the first and second opposed extension arms are separated by opposed slots extending from a distal end of the hollow elongate tube to a proximal end of the hollow elongate tube.

19. The system of claim 14, wherein the bone-engaging member comprises a threaded shank.

20. The system of claim 14, wherein the frangible portion comprises an annular groove formed around the extension member.

21. The system of claim 14, wherein the engagement member is configured to engage corresponding threads formed on an inner surface of the first and second extension arms.

22. The system of claim 14, wherein the length of the first and second opposed extension arms is in the range of about 85 mm to 185 mm.



**15**

**23.** The system of claim **14**, further comprising proximal threads formed within the first and second opposed extension arms proximal to the frangible portion, and distal threads formed within the receiver member distal to the frangible portion, the proximal and distal threads differing from one another. 5

**16**

**24.** The system of claim **14**, further comprising threads formed within a proximal end of the first and second opposed extension arms for threadably mating with the threaded engagement member.

\* \* \* \* \*