

(12) **United States Patent**
Blank et al.

(10) **Patent No.:** **US 8,282,226 B2**
(45) **Date of Patent:** **Oct. 9, 2012**

(54) **INTERIOR REARVIEW MIRROR SYSTEM**

(75) Inventors: **Rodney K. Blank**, Zeeland, MI (US);
Kenneth L. Schierbeek, Zeeland, MI
(US); **Niall R. Lynam**, Holland, MI (US)

(73) Assignee: **Donnelly Corporation**, Holland, MI
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 246 days.

(21) Appl. No.: **12/906,519**

(22) Filed: **Oct. 18, 2010**

(65) **Prior Publication Data**

US 2011/0026152 A1 Feb. 3, 2011

Related U.S. Application Data

(63) Continuation of application No. 12/766,160, filed on
Apr. 23, 2010, now Pat. No. 7,815,326, which is a
continuation of application No. 12/575,726, filed on
Oct. 8, 2009, now Pat. No. 7,726,822, which is a
continuation of application No. 12/370,043, filed on
Feb. 12, 2009, now Pat. No. 7,600,878, which is a
continuation of application No. 12/029,073, filed on
Feb. 11, 2008, now Pat. No. 7,490,944, which is a
continuation of application No. 11/305,637, filed on
Dec. 16, 2005, now Pat. No. 7,329,013, which is a
continuation-in-part of application No. 11/226,628,
filed on Sep. 14, 2005, now abandoned, and a
continuation-in-part of application No. 10/456,599,
filed on Jun. 6, 2003, now Pat. No. 7,004,593.

(60) Provisional application No. 60/692,113, filed on Jun.
20, 2005, provisional application No. 60/677,990,
filed on May 5, 2005, provisional application No.
60/653,787, filed on Feb. 17, 2005, provisional
application No. 60/642,227, filed on Jan. 7, 2005,
provisional application No. 60/638,250, filed on Dec.
21, 2004, provisional application No. 60/636,931,
filed on Dec. 17, 2004, provisional application No.

60/624,091, filed on Nov. 1, 2004, provisional
application No. 60/609,642, filed on Sep. 14, 2004,
provisional application No. 60/420,010, filed on Oct.
21, 2002, provisional application No. 60/398,240,
filed on Jul. 24, 2002, provisional application No.
60/386,373, filed on Jun. 6, 2002.

(51) **Int. Cl.**
G02B 7/182 (2006.01)

(52) **U.S. Cl.** **359/879**


(58) **Field of Classification Search** 359/871-879;
340/438; 250/239

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,096,452 A	5/1914	Perrin
1,563,258 A	11/1925	Cunningham
2,069,368 A	2/1937	Horinstein
2,166,303 A	7/1939	Hodny et al.
2,263,382 A	11/1941	Gotzinger
2,414,223 A	1/1947	DeVirgilis
2,457,348 A	12/1948	Chambers
2,561,582 A	7/1951	Marbel
2,580,014 A	12/1951	Gazda
3,004,473 A	10/1961	Arthur et al.
3,075,430 A	1/1963	Woodward et al.
3,141,393 A	7/1964	Platt
3,152,216 A	10/1964	Woodward
3,162,008 A	12/1964	Berger et al.
3,185,020 A	5/1965	Thelen
3,266,016 A	8/1966	Maruyama et al.
3,280,701 A	10/1966	Donnelly et al.
3,432,225 A	3/1969	Rock
3,451,741 A	6/1969	Manos
3,453,038 A	7/1969	Kissa et al.
3,467,465 A	9/1969	Van Noord
3,473,867 A	10/1969	Byrnes
3,480,781 A	11/1969	Mandalakas
3,499,112 A	3/1970	Heilmeier et al.
3,499,702 A	3/1970	Goldmacher et al.
3,521,941 A	7/1970	Deb et al.
3,543,018 A	11/1970	Barcus et al.
3,557,265 A	1/1971	Chisholm et al.
3,565,985 A	2/1971	Schrenk et al.
3,612,654 A	10/1971	Klein
3,614,210 A	10/1971	Caplan
3,628,851 A	12/1971	Robertson



US 8,282,226 B2

Page 2

3,676,668	A	7/1972	Collins et al.	4,603,946	A	8/1986	Kato et al.
3,680,951	A	8/1972	Jordan et al.	4,623,222	A	11/1986	Itoh et al.
3,689,695	A	9/1972	Rosenfield et al.	4,625,210	A	11/1986	Sagl
3,711,176	A	1/1973	Alfrey, Jr. et al.	4,626,850	A	12/1986	Chey
3,712,710	A	1/1973	Castellion et al.	4,630,040	A	12/1986	Haertling
3,748,017	A	7/1973	Yamamura et al.	4,630,109	A	12/1986	Barton
3,781,090	A	12/1973	Sumita	4,630,904	A	12/1986	Pastore
3,806,229	A	4/1974	Schoot et al.	4,634,835	A	1/1987	Suzuki
3,807,832	A	4/1974	Castellion	4,635,033	A	1/1987	Inukai et al.
3,807,833	A	4/1974	Graham et al.	4,636,782	A	1/1987	Nakamura et al.
3,821,590	A	6/1974	Kosman et al.	4,638,287	A	1/1987	Umebayashi et al.
3,837,129	A	9/1974	Losell	4,646,210	A	2/1987	Skogler et al.
3,860,847	A	1/1975	Carley	4,652,090	A	3/1987	Uchikawa et al.
3,862,798	A	1/1975	Hopkins	4,655,549	A	4/1987	Suzuki et al.
3,870,404	A	3/1975	Wilson et al.	4,665,311	A	5/1987	Cole
3,876,287	A	4/1975	Sprokel	4,665,430	A	5/1987	Hiroyasu
3,932,024	A	1/1976	Yaguchi et al.	4,669,827	A	6/1987	Fukada et al.
3,940,822	A	3/1976	Emerick et al.	4,671,615	A	6/1987	Fukada et al.
3,956,017	A	5/1976	Shigemasa	4,671,619	A	6/1987	Kamimori et al.
3,978,190	A	8/1976	Kurz, Jr. et al.	4,678,281	A	7/1987	Bauer
3,985,424	A	10/1976	Steinacher	4,679,906	A	7/1987	Brandenburg
4,006,546	A	2/1977	Anderson et al.	4,682,083	A	7/1987	Alley
4,035,681	A	7/1977	Savage	4,692,798	A	9/1987	Seko et al.
4,040,727	A	8/1977	Ketchpel	4,694,295	A	9/1987	Miller et al.
4,052,712	A	10/1977	Ohama et al.	4,697,883	A	10/1987	Suzuki et al.
4,075,468	A	2/1978	Marcus	4,701,022	A	10/1987	Jacob
4,088,400	A	5/1978	Assouline et al.	4,702,566	A	10/1987	Tukude
4,093,364	A	6/1978	Miller	4,704,740	A	11/1987	McKee et al.
4,097,131	A	6/1978	Nishiyama	4,711,544	A	12/1987	Iino et al.
4,109,235	A	8/1978	Bouthors	4,712,879	A	12/1987	Lynam et al.
4,139,234	A	2/1979	Morgan	4,713,685	A	12/1987	Nishimura et al.
4,159,866	A	7/1979	Wunsch et al.	RE32,576	E	1/1988	Pastore
4,161,653	A	7/1979	Bedini et al.	4,718,756	A	1/1988	Lancaster
4,171,875	A	10/1979	Taylor et al.	4,721,364	A	1/1988	Itoh et al.
4,174,152	A	11/1979	Giglia et al.	4,729,068	A	3/1988	Ohe
4,200,361	A	4/1980	Malvano et al.	4,729,076	A	3/1988	Masami et al.
4,202,607	A	5/1980	Washizuka et al.	4,731,669	A	3/1988	Hayashi et al.
4,211,955	A	7/1980	Ray	4,733,335	A	3/1988	Serizawa et al.
4,214,266	A	7/1980	Myers	4,733,336	A	3/1988	Skogler et al.
4,219,760	A	8/1980	Ferro	4,740,838	A	4/1988	Mase et al.
4,221,955	A	9/1980	Joslyn	4,761,061	A	8/1988	Nishiyama et al.
4,228,490	A	10/1980	Thillays	4,773,740	A	9/1988	Kawakami et al.
4,247,870	A	1/1981	Gabel et al.	4,780,752	A	10/1988	Angerstein et al.
4,257,703	A	3/1981	Goodrich	4,781,436	A	11/1988	Armbruster
4,274,078	A	6/1981	Isobe et al.	4,789,904	A	12/1988	Peterson
4,277,804	A	7/1981	Robison	4,793,690	A	12/1988	Gahan et al.
4,281,899	A	8/1981	Oskam	4,793,695	A	12/1988	Wada et al.
4,288,814	A	9/1981	Talley et al.	4,794,261	A	12/1988	Rosen
RE30,835	E	12/1981	Giglia	D299,491	S	1/1989	Masuda
4,306,768	A	12/1981	Egging	4,799,768	A	1/1989	Gahan
4,310,851	A	1/1982	Pierrat	4,803,599	A	2/1989	Trine et al.
4,331,382	A	5/1982	Graff	4,807,096	A	2/1989	Skogler et al.
4,338,000	A	7/1982	Kamimori et al.	4,820,933	A	4/1989	Hong et al.
4,377,613	A	3/1983	Gordon	4,825,232	A	4/1989	Howdle
4,398,805	A	8/1983	Cole	4,826,289	A	5/1989	Vandenbrink et al.
4,419,386	A	12/1983	Gordon	4,827,086	A	5/1989	Rockwell
4,420,238	A	12/1983	Felix	4,837,551	A	6/1989	Iino
4,425,717	A	1/1984	Marcus	4,842,378	A	6/1989	Flasck et al.
4,435,042	A	3/1984	Wood et al.	4,845,402	A	7/1989	Smith
4,435,048	A	3/1984	Kamimori et al.	4,847,772	A	7/1989	Michalopoulos et al.
4,436,371	A	3/1984	Wood et al.	4,855,161	A	8/1989	Moser et al.
4,438,348	A	3/1984	Casper et al.	4,855,550	A	8/1989	Schultz, Jr.
4,443,057	A	4/1984	Bauer et al.	4,859,813	A	8/1989	Rockwell
4,446,171	A	5/1984	Thomas	4,859,867	A	8/1989	Larson et al.
4,465,339	A	8/1984	Baucke et al.	4,860,171	A	8/1989	Kojima
4,473,695	A	9/1984	Wrighton et al.	4,862,594	A	9/1989	Schierbeek et al.
4,490,227	A	12/1984	Bitter	4,871,917	A	10/1989	O'Farrell et al.
4,491,390	A	1/1985	Tong-Shen	4,872,051	A	10/1989	Dye
4,499,451	A	2/1985	Suzuki et al.	4,882,466	A	11/1989	Friel
4,521,079	A	6/1985	Leenhouts et al.	4,882,565	A	11/1989	Gallmeyer
4,524,941	A	6/1985	Wood et al.	4,883,349	A	11/1989	Mittelhäuser
4,538,063	A	8/1985	Bulat	4,884,135	A	11/1989	Schiffman
4,546,551	A	10/1985	Franks	4,886,960	A	12/1989	Molyneux et al.
4,555,694	A	11/1985	Yanagishima et al.	4,889,412	A	12/1989	Clerc et al.
4,561,625	A	12/1985	Weaver	4,891,828	A	1/1990	Kawazoe
4,572,619	A	2/1986	Reininger et al.	4,892,345	A	1/1990	Rachael, III
4,580,196	A	4/1986	Task	4,902,103	A	2/1990	Miyake et al.
4,581,827	A	4/1986	Higashi	4,902,108	A	2/1990	Byker
4,588,267	A	5/1986	Pastore	4,906,085	A	3/1990	Sugihara et al.

4,909,606 A	3/1990	Wada et al.	5,160,201 A	11/1992	Wrobel
4,910,591 A	3/1990	Petrossian et al.	5,166,815 A	11/1992	Elderfield
4,916,374 A	4/1990	Schierbeek et al.	5,168,378 A	12/1992	Black et al.
4,926,170 A	5/1990	Beggs et al.	5,173,881 A	12/1992	Sindle
4,930,742 A	6/1990	Schofield et al.	5,177,031 A	1/1993	Buchmann et al.
4,933,814 A	6/1990	Sanai	5,178,448 A	1/1993	Adams et al.
4,935,665 A	6/1990	Murata	5,179,471 A	1/1993	Caskey et al.
4,936,533 A	6/1990	Adams et al.	5,183,099 A	2/1993	Bechu
4,937,796 A	6/1990	Tendler	5,184,956 A	2/1993	Langlais et al.
4,937,945 A	7/1990	Schofield et al.	5,189,537 A	2/1993	O'Farrell
4,943,796 A	7/1990	Lee	5,193,029 A	3/1993	Schofield et al.
4,948,242 A	8/1990	Desmond et al.	5,197,562 A	3/1993	Kakinami et al.
4,953,305 A	9/1990	Van Lente et al.	5,202,950 A	4/1993	Arego et al.
4,956,591 A	9/1990	Schierbeek et al.	5,207,492 A	5/1993	Roberts
4,957,349 A	9/1990	Clerc et al.	5,210,967 A	5/1993	Brown
4,959,247 A	9/1990	Moser et al.	5,212,819 A	5/1993	Wada
4,959,865 A	9/1990	Stettiner et al.	5,214,408 A	5/1993	Asayama
4,970,653 A	11/1990	Kenue	5,217,794 A	6/1993	Schrenk
4,973,844 A	11/1990	O'Farrell et al.	5,223,814 A	6/1993	Suman
4,974,122 A	11/1990	Shaw	5,223,844 A	6/1993	Mansell et al.
4,978,196 A	12/1990	Suzuki et al.	5,229,975 A	7/1993	Truesdell et al.
4,983,951 A	1/1991	Igarashi et al.	5,230,400 A	7/1993	Kakinami et al.
4,985,809 A	1/1991	Matsui et al.	5,233,461 A	8/1993	Dornan et al.
4,987,357 A	1/1991	Masaki	5,235,316 A	8/1993	Qualizza
4,996,083 A	2/1991	Moser et al.	5,239,405 A	8/1993	Varaprasad et al.
5,001,386 A	3/1991	Sullivan et al.	5,239,406 A	8/1993	Lynam
5,001,558 A	3/1991	Burley et al.	5,243,417 A	9/1993	Pollard
5,005,213 A	4/1991	Hanson et al.	5,245,422 A	9/1993	Borcherts et al.
5,006,971 A	4/1991	Jenkins	5,252,354 A	10/1993	Cronin et al.
5,014,167 A	5/1991	Roberts	5,253,109 A	10/1993	O'Farrell et al.
5,016,988 A	5/1991	Iimura	5,255,442 A	10/1993	Schierbeek et al.
5,016,996 A	5/1991	Ueno	5,260,626 A	11/1993	Takase et al.
5,017,903 A	5/1991	Krippelz, Sr.	5,277,986 A	1/1994	Cronin et al.
5,018,839 A	5/1991	Yamamoto et al.	5,280,555 A	1/1994	Ainsburg
5,027,200 A	6/1991	Petrossian et al.	5,285,060 A	2/1994	Larson et al.
5,037,182 A	8/1991	Groves et al.	5,289,321 A	2/1994	Secor
5,038,255 A	8/1991	Nishihashi et al.	5,296,924 A	3/1994	de Saint Blancard et al.
5,052,163 A	10/1991	Czekala	5,303,075 A	4/1994	Wada et al.
5,056,899 A	10/1991	Warszawski	5,303,205 A	4/1994	Gauthier et al.
5,057,974 A	10/1991	Mizobe	5,304,980 A	4/1994	Maekawa
5,058,851 A	10/1991	Lawlor et al.	5,305,012 A	4/1994	Faris
5,059,015 A	10/1991	Tran	5,307,136 A	4/1994	Saneyoshi
5,066,108 A	11/1991	McDonald	5,313,335 A	5/1994	Gray et al.
5,066,112 A	11/1991	Lynam et al.	5,325,096 A	6/1994	Pakett
5,069,535 A	12/1991	Baucke et al.	5,325,386 A	6/1994	Jewell et al.
5,070,323 A	12/1991	Iino et al.	5,327,288 A	7/1994	Wellington et al.
5,073,012 A	12/1991	Lynam	5,330,149 A	7/1994	Haan et al.
5,076,673 A	12/1991	Lynam et al.	5,331,312 A	7/1994	Kudoh
5,076,674 A	12/1991	Lynam	5,331,358 A	7/1994	Schurle et al.
5,078,480 A	1/1992	Warszawski	5,339,075 A	8/1994	Abst et al.
5,096,287 A	3/1992	Kakinami et al.	5,339,529 A	8/1994	Lindberg
5,100,095 A	3/1992	Haan et al.	5,341,437 A	8/1994	Nakayama
5,101,139 A	3/1992	Lechter	D351,370 S	10/1994	Lawlor et al.
5,105,127 A	4/1992	Lavaud et al.	5,354,965 A	10/1994	Lee
5,115,346 A	5/1992	Lynam	5,355,118 A	10/1994	Fukuhara
5,117,346 A	5/1992	Gard	5,355,245 A	10/1994	Lynam
5,119,220 A	6/1992	Narita et al.	5,355,284 A	10/1994	Roberts
5,121,200 A	6/1992	Choi	5,361,190 A	11/1994	Roberts et al.
5,122,619 A	6/1992	Dlubak	5,363,294 A	11/1994	Yamamoto et al.
5,123,077 A	6/1992	Endo et al.	5,371,659 A	12/1994	Pastrick et al.
5,124,845 A	6/1992	Shimojo	5,373,482 A	12/1994	Gauthier
5,124,890 A	6/1992	Choi et al.	5,379,146 A	1/1995	Defendini
5,128,799 A	7/1992	Byker	5,386,285 A	1/1995	Asayama
5,130,898 A	7/1992	Akahane	5,386,306 A	1/1995	Gunjima et al.
5,131,154 A	7/1992	Schierbeek et al.	5,400,158 A	3/1995	Ohnishi et al.
5,134,507 A	7/1992	Ishii	5,402,103 A	3/1995	Tashiro
5,134,549 A	7/1992	Yokoyama	5,406,395 A	4/1995	Wilson et al.
5,135,298 A	8/1992	Feltman	5,406,414 A	4/1995	O'Farrell et al.
5,136,483 A	8/1992	Schöniger et al.	5,408,353 A	4/1995	Nichols et al.
5,140,455 A	8/1992	Varaprasad et al.	5,408,357 A	4/1995	Beukema
5,140,465 A	8/1992	Yasui et al.	5,410,346 A	4/1995	Saneyoshi et al.
5,142,407 A	8/1992	Varaprasad et al.	5,414,439 A	5/1995	Groves et al.
5,145,609 A	9/1992	Varaprasad et al.	5,414,461 A	5/1995	Kishi et al.
5,150,232 A	9/1992	Gunkima et al.	5,416,313 A	5/1995	Larson et al.
5,151,816 A	9/1992	Varaprasad et al.	5,416,478 A	5/1995	Morinaga
5,151,824 A	9/1992	O'Farrell	5,418,610 A	5/1995	Fischer
5,154,617 A	10/1992	Suman et al.	5,422,756 A	6/1995	Weber
5,158,638 A	10/1992	Osanami et al.	5,424,726 A	6/1995	Beymer
5,160,200 A	11/1992	Cheselske	5,424,865 A	6/1995	Lynam

5,424,952 A	6/1995	Asayama	5,617,085 A	4/1997	Tsutsumi et al.
5,426,524 A	6/1995	Wada et al.	5,619,374 A	4/1997	Roberts
5,430,431 A	7/1995	Nelson	5,619,375 A	4/1997	Roberts
5,432,496 A	7/1995	Lin	5,626,800 A	5/1997	Williams et al.
5,432,626 A	7/1995	Sasuga et al.	5,631,089 A	5/1997	Center, Jr. et al.
5,436,741 A	7/1995	Crandall	5,631,638 A	5/1997	Kaspar et al.
5,437,931 A	8/1995	Tsai et al.	5,631,639 A	5/1997	Hibino et al.
5,439,305 A	8/1995	Santo	5,632,092 A	5/1997	Blank et al.
5,444,478 A	8/1995	Lelong et al.	5,632,551 A	5/1997	Roney et al.
5,446,576 A	8/1995	Lynam et al.	5,634,709 A	6/1997	Iwama
5,455,716 A	10/1995	Suman et al.	5,640,216 A	6/1997	Hasegawa et al.
5,461,361 A	10/1995	Moore	5,642,238 A	6/1997	Sala
D363,920 S	11/1995	Roberts et al.	5,644,851 A	7/1997	Blank et al.
5,469,187 A	11/1995	Yaniv	5,646,614 A	7/1997	Abersfelder et al.
5,469,298 A	11/1995	Suman et al.	5,649,756 A	7/1997	Adams et al.
5,475,366 A	12/1995	Van Lente et al.	5,649,758 A	7/1997	Dion
5,475,494 A	12/1995	Nishida et al.	5,650,765 A	7/1997	Park
5,481,409 A	1/1996	Roberts	5,650,929 A	7/1997	Potter et al.
5,483,453 A	1/1996	Uemura et al.	5,661,455 A	8/1997	Van Lente et al.
5,485,161 A	1/1996	Vaughn	5,661,651 A	8/1997	Geschke et al.
5,485,378 A	1/1996	Franke et al.	5,661,804 A	8/1997	Dykema et al.
5,487,522 A	1/1996	Hook	5,662,375 A	9/1997	Adams et al.
5,488,496 A	1/1996	Pine	5,666,157 A	9/1997	Aviv
5,497,305 A	3/1996	Pastrick et al.	5,667,289 A	9/1997	Akahane et al.
5,497,306 A	3/1996	Pastrick	5,668,663 A	9/1997	Varaprasad et al.
5,500,760 A	3/1996	Varaprasad et al.	5,668,675 A	9/1997	Fredricks
5,506,701 A	4/1996	Ichikawa	5,669,698 A	9/1997	Veldman et al.
5,509,606 A	4/1996	Breithaupt et al.	5,669,699 A	9/1997	Pastrick et al.
5,510,983 A	4/1996	Iino	5,669,704 A	9/1997	Pastrick
5,515,448 A	5/1996	Nishitani	5,669,705 A	9/1997	Pastrick et al.
5,519,621 A	5/1996	Wortham	5,670,935 A	9/1997	Schofield et al.
5,521,744 A	5/1996	Mazurek	5,671,996 A	9/1997	Bos et al.
5,521,760 A	5/1996	De Young et al.	5,673,994 A	10/1997	Fant, Jr. et al.
5,523,811 A	6/1996	Wada et al.	5,673,999 A	10/1997	Koenck
5,523,877 A	6/1996	Lynam	5,677,598 A	10/1997	De Hair et al.
5,525,264 A	6/1996	Cronin et al.	5,679,283 A	10/1997	Tonar et al.
5,525,977 A	6/1996	Suman	5,680,123 A	10/1997	Lee
5,528,422 A	6/1996	Roberts	5,680,245 A	10/1997	Lynam
5,528,474 A	6/1996	Roney et al.	5,680,263 A	10/1997	Zimmermann et al.
5,529,138 A	6/1996	Shaw et al.	5,686,975 A	11/1997	Lipton
5,530,240 A	6/1996	Larson et al.	5,686,979 A	11/1997	Weber et al.
5,530,420 A	6/1996	Tsuchiya et al.	5,689,241 A	11/1997	Clark, Sr. et al.
5,530,421 A	6/1996	Marshall et al.	5,689,370 A	11/1997	Tonar et al.
5,535,056 A	7/1996	Caskey et al.	5,691,848 A	11/1997	Van Lente et al.
5,535,144 A	7/1996	Kise	5,692,819 A	12/1997	Mitsutake et al.
5,539,397 A	7/1996	Asanuma et al.	5,696,529 A	12/1997	Evanicky et al.
5,541,590 A	7/1996	Nishio	5,696,567 A	12/1997	Wada et al.
5,550,677 A	8/1996	Schofield et al.	5,699,044 A	12/1997	Van Lente et al.
5,555,172 A	9/1996	Potter	5,699,188 A	12/1997	Gilbert et al.
5,561,333 A	10/1996	Darius	5,703,568 A	12/1997	Hegy
5,566,224 A	10/1996	ul Azam et al.	5,708,410 A	1/1998	Blank et al.
5,567,360 A	10/1996	Varaprasad et al.	5,708,415 A	1/1998	Van Lente et al.
5,568,316 A	10/1996	Schrenk et al.	5,708,857 A	1/1998	Ishibashi
5,570,127 A	10/1996	Schmidt	5,715,093 A	2/1998	Schierbeek et al.
5,572,354 A	11/1996	Desmond et al.	5,724,187 A	3/1998	Varaprasad et al.
5,574,426 A	11/1996	Shisgal et al.	5,724,316 A	3/1998	Brunts
5,574,443 A	11/1996	Hsieh	5,729,194 A	3/1998	Spears et al.
5,575,552 A	11/1996	Faloon et al.	5,737,226 A	4/1998	Olson et al.
5,576,687 A	11/1996	Blank et al.	5,741,966 A	4/1998	Handfield et al.
5,576,854 A	11/1996	Schmidt et al.	5,744,227 A	4/1998	Bright et al.
5,576,975 A	11/1996	Sasaki et al.	5,745,050 A	4/1998	Nakagawa
5,578,404 A	11/1996	Kliem	5,745,266 A	4/1998	Smith
5,587,236 A	12/1996	Agrawal et al.	5,748,172 A	5/1998	Song et al.
5,587,699 A	12/1996	Faloon et al.	5,748,287 A	5/1998	Takahashi et al.
5,593,221 A	1/1997	Evanicky et al.	5,751,211 A	5/1998	Shirai et al.
5,594,222 A	1/1997	Caldwell	5,751,246 A	5/1998	Hertel
5,594,560 A	1/1997	Jelley et al.	5,751,390 A	5/1998	Crawford et al.
5,594,615 A	1/1997	Spijkerman et al.	5,751,489 A	5/1998	Caskey et al.
5,602,542 A	2/1997	Widmann et al.	5,754,099 A	5/1998	Nishimura et al.
5,602,670 A	2/1997	Keegan	D394,833 S	6/1998	Muth
5,603,104 A	2/1997	Phelps, III et al.	5,760,828 A	6/1998	Cortes
5,608,550 A	3/1997	Epstein et al.	5,760,931 A	6/1998	Saburi et al.
5,609,652 A	3/1997	Yamada et al.	5,760,962 A	6/1998	Schofield et al.
5,610,380 A	3/1997	Nicolaisen	5,761,094 A	6/1998	Olson et al.
5,610,756 A	3/1997	Lynam et al.	5,762,823 A	6/1998	Hikmet
5,611,966 A	3/1997	Varaprasad et al.	5,764,139 A	6/1998	Nojima et al.
5,614,885 A	3/1997	Van Lente et al.	5,765,940 A	6/1998	Levy et al.
5,615,023 A	3/1997	Yang	5,767,793 A	6/1998	Agravante et al.
5,615,857 A	4/1997	Hook	5,768,020 A	6/1998	Nagao

US 8,282,226 B2

Page 5

5,775,762 A	7/1998	Vitito	5,940,120 A	8/1999	Frankhouse et al.
5,777,779 A	7/1998	Hashimoto et al.	5,940,201 A	8/1999	Ash et al.
5,780,160 A	7/1998	Allemand et al.	5,942,895 A	8/1999	Popovic et al.
5,786,772 A	7/1998	Schofield et al.	5,947,586 A	9/1999	Weber
5,788,357 A	8/1998	Muth et al.	5,949,331 A	9/1999	Schofield et al.
5,790,298 A	8/1998	Tonar	5,949,506 A	9/1999	Jones et al.
5,790,502 A	8/1998	Horinouchi et al.	5,956,079 A	9/1999	Ridgley
5,790,973 A	8/1998	Blaker et al.	5,956,181 A	9/1999	Lin
5,793,308 A	8/1998	Rosinski et al.	5,959,367 A	9/1999	O'Farrell et al.
5,793,420 A	8/1998	Schmidt	5,959,555 A	9/1999	Furuta
5,796,094 A	8/1998	Schofield et al.	5,959,577 A	9/1999	Fan et al.
5,796,176 A	8/1998	Kramer et al.	5,963,247 A	10/1999	Banitt
5,798,057 A	8/1998	Hikmet	5,963,284 A	10/1999	Jones et al.
5,798,575 A	8/1998	O'Farrell et al.	5,965,247 A	10/1999	Jonza et al.
5,798,688 A	8/1998	Schofield	5,968,538 A	10/1999	Snyder, Jr.
5,800,918 A	9/1998	Chartier et al.	5,971,552 A	10/1999	O'Farrell et al.
5,802,727 A	9/1998	Blank et al.	5,973,760 A	10/1999	Dehmlow
5,803,579 A	9/1998	Turnbull et al.	5,975,715 A	11/1999	Bauder
5,805,330 A	9/1998	Byker et al.	5,984,482 A	11/1999	Rumsey et al.
5,805,367 A	9/1998	Kanazawa	5,986,730 A	11/1999	Hansen et al.
5,806,879 A	9/1998	Hamada et al.	5,990,469 A	11/1999	Bechtel et al.
5,806,965 A	9/1998	Deese	5,990,625 A	11/1999	Meissner et al.
5,808,197 A	9/1998	Dao	5,995,180 A	11/1999	Moriwaki et al.
5,808,566 A	9/1998	Behr et al.	5,998,617 A	12/1999	Srinivasa et al.
5,808,589 A	9/1998	Ferguson	5,998,929 A	12/1999	Bechtel et al.
5,808,713 A	9/1998	Broer et al.	6,000,823 A	12/1999	Desmond et al.
5,808,777 A	9/1998	Lynam et al.	6,001,486 A	12/1999	Varaprasad et al.
5,808,778 A	9/1998	Bauer et al.	6,002,511 A	12/1999	Varaprasad et al.
5,812,321 A	9/1998	Schierbeek et al.	6,002,544 A	12/1999	Yatsu
5,813,745 A	9/1998	Fant, Jr. et al.	6,005,724 A	12/1999	Todd
5,818,625 A	10/1998	Forgette et al.	6,007,222 A	12/1999	Thau
5,820,097 A	10/1998	Spooner	6,008,486 A	12/1999	Stam et al.
5,820,245 A	10/1998	Desmond et al.	6,008,871 A	12/1999	Okumura
5,822,023 A	10/1998	Suman et al.	6,009,359 A	12/1999	El-Hakim et al.
5,823,654 A	10/1998	Pastrick et al.	6,016,035 A	1/2000	Eberspächer et al.
5,825,527 A	10/1998	Forgette et al.	6,016,215 A	1/2000	Byker
5,835,166 A	11/1998	Hall et al.	6,019,411 A	2/2000	Carter et al.
5,837,994 A	11/1998	Stam et al.	6,019,475 A	2/2000	Lynam et al.
5,844,505 A	12/1998	Van Ryzin	6,020,987 A	2/2000	Baumann et al.
5,848,373 A	12/1998	DeLorme et al.	6,021,371 A	2/2000	Fultz
5,850,176 A	12/1998	Kinoshita et al.	6,023,229 A	2/2000	Bugno et al.
5,850,205 A	12/1998	Blouin	6,025,872 A	2/2000	Ozaki et al.
5,863,116 A	1/1999	Pastrick et al.	6,028,537 A	2/2000	Suman et al.
5,864,419 A	1/1999	Lynam	6,037,689 A	3/2000	Bingle et al.
5,867,801 A	2/1999	Denny	6,040,939 A	3/2000	Demiryont et al.
5,871,275 A	2/1999	O'Farrell et al.	6,042,253 A	3/2000	Fant, Jr. et al.
5,871,843 A	2/1999	Yoneda et al.	6,042,934 A	3/2000	Guiselin et al.
5,877,707 A	3/1999	Kowalick	6,045,243 A	4/2000	Muth et al.
5,877,897 A	3/1999	Schofield et al.	6,045,643 A	4/2000	Byker et al.
5,878,353 A	3/1999	ul Azam et al.	6,046,766 A	4/2000	Sakata
5,878,370 A	3/1999	Olson	6,046,837 A	4/2000	Yamamoto
5,879,074 A	3/1999	Pastrick	6,049,171 A	4/2000	Stam et al.
5,883,605 A	3/1999	Knapp	D425,466 S	5/2000	Todd et al.
5,883,739 A	3/1999	Ashihara et al.	6,060,989 A	5/2000	Gehlot
5,888,431 A	3/1999	Tonar et al.	6,061,002 A	5/2000	Weber et al.
5,894,196 A	4/1999	McDermott	6,062,920 A	5/2000	Jordan et al.
D409,540 S	5/1999	Muth	6,064,508 A	5/2000	Forgette et al.
5,899,551 A	5/1999	Neijzen et al.	6,065,840 A	5/2000	Caskey et al.
5,899,956 A	5/1999	Chan	6,066,920 A	5/2000	Torihara et al.
5,904,729 A	5/1999	Ruzicka	6,067,111 A	5/2000	Hahn et al.
5,910,854 A	6/1999	Varaprasad et al.	6,067,500 A	5/2000	Morimoto et al.
5,914,815 A	6/1999	Bos	6,068,380 A	5/2000	Lynn et al.
5,917,664 A	6/1999	O'Neill et al.	D426,506 S	6/2000	Todd et al.
5,918,180 A	6/1999	Dimino	D426,507 S	6/2000	Todd et al.
5,922,176 A	7/1999	Caskey	D427,128 S	6/2000	Mathieu
5,923,027 A	7/1999	Stam et al.	6,072,391 A	6/2000	Suzuki et al.
5,923,457 A	7/1999	Byker et al.	6,074,077 A	6/2000	Pastrick et al.
5,924,212 A	7/1999	Domanski	6,074,777 A	6/2000	Reimers et al.
5,926,087 A	7/1999	Busch et al.	6,076,948 A	6/2000	Bukosky et al.
5,927,792 A	7/1999	Welling et al.	6,078,355 A	6/2000	Zengel
5,928,572 A	7/1999	Tonar et al.	6,078,865 A	6/2000	Koyanagi
5,929,786 A	7/1999	Schofield et al.	D428,372 S	7/2000	Todd et al.
5,931,555 A	8/1999	Akahane et al.	D428,373 S	7/2000	Todd et al.
5,935,702 A	8/1999	Macquart et al.	6,082,881 A	7/2000	Hicks
5,936,774 A	8/1999	Street	6,084,700 A	7/2000	Knapp et al.
5,938,320 A	8/1999	Crandall	6,086,131 A	7/2000	Bingle et al.
5,938,321 A	8/1999	Bos et al.	6,086,229 A	7/2000	Pastrick
5,938,721 A	8/1999	Dussell et al.	6,087,012 A	7/2000	Varaprasad et al.
5,940,011 A	8/1999	Agravante et al.	6,087,953 A	7/2000	DeLine et al.

US 8,282,226 B2

Page 6

6,091,343	A	7/2000	Dykema et al.	6,185,501	B1	2/2001	Smith et al.
6,093,976	A	7/2000	Kramer et al.	6,188,505	B1	2/2001	Lomprey et al.
6,094,618	A	7/2000	Harada	6,191,704	B1	2/2001	Takenaga et al.
D428,842	S	8/2000	Todd et al.	6,193,912	B1	2/2001	Thieste et al.
D429,202	S	8/2000	Todd et al.	6,195,194	B1	2/2001	Roberts et al.
D430,088	S	8/2000	Todd et al.	6,196,688	B1	3/2001	Caskey et al.
6,097,023	A	8/2000	Schofield et al.	6,198,409	B1	3/2001	Schofield et al.
6,097,316	A	8/2000	Liaw et al.	6,199,014	B1	3/2001	Walker et al.
6,099,131	A	8/2000	Fletcher et al.	6,199,810	B1	3/2001	Wu et al.
6,099,155	A	8/2000	Pastrick et al.	6,200,010	B1	3/2001	Anders
6,102,546	A	8/2000	Carter	6,201,642	B1	3/2001	Bos
6,102,559	A	8/2000	Nold et al.	6,206,553	B1	3/2001	Boddy et al.
6,104,552	A	8/2000	Thau et al.	6,207,083	B1	3/2001	Varaprasad et al.
6,106,121	A	8/2000	Buckley et al.	6,210,008	B1	4/2001	Hoekstra et al.
6,111,498	A	8/2000	Jobes et al.	6,210,012	B1	4/2001	Broer
6,111,683	A	8/2000	Cammenga et al.	6,212,470	B1	4/2001	Seymour et al.
6,111,684	A	8/2000	Forgette et al.	6,217,181	B1	4/2001	Lynam et al.
6,111,685	A	8/2000	Tench et al.	6,218,934	B1	4/2001	Regan
6,111,696	A	8/2000	Allen et al.	6,222,447	B1	4/2001	Schofield et al.
6,115,086	A	9/2000	Rosen	6,222,460	B1	4/2001	DeLine et al.
6,115,651	A	9/2000	Cruz	6,222,689	B1	4/2001	Higuchi et al.
6,116,743	A	9/2000	Hoek	6,227,689	B1	5/2001	Miller
6,118,219	A	9/2000	Okigami et al.	6,232,937	B1	5/2001	Jacobsen et al.
6,122,597	A	9/2000	Saneyoshi et al.	6,236,514	B1	5/2001	Sato
6,122,921	A	9/2000	Brezoczky et al.	6,239,851	B1	5/2001	Hatazawa et al.
6,124,647	A	9/2000	Marcus et al.	6,239,898	B1	5/2001	Byker et al.
6,124,886	A	9/2000	DeLine et al.	6,239,899	B1	5/2001	DeVries et al.
6,127,919	A	10/2000	Wysin	6,243,003	B1	6/2001	DeLine et al.
6,127,945	A	10/2000	Mura-Smith	6,244,716	B1	6/2001	Steenwyk et al.
6,128,576	A	10/2000	Nishimoto et al.	6,245,262	B1	6/2001	Varaprasad et al.
6,130,421	A	10/2000	Bechtel et al.	6,247,820	B1	6/2001	Van Order
6,130,448	A	10/2000	Bauer et al.	6,249,214	B1	6/2001	Kashiwazaki
6,132,072	A	10/2000	Turnbull et al.	6,249,310	B1	6/2001	Lefkowitz
6,137,620	A	10/2000	Guarr et al.	6,249,369	B1	6/2001	Theiste et al.
6,139,171	A	10/2000	Waldmann	6,250,148	B1	6/2001	Lynam
6,139,172	A	10/2000	Bos et al.	6,250,766	B1	6/2001	Strumolo et al.
6,140,933	A	10/2000	Bugno et al.	6,250,783	B1	6/2001	Stidham et al.
6,142,656	A	11/2000	Kurth	6,255,639	B1	7/2001	Stam et al.
6,146,003	A	11/2000	Thau	6,257,746	B1	7/2001	Todd et al.
6,147,934	A	11/2000	Arikawa et al.	6,259,412	B1	7/2001	Duroux
6,148,261	A	11/2000	Obradovich et al.	6,259,475	B1	7/2001	Ramachandran et al.
6,149,287	A	11/2000	Pastrick et al.	6,260,608	B1	7/2001	Kim
6,150,014	A	11/2000	Chu et al.	6,262,842	B1	7/2001	Ouderkirk et al.
6,151,065	A	11/2000	Steed et al.	6,264,353	B1	7/2001	Caraher et al.
6,151,539	A	11/2000	Bergholz et al.	6,265,968	B1	7/2001	Betzitza et al.
6,152,551	A	11/2000	Annas	6,268,803	B1	7/2001	Gunderson et al.
6,152,590	A	11/2000	Fürst et al.	6,268,837	B1	7/2001	Kobayashi et al.
6,154,149	A	11/2000	Tyckowski et al.	6,269,308	B1	7/2001	Kodaka et al.
6,154,306	A	11/2000	Varaprasad et al.	6,271,901	B1	8/2001	Ide et al.
6,157,294	A	12/2000	Urai et al.	6,274,221	B2	8/2001	Smith et al.
6,157,418	A	12/2000	Rosen	6,276,821	B1	8/2001	Pastrick et al.
6,157,424	A	12/2000	Eichenlaub	6,276,822	B1	8/2001	Bedrosian et al.
6,157,480	A	12/2000	Anderson et al.	6,277,471	B1	8/2001	Tang
6,158,655	A	12/2000	DeVries, Jr. et al.	6,278,271	B1	8/2001	Schott
6,161,865	A	12/2000	Rose et al.	6,278,377	B1	8/2001	DeLine et al.
6,164,564	A	12/2000	Franco et al.	6,278,941	B1	8/2001	Yokoyama
6,166,625	A	12/2000	Teowee et al.	6,280,068	B1	8/2001	Mertens et al.
6,166,629	A	12/2000	Hamma et al.	6,280,069	B1	8/2001	Pastrick et al.
6,166,834	A	12/2000	Taketomi et al.	6,281,804	B1	8/2001	Haller et al.
6,166,847	A	12/2000	Tench et al.	6,286,965	B1	9/2001	Caskey et al.
6,166,848	A	12/2000	Cammenga et al.	6,286,984	B1	9/2001	Berg
6,167,755	B1	1/2001	Damson et al.	6,289,332	B2	9/2001	Menig et al.
6,169,955	B1	1/2001	Fultz	6,290,378	B1	9/2001	Buchalla et al.
6,170,956	B1	1/2001	Rumsey et al.	6,291,905	B1	9/2001	Drummond et al.
6,172,600	B1	1/2001	Kakinama et al.	6,291,906	B1	9/2001	Marcus et al.
6,172,601	B1	1/2001	Wada et al.	6,294,989	B1	9/2001	Schofield et al.
6,172,613	B1	1/2001	DeLine et al.	6,296,379	B1	10/2001	Pastrick
6,173,501	B1	1/2001	Blank et al.	6,297,781	B1	10/2001	Turnbull et al.
6,175,164	B1	1/2001	O'Farrell et al.	6,299,333	B1	10/2001	Pastrick et al.
6,175,300	B1	1/2001	Kendrick	6,300,879	B1	10/2001	Ragan et al.
6,176,602	B1	1/2001	Pastrick et al.	6,301,039	B1	10/2001	Tench
6,178,034	B1	1/2001	Allemand et al.	6,304,173	B2	10/2001	Pala et al.
6,178,377	B1	1/2001	Ishihara et al.	6,305,807	B1	10/2001	Schierbeek
6,181,387	B1	1/2001	Rosen	6,310,611	B1	10/2001	Caldwell
6,182,006	B1	1/2001	Meek	6,310,714	B1	10/2001	Lomprey et al.
6,183,119	B1	2/2001	Desmond et al.	6,310,738	B1	10/2001	Chu
6,184,679	B1	2/2001	Popovic et al.	6,313,454	B1	11/2001	Bos et al.
6,184,781	B1	2/2001	Ramakesavan	6,314,295	B1	11/2001	Kawamoto
6,185,492	B1	2/2001	Kagawa et al.	6,315,440	B1	11/2001	Satoh

US 8,282,226 B2

Page 7

6,317,057	B1	11/2001	Lee	6,447,128	B1	9/2002	Lang et al.
6,317,180	B1	11/2001	Kuroiwa et al.	6,449,082	B1	9/2002	Agrawal et al.
6,317,248	B1	11/2001	Agrawal et al.	6,452,533	B1	9/2002	Yamabuchi et al.
6,318,870	B1	11/2001	Spooner et al.	6,452,572	B1	9/2002	Fan et al.
6,320,176	B1	11/2001	Schofield et al.	6,462,795	B1	10/2002	Clarke
6,320,282	B1	11/2001	Caldwell	6,463,369	B2	10/2002	Sadano et al.
6,320,612	B1	11/2001	Young	6,466,701	B1	10/2002	Ejiri et al.
6,324,295	B1	11/2001	Valery et al.	6,471,362	B1	10/2002	Carter et al.
6,326,613	B1	12/2001	Heslin et al.	6,472,977	B1	10/2002	Pöchmüller
6,326,900	B2	12/2001	DeLine et al.	6,472,979	B2	10/2002	Schofield et al.
6,329,925	B1	12/2001	Skiver et al.	6,473,001	B1	10/2002	Blum
6,330,511	B2	12/2001	Ogura et al.	6,474,853	B2	11/2002	Pastrick et al.
6,331,066	B1	12/2001	Desmond et al.	6,476,731	B1	11/2002	Miki et al.
6,333,759	B1	12/2001	Mazzilli	6,477,460	B2	11/2002	Kepler
6,335,680	B1	1/2002	Matsuoka	6,477,464	B2	11/2002	McCarthy et al.
6,336,737	B1	1/2002	Thau	6,483,429	B1	11/2002	Yasui et al.
6,340,850	B2	1/2002	O'Farrell et al.	6,483,438	B2	11/2002	DeLine et al.
6,341,523	B2	1/2002	Lynam	6,483,613	B1	11/2002	Woodgate et al.
6,344,805	B1	2/2002	Yasui et al.	6,487,500	B2	11/2002	Lemelson et al.
6,346,698	B1	2/2002	Turnbull	6,494,602	B2	12/2002	Pastrick et al.
6,347,880	B1	2/2002	Fürst et al.	6,498,620	B2	12/2002	Schofield et al.
6,348,858	B2	2/2002	Weis et al.	6,501,387	B2	12/2002	Skiver et al.
6,351,708	B1	2/2002	Takagi et al.	6,512,203	B2	1/2003	Jones et al.
6,353,392	B1	3/2002	Schofield et al.	6,512,624	B2	1/2003	Tonar et al.
6,356,206	B1	3/2002	Takenaga et al.	6,513,252	B1	2/2003	Schierbeek et al.
6,356,376	B1	3/2002	Tonar et al.	6,515,581	B1	2/2003	Ho
6,356,389	B1	3/2002	Nilsen et al.	6,515,582	B1	2/2003	Teowee
6,357,883	B1	3/2002	Strumolo et al.	6,515,597	B1	2/2003	Wada et al.
6,362,121	B1	3/2002	Chopin et al.	6,516,664	B2	2/2003	Lynam
6,362,548	B1	3/2002	Bingle et al.	6,518,691	B1	2/2003	Baba
6,363,326	B1	3/2002	Scully	6,519,209	B1	2/2003	Arikawa et al.
6,366,013	B1	4/2002	Leenders et al.	6,520,667	B1	2/2003	Mousseau
6,366,213	B2	4/2002	DeLine et al.	6,522,451	B1	2/2003	Lynam
6,370,329	B1	4/2002	Teuchert	6,522,969	B2	2/2003	Kannonji
6,371,636	B1	4/2002	Wesson	6,525,707	B1	2/2003	Kaneko et al.
6,379,013	B1	4/2002	Bechtel et al.	6,534,884	B2	3/2003	Marcus et al.
6,379,788	B2	4/2002	Choi et al.	6,538,709	B1	3/2003	Kurihara et al.
6,382,805	B1	5/2002	Miyabukuro	6,539,306	B2	3/2003	Turnbull et al.
6,385,139	B1	5/2002	Arikawa et al.	6,542,085	B1	4/2003	Yang
6,386,742	B1	5/2002	DeLine et al.	6,542,182	B1	4/2003	Chautorash
6,390,529	B1	5/2002	Bingle et al.	6,543,163	B1	4/2003	Ginsberg
6,390,626	B2	5/2002	Knox	6,545,598	B1	4/2003	de Villeroche
6,390,635	B2	5/2002	Whitehead et al.	6,549,253	B1	4/2003	Robbie et al.
6,396,397	B1	5/2002	Bos et al.	6,549,335	B1	4/2003	Trapani et al.
6,396,408	B2	5/2002	Drummond et al.	6,550,949	B1	4/2003	Bauer et al.
6,396,637	B2	5/2002	Roest et al.	6,552,326	B2	4/2003	Turnbull
6,407,847	B1	6/2002	Poll et al.	6,553,308	B1	4/2003	Uhlmann et al.
6,408,247	B1	6/2002	Ichikawa et al.	6,559,902	B1	5/2003	Kusuda et al.
6,411,204	B1	6/2002	Bloomfield et al.	6,560,004	B2	5/2003	Theiste et al.
6,412,959	B1	7/2002	Tseng	6,560,027	B2	5/2003	Meine
6,412,973	B1	7/2002	Bos et al.	6,566,821	B2	5/2003	Nakatsuka et al.
6,414,910	B1	7/2002	Kaneko et al.	6,567,060	B1	5/2003	Sekiguchi
6,415,230	B1	7/2002	Maruko et al.	6,568,839	B1	5/2003	Pastrick et al.
6,416,208	B2	7/2002	Pastrick et al.	6,572,233	B1	6/2003	Northman et al.
6,417,786	B2	7/2002	Learman et al.	6,573,957	B1	6/2003	Suzuki
6,418,376	B1	7/2002	Olson	6,573,963	B2	6/2003	Ouderkirk et al.
6,419,300	B1	7/2002	Pavao et al.	6,575,582	B2	6/2003	Tenmyo
6,420,036	B1	7/2002	Varaprasad et al.	6,575,643	B2	6/2003	Takahashi
6,420,975	B1	7/2002	DeLine et al.	6,578,989	B2	6/2003	Osumi et al.
6,421,081	B1	7/2002	Markus	6,580,373	B1	6/2003	Ohashi
6,424,272	B1	7/2002	Gutta et al.	6,580,479	B1	6/2003	Sekiguchi et al.
6,424,273	B1	7/2002	Gutta et al.	6,580,562	B2	6/2003	Aoki et al.
6,424,786	B1	7/2002	Beeson et al.	6,581,007	B2	6/2003	Hasegawa et al.
6,424,892	B1	7/2002	Matsuoka	6,583,730	B2	6/2003	Lang et al.
6,426,492	B1	7/2002	Bos et al.	6,591,192	B2	7/2003	Okamura et al.
6,426,568	B2	7/2002	Turnbull et al.	6,592,230	B2	7/2003	Dupay
6,427,349	B1	8/2002	Blank et al.	6,593,565	B2	7/2003	Heslin et al.
6,428,172	B1	8/2002	Hutzel et al.	6,593,984	B2	7/2003	Arakawa et al.
6,433,676	B2	8/2002	DeLine et al.	6,594,065	B2	7/2003	Byker et al.
6,433,680	B1	8/2002	Ho	6,594,067	B2	7/2003	Poll et al.
6,433,914	B1	8/2002	Lompfrey et al.	6,594,090	B2	7/2003	Kruschwitz et al.
6,437,688	B1	8/2002	Kobayashi	6,594,583	B2	7/2003	Ogura et al.
6,438,491	B1	8/2002	Farmer	6,594,614	B2	7/2003	Studt et al.
6,439,755	B1	8/2002	Fant, Jr. et al.	6,595,649	B2	7/2003	Hoekstra et al.
6,441,872	B1	8/2002	Ho	6,597,489	B1	7/2003	Guarr et al.
6,441,943	B1	8/2002	Roberts et al.	6,606,183	B2	8/2003	Ikai et al.
6,441,963	B2	8/2002	Murakami et al.	6,611,202	B2	8/2003	Schofield et al.
6,441,964	B1	8/2002	Chu et al.	6,611,227	B1	8/2003	Nebiyeloul-Kifle et al.
6,445,287	B1	9/2002	Schofield et al.	6,611,759	B2	8/2003	Brosche

6,614,387	B1	9/2003	Deadman	6,757,109	B2	6/2004	Bos
6,614,419	B1	9/2003	May	D493,131	S	7/2004	Lawlor et al.
6,614,579	B2	9/2003	Roberts et al.	D493,394	S	7/2004	Lawlor et al.
6,615,438	B1	9/2003	Franco et al.	6,759,113	B1	7/2004	Tang
6,616,313	B2	9/2003	Fürst et al.	6,759,945	B2	7/2004	Richard
6,616,764	B2	9/2003	Krämer et al.	6,760,157	B1	7/2004	Allen et al.
6,618,672	B2	9/2003	Sasaki et al.	6,773,116	B2	8/2004	De Vaan et al.
6,621,616	B1	9/2003	Bauer et al.	6,774,356	B2	8/2004	Heslin et al.
6,624,936	B2	9/2003	Kotchick et al.	6,774,810	B2	8/2004	DeLine et al.
6,627,918	B2	9/2003	Getz et al.	6,778,904	B2	8/2004	Iwami et al.
6,630,888	B2	10/2003	Lang et al.	6,779,900	B1	8/2004	Nolan-Brown
6,636,190	B2	10/2003	Hirakata et al.	6,784,129	B2	8/2004	Seto et al.
6,636,258	B2	10/2003	Strumolo	6,797,396	B1	9/2004	Liu et al.
6,638,582	B1	10/2003	Uchiyama et al.	6,800,871	B2	10/2004	Matsuda et al.
6,639,360	B2	10/2003	Roberts et al.	6,801,283	B2	10/2004	Koyama et al.
6,642,840	B2	11/2003	Lang et al.	6,805,474	B2	10/2004	Walser et al.
6,642,851	B2	11/2003	DeLine et al.	6,806,452	B2	10/2004	Bos et al.
6,646,697	B1	11/2003	Sekiguchi et al.	6,806,922	B2	10/2004	Ishitaka
6,648,477	B2	11/2003	Hutzel et al.	6,810,323	B1	10/2004	Bullock et al.
6,650,457	B2	11/2003	Busscher et al.	6,812,907	B1	11/2004	Gennetten et al.
6,657,607	B1	12/2003	Evanicky et al.	6,819,231	B2	11/2004	Berberich et al.
6,657,708	B1	12/2003	Drevillon et al.	6,824,281	B2	11/2004	Schofield et al.
6,661,482	B2	12/2003	Hara	6,831,268	B2	12/2004	Bechtel et al.
6,661,830	B1	12/2003	Reed et al.	6,832,848	B2	12/2004	Pastrick
6,665,592	B2	12/2003	Kodama	6,834,969	B2	12/2004	Bade et al.
6,669,109	B2	12/2003	Ivanov et al.	6,836,725	B2	12/2004	Millington et al.
6,669,285	B1	12/2003	Park et al.	6,842,276	B2	1/2005	Poll et al.
6,670,207	B1	12/2003	Roberts	6,845,805	B1	1/2005	Köster
6,670,910	B2	12/2003	Delcheccolo et al.	6,846,098	B2	1/2005	Bourdelaïs et al.
6,670,941	B2	12/2003	Albu et al.	6,847,424	B2	1/2005	Gotoh et al.
6,671,080	B2	12/2003	Poll et al.	6,847,487	B2	1/2005	Burgner
6,672,731	B2	1/2004	Schnell et al.	6,848,817	B2	2/2005	Bos et al.
6,672,734	B2	1/2004	Lammers	6,849,165	B2	2/2005	Klöppel et al.
6,672,744	B2	1/2004	DeLine et al.	6,853,491	B1	2/2005	Ruhle et al.
6,672,745	B1	1/2004	Bauer et al.	6,861,789	B2	3/2005	Wei
6,674,370	B2	1/2004	Rodewald et al.	6,870,655	B1	3/2005	Northman et al.
6,675,075	B1	1/2004	Engelsburg et al.	6,870,656	B2	3/2005	Tonar et al.
6,678,083	B1	1/2004	Anstee	6,871,982	B2	3/2005	Holman et al.
6,678,614	B2	1/2004	McCarthy et al.	6,877,888	B2	4/2005	DeLine et al.
6,679,608	B2	1/2004	Bechtel et al.	6,882,287	B2	4/2005	Schofield
6,683,539	B2	1/2004	Trajkovic et al.	6,889,064	B2	5/2005	Baratono et al.
6,683,969	B1	1/2004	Nishigaki et al.	6,891,563	B2	5/2005	Schofield et al.
6,685,348	B2	2/2004	Pastrick et al.	6,891,677	B2	5/2005	Nilsen et al.
6,690,262	B1	2/2004	Winnett	6,902,284	B2	6/2005	Hutzel et al.
6,690,268	B2	2/2004	Schofield et al.	6,904,348	B2	6/2005	Drummond et al.
6,690,413	B1	2/2004	Moore	6,906,632	B2	6/2005	DeLine et al.
6,690,438	B2	2/2004	Sekiguchi	6,909,486	B2	6/2005	Wang et al.
6,693,517	B2	2/2004	McCarthy et al.	6,910,779	B2	6/2005	Abel et al.
6,693,518	B2	2/2004	Kumata et al.	6,912,396	B2	6/2005	Sziraki et al.
6,693,519	B2	2/2004	Keirstead	6,916,099	B2	7/2005	Su et al.
6,693,524	B1	2/2004	Payne	6,922,902	B2 *	8/2005	Schierbeek et al. 33/356
6,700,692	B2	3/2004	Tonar et al.	6,928,180	B2	8/2005	Stam et al.
6,709,136	B2	3/2004	Pastrick et al.	6,928,366	B2	8/2005	Ockerse et al.
6,713,783	B1	3/2004	Mase et al.	6,930,737	B2	8/2005	Weindorf et al.
6,717,109	B1	4/2004	Macher et al.	6,934,067	B2	8/2005	Ash et al.
6,717,610	B1	4/2004	Bos et al.	6,946,978	B2	9/2005	Schofield
6,717,712	B2	4/2004	Lynam et al.	6,947,576	B2	9/2005	Stam et al.
6,719,215	B2	4/2004	Drouillard	6,947,577	B2	9/2005	Stam et al.
6,724,446	B2	4/2004	Motomura et al.	6,949,772	B2	9/2005	Shimizu et al.
6,726,337	B2	4/2004	Whitehead et al.	6,951,410	B2	10/2005	Parsons
6,727,807	B2	4/2004	Trajkovic et al.	6,951,681	B2	10/2005	Hartley et al.
6,727,808	B1	4/2004	Uselmann et al.	6,952,312	B2	10/2005	Weber et al.
6,727,844	B1	4/2004	Zimmermann et al.	6,958,495	B2	10/2005	Nishijima et al.
6,731,332	B1	5/2004	Yasui et al.	6,958,683	B2	10/2005	Mills et al.
6,734,807	B2	5/2004	King	6,961,178	B2	11/2005	Sugino et al.
6,736,526	B2	5/2004	Matsuba et al.	6,963,438	B2	11/2005	Busscher et al.
6,737,629	B2	5/2004	Nixon et al.	6,968,273	B2	11/2005	Ockerse et al.
6,737,630	B2	5/2004	Turnbull	6,972,888	B2	12/2005	Poll et al.
6,737,964	B2	5/2004	Samman et al.	6,974,236	B2	12/2005	Tenmyo
6,738,088	B1	5/2004	Uskolovsky et al.	6,975,215	B2	12/2005	Schofield et al.
6,742,904	B2	6/2004	Bechtel et al.	6,977,702	B2	12/2005	Wu
6,744,353	B2	6/2004	Sjönell	6,980,092	B2	12/2005	Turnbull et al.
6,746,775	B1	6/2004	Boire et al.	6,985,291	B2	1/2006	Watson et al.
6,747,716	B2	6/2004	Kuroiwa et al.	6,992,718	B1	1/2006	Takahara
6,748,211	B1	6/2004	Isaac et al.	7,001,058	B2	2/2006	Inditsky
6,749,308	B1	6/2004	Niendorf et al.	7,004,592	B2	2/2006	Varaprasad et al.
6,755,542	B2	6/2004	Bechtel et al.	7,004,593	B2	2/2006	Weller et al.
6,756,912	B2	6/2004	Skiver et al.	7,006,173	B1	2/2006	Hiyama et al.
6,757,039	B2	6/2004	Ma	7,009,751	B2	3/2006	Tonar et al.

7,012,543 B2	3/2006	DeLine et al.	7,323,819 B2	1/2008	Hong et al.
7,029,156 B2	4/2006	Suehiro et al.	7,324,172 B2	1/2008	Yamazaki
7,041,965 B2	5/2006	Heslin et al.	7,324,174 B2	1/2008	Hafuka et al.
7,042,616 B2	5/2006	Tonar et al.	7,324,261 B2	1/2008	Tonar et al.
7,046,418 B2	5/2006	Lin et al.	7,327,225 B2	2/2008	Nicholas et al.
7,046,448 B2	5/2006	Burgner	7,327,226 B2	2/2008	Turnbull et al.
7,057,681 B2	6/2006	Hinata et al.	7,327,855 B1	2/2008	Chen
7,063,893 B2	6/2006	Hoffman	7,328,103 B2	2/2008	McCarthy et al.
7,064,882 B2	6/2006	Tonar et al.	7,329,013 B2	2/2008	Blank et al.
7,074,486 B2	7/2006	Boire et al.	7,329,850 B2	2/2008	Drummond et al.
7,081,810 B2	7/2006	Henderson et al.	7,338,177 B2	3/2008	Lynam
7,092,052 B2	8/2006	Okamoto et al.	7,344,284 B2	3/2008	Lynam et al.
7,106,213 B2	9/2006	White	7,349,143 B2	3/2008	Tonar et al.
7,106,392 B2	9/2006	You	7,362,505 B2	4/2008	Hikmet et al.
7,108,409 B2	9/2006	DeLine et al.	7,370,983 B2	5/2008	DeWind et al.
7,114,554 B2	10/2006	Bergman et al.	7,372,611 B2	5/2008	Tonar et al.
7,121,028 B2	10/2006	Shoen et al.	7,375,895 B2	5/2008	Brynielsson
7,125,131 B2	10/2006	Olczak	7,379,224 B2	5/2008	Tonar et al.
7,130,727 B2	10/2006	Liu et al.	7,379,225 B2	5/2008	Tonar et al.
7,132,064 B2	11/2006	Li et al.	7,379,243 B2	5/2008	Horsten et al.
7,136,091 B2	11/2006	Ichikawa et al.	7,379,814 B2	5/2008	Ockerse et al.
7,138,974 B2	11/2006	Hirakata et al.	7,389,171 B2	6/2008	Rupp
7,149,613 B2	12/2006	Stam et al.	7,396,147 B2	7/2008	Munro
7,151,515 B2	12/2006	Kim et al.	7,411,732 B2	8/2008	Kao et al.
7,151,997 B2	12/2006	Uhlmann et al.	7,412,328 B2	8/2008	Uhlmann et al.
7,153,588 B2	12/2006	McMan et al.	7,417,781 B2	8/2008	Tonar et al.
7,154,657 B2	12/2006	Poll et al.	7,420,159 B2	9/2008	Heslin et al.
7,158,881 B2	1/2007	McCarthy et al.	7,446,462 B2	11/2008	Lim et al.
7,160,017 B2	1/2007	Lee et al.	7,446,650 B2	11/2008	Schofield et al.
7,161,567 B2	1/2007	Homma et al.	7,446,924 B2	11/2008	Schofield et al.
7,167,796 B2	1/2007	Taylor et al.	7,448,776 B2	11/2008	Tang
7,175,291 B1	2/2007	Li	7,452,090 B2	11/2008	Weller et al.
7,176,790 B2	2/2007	Yamazaki	7,453,057 B2	11/2008	Drummond et al.
7,184,190 B2	2/2007	McCabe et al.	7,455,412 B2	11/2008	Rottcher
7,185,995 B2	3/2007	Hatanaka et al.	7,460,007 B2	12/2008	Schofield et al.
7,187,498 B2	3/2007	Bengoechea et al.	7,467,883 B2	12/2008	DeLine et al.
7,188,963 B2	3/2007	Schofield et al.	7,468,651 B2	12/2008	DeLine et al.
7,193,764 B2	3/2007	Lin et al.	7,471,438 B2	12/2008	McCabe et al.
7,195,381 B2	3/2007	Lynam et al.	7,474,963 B2	1/2009	Taylor et al.
7,199,767 B2	4/2007	Spero	7,477,439 B2	1/2009	Tonar et al.
7,206,697 B2	4/2007	Olney et al.	7,480,149 B2	1/2009	DeWard et al.
7,209,277 B2	4/2007	Tonar et al.	7,488,080 B2	2/2009	Skiver et al.
7,215,238 B2	5/2007	Buck et al.	7,489,374 B2	2/2009	Utsumi et al.
7,215,473 B2	5/2007	Fleming	7,490,007 B2	2/2009	Taylor et al.
7,221,363 B2	5/2007	Roberts et al.	7,490,943 B2	2/2009	Kikuchi et al.
7,224,324 B2	5/2007	Quist et al.	7,490,944 B2	2/2009	Blank et al.
7,230,523 B2	6/2007	Harter, Jr. et al.	7,494,231 B2	2/2009	Varaprasad et al.
7,232,231 B2	6/2007	Shih	7,495,719 B2	2/2009	Adachi et al.
7,233,304 B1	6/2007	Aratani et al.	7,496,439 B2	2/2009	McCormick
7,235,918 B2	6/2007	McCullough et al.	7,502,156 B2	3/2009	Tonar et al.
7,241,030 B2	7/2007	Mok et al.	7,505,188 B2	3/2009	Niiyama et al.
7,241,037 B2	7/2007	Mathieu et al.	7,511,607 B2	3/2009	Hubbard et al.
7,245,207 B1	7/2007	Dayan et al.	7,511,872 B2	3/2009	Tonar et al.
7,245,336 B2	7/2007	Hiyama et al.	7,525,715 B2	4/2009	McCabe et al.
7,248,305 B2	7/2007	Ootsuta et al.	7,526,103 B2	4/2009	Schofield et al.
7,251,079 B2	7/2007	Capaldo et al.	7,533,998 B2	5/2009	Schofield et al.
7,255,451 B2	8/2007	McCabe et al.	7,538,316 B2	5/2009	Heslin et al.
7,255,465 B2	8/2007	DeLine et al.	7,540,620 B2	6/2009	Weller et al.
7,259,036 B2	8/2007	Borland et al.	7,541,570 B2	6/2009	Drummond et al.
7,262,406 B2	8/2007	Heslin et al.	7,542,193 B2	6/2009	McCabe et al.
7,262,916 B2	8/2007	Kao et al.	7,543,947 B2	6/2009	Varaprasad et al.
7,265,342 B2	9/2007	Heslin et al.	7,547,467 B2	6/2009	Olson et al.
7,268,841 B2	9/2007	Kasajima et al.	7,548,291 B2	6/2009	Lee et al.
7,269,327 B2	9/2007	Tang	7,551,354 B2	6/2009	Horsten et al.
7,269,328 B2	9/2007	Tang	7,561,181 B2	7/2009	Schofield et al.
7,271,951 B2	9/2007	Weber et al.	7,562,985 B2	7/2009	Cortenraad et al.
7,274,501 B2	9/2007	McCabe et al.	7,567,291 B2	7/2009	Bechtel et al.
7,281,491 B2	10/2007	Iwamaru	7,571,038 B2	8/2009	Butler et al.
7,286,280 B2	10/2007	Whitehead et al.	7,571,042 B2	8/2009	Taylor et al.
7,287,868 B2	10/2007	Carter et al.	7,572,490 B2	8/2009	Park et al.
7,289,037 B2	10/2007	Uken et al.	7,579,939 B2	8/2009	Schofield et al.
7,290,919 B2	11/2007	Pan et al.	7,579,940 B2	8/2009	Schofield et al.
7,292,208 B1	11/2007	Park et al.	7,580,795 B2	8/2009	McCarthy et al.
7,300,183 B2	11/2007	Kiyomoto et al.	7,581,859 B2	9/2009	Lynam
7,308,341 B2	12/2007	Schofield et al.	7,581,867 B2	9/2009	Lee et al.
7,310,177 B2	12/2007	McCabe et al.	7,583,184 B2	9/2009	Schofield et al.
7,311,428 B2	12/2007	DeLine et al.	7,586,566 B2	9/2009	Nelson et al.
7,316,485 B2	1/2008	Roose	7,586,666 B2	9/2009	McCabe et al.
7,318,664 B2	1/2008	Hatanaka et al.	7,589,893 B2	9/2009	Rottcher

US 8,282,226 B2

Page 10

7,600,878	B2	10/2009	Blank et al.	2003/0146831	A1	8/2003	Berberich et al.
7,605,883	B2	10/2009	Yamaki et al.	2003/0156193	A1	8/2003	Nakamura
7,619,508	B2	11/2009	Lynam et al.	2003/0169158	A1	9/2003	Paul, Jr.
7,623,202	B2	11/2009	Araki et al.	2003/0179293	A1	9/2003	Oizumi
7,626,749	B2	12/2009	Baur et al.	2003/0189754	A1	10/2003	Sugino et al.
7,633,567	B2	12/2009	Yamada et al.	2003/0202096	A1	10/2003	Kim
7,636,188	B2	12/2009	Baur et al.	2003/0206256	A1	11/2003	Drain et al.
7,636,195	B2	12/2009	Nieuwkerk et al.	2003/0214576	A1	11/2003	Koga
7,636,930	B2	12/2009	Chang	2003/0214584	A1	11/2003	Ross, Jr.
7,643,200	B2	1/2010	Varaprasad et al.	2003/0214733	A1	11/2003	Fujikawa et al.
7,643,927	B2	1/2010	Hils	2003/0222793	A1	12/2003	Tanaka et al.
7,651,228	B2	1/2010	Skiver et al.	2003/0222983	A1	12/2003	Nobori et al.
7,658,521	B2	2/2010	DeLine et al.	2003/0227546	A1	12/2003	Hilborn et al.
7,663,798	B2	2/2010	Tonar et al.	2004/0004541	A1	1/2004	Hong
7,667,579	B2	2/2010	DeLine et al.	2004/0027695	A1	2/2004	Lin
7,670,016	B2	3/2010	Weller et al.	2004/0032321	A1	2/2004	McMahon et al.
7,688,495	B2	3/2010	Tonar et al.	2004/0032655	A1	2/2004	Kikuchi et al.
7,695,174	B2	4/2010	Takayanagi et al.	2004/0032676	A1	2/2004	Drummond et al.
7,696,964	B2	4/2010	Lankhorst et al.	2004/0036768	A1	2/2004	Green
7,706,046	B2	4/2010	Bauer et al.	2004/0046870	A1	3/2004	Leigh Travis
7,710,631	B2	5/2010	McCabe et al.	2004/0051634	A1	3/2004	Schofield et al.
7,711,479	B2	5/2010	Taylor et al.	2004/0056955	A1	3/2004	Berberich et al.
7,726,822	B2	6/2010	Blank et al.	2004/0057131	A1	3/2004	Hutzel et al.
7,728,276	B2	6/2010	Drummond et al.	2004/0064241	A1	4/2004	Sekiguchi
7,728,721	B2	6/2010	Schofield et al.	2004/0066285	A1	4/2004	Sekiguchi
7,728,927	B2	6/2010	Nieuwkerk et al.	2004/0075603	A1	4/2004	Kodama
7,734,392	B2	6/2010	Schofield et al.	2004/0077359	A1	4/2004	Bernas et al.
7,746,534	B2	6/2010	Tonar et al.	2004/0080404	A1	4/2004	White
7,787,077	B2	8/2010	Kondoh et al.	2004/0085196	A1	5/2004	Miller et al.
7,791,694	B2	9/2010	Molsen et al.	2004/0085499	A1	5/2004	Baek
7,795,675	B2	9/2010	Darwish et al.	2004/0090314	A1	5/2004	Iwamoto
7,830,583	B2	11/2010	Neuman et al.	2004/0090317	A1	5/2004	Rothkop
7,842,154	B2	11/2010	Lynam	2004/0096082	A1	5/2004	Nakai et al.
2001/0019356	A1	9/2001	Takeda et al.	2004/0098196	A1	5/2004	Sekiguchi
2001/0022616	A1	9/2001	Rademacher et al.	2004/0105614	A1	6/2004	Kobayashi et al.
2001/0026215	A1	10/2001	Nakaho et al.	2004/0107030	A1	6/2004	Nishira et al.
2001/0026316	A1	10/2001	Senatore	2004/0109060	A1	6/2004	Ishii
2001/0030857	A1	10/2001	Futhey et al.	2004/0114039	A1	6/2004	Ishikura
2001/0035853	A1	11/2001	Hoelen et al.	2004/0170008	A1	9/2004	Tenmyo
2001/0045981	A1	11/2001	Gloger et al.	2004/0202001	A1	10/2004	Roberts et al.
2002/0036828	A1	3/2002	Wong	2004/0239243	A1	12/2004	Roberts et al.
2002/0044065	A1	4/2002	Quist et al.	2004/0239849	A1	12/2004	Wang
2002/0049535	A1	4/2002	Rigo et al.	2004/0243303	A1	12/2004	Padmanabhan
2002/0085155	A1	7/2002	Arikawa	2004/0251804	A1	12/2004	McCullough et al.
2002/0092958	A1	7/2002	Lusk	2004/0264011	A1	12/2004	Lynam
2002/0118321	A1	8/2002	Ge	2005/0018738	A1	1/2005	Duan et al.
2002/0133144	A1	9/2002	Chan et al.	2005/0024591	A1	2/2005	Lian et al.
2002/0149727	A1	10/2002	Wang	2005/0024729	A1	2/2005	Ockerse et al.
2002/0154007	A1	10/2002	Yang	2005/0078389	A1	4/2005	Kulas et al.
2002/0196639	A1	12/2002	Weidel	2005/0079326	A1	4/2005	Varaprasad et al.
2003/0002165	A1	1/2003	Mathias et al.	2005/0099559	A1	5/2005	Lee et al.
2003/0002179	A1	1/2003	Roberts et al.	2005/0099693	A1	5/2005	Schofield et al.
2003/0007261	A1	1/2003	Hutzel et al.	2005/0111070	A1	5/2005	Lin et al.
2003/0016287	A1	1/2003	Nakayama et al.	2005/0117095	A1	6/2005	Ma
2003/0016542	A1	1/2003	Pastrick et al.	2005/0134983	A1	6/2005	Lynam
2003/0025596	A1	2/2003	Lang et al.	2005/0140855	A1	6/2005	Utsumi et al.
2003/0030546	A1	2/2003	Tseng	2005/0168995	A1	8/2005	Kittelmann et al.
2003/0030724	A1	2/2003	Okamoto	2005/0169003	A1	8/2005	Lindahl et al.
2003/0035050	A1	2/2003	Mizusawa et al.	2005/0172504	A1	8/2005	Ohm et al.
2003/0043269	A1	3/2003	Park	2005/0237440	A1	10/2005	Sugimura et al.
2003/0043589	A1	3/2003	Blank	2005/0259326	A1	11/2005	Weber et al.
2003/0048639	A1	3/2003	Boyd et al.	2005/0270766	A1	12/2005	Kung et al.
2003/0052969	A1	3/2003	Satoh et al.	2006/0001641	A1	1/2006	Degwekar et al.
2003/0058338	A1	3/2003	Kawauchi et al.	2006/0050018	A1	3/2006	Hutzel et al.
2003/0069690	A1	4/2003	Correia et al.	2006/0061008	A1	3/2006	Karner et al.
2003/0080877	A1	5/2003	Takagi et al.	2006/0076860	A1	4/2006	Hoss
2003/0088361	A1	5/2003	Sekiguchi	2006/0139953	A1	6/2006	Chou et al.
2003/0090568	A1	5/2003	Pico	2006/0164230	A1	7/2006	DeWind et al.
2003/0090569	A1	5/2003	Poechmueller	2006/0171704	A1	8/2006	Bingle et al.
2003/0090570	A1	5/2003	Takagi et al.	2006/0187378	A1	8/2006	Bong et al.
2003/0095331	A1	5/2003	Bengoechea et al.	2006/0274218	A1	12/2006	Xue
2003/0098908	A1	5/2003	Misaiji et al.	2006/0279522	A1	12/2006	Kurihara
2003/0101749	A1	6/2003	Lingle et al.	2007/0041096	A1	2/2007	Nieuwkerk et al.
2003/0103142	A1	6/2003	Hitomi et al.	2007/0058257	A1	3/2007	Lynam
2003/0117522	A1	6/2003	Okada	2007/0064108	A1	3/2007	Haler
2003/0122929	A1	7/2003	Minaudo et al.	2007/0080585	A1	4/2007	Lyu
2003/0133014	A1	7/2003	Mendoza	2007/0118287	A1	5/2007	Taylor et al.
2003/0137586	A1	7/2003	Lewellen	2007/0183037	A1	8/2007	De Boer et al.
2003/0141965	A1	7/2003	Gunderson et al.	2007/0183066	A1	8/2007	Varaprasad et al.

2007/0184284	A1	8/2007	Varaprasad et al.	DE	9306989.8	U1	7/1993
2007/0201122	A1	8/2007	Dozeman et al.	DE	4329983		8/1995
2007/0262732	A1	11/2007	Shen	DE	4444443	A1	6/1996
2008/0002106	A1	1/2008	Van De Witte et al.	DE	29703084	U1	6/1997
2008/0030311	A1	2/2008	Dayan et al.	DE	29805142	U1	5/1998
2008/0068520	A1	3/2008	Miniskey, Jr. et al.	DE	19741896		4/1999
2008/0077882	A1	3/2008	Kramer et al.	DE	19755008		7/1999
2008/0094685	A1	4/2008	Varaprasad et al.	DE	29902344	U1	7/1999
2008/0180529	A1	7/2008	Taylor et al.	DE	19934999		2/2001
2008/0180781	A1	7/2008	Varaprasad et al.	DE	19943355		3/2001
2008/0212189	A1	9/2008	Baur et al.	DE	20118868		3/2002
2008/0225538	A1	9/2008	Lynam et al.	DE	10131459		1/2003
2008/0231704	A1	9/2008	Schofield et al.	EP	0299509	A2	1/1989
2008/0266389	A1	10/2008	DeWind et al.	EP	0513476	A1	11/1992
2008/0291522	A1	11/2008	Varaprasad et al.	EP	0524766		1/1993
2008/0308219	A1	12/2008	Lynam	EP	0729864	A1	12/1995
2009/0002491	A1	1/2009	Haler	EP	0728618	A2	8/1996
2009/0015736	A1	1/2009	Weller et al.	EP	0825477		2/1998
2009/0033837	A1	2/2009	Molsen et al.	EP	0830985		3/1998
2009/0040465	A1	2/2009	Conner et al.	EP	0928723	A2	7/1999
2009/0040588	A1	2/2009	Tonar et al.	EP	937601	A2	8/1999
2009/0040778	A1	2/2009	Takayanagi et al.	EP	1075986		2/2001
2009/0052003	A1	2/2009	Schofield et al.	EP	1097848	A	5/2001
2009/0067032	A1	3/2009	Varaprasad et al.	EP	1152285	A2	11/2001
2009/0080055	A1	3/2009	Baur et al.	EP	1193773		3/2002
2009/0085729	A1	4/2009	Nakamura et al.	EP	1256833		11/2002
2009/0096937	A1	4/2009	Bauer et al.	EP	0899157		10/2004
2009/0141331	A1	6/2009	Skiver et al.	EP	1315639		2/2006
2009/0174776	A1	7/2009	Taylor et al.	FR	1021987	A	2/1953
2009/0184904	A1	7/2009	S. et al.	FR	1461419		12/1966
2009/0201137	A1	8/2009	Weller et al.	FR	2585991		2/1987
2009/0219394	A1	9/2009	Heslin et al.	FR	2672857	A1	8/1992
2009/0231741	A1	9/2009	Weller et al.	FR	2673499	A1	9/1992
2009/0237820	A1	9/2009	McCabe et al.	FR	2759045		8/1998
2009/0243824	A1	10/2009	Hook et al.	GB	810010		3/1959
2009/0244740	A1	10/2009	Takayanagi et al.	GB	934037		8/1963
2009/0262192	A1	10/2009	Schofield et al.	GB	1008411		10/1965
2009/0262422	A1	10/2009	Cross et al.	GB	1136134		12/1968
2009/0290369	A1	11/2009	Schofield et al.	GB	1553376		9/1979
2009/0296190	A1	12/2009	Anderson et al.	GB	2137573	A	10/1984
2010/0033797	A1	2/2010	Schofield et al.	GB	2161440		1/1986
2010/0045790	A1	2/2010	Lynam et al.	GB	2192370		1/1988
2010/0045899	A1	2/2010	Ockerse	GB	2222991		3/1990
2010/0046059	A1	2/2010	McCabe et al.	GB	2255539	A	11/1992
2010/0053723	A1	3/2010	Varaprasad et al.	GB	2351055	A	12/2000
2010/0085645	A1	4/2010	Skiver et al.	GB	2362494		11/2001
2010/0091509	A1	4/2010	DeLine et al.	JP	50-000638	A	1/1975
2010/0110523	A1	5/2010	Varaprasad et al.	JP	52-146988		11/1977
2010/0110553	A1	5/2010	Anderson et al.	JP	55-039843		3/1980
2010/0117815	A1	5/2010	Deline et al.	JP	57-30639		2/1982
2010/0126030	A1	5/2010	Weller et al.	JP	57-208530		12/1982
2010/0165437	A1	7/2010	Tonar et al.	JP	58-030729		2/1983
2010/0172008	A1	7/2010	McCabe et al.	JP	58020954		2/1983
2010/0174485	A1	7/2010	Taylor et al.	JP	58-110334		6/1983
2010/0194890	A1	8/2010	Weller et al.	JP	58-180347		10/1983
2010/0195226	A1	8/2010	Heslin et al.	JP	58-209635		12/1983
2010/0201896	A1	8/2010	Ostreko et al.	JP	59-114139		7/1984
2010/0202075	A1	8/2010	Blank et al.	JP	60-212730		10/1985
2010/0207013	A1	8/2010	Drummond et al.	JP	60-261275		12/1985
2010/0214662	A1	8/2010	Takayanagi et al.	JP	61127186		6/1986
2010/0219985	A1	9/2010	Schofield et al.	JP	61-260217		11/1986
2010/0222963	A1	9/2010	Schofield et al.	JP	62-043543		2/1987
2010/0245701	A1	9/2010	Sato et al.	JP	62-075619		4/1987
2010/0246017	A1	9/2010	Tonar et al.	JP	62-122487		6/1987
2010/0277786	A1	11/2010	Anderson et al.	JP	62131232		6/1987
2010/0289995	A1	11/2010	Hwang et al.	JP	63-02753		1/1988
2011/0109746	A1	5/2011	Schofield et al.	JP	63085525		4/1988
2011/0141543	A1	6/2011	Uken et al.	JP	63-106730		5/1988
FOREIGN PATENT DOCUMENTS				JP	63-106731		5/1988
				JP	63-274286		11/1988
AU	A-40317/95	2/1995		JP	64-14700		1/1989
CN	1189224	7/1998		JP	01-123587		5/1989
DE	941408	4/1956		JP	01130578		5/1989
DE	944531	7/1956		JP	02-122844		10/1990
DE	7323996	11/1973		JP	03-28947		3/1991
DE	3248511	7/1984	A1	JP	03-052097		3/1991
DE	3301945	7/1984		JP	30-061192		3/1991
DE	3614882	11/1987		JP	328947		3/1991
DE	3720848	1/1989		JP	03-110855		5/1991

JP	03198026	8/1991
JP	03-243914	10/1991
JP	04-114587	4/1992
JP	04-245886	9/1992
JP	05080716	4/1993
JP	05183194	7/1993
JP	05-213113	8/1993
JP	05-257142	10/1993
JP	60-80953 A	3/1994
JP	61-07035 A	4/1994
JP	62-27318 A	8/1994
JP	06318734	11/1994
JP	07146467	6/1995
JP	07-175035	7/1995
JP	07191311	7/1995
JP	07-266928	10/1995
JP	07-277072	10/1995
JP	07-281185	10/1995
JP	07267002	10/1995
JP	07281150	10/1995
JP	08-008083	1/1996
JP	08-083581	3/1996
JP	08-216789	8/1996
JP	08227769	9/1996
JP	09033886	2/1997
JP	09-260074	3/1997
JP	05-077657	7/1997
JP	09-220976	8/1997
JP	09230827	9/1997
JP	09-266078	10/1997
JP	09-288262	11/1997
JP	10-076880	3/1998
JP	10-199480	7/1998
JP	10190960	7/1998
JP	10-206643	8/1998
JP	10221692	8/1998
JP	10239659	9/1998
JP	10276298	10/1998
JP	11-038381	2/1999
JP	11-067485	3/1999
JP	11-078693	3/1999
JP	11-109337	4/1999
JP	11-160539	6/1999
JP	11-212073	8/1999
JP	11-283759	10/1999
JP	11-298058	10/1999
JP	11-305197	11/1999
JP	2000-131681	5/2000
JP	2000-153736	6/2000
JP	2000-159014	6/2000
JP	2000-255321	9/2000
JP	2000-330107	11/2000
JP	2001-083509	3/2001
JP	2001-222005	8/2001
JP	200272901	3/2002
JP	2002-120649	4/2002
JP	2002-122860	4/2002
JP	2002162626	6/2002
JP	2002-352611	12/2002
JP	2003-267129	9/2003
JP	2004-182156	7/2004
JP	2005-148119	6/2005
JP	2005-327600	11/2005
JP	38-46073	11/2006
JP	2008083657	4/2008
KR	20060038856	5/2006
KR	100663930	1/2007
WO	WO 82/02448	7/1982
WO	WO8606179	10/1986
WO	WO 94/19212	9/1994
WO	WO 96/21581	7/1996
WO	WO 98/14974	4/1998
WO	WO 98/38547	9/1998

WO	WO 99/15360	4/1999
WO	WO 00/23826	4/2000
WO	WO 00/52661	9/2000
WO	WO 00/55685	9/2000
WO	WO 01/01192	1/2001
WO	WO 02/18174	3/2002
WO	WO 02/49881	6/2002
WO	WO 03/021343	3/2003
WO	WO03078941	9/2003

OTHER PUBLICATIONS

Stewart, James W.; HP SnapLED: LED Assemblies for Automotive Signal Applications; Nov. 1, 1998; Hewlett-Packard Journal; vol. 50, No. 1, www.hpl.hp.com/hpjournal/98nov/nov98al.pdf.

Edgar, Julian; Goodbye 12 Volts . . . Hello 42 Volts!; Oct. 5, 1999; Autospeed 50; Issue 50; www.autospeed.co.nz/cms/A_0319/article.html.

Kobe, Gerry; 42 Volts Goes Underhood; Mar. 2000; Automotive Industries; Cahners Publishing Company; www.findarticles.com/p/articles/mi_m3012/is_3_180/ai_61361677.

Jewett, Dale; Aug. 2000; Automotive Industries; Cahners Publishing Company; www.findarticles.com/p/articles/mi_m3012/is_8_180ai_64341779.

National Semiconductor, LM78S40, Universal Switching Regulator Subsystem, National Semiconductor Corporation, Apr. 1996, p. 6.

Dana H. Ballard and Christopher M. Brown, Computer Vision, article, 4 pages Prentice-Hall, Englewood Cliffs, New Jersey, believed to be published more than one year prior to the filing date of the present application.

G. Wang, D. Renshaw, P.B. Denyer and M. Lu, CMOS Video Cameras, article, 1991, 4 pages, University of Edinburgh, UK.

International Search Report dated Oct. 6, 2003, 1 page, received from the International Searching Authority in connection with International Application No. PCT/US03/17804.

European Supplementary Search Report dated Mar. 7, 2008, 2 pages, received from the European Patent Office in connection with European Patent Application No. 03736877.6.

* cited by examiner


Primary Examiner — Euncha P Cherry

(74) *Attorney, Agent, or Firm* — Gardner, Linn, Burkhart & Flory, LLP

(57) **ABSTRACT**

An interior rearview mirror system for a vehicle includes an interior rearview mirror assembly having a mirror casing, a reflective element and an application specific integrated compass chip. The application specific integrated compass chip includes at least two magnetoresponsive sensing elements established on a semiconductor substrate, and further includes associated circuitry commonly established with the magnetoresponsive sensing elements on the semiconductor substrate. Processing of an algorithm by a microprocessor of the interior rearview mirror system determines a directional heading of the vehicle responsive to a sensing of a magnetic field by the magnetoresponsive sensing elements and automatically compensates for a deviating magnetic field. An information display of the interior rearview mirror assembly displays the directional heading of the vehicle. The application specific integrated compass chip may have an area of less than approximately two square centimeters.

37 Claims, 5 Drawing Sheets






FIG. 2




FIG. 3




FIG. 5




FIG. 4




FIG. 6




FIG. 7

INTERIOR REARVIEW MIRROR SYSTEM**CROSS REFERENCE TO RELATED APPLICATIONS**

The present application is a continuation of U.S. patent application Ser. No. 12/766,160, filed Apr. 23, 2010, now U.S. Pat. No. 7,815,326, which is a continuation of U.S. patent application Ser. No. 12/575,726, filed Oct. 8, 2009, now U.S. Pat. No. 7,726,822, which is a continuation of U.S. patent application Ser. No. 12/370,043, filed Feb. 12, 2009, now U.S. Pat. No. 7,600,878, which is a continuation of U.S. patent application Ser. No. 12/029,073, filed Feb. 11, 2008, now U.S. Pat. No. 7,490,944, which is a continuation of U.S. patent application Ser. No. 11/305,637, filed Dec. 16, 2005, now U.S. Pat. No. 7,329,013, which claims benefit of U.S. provisional application Ser. No. 60/636,931, filed Dec. 17, 2004, and U.S. patent application Ser. No. 11/305,637 is a continuation-in-part of U.S. patent application Ser. No. 10/456,599, filed Jun. 6, 2003, now U.S. Pat. No. 7,004,593, which claims the benefit of U.S. provisional applications, Ser. No. 60/420,010, filed Oct. 21, 2002; Ser. No. 60/398,240, filed Jul. 24, 2002; and Ser. No. 60/386,373, filed Jun. 6, 2002, which are all hereby incorporated herein by reference in their entirety; and the present application is also a continuation-in-part of U.S. patent application Ser. No. 11/226,628, filed Sep. 14, 2005, which claims the benefit of U.S. provisional applications, Ser. No. 60/692,113, filed Jun. 20, 2005; Ser. No. 60/677,990, filed May 5, 2005; Ser. No. 60/653,787, filed Feb. 17, 2005; Ser. No. 60/642,227, filed Jan. 7, 2005; Ser. No. 60/638,250, filed Dec. 21, 2004; Ser. No. 60/624,091, filed Nov. 1, 2004, and Ser. No. 60/609,642, filed Sep. 14, 2004.

FIELD OF THE INVENTION

The present invention relates generally to interior rearview mirror assemblies for vehicles and, more particularly, to an interior rearview mirror assembly which includes a compass system.

BACKGROUND OF THE INVENTION

Interior rearview mirror assemblies which include a directional or compass display are known, such as the types disclosed in U.S. Pat. No. 5,802,727, which is hereby incorporated herein by reference. Typically, such mirror assemblies include a compass sensor, such as a magnetoresistive sensor, a magnetocapacitive sensor, a magnetoinductive sensor, a Hall effect sensor, or a flux gate sensor or the like, which is fixedly attached to the mirror mount that attaches the mirror assembly to a mirror assembly mounting element, such as a conventional mounting button mounted on an interior surface of the windshield of the vehicle. The mirror assemblies also include processing circuitry and a compass information display, typically included in the interior mirror casing (that includes the mirror reflector) which is pivotally adjustable by the driver to suit his or her rearward field of view.

Predominantly, compass mirror assemblies in the market today involve the fixed placement of the compass sensor (and any locally associated sensor circuitry), such as at the mirror mount where the mirror attaches to the windshield or headliner of the vehicle. The compass system typically involves a cable/harness connection to the processing circuitry (which is typically in the pivotable housing of the mirror assembly), which may include the compass compensation circuitry and the like, which feeds or connects to a display (such as a

vacuum fluorescent (VF) display or the like) that is typically included in the adjustable mirror casing (such as behind the reflective element so as to display from behind and through the reflective element, or at an eyebrow or chin region of the bezel area of the mirror casing). The display then typically displays an output of the directional heading of the vehicle to the driver or passenger of the vehicle, such as an eight point display, such as N, S, E, W, NE, NW, SE, SW, or the like.

It has been proposed in the art to mount the compass sensor within the movable housing of the rearview mirror assembly. Processes have also been proposed to compensate for movement of the sensor during normal use of the mirror, such as when the mirror head or casing is adjusted by the driver. Such proposed systems, such as described in U.S. Pat. Nos. 6,140,933 and 6,023,229, which are hereby incorporated herein by reference, are often implemented with a specially adapted single ball mount or single pivot mirror assembly. Such compass mirror assemblies can be costly and often involve special tooling and complicated adaptation of the mirror assembly itself and the casing of the mirror assembly. Also, such compass systems as described in the patents referenced above are not readily adapted for use with double ball or double pivot mirror assemblies. Other compass systems and compass compensation systems, such as the types described in U.S. Pat. Nos. 4,581,827; 5,339,529; 5,455,716; 5,699,044; 5,737,226; and 5,808,197, and/or in PCT Publication No. WO 2004/076971 A2, published Sep. 10, 2004; and/or in PCT Publication No. WO 2003/044540 A2, published May 30, 2003; and/or in PCT Publication No. WO 2003/074969 A3, published Sep. 12, 2003 (which are all hereby incorporated herein by reference), may be implemented in interior rearview mirror assemblies, but may be costly and difficult to implement within the movable mirror head of an interior rearview mirror assembly with a single or double ball mounting arrangement.

Therefore, there is a need in the art for an interior rearview mirror assembly having a compass system associated therewith that overcomes the shortcomings of the prior art.

SUMMARY OF THE INVENTION

The present invention is intended to provide an interior rearview mirror system which includes a compass system having a display which indicates the general direction in which the vehicle is traveling.

According to an aspect of the present invention, a mirror and compass system includes an interior rearview mirror assembly having a reflective element and a casing that are adjustable relative to a mounting structure. A compass sensor having at least two magnetoresponsive sensing elements is positioned within the mirror casing and at a position and orientation that reduces the effect of adjustment of the mirror on the compass sensor output.

The compass sensor is preferably positioned at a generally central location of the mirror and at or near the centerline of the mirror head. Preferably, the compass sensor is positioned at or near a lower region of the mirror casing to position the sensor remotely from the roof of the vehicle and any wiring or lights or the like that may be positioned at the roof of the vehicle, in order to reduce the effect of such items on the compass sensor performance.

Preferably, the compass sensor is oriented such that one of the sensing elements is generally along a longitudinal axis of the vehicle and the other sensing element is generally along a cross car axis of the vehicle when the mirror is oriented at a typical in-use position (such as at an angle of about 20 degrees rotation toward the driver side and at an angle of about 9

3

degrees tilt downward). Optionally, the system may determine when a prismatic mirror is flipped or toggled between the daytime and nighttime orientations and may compensate or adjust the processing of the compass sensor output to compensate for the known movement (such as about 4½ degrees upward or downward) of the mirror head/reflective element and compass sensor.

Optionally, the compass sensor may be positioned in close proximity to the mirror ball of the mounting arm (the ball that is received in the socket at the mirror casing or reflective element or toggle portion of the mirror assembly) so as to reduce movement of the compass sensor when the mirror is adjusted, in order to reduce the effects of mirror adjustment on the compass sensor performance. Optionally, the compass sensor may be generally fixedly positioned relative to the mirror ball of the mounting arm so that the compass sensor is generally fixed and do not move during adjustments of the mirror head/reflective element when the driver grasps and moves the mirror head/reflective element to adjust to his or her preferred field of view rearward through the rear window of the vehicle.

Optionally, the mirror and compass system may operate to enter a rapid compensating and aggressive calibration mode in response to a detection of an abrupt movement of the mirror head and compass sensor. The system may determine when such an abrupt movement is indicative of a mirror adjustment (such as an adjustment between the daytime and nighttime orientations for a prismatic mirror or an adjustment of the mirror by a person who has just entered the vehicle or started the vehicle ignition), and then may enter the aggressive calibration mode in response to such a determination. The system thus may discern, such as algorithmically via software and/or aided via a movement/mechanical adjust detector/sensor element, between a change in sensor output that is indicative of a mirror adjustment and a change in sensor output that is indicative of a change in vehicle direction and may enter the aggressive calibration mode when the change in sensor output is indicative of a mirror adjustment. Such a mirror adjustment typically occurs rapidly (such as in less than one second) and has a predictable range and/or direction, so that the compass system can discern when a change in sensor output is indicative of a mirror adjustment versus a detection of a magnetic field anomaly or the like or versus a change in directional heading of the vehicle.

According to another aspect of the present invention, an interior rearview mirror system for a vehicle includes an interior rearview mirror assembly, a casing having a reflective element, a compass sensor and a control. The casing is adjustable relative to a mounting structure that mounts the interior rearview mirror assembly to an interior portion of the vehicle. The compass sensor has a first magnetoresponsive sensing element and a second magnetoresponsive sensing element. The compass sensor is disposed within the mirror casing. The control receives a first signal indicative of a magnetic field sensed by the first magnetoresponsive sensing element and receives a second signal indicative of a magnetic field sensed by the second magnetoresponsive sensing element. The control determines a directional heading of the vehicle based on the first and second signals. The control automatically compensates for a deviating magnetic field of the vehicle and generates a signal indicative of the directional heading of the vehicle. The control determines that the casing is adjusted by an occupant of the vehicle in response to a change in the first and second signals being indicative of an abrupt movement of the casing about the mounting structure by an occupant of the vehicle (such as when the driver or occupant of the vehicle adjusts the mirror reflective element to provide a desired

4

reflector rearward field of view). The control is operable to enter a rapid compensating mode to compensate for the mirror adjustment in response to the control determining that the casing is adjusted by an occupant of the vehicle.

According to another aspect of the present invention, an interior rearview mirror system for a vehicle includes an interior rearview mirror assembly, a casing having a reflective element, a compass sensor and a control. The casing is adjustable relative to a mounting structure that mounts the interior rearview mirror assembly to an interior portion of the vehicle. The compass sensor has a first magnetoresponsive sensing element and a second magnetoresponsive sensing element. The compass sensor is disposed within the mirror casing. The control receives a first signal indicative of a magnetic field sensed by the first magnetoresponsive sensing element and a second signal indicative of a magnetic field sensed by the second magnetoresponsive sensing element. The control determines a directional heading of the vehicle based on the first and second signals and automatically compensates for a deviating magnetic field of the vehicle and generates a signal indicative of the directional heading of the vehicle. The control is operable to enter a rapid compensating mode in response to an ignition cycle of the vehicle. The control automatically exits the rapid compensating mode and enters a less aggressive calibration mode that distinguishes the Earth's magnetic field from magnetic anomalies and non-abrupt changes in the vehicle magnetic signature. The control automatically exits the rapid compensating mode after a predetermined period of time has elapsed since the ignition cycle.

Therefore, the present invention provides a mirror and compass system that positions the compass sensor within the movable head portion of the mirror assembly. The compass sensor is positioned in a manner that reduces the effects of mirror adjustment on the sensor performance. The system may adjust processing in response to known movements of the mirror head to compensate for such known movements. The system may enter an aggressive calibration mode to calibrate the compass sensor when the mirror has been adjusted by a user. The compass system may distinguish between the anomaly signature or pattern and the mirror adjustment signature or pattern and may enter the calibration mode when the mirror adjustment is detected.

These and other objects, advantages, purposes and features of the present invention will become apparent upon review of the following specification in conjunction with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a forward facing elevation of an interior rearview mirror assembly in accordance with the present invention, as facing forward with respect to a direction of travel of a vehicle;

FIG. 2 is a forward facing elevation of a interior rearview mirror assembly of the present invention;

FIG. 3 is a sectional view of the interior rearview mirror assembly taken along the line III-III in FIG. 2;

FIG. 4 is a top plan view of the interior rearview mirror assembly of the present invention;

FIG. 5 is a sectional view of the interior rearview mirror assembly of FIG. 4;

FIG. 6 is a sectional view of another interior rearview mirror assembly in accordance with the present invention; and

FIG. 7 is a sectional view of another interior rearview mirror assembly and mounting assembly in accordance with the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the drawings and the illustrative embodiments depicted therein, a compassized prismatic interior rearview mirror assembly or system **10** includes a double pivot or double ball mounting arrangement **12** for pivotally or adjustably mounting a casing **14**, bezel portion **15** and prismatic reflective element **16** of mirror assembly **10** relative to an interior portion of a vehicle, such as to an interior surface of a windshield **11** of a vehicle or the like (FIGS. 1-3). The mirror assembly **10** includes a compass system **18**, which includes a magnetoresponsive compass sensor **20** and a display **22** for providing a display or indication of the directional heading of the vehicle, such as at the reflective element **16** of the mirror.

The mirror casing or housing **14** may comprise a polypropylene material or the like and is adjustably mounted to a mirror mount (not shown) positioned at an interior portion of a vehicle, such as a mirror mounting button on a windshield of the vehicle or any other mounting member at the windshield or at a headliner or overhead console of the vehicle or the like. The mirror housing may be adjustably mounted at the vehicle via connection to a single or double ball mounting arrangement, or via connection to any other mounting arrangement, without affecting the scope of the present invention. The mirror housing **14** may then pivot or actuate around one or more ball and socket joints or connections to be adjusted relative to the interior portion of the vehicle to a desired orientation by the driver of the vehicle.

As shown in FIGS. 1 and 3, the double ball or double pivot mirror mounting arrangement **12** includes a mounting arm **12a** which is pivotally mounted at opposite ends to a mirror mount **12b** (mounted at the windshield or headliner of the vehicle, such as at a mounting button at the interior surface of the vehicle) and a mirror casing mount **12c**. Examples of double pivot or double ball mounting arrangements are described in commonly assigned U.S. Pat. Nos. 4,646,210 and 6,331,066, which are hereby incorporated herein by reference. Preferably, the mirror mounting components provide a breakaway type connection or mount, such as the types disclosed in U.S. Pat. Nos. 6,774,810; 6,642,851; 6,483,438; 6,366,213; 6,326,900; 6,222,460; 6,172,613; 6,087,953; 5,820,097; 5,377,949; and/or 5,330,149, which are hereby incorporated herein by reference. Optionally, the mirror assembly may incorporate a mounting arrangement of the types described in U.S. provisional applications, Ser. No. 60/692,113, filed Jun. 20, 2005; Ser. No. 60/677,990, filed May 5, 2005; Ser. No. 60/653,787, filed Feb. 17, 2005; Ser. No. 60/642,227, filed Jan. 7, 2005; Ser. No. 60/638,250, filed Dec. 21, 2004; Ser. No. 60/624,091, filed Nov. 1, 2004, and Ser. No. 60/609,642, filed Sep. 14, 2004; and Ser. No. 60/729,430, filed Oct. 21, 2005 by Hook for MOUNTING ASSEMBLY FOR VEHICLE INTERIOR MIRROR; and/or PCT Application No. PCT/US04/015424, filed May 18, 2004 by Donnelly Corp. et al. for MIRROR ASSEMBLY FOR VEHICLE, and published on Dec. 2, 2004, as International Publication No. WO 2004/103772; and U.S. patent application Ser. No. 10/933,842, filed Sep. 3, 2004, now U.S. Pat. No. 7,249,860; and/or Ser. No. 11/226,628, filed Sep. 14, 2005, which are hereby incorporated by reference herein. Optionally, and as shown in FIGS. 3-5, the mounting arrangement

may comprise a single ball mounting arrangement, without affecting the scope of the present invention.

In the illustrated embodiment, the reflective element **16** comprises a prismatic reflective element. The prismatic interior rearview mirror assembly may comprise any type of prismatic interior rearview mirror assembly, such as the types described in U.S. Pat. Nos. 6,318,870; 6,598,980; 5,327,288; 4,948,242; 4,826,289; 4,436,371; and 4,435,042; and PCT Application No. PCT/US2004/015424, filed May 18, 2004 by Donnelly Corporation et al. for MIRROR ASSEMBLY FOR VEHICLE, and published on Dec. 2, 2004, as International Publication No. WO 2004/103772; and U.S. patent application Ser. No. 10/933,842, filed Sep. 3, 2004 by Kulas et al. for INTERIOR REARVIEW MIRROR ASSEMBLY, now U.S. Pat. No. 7,249,860, which are hereby incorporated herein by reference. Optionally, the prismatic reflective element may comprise a conventional prismatic reflective element or prism or may comprise a prismatic reflective element of the types described in U.S. patent application Ser. No. 10/528,269, filed Mar. 17, 2005, now U.S. Pat. No. 7,274,501; Ser. No. 10/709,434, filed May 5, 2004 by Lynam for MIRROR REFLECTIVE ELEMENT, now U.S. Pat. No. 7,420,756; Ser. No. 10/933,842, filed Sep. 3, 2004 by Kulas et al. for INTERIOR REARVIEW MIRROR ASSEMBLY, now U.S. Pat. No. 7,249,860; Ser. No. 11/021,065, filed Dec. 23, 2004, now U.S. Pat. No. 7,255,451; and/or Ser. No. 10/993,302, filed Nov. 19, 2004 by Lynam for MIRROR REFLECTIVE ELEMENT FOR A VEHICLE, now U.S. Pat. No. 7,338,177; and/or PCT Application No. PCT/US03/29776, filed Sep. 19, 2003 by Donnelly Corp. et al. for MIRROR REFLECTIVE ELEMENT ASSEMBLY; and/or PCT Application No. PCT/US2004/015424, filed May 18, 2004 by Donnelly Corporation et al. for MIRROR ASSEMBLY FOR VEHICLE, and published on Dec. 2, 2004, as International Publication No. WO 2004/103772; and U.S. provisional application Ser. No. 60/525,952, filed Nov. 26, 2003 by Lynam for MIRROR REFLECTIVE ELEMENT FOR A VEHICLE, which are all hereby incorporated herein by reference, without affecting the scope of the present invention. A variety of mirror accessories and constructions are known in the art, such as those disclosed in U.S. Pat. Nos. 5,555,136; 5,582,383; 5,680,263; 5,984,482; 6,227,675; 6,229,319; and 6,315,421 (the entire disclosures of which are hereby incorporated by reference herein), that can benefit from the present invention.

The prismatic reflective element **16** may be formed from various materials such as plastic or glass, but preferably is glass, and preferably has a planar front surface **16a** extending at an angle to a planar rear surface **16b** (FIG. 3). Rear surface **16b** is preferably coated with a reflective layer of metal such as chromium, aluminum or alloys thereof as is conventionally known in the industry. The mirror casing **14** is pivotable relative to mounting arm **12a** and mirror mount **12b** to pivot the reflective element **16** in order to reduce glare during nighttime conditions. When the mirror casing is pivoted (such as via adjustment or movement of a toggle tab or actuator **24**) from a full reflectivity daytime position to a reduced reflectivity nighttime position, the reflective surface **16b** is rotated or pivoted such that the uncoated front surface **16a** of reflective element **16** is aligned for viewing by the vehicle driver instead of reflective surface **16b**. Preferably, reflective surface **16b** reflects at least about 60 percent to 95 percent of the light incident thereon, while the uncoated front surface **16a** reflects about 4 percent of the light incident thereon, such that the reflective element significantly reduces glare from headlights or other bright lights rearward of the vehicle to the driver's eyes when pivoted to the nighttime position. Although shown

and described as having a prismatic reflective element, it is envisioned that many aspects of the present invention may be equally suitable and applicable to electro-optic or electrochromic interior rearview mirror assemblies having electro-optic or electrochromic reflective elements, such as described below.

As shown in FIGS. 4 and 5, when installed in the vehicle and adjusted for viewing by a typical sized driver, the reflective element 16 is angled approximately 20 to 22 degrees toward the driver side (from a longitudinal axis 26 of the vehicle) and approximately 9 degrees downward (from a generally horizontal plane 28) toward the floor of the vehicle. This is the nominal or typical position of the reflective element when set to the daytime orientation. When the toggle 24 is flipped to set the reflective element to the nighttime orientation, the mirror head (including the reflective element and casing and circuit board and circuitry) is pivoted about 4½ degrees or thereabouts upward or downward. Typically, prism flip angles range from about 3½ degrees to about 5 degrees, and most typically are about 4¼ to about 4½ degrees.

The compass sensor 20 of compass system 18 functions to detect a directional heading of the vehicle relative to the Earth's magnetic field, as is known in the art. The compass system and sensor may utilize aspects of the compass systems described in U.S. patent application Ser. No. 10/352,691, filed Jan. 28, 2003 by Schierbeek et al. for VEHICLE COMPASS COMPENSATION, now U.S. Pat. No. 6,922,902; Ser. No. 10/933,842, filed Sep. 3, 2004 by Kulas et al. for INTERIOR REARVIEW MIRROR ASSEMBLY, now U.S. Pat. No. 7,249,860; and/or Ser. No. 10/456,599, filed Jun. 6, 2003 by Weller et al. for INTERIOR REARVIEW MIRROR SYSTEM WITH COMPASS, now U.S. Pat. No. 7,004,593, and/or U.S. Pat. Nos. 4,546,551; 5,699,044; 4,953,305; 5,576,687; 5,632,092; 5,677,851; 5,708,410; 5,737,226; 5,802,727; 5,878,370; 6,087,953; 6,173,508; 6,222,460; 6,513,252; and 6,642,851, and/or PCT Application No. PCT/US2004/015424, filed May 18, 2004 by Donnelly Corp. et al. for MIRROR ASSEMBLY FOR VEHICLE, and published on Dec. 2, 2004, as International Publication No. WO 2004/103772, and/or European patent application, published Oct. 11, 2000 under Publication No. EP 0 1043566, and/or Ser. No. 11/226,628, filed Sep. 14, 2005; U.S. provisional applications, Ser. No. 60/624,091, filed Nov. 1, 2004 by Karner et al. for MOUNTING ASSEMBLY FOR MIRROR AND METHOD OF MAKING SAME; and/or Ser. No. 60/630,061, filed Nov. 22, 2004 by Lynam et al. for MIRROR ASSEMBLY WITH VIDEO DISPLAY, which are all hereby incorporated herein by reference. The compass circuitry may include the compass sensor, such as a magneto-responsive sensor, such as a magneto-resistive sensor, such as the types disclosed in U.S. Pat. Nos. 5,255,442; 5,632,092; 5,802,727; 6,173,501; 6,427,349; and 6,513,252 (which are hereby incorporated herein by reference), a magneto-capacitive sensor, a Hall-effect sensor, such as the types described in U.S. Pat. Nos. 6,278,271; 5,942,895 and 6,184,679 (which are hereby incorporated herein by reference), a magneto-inductive sensor, such as described in U.S. Pat. No. 5,878,370 (which is hereby incorporated herein by reference), a magneto-impedance sensor, such as the types described in PCT Publication No. WO 2004/076971 A2, published Sep. 10, 2004 (which is hereby incorporated herein by reference), or a flux-gate sensor or the like, and/or may comprise a compass chip, such as described in U.S. patent application Ser. No. 11/226,628, filed Sep. 14, 2005; and U.S. provisional applications, Ser. No. 60/624,091, filed Nov. 1, 2004 by Karner et al. for MOUNTING ASSEMBLY FOR MIRROR AND METHOD OF MAKING SAME; and/or Ser. No. 60/630,

061, filed Nov. 22, 2004 by Lynam et al. for MIRROR ASSEMBLY WITH VIDEO DISPLAY, which are hereby incorporated herein by reference.

The sensor circuitry and/or the circuitry in the mirror housing and associated with the compass sensor may include processing circuitry. For example, and as shown in FIGS. 1 and 2, compass system 18 may include a printed circuit board (PCB) 30, which may be mounted or positioned or bonded along the rear surface 16b of the reflective element 16. The printed circuit board 30 may include all of the processing circuitry and the compass sensor. The processing circuitry may include compensation methods, such as those described in U.S. Pat. Nos. 4,546,551; 5,699,044; 4,953,305; 5,255,442; 5,576,687; 5,632,092; 5,677,851; 5,708,410; 5,737,226; 5,802,727; 5,878,370; 6,087,953; 6,173,508; 6,222,460; 6,513,252; and 6,642,851, and U.S. patent application Ser. No. 10/352,691, filed Jan. 28, 2003 by Schierbeek et al. for VEHICLE COMPASS COMPENSATION, now U.S. Pat. No. 6,922,902; and Ser. No. 10/456,599, filed Jun. 6, 2003 by Weller et al. for INTERIOR REARVIEW MIRROR SYSTEM WITH COMPASS, now U.S. Pat. No. 7,004,593, and European patent application, published Oct. 11, 2000 under Publication No. EP 0 1043566, which are all hereby incorporated herein by reference. The compass sensor may be incorporated in or associated with a compass system and/or display system for displaying a directional heading of the vehicle to the driver, such as a compass system of the types described in U.S. Pat. Nos. 5,924,212; 4,862,594; 4,937,945; 5,131,154; 5,255,442; and/or 5,632,092, and/or U.S. patent application Ser. No. 10/456,599, filed Jun. 6, 2003 by Weller et al. for INTERIOR REARVIEW MIRROR SYSTEM WITH COMPASS, now U.S. Pat. No. 7,004,593, and/or Ser. No. 11/284,543, filed Nov. 22, 2005 by DeWind et al. for INTERIOR MIRROR ASSEMBLY WITH DISPLAY, now U.S. Pat. No. 7,370,983, and/or PCT Application No. PCT/US2004/015424, filed May 18, 2004 by Donnelly Corp. et al. for MIRROR ASSEMBLY FOR VEHICLE, and published on Dec. 2, 2004, as International Publication No. WO 2004/103772, and/or U.S. provisional applications, Ser. No. 60/630,061, filed Nov. 22, 2004 by Lynam et al. for MIRROR ASSEMBLY WITH VIDEO DISPLAY; and/or Ser. No. 60/667,048, filed Mar. 31, 2005, which are all hereby incorporated herein by reference.

When an interior rearview mirror that includes a compass system (such as a known compass system) is first installed in a vehicle at a vehicle assembly plant (such as when the mirror assembly (including the compass sensor and circuitry) is attached to a mounting button at a vehicle windshield or other mounting portion at an interior portion of the vehicle) and first powered, known compass systems, which typically have the compass sensor fixedly mounted at the mirror foot or base or mount, include an initial calibration mode intended to allow the vehicle to be delivered from the assembly plant to an automobile dealership with the compass appropriately calibrated. Taking, for example, such a known interior mirror compass system currently supplied by the assignee to automakers, the compass system enters an aggressive calibration mode or rapid calibration/compensating mode (such as the Cal-1 mode as described in U.S. Pat. No. 6,513,252, and U.S. patent application Ser. No. 10/352,691, filed Jan. 28, 2003 by Schierbeek et al. for VEHICLE COMPASS COMPENSATION, now U.S. Pat. No. 6,922,902, which are hereby incorporated herein by reference) to calibrate the compass as the vehicle on the assembly line weaves and turns on the assembly conveyor line and as the vehicle is driven through the assembly plant and through the staging or storage lot and onto a truck for shipping to a dealer. In so doing, the assignee's

compass system determines three cardinal points (other competitive compass systems require detection of all four cardinal (N, W, S, E) points) and then deduces the true directional heading of the vehicle, compensating for the magnetic deviation inherent in the vehicle. After the vehicle is shipped to a dealer and purchased, the compass system is calibrated and the correct heading is shown on the compass display typically provided at the mirror reflector or at the mirror bezel. After this initial Cal-1 or aggressive calibration has been completed, calibration and/or compensation for stray magnetic fields and other magnetic anomalies, such as typically encountered exterior the vehicle during driving (and from the likes of metal bridges, subway lines, cellular telephone towers, large metal structures and the like), are compensated for via other less aggressive calibration/compensation modes. Thus, for example, and referring to U.S. Pat. No. 6,513,252 and U.S. patent application Ser. No. 10/352,691, filed Jan. 28, 2003 by Schierbeek et al. for VEHICLE COMPASS COMPENSATION, now U.S. Pat. No. 6,922,902, and/or Ser. No. 10/456,599, filed Jun. 6, 2003 by Weller et al. for INTERIOR REARVIEW MIRROR SYSTEM WITH COMPASS, now U.S. Pat. No. 7,004,593, which are hereby incorporated herein by reference, the compass system may initially operate in the aggressive Cal-1 calibration mode, and then may later function in a less aggressive calibration/compensation mode, such as Cal-2 or Cal-3 calibration modes.

Using the compass system of the present invention, as the vehicle is typically driven on highways (and with the compass system of the present invention in its normal operating mode or non-calibration mode), the compass system is exposed to and may be affected by the various magnetic anomalies, such as from bridges, cell towers, and/or the like referenced above. Such magnetic anomalies, however, have a particular, and often predictable, anomaly signature and/or pattern. The magnetic anomalies may impact the compass system performance and may lead to temporary inaccurate compass readings and/or an erroneous compensation of the compass system, and thus lead to display of erroneous/inaccurate compass display headings.

The compass system of the present invention includes an algorithm expressed in software processed by a microprocessor that includes a mirror adjust detection routine. This mirror adjust detection routine takes advantage of the fact that magnetic anomalies/stray magnetic fields, which emanate from structures typically external to the vehicle as it passes by such structures and objects along a road or highway, are typically temporary and relatively short lived because of the speed of passage of the vehicle. The mirror adjust detection routine further takes account of the fact that mirror adjustments by a driver of a vehicle are relatively predictable events that occur abruptly and that remain adjusted typically for the duration of that particular journey. Thus, the mirror adjust detection routine of the present invention algorithmically reduces or prevents or suppresses confusion of a mirror adjust event from other stray magnetic field/magnetic anomaly effects that are external to the vehicle. For example, the compass system of the present invention (via software operated by a microprocessor of the control of the compass system) may distinguish and/or learn the pattern and signature of such stray magnetic fields/magnetic anomalies and may ignore such and/or avoid entering particular calibration mode or modes or portions of modes when such anomalies are detected and recognized/distinguished by the compass system.

Optionally, the compass sensing device or sensor **20** may comprise a two-axis sensor (comprising two magneto-responsive sensing elements disposed at a fixed angle relative to each other, such as orthogonally to each other, and disposed

on a platform or circuit board or substrate **32** so that they are positioned generally parallel to the floor plane of the vehicle so as to be sensitive to the horizontal component of the Earth's magnetic field), or the sensor may comprise a three-axis sensor (comprising two magneto-responsive sensing elements disposed orthogonally to each other and disposed in the mirror casing cavity, and a third magneto-responsive sensing element, sometimes referred to as a z-axis sensing element, at a right angle (approximately ninety degrees) to the two sensing elements and disposed in the cavity, so that the three-axis sensor is sensitive to the horizontal component and to the vertical component of the Earth's magnetic field), without affecting the scope of the present invention. The third axis sensing element is an optional and not necessary addition to the sensor of the compass system of the present invention. However, the z-axis sensing element may be helpful in detecting and distinguishing magnetic anomalies exterior to the vehicle (as discussed above), but is not needed for the primary compass direction determination and/or the detection of a tilt or rotation of the mirror. The compass sensor may be arranged at a desired angle to provide enhanced sensing in the horizontal directions when the mirror assembly is installed in the vehicle, as discussed below.

In the illustrated embodiment of FIGS. **4** and **5**, the compass sensor **20** includes a pair of sensing elements **20a**, **20b** positioned generally orthogonal to one another. The pair of generally orthogonal sensing elements are preferably oriented relative to the vehicle such that one of the sensing elements (**20a**) is generally parallel to the floor of the vehicle and pointing generally forwardly in the direction of travel of the vehicle, while the other sensing element (**20b**) is generally orthogonal or perpendicular to the first sensing element and preferably also generally parallel to the floor of the vehicle. The compass sensor provides an output signal to compass processing circuitry, which is operable to process the output signal to determine the vehicle heading and to actuate or control or adjust an output of the display in response to the output signal.

Optionally, and desirably, the compass sensor may be positioned at a compass sensor board or substrate **32** that may extend generally horizontally from the printed circuit board **30** at the rear of the reflective element **16**. The compass sensor **20** may comprise a pair of generally orthogonal sensing elements and thus may provide a two axis sensing ability and function to provide direction sensing throughout the range of mirror adjustment with reduced or minimal impact on the accuracy of the directional sensing during such adjustment. The impact may be further reduced by various mounting arrangements or configurations and algorithms and the like, as discussed below.

As shown in FIGS. **2** and **4**, the compass sensor is desirably positioned generally centrally from side to side within the mirror assembly, such as along a centerline of the mirror assembly or along the longitudinal axis **26**, in order to reduce or minimize the affects or angular impact of the mirror adjustments on the compass sensor output. The compass sensor is also desirably positioned at or near a lower region of the circuit board and mirror assembly, so as to be positioned further from the upper sheet metal or roof of the vehicle and further from the overhead wiring or lighting, or other devices or systems that may provide dynamic magnetic disturbances, for enhanced performance of the compass sensor.

One of the sensing elements **20a** of the compass sensor **20** is preferably oriented generally along or parallel to the longitudinal axis **26** of the vehicle and the other sensing element **20b** is preferably oriented along or generally parallel to a lateral or cross-car axis **34** of the vehicle (in a side to side

orientation and generally parallel to the vehicle floor), with the sensing elements being generally normal or at a right angle to one another. Optionally, and as shown in FIG. 4, the compass sensing elements **20a**, **20b** may be oriented relative to the mirror reflective element so that the sensing element **20a** is generally parallel to the longitudinal axis **26** of the vehicle, while the other sensing element **20b** is generally parallel to the lateral or cross-car axis **34** of the vehicle when the reflective element is angled or oriented at the typical viewing position. The orthogonally oriented compass sensing elements **20a**, **20b** are thus positioned at their optimal angle for the typical setting or position or orientation of the mirror assembly during typical use of the mirror assembly in the vehicle.

For example, and as shown in FIGS. 4 and 5, the reflective element is typically rotatably angled horizontally and sidewardly toward the driver at an angle A, which is typically about 20 degrees (for a typical driver) relative to the cross car axis, and the reflective element is typically tiltably angled vertically and downwardly at an angle B, which is typically about 9 degrees (for a typical driver) relative to a vertical plane **36**. Because the mirror casing and reflective element may be pivoted to be angled generally toward the head of the driver of the vehicle, such as, for example, rotatably angled approximately 17-25 degrees toward the driver side of the vehicle and tiltably angled approximately 6 to 12 degrees downward, the compassized interior rearview mirror assembly of the present invention thus may be adapted to mount the compass sensor on a physical mount or tilt/rotation offset element at the printed circuit board which compensates for or approximates and effectively cancels the approximate angle of the mirror casing so as to orient the compass sensor generally in the desired orientation, even when the mirror casing and reflective element are angled toward the driver of the vehicle (such as described in U.S. patent application Ser. No. 10/456,599, filed Jun. 6, 2003 by Weller et al. for INTERIOR REARVIEW MIRROR SYSTEM WITH COMPASS, now U.S. Pat. No. 7,004,593, which is hereby incorporated herein by reference).

For example, a printed circuit board or equivalent may be positioned at and attached to the rear surface of the reflective element (the surface within the casing of the mirror assembly and facing away from the driver of the vehicle when the mirror assembly is installed in the vehicle), such as via adhesive or an attachment or backing plate or the like. The circuit board may comprise a generally flat, rectangular element or substrate with conductive traces and circuitry disposed thereon. When the mirror head and reflective element are arranged so that the reflective surface (the flat rear surface) of the reflective element is generally vertical, the circuit board is also generally vertically oriented. Where a compass sensor chip (which may include a pair of orthogonally oriented sensing elements arranged in a common plane) is disposed on and along the substrate or circuit board (PCB), the chip itself (and hence the sensing elements disposed therein) may be placed on the PCB in any orientation chosen by the PCB manufacturer. Thus, the compass sensor chip may be oriented such that the principal axis of one sensor is generally horizontal and toward a side of the vehicle, while the principal axis of the other sensor may be generally vertically oriented when the PCB is attached to a reflective element and the reflective element is generally vertically oriented. Thus, the actual placement of the compass chip itself thus may largely or substantially take care of or account for the rotational orientation of the mirror head.

Because it is desired to provide sensing in the x-y directions (or in a horizontal plane), the compass sensor is prefer-

ably disposed on a compass sensor mount or board that extends at an angle from the circuit board and/or rear surface of the reflective element so that the compass sensor elements are generally horizontal when the mirror assembly is installed in the vehicle at its nominal (such as about 20 degree sideward and 9 degree downward) orientation. Preferably, the compass sensor mount is mounted to the circuit board such that the compass sensor mount is oriented at about a 9 degree downward angle from being perpendicular or normal to the circuit board, such that the compass sensor mount or chip is substantially horizontal relative to the floor of the vehicle and thus the ground when the mirror head and reflective element are oriented at the typical or nominal orientation with about a 9 degree downward tilt toward the typical driver's head location. Likewise, the compass sensor is preferably mounted to the compass sensor mount at an angle so that the principal axes of the compass sensing elements are at a desired respective angle relative to the reflective element. For example, a first one of the sensing elements may be at an angle of about 20 degrees toward the driver side of the mirror assembly relative to the longitudinal axis of the vehicle, while a second sensing element may be generally orthogonal to the first sensing element and along the plane of the compass sensor mount. Thus, when the mirror head and reflective element are oriented at the typical or nominal orientation with about a 9 degree downward tilt and about a 20 degree sideward rotation toward the typical driver's head location, the sensing elements are oriented along a generally horizontal plane and are oriented such that the principal axis of the first sensing element is in the direction of travel of the vehicle, while the principal axis of the second sensing element is normal to the first principal axis and directed toward the side of the vehicle. The compass sensor mount may be mounted to the printed circuit board and/or the reflective element via a generally wedge-shaped mounting element or offset element (or via other mounting means) or the compass sensor itself may be attached to or mounted to the printed circuit board at the desired angle, such as via other mounting attachment means, to provide the desired orientation of the compass sensor relative to the reflective element. It is further envisioned that the tilt/rotation offset element may be otherwise formed (or the compass sensor may be otherwise mounted to the circuit board) to provide other offset angles depending on the particular application of the mirror assembly and the nominal orientation of the reflective element that directs the reflective element generally toward the location of a typical driver to provide the typical driver with the appropriate or desired field of view rearward and through the rear window of the vehicle.

Thus, by using the tilt/rotation offset element of the present invention, typically a plastic molding that, for example, attaches to the rear of the reflective element, an angled shelf or ledge is created upon which rests the compass sensor itself and/or its printed circuit board (PCB). Thus, when the interior rearview mirror assembly is installed in a vehicle, such as at the assembly plant (and adjusted at a generally nominal position for viewing by a driver, such that the algorithm can take over and generally or substantially calibrate the compass system as the vehicle is moved through the vehicle assembly plant), and/or is used by the average or typical driver, the tilt/rotation offset element compensates for the nominal 20 degree sideward rotation/9 degree downward tilt, such that the magneto-responsive sensing elements are oriented in the vehicle in which the mirror assembly is mounted with the principal axis of a first one of the magnetoresponsive sensing elements pointing directly forward through the windshield in the direction of travel of the vehicle, and with the principal axis of a second magnetoresponsive sensing element at 90

degrees relative thereto and pointed sidewardly toward a side of the vehicle, and with both the first and second principal axes/magnetoresponsive sensing elements lying in the same plane, and with that plane being generally horizontal with the floor of the vehicle and thus with the road being traveled. Thus, the tilt/rotation offset element and/or the physical tilt and rotation offset means (that may be tied to or separate from the offset element and/or sensor mount) of the present invention physically ensures that the compass sensor has at least two magnetoresponsive sensing elements oriented generally horizontal to the ground (with one facing forward of the vehicle and one facing orthogonally sideward). Thus, at the nominal (about 20 degree sideward/9 degree downward) mirror orientation or setting, the compass sensor is oriented in a known orientation relative to the Earth's horizontal magnetic field. The mirror adjust detection algorithm or routine of the present invention may reference against this as a base or reference orientation from which mirror/sensor adjustment is estimated and/or accommodated/compensated against.

Optionally, in order to reduce the affect of mirror adjustment on the compass sensor, the compass sensor may be mounted or positioned in close proximity to the mirror ball (the ball (referred to at 13a in FIG. 5) that is pivotally received at the mirror casing or toggle element of the mirror assembly). Optionally, the compass sensor may be fixedly positioned relative to the mirror ball (or may be mounted at the end of the mounting arm and mirror ball) so that there is reduced or little or no movement of the compass sensor during minor adjustments of the reflective element, such as when the reflective element is toggled or flipped between the daytime and nighttime orientations. For example, and as shown in FIG. 6, the compass sensor may be disposed on a circuit board or platform 32' that is attached to a portion of the mirror ball 13a' of the mounting arm 13', such as at a lower portion of the ball (to position the sensors remote from the roof of the vehicle). An electrical connector or wire or lead 38 may connect the compass sensor to the circuitry and display elements at the circuit board 30' at the reflective element 16. As shown in FIG. 5, the mounting arm 13' is part of a single ball mounting arrangement, but may be a mounting arm of a double ball mounting arrangement, such as the type shown in FIGS. 1 and 3, without affecting the scope of the present invention.

Optionally, and as described in U.S. patent application Ser. No. 10/456,599, filed Jun. 6, 2003 by Weller et al. for INTERIOR REARVIEW MIRROR SYSTEM WITH COMPASS, now U.S. Pat. No. 7,004,593, which is hereby incorporated herein by reference, the printed circuit board 30 may be mounted at a physical mount at the reflective element to accommodate the approximate angle of the mirror casing. The physical mount may be a wedge shaped mounting element or bracket or any other means for orienting the compass sensor relative to the reflective element to accommodate for the typical angle of tilt of the mirror head toward a driver of a vehicle. The typical angle or tilt of the mirror head or casing may be calculated or otherwise determined or approximated and the physical mount may then be formed to compensate or cancel the typical angle of the mirror. The desired mounting orientation may vary depending on the particular vehicle in which the compassized mirror assembly is being installed, since the mirror assembly may be mounted at different heights along the windshield or at the headliner of different vehicle models. In lieu of a physical orientation as described above, software compensation, as known in the art, can be used to negate or cancel out the above effects.

Optionally, in applications where illumination sources or lights or any other electrically conducting/powered electrical accessory or the like may be sufficiently close to the compass

sensor such that operation of the lights may impact the compass performance (due to the magnetic field generated by the current going through the lights), the lights may be controlled or modulated via a pulse width modulation (PWM) control, so that the lights are modulated between "on" and "off" settings by the PWM control. The PWM control may be optimized to minimize emissions and to maintain vehicle lighting requirements. The compass algorithm or control or microprocessor may monitor the PWM control and may enter a different operation mode when the lights are being PWM controlled. For example, the compass control may optimize the hardware for throughput and may synchronize the light's PWM "off" time with the data collection by the compass sensors, in order to reduce or minimize the impact of the field generated by the current passing through the wires when the lights are on or energized. Preferably, the lighting requirements may be maintained while allowing sufficient time for the compass system signals to settle after the PWM signal for the light is shut down or off. The preferred or desirable settings may be selected based on a compromise between the emission of the illumination source or sources and the ability to successfully read the compass sensor signals or output at the desired accuracy.

As described above, adjustment of the mirror housing (that includes the mirror reflective element) about its pivot connection to its support (typically a double-ball support arm as described above, although a single-ball support arm can also be used, without affecting the scope of the present invention) to the windshield (or to a header region at the joint of the windshield and the roof of the interior cabin of the vehicle) can cause the compass direction sensing sensor attached to the rear of the mirror reflective element to also move. Thus, the compass control circuitry may detect a change in sensed compass directional signal (for example, about 3 degrees to about 8 degrees or thereabouts) when the mirror is adjusted by a driver of the vehicle. Should the vehicle be heading in a direction that is close to half-way between one octant or another in an eight-octant resolving compass display system, this adjustment by the driver of the mirror housing to set the rearward field of view of the mirror reflective element to suit that driver's needs/preference (typically occurring when the driver starts the journey) may cause the heading displayed to the driver to change from, for example, NW to N, because the adjustment by the driver of the mirror housing has changed the orientation/alignment of the magnetic field detecting elements of the compass sensor (for example, a magnetoresistive sensor or Hall effect sensor) relative to the Earth's magnetic field. Modern automatic automotive compass control systems, such as those described in U.S. Pat. Nos. 4,546,551; 5,699,044; 4,953,305; 5,576,687; 5,632,092; 5,677,851; 5,708,410; 5,737,226; 5,802,727; 5,878,370; 6,087,953; 6,173,508; 6,222,460; and 6,513,252, U.S. patent application Ser. No. 10/352,691, filed Jan. 28, 2003 by Schierbeek et al. for VEHICLE COMPASS COMPENSATION, now U.S. Pat. No. 6,922,902, and European patent application, published Oct. 11, 2000 under Publication No. EP 0 1043566, which are all hereby incorporated herein by reference, comprise processing circuitry that includes compensation methods that correct for such changes in sensed compass heading. Thus, and as indicated in U.S. Pat. No. 6,642,851, which is hereby incorporated herein by reference, such known compensation methods can be used to recalibrate the compass mirror system of the present invention after adjustment of the mirror housing by the driver.

Techniques and methods for compensating for such adjustments, such as suggested in U.S. Pat. No. 6,418,376 (the entire disclosure of which is hereby incorporated herein by

15

reference), may be used in conjunction with the present invention. Such methods use a position sensor (such as a tilt sensor) that determines displacement of the mirror housing with respect to a generally horizontal plane. For example, the compass system of the present invention may incorporate a tilt sensor or position sensor or rotation sensor or sensing means or element (such as a tilt sensor, a clinometer or a protractor or the like) that is operable to detect the position or orientation or movement of the mirror and compass sensors relative to a generally horizontal plane and/or a generally vertical plane. For example, the compass system may incorporate an electronic tilt sensor or clinometer, such as the types commercially available from various sources, such as, for example, from Schaevitz® Sensors of Hampton, Va., such as an AccuStar® electronic clinometer or the like, and which may have a resolution of about 0.001 degrees and a range of about 60 degrees or thereabouts, and that may provide an analog, ratiometric, digital pulse width, or serial output. Optionally, for example, the compass system may incorporate an electrolytic tilt sensor, which includes electrically conductive fluid that remains substantially level as the sensor body is tilted, whereby the conductivity between a pair of electrodes within the sensor body is proportional to the length or amount of the electrode immersed in the conductive fluid, such that the degree of tilt may be determined. Such electrolytic tilt sensors are commercially available from various sources and may provide accurate pitch and roll measurements and enhanced repeatability, stability, and accuracy when operating at low frequencies. For example, a dual-axis, or 5-pin, sensor may be packaged in a cylindrical vial that stands between about ½ inch to about 1 inch high, and that provides an operating range of tilt from about ±10 degrees to about ±75 degrees. Optionally, the compass system may incorporate an AMR (anisotropic magnetoresistive) magnetic field sensor or the like, which may provide a tilt detection/determination. Other tilt sensors, clinometers, protractors, electrolytic sensors and/or the like may be implemented with the compass system, without affecting the scope of the present invention.

Optionally, the mirror ball and/or mirror socket may include a transducer/sensor that may determine the orientation of the mirror ball relative to the mirror socket. As the ball rotates in the socket (such as due to adjustment of the mirror head/reflective element by the driver), the orientation of the ball relative to the socket is detected and transmitted or communicated to the control/microprocessor of the compass system. The compass system may then determine the angular adjustment and may adjust the sensor processing and/or compensate for the angular change in response to the detected angular change in the position/orientation of the mirror head relative to the ball of the mounting arm.

The control or circuitry or microprocessor may adjust the degree of compensation of the compass sensor output in response to the output or outputs of the position sensor/sensors. Optionally, other techniques, such as the techniques and methods described in U.S. Pat. Nos. 6,140,933 and 6,023,229, which are hereby incorporated herein by reference, may also or otherwise be implemented.

Optionally, a magnetic field emitter or radiator or generator may be placed in a known fixed location within the vehicle interior cabin (for example, the magnetic field emitter may be placed as part of the mirror foot or mount or base that fixedly attaches to the mirror mounting button or may be otherwise fixedly positioned relative to the vehicle). The magnetic field emitter may optionally be operated to emit a magnetic field in a pulsed and/or coded magnetic field signature. The magnetic field signature/signal emitted by the fixed magnetic field,

16

emitter or source will be picked up by the x-y orthogonally oriented magnetoresponsive sensing elements of the compass sensor (that are positioned within the movable mirror head and that move with the mirror head as it is pivoted about its single or double ball joint support), and thus that move relative to the fixed magnetic field emitter. Because the physical location of the fixed magnetic field emitter is known, the emitter can function as a homing beacon for the movable head/sensing elements, and thus a triangulation algorithm or the like can be used to determine the particular orientation of the sensing elements and any deviation from a known orientation. The compass sensor thus may detect the emitted magnetic field (such as when the emitter is pulsed) and the control or circuitry or microprocessor may process the compass sensor output (such as the output signal that corresponds to when the emitter is pulsed) to discern or distinguish the pulsed magnetic field or signature magnetic field as emitted by the fixed magnetic field emitter to determine the orientation of the mirror head and compass sensor relative to the fixed magnetic field emitter, and thus to determine the degree of adjustment of the mirror head or reflective element relative to the mounting base or known initial orientation or the like. The control may then adjust or alter the directional heading signal and/or the display output in response to the detection of a change in orientation or position of the mirror head relative to the fixed reference point.

Optionally, an algorithmic technique may be implemented whereby, when an abrupt change in detected heading is detected that is characteristic of an adjustment of the mirror housing by the driver of the vehicle, the automatic compass circuitry changes its calibration status from its ongoing state (that compensates for such heading changes over a prolonged period, and one that typically may span an ignition cycle of the vehicle or several vehicle ignition cycles) to a more aggressive, faster calibration stage (such as a Cal-1 or Cal-2 calibration mode as described in U.S. Pat. No. 6,513,252 and U.S. patent application Ser. No. 10/352,691, filed Jan. 28, 2003 by Schierbeek et al. for VEHICLE COMPASS COMPENSATION, now U.S. Pat. No. 6,922,902, which are hereby incorporated herein by reference) that more rapidly, and preferably within that same ignition cycle, recalibrates the compass system and so compensates for the driver's adjustment of the mirror housing/casing and for the concomitant movement of the compass sensor housed therein.

Thus, for example, when a change in compass heading is detected that is indicative of and characteristic of an adjustment of the mirror housing by the driver, such as to adjust the mirror to provide a desired rearward field of view (such adjustment causes an abnormal change of the compass output that is different, such as by magnitude and/or rate of change, than what would occur during normal driving), then the calibration changes to a faster or rapid or more aggressive compensation/calibration algorithm/method. Such mirror adjustments are typically within the range of plus or minus about 2 to 4 degrees upward or downward from the nominal downward angle (of about 9 degrees downward) of the mirror head/reflective element, and plus or minus about 3 to 5 degrees to either side from the nominal sideward angle (of about 20 degrees toward the driver side) of the mirror head/reflective element. Such mirror adjustments, which typically occur rapidly, such as within less than about one to two seconds or thereabouts, create their own known and predictable signature or pattern and thus may be detected and discerned by the compass system. Thus, and referring to U.S. Pat. No. 6,513,252 and U.S. patent application Ser. No. 10/352,691, filed Jan. 28, 2003 by Schierbeek et al. for VEHICLE COMPASS COMPENSATION, now U.S. Pat.

No. 6,922,902, and/or Ser. No. 10/456,599, filed Jun. 6, 2003 by Weller et al. for INTERIOR REARVIEW MIRROR SYSTEM WITH COMPASS, now U.S. Pat. No. 7,004,593, which are hereby incorporated herein by reference, upon detection of a change in compass heading that is indicative of and characteristic of an adjustment of the mirror housing by the driver, the calibration of the compass system would reinitiate back from Cal-3 (or Cal-2) to the beginning of Cal-1. Note that a mechanical element such as a mechanical movement detector can be used to detect adjustment by the driver of the mirror housing, and the recalibration can be initiated in response to a signal output of such a mechanical element.

Desirably, if a mirror adjustment is detected that is beyond the normal range or zone of adjustment of the mirror (such as may occur if the passenger angles the mirror toward the passenger side to borrow the mirror or the mirror is otherwise rotated away from the driver, or such as may occur if the mirror is inadvertently hit or moved to a severely adjusted condition such that no reasonable driver would reasonably view rearwardly through the rear window with the mirror so adjusted), the compass system may detect and discern such egregious or non-normal movement/adjustment and may suspend the calibration activities because such movement/adjustment is an abnormal and typically temporary condition. The compass system may return to its normal and/or calibration mode of operation when the mirror head/reflective element is returned to within the normal range of angular adjustment/position/orientation, such as within a predetermined degree upward/downward and sideward of the nominal position/orientation.

For example, the compass compensation or calibration process may provide for initialization of a rapid or aggressive calibration stage in response to movement of the mirror housing by the driver grasping and moving the mirror head/reflective element to adjust to his or her preferred field of view rearward through the rear window of the vehicle. The compass circuitry may be operable to detect and discern or distinguish a change in the sensed heading which is characteristic of an adjustment of the mirror housing by a driver of the vehicle. The compass circuitry then may respond by reinitializing the compass calibration to the rapid or aggressive calibration stage or mode. The compass circuitry then may compensate for the movement of the compass sensor caused by the adjustment of the mirror housing via a microprocessor-based algorithm software. After completion of the rapid calibration stage, such as after the compass sensor is re-calibrated or after a predetermined amount of time following the onset of the rapid or aggressive calibration stage, the compass circuitry may return to its normal operation.

Optionally, the compass circuitry/software can set or return to the beginning of the aggressive calibration stage (such as to the beginning of Cal-1 as described above) each time the mirror compass circuitry is initially powered, such as by a fresh ignition cycle of the vehicle. Thus, for example, should a driver or occupant of the vehicle adjust the interior rearview mirror orientation during the immediately previous ignition cycle, and thus potentially disturb the established proper compass calibration, then an aggressive and rapid recalibration may automatically occur at the start of the following or next ignition cycle (and thus any potential calibration misalignment may only be temporarily experienced by the driver). Optionally, such an aggressive recalibration may occur in response to actuation of a key fob or remote keyless entry device or remote starter device or the like.

Optionally, the degree of aggression of the rapid calibration stage may be effected by the time elapsed between the ignition activation (or actuation of the key fob or remote

keyless entry device or the like) and the perceived or detected adjustment of the mirror. For example, if the circuitry detects an abrupt adjustment of the sensor orientation within a threshold time after the ignition is activated, then the control may determine that the change in orientation is due to a mirror adjustment (such as may occur when the driver first enters the vehicle and before or soon after shifting into drive or reverse) and thus may enter the rapid and aggressive calibration mode. Optionally, the microprocessor or control may include a first start protocol that causes the compass system to enter the aggressive calibration mode in response to the first ever startup of the vehicle ignition, such as typically occurs at the vehicle assembly plant.

Optionally, the compass system may acquire directional heading data at the activation of the ignition (or activation of a key fob or the like) and, if an adjustment of the mirror head is detected soon after such activation, the compass system may acquire heading data with the sensors at the new orientation. Because the initial heading data sampled after the ignition cycle may be correct data or may be indicative of the vehicle heading, the compass system may compensate or adjust the new data to account for the change in orientation of the compass sensor from the initial and adjusted position. The compass system thus may algorithmically adjust the compass heading or sensor processing to account for the perceived movement or adjustment of the mirror head without entering the aggressive calibration mode.

Optionally, the degree of aggression or entry into the rapid aggressive calibration mode may be affected by the speed of the vehicle when the change in orientation of the compass sensors is detected. For example, if an abrupt change in the orientation of the sensors is detected when the vehicle is stopped or moving at or below a threshold speed (such as at or below about 10 mph or thereabouts), the control may determine that the abrupt change may be due to an adjustment of the mirror head or reflective element, and thus may enter the rapid and aggressive calibration mode. Alternately, if the vehicle speed is detected (such as via a wheel speed sensor or the like) to be above a threshold speed (such as at or above about 60 mph or thereabouts), any change in the sensed direction may be determined to be a change in vehicle direction, since it is not likely that a driver would typically adjust the mirror position while driving at highway speeds.

Thus, when a mirror adjustment is detected that is within the expected range and/or time so as to be indicative of an adjustment of the mirror head/reflective element by the driver of the vehicle to adjust his or her field of view rearward through the rear window of the vehicle, the compass system of the present invention may enter the aggressive calibration mode and begin looking for cardinal directional headings (such as North, South, East or West), such as three or more of the cardinal directional points. The compass system may distinguish between deviations or signatures or patterns that are indicative of anomalies and signatures or patterns that are indicative of normal mirror adjustments by the driver and may enter the calibration mode when a mirror adjustment is detected.

The compass system may remain in the aggressive calibration mode for an aggressive calibration period. The aggressive calibration period may continue until, for example, the three cardinal points or more or less are detected so that the compass system is again considered recalibrated. Optionally, and desirably, the aggressive calibration period may terminate even if the compass system has not yet sensed three or more cardinal points, such as after a predetermined or threshold period of time has elapsed since detection of the adjustment, or after the ignition cycle is terminated or the ignition is

turned off, and before detection of the third cardinal point, so that the compass system does not remain in the aggressive calibration mode for an excessive period of time. Because it is possible that the compass system may pick up an anomaly during the aggressive calibration mode (such as, for example, if the compass system detects the true North and West cardinal points, but detects an anomaly and erroneously considers the anomaly to be the East cardinal point), and thus may use the false signal and result in a premature exit of the calibration mode and an erroneous directional heading indication, it is desirable that the compass system return to the aggressive calibration mode at the onset of each ignition cycle, and/or the next ignition cycle following the detection of the mirror adjustment and aggressive calibration mode. Desirably, the compass system may initiate the aggressive calibration mode at the onset of each ignition cycle, and the compass system may remain in the aggressive calibration mode until three cardinal points (or more or less as desired) are detected or for a predetermined period of time following the ignition activation or when the ignition cycle is terminated.

Optionally, if an abrupt change upward or downward (or pivoting about a generally horizontal axis) is detected, the control circuitry may determine that such an adjustment is indicative of toggling or flipping the mirror reflective element between the daytime and nighttime orientations, and may account for the $4\frac{1}{2}$ degree (or thereabouts, depending on the particular mirror application) change or adjustment via software compensation. Preferably, in such an embodiment, the nominal condition or orientation of the compass sensor is met when the mirror reflective element is at the daytime position or orientation. The determination of the downward or upward movement of the mirror assembly may be made irrespective of the vehicle speed, since such an adjustment (the flipping or toggling of the reflective element between the daytime and nighttime positions) may often occur while the driver is driving the vehicle at higher speeds.

The compass display 22 may provide a display region at the reflective element 16 which includes ports or portions, which may comprise icons, characters or letters or the like representative of only the cardinal directional points, such as, for example, the characters N, S, E, W, formed or etched in the reflective film coating of the reflective element (and forming a transparent window therein), such as via techniques such as disclosed in commonly assigned U.S. Pat. No. 4,882,565, issued to Gallmeyer on Nov. 21, 1989, and such as described in Ser. No. 10/456,599, filed Jun. 6, 2003 by Weller et al. for INTERIOR REARVIEW MIRROR SYSTEM WITH COMPASS, now U.S. Pat. No. 7,004,593. Optionally, however, reflective element may comprise a transfective or display on demand (DOD) reflective element, and the compass display may be a display on demand (DOD) type of display, such as disclosed in commonly assigned U.S. Pat. Nos. 6,690,268; 5,668,663 and 5,724,187, and U.S. patent application Ser. No. 10/054,633, filed Jan. 22, 2002 by Lynam et al. for VEHICULAR LIGHTING SYSTEM, now U.S. Pat. No. 7,195,381, the entire disclosures of which are hereby incorporated by reference herein, without affecting the scope of the present invention.

The display may include a plurality of illumination sources, such as light emitting diodes and such as blue light emitting diodes, such as an OSRAM LBT673-M2N2-35 light emitting diode or the like, which are operable to illuminate one or more ports or regions or appropriate characters or letters (or through the transfective DOD reflective element) to indicate the direction in which the vehicle is driving, such as described in Ser. No. 10/456,599, filed Jun. 6, 2003 by Weller et al. for INTERIOR REARVIEW MIRROR SYS-

TEM WITH COMPASS, now U.S. Pat. No. 7,004,593. The display ports or characters of the display may include only the four cardinal directional points (such as, for example, the characters N, S, E, W) formed or etched in the reflective film coating of the reflective element (and forming a transparent window therein), or may include eight directional points, such as the four cardinal directional points and the four intercardinal points (such as, for example, the characters N, NE, E, SE, S, SW, W, NW), without affecting the scope of the present invention.

The reflective element 16 may also include a port or aperture or hole in the center area or region of the display area (or, as discussed above, may comprise a transfective or DOD reflective element) to accommodate a photo detector or sensor (not shown), such as a photo transistor, a photo resistor, a photo diode or the like, which may be operable to sense the ambient light levels surrounding the mirror assembly or the light from headlights of vehicles rearward of the subject vehicle. The photosensor may be positioned or mounted on the printed circuit board and may be positioned, aligned and directed to receive illumination through the aperture or hole in the reflective element coating at the display region or elsewhere on the reflective element or the casing (such as through an opening formed in a wall of the casing immediately adjacent to the location of the photosensor). The photosensor may detect the ambient light levels generally surrounding the mirror assembly to provide for dimming of the output of the display in darkened lighting conditions, such as at nighttime conditions, in order to reduce the intensity of the display to reduce glare and distraction and annoyance to the driver of the vehicle. Optionally, such dimming of the display may be performed in response to an instrument panel dimming system of the vehicle, without affecting the scope of the present invention.

Optionally, the magnetoresponsive compass sensor or circuitry responsive to the Earth's magnetic field may be operable in conjunction with the global positioning system of the vehicle to provide directional heading data to the global positioning system, such as disclosed in U.S. patent application Ser. No. 10/422,378, filed Apr. 24, 2003 by Schofield for IMAGING SYSTEM FOR VEHICLE, now U.S. Pat. No. 6,946,978, and/or Ser. No. 10/456,599, filed Jun. 6, 2003 by Weller et al. for INTERIOR REARVIEW MIRROR SYSTEM WITH COMPASS, now U.S. Pat. No. 7,004,593, which are hereby incorporated herein by reference. The compass sensor circuitry may provide such directional heading data to assist the global positioning system in maintaining tracking of the location of the vehicle, such as between waypoints or the like, when the satellite signal to the global positioning system is interrupted, such as may occur in cities between tall buildings (often referred to as "urban canyons") or the like. Other vehicle movement data may also be provided, such as vehicle speed data or vehicle odometer data or the like, to further assist in determining and tracking the location of the vehicle in situations where the satellite communication to the global positioning system of the vehicle may be temporarily interrupted or compromised. Optionally, an imaging system (such as described in U.S. patent application Ser. No. 10/422,378, filed Apr. 24, 2003 by Schofield for IMAGING SYSTEM FOR VEHICLE, now U.S. Pat. No. 6,946,978, which is hereby incorporated herein by reference) may be used to further assist in determining and tracking the location of the vehicle in situations where the satellite communication to the global positioning system may be temporarily interrupted or compromised.

Optionally, the printed circuit board of the compass or mirror system (such as a printed circuit board of a compass

module or pod or a printed circuit board of the mirror assembly) of the present invention may include another display element along or partially along an edge of the board and may include one or more user-actuable controls or buttons near or adjacent to the display element. The display element may be any type of display, such as a vacuum fluorescent (VF) display, a light emitting diode (LED) display, an electroluminescent (EL) display, a liquid crystal display (LCD), a video screen display or the like, and may be operable to display various information (as discrete characters, icons or the like, or in a multi-pixel manner) to the driver of the vehicle, such as passenger side inflatable restraint (PSIR) information, tire pressure status, and/or the like. The buttons may be for actuating or controlling various accessories or controls or components, associated with the vehicle, such as for a compass calibration setting or zone setting, a telematics actuation, a garage door opener, an electronic toll control (such as disclosed in U.S. Pat. No. 6,690,268, which is hereby incorporated herein by reference), and/or other accessories or systems or functions or the like, or may be for switching the display between various functions or modes, without affecting the scope of the present invention. The mirror casing may include appropriate openings, such that the display element is visible through one opening, while the buttons or controls may partially protrude through other corresponding openings when an appropriate circuit board is installed within the mirror casing.

Optionally, the mirror assembly and/or a mounting base of the mirror mounting assembly may include or incorporate an electrical accessory or element or circuitry that may be electrically connected to a corresponding electrical accessory or element or circuitry within the mirror casing. For example, and with reference to FIG. 7, a mirror assembly 110 may include an essentially all-polymeric or plastic mounting assembly 112 having a mounting base 124 that houses or contains an electrical element or circuitry or sensor 132, such as a compass sensor, such as a magneto-responsive sensor, such as a magneto-resistive sensor, a magneto-capacitive sensor, a magneto-inductive sensor, a flux-gate sensor or a Hall-effect sensor or the like. The sensor 132 may be positioned at and within the molded base portion 126a so that the sensor is substantially fixedly positioned within the vehicle when the mounting base is attached to the mounting button or structure of the vehicle, such as described in U.S. patent application Ser. No. 11/226,628, filed Sep. 14, 2005, which is hereby incorporated herein by reference. The sensor 132 may include a lead or wire or wires 134 with a connector 134a, such as a multi-pin plug or socket or the like, at an end thereof for connecting to a corresponding connector or plug or socket 130b of electrical conductors 130 of support arm 122. The support arm 122 and electrical conductors 128, connectors 130a, 130b, mirror housing or casing 118 and socket 120 of mirror assembly 110 may utilize aspects of the mirror assemblies described in U.S. patent application Ser. No. 11/226,628, filed Sep. 14, 2005, which are hereby incorporated herein by reference.

Mounting base 124 may be molded or formed to define the base portion 126a and a socket portion 124a for receiving ball member 122b of support arm 122. The base portion 126a may be molded over and at least partially around a metallic insert 126b. Base portion 126a may be molded or formed with a cavity 126c and/or passageway for receiving the sensor or wire, or may be overmolded over and at least partially around the sensor and/or wire. The wire 134 comprises a flying lead or flexible lead that extends from the base portion 126a to the connector or terminals at the support arm 122, and includes sufficient slack or flexibility to accommodate pivotal move-

ment or articulation of the support arm relative to the socket 124a of mounting base 124. The other connector 130a (at ball member 122a received in socket 120 (which may be formed at the casing or at a toggle member or attachment or back plate of the mirror)) may connect to a corresponding connector at a circuit board or electrical element or the like at the mirror casing, such as to circuitry on a circuit board at the reflective element or the like. The electrical element at or in the mirror casing may include controls or display circuitry and elements that are associated with or incorporated in a compass system and/or display system of the mirror assembly.

The accessory or sensor (or other electrical component or circuitry) thus may be positioned or located at or within the plastic molded mounting base of the mirror assembly. The accessory thus is positioned generally along the longitudinal axis of the mounting arm, and generally between the ball member 122b and the mounting base/mounting button at the windshield when the mirror assembly is installed in a vehicle, and not substantially above or below the mounting base (such as in a pod or gondola or module located above or below the mirror assembly) such as is typically done in known mirror assemblies. By positioning the accessory generally along the longitudinal axis of the support arm or generally along the z-axis (the axis along the vehicle and normal to the cross car or x-axis and the vertical or y-axis), the accessory is located generally between the windshield and the mirror casing and reflective element when the mirror assembly is installed in the vehicle, and does not extend substantially above or below or to either side of the mirror when the mirror assembly is installed in the vehicle. The mounting base thus may house or contain the accessory in a location that does not interfere with the forward field of view of the driver of the vehicle. The mirror assembly of the present invention thus may provide a fixed sensor with double ball movement or articulation, and with reduced interference with the forward field of view by the driver of the vehicle.

Optionally, the electrical accessory or circuitry housed or contained within the mounting base may comprise a compass sensor that is part of a compass system and/or display of the mirror assembly and/or vehicle. Note that the magneto-responsive sensor used with the mirror assembly may comprise a magneto-responsive sensor, such as a magneto-resistive sensor such as the types disclosed in U.S. Pat. Nos. 5,255,442; 5,632,092; 5,802,727; 6,173,501; 6,427,349; and 6,513,252 (which are hereby incorporated herein by reference), or a magneto-inductive sensor, such as described in U.S. Pat. No. 5,878,370 (which is hereby incorporated herein by reference), or a magneto-impedance sensor, such as the types described in PCT Publication No. WO 2004/076971 A2, published Sep. 10, 2004 (which is hereby incorporated herein by reference), or a Hall-effect sensor, such as the types described in U.S. Pat. Nos. 6,278,271; 5,942,895 and 6,184,679 (which are hereby incorporated herein by reference). The sensor circuitry and/or the circuitry in the mirror housing and associated with the sensor may include processing circuitry. For example, a printed circuit board may include processing circuitry which may include compensation methods such as those described in U.S. Pat. Nos. 4,546,551; 5,699,044; 4,953,305; 5,576,687; 5,632,092; 5,677,851; 5,708,410; 5,737,226; 5,802,727; 5,878,370; 6,087,953; 6,173,508; 6,222,460; and 6,642,851, which are all hereby incorporated herein by reference. The compass sensor may be incorporated in or associated with a compass system and/or display system for displaying a directional heading of the vehicle to the driver, such as a compass system of the types described in U.S. Pat. Nos. 5,924,212; 4,862,594; 4,937,945; 5,131,154; 5,255,442; and/or 5,632,092, and/or U.S. patent application

Ser. No. 10/456,599, filed Jun. 6, 2003 by Weller et al. for INTERIOR REARVIEW MIRROR SYSTEM WITH COMPASS, now U.S. Pat. No. 7,004,593; and/or Ser. No. 11/029,695, filed Jan. 5, 2005 by Lindahl et al. for MIRROR ASSEMBLY, now U.S. Pat. No. 7,253,723, and/or PCT Application No. PCT/US2004/015424, filed May 18, 2004 by Donnelly Corp. et al. for MIRROR ASSEMBLY FOR VEHICLE, and published on Dec. 2, 2004, as International Publication No. WO 2004/103772, and/or U.S. provisional application Ser. No. 60/636,931, filed Dec. 17, 2004, which are all hereby incorporated herein by reference.

Optionally, the sensor may comprise a two-axis sensor (comprising two magneto-responsive sensor elements disposed at a fixed angle relative to each other, such as, preferably, orthogonally to each other, and disposed in the cavity 126c generally parallel to the floor plane of the vehicle so as to be sensitive to the horizontal component of the Earth's magnetic field), or the sensor may comprise a three-axis sensor (comprising two magneto-responsive sensor elements disposed orthogonally to each other and disposed in the cavity, and a third magneto-responsive sensor element at a right angle (approximately ninety degrees) to the two sensor elements and disposed in the cavity, so that the three-axis sensor is sensitive to the horizontal component and to the vertical component of the Earth's magnetic field), without affecting the scope of the present invention. The sensor may be arranged at a desired angle to provide enhanced sensing in the horizontal directions when the mirror assembly is installed in the vehicle. For example, aspects of constructions such as are disclosed in U.S. Pat. Nos. 6,140,933 and 6,928,366, which are hereby incorporated herein by reference, may be utilized.

Optionally, an integrated automotive "compass-on-a-chip" may be disposed in the cavity of the mounting base and may comprise at least two magneto-responsive sensor elements (preferably Hall effect sensors established on the semiconductor substrate, preferably a silicon substrate, in the same VLSI chip/circuitry manufacturing process, using chip manufacturing processing means as known in the ASIC art), associated A/D and D/A converters, associated microprocessor(s) and memory, associated signal processing and filtering, associated display driver and associated LIN/CAN BUS interface and the like, all (or a sub-set thereof) created or disposed onto a semiconductor substrate, such as a silicon substrate (such as using CMOS technology), and constituting an ASIC chip, which is small (preferably less than approximately a two square centimeter area, more preferably less than approximately a 1.5 square centimeter area, and most preferably less than approximately a one square centimeter area or thereabouts) and readily packagable into the cavity. Thus, power (such as 12 volts or thereabouts, such as from the vehicle power source or the like) may be supplied to the ASIC chip and the ASIC chip may include all or substantially all of the circuitry for operation when the power source is connected to the ASIC chip.

Optionally, and preferably, such a compass-on-a-chip ASIC may also include the hardware and software required to receive an output from a temperature sensor (such as a thermocouple or thermostat that is located external the vehicle cabin in order to sense and monitor the temperature external to the vehicle) and to convert this signal to a reading in degrees Fahrenheit or Celsius, and to provide this reading via an on-chip temperature display driver and/or via a BUS protocol or via an on-chip wireless transmitter or the like to a digital or other type of temperature display so that the driver and/or occupants of the vehicle can view the temperature being measured (such as the temperature external the vehicle and/or the temperature within the vehicle cabin). Thus, for

example, a monolithic compass/temp-on-a-chip ASIC may be disposed in the likes of a mirror mount or within the mirror head/housing of an interior rearview mirror assembly, and it may provide both the external temperature readout and a compass direction heading readout to an information display at the mirror head/housing (or elsewhere in the vehicle, such as the instrument panel/cluster or at an overhead console or accessory module or the like). Optionally, such a chip or circuit board or circuitry may also or otherwise comprise EC driver circuitry for controlling/driving an electro-optic or electrochromic reflective element or cell, such as by utilizing aspects of the EC driver-on-a-chip such as described in U.S. patent application Ser. No. 11/201,661, filed Aug. 11, 2005 by DeWard et al. for ACCESSORY MODULE FOR VEHICLE, now U.S. Pat. No. 7,480,149, which is hereby incorporated herein by reference.

Optionally, the compass ASIC chip and/or compass sensor may be disposed at or in an exterior rearview mirror assembly of the vehicle (which typically utilizes a plastic housing). Such a location may locate the compass chip and compass sensor outside of the magnetic anomalies of the vehicle and at a location where the compass sensor may be less susceptible to or less effected by the windshield wipers of the vehicle or other accessories or metal of the vehicle. Optionally, and regardless of whether the compass chip is located behind the mirror reflector element or at the mirror mount or at an exterior mirror assembly of the vehicle or elsewhere in the vehicle, the display associated with the compass chip may be located at the reflector element or elsewhere in the vehicle, such as at the mirror mount or at an accessory module or windshield electronics module or console or the like of the vehicle.

Optionally, the printed circuit board, or the mirror assembly (or the compass module or an accessory module associated with the mirror assembly), may include other accessories, such as an image sensor (such as a video camera, such as a CMOS imaging array sensor, a CCD sensor or the like, such as the types of imaging sensors or cameras disclosed in commonly assigned, U.S. Pat. Nos. 5,550,677; 6,097,023 and 5,796,094, and/or PCT Application No. PCT/US2003/036177, filed Nov. 14, 2003 by Donnelly Corp. for IMAGING SYSTEM FOR VEHICLE, which are hereby incorporated herein by reference), a temperature sensor (such as a contact temperature sensor for measuring the temperature at or of the windshield), an antenna, or any other sensor or device. For example, the mirror assembly may include a forward facing video image sensor or system, which may include or may be associated with an intelligent rain sensor (such as the types disclosed in commonly assigned U.S. Pat. Nos. 6,320,176; 6,353,392 and 6,313,454, which are hereby incorporated herein by reference), an image or vision system (including an imaging sensor, such as a video camera, such as a CMOS imaging array sensor, a CCD sensor or the like, such as the types disclosed in commonly assigned, U.S. Pat. Nos. 5,550,677; 6,097,023 and 5,796,094, and U.S. patent application Ser. No. 10/422,378, filed Apr. 24, 2003 by Schofield for IMAGING SYSTEM FOR VEHICLE, now U.S. Pat. No. 6,946,978, which are hereby incorporated herein by reference), such as an imaging or object detection system or back up aid of the types described in U.S. Pat. Nos. 6,757,109; 6,717,610; 6,590,719; 6,201,642; 5,929,786; and/or 5,786,772, and/or U.S. patent application Ser. No. 10/427,051, filed Apr. 30, 2003 by Pawlicki et al. for OBJECT DETECTION SYSTEM FOR VEHICLE, now U.S. Pat. No. 7,038,577; and/or Ser. No. 11/239,980, filed Sep. 30, 2005 by Camilleri et al. for VISION SYSTEM FOR VEHICLE, and/or U.S. provisional applications, Ser. No. 60/628,709, filed Nov. 17,

2004 by Camilleri et al. for IMAGING AND DISPLAY SYSTEM FOR VEHICLE; Ser. No. 60/614,644, filed Sep. 30, 2004; and/or Ser. No. 60/618,686, filed Oct. 14, 2004 by Laubinger for VEHICLE IMAGING SYSTEM, which are hereby incorporated herein by reference, or an intelligent headlamp controller (such as the types described in U.S. Pat. Nos. 5,796,094; 5,715,093; and/or 6,824,281, and/or in U.S. patent application Ser. No. 10/958,087, filed Oct. 4, 2004 by Schofield et al. for VEHICLE ACCESSORY MODULE, now U.S. Pat. No. 7,188,963, and/or U.S. patent application Ser. No. 11/105,757, filed Apr. 14, 2005, now U.S. Pat. No. 7,526,103; and U.S. provisional applications, Ser. No. 60/607,963, filed Sep. 8, 2004 by Schofield for IMAGING SYSTEM FOR VEHICLE; and Ser. No. 60/562,480, filed Apr. 15, 2004 by Schofield for IMAGING SYSTEM FOR VEHICLE, which are hereby incorporated herein by reference), or an intelligent lane departure warning system (such as the types described in U.S. patent application Ser. No. 10/209,173, filed Jul. 31, 2001 by Schofield for AUTOMOTIVE LANE CHANGE AID, now U.S. Pat. No. 6,882,287; and/or Ser. No. 10/427,051, filed Apr. 30, 2003 by Pawlicki et al. for OBJECT DETECTION SYSTEM FOR VEHICLE, now U.S. Pat. No. 7,038,577, which are hereby incorporated herein by reference), or indicator/display for a blind spot indicator or object detection system, such as the types described in U.S. provisional application Ser. No. 60/696,953, filed Jul. 6, 2005; and U.S. patent application Ser. No. 11/226,628, filed Sep. 14, 2005, which are hereby incorporated herein by reference, and/or the like. In applications where the mirror assembly includes or is associated with an automatic headlamp control system, it is envisioned that the display of the mirror system may include or provide a high beam/low beam indicator (such as an icon or indicia indicative of the high beams being activated, such as a blue headlamp indicia or the like) to indicate the status of the high beams of the vehicle to the driver or occupant of the vehicle.

Optionally, the mirror assembly or compass or accessory or electronic module of the present invention may include one or more displays, such as a text display, an icon display, a display on demand (DOD) type display (such as may be implemented with a transfective reflective element, such as described in U.S. Pat. Nos. 5,668,663; 5,724,187; and 6,690,268, the entire disclosures of which are hereby incorporated by reference herein), such as a video or touch screen interface display, or a video display screen, such as the types described in PCT Application No. PCT/US03/40611, filed Dec. 19, 2003 by Donnelly Corp. et al. for ACCESSORY SYSTEM FOR VEHICLE, and/or U.S. patent application Ser. No. 11/284,543, filed Nov. 22, 2005, now U.S. Pat. No. 7,370,983, and/or U.S. provisional applications, Ser. No. 60/630,061, filed Nov. 22, 2004 by Lynam et al. for MIRROR ASSEMBLY WITH VIDEO DISPLAY; and Ser. No. 60/667,048, filed Mar. 31, 2005, which are hereby incorporated herein by reference, or the like, and/or one or more sensors or other accessories, such as a biometric imager, such as for fingerprint authentication or the like, an infrared sensor, such as a zonal temperature sensor, such as suitable for an auto climate control, a forward facing image sensor, such as described above, a rearward facing image sensor (such as for biometric imaging (such as for face recognition, iris recognition or the like), seat height or position detection, drowsiness detection, safety/restraints object detection and position, emergency response image capture system, intrusion detection or the like), an electromagnetic field sensor (such as the type disclosed in commonly assigned U.S. Pat. No. 6,768,420, which is hereby incorporated herein by reference).

Optionally, and for a mirror assembly having a slideout or extendable/retractable display, such as a video slideout display or the like (such as the types described in PCT Application No. PCT/US03/40611, filed Dec. 19, 2003 by Donnelly Corp. et al. for ACCESSORY SYSTEM FOR VEHICLE, and/or U.S. patent application Ser. No. 11/284,543, filed Nov. 22, 2005, now U.S. Pat. No. 7,370,983, and/or U.S. provisional applications, Ser. No. 60/630,061, filed Nov. 22, 2004 by Lynam et al. for MIRROR ASSEMBLY WITH VIDEO DISPLAY; and Ser. No. 60/667,048, filed Mar. 31, 2005, which are hereby incorporated herein by reference), the display may be operable or activatable when in its retracted or partially retracted position so as to provide display information, such as directional heading information or temperature information or other vehicle information or the like, that is viewable through the reflective element when the display is at least partially retracted. As described in the above referenced applications, such a slideout display is extended to display information to the driver of the vehicle and may be retracted when such information is not being displayed. When retracted, the display typically is deactivated and located behind the mirror reflector. In such a retracted or partially retracted position, the display element or screen is positioned at least partially at the rear of the mirror reflector element with the display element or screen facing the rear surface of the mirror reflector element.

It is thus envisioned that the display element (such as a video display element or LCD element or the like) may be activated when it is retracted or at least partially retracted, so that the display information or illumination emitted by the display element may be projected through the transfective mirror reflector element for viewing at the mirror reflector element. For example, and for mirror assemblies having a transfective mirror reflector element, the opaque backing of the reflector element may have a window or aperture or display area formed therethrough so that at least a portion of the display element, when activated in its retracted or partially retracted position, is viewable through the transfective mirror reflector at the display area.

In such an embodiment, it is desirable that there be a close or substantial optical coupling between the front surface of the display element or screen (the surface facing generally toward the driver of the vehicle when the mirror assembly is mounted in the vehicle) and the rear surface of the mirror reflector element (the surface facing generally away from the driver of the vehicle when the mirror assembly is mounted in the vehicle). Preferably, the mirror assembly may include an opaquifying or shading cover or baffle element that covers the display area when the slideout display is extended or at least partially extended and not activated to provide display information at the display area. For example, an opaque shading element may move over the window area at the rear of the mirror reflector element to cover/shade/opaquify the window/display area so that the internal components of the mirror assembly are not viewable through the window/display area when the display element is moved at least partially toward its extended position.

Thus, for example, a video slideout interior rearview mirror assembly can be provided that, when the driver selects reverse gear, a back lit TFT LCD screen may extend at the passenger side to display an image of a scene occurring immediately to the rear of the vehicle (such as captured by a rear mounted camera) so that the driver may view the image during a reversing maneuver to assist in reversing the vehicle. Preferably, such a display may include a graphic overlay or other indicia or the like, such as described in U.S. patent application Ser. No. 11/284,543, filed Nov. 22, 2005, now

U.S. Pat. No. 7,370,983, to assist the driver in making the reversing maneuver. Upon the disengagement of the reverse gear by the driver, the display slides in or retracts to its stowed position. When the driver is driving the vehicle forward along a road, a compass display is viewable to the driver when he or she looks at the mirror. The compass display may be derived from a compass-on-a-chip sensor that is preferably mounted within a mirror mount or alternatively within the mirror casing or elsewhere in the vehicle. The compass display at the mirror reflector or reflective element (such as a transfective electrochromic reflective element or a transfective prismatic reflective element or the like) is provided by the same TFT LCD display screen or display element that is now stowed behind the reflective element and is seen through the transfective reflective element. Thus, the utility and user appreciation of the slideout display is enhanced because, when the vehicle is reversing, the display can slideout or extend to show the reversing scene and, when the display is stowed, such as during normal driving conditions, the same display element is used to provide an information display at the mirror reflector.

The display and/or accessories may be associated with a communication system, a speaker, a telematics module (which may include a GPS module, a wireless communication module, an human/machine interface (HMI), a display, such as an LED display, a dot matrix display, an alpha numeric display, a video display or the like, and/or a microphone, which may be operable for speech or voice recognition, noise reduction or noise cancellation), a humidity sensor, a remote keyless entry sensor, a tire pressure monitoring system (TPMS), an electronic toll collection sensor, an intelligent headlamp control, user interface controls (such as buttons, switches or the like for controlling various accessories of the vehicle, such as a sunroof, a communication system, lamps, security systems, displays or the like) or any other accessories, sensors, lights, indicators, displays or the like which may be suitable for mounting or positioning at or within the interior rearview mirror assembly or accessory module. The interior rearview mirror assembly and/or compass or accessory module may also provide for glare reduction characteristics of the reflective element of the rearview mirror assembly.

Optionally, the mirror assembly of the present invention may include one or more other accessories at or within the mirror casing, such as one or more electrical or electronic devices or accessories, such as antennas, including global positioning system (GPS) or cellular phone antennas, such as disclosed in U.S. Pat. No. 5,971,552, a communication module, such as disclosed in U.S. Pat. No. 5,798,688, transmitters and/or receivers, such as a garage door opener or the like, a digital network, such as described in U.S. Pat. No. 5,798,575, a memory mirror system, such as disclosed in U.S. Pat. No. 5,796,176, a hands-free phone attachment, a video device for internal cabin surveillance and/or video telephone function, such as disclosed in U.S. Pat. Nos. 5,760,962 and/or 5,877,897; and/or PCT Application No. PCT/US03/40611, filed Dec. 19, 2003 by Donnelly Corp. et al. for ACCESSORY SYSTEM FOR VEHICLE, and/or U.S. patent application Ser. No. 11/284,543, filed Nov. 22, 2005, now U.S. Pat. No. 7,370,983, and/or U.S. provisional applications, Ser. No. 60/630,061, filed Nov. 22, 2004 by Lynam et al. for MIRROR ASSEMBLY WITH VIDEO DISPLAY; and Ser. No. 60/667,048, filed Mar. 31, 2005, a remote keyless entry receiver or system or circuitry and/or a universal garage door opening system or circuitry (such as the types disclosed in U.S. Pat. Nos. 6,396,408; 6,362,771; 5,798,688 and 5,479,155, and/or U.S. patent application Ser. No. 10/770,736, filed Feb. 3, 2004 by Baumgardner et al. for GARAGE DOOR OPENING

SYSTEM FOR VEHICLE, now U.S. Pat. No. 7,023,322), a remote keyless entry receiver, lights, such as map reading lights or one or more other lights or illumination sources, such as disclosed in U.S. Pat. Nos. 6,690,268; 5,938,321; 5,813,745; 5,820,245; 5,673,994; 5,649,756; 5,178,448; 5,671,996; 4,646,210; 4,733,336; 4,807,096; 6,042,253; and/or 5,669,698, and/or U.S. patent application, Ser. No. 10/054,633, filed Jan. 22, 2002 by Lynam et al. for VEHICULAR LIGHTING SYSTEM, now U.S. Pat. No. 7,195,381, microphones, such as disclosed in U.S. Pat. Nos. 6,243,003; 6,278,377; and/or 6,420,975; and/or PCT Application No. PCT/US03/30877, filed Oct. 1, 2003, speakers, a tire pressure monitoring system, such as the types disclosed in U.S. Pat. Nos. 6,294,989; 6,445,287; and/or 6,472,979, and/or U.S. patent application Ser. No. 11/232,324, filed Sep. 21, 2005, now U.S. Pat. No. 7,423,522, and U.S. provisional application Ser. No. 60/611,796, filed Sep. 21, 2004 by O'Brien for TIRE PRESSURE ALERT SYSTEM, a navigation system, such as described in U.S. Pat. No. 6,477,464, and U.S. patent application Ser. No. 10/456,599, filed Jun. 6, 2003 by Weller et al. for INTERIOR REARVIEW MIRROR SYSTEM WITH COMPASS, now U.S. Pat. No. 7,004,593; Ser. No. 10/287,178, filed Nov. 4, 2002 by McCarthy et al. for NAVIGATION SYSTEM FOR A VEHICLE, now U.S. Pat. No. 6,678,614; Ser. No. 10/645,762, filed Aug. 20, 2003 by Taylor et al. for VEHICLE NAVIGATION SYSTEM FOR USE WITH A TELEMATICS SYSTEM, now U.S. Pat. No. 7,167,796; and Ser. No. 10/422,378, filed Apr. 24, 2003, now U.S. Pat. No. 6,946,978; and/or PCT Application No. PCT/US03/40611, filed Dec. 19, 2003 by Donnelly Corp. et al. for ACCESSORY SYSTEM FOR VEHICLE, a seat occupancy detector, a vehicle occupancy detector, such as the types described in U.S. Pat. No. 6,768,420 and/or PCT Application No. PCT/US05/42504, filed Nov. 22, 2005 by Donnelly Corp. et al. for OCCUPANT DETECTION SYSTEM FOR VEHICLE; and/or U.S. provisional application Ser. No. 60/630,364, filed Nov. 22, 2004 by Wählström for OCCUPANT DETECTION SYSTEM FOR VEHICLE, a trip computer, an ONSTAR® system and/or the like (with all of the above-referenced patents and patent applications and PCT applications and provisional applications being commonly assigned to Donnelly Corp., and with the disclosures of the referenced patents and patent applications and PCT applications and provisional applications being hereby incorporated herein by reference in their entireties). The accessory or accessories may be positioned at or within the mirror casing and may be included on or integrated in a printed circuit board positioned within the mirror casing, such as along a rear surface of the reflective element or elsewhere within a cavity defined by the casing, without affecting the scope of the present invention.

The interior rearview mirror assembly and/or an associated accessory module may also include user interface controls, such as buttons, switches or the like, displays, indicators, microphones, speakers or the like. Some of these may be provided at or along a display or interface area at or above the mirror. Optionally, the mirror assembly may include a user actuable input or inputs to activate or deactivate or adjust one or more accessories of the mirror assembly or accessory module or console or of the vehicle. The inputs may be positioned at the mirror casing or bezel portion of the mirror assembly where they may be readily accessible by the driver or occupant of the vehicle. The inputs may comprise push buttons or the like or touch sensitive elements or sensors or proximity sensors or the like that may be selectively touched or depressed or approached to activate/deactivate/adjust the accessory or accessories, as discussed below. The inputs may utilize aspects such as those described in PCT Application

No. PCT/US2003/036177, filed Nov. 14, 2003 by Donnelly Corp. for IMAGING SYSTEM FOR VEHICLE and/or PCT Application No. PCT/US04/015424, filed May 18, 2004 by Donnelly Corp. et al. for MIRROR ASSEMBLY FOR VEHICLE, published Dec. 2, 2004 as PCT Publication No. WO 2004/103772 A2, which are hereby incorporated herein by reference, or may utilize aspects of touch sensitive elements of the types described in U.S. Pat. Nos. 5,594,222; 6,001,486; 6,310,611; 6,320,282; and 6,627,918, and U.S. patent application Ser. No. 09/817,874, filed Mar. 26, 2001 by Quist et al. for INTERACTIVE AUTOMOTIVE REARVISION SYSTEM, now U.S. Pat. No. 7,224,324, which are hereby incorporated herein by reference, or may comprise proximity sensors of the types described in U.S. Pat. Publication No. 2002/0044065, published Apr. 18, 2002 by Quist et al. for INTERACTIVE AUTOMOTIVE REARVISION SYSTEM, now U.S. Pat. No. 7,224,324; and/or U.S. patent application Ser. No. 11/284,543, filed Nov. 22, 2005, now U.S. Pat. No. 7,370,983; Ser. No. 10/933,842, filed Sep. 3, 2004, now U.S. Pat. No. 7,249,860; and/or Ser. No. 10/956,749, filed Oct. 1, 2004, now U.S. Pat. No. 7,446,924; and/or PCT Application No. PCT/US03/40611, filed Dec. 19, 2003 by Donnelly Corp. et al. for ACCESSORY SYSTEM FOR VEHICLE, and/or U.S. provisional applications, Ser. No. 60/630,061, filed Nov. 22, 2004 by Lynam et al. for MIRROR ASSEMBLY WITH VIDEO DISPLAY; and Ser. No. 60/667,048, filed Mar. 31, 2005, which are hereby incorporated herein by reference, or may comprise inputs molded within the bezel of the mirror assembly, such as described in U.S. patent application Ser. No. 11/029,695, filed Jan. 5, 2005, now U.S. Pat. No. 7,253,723, and U.S. provisional applications, Ser. No. 60/535,559, filed Jan. 9, 2004 by Lindahl for MIRROR ASSEMBLY; and Ser. No. 60/553,517, filed Mar. 16, 2004 by Lindahl et al. for MIRROR ASSEMBLY, which are hereby incorporated herein by reference, or may comprise membrane type switches, such as described in U.S. patent application Ser. No. 11/140,396, filed May 27, 2005, now U.S. Pat. No. 7,360,932, and U.S. provisional applications, Ser. No. 60/575,904, filed Jun. 1, 2004 by Uken for MIRROR ASSEMBLY FOR VEHICLE; and/or Ser. No. 60/624,320, filed Nov. 2, 2004 by Uken for MIRROR ASSEMBLY FOR VEHICLE, which are hereby incorporated herein by reference, or other types of switches or buttons or inputs, such as, for example, inputs of the types described in U.S. provisional applications, Ser. No. 60/719,482, filed Sep. 22, 2005; and Ser. No. 60/690,401, filed Jun. 14, 2005, which are hereby incorporated herein by reference, and/or the like, without affecting the scope of the present invention.

The accessory or accessories may be positioned at or within the mirror casing and may be included on or integrated in the printed circuit board positioned within the mirror casing, such as along a rear surface of the reflective element or elsewhere within a cavity defined by the casing, without affecting the scope of the present invention. The user actuable inputs described above may be actuable to control and/or adjust the accessories of the mirror assembly/system and/or an overhead console and/or an accessory module/windshield electronics module and/or the vehicle. The connection or link between the controls and the systems or accessories may be provided via vehicle electronic or communication systems and the like, and may be connected via various protocols or nodes, such as Bluetooth™, SCP, UBP, J1850, CAN J2284, Fire Wire 1394, MOST, LIN, FlexRay™, Byte Flight and/or the like, or other vehicle-based or in-vehicle communication links or systems (such as WIFI and/or IRDA) and/or the like, depending on the particular application of the mirror/accessory system and the vehicle.

Optionally, the connections or links may be provided via wireless connectivity or links, such as via a wireless communication network or system, such as described in U.S. patent application Ser. No. 10/456,599, filed Jun. 6, 2003 by Weller et al. for INTERIOR REARVIEW MIRROR SYSTEM WITH COMPASS, now U.S. Pat. No. 7,004,593, which is hereby incorporated herein by reference, without affecting the scope of the present invention.

Optionally, the interior rearview mirror assembly or an associated accessory module or windshield electronics module or console may include a network bus, such as a CAN bus or a LIN bus, such as disclosed in U.S. Pat. No. 6,291,905, which is hereby incorporated herein by reference. The network bus may be operable to communicate with other systems of the vehicle, such as with accessories or elements of an accessory module, such as an accessory module of the type disclosed in commonly assigned U.S. Pat. Nos. 6,824,281; 6,243,003; 6,278,377 and 6,420,975; U.S. patent application Ser. No. 10/054,633, filed Jan. 22, 2002 by Lynam et al. for VEHICULAR LIGHTING SYSTEM, now U.S. Pat. No. 7,195,381; U.S. patent application Ser. No. 10/958,087, filed Oct. 4, 2004 by Schofield et al. for VEHICLE ACCESSORY MODULE, now U.S. Pat. No. 7,188,963; and/or International Publication No. WO 01/64481, published Sep. 7, 2001, which are all hereby incorporated herein by reference.

Optionally, the mirror assembly may comprise an electro-optic or electrochromic mirror assembly and may include an electro-optic or electrochromic reflective element. The electrochromic mirror element of the electrochromic mirror assembly may utilize the principles disclosed in commonly assigned U.S. Pat. Nos. 6,690,268; 5,140,455; 5,151,816; 6,178,034; 6,154,306; 6,002,544; 5,567,360; 5,525,264; 5,610,756; 5,406,414; 5,253,109; 5,076,673; 5,073,012; 5,117,346; 5,724,187; 5,668,663; 5,910,854; 5,142,407 and/or 4,712,879, which are hereby incorporated herein by reference, and/or as disclosed in the following publications: N. R. Lynam, "Electrochromic Automotive Day/Night Mirrors", SAE Technical Paper Series 870636 (1987); N. R. Lynam, "Smart Windows for Automobiles", SAE Technical Paper Series 900419 (1990); N. R. Lynam and A. Agrawal, "Automotive Applications of Chromogenic Materials", Large Area Chromogenics: Materials and Devices for Transmittance Control, C. M. Lampert and C. G. Granquist, EDS., Optical Engineering Press, Wash. (1990), which are hereby incorporated by reference herein; and/or as described in U.S. patent application Ser. No. 10/054,633, filed Jan. 22, 2002 by Lynam et al. for VEHICULAR LIGHTING SYSTEM, now U.S. Pat. No. 7,195,381, which are hereby incorporated herein by reference. The mirror assembly may include one or more other displays, such as the types disclosed in U.S. Pat. Nos. 5,530,240 and/or 6,329,925, which are hereby incorporated herein by reference, and/or display-on-demand transfective type displays, such as the types described in U.S. Pat. Nos. 5,668,663; 5,724,187 and/or 6,690,268, and/or in U.S. patent application Ser. No. 10/054,633, filed Jan. 22, 2002 by Lynam et al. for VEHICULAR LIGHTING SYSTEM, now U.S. Pat. No. 7,195,381; Ser. No. 11/021,065, filed Dec. 23, 2004, now U.S. Pat. No. 7,255,451; Ser. No. 11/226,628, filed Sep. 14, 2005; and/or Ser. No. 10/538,724, filed Jun. 13, 2005; Ser. No. 10/528,269, filed Mar. 17, 2005, now U.S. Pat. No. 7,274,501; and/or Ser. No. 10/533,762, filed May 4, 2005, now U.S. Pat. No. 7,184,190, and/or PCT Application No. PCT/US03/29776, filed Sep. 9, 2003 by Donnelly Corp. et al. for MIRROR REFLECTIVE ELEMENT ASSEMBLY, which are all hereby incorporated herein by reference, or ultra small information displays, such as are disclosed in U.S. patent application Ser. No. 10/225,851, filed Aug. 22, 2002 by Burgner for

VEHICLE INFORMATION DISPLAY, now U.S. Pat. No. 6,847,487, the entire disclosure of which is hereby incorporated by reference herein. The thicknesses and materials of the coatings on the substrates, such as on the third surface of the reflective element assembly, may be selected to provide a desired color or tint to the mirror reflective element, such as a blue colored reflector, such as is known in the art and such as described in U.S. Pat. Nos. 5,910,854 and 6,420,036, and in U.S. patent application Ser. No. 10/528,269, filed Mar. 17, 2005, now U.S. Pat. No. 7,274,501, and in PCT Application No. PCT/US03/29776, filed Sep. 9, 2003 by Donnelly Corp. et al. for MIRROR REFLECTIVE ELEMENT ASSEMBLY, which are all hereby incorporated herein by reference. The coatings and/or encapsulants and the like may be selected to provide the desired appearance and features for the reflective element assembly, such as utilizing the principles described in U.S. patent application Ser. No. 11/021,065, filed Dec. 23, 2004, now U.S. Pat. No. 7,255,451; and U.S. provisional applications, Ser. No. 60/563,342, filed Apr. 19, 2004 by Bareman et al. for METHOD OF MANUFACTURING ELECTRO-OPTIC MIRROR CELL; and/or Ser. No. 60/629,926, filed Nov. 22, 2004 by McCabe et al. for METHOD OF MANUFACTURING ELECTRO-OPTIC MIRROR CELL, which are hereby incorporated herein by reference.

It is further envisioned that the interior rearview mirror assembly may include a transfective one way mirror element, such as disclosed in commonly assigned U.S. patent application Ser. No. 10/054,633, filed Jan. 22, 2002 by Lynam et al. for VEHICULAR LIGHTING SYSTEM, now U.S. Pat. No. 7,195,381, which is hereby incorporated herein by reference. Preferably, the mirror reflective element (behind which a video display screen may be disposed so that the image displayed is visible by viewing through the mirror reflective element) of the interior mirror assembly comprises a transfective mirror reflector such that the mirror reflective element is significantly transmitting to visible light incident from its rear (i.e. the portion furthest from the driver in the vehicle), with at least about 15 percent transmission of light therethrough preferred, at least about 20 percent transmission of light therethrough more preferred and at least about 25 percent transmission of light therethrough most preferred, while simultaneously, the mirror reflective element is substantially reflective to visible light incident from its front (i.e. the position closest to the driver when the interior mirror assembly is mounted in the vehicle), with at least about 60 percent reflectance of light incident thereon preferred, at least about 70 percent reflectance of light incident thereon more preferred and at least about 75 percent reflectance of light incident thereon most preferred. Preferably, a transfective electrochromic reflective mirror element is used (such as is disclosed in U.S. Pat. Nos. 5,668,663; 5,724,187; and 6,690,268, the entire disclosures of which are hereby incorporated by reference herein) that comprises an electrochromic medium sandwiched between two substrates.

Optionally, the mirror assembly and/or prismatic or electrochromic reflective element may include one or more displays, such as for the accessories or circuitry described herein. The displays may be similar to those described above, or may be of types disclosed in U.S. Pat. Nos. 5,530,240 and/or 6,329,925, which are hereby incorporated herein by reference, and/or may be display-on-demand or transfective type displays, such as the types disclosed in U.S. Pat. Nos. 6,690,298; 5,668,663 and/or 5,724,187, and/or in U.S. patent application Ser. No. 10/054,633, filed Jan. 22, 2002, now U.S. Pat. No. 7,195,381; Ser. No. 11/226,628, filed Sep. 14, 2005 by Karner et al.; and/or Ser. No. 10/993,302, filed Nov. 19, 2004, now U.S. Pat. No. 7,338,177; and/or in U.S. provisional

applications, Ser. No. 60/525,952, filed Nov. 26, 2003 by Lynam for MIRROR REFLECTIVE ELEMENT FOR A VEHICLE; Ser. No. 60/717,093, filed Sep. 14, 2005 by Lynam; and/or Ser. No. 60/732,245, filed Nov. 1, 2005 by Weller for INTERIOR REARVIEW MIRROR ASSEMBLY WITH DISPLAY, and/or in PCT Application No. PCT/US03/29776, filed Sep. 19, 2003 by Donnelly Corp. et al. for MIRROR REFLECTIVE ELEMENT ASSEMBLY, which are all hereby incorporated herein by reference. Optionally, a prismatic reflective element may comprise a display on demand or transfective prismatic element (such as described in PCT Application No. PCT/US03/29776, filed Sep. 19, 2003 by Donnelly Corp. et al. for MIRROR REFLECTIVE ELEMENT ASSEMBLY; and/or U.S. patent application Ser. No. 10/993,302, filed Nov. 19, 2004, now U.S. Pat. No. 7,338,177, which are all hereby incorporated herein by reference) so that the displays are viewable through the reflective element, while the display area still functions to substantially reflect light, in order to provide a generally uniform prismatic reflective element even in the areas that have display elements positioned behind the reflective element.

Optionally, the display and any associated user inputs may be associated with various accessories or systems, such as, for example, a tire pressure monitoring system or a passenger air bag status or a garage door opening system or a telematics system or any other accessory or system of the mirror assembly or of the vehicle or of an accessory module or console of the vehicle, such as an accessory module or console of the types described in U.S. Pat. Nos. 6,690,268; 6,672,744; 6,386,742; and 6,124,886, and/or U.S. patent application Ser. No. 10/739,766, filed Dec. 18, 2003 by DeLine et al. for MODULAR REARVIEW MIRROR ASSEMBLY, now U.S. Pat. No. 6,877,888; and/or Ser. No. 10/355,454, filed Jan. 31, 2003 by Schofield et al. for VEHICLE ACCESSORY MODULE, now U.S. Pat. No. 6,824,281, and/or PCT Application No. PCT/US03/03012, filed Jan. 31, 2003 by Donnelly Corporation for VEHICLE ACCESSORY MODULE, and/or PCT Application No. PCT/US03/40611, filed Dec. 19, 2003 by Donnelly Corporation for ACCESSORY SYSTEM FOR VEHICLE, and/or PCT Application No. PCT/US04/15424, filed May 18, 2004 by Donnelly Corporation et al. for MIRROR ASSEMBLY FOR VEHICLE, and published on Dec. 2, 2004, as International Publication No. WO 2004/103772, which are hereby incorporated herein by reference.

Optionally, the mirror system or interior rearview mirror assembly and/or compass system of the present invention may include electrochromic control circuitry for controlling the reflectivity of an electrochromic mirror. The circuitry may include a rearward viewing glare detector or sensor and a forward viewing and/or downward and/or sideward viewing ambient light detector or sensor, such as described in U.S. Pat. No. 4,793,690, which is hereby incorporated herein by reference, or may include a single sensor, such as described in U.S. Pat. No. 5,193,029, which is hereby incorporated herein by reference. The output of the circuitry may control an outside electrochromic mirror as well as the interior rearview electrochromic mirror. It is further envisioned that the circuitry may control an outside electrochromic mirror, while the interior rearview mirror assembly may be a prismatic mirror, without affecting the scope of the present invention.

The network bus of the interior rearview mirror assembly may then be in communication with the reversing system of the vehicle, such that the interior rearview mirror assembly knows when the vehicle is shifted into reverse. The bus may then be operable to disable the electrochromic dimming of the mirror when the vehicle is in reverse, as is desired and known in the art.

Further, automatic dimming circuitry used in the electrochromic mirror assembly and/or in an accessory module may utilize one or more (typically two) photosensors to detect glaring and/or ambient lighting. Optionally, the mirror assembly (such as for an interior or exterior rearview mirror assembly) may include a photo sensor or light sensor (such as the types described in U.S. Pat. Nos. 6,831,268; 6,742,904; 6,737,629; 4,799,768; and 4,793,690, and U.S. patent application Ser. No. 10/456,599, filed Jun. 6, 2003 by Weller et al. for INTERIOR REARVIEW MIRROR SYSTEM WITH COMPASS, now U.S. Pat. No. 7,004,593, which are hereby incorporated herein by reference) at the rear or fourth surface of the reflective element assembly, such that the photo sensor detects light passing through the reflective element assembly. Examples of such configurations are described in U.S. Pat. Nos. 4,793,690; 5,550,677 and 5,193,029, and U.S. patent application Ser. No. 10/456,599, filed Jun. 6, 2003 by Weller et al. for INTERIOR REARVIEW MIRROR SYSTEM WITH COMPASS, now U.S. Pat. No. 7,004,593, which are all hereby incorporated herein by reference. For example, a silicon photosensor, such as a TSL235R Light-to-Frequency converter (available from Texas Advanced Optoelectronic Solutions Inc. of Plano, Tex.), may be used as such a photosensor. Such light-to-frequency converters comprise the combination of a silicon photodiode and a current-to-frequency converter on a single monolithic CMOS integrated circuit.

Optionally, a silicon based optical sensor may provide a non-linear response for the electro-optic or electrochromic reflective element dimming circuitry. Optionally, an infrared (IR) filtering thin film may be deposited on the sensor (or may be disposed in front of the sensor) to filter or attenuate infrared radiation at the photo sensor. Optionally, the sensor may be mounted at the rear of the reflective element assembly and may be mounted at a black plastic surface mount that has a clear window, such that light leakage from non-intended light sources is reduced and such that the environmental properties of the sensor and mounting package are substantially enhanced.

The interior rearview mirror assembly may include the bezel portion and the casing, such as described above, or the mirror assembly may comprise other types of casings or bezel portions or the like, such as described in U.S. Pat. Nos. 6,439,755; 4,826,289; and 6,501,387; and/or PCT Application No. PCT/US2004/015424, filed May 18, 2004 by Donnelly Corp. et al. for MIRROR ASSEMBLY FOR VEHICLE, and published on Dec. 2, 2004, as International Publication No. WO 2004/103772; and/or U.S. patent application Ser. No. 10/933,842, filed Sep. 3, 2004 by Kulas et al. for INTERIOR REARVIEW MIRROR ASSEMBLY, now U.S. Pat. No. 7,249,860; and/or Ser. No. 10/993,302, filed Nov. 19, 2004 by Lynam for MIRROR REFLECTIVE ELEMENT FOR A VEHICLE, now U.S. Pat. No. 7,338,177, which are all hereby incorporated herein by reference, without affecting the scope of the present invention. For example, the mirror assembly may comprise a flush or frameless or bezelless reflective element, such as the types described in PCT Application No. PCT/US2004/015424, filed May 18, 2004 by Donnelly Corp. et al. for MIRROR ASSEMBLY FOR VEHICLE, and published on Dec. 2, 2004, as International Publication No. WO 2004/103772; PCT Application No. PCT/US03/35381, filed Nov. 5, 2003 by Donnelly Corp. et al. for ELECTRO-OPTIC REFLECTIVE ELEMENT ASSEMBLY; and/or in U.S. patent application Ser. No. 11/140,396, filed May 27, 2005, now U.S. Pat. No. 7,360,932; Ser. No. 11/226,628, filed Sep. 14, 2005; Ser. No. 11/021,065, filed Dec. 23, 2004, now U.S. Pat. No. 7,255,451; Ser. No. 10/528,269, filed Mar. 17, 2005, now U.S. Pat. No. 7,274,501; Ser. No. 10/533,762, filed May

4, 2005, now U.S. Pat. No. 7,184,190; and/or Ser. No. 10/538,724, filed Jun. 13, 2005; and/or in U.S. provisional applications, Ser. No. 60/563,342, filed Apr. 19, 2004 by Bareman et al. for METHOD OF MANUFACTURING ELECTRO-OPTIC MIRROR CELL; Ser. No. 60/629,926, filed Nov. 22, 2004 by McCabe et al. for METHOD OF MANUFACTURING ELECTRO-OPTIC MIRROR CELL; Ser. No. 60/624,320, filed Nov. 2, 2004 by Uken for MIRROR ASSEMBLY FOR VEHICLE; Ser. No. 60/681,250, filed May 16, 2005; Ser. No. 60/690,400, filed Jun. 14, 2005; Ser. No. 60/695,149, filed Jun. 29, 2005; and/or Ser. No. 60/730,334, filed Oct. 26, 2005 by Baur for VEHICLE MIRROR ASSEMBLY WITH INDICIA AT REFLECTIVE ELEMENT, which are all hereby incorporated herein by reference.

Therefore, the present invention provides a mirror and compass system that positions the compass sensors within the movable head portion of the mirror assembly in a manner that reduces the effects of mirror adjustment on the sensor performance. The compass system may adjust processing in response to known movements of the mirror head to compensate for such known movements. The compass system of the present invention may distinguish between deviations, signatures or patterns indicative of magnetic anomalies or stray magnetic fields or the like generated external to the vehicle (such as by metal bridges, subway lines, cellular telephone towers, large metal structures and the like), and deviations, signatures or patterns indicative of mirror adjustments by the driver (as the driver may grasp and move the mirror head/reflective element to adjust his or her field of view rearward through the rear window of the vehicle), and may enter the calibration mode when a mirror adjustment is detected and distinguished or recognized. The compass system may enter an aggressive calibration mode to calibrate the sensors when the mirror has been adjusted by a user. The commencement of the aggressive calibration mode may be effected by the type of adjustment, vehicle speed, time elapsed since activation of the vehicle ignition or other activating or triggering event or the like.

Changes and modifications in the specifically described embodiments can be carried out without departing from the principles of the present invention, which is intended to be limited only by the scope of the appended claims as interpreted according to the principles of patent law.

The invention claimed is:

1. An interior rearview mirror system for a vehicle, said interior rearview mirror system comprising:
 - an interior rearview mirror assembly comprising a mirror casing and a reflective element;
 - wherein said reflective element provides a field of view rearward of the vehicle to a driver of the vehicle when said interior rearview mirror assembly is normally mounted in the vehicle and is adjusted to a viewing orientation;
 - wherein a mounting structure mounts said interior rearview mirror assembly to an interior portion of the vehicle, and wherein said mirror casing is adjustable by the driver of the vehicle relative to the interior portion of the vehicle via at least one pivot element of said mounting structure to adjust the rearward field of view of said reflective element when said interior rearview mirror assembly is normally mounted in the vehicle;
 - wherein said interior rearview mirror assembly comprises an application specific integrated compass chip;
 - said application specific integrated compass chip comprising at least two magnetoresponsive sensing elements established on a semiconductor substrate;

35

said application specific integrated compass chip further comprising associated circuitry commonly established with said magnetoresponsive sensing elements on said semiconductor substrate;

wherein said application specific integrated compass chip has an area of less than approximately two square centimeters;

wherein processing of an algorithm by a microprocessor of said interior rearview mirror system determines a directional heading of the vehicle responsive to a sensing of a magnetic field by said magnetoresponsive sensing elements and automatically compensates for a deviating magnetic field; and

wherein an information display of said interior rearview mirror assembly displays the directional heading of the vehicle.

2. The interior rearview mirror system of claim 1, wherein said associated circuitry comprises at least one of (i) an A/D converter, (ii) a D/A converter and (iii) signal processing circuitry.

3. The interior rearview mirror system of claim 2, wherein said associated circuitry comprises at least one of (i) memory, (ii) signal filtering circuitry, (iii) a display driver and (iv) a vehicle bus interface.

4. The interior rearview mirror system of claim 3, wherein said associated circuitry comprises said microprocessor.

5. The interior rearview mirror system of claim 1, wherein said magnetoresponsive sensing elements and said associated circuitry are commonly established on said semiconductor substrate using CMOS technology.

6. The interior rearview mirror system of claim 5, wherein said semiconductor substrate comprises a silicon substrate.

7. The interior rearview mirror system of claim 1, wherein said application specific integrated compass chip is disposed in said mirror casing and moves in tandem with said mirror casing and said reflective element when said mirror casing is adjusted by the driver of the vehicle relative to the interior portion of the vehicle.

8. The interior rearview mirror system of claim 7, wherein said application specific integrated compass chip is oriented in said mirror casing such that said magnetoresponsive sensing elements are arranged generally horizontally when said interior rearview mirror assembly is normally mounted in a vehicle.

9. The interior rearview mirror system of claim 7, wherein said application specific integrated compass chip is supported by said reflective element.

10. The interior rearview mirror system of claim 7, wherein an algorithm processed by said microprocessor discerns between a change in said sensing by said magnetoresponsive sensing elements that is indicative of an adjustment of said mirror casing by the driver of the vehicle and a change in said sensing by said magnetoresponsive sensing elements that is indicative of a change in vehicle direction, and causes said interior rearview mirror system to enter a rapid compensating mode when the change in said sensing by said magnetoresponsive sensing elements is indicative of an adjustment of said mirror casing by the driver of the vehicle.

11. The interior rearview mirror system of claim 7, wherein electrical wiring providing electrical power for said application specific integrated compass chip passes through said at least one pivot element of said mounting structure.

12. The interior rearview mirror system of claim 11, wherein said at least one pivot element comprises two pivot elements that are part of a double pivot mounting structure, and wherein said electrical wiring passes through both of said pivot elements of said double pivot mounting structure.

36

13. The interior rearview mirror system of claim 11, wherein the interior portion of the vehicle comprises a mounting button attached at an interior surface of the windshield of the vehicle and wherein said mounting structure comprises a mount for mounting said interior rearview mirror assembly to the mirror mounting button attached at the interior surface of the windshield of the vehicle.

14. The interior rearview mirror system of claim 7, wherein said application specific integrated compass chip is oriented in a manner that reduces the effect of an adjustment of said mirror casing on the output of said magnetoresponsive sensing elements.

15. The interior rearview mirror system of claim 1, wherein said application specific integrated compass chip is operable to receive an output from a temperature sensor and to determine a temperature reading and to display the temperature reading on said information display.

16. The interior rearview mirror system of claim 1, wherein said application specific integrated compass chip further comprises a temperature sensor and wherein said temperature sensor is commonly established with said magnetoresponsive sensing elements and said associated circuitry on said semiconductor substrate.

17. The interior rearview mirror system of claim 1, wherein said reflective element comprises a variable reflectance electro-optic reflective element and wherein said application specific integrated compass chip controls, at least in part, the reflectance of said electro-optic reflective element.

18. The interior rearview mirror system of claim 1, wherein said at least two magnetoresponsive sensing elements comprise first, second and third magnetoresponsive sensing elements.

19. The interior rearview mirror system of claim 1, wherein said at least two magnetoresponsive sensing elements comprise at least two Hall effect magnetoresponsive sensing elements.

20. The interior rearview mirror system of claim 1, wherein said interior rearview mirror system enters an initial rapid compensating mode in response to an ignition cycle of the vehicle to achieve at least an approximate compensation for a deviating magnetic field of the vehicle, and wherein said interior rearview mirror system automatically exits said rapid compensating mode and enters a less aggressive calibration mode that distinguishes the Earth's magnetic field from magnetic anomalies and non-abrupt changes in the vehicle magnetic signature, and wherein said interior rearview mirror system automatically exits said rapid compensating mode after a predetermined period of time has elapsed since the ignition cycle.

21. The interior rearview mirror system of claim 1, wherein said interior rearview mirror system operates in an automatic compensation mode to achieve at least an approximate compensation for a deviating magnetic field of the vehicle and wherein the automatic compensation does not require the vehicle to turn through a 360 degree circle to compensate for a deviating magnetic field of the vehicle.

22. The interior rearview mirror system of claim 1, wherein said information display comprises at least one of (a) a vacuum fluorescent display, (b) a light emitting diode display, (c) an electroluminescent display, (d) a liquid crystal display, (e) a backlit thin film transistor liquid crystal display and (f) a video screen display.

23. An interior rearview mirror system for a vehicle, said interior rearview mirror system comprising:
an interior rearview mirror assembly comprising a mirror casing and a reflective element;

37

wherein said reflective element provides a field of view rearward of the vehicle to a driver of the vehicle when said interior rearview mirror assembly is normally mounted in the vehicle and is adjusted to a viewing orientation;

wherein a mounting structure mounts said interior rearview mirror assembly to an interior portion of the vehicle, and wherein said mirror casing is adjustable by the driver of the vehicle relative to the interior portion of the vehicle via at least one pivot element of said mounting structure to adjust the rearward field of view of said reflective element when said interior rearview mirror assembly is normally mounted in the vehicle;

wherein said interior rearview mirror assembly comprises an application specific integrated compass chip;

said application specific integrated compass chip comprising at least two magnetoresponsive sensing elements established on a semiconductor substrate, wherein said semiconductor substrate comprises a silicon substrate;

said application specific integrated compass chip further comprising associated circuitry commonly established with said magnetoresponsive sensing elements on said semiconductor substrate;

wherein said magnetoresponsive sensing elements and said associated circuitry are commonly established on said semiconductor substrate using CMOS technology;

wherein processing of an algorithm by a microprocessor of said interior rearview mirror system determines a directional heading of the vehicle responsive to a sensing of a magnetic field by said magnetoresponsive sensing elements and automatically compensates for a deviating magnetic field; and

wherein an information display of said interior rearview mirror assembly displays the directional heading of the vehicle.

24. The interior rearview mirror system of claim 23, wherein said application specific integrated compass chip is disposed in said mirror casing and moves in tandem with said mirror casing and said reflective element when said mirror casing is adjusted by the driver of the vehicle relative to the interior portion of the vehicle.

25. The interior rearview mirror system of claim 24, wherein electrical wiring providing electrical power for said application specific integrated compass chip passes through said at least one pivot element of said mounting structure.

26. The interior rearview mirror system of claim 25, wherein said at least one pivot element comprises two pivot elements that are part of a double pivot mounting structure, and wherein said electrical wiring passes through both of said pivot elements of said double pivot mounting structure.

27. The interior rearview mirror system of claim 24, wherein said application specific integrated compass chip has an area of less than approximately two square centimeters.

28. The interior rearview mirror system of claim 27, wherein said application specific integrated compass chip further comprises a temperature sensor and wherein said temperature sensor is commonly established with said magnetoresponsive sensing elements and said associated circuitry on said semiconductor substrate, and wherein said application specific integrated compass chip is operable to determine a temperature reading for displaying the temperature reading on said information display.

29. The interior rearview mirror system of claim 23, wherein said reflective element comprises a variable reflectance electro-optic reflective element and wherein said application specific integrated compass chip controls, at least in part, the reflectance of said electro-optic reflective element.

38

30. The interior rearview mirror system of claim 23, wherein said at least two magnetoresponsive sensing elements comprise first, second and third magnetoresponsive sensing elements.

31. The interior rearview mirror system of claim 23, wherein said at least two magnetoresponsive sensing elements comprise at least two Hall effect magnetoresponsive sensing elements.

32. The interior rearview mirror system of claim 23, wherein said information display comprises a video screen display.

33. An interior rearview mirror system for a vehicle, said interior rearview mirror system comprising:

an interior rearview mirror assembly comprising a mirror casing and a reflective element;

wherein said reflective element provides a field of view rearward of the vehicle to a driver of the vehicle when said interior rearview mirror assembly is normally mounted in the vehicle and is adjusted to a viewing orientation;

wherein a mounting structure mounts said interior rearview mirror assembly to an interior portion of the vehicle, and wherein said mirror casing is adjustable by the driver of the vehicle relative to the interior portion of the vehicle via at least one pivot element of said mounting structure to adjust the rearward field of view of said reflective element when said interior rearview mirror assembly is normally mounted in the vehicle;

wherein said interior rearview mirror assembly comprises an application specific integrated compass chip;

wherein said application specific integrated compass chip is disposed in said mirror casing and moves in tandem with said mirror casing and said reflective element when said mirror casing is adjusted by the driver of the vehicle relative to the interior portion of the vehicle;

said application specific integrated compass chip comprising at least two magnetoresponsive sensing elements established on a semiconductor substrate, wherein said semiconductor substrate comprises a silicon substrate;

said application specific integrated compass chip further comprising associated circuitry commonly established with said magnetoresponsive sensing elements on said semiconductor substrate, and wherein said associated circuitry comprises a microprocessor;

wherein said magnetoresponsive sensing elements and said associated circuitry are commonly established on said semiconductor substrate using CMOS technology;

wherein said application specific integrated compass chip has an area of less than approximately two square centimeters;

wherein said reflective element comprises a variable reflectance electro-optic reflective element and wherein said application specific integrated compass chip controls, at least in part, the reflectance of said electro-optic reflective element;

wherein processing of an algorithm by said microprocessor determines a directional heading of the vehicle responsive to a sensing of a magnetic field by said magnetoresponsive sensing elements and automatically compensates for a deviating magnetic field; and

wherein an information display of said interior rearview mirror assembly displays the directional heading of the vehicle.

34. The interior rearview mirror system of claim 33, wherein said application specific integrated compass chip is supported by said reflective element, and wherein said appli-

39

cation specific integrated compass chip has an area of less than approximately one square centimeter.

35. The interior rearview mirror system of claim 34, wherein said associated circuitry comprises at least two of (i) an A/D converter, (ii) a D/A converter, (iii) signal processing circuitry, (iv) memory, (v) signal filtering circuitry, (vi) a display driver and (vii) a vehicle bus interface.

36. The interior rearview mirror system of claim 35, wherein said application specific integrated compass chip further comprises a temperature sensor and wherein said temperature sensor is commonly established with said magneto-responsive sensing elements and said associated circuitry on said semiconductor substrate.

40

37. The interior rearview mirror system of claim 35, wherein said variable reflectance electro-optic reflective element comprises a variable reflectance electrochromic reflective element, and wherein said variable reflectance electrochromic reflective element has a transflective mirror reflector disposed at a surface thereof, and wherein said information display is disposed behind said variable reflectance electrochromic reflective element and, when said interior rearview mirror assembly is normally mounted in the vehicle, said information display operates to display the directional heading of the vehicle for viewing by the driver of the vehicle through said transflective mirror reflector of said electrochromic reflective element.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 8,282,226 B2
APPLICATION NO. : 12/906519
DATED : October 9, 2012
INVENTOR(S) : Rodney K. Blank, Kenneth L. Scierbeek and Niall R. Lynam

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Specifications:

Column 1

Line 13, “No,” should be --No.--

Column 6

Line 21, “No,” should be --No.--

Line 25, “No,” should be --No.--

Column 15

Line 67, Delete “,” after “field”

Column 17

Line 45, “algorithm software” should be --algorithm/software--

Column 21

Lines 14-15, Delete “,” after “components”

Signed and Sealed this
Fifth Day of March, 2013



Teresa Stanek Rea
Acting Director of the United States Patent and Trademark Office