

US008292146B2

(12) **United States Patent**  
**Holsten et al.**

(10) **Patent No.:** **US 8,292,146 B2**  
(45) **Date of Patent:** **\*Oct. 23, 2012**

(54) **SURGICAL STAPLING INSTRUMENTS INCLUDING A CARTRIDGE HAVING MULTIPLE STAPLE SIZES**

(75) Inventors: **Henry E. Holsten**, Southington, CT (US); **Frank J. Viola**, Sandy Hook, CT (US); **Clifford L. Emmons**, Oakville, CT (US)

(73) Assignee: **Tyco Healthcare Group LP**, Mansfield, MA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **12/765,126**

(22) Filed: **Apr. 22, 2010**

(65) **Prior Publication Data**  
US 2010/0200641 A1 Aug. 12, 2010

**Related U.S. Application Data**  
(60) Division of application No. 12/075,820, filed on Mar. 13, 2008, now Pat. No. 7,726,538, which is a continuation of application No. 11/512,943, filed on Aug. 29, 2006, now Pat. No. 7,837,079, which is a continuation of application No. 11/204,060, filed on Aug. 15, 2005, now Pat. No. 7,407,075.

(51) **Int. Cl.**  
**A61B 17/068** (2006.01)  
(52) **U.S. Cl.** ..... **227/175.1**; 227/19; 606/219  
(58) **Field of Classification Search** .... 227/175.1-182.1, 227/19  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,771,526	A *	11/1973	Rudie .....	606/153
4,319,576	A	3/1982	Rothfuss	
4,605,001	A	8/1986	Rothfuss et al.	
4,608,981	A	9/1986	Rothfuss et al.	
4,610,383	A	9/1986	Rothfuss et al.	
4,767,044	A	8/1988	Green	
4,809,695	A	3/1989	Gwathmey et al.	
4,848,637	A	7/1989	Pruitt	
4,930,503	A	6/1990	Pruitt	
4,941,623	A	7/1990	Pruitt	
4,978,049	A	12/1990	Green	
5,027,834	A	7/1991	Pruitt	
5,180,092	A	1/1993	Crainich	
5,240,163	A	8/1993	Stein et al.	

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0878169 11/1998

(Continued)

OTHER PUBLICATIONS



European Search Report for EP 06016963.8-2318 date of completion is Mar. 9, 2007 (9 pages).

*Primary Examiner* — Lindsay Low

(57) **ABSTRACT**

A surgical stapling apparatus includes a staple cartridge and an anvil member. The staple cartridge includes a plurality of surgical fasteners disposed in rows of retention slots. The staple cartridge may have an annular or linear configuration of retention slots. The tissue contacting surface of the staple cartridge may be tapered or stepped. The anvil member has a tissue contacting surface that includes a number of pockets arranged for substantially aligning with the retention slots. In addition, the tissue contacting surface of the anvil member may complement the tissue contacting surface of the staple cartridge.

**9 Claims, 16 Drawing Sheets**



U.S. PATENT DOCUMENTS

5,342,396 A 8/1994 Cook  
 5,368,599 A \* 11/1994 Hirsch et al. .... 606/139  
 5,441,193 A \* 8/1995 Gravener ..... 227/176.1  
 5,452,836 A 9/1995 Huitema et al.  
 5,452,837 A 9/1995 Williamson, IV et al.  
 5,467,911 A \* 11/1995 Tsuruta et al. .... 227/175.1  
 5,484,095 A 1/1996 Green et al.  
 5,497,931 A 3/1996 Nakamura  
 5,571,116 A 11/1996 Bolanos et al.  
 5,571,285 A 11/1996 Chow et al.  
 5,676,674 A 10/1997 Bolanos et al.  
 5,697,542 A 12/1997 Knodel et al.  
 5,709,680 A 1/1998 Yates et al.  
 5,865,361 A 2/1999 Milliman et al.  
 5,871,135 A 2/1999 Williamson, IV et al.  
 5,915,616 A 6/1999 Viola et al.  
 5,964,394 A 10/1999 Robertson  
 6,202,914 B1 3/2001 Geiste et al.  
 6,241,139 B1 \* 6/2001 Milliman et al. .... 227/175.1  
 6,325,810 B1 12/2001 Hamilton et al.  
 6,786,382 B1 9/2004 Hoffman  
 6,905,057 B2 6/2005 Swayze et al.  
 6,959,852 B2 11/2005 Shelton, IV et al.  
 6,964,363 B2 11/2005 Wales et al.  
 6,978,921 B2 12/2005 Shelton, IV et al.  
 6,988,649 B2 1/2006 Shelton, IV et al.  
 7,000,818 B2 2/2006 Shelton, IV et al.  
 7,000,819 B2 2/2006 Swzyze et al.  
 7,044,352 B2 5/2006 Shelton, IV et al.  
 7,055,731 B2 6/2006 Shelton, IV et al.  
 7,059,508 B2 6/2006 Shelton, IV et al.  
 7,070,083 B2 7/2006 Jankowski  
 7,455,676 B2 11/2008 Holsten et al.  
 2003/0178465 A1 9/2003 Bilotti et al.  
 2004/0004105 A1 1/2004 Jankowski  
 2004/0232195 A1 11/2004 Shelton et al.  
 2004/0232199 A1 11/2004 Shelton et al.  
 2005/0006430 A1 1/2005 Wales  
 2005/0006431 A1 1/2005 Shelton et al.


2005/0006434 A1 1/2005 Wales et al.  
 2005/0023324 A1 2/2005 Doll et al.  
 2005/0070925 A1 3/2005 Shelton et al.  
 2005/0070958 A1 3/2005 Swayze et al.  
 2005/0173490 A1 8/2005 Shelton  
 2005/0178813 A1 8/2005 Swayze et al.  
 2005/0187576 A1 8/2005 Whitman et al.  
 2005/0263562 A1 12/2005 Shelton et al.  
 2006/0000868 A1 1/2006 Shelton et al.  
 2006/0022014 A1 2/2006 Shelton et al.  
 2006/0022015 A1 2/2006 Shelton et al.  
 2006/0025809 A1 2/2006 Shelton, IV  
 2006/0025810 A1 2/2006 Shelton, IV  
 2006/0025811 A1 2/2006 Shelton, IV  
 2006/0025812 A1 2/2006 Shelton, IV  
 2006/0025813 A1 2/2006 Shelton et al.  
 2006/0025816 A1 2/2006 Shelton, IV  
 2006/0025817 A1 2/2006 Ortiz et al.  
 2006/0049230 A1 3/2006 Shelton et al.  
 2006/0097026 A1 5/2006 Shelton, IV  
 2006/0226196 A1 10/2006 Hueil et al.  
 2007/0010838 A1 1/2007 Shelton et al.

FOREIGN PATENT DOCUMENTS

EP 1090592 4/2001  
 EP 1316290 11/2002  
 EP 1479346 5/2004  
 EP 1754445 A2 2/2007  
 FR 2838952 10/2003  
 SU 405234 9/1975  
 SU 1333319 8/1987  
 SU 1459659 2/1989  
 SU 1442191 12/1998  
 WO WO86/02254 A1 4/1986  
 WO WO 90/05489 5/1990  
 WO WO 97/34533 9/1997  
 WO WO 03/094743 11/2003  
 WO WO 03/094747 11/2003

\* cited by examiner








FIG. 2




FIG. 3A




FIG. 3B






FIG. 3C




FIG. 3D





FIG. 4









FIG. 6



**FIG. 6A**




FIG. 7






FIG. 7A




FIG. 8




FIG. 9




FIG. 10






FIG. 11




FIG. 12




FIG. 13




FIG. 14








FIG. 16



**SURGICAL STAPLING INSTRUMENTS  
INCLUDING A CARTRIDGE HAVING  
MULTIPLE STAPLE SIZES**

CROSS-REFERENCE TO RELATED  
APPLICATIONS

This application is a divisional of U.S. patent application Ser. No. 12/075,820 filed Mar. 13, 2008, now U.S. Pat. No. 7,726,538 which is a continuation of U.S. patent application Ser. No. 11/512,943 filed Aug. 29, 2006 now U.S. Pat. No. 7,837,079, which is a continuation of application Ser. No. 11/204,060 filed Aug. 15, 2005 now U.S. Pat. No. 7,407,075. Each of these applications is incorporated herein in their entirety by this reference.

BACKGROUND

1. Technical Field

The present disclosure relates to surgical stapling instruments and, more particularly, to surgical stapling instruments including a cartridge having multiple staple sizes.

2. Background of Related Art

There are several known types of surgical stapling instruments specifically adapted for use in various procedures such as end-to-end anastomosis, gastrointestinal anastomosis, endoscopic gastrointestinal anastomosis, and transverse anastomosis. Examples of stapling instruments for these various procedures can be found in U.S. Pat. Nos. 5,915,616; 6,202,914; 5,865,361; and 5,964,394.

Each surgical stapling instrument includes an anvil which is approximated relative to a staple cartridge. The staple cartridge typically has one or more laterally spaced rows of staples which, depending on the particular stapling instrument, may be arranged in a linear or non-linear configuration. The anvil includes staple forming depressions which are aligned with and/or in registration with the staple slots of the staples in the cartridge. In use, each of the surgical stapling instruments involves the gripping of tissue to be fastened, the ejecting of individual staples, the forcing of staples through the gripped tissue and the closing and/or forming of the staples against the staple forming depressions of the anvil.

A common issue in transecting tissue and/or in anastomosis procedures, employing any one of the surgical stapling instruments disclosed above, is the balance between anastomotic strength and the degree of hemostasis achievable. It is known to include different size staples in a surgical stapling apparatus having a constant gap (i.e. a uniform distance) between an anvil and a staple cartridge.

SUMMARY

The present disclosure is directed towards surgical stapling instruments configured to effectuate an improved balance between the anastomotic strength and the degree of hemostasis at the tissue interface. In particular, embodiments of the present disclosure include surgical fasteners of different sizes. Further still, the distance between an anvil member and a staple cartridge (i.e. the gap) varies from a centerline of the staple cartridge to an outer edge of the staple cartridge. Combining the different sizes of surgical fasteners with the varying gap between the anvil member and the staple cartridge improves the anastomotic strength and the degree of hemostasis at the tissue interface.

According to one aspect of the disclosure, the surgical stapling instrument includes a first structure defining having an anvil member operatively associated therewith, and a sec-

ond structure defining a staple cartridge operatively associated therewith. The staple cartridge has a tissue contacting surface with a stepped cross-sectional profile. The tissue contacting surface of the staple cartridge also includes a plurality of retention slots formed therein for retaining a surgical fastener. During operation of the surgical stapling instrument, the anvil member and the staple cartridge can be approximated relative to one another.

The stepped tissue contact surface of the staple cartridge defines a plurality of tissue contacting surfaces each having a different height. In one embodiment, the stepped tissue contacting surface of the cartridge includes an inner tissue contacting surface having a height, an intermediate tissue contacting surface having a height less than the height of the inner tissue contacting surface, and an outer tissue contacting surface having a height less than the height of the intermediate tissue contacting surface.

The inner, intermediate, and outer tissue contacting surfaces each include at least one row of retention slots formed therein. A plurality of surgical fasteners is disposed, one each, in each retention slot. Each surgical fastener includes a backspan and a pair of descending legs.

The surgical fasteners retained in the retention slots formed in the inner tissue contacting surface have a first leg length, the surgical fasteners retained in the retention slots formed in the intermediate tissue contacting surface have a second leg length, and the surgical fasteners retained in the retention slots formed in the outer tissue contacting surface have a third leg length. In one embodiment, the surgical fasteners retained in the retention slots formed in the inner tissue contacting surface have a leg length of about 2.3 mm, while the surgical fasteners retained in the retention slots formed in the intermediate tissue contacting surface have a leg length of about 3.5 mm, and the surgical fasteners retained in the retention slots formed in the outer tissue contacting surface have a leg length of about 4.1 mm.

It is envisioned that the surgical stapling instrument can be a circular-type surgical stapling instrument wherein the anvil member and the staple cartridge can be annular. In one embodiment, the plurality of tissue contacting surfaces decreases in height in a radially outward direction. Accordingly, the inner tissue contacting surface is closest to the center and the outer tissue contacting surface is furthest from the center of the annular staple cartridge. Moreover, surgical fasteners having relatively short leg lengths are retained in the retention slots closest to the center of the annular staple cartridge while surgical fasteners having relatively longer leg lengths are retained in the retention slots furthest from the center of the annular staple cartridge.

It is further envisioned that the surgical stapling instrument can be a linear-type surgical stapling instrument wherein the anvil member and the staple cartridge are linear. In these instruments, the staple cartridge and/or the anvil member may define a knife cut line. Accordingly, the plurality of tissue contacting surfaces decreases in height in a direction orthogonally outward from the knife cut line. In particular, the inner tissue contacting surface is closest to the knife cut line while the outer tissue contacting surface is furthest from the knife cut line. In addition, surgical fasteners having relatively short leg lengths are retained in the retention slots closest to the knife cut line while surgical fasteners having relatively longer leg lengths are retained in the retention slots furthest from the knife cut line.

It is envisioned that the anvil member can have a tissue contacting surface with a stepped cross-sectional profile including a plurality of tissue contacting surfaces, wherein each tissue contacting surface has a different height. In addi-



tion, each one of the plurality of tissue contacting surfaces can include at least one annular and/or linear row of surgical fastener forming depressions formed therein.

In one embodiment, the anvil member can have a tissue contacting surface which is shaped (i.e. stepped) to complement the stepped tissue contacting surface of the staple cartridge. In another embodiment, the anvil member can have a tissue contacting surface which is stepped while the tissue contacting surface of the staple cartridge is substantially planar. In yet another embodiment, the anvil member can have a tissue contacting surface which is shaped to substantially complement the stepped tissue contacting surface of the staple cartridge (i.e. the depths of the tissue contacting surfaces of the stepped anvil member are not equal to the heights of the individual tissue contacting surfaces of the tissue contacting surface of the staple cartridge). In still another embodiment, the anvil member can have a tissue contacting surface which is stepped to mirror the tissue contacting surface of the staple cartridge (i.e. the depths of individual tissue contacting surfaces of the tissue contacting surface of the anvil member are substantially equal to the depths of the individual tissue contacting surfaces of the staple cartridge).

In other embodiments of the present disclosure, a surgical stapling instrument includes an operative tool disposed at one end thereof. The operative tool includes an anvil member and a staple cartridge. The staple cartridge may be included in a disposable surgical stapling apparatus or in a reusable surgical stapling apparatus. Further still, a replaceable loading unit may be located in either the disposable or the reusable surgical stapling apparatus. In one embodiment, the replaceable loading unit includes a staple cartridge, while an alternate embodiment of the replaceable loading unit includes a staple cartridge and an anvil member. In particular, the staple cartridge includes a plurality of surgical fasteners disposed in rows of retention slots. The surgical fasteners may have different leg lengths wherein a plurality of surgical fasteners having substantially the same leg length is disposed in a row. A number of fastener ejection members are disposed in the staple cartridge wherein each fastener ejection member includes a plurality of staple pushers for ejecting the surgical fasteners in cooperation with an actuation mechanism.

The staple cartridge may include an angled tissue contacting surface that peaks at a centerline of the staple cartridge and tapers towards outer walls of the staple cartridge. Alternatively, the tissue contacting surface of the staple cartridge may have a surface that is parallel with the bottom surface of the staple cartridge or parallel to a plane defined by the backspans of surgical fasteners disposed in a selected row. The parallel surface of the tissue contacting surface has a width dimension that is sufficient to accommodate at least one row of surgical fasteners. The staple cartridge may include a knife channel.

In cooperation with the presently disclosed staple cartridge, the anvil member may include a planar tissue contacting surface that is substantially parallel to the bottom surface of the staple cartridge or parallel to a plane defined by the backspins of surgical fasteners disposed in a selected row. In the alternative, the tissue contacting surface of the anvil member may be angled in an opposed manner to the angle of the tissue contacting surface of the staple cartridge. Further still, the tissue contacting surface of the anvil member may have a planar surface that is substantially parallel to the bottom surface of the staple cartridge or parallel to a plane defined by the backspins of surgical fasteners disposed in a selected row and tapered surfaces that define angles opposite to the angles defined by the tissue contacting surface of the staple cartridge. The parallel surfaces of the anvil member have a width

dimension that corresponds to a width dimension of the parallel surface of the staple cartridge.

It is further contemplated that one embodiment of the surgical stapling apparatus includes structures for supplemental sealing of the fastened layers of tissue. In one embodiment, the surgical stapling apparatus includes a wound closure assembly having a reservoir and a supply line. The reservoir is adapted for storing a quantity of a wound closure material and is fluidly coupled to the staple cartridge via the supply line for delivering amounts of the wound closure material to the plurality of retention slots.

The presently disclosed surgical stapling instruments, together with attendant advantages, will be more clearly illustrated below by the description of the drawings and the detailed description of the embodiments.

Other objects and features of the present disclosure will become apparent from consideration of the following description taken in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments of the presently disclosed surgical stapling apparatus are described herein with reference to the accompanying drawings, wherein:

FIG. 1 is a perspective view of a surgical stapling instrument constructed in accordance with the present disclosure;

FIG. 2 is a schematic cross-sectional side elevational view of the distal end portion of the surgical stapling instrument of FIG. 1, as taken through 2-2 of FIG. 1;

FIG. 3A is an enlarged schematic representation of the indicated area of FIG. 2, illustrating tissue contacting surfaces in accordance with an alternate embodiment of the present disclosure;

FIG. 3B is an enlarged schematic representation of the indicated area of FIG. 2, illustrating tissue contacting surfaces in accordance with another embodiment of the present disclosure;

FIG. 3C is an enlarged schematic representation of the indicated area of FIG. 2, illustrating tissue contacting surfaces in accordance with still another embodiment of the present disclosure;

FIG. 3D is an enlarged schematic representation of the indicated area of FIG. 2, illustrating tissue contacting surfaces in accordance with a further embodiment of the present disclosure;

FIG. 4 is a perspective view of an alternative surgical stapling instrument constructed in accordance with the present disclosure;

FIG. 5 is a perspective view of yet another surgical stapling instrument constructed in accordance with the present disclosure;

FIG. 6 is a perspective view of still another surgical stapling instrument constructed in accordance with the present disclosure;

FIG. 6A is a perspective view of a portion of an anvil member of FIG. 6;

FIG. 7 is a schematic cross-sectional side elevational view of the distal end portion of the surgical stapling instruments of FIGS. 4-6, as taken through 7-7 of each of FIGS. 4-6;

FIG. 7A is a schematic cross-sectional side elevational view of an alternate embodiment of the distal portion of the surgical stapling instrument of FIG. 6

FIG. 8 is a perspective view of a staple cartridge according to another embodiment of the present disclosure;

FIG. 9 is a cross-sectional end view of the staple cartridge of FIG. 8 showing a first arrangement of surgical fasteners;



## 5

FIG. 10 is an alternate embodiment of the staple cartridge of FIG. 9 illustrating a second embodiment of the surgical fasteners;

FIG. 11 is an alternate embodiment of an anvil member and the staple cartridge of FIG. 10;

FIG. 12 is a further embodiment of the staple cartridge of FIG. 8;

FIG. 13 is another embodiment of the anvil member and the staple cartridge of FIG. 12;

FIG. 14 is another embodiment of the staple cartridge and anvil member of FIG. 8;

FIG. 15 is alternate embodiment of an anvil member with the staple cartridge of FIG. 14; and

FIG. 16 is a cross-sectional side elevational view of the resulting tissue interface following the firing of surgical stapling instrument of FIGS. 7 and 10-15.

## DETAILED DESCRIPTION OF EMBODIMENTS

Embodiments of the presently disclosed surgical stapling instruments will now be described in detail with reference to the drawing figures wherein like reference numerals identify similar or identical elements. In the drawings and in the description which follows, the term “proximal”, as is traditional, will refer to the end of the surgical stapling instrument which is closest to the operator while the term “distal” will refer to the end of the device which is furthest from the operator.

The present disclosure relates to a staple cartridge and an anvil member for use in a disposable or re-usable surgical stapling apparatus. The presently disclosed staple cartridge and anvil member, as will be discussed in detail hereinbelow, may be used with any of the surgical stapling apparatus shown in FIG. 1, 4, 5, or 6. In addition, a replaceable loading unit may be located in either the disposable or the reusable surgical stapling apparatus. In one embodiment, the replaceable loading unit includes a staple cartridge, including any of the staple cartridges disclosed herein. Alternatively, the replaceable loading unit includes the staple cartridge and an anvil member, including any of the anvil members disclosed herein. In combination with the disposable or the reusable surgical stapling apparatus, the replaceable loading unit provides improved flexibility of the respective surgical stapling apparatus in that the respective surgical stapling apparatus is readily adaptable for different stapling procedures.

Referring now in detail to FIGS. 1-2, in which like reference numerals identify similar or identical elements, a surgical stapling instrument, in accordance with a first embodiment of the disclosure, is generally designated as 100.

As seen in FIG. 1, surgical stapling instrument 100 includes a handle assembly 102 having at least one pivotable actuating handle member 103, and further includes advancing means 105. Extending from handle assembly 102, there is provided a tubular body portion 104 which may be constructed so as to have a curved shape along its length. Tubular body portion 104 terminates in a fastener ejection member assembly 106 having a circular staple cartridge 118 including a tissue contacting surface 121 disposed at a distal end thereof.

As seen in FIG. 2, tissue contacting surface 121 is stepped including an outer tissue contacting surface 121a, an intermediate tissue contacting surface 121b, and an inner tissue contacting surface 121c. Each tissue contacting surface 121a-121c has a different height from one another as measured from a bottom surface 131 of a staple pusher or fastener ejection member 130. Specifically, tissue contacting surfaces 121a-121c are planar structures that are substantially parallel

## 6

to one another, but are not co-planar (i.e. stepped) with one another. In addition, each tissue contacting surface 121a-c defines a planar axis that extends through the respective tissue contacting surface 121a-c. A first wall surface interconnects tissue contacting surfaces 121a and 121b, while a second wall surface interconnects tissue contacting surfaces 121b and 121c. The first and second wall surfaces are planar structures wherein each wall surface defines a planar axis. In one embodiment, the planar axes of the wall surfaces are orthogonal to the planar axes of tissue contacting surfaces 121a-c.

Inner tissue contacting surface 121c has the greatest height, outer tissue contacting surface 121a has the least height, and intermediate tissue contacting surface 121b has a height between the heights of outer and inner tissue contacting surfaces 121a, 121c. While tissue contacting surfaces 121a-121c are shown as increasing in height from outer tissue contacting surface 121a to inner tissue contacting surface 121c (i.e. radially inward), it is within the scope of the present disclosure that the heights of each tissue contacting surface can vary depending on the particular surgical procedure. For example, tissue contacting surfaces 121a-121c can increase in height in a radially outward direction, the intermediate tissue contacting surface 121b can be the highest or the lowest tissue contacting surface, or at least two of tissue contacting surfaces 121a-121c can have the same height.

In one embodiment, each tissue contacting surface 121a-121c includes a respective annular row 119a-119c of retention slots 123 formed therein. Each retention slot 123 of annular rows 119a-119c is configured and dimensioned to retain a staple or surgical fastener 125 therein. Each surgical fastener 125 includes a backspan (not shown) and a pair of depending legs 25. In one embodiment, each annular row 119a-119c of slots 123 includes a respective surgical fastener 125a-125c having its own characteristic features.

As seen in FIG. 2, legs 25a of surgical fasteners 125a have a first leg length, legs 25b of surgical fasteners 125b have a second leg length, and legs 25c of surgical fasteners 125c have a third leg length. In particular, surgical fasteners 125a-125c increase in height in a radially outward direction. In one embodiment, legs 25c of surgical fasteners 125c have a leg length of about 2.3 mm, legs 25b of surgical fasteners 125b have a leg length of about 3.5 mm, and legs 25a of surgical fasteners 125a have a leg length of about 4.1 mm. As such, inner tissue contacting surface 121c has the greatest height and retains surgical fasteners 125c having the shortest leg lengths, and outer tissue contacting surface 121a has the least height and retains surgical fasteners 125a having the longest leg lengths. Having tissue contacting surface 121 step progressively downward at intermediate tissue contacting surface 121b and then again at outer tissue contacting surface 121a results in the formation of surgical fasteners 125b and 125c, respectively. It is envisioned and within the scope of the present disclosure that any number of arrangements are possible.

While a single annular row 119a-119c of retention slots 123 is shown for each tissue contacting surface 121a-121c, it is envisioned and within the scope of the present disclosure that each tissue contacting surface 121a-121c can include multiple annular rows of retention slots.

As seen in FIG. 2, a fastener ejection assembly 106 of surgical stapling instrument 100 includes fastener ejection member 130 disposed within staple cartridge 118. Fastener ejection member 130 includes a proximal portion 132 having a generally frusto-conical shape and a distal portion defining concentric rings of peripherally spaced staple pushers 134a-c, each one of which is received within a respective staple retention slot 123 and is cooperative with its respective sur-



gical fastener **125a-c** disposed in annular rows **119a-c**. In one embodiment, it is envisioned that proximal portion **132** of fastener ejection member **130** is configured and dimensioned to be contacted by a distal end of a driver tube **138**. Hence, upon advancing fastener ejection member **130** by advancing driver tube **138**, staple pushers **134a-c** will pass further into retention slots **123** thereby pushing surgical fasteners **125** contained therein axially outward.

In an alternate embodiment, staple pushers **134a-c** of fastener ejection member **130** have different heights for cooperating with different sized surgical fasteners. In particular, staple pushers **134a-c** are sized such that when surgical fasteners **125a-c** are disposed in their respective annular rows **119a-c**, tips of surgical fasteners **125a-c** are located substantially in the same plane despite the difference in leg lengths between each row of surgical fasteners.

Surgical stapling instrument **100** further includes a circular anvil assembly **108** having an anvil head **109** and an anvil shaft **110** extending from a proximal end thereof and adapted to engage a shaft **111** extending distally from staple cartridge **118**. Anvil head **109** includes an annular anvil member **112** disposed at a proximal end thereof, wherein anvil member **112** includes at least one, row of fastener forming depressions **114** formed circumferentially thereabout. In one embodiment, surgical stapling instrument **100** includes three laterally spaced rows of fastener forming depressions **114** formed circumferentially thereabout. Each fastener forming depression **114** is in registration with a corresponding retention slot **123**.

While anvil member **112** is shown in FIG. 2 as having a substantially planar tissue contacting surface, it is envisioned and within the scope of the present disclosure for surgical stapling instrument **100** to have a number of alternate configurations. For example, as seen in FIG. 3A, anvil member **112** can have a tissue contacting surface **112a** which is shaped (i.e. stepped) to complement stepped tissue contacting surface **121** of staple cartridge **118** or, as seen in FIG. 3B, anvil member **112** can have a tissue contacting surface **112b** which is stepped while tissue contacting surface **121** of staple cartridge **118** is substantially planar. In addition, for example, as seen in FIG. 3C, anvil member **112** can have one row of staple pockets **114b** that extends a greater distance than staple pockets **114a** or **114c** into anvil member **112** for accommodating surgical fasteners having a longer leg length or, as seen in FIG. 3D, anvil member **112** can have a tissue contacting surface **112d** which is stepped to mirror tissue contacting surface **121** of staple cartridge **118** (i.e. the depths of individual tissue contacting surfaces of tissue contacting surface **112d** of anvil member **112** are substantially equal to the depths of the individual tissue contacting surfaces **121a-121c** of staple cartridge **118**).

The sizes of surgical fasteners **125a-125c** are selected and intended for use in gastric firings typically required in bariatric procedures. However, it is envisioned and within the scope of the present disclosure that the sizes of surgical fasteners **125a-125c** selected can be chosen for performance in different types of tissue, such as, for example, the colon, bowels, lungs, the bronchus, pulmonary vessels, the liver, and the like.

In operation, surgical stapling instrument **100** is positioned within a tubular organ in the body of the patient and the ends of the organ to be joined are positioned in a gap between staple cartridge **118** and anvil assembly **108**. As is conventional, the ends of the organ may be secured around anvil shaft **110** by a purse string suture prior to approximation of anvil assembly **108** to staple cartridge **118**. Surgical stapling instrument **100** is then approximated and fired. An example of a

surgical stapling apparatus and methods for its use are disclosed in U.S. Pat. No. 5,915,616, currently assigned to Tyco Healthcare Group LP, the entire contents of which is incorporated herein by reference.

Turning now to FIGS. 4 and 7, a surgical stapling instrument, of the gastro-intestinal anastomosis type for performing surgical anastomotic stapling, in accordance with another embodiment of the disclosure, is generally designated as **200**. Surgical stapling instrument **200** includes a first handle **202** having a jaw **230** defining a staple cartridge receiving section extending from a distal end thereof, a staple cartridge **204** receivable in jaw **203**, a second handle **206** having a jaw **205** defining an anvil member receiving section extending from a distal end thereof, and an anvil member **208** operatively associated with jaw **205**. First and second handles **202**, **206** are configured such that staple cartridge **204** is substantially aligned with anvil member **208**.

As seen in FIG. 7, staple cartridge **204** includes a stepped tissue contacting surface **121** including an outer tissue contacting surface **121a**, an intermediate tissue contacting surface **121b**, and an inner tissue contacting surface **121c**, each of which has a different height from one another as measured from a bottom surface **231** of staple cartridge **204**. Tissue contacting surfaces **121a-121c** are planar structures that are substantially parallel to one another, but are not co-planar with one another. For example, tissue contacting surfaces **121a-121c**, as shown in FIG. 7, can decrease in height in a direction orthogonally outward from knife track **222**. In embodiments that do not include knife track **222**, tissue contacting surfaces **121a-c** decrease in height in a direction orthogonally outward from a centerline of staple cartridge **204**.

Each tissue contacting surface **121a-121c** includes a respective linear row **119a-119c** of retention slots **123** formed therein. Each retention slot **123** of linear rows **119a-119c** is configured and dimensioned to retain a surgical fastener **125** therein. Each linear row **119a-119c** of slots **123** includes a respective surgical fastener **125a-125c** having its own characteristic features.

As seen in FIG. 7, legs **25a** of surgical fasteners **125a** have a first leg length of about 4.1 mm, legs **25b** of surgical fasteners **125b** have a second leg length of about 3.5 mm, and legs **25c** of surgical fasteners **125c** have a third leg length of about 2.3 mm. In particular, surgical fasteners **125a-125c** increase in height in an orthogonally outward direction relative towards optional knife track **222**. Knife track **222** is disposed along a centerline of staple cartridge **204**, **310**, or **412** and is adapted for slidably receiving an optional knife (not shown). Having tissue contacting surface **121** step progressively downward at intermediate tissue contacting surface **121b** and then again at outer tissue contacting surface **121a** results in the formation of surgical fasteners **125b** and **125c**, respectively. It is envisioned and within the scope of the present disclosure that any number of arrangements are possible.

In operation, surgical stapling instrument **200** is fired similarly to and in accordance with other known surgical stapling instruments. An example of a surgical stapling apparatus and methods for its use are disclosed in U.S. Pat. No. 6,202,914, currently assigned to Tyco Healthcare Group LP, the entire contents of which is incorporated herein by reference.

Referring additionally to FIG. 16, following the firing of surgical stapling instrument **200**, the resulting tissue interface is seen in cross-section. Accordingly, surgical fasteners **125a** and **125b** (i.e. the two rows of surgical fasteners furthest from knife cut line "C") serve to hold tissues "A" and "B" to one



another while surgical fasteners **125c** (i.e. the row of surgical fasteners closest to knife cut line “C”) serve to provide the hemostasis.

While surgical stapling instrument **200** is a linear-type surgical stapler, it is envisioned and within the scope of the present disclosure, that surgical stapling instrument **200** can include a tissue contacting surface having a cross-sectional profile for at least one of the anvil member and the staple cartridge which is substantially similar to the tissue contacting surfaces of the anvil member and the staple cartridge of surgical stapling instrument **100**, as shown in FIGS. 3A-3D.

Turning now to FIGS. 5 and 7, a surgical stapling instrument, of the laparoscopic type for performing surgical anastomotic stapling, in accordance with another embodiment of the disclosure, is generally designated as **300**. Surgical stapling instrument **300** includes a handle **302**, an operative tool **306**, and an elongated shaft **304** for interconnecting operative tool **306** to handle **302**. In general, operative tool **306** is designed to clamp over and then to staple and divide tissue held therein. Accordingly, as seen in FIG. 5, operative tool **306** is a pair of opposed jaws including an anvil member **308** and a staple cartridge **310** pivotally coupled to one another.

Staple cartridge **310** of surgical stapling instrument **300** includes a stepped tissue contacting surface **121** similar to tissue contacting surface **121** of staple cartridge **204** of surgical stapling instrument **200**. Accordingly, reference is made to FIG. 7 and the above detailed discussion of tissue contacting surface **121** of staple cartridge **204** for an illustration and a discussion of tissue contacting surface **121** of staple cartridge **310** of surgical stapling instrument **300**.

In operation, surgical stapling instrument **300** is fired similarly to and in accordance with other known surgical stapling instruments. For a detailed discussion of the approximation and firing of surgical stapling instrument **300**, reference is made to commonly assigned U.S. Pat. No. 5,865,361, currently assigned to Tyco Healthcare Group LP, the entire contents of which is incorporated herein by reference.

Following the firing of surgical stapling instrument **300** the resulting tissue interface, as seen in cross-section, is substantially similar to the resulting tissue interface, as seen in cross-section, following the firing of surgical stapling instruments **100** and **200**. Accordingly, as seen in FIG. 16, surgical fasteners **125a** and **125b** (i.e. the two rows of surgical fasteners furthest from knife cut line “C”) serve to hold tissues “A” and “B” to one another while surgical fasteners **125c** (i.e. the row of surgical fasteners closest to knife cut line “C”) serve to provide the hemostasis.

While surgical stapling instrument **300** is a linear-type surgical stapler as compared to surgical stapling instrument **100**, it is envisioned and within the scope of the present disclosure, that surgical stapling instrument **300** can include a tissue contacting surface having a cross-sectional profile for at least one of the anvil and the staple cartridge which is substantially similar to the tissue contacting surfaces of the anvil and the staple cartridge of surgical stapling instrument **100**, as shown in FIGS. 3A-3D.

Turning now to FIGS. 6, 6A, 7, and 7A, a surgical stapling instrument, of the transverse anastomosis type for performing surgical anastomotic stapling, in accordance with yet another embodiment of the disclosure, is generally designated as **400**. Surgical stapling instrument **400** includes a handle **402**, a barrel **404** extending from handle **402**, and an arm **406** extending from the distal end of barrel **404**. Surgical stapling instrument **400** further includes an anvil member **408** orthogonally affixed to a distal end of arm **406** and a staple cartridge receiver **410** operatively coupled to the distal end of barrel **404** for holding a disposable staple cartridge **412**

thereon. Anvil member **408** is illustrated in further detail in FIG. 6A and includes a tissue contacting surface **420** wherein tissue contacting surface **420** has a plurality of pockets **425** that substantially align with retention slots **123** (FIG. 7). Cooperative alignment between pockets **425** and retention slots **123** form completed surgical fasteners **125** upon actuation of the actuation mechanism in surgical stapling instrument **400**.

Staple cartridge **412** of surgical stapling instrument **400** includes a stepped tissue contacting surface **121** similar to tissue contacting surface **121** of staple cartridge **204** of surgical stapling instrument **200**. Accordingly, reference is made to FIG. 7 and the above detailed discussion of tissue contacting surface **121** of staple cartridge **204** for an illustration and a discussion of tissue contacting surface **121** of staple cartridge **412** of surgical stapling instrument **400**. Further still, staple cartridge **412** may include knife track **222** for slidably receiving a knife (not shown) therein.

In a further embodiment of the present disclosure, staple cartridge **412'** is illustrated in FIG. 7A and discussed in detail hereinafter. Staple cartridge **412'** is similar to staple cartridge **412**, but only includes three rows **119a-c** of retention slots **123** disposed between outer walls of staple cartridge **412'**. As in the previously discussed embodiment, each row **119a-c** includes a plurality of surgical fasteners wherein surgical fasteners in row **119a** have a different leg length from surgical fasteners disposed in row **119b**, while surgical fasteners disposed in row **119c** have a leg length that is different from at least one of rows **119a** or **119b**. This embodiment of the staple cartridge does not include a knife track. The arrangement and interrelationship of tissue contacting surfaces **125a-c** is similar to that previously disclosed with reference to FIG. 7.

In operation, surgical stapling instrument **400** is fired similarly to and in accordance with other known surgical stapling instruments. For a detailed discussion of the approximation and firing of surgical stapling instrument **400**, reference is made to commonly assigned U.S. Pat. No. 5,964,394, currently assigned to Tyco Healthcare Group LP, the entire contents of which is incorporated herein by reference.

Following the firing of surgical stapling instrument **400** the resulting tissue interface, as seen in cross-section, is substantially similar to the resulting tissue interface, as seen in cross-section, following the firing of surgical stapling instruments **100-300**. Accordingly, as seen in FIG. 16, surgical fasteners **125a** and **125b** (i.e. the two rows of surgical fasteners furthest from knife cut line “C”) serve to hold tissues “A” and “B” to one another while surgical fasteners **125c** (i.e. the row of surgical fasteners closest to knife cut line “C”) serve to provide the hemostasis.

While surgical stapling instrument **400** is a linear-type surgical stapler as compared to surgical stapling instrument **100**, it is envisioned and within the scope of the present disclosure, that surgical stapling instrument **400** can include a tissue contacting surface having a cross-sectional profile for at least one of the anvil and the staple cartridge which is substantially similar to the tissue contacting surfaces of the anvil and the staple cartridge of surgical stapling instrument **100**, as shown in FIGS. 3A-3D.

While each of the surgical stapling instruments described above and shown herein are configured and adapted to fire surgical fasteners **125**, it is envisioned and within the scope of the present disclosure, that tissue contacting surfaces of surgical instruments used in connection with applying two-part fasteners can also have stepped configurations as shown and described herein. A typical two-part surgical fastener applying instrument is shown and described in commonly assigned



U.S. Pat. No. 5,573,169, currently assigned to Tyco Healthcare Group LP, the entire contents of which is incorporated herein by reference.

In one further embodiment of the present disclosure, as illustrated in FIGS. 8-10, surgical stapling apparatus 300 includes an operative tool 506 disposed at one end of elongated shaft 304. Operative tool 506 includes anvil member 308 and a staple cartridge 510. Staple cartridge 510 may be included in a disposable surgical stapling apparatus or in a reusable surgical stapling apparatus. In particular, staple cartridge 510 includes a tissue contacting surface 520 having a plurality of retention slots 523 disposed therein and arranged in rows that are substantially aligned with a longitudinal axis of staple cartridge 510. As seen in FIG. 8, each row of retention slots 523 is longitudinally offset from an adjacent row of retention slots. In particular, an optional knife channel 530 is disposed along the longitudinal axis of staple cartridge 510 that is adapted for slidably receiving a knife (not shown).

Referring now to FIG. 9, operative tool 506 is shown in cross-section and illustrates the several components included in staple cartridge 510. Anvil member 308 includes a substantially planar tissue contacting surface 320 that is substantially parallel to a bottom surface 512 or parallel to a plane defined by the backspans of surgical fasteners 125a, 125b, or 125c. Staple cartridge 510 includes outer walls 514 having a first height and inner walls 516 having a second height wherein the second height is greater than the first height. Tissue contacting surface 520 is attached to inner walls 516 and to outer walls 514 and defines an angle with respect to a plane that is orthogonal to inner walls 516. Tissue contacting surface 520 defines a generally curved path between outer walls 514 (i.e. generally convex or elliptical as viewed in cross-section). Additionally, a plurality of surgical fasteners 125a-c are disposed in staple cartridge 510 wherein each row of retention pockets 523 includes a number of substantially identical surgical fasteners (i.e. 125a, 125b, or 125c). Similar to previous embodiments, legs 25a-c of surgical fasteners 125a-c have different lengths. In this embodiment, surgical fasteners 25a have a leg length of about 3.8 mm, surgical fasteners 25b have a leg length of about 3.5 mm, and surgical fasteners 25c have a leg length of about 2.5 mm. As seen in FIG. 9, surgical fasteners 125a-c are disposed in staple cartridge 510 such that surgical fasteners 125c are proximate to outer walls 514, surgical fasteners 125a are disposed proximate to inner walls 516, and surgical fasteners 125b are disposed therebetween. In cooperation with the surgical fasteners of varying height, staple cartridge 510 includes fastener ejection members 540 that include staple pushers 542, 544, and 546 of differing heights. Staple pusher 542 has the greatest height dimension, staple pusher 546 has the least height dimension, and staple pusher 544 has a height dimension therebetween. In this embodiment, surgical fasteners 125a-c are arranged to cooperate with staple pushers 546, 544, and 542 respectively. Fastener ejection member 540 is adapted for substantially vertical movement when it cooperatively engages with an actuation mechanism (not shown). An example of a suitable actuation mechanism is disclosed in U.S. Pat. No. 5,865,361 as discussed with reference to previously disclosed surgical stapling instrument 300.

Alternatively, as shown in FIG. 10, surgical fasteners 125a-c are disposed in staple cartridge 510' such that surgical fasteners 125a are proximate to outer walls 514, surgical fasteners 125c are disposed proximate to inner walls 516, and surgical fasteners 125b are disposed therebetween. Contrary to the previous embodiment, surgical fasteners 125a-c are arranged to cooperate with staple pushers 542, 544, and 546 respectively. After a number of layers of body tissue are

positioned between tissue contacting surfaces 320 and 520, the actuation mechanism is actuated for sequentially ejecting surgical fasteners 125a-c through retention slots 523 whereby interaction between surgical fasteners 125a-c and anvil member 308 forms completed surgical fasteners for joining the layers of body tissue.

When tissue contacting surface 320 of anvil member 308 is repositioned proximate to tissue contacting surface 520 of staple cartridge 510', the amount of pressure applied to the layers of tissue disposed therebetween varies along a plane that is transverse to the longitudinal axis of staple cartridge 510'. Since the distance between tissue contacting surfaces 320 and 520 is at a minimum in the region nearest inner walls 516 (i.e. the centerline of staple cartridge 510'), a maximum pressure is applied to the layers of tissue disposed in this region. Conversely, the distance between tissue contacting surfaces 320 and 520 is at a maximum in the region near outer walls 514, a minimum pressure is applied to the layers disposed in this region. In addition, the proximal relationship between anvil member 308 and staple cartridge 510' defines a plurality of gaps therebetween. A first gap is defined between tissue contacting surfaces 320 and 520 (i.e. along the centerline of staple cartridge 510'), while a second gap is defined between tissue contacting surfaces 320 and 520 along outer walls 514. As seen in FIG. 10, the first gap is not equal to the second gap. Further still, a number of other gaps may be defined between tissue contacting surfaces 320 and 520 at other points of reference existing between the centerline and outer walls 514 in staple cartridge 510'. Since tissue contacting surface 520 slopes toward outer walls 514 to define a substantially uniform angle, the pressure applied to the layers of tissue disposed between tissue contacting surfaces 320 and 520 uniformly decreases from inner wall 516 to outer wall 514.

By angling tissue contacting surface 520 downwards from the centerline of staple cartridge 510', reduced compressive forces are applied to the layers of tissue disposed between tissue contacting surfaces 320 and 520 thereby minimizing trauma to the layers of tissue disposed therebetween. Therefore, layers of tissue disposed between tissue contacting surfaces 320 and 520 will have a minimum thickness nearest knife channel 530 (i.e. nearest the centerline of staple cartridge 510') and a maximum thickness nearest outer walls 514. In addition, anvil member 308 and staple cartridge 510' are dimensioned and arranged such that compressive forces applied to the layers of tissue are minimal thereby further reducing trauma to the layers of tissue. This configuration defines a gap between tissue contacting surfaces 320 and 520 that is a maximum along knife channel 530 (i.e. the centerline of staple cartridge 510 or 510') and a minimum along outer walls of staple cartridge 510 (FIG. 9) or 510' (FIG. 10).

Further still, this configuration is applicable to similar staple cartridges and anvil members as will be discussed in detail hereinafter with respect to FIGS. 11-15. When anvil member 308 is repositioned into proximity with staple cartridge 510' (i.e. in a pre-fire position) to retain layers of body tissue therebetween, the layers of tissue are compressed. The maximum compression occurs along the centerline (i.e. first or minimum gap) and urges fluid stored in the layers of tissue towards the outer edges of the tissue (i.e. away from the centerline of staple cartridge 510'). By reducing the amount of fluid retained in the layers of tissue proximal to the centerline, the overall thickness of the tissue layers decreases. The decrease in overall tissue thickness is such that a staple having a shorter leg length (i.e. surgical fastener 125c) is capable of fastening both layers of tissue while minimizing trauma to the fastened layers of tissue. The gap increases towards the outer



walls of staple cartridge **510'** (i.e. the amount of compression decreases) and surgical fasteners having a longer leg length (i.e. surgical fasteners **125a** and **125b**) are capable of fastening both layers of tissue.

Leg lengths of surgical fasteners **125c**, **125b**, and **125a** increase in a direction moving from inner walls **516** towards outer walls **514**. By providing surgical fasteners having increasing leg lengths along a plane that is orthogonal to inner walls **516**, the completed (i.e. formed) surgical fasteners join increasing thicknesses of tissue without unduly traumatizing the joined layers of tissue.

In a further embodiment, as illustrated in FIG. 11, operative tool **506'** includes staple cartridge **510'** and anvil member **308'**. Staple cartridge **510'** was previously discussed in detail hereinabove with reference to FIG. 10. Tissue contacting surface **520** may define a more uniform angle (FIG. 11) than in the embodiments of FIGS. 9 and 10 wherein the angle or pitch of tissue contacting surface is substantially constant between inner walls **516** and outer walls **514**. Anvil member **308'** includes tissue contacting surface **320'** having tapered surfaces **322'** and **324'**. Surfaces **322'** and **324'** are connected to outer walls of anvil member **308'** while extending inwards (i.e. towards the centerline of staple cartridge **510'**) and downwards (i.e. towards tissue contacting surface **520**) thereby defining an angle. It is envisioned that the angle defined by tapered surfaces **322'** and **324'** will be substantially similar to the angle defined by tissue contacting surface **520**, but in an opposed direction forming a generally V-shaped configuration. Thus, compressive forces applied to the layers of tissue will be further reduced thereby further reducing the trauma to layers of tissue disposed between tissue contacting surfaces **520** and **320'**. As in the embodiment of FIG. 10, the maximum pressure applied to the layers of tissue will exist in the region near knife channel **530** while pressures applied to the layers of tissue will decrease uniformly towards outer walls **514**. Formation and location of surgical fasteners **125a-c** is substantially similar to that of the embodiment of FIG. 10 along with the attendant advantages.

Referring now to FIG. 12, a further embodiment of the present disclosure is shown as part of operative tool **606**. Operative tool **606** includes a staple cartridge **610** and anvil member **308**. In this embodiment, tissue contacting surface **620** includes surfaces **622** and **624**. Surface **622** is bisected along its longitudinal axis by knife channel **630** and substantially parallel to a bottom surface **612** or parallel to a plane defined by the backspins of surgical fasteners **125a**, **125b**, or **125c**. In addition, surface **622** has a width dimension sufficient to accommodate at least one row of retention slots **623** on each side of knife channel **630**. Surface **624** connects outer edges of surface **622** to outer walls **614** defining an angle on either side of knife channel **630** with respect to a plane that is substantially orthogonal to inner walls **616** (i.e. substantially parallel to surface **622**) and has a width dimension sufficient to accommodate at least one row of retention slots on each side of knife channel **630**. Staple cartridge **610** includes a plurality of surgical fasteners **125a-c** and fastener ejection members **540** that were previously discussed in detail with respect to FIGS. 9 and 10. In particular, staple cartridge **610** includes the arrangement of surgical fasteners **125a-c** and fastener ejection members **540** as described with respect to staple cartridge **510'** (FIGS. 10 and 11).

Similarly to operative tool **506**, tissue contacting surface **320** is repositioned proximate to tissue contacting surface **620** of staple cartridge **610**. In this arrangement, the amount of pressure applied to the layers of tissue disposed therebetween varies along a plane that is transverse to the longitudinal axis of staple cartridge **610**. Specifically, the distance between

tissue contacting surface **320** and surface **622** is a minimum, a maximum pressure is applied to the layers of tissue disposed in this region. Conversely, the distance between tissue contacting surface **320** and surfaces **624** is at a maximum in the region near outer walls **614**, a minimum pressure is applied to the layers disposed in this region. Since surface **624** slopes toward outer walls **614** to define a substantially uniform angle, the pressure applied to the layers of tissue disposed between tissue contacting surface **320** and surfaces **624** uniformly decreases from an outer edge of surface **622** towards outer wall **614**.

By angling surface **624** downwards from the edge of surface **622**, reduced compressive forces are applied to the layers of tissue disposed between tissue contacting surface **320** and surfaces **624** thereby minimizing trauma to the layers of tissue disposed therebetween. Layers of tissue disposed between tissue contacting surfaces **320** and **620** will have a minimum thickness nearest knife channel **630** and a maximum thickness nearest outer walls **614**. In addition, anvil member **308** and staple cartridge **610** are dimensioned and arranged such that compressive forces applied to the layers of tissue are minimal thereby further reducing trauma to the layers of tissue.

Leg lengths of surgical fasteners **125c**, **125b**, and **125a** increase in a direction moving from inner walls **616** towards outer walls **614**. By providing surgical fasteners having increasing leg lengths along a plane that is orthogonal to inner walls **616**, the completed (i.e. formed) surgical fasteners join increasing thicknesses of tissue without unduly traumatizing the joined layers of tissue.

In a further embodiment, operative tool **606'** is illustrated in FIG. 13. Operative tool **606'** includes staple cartridge **610**, that was described in detail hereinabove with respect to FIG. 12, and anvil member **608**. Anvil member **608** includes a tissue contacting surface **620** formed from surfaces **632** and **636**. Surface **636** is substantially parallel to surface **622** and has a width dimension that is substantially similar to the width dimension of surface **622**. Surfaces **632** are tapered and connected to outer walls of anvil member **608** and extend inwards (i.e. towards the centerline of staple cartridge **610**) and downwards (i.e. towards tissue contacting surface **620**) thereby defining an angle. It is envisioned that the angle defined by tapered surfaces **632** will be substantially similar to the angle defined by surfaces **624**, but in an opposed direction. Thus, compressive forces applied to the layers of tissue will be further reduced thereby further reducing the trauma to layers of tissue disposed between surfaces **624** and **632**. As in the embodiment of FIG. 10, the maximum pressure applied to the layers of tissue will exist in the region along surface **622** while pressures applied to the layers of tissue will decrease uniformly along surfaces **624** towards outer walls **614**. Formation and location of surgical fasteners **125a-c** is substantially similar to that of the embodiment of FIG. 12 along with the attendant advantages.

In yet another embodiment, operative tool **706** is illustrated in FIG. 14. Staple cartridge **710** is similar to staple cartridge **610**. The differences between staple cartridges **610** and **710** will be discussed hereinafter. As in staple cartridge **610** (FIG. 12), staple cartridge **710** includes tissue contacting surface **720** formed from surfaces **722** and **724**. Surface **722** differs from surface **622** in that it has a width dimension sufficient to accommodate at least two rows of surgical fasteners. As in staple cartridge **610**, surfaces **724** are attached to outer edges of surface **722** and outer walls **714** to define angles. The interaction between staple cartridge **710** and anvil member **308** for capturing tissue and forming surgical fasteners is



## 15

substantially similar to the interaction between staple cartridge 610 and anvil member 308 and, for the sake of brevity, will not be repeated herein.

In a further embodiment, operative tool 706' is shown in FIG. 15 and includes staple cartridge 710, as described with respect to FIG. 14, and anvil member 708. Anvil member 708 includes a tissue contacting surface 720 formed from surfaces 732 and 736. Surface 736 is substantially parallel to surface 722 and has a width dimension that is substantially similar to the width dimension of surface 722. Surfaces 732 are tapered and connected to outer walls of anvil member 708 and extend inwards (i.e. towards the centerline of staple cartridge 710) and downwards (i.e. towards tissue contacting surface 720) thereby defining an angle. It is envisioned that the angle defined by tapered surfaces 732 will be substantially similar to the angle defined by surfaces 724, but in an opposed direction. Thus, compressive forces applied to the layers of tissue will be further reduced thereby further reducing the trauma to layers of tissue disposed between surfaces 724 and 732. As in the embodiment of FIG. 14, the maximum pressure applied to the layers of tissue will exist in the region along surface 722 while pressures applied to the layers of tissue will decrease uniformly along surfaces 724 towards outer walls 714. Formation and location of surgical fasteners 125a-c is substantially similar to that of the embodiment of FIG. 14 along with the attendant advantages.

In FIG. 15, an alternate embodiment of operative tool 706' is illustrated. Operative tool 706' includes staple cartridge 710, as discussed in detail hereinabove, and anvil member 708. Anvil member 708 includes a tissue contacting surface 720 formed from surfaces 732 and 736. Surface 736 is substantially parallel to surface 722 and has a width dimension that is substantially similar to a width dimension of surface 722. Surfaces 732 are tapered and connected to outer walls of anvil member 708 and extend inwards (i.e. towards centerline of staple cartridge 710) and downwards (i.e. towards tissue contacting surface 720) thereby defining an angle. It is envisioned that the angle defined by tapered surfaces 732 will be substantially similar to the angle defined by surfaces 724, but in an opposed direction. Thus, compressive forces applied to the layers of tissue will be further reduced, thereby further reducing the trauma to the layers of tissue disposed between surfaces 724 and 732. As in the embodiment of FIG. 14, the maximum pressure applied to the layers of tissue will exist in the region along surface 722 while pressures applied to the layers of tissue will decrease uniformly along surfaces 724 towards outer walls 714. Formation and location of surgical fasteners 125a-c is substantially similar to that of the embodiment of FIG. 14 along with the attendant advantages.

Turning now to FIG. 16, a cross-section of the resulting tissue interface, following the firing of staple cartridge 510', is shown. As seen in FIG. 16, the tissue interface has a substantially tapered profile. In particular, surgical fasteners 125a and 125b (i.e. the two rows of surgical fasteners furthest from knife cut line "C") serve to hold tissues "A" and "B" to one another while surgical fasteners 125c (i.e. the row of surgical fasteners closest to knife cut line "C") serve to provide the hemostasis. This resulting cross-section is also applicable to the firing of staple cartridges 610 and 710. When staple cartridge 510 is fired, surgical fasteners 125b and 125c (i.e. the two rows of surgical fasteners furthest from knife cut line "C") serve to hold tissues "A" and "B" to one another while surgical fasteners 125a (i.e. the row of surgical fasteners closest to knife cut line "C") serve to provide the hemostasis.

In a further embodiment of the present disclosure, as shown in FIGS. 8 and 10, operative tool 506' includes a wound closure assembly 50. Wound closure assembly 50

## 16

includes at least one storage device or reservoir 52 and at least one supply line 54. Supply line 54 fluidly couples reservoir 52 to staple cartridge 510' for delivering an amount of a wound closure material "W". In particular, supply line 54 delivers wound closure material "W" into knife channel 530 such that when surgical fasteners 125a-c are formed, wound closure material "W" migrates along the layers of tissue adjacent to tissue contacting surface 520 (i.e. the target site). By providing wound closure material "W" in combination with surgical fasteners 125a-c, the bond formed between the layers of tissue has improved strength.

Compression of reservoir 52 causes wound closure material "W" contained therein to be urged through supply line 54 and dispensed via knife channel 530. Preferably, wound closure material "W" is dispensed during the staple firing procedure so that wound closure material "W" is dispensed along the length of the staple line and/or a knife cut line. Although wound closure assembly is discussed and illustrated with respect to FIG. 10, it is contemplated that wound closure assembly 50 is adaptable for use with other disclosed embodiments of staple cartridge 510' (i.e. 510, 610, or 710). It is further contemplated that an additional reservoir may be included for wound closure materials formed by combining two substances or that reservoir 52 may include a plurality of internal chambers (shown in phantom) for storing quantities of substances to be combined to form wound closure material "W". Further still, wound closure assembly 50 may be included in surgical stapling apparatus 100 (FIG. 1) wherein at least one opening 56 is disposed in a wall of anvil shaft 110 for dispensing wound closure material "W".

It is envisioned that wound closure material "W" can include one or a combination of adhesives, hemostats, sealants. Surgical biocompatible wound closure materials which can be employed in or applied the surgical instruments, especially surgical staplers, include adhesives whose function is to attach or hold organs, tissues or structures, sealants to prevent fluid leakage, and hemostats to halt or prevent bleeding. Examples of adhesives which can be employed include protein derived, aldehyde-based adhesive materials, for example, the commercially available albumin/glutaraldehyde materials sold under the trade designation BioGlue™ by Cryolife, Inc., and cyanoacrylate-based materials sold under the trade designations Indermil™ and Derma Bond by Tyco Healthcare Group, LP and Ethicon Endosurgery, Inc., respectively. Examples of sealants, which can be employed, include fibrin sealants and collagen-based and synthetic polymer-based tissue sealants. Examples of commercially available sealants are synthetic polyethylene glycol-based, hydrogel materials sold under the trade designation CoSeal™ by Cohesion Technologies and Baxter International, Inc. Examples of hemostat materials, which can be employed, include fibrin-based, collagen-based, oxidized regenerated cellulose-based and gelatin-based topical hemostats. Examples of commercially available hemostat materials are fibrinogen-thrombin combination materials under sold the trade designations CoStasis™ by Tyco Healthcare Group, LP, and Tisseel™ sold by Baxter International, Inc. Hemostats herein include astringents, e.g., aluminum sulfate, and coagulants.

It is to be understood that the dispensing of wound closure material "W" can be as a fluid spray of any suitable volume, including a mist, applied temporarily, continuously, or continually. Particulate material, e.g. a fine powder is contemplated to be a fluid within the scope of this disclosure.

It is provided that a number of different wound closure materials "W" can be dispensed by wound closure assembly 50 or a combination of the number of different wound closure materials "W". The wound closure material dispensed by



wound closure assembly **50** can, for example, be an astringent, such as a sulfate of aluminum, which causes small blood vessels to close and helps the blood to coagulate. It is provided that wound closure material “W” can be an astringent 5 provided in the material commercially available under the trade designation No Nix Styptic Pencils from Requa™, Inc.

In addition, while each of the surgical stapling instruments described above and shown herein include tissue contacting surfaces having a stepped profile, it is envisioned that any of the surgical stapling instruments disclosed herein can have 10 tissue contacting surfaces having any one of a number of profiles including and not limited to angles, conical, tapered, arcuate and the like, as disclosed in commonly assigned U.S. patent application Ser. No. 10/411,686, filed on May 11, 2003, entitled “Surgical Stapling Apparatus Including an Anvil and Cartridge Each Having Cooperating Mating Surfaces,” currently assigned to Tyco Healthcare Group LP, the entire contents of which is incorporated herein by reference.

It will be understood that various modifications may be made to the embodiments of the presently disclosed surgical 20 stapling instruments. Therefore, the above description should not be construed as limiting, but merely as exemplifications of embodiments. Those skilled in the art will envision other modifications within the scope and spirit of the present disclosure.

What is claimed is:

**1.** An end effector for a surgical stapling instrument comprising:

a staple cartridge having a cross-sectional profile defined 30 by a first tissue contacting surface, a second tissue contacting surface, and a third surface, the first tissue contacting surface and the second tissue contacting surface defining respective first and second planes, the first and second planes being substantially parallel to each other and extending from a proximal portion of the staple cartridge to a distal portion of the staple cartridge, and the third surface connecting the first and second surfaces, the third surface defining a third plane that intersects the first and second planes;

an anvil arranged with the staple cartridge, the anvil and the cross-sectional profile of the staple cartridge defining a tissue compression gradient, the tissue compression gradient including a first value of tissue compression between the anvil and the first plane, and a second value of tissue compression between the anvil and the second plane, the first value of tissue compression different from the second value of tissue compression;

the cartridge having a first plurality of staples associated with the first tissue contacting surface and a second plurality of staples associated with the second surface, the size of the first plurality of staples being selected to correspond to the first tissue contacting surface and the size of the second plurality of staples being selected to correspond to the second tissue contacting surface.

**2.** The staple cartridge of claim **1**, wherein the first plurality of staples has a first leg length and the second plurality of staples has a second leg length that is different from the first leg length.

**3.** The staple cartridge of claim **1**, wherein the end effector is releasably attachable to a body of the surgical instrument.

**4.** The staple cartridge of claim **2**, wherein the first leg length is greater than the second leg length.

**5.** The staple cartridge of claim **1**, further including a knife channel extending longitudinally along the staple cartridge.

**6.** The staple cartridge of claim **5**, wherein the first plurality of staples has a first leg length and the second plurality of staples has a second leg length that is less than the first leg length, the second plurality of staples being disposed closer to the knife channel than the first plurality of staples.

**7.** The staple cartridge of claim **1**, wherein a length of the third surface defines a distance between the first plane of the first tissue contacting surface and the second plane of the second tissue contacting surface.

**8.** The staple cartridge of claim **5**, further including a knife disposed in the knife channel, the knife being movable longitudinally between the proximal portion of the staple cartridge and the distal portion of the staple cartridge.

**9.** The staple cartridge of claim **5**, wherein the knife channel is located adjacent the first tissue contacting surface.

\* \* \* \* \*