

US008297265B2

(12) **United States Patent**
McAlister et al.

(10) **Patent No.:** **US 8,297,265 B2**
(45) **Date of Patent:** **Oct. 30, 2012**

(54) **METHODS AND SYSTEMS FOR ADAPTIVELY COOLING COMBUSTION CHAMBERS IN ENGINES**

(75) Inventors: **Roy Edward McAlister**, Phoenix, AZ (US); **Melvin James Larsen**, Chandler, AZ (US); **Roy Edward McAlister**, legal representative, Chandler, AZ (US)

(73) Assignee: **McAlister Technologies, LLC**, Phoenix, AZ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/027,170**

(22) Filed: **Feb. 14, 2011**

(65) **Prior Publication Data**

US 2012/0037100 A1 Feb. 16, 2012

Related U.S. Application Data

(63) Continuation-in-part of application No. 12/961,461, filed on Dec. 6, 2010.

(60) Provisional application No. 61/304,403, filed on Feb. 13, 2010.

(51) **Int. Cl.**
F01P 7/14 (2006.01)
F01P 7/16 (2006.01)

(52) **U.S. Cl.** **123/578**

(58) **Field of Classification Search** 123/578,
123/575, 25 C, 25 K, 25 J, 25 Q
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,451,384 A 4/1923 Whyte
1,765,237 A 6/1930 King
2,255,203 A 9/1941 Wiegand

2,441,277 A 5/1948 Lamphere
2,721,100 A 10/1955 Bodine, Jr.
3,058,453 A 10/1962 May
3,060,912 A 10/1962 May
3,081,758 A 3/1963 May
3,243,335 A 3/1966 Faile
3,286,164 A 11/1966 De Huff
3,373,724 A 3/1968 Papst
3,520,961 A 7/1970 Suda et al.
3,594,877 A 7/1971 Suda et al.

(Continued)

FOREIGN PATENT DOCUMENTS

DE 3443022 A1 5/1986

(Continued)

OTHER PUBLICATIONS

Non-Final Office Action for U.S. Appl. No. 13/027,170; Applicant: McAlister et al.; Date of Mailing: Jan. 12, 2012; 10 pages.

(Continued)


Primary Examiner — Mahmoud Gimie

(74) *Attorney, Agent, or Firm* — Perkins Coie LLP

(57) **ABSTRACT**

The present disclosure is directed to various embodiments of systems and methods for cooling a combustion chamber of an engine. One method includes introducing fuel into the combustion chamber of an engine having an energy transfer device that moves through an intake stroke, a compression stroke, a power stroke, and an exhaust stroke. The method further includes monitoring a temperature of the combustion chamber. When the temperature reaches a predetermined value, the method also includes introducing coolant into the combustion chamber only during at least one of the power stroke and the exhaust stroke of the energy transfer device.

20 Claims, 10 Drawing Sheets



U.S. PATENT DOCUMENTS							
3,608,050	A	9/1971	Carman et al.	5,456,241	A	10/1995	Ward
3,689,293	A	9/1972	Beall	5,475,772	A	12/1995	Hung et al.
3,926,169	A	12/1975	Leshner et al.	5,497,744	A	3/1996	Nagaosa et al.
3,931,438	A	1/1976	Beall et al.	5,517,961	A	5/1996	Ward
3,960,995	A	6/1976	Kourkene	5,531,199	A	7/1996	Bryant et al.
3,976,039	A	8/1976	Henault	5,549,746	A	8/1996	Scott et al.
3,997,352	A	12/1976	Beall	5,568,801	A	10/1996	Paterson et al.
4,020,803	A	5/1977	Thuren et al.	5,584,490	A	12/1996	Inoue et al.
4,066,046	A	1/1978	McAlister	5,588,299	A	12/1996	DeFreitas
4,095,580	A	6/1978	Murray et al.	5,605,125	A	2/1997	Yaoita
4,122,816	A	10/1978	Fitzgerald et al.	5,607,106	A	3/1997	Bentz et al.
4,135,481	A	1/1979	Resler, Jr.	5,608,832	A	3/1997	Pfandl et al.
4,183,467	A	1/1980	Sheraton et al.	5,662,389	A	9/1997	Truglio et al.
4,203,393	A	5/1980	Giardini	5,676,026	A	10/1997	Tsuboi et al.
4,293,188	A	10/1981	McMahon	5,694,761	A	12/1997	Griffin, Jr.
4,330,732	A	5/1982	Lowther	5,699,253	A	12/1997	Puskorius et al.
4,332,223	A	6/1982	Dalton	5,702,761	A	12/1997	DiChiara, Jr. et al.
4,364,342	A	12/1982	Asik	5,704,321	A	1/1998	Suckewer et al.
4,368,707	A	1/1983	Leshner et al.	5,704,553	A	1/1998	Wieczorek et al.
4,377,455	A	3/1983	Kadija et al.	5,714,680	A	2/1998	Taylor et al.
4,381,740	A	5/1983	Crocker	5,715,788	A	2/1998	Tarr et al.
4,382,189	A	5/1983	Wilson	5,738,818	A	4/1998	Atmur et al.
4,469,160	A	9/1984	Giamei	5,745,615	A	4/1998	Atkins et al.
4,483,485	A	11/1984	Kamiya et al.	5,746,171	A	5/1998	Yaoita
4,511,612	A	4/1985	Huther et al.	5,767,026	A	6/1998	Kondoh et al.
4,528,270	A	7/1985	Matsunaga	5,806,581	A	9/1998	Haasch et al.
4,536,452	A	8/1985	Stempin et al.	5,816,217	A	10/1998	Wong
4,567,857	A	2/1986	Houseman et al.	5,853,175	A	12/1998	Udagawa
4,574,037	A	3/1986	Samejima et al.	5,863,326	A	1/1999	Nause et al.
4,677,960	A	7/1987	Ward	5,876,659	A	3/1999	Yasutomi et al.
4,684,211	A	8/1987	Weber et al.	5,915,272	A	6/1999	Foley et al.
4,688,538	A	8/1987	Ward et al.	5,930,420	A	7/1999	Atkins et al.
4,716,874	A	1/1988	Hilliard et al.	5,941,207	A	8/1999	Anderson et al.
4,733,646	A	3/1988	Iwasaki	5,947,091	A	9/1999	Krohn et al.
4,736,718	A	4/1988	Linder	5,975,032	A	11/1999	Iwata
4,742,265	A	5/1988	Giachino et al.	6,015,065	A	1/2000	McAlister
4,760,818	A	8/1988	Brooks et al.	6,017,390	A	1/2000	Charych et al.
4,760,820	A	8/1988	Tozzi	6,026,568	A	2/2000	Atmur et al.
4,774,914	A	10/1988	Ward	6,029,627	A	2/2000	VanDyne
4,774,919	A	10/1988	Matsuo et al.	6,042,028	A	3/2000	Xu
4,777,925	A	10/1988	LaSota	6,062,498	A	5/2000	Klopper
4,834,033	A	5/1989	Larsen	6,081,183	A	6/2000	Mading et al.
4,841,925	A	6/1989	Ward	6,085,990	A	7/2000	Augustin
4,922,883	A	5/1990	Iwasaki	6,092,501	A	7/2000	Matayoshi et al.
4,932,263	A	6/1990	Wlodarczyk	6,092,507	A	7/2000	Bauer et al.
4,967,708	A	11/1990	Linder et al.	6,093,338	A	7/2000	Tani et al.
4,977,873	A	12/1990	Cherry et al.	6,102,303	A	8/2000	Bright et al.
4,982,708	A	1/1991	Stutzenberger	6,131,607	A	10/2000	Cooke
5,034,852	A	7/1991	Rosenberg	6,138,639	A	10/2000	Hiraya et al.
5,035,360	A	7/1991	Green et al.	6,155,212	A	12/2000	McAlister
5,036,669	A	8/1991	Earleson et al.	6,157,011	A	12/2000	Lai
5,055,435	A	10/1991	Hamanaka et al.	6,173,913	B1	1/2001	Shafer et al.
5,056,496	A	10/1991	Morino et al.	6,185,355	B1	2/2001	Hung
5,072,617	A	12/1991	Weiss	6,189,522	B1	2/2001	Moriya
5,076,223	A	12/1991	Harden et al.	6,253,728	B1	7/2001	Matayoshi et al.
5,095,742	A	3/1992	James et al.	6,267,307	B1	7/2001	Pontoppidan
5,107,673	A	4/1992	Sato et al.	6,281,976	B1	8/2001	Taylor et al.
5,109,817	A	5/1992	Cherry	6,335,065	B1	1/2002	Steinlage et al.
5,131,376	A	7/1992	Ward et al.	6,338,445	B1	1/2002	Lambert et al.
5,150,682	A	9/1992	Magnet	6,340,015	B1	1/2002	Benedikt et al.
5,193,515	A	3/1993	Oota et al.	6,378,485	B2	4/2002	Elliott
5,207,208	A	5/1993	Ward	6,386,178	B1	5/2002	Rauch
5,211,142	A	5/1993	Matthews et al.	6,446,597	B1	9/2002	McAlister
5,220,901	A	6/1993	Morita et al.	6,453,660	B1	9/2002	Johnson et al.
5,222,481	A	6/1993	Morikawa	6,455,173	B1	9/2002	Marijnissen et al.
5,267,601	A	12/1993	Dwivedi	6,478,007	B2	11/2002	Miyashita et al.
5,297,518	A	3/1994	Cherry	6,483,311	B1	11/2002	Ketterer et al.
5,305,360	A	4/1994	Remark et al.	6,490,391	B1	12/2002	Zhao et al.
5,329,606	A	7/1994	Andreassen	6,501,875	B2	12/2002	Zhao et al.
5,377,633	A	1/1995	Wakeman	6,503,584	B1	1/2003	McAlister
5,390,546	A	2/1995	Wlodarczyk	6,506,336	B1	1/2003	Beall et al.
5,392,745	A	2/1995	Beck	6,516,114	B2	2/2003	Zhao et al.
5,394,838	A	* 3/1995	Chandler 123/25 C	6,532,315	B1	3/2003	Hung et al.
5,394,852	A	3/1995	McAlister	6,536,405	B1	3/2003	Rieger et al.
5,421,195	A	6/1995	Wlodarczyk	6,542,663	B1	4/2003	Zhao et al.
5,421,299	A	6/1995	Cherry	6,543,700	B2	4/2003	Jameson et al.
5,435,286	A	7/1995	Carroll, III et al.	6,549,713	B1	4/2003	Pi et al.
5,439,532	A	8/1995	Fraas	6,550,458	B2	4/2003	Yamakado et al.
				6,556,746	B1	4/2003	Zhao et al.

US 8,297,265 B2

6,561,168 B2	5/2003	Hokao et al.	7,404,395 B2	7/2008	Yoshimoto
6,567,599 B2	5/2003	Hung	7,409,929 B2	8/2008	Miyahara et al.
6,571,035 B1	5/2003	Pi et al.	7,418,940 B1	9/2008	Yi et al.
6,578,775 B2	6/2003	Hokao	7,481,043 B2	1/2009	Hirata et al.
6,583,901 B1	6/2003	Hung	7,484,369 B2	2/2009	Myhre
6,584,244 B2	6/2003	Hung	7,513,222 B2	4/2009	Orlosky
6,585,171 B1	7/2003	Boecking	7,527,041 B2	5/2009	Wing et al.
6,587,239 B1	7/2003	Hung	7,540,271 B2	6/2009	Stewart et al.
6,615,810 B2	9/2003	Funk et al.	7,554,250 B2	6/2009	Kadotani et al.
6,615,899 B1	9/2003	Woodward et al.	7,588,012 B2	9/2009	Gibson et al.
6,621,964 B2	9/2003	Quinn et al.	7,625,531 B1	12/2009	Coates et al.
6,647,948 B2	11/2003	Kyuuma et al.	7,626,315 B2	12/2009	Nagase
6,663,027 B2	12/2003	Jameson et al.	7,628,137 B1	12/2009	McAlister
6,672,277 B2	1/2004	Yasuoka et al.	7,650,873 B2	1/2010	Hofbauer et al.
6,700,306 B2	3/2004	Nakamura et al.	7,703,775 B2	4/2010	Matsushita et al.
6,705,274 B2	3/2004	Kubo	7,707,832 B2	5/2010	Commaret et al.
6,719,224 B2	4/2004	Enomoto et al.	7,714,483 B2	5/2010	Hess et al.
6,722,340 B1	4/2004	Sukegawa et al.	7,728,489 B2	6/2010	Heinz et al.
6,722,840 B2	4/2004	Fujisawa et al.	7,849,833 B2	12/2010	Toyoda
6,725,826 B2	4/2004	Esteghlal	7,880,193 B2	2/2011	Lam
6,745,744 B2	6/2004	Suckewer et al.	7,898,258 B2	3/2011	Neuberth et al.
6,748,918 B2	6/2004	Rieger et al.	7,918,212 B2	4/2011	Verdejo et al.
6,749,043 B2	6/2004	Brown et al.	7,938,102 B2	5/2011	Sherry
6,756,140 B1	6/2004	McAlister	7,942,136 B2	5/2011	Lepsch et al.
6,763,811 B1	7/2004	Tamol, Sr.	8,069,836 B2	12/2011	Ehresman
6,776,352 B2	8/2004	Jameson	2002/0046729 A1	4/2002	Kyuuma et al.
6,796,516 B2	9/2004	Maier et al.	2002/0070267 A1	6/2002	Okamura et al.
6,799,513 B2	10/2004	Schafer	2002/0084793 A1	7/2002	Hung et al.
6,811,103 B2	11/2004	Gurich et al.	2002/0131171 A1	9/2002	Hung
6,814,313 B2	11/2004	Petrone et al.	2002/0131666 A1	9/2002	Hung et al.
6,832,472 B2	12/2004	Huang et al.	2002/0131673 A1	9/2002	Hung
6,832,588 B2	12/2004	Herden et al.	2002/0131674 A1	9/2002	Hung
6,845,920 B2	1/2005	Sato et al.	2002/0131686 A1	9/2002	Hung
6,851,413 B1	2/2005	Tamol, Sr.	2002/0131706 A1	9/2002	Hung
6,854,438 B2	2/2005	Hilger et al.	2002/0131756 A1	9/2002	Hung
6,883,490 B2	4/2005	Jayne	2002/0141692 A1	10/2002	Hung
6,892,971 B2	5/2005	Rieger et al.	2002/0150375 A1	10/2002	Hung et al.
6,898,355 B2	5/2005	Johnson et al.	2002/0151113 A1	10/2002	Hung et al.
6,899,076 B2	5/2005	Funaki et al.	2002/0166536 A1	11/2002	Hitomi et al.
6,904,893 B2	6/2005	Hotta et al.	2003/0012985 A1	1/2003	McAlister
6,912,998 B1	7/2005	Rauznitz et al.	2003/0042325 A1	3/2003	D'Arrigo
6,925,983 B2	8/2005	Herden et al.	2003/0127531 A1	7/2003	Hohl
6,940,213 B1	9/2005	Heinz et al.	2004/0008989 A1	1/2004	Hung
6,954,074 B2	10/2005	Zhu et al.	2004/0256495 A1	12/2004	Baker et al.
6,955,165 B2	10/2005	Liu	2005/0045146 A1	3/2005	McKay et al.
6,959,693 B2 *	11/2005	Oda 123/431	2005/0045148 A1	3/2005	Katsuragawa et al.
6,976,683 B2	12/2005	Eckert et al.	2005/0098663 A1	5/2005	Ishii
6,984,305 B2	1/2006	McAlister	2005/0255011 A1	11/2005	Greathouse et al.
6,993,960 B2	2/2006	Benson	2005/0257776 A1	11/2005	Bonutti
6,994,073 B2	2/2006	Tozzi et al.	2006/0005738 A1	1/2006	Kumar
7,007,658 B1	3/2006	Cherry et al.	2006/0005739 A1	1/2006	Kumar
7,007,661 B2	3/2006	Warlick	2006/0016916 A1	1/2006	Petrone et al.
7,013,863 B2	3/2006	Shiraishi et al.	2006/0037563 A1 *	2/2006	Raab et al. 123/25 C
7,025,358 B2	4/2006	Ueta et al.	2006/0102140 A1	5/2006	Sukegawa et al.
7,032,845 B2	4/2006	Dantes et al.	2006/0108452 A1	5/2006	Anzinger et al.
7,070,126 B2	7/2006	Shinogle	2006/0169244 A1	8/2006	Allen
7,073,480 B2	7/2006	Shiraishi et al.	2007/0142204 A1	6/2007	Park et al.
7,077,108 B2	7/2006	Fujita et al.	2007/0189114 A1	8/2007	Reiner et al.
7,077,379 B1	7/2006	Taylor	2007/0277775 A1 *	12/2007	Orlosky 123/25 C
7,086,376 B2	8/2006	McKay	2007/0283927 A1	12/2007	Fukumoto et al.
7,104,246 B1	9/2006	Gagliano et al.	2008/0072871 A1	3/2008	Vogel et al.
7,104,250 B1	9/2006	Yi et al.	2008/0081120 A1	4/2008	Van Ooij et al.
7,121,253 B2	10/2006	Shiraishi et al.	2008/0098984 A1	5/2008	Sakamaki
7,131,426 B2	11/2006	Ichinose et al.	2008/0103672 A1	5/2008	Ueda et al.
7,137,382 B2	11/2006	Zhu et al.	2009/0078798 A1	3/2009	Gruendl et al.
7,140,347 B2	11/2006	Suzuki et al.	2009/0093951 A1	4/2009	McKay et al.
7,140,353 B1	11/2006	Rauznitz et al.	2009/0204306 A1	8/2009	Goeke et al.
7,140,562 B2	11/2006	Holzgreffe et al.	2009/0264574 A1	10/2009	Van Ooij et al.
7,204,133 B2	4/2007	Benson et al.	2010/0020518 A1	1/2010	Bustamante
7,228,840 B2	6/2007	Sukegawa et al.	2010/0043758 A1	2/2010	Caley
7,249,578 B2	7/2007	Fricke et al.	2010/0077986 A1 *	4/2010	Chen 123/25 C
7,255,290 B2	8/2007	Bright et al.	2010/0108023 A1	5/2010	McAlister
7,272,487 B2	9/2007	Christen et al.	2010/0183993 A1	7/2010	McAlister
7,278,392 B2	10/2007	Zillmer et al.	2011/0036309 A1	2/2011	McAlister
7,305,971 B2	12/2007	Fujii	2011/0042476 A1	2/2011	McAlister
7,309,029 B2	12/2007	Boecking	2011/0048371 A1	3/2011	McAlister
7,340,118 B2	3/2008	Wlodarczyk et al.	2011/0048374 A1	3/2011	McAlister
7,367,319 B2	5/2008	Kuo et al.	2011/0048381 A1	3/2011	McAlister
7,386,982 B2	6/2008	Runkle et al.	2011/0056458 A1	3/2011	McAlister

2011/0057058 A1 3/2011 McAlister
 2011/0132319 A1 6/2011 McAlister
 2011/0134049 A1 6/2011 Lin et al.

FOREIGN PATENT DOCUMENTS

EP 392594 A2 10/1990
 EP 671555 A1 9/1995
 EP 1972606 A1 9/2008
 GB 1038490 A 8/1966
 JP 61-023862 A 2/1986
 JP 02-259268 A 10/1990
 JP 08-049623 A 2/1996
 JP 2008-334077 12/1996
 JP 2004-324613 A 11/2004
 KR 2007-0026296 A 3/2007
 KR 2008-0073635 A 8/2008
 WO WO-2008-017576 A1 2/2008

OTHER PUBLICATIONS

International Search Report and Written Opinion for PCT Application No. PCT/US2011/024797; Applicant: McAlister Technologies, LLC; Date of Mailing: Feb. 14, 2011; 8 pages.

"Ford DIS/EDIS "Waste Spark" Ignition System." Accessed: Jul. 15, 2010. Printed: Jun. 8, 2011. <http://rockledge.home.comcast.net/~rockledge/RangerPictureGallery/DIS_EDIS.htm>. pp. 1-4.

"PdV's Custom Data Acquisition Systems Capabilities." PdV Consulting. Accessed: Jun. 28, 2010. Printed: May 16, 2011. <<http://www.pdvconsult.com/capabilities%20-%20daqsys.html>>. pp. 1-10.

"Piston motion equations." Wikipedia, the Free Encyclopedia. Published: Jul. 4, 2010. Accessed: Aug. 7, 2010. Printed: Aug. 7, 2010. <<http://en.wikipedia.org/wiki/Dopant>>. pp. 1-6.

"Piston Velocity and Acceleration." EPI, Inc. Accessed: Jun. 28, 2010. Printed: May 16, 2011. <http://www.epi-eng.com/piston_engine_technology/piston_velocity_and_acceleration.htm>. pp. 1-3.

"SmartPlugs—Aviation." SmartPlugs.com. Published: Sep. 2000. Accessed: May 31, 2011. <<http://www.smartplugs.com/news/aeronews0900.htm>>. pp. 1-3.

Bell et al. "A Super Solar Flare." NASA Science. Published: May 6, 2008. Accessed: May 17, 2011. <http://science.nasa.gov/science-news/science-at-nasa/2008/06may_carringtonflare/>. pp. 1-5.

Birchenough, Arthur G. "A Sustained-arc Ignition System for Internal Combustion Engines." Nasa Technical Memorandum (NASA TM-73833). Lewis Research Center. Nov. 1977. pp. 1-15.

Britt, Robert Roy. "Powerful Solar Storm Could Shut Down U.S. for Months—Science News | Science & Technology | Technology News—FOXNews.com." FoxNews.com, Published: Jan. 9, 2009. Accessed: May 17, 2011. <<http://www.foxnews.com/story/0,2933,478024,00.html>>. pp. 1-2.

Brooks, Michael. "Space Storm Alert: 90 Seconds from Catastrophe." NewScientist. Mar. 23, 2009. pp. 1-7.

Doggett, William. "Measuring Internal Combustion Engine In-Cylinder Pressure with LabVIEW." National Instruments. Accessed: Jun. 28, 2010. Printed: May 16, 2011. <<http://sine.ni.com/cs/app/doc/p/id/cs-217>>. pp. 1-2.

Hodgin, Rick. "NASA Studies Solar Flare Dangers to Earth-based Technology." TG Daily. Published: Jan. 6, 2009. Accessed: May 17, 2011. <<http://www.tgdaily.com/trendwatch/40830-nasa-studies-solar-flare-dangers-to-earth-based-technology>>. pp. 1-2.

InfraTec GmbH. "Evaluation Kit for FPI Detectors | Datasheet—Detector Accessory." 2009. pp. 1-2.

International Search Report and Written Opinion for Application No. PCT/US2009/067044; Applicant: McAlister Technologies, LLC.; Date of Mailing: Apr. 14, 2010 (11 pages).

International Search Report and Written Opinion for Application No. PCT/US2010/002076; Applicant: McAlister Technologies, LLC.; Date of Mailing: Apr. 29, 2011 (8 pages).

International Search Report and Written Opinion for Application No. PCT/US2010/002077; Applicant: McAlister Technologies, LLC.; Date of Mailing: Apr. 29, 2011 (8 pages).

International Search Report and Written Opinion for Application No. PCT/US2010/002078; Applicant: McAlister Technologies, LLC.; Date of Mailing: Dec. 17, 2010 (9 pages).

International Search Report and Written Opinion for Application No. PCT/US2010/042812; Applicant: McAlister Technologies, LLC.; Date of Mailing: May 13, 2011 (9 pages).

International Search Report and Written Opinion for Application No. PCT/US2010/042815; Applicant: McAlister Technologies, LLC.; Date of Mailing: Apr. 29, 2011 (10 pages).

International Search Report and Written Opinion for Application No. PCT/US2010/042817; Applicant: McAlister Technologies, LLC.; Date of Mailing: Apr. 29, 2011 (8 pages).

Lewis Research Center. "Fabry-Perot Fiber-Optic Temperature Sensor." NASA Tech Briefs. Published: Jan. 1, 2009. Accessed: May 16, 2011. <<http://www.techbriefs.com/content/view/2114/32/>>.

Pall Corporation, Pall Industrial Hydraulics. "Increase Power Output and Reduce Fugitive Emissions by Upgrading Hydrogen Seal Oil System Filtration." 2000. pp. 1-4.

Riza et al. "All-Silicon Carbide Hybrid Wireless-Wired Optics Temperature Sensor Network Basic Design Engineering for Power Plant Gas Turbines." International Journal of Optomechatronics, vol. 4, Issue 1. Jan. 2010. pp. 83-91.

Riza et al. "Hybrid Wireless-Wired Optical Sensor for Extreme Temperature Measurement in Next Generation Energy Efficient Gas Turbines." Journal of Engineering for Gas Turbines and Power, vol. 132, Issue 5. May 2010. pp. 051601-1-51601-11.

Salib et al. "Role of Parallel Reformable Bonds in the Self-Healing of Cross-Linked Nanogel Particles." Langmuir, vol. 27, Issue 7. 2011. pp. 3991-4003.

Erjavec, Jack. "Automotive Technology: a Systems Approach, vol. 2." Thomson Delmar Learning. Clifton Park, NY. 2005. p. 845.

Hollembek, Barry. "Automotive Fuels & Emissions." Thomson Delmar Learning. Clifton Park, NY. 2005. p. 298.

International Search Report and Written Opinion for Application No. PCT/US2010/002080; Applicant: McAlister Technologies, LLC.; Date of Mailing: Jul. 7, 2011 (8 pages).

International Search Report and Written Opinion for Application No. PCT/US2010/054361; Applicant: McAlister Technologies, LLC.; Date of Mailing: Oct. 27, 2010, 9 pages.

International Search Report and Written Opinion for Application No. PCT/US2010/054364; Applicant: McAlister Technologies, LLC.; Date of Mailing: Oct. 27, 2010, 8 pages.

International Search Report and Written Opinion for Application No. PCT/US2010/059146; Applicant: McAlister Technologies, LLC.; Date of Mailing: Dec. 6, 2010, 11 pages.

International Search Report and Written Opinion for Application No. PCT/US2010/059147; Applicant: McAlister Technologies, LLC.; Date of Mailing: Dec. 6, 2010, 11 pages.

* cited by examiner




Fig. 2A




Fig. 2B




Fig. 2C




Fig. 2D




Fig. 2E




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7

1

**METHODS AND SYSTEMS FOR
ADAPTIVELY COOLING COMBUSTION
CHAMBERS IN ENGINES**

CROSS-REFERENCE TO RELATED
APPLICATIONS

The present application claims priority to and the benefit of U.S. Patent Application No. 61/304,403, filed on Feb. 13, 2010 and titled FULL SPECTRUM ENERGY AND RESOURCE INDEPENDENCE. The present application is a continuation in part of U.S. patent application Ser. No. 12/961,461, filed on Dec. 6, 2010 and titled INTEGRATED FUEL INJECTOR IGNITERS CONFIGURED TO INJECT MULTIPLE FUELS AND/OR COOLANTS AND ASSOCIATED METHODS OF USE AND MANUFACTURE. Each of these applications is incorporated herein by reference in its entirety. To the extent the foregoing application and/or any other materials incorporated herein by reference conflict with the disclosure presented herein, the disclosure herein controls.

TECHNICAL FIELD

The following disclosure relates generally to methods and systems for cooling combustion chambers of internal combustion engines.

BACKGROUND

Fuel injection systems are typically used to inject a fuel spray into an inlet manifold or a combustion chamber of an engine. Fuel injection systems have become the primary fuel delivery system used in automotive engines, having almost completely replaced carburetors since the late 1980s. Conventional direct-injection fuel metering systems are typically connected to a pressurized fuel supply, and fuel injectors used in these fuel injection systems generally inject or otherwise release the pressurized fuel into the combustion chamber at a specific time relative to the power stroke of the engine. In many engines, and particularly in large engines, the size of the bore or port through which the fuel injector enters the combustion chamber is small. This small port accordingly limits the size of the components that can be used to actuate or otherwise inject fuel from the injector. Moreover, such engines also generally have crowded intake and exhaust valve train mechanisms, further restricting the space available for components of these fuel injection systems.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic diagram of a system configured in accordance with an embodiment of the disclosure.

FIGS. 2A-2E are a series of schematic diagrams of an operational cycle of the system of FIG. 1 configured in accordance with embodiments of the disclosure.

FIG. 3 is a schematic diagram of a system configured in accordance with another embodiment of the disclosure.

FIG. 4 is a flow diagram of a method for cooling a combustion chamber of an engine in accordance with an embodiment of the disclosure.

FIGS. 5 and 6 are schematic diagrams of systems configured in accordance with additional embodiments of the disclosure.

FIG. 7 is a flow diagram of a method for cooling one or more electrical generating components and for cooling a

2

combustion chamber of an engine in accordance with embodiments of the disclosure.

DETAILED DESCRIPTION

The present disclosure describes methods and systems for cooling combustion chambers of internal combustion engines. For example, several of the embodiments described below are directed generally to systems and methods that can inject a first fuel into a combustion chamber and adaptively a second fuel or coolant based on combustion chamber conditions. The second fuel or coolant produces cooling in the combustion chamber. Certain details are set forth in the following description and in FIGS. 1-7 to provide a thorough understanding of various embodiments of the disclosure. However, other details describing well-known structures and systems often associated with internal combustion engines, injectors, igniters, and/or other aspects of combustion systems are not set forth below to avoid unnecessarily obscuring the description of various embodiments of the disclosure. Thus, it will be appreciated that several of the details set forth below are provided to describe the following embodiments in a manner sufficient to enable a person skilled in the relevant art to make and use the disclosed embodiments. Several of the details and advantages described below, however, may not be necessary to practice certain embodiments of the disclosure.

Many of the details, dimensions, angles, shapes, and other features shown in the Figures are merely illustrative of particular embodiments of the disclosure. Accordingly, other embodiments can have other details, dimensions, angles, and features without departing from the spirit or scope of the present disclosure. In addition, those of ordinary skill in the art will appreciate that further embodiments of the disclosure can be practiced without several of the details described below. Furthermore, many features of the disclosure illustrated in the Figures are shown schematically.

Reference throughout this specification to “one embodiment” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the present disclosure. Thus, the occurrences of the phrases “in one embodiment” and “in an embodiment” in various places throughout this specification are not necessarily all referring to the same embodiment. Furthermore, the particular features, structures, or characteristics described with reference to a particular embodiment may be combined in any suitable manner in one or more other embodiments.

1. Systems and Methods for Adaptively Cooling Combustion Chambers

FIG. 1 is a schematic diagram of a system 100 configured in accordance with an embodiment of the disclosure for adaptively cooling or limiting the peak operating temperature of a combustion chamber 106. In the illustrated embodiment, the system 100 includes a portion of an engine 101 (e.g., a two or four stroke engine) having at least one reciprocating energy transfer device or piston 108 that moves at least partially within the corresponding combustion chamber 106. The system 100 also includes one or more air flow valves 110 (identified individually as a first valve 110a and a second valve 110b) that are operable to allow air flow to enter and exhaust gases to exit the combustion chamber 106. For example, the first valve 110a can be an intake valve that allows inlet air flow to enter the combustion chamber 106 via a first or intake passage 109a, and the second valve 110b can be an exhaust valve that allows air flow and/or exhaust to exit the combustion chamber 106 via a second or exhaust passage 109b.

Although two valves are shown in FIG. 1A, one of ordinary skill in the art will appreciate that the system can include more than two valves **110**.

The system **100** further includes an integrated injector igniter **102** (“injector **102**”) that is configured to inject fuel and/or coolant into the combustion chamber **106**, as well as to ignite the fuel and/or coolant in the combustion chamber **106**. In certain embodiments, the injector can include any of the features of the injectors described in U.S. patent application Ser. No. 12/961,461, entitled “INTEGRATED FUEL INJECTOR IGNITERS CONFIGURED TO INJECT MULTIPLE FUELS AND/OR COOLANTS AND ASSOCIATED METHODS OF USE AND MANUFACTURE,” filed Dec. 6, 2010, and incorporated herein by reference in its entirety. In other embodiments, the injector **102** can include the features of any of the integrated injector igniters described in the co-pending patent applications incorporated by reference in their entireties above. For example, the injector **102** can include one or more integrated ignition features (e.g., for initiating a spark, plasma, or other suitable igniting event). According to embodiments of the present disclosure and as described in detail below, the injector **102** can also adaptively inject two or more fuels, coolants, or combinations of fuels and coolants into the combustion chamber **106** during operation. As used herein, the term coolant can include any temperature controlling fluid (e.g., gas or liquid) that produces cooling in the combustion chamber **106** (e.g., lowering a temperature in the combustion chamber and/or transferring heat away from components of the combustion chamber **106**). In one embodiment, for example, a coolant can include non-combusting fluid. In other embodiments, however, a coolant can include a fuel that ignites and/or combusts at a lower temperature than another fuel that ignites and/or combusts in combustion chamber **106** prior to the injection of the coolant. In still further embodiments, a coolant can be a hydrogenous coolant (e.g., a hydrogen containing coolant). As described in detail below, the injector **102** can be controlled to adaptively adjust the pattern and/or frequency of the fuel/coolant injections based on properties in the combustion chamber **106**.

In the embodiment shown in FIG. 1, the system **100** also includes a number of sensing and/or computing devices for adaptively controlling the fuel and/or coolant delivery and ignition in the combustion chamber **106**. For example, the injector **102** can include one or more sensors that detect and communicate combustion chamber properties. More specifically, the injector **102** can include one or more fiber optic elements located on a distal end portion of the injector **102** exposed to an interface of the combustion chamber **106**. As described in accordance with various embodiments herein, these sensors can also include various means and devices for measuring combustion chamber temperature and pressure including utilization of high frequency strobe of infrared IR, visible, and/or UV light transmitted by the fiber optic portion of the injector **102**. For example, the means for measuring combustion chamber temperature and/or pressure can include a Fabry-Perot interferometer. In other embodiments, the temperature and/or pressure profiles within the combustion chamber **106** can be determined as a function of time or other parameters that can be measured using other types of suitable temperature and/or pressure sensors known in the art. Such temperature sensors can include, for example, various types of thermocouple, resistive, and IR devices, and such pressure sensors can include, for example, various types of transducer and piezoelectric devices.

In the illustrated embodiment, temperature and/or pressure data (or other combustion chamber properties) from the combustion chamber **106** can be processed by an optional sensing

module **112** (shown in broken lines). Such processing can include, for example, filtering, converting, and/or formatting the data before transmitting it to a computer **114**. The computer **114** can include one or more processors **116** for analyzing the data from the combustion chamber **106** to determine when and how to change injection and ignition characteristics from the injector **102**. The results of the processing analysis can be stored in local memory **118** or an associated database **119**.

According to additional features of the illustrated embodiment, the system **100** also includes a fuel source or fuel storage **120** that is operably coupled to the injector **102** to deliver fuel and/or coolant to the combustion chamber **106** via the injector **102**. The fuel source **120** can store or otherwise provide access to one or more fuels *F* and/or one or more coolants *C*. Although the fuel source **120** is schematically illustrated with multiple fuels *F* and coolants *C*, one of ordinary skill in the art will appreciate that different fuels and/or coolants can be stored in separate containers. The fuel source **120** is also operably coupled to the computer **116** and can optionally include one or more processors **122** for selectively controlling the distribution of fuels *F* and/or coolants *C* to the injector **102**.

Operation of the system **100** is described in detail below with reference to FIGS. 2A-2E. More specifically, FIGS. 2A-2E are a series of schematic diagrams of a portion of the system **100** of FIG. 1 illustrating an operational cycle including, for example, an intake stroke, a compression stroke, a power stroke, and an exhaust stroke. Referring first to FIG. 2A, FIG. 2A illustrates a direct-injection system **100** during an intake stroke of the cycle. During the intake stroke, the piston **108** begins at a top dead center (“TDC”) position where the piston **108** creates a minimum volume of the combustion chamber (not shown in FIG. 2A). Fuel may be injected to produce a relatively homogeneous charge as the piston **108** moves away from TDC to expand the volume of the combustion chamber **106** (e.g., in the direction of arrow **232**), the system **100** draws intake air flow **230** into the combustion chamber **106**. Production of a relatively stratified charge of combustible fuel and air mixture is provided by fuel injection during the compression and/or power stroke that follows. More specifically, during the intake stroke the second valve **110b** remains closed and the first valve **110a** is at least partially opened to allow the intake air flow **230** to enter the combustion chamber **106** as the piston **108** moves away from TDC.

In certain embodiments, the system **100** is configured such that the valves **110** maintain an ambient pressure or a positive pressure in the combustion chamber **106** prior to a later combustion event. For instance, the system **100** can operate the intake stroke without throttling or otherwise impeding the intake air flow **230** into the combustion chamber **106** such that a vacuum is not created in the combustion chamber **106** during the intake stroke. Due to the ambient or positive pressure in the combustion chamber **106**, an excess oxidant can form an insulative barrier adjacent to the surfaces of the combustion chamber (e.g., the cylinder walls, piston, engine head, etc.). As the piston **108** continues in the direction of arrow **232** and approaches or reaches bottom dead center (“BDC”), which is when the piston **108** is at the bottom of its stroke thereby resulting in a maximum volume of the combustion chamber **106**, the first valve **110a** closes to seal the combustion chamber **106**.

In certain embodiments, the system **100** can further be configured to introduce fuel *F* into the combustion chamber **106** during the intake, compression, power, or exhaust strokes. For example, during predetermined operating condi-

5

tions, such as a high load requirement or a high torque requirement, the injector **102** can dispense fuel **F** into the combustion chamber **106** during the intake of the air flow **230**. Moreover, when introducing the fuel **F** the injector **102** can introduce a layered or stratified charge of the fuel **F**, into the combustion chamber **106**, as well as other desired fuel distribution patterns and injection frequencies, as disclosed, for example, in the applications incorporated by reference above. In certain embodiments, introducing the fuel **F** into the combustion chamber **106** results in a homogenous air fuel mixture at combustion. In still further embodiments, however, the system **100** can operate such that the injector **102** meters fuel into the combustion chamber to produce a stratified charge during the compression and/or power stroke of the piston **108**.

Referring next to FIG. 2B, FIG. 2B illustrates the system **100** during a compression portion or compression stroke of the cycle. During the compression stroke, the valves **110** are closed and the piston **108** moves away from BDC toward TDC (e.g., in the direction of arrow **234**). As the piston **108** moves toward TDC, the piston **108** decreases the volume of the combustion chamber **106** and accordingly increases the pressure within the combustion chamber **106**. In certain embodiments, during the compression stroke the injector **102** can dispense fuel **F** into the combustion chamber **106**. For example, during predetermined operating conditions, such as for production of maximum fuel economy, particularly in conjunction with low load or low torque requirements, the injector **102** can dispense the fuel **F** during the compression stroke of the piston **108**. Moreover, the injector **102** can dispense the fuel **F** in any desired distribution pattern, shape, stratified layers, etc., as noted above. As such, during the compression stroke the piston **108** can compress the air-fuel mixture as the piston **108** reduces the volume of the cavity **106**. In other embodiments, however, the system **100** can operate such that the injector **102** does not introduce fuel **F** into the combustion chamber **106** during the compression stroke of the piston **108**.

Referring next to FIG. 2C, as the piston **108** approaches or expands from TDC the injector **102** generates one or more ignition events to ignite or otherwise initiate combustion of the air fuel combination in the combustion chamber **106**. For example, the injector **102** can include one or more integrated ignition features (e.g., features for initiating a spark, plasma, or other suitable igniting event) as disclosed in the applications incorporated by reference above. In certain embodiments, the injector **102** can generate the ignition event as the piston **108** reaches TDC. In other embodiments, however, the injector **102** can generate the ignition event before the piston **108** reaches TDC and/or after the piston **108** moves away from TDC.

Referring next to FIG. 2D, FIG. 2D illustrates the system **100** during a power portion or power stroke of the cycle, which is the source of torque or power generated by the system **100**. During the power stroke, the first and second valves **110** remain closed and the pressure resulting from the combustion of the compressed air fuel mixture forces the piston **108** toward BDC in the direction indicated by arrow **232**. According to features of the illustrated embodiment, the injector **102** selectively dispenses coolant **C** directly into the combustion chamber **106** during the power stroke to cool the combustion chamber **106** or otherwise control or limit the peak combustion temperature. As described in detail below, under circumstances where the injector **102** dispenses the coolant **C** during the power stroke, the system **100** can adaptively determine which power strokes the injector **102** will dispense the coolant **C**. For example, the system **100** may sense the temperature of combustion chamber components to

6

determine that the injector **102** should dispense the coolant **C** during every third power stroke during operation of the system **100**. In other embodiments, however, the system **100** may determine the need to inject the coolant **C** more frequently (e.g., during each power stroke or during every second power stroke) or less frequently (e.g., during every fourth or greater power stroke). The determination of when to inject the coolant **C** can accordingly be adaptively determined and controlled based on the operating conditions of the system **100**. In still further embodiments, the determination of when to inject the coolant can be correlating or otherwise determining the combustion chamber temperature to an acceleration of a power train component of the system, as described in U.S. patent application Ser. No. 12/804,508, titled "METHODS AND SYSTEMS FOR REDUCING THE FORMATION OF OXIDES OF NITROGEN DURING COMBUSTION IN ENGINES," filed Jul. 21, 2010, and incorporated herein by reference in its entirety.

Although additional advantages of injecting the coolant **C** in accordance with embodiments of the disclosure are discussed in detail below, one advantage of injecting the coolant **C** during the power stroke is the ability to improve the volumetric efficiency and specific capacity rating of the combustion in the combustion chamber **106**. For example, selectively cooling the combustion chamber **106** during the power stroke allows for more fuel to burn per cycle or unit time out of the same volume in comparison with conventional high temperature conditions that limit the amount of fuel that burns. Allowing more fuel to burn during the power stroke accordingly provides more power output from the system. A corollary advantage is that the combustion chamber components become a type of thermal flywheel that provides rapid heating of the coolant **C** to produce expansion and work to increase the net power production of the engine.

Referring next to FIG. 2E, FIG. 2E illustrates the system **100** during an exhaust portion or exhaust stroke of the cycle. During the exhaust stroke, the first valve **110a** remains closed and the second valve **110b** opens and the piston **108** returns to TDC (e.g., in the direction of the arrow **234**). As the piston **108** reduces the volume of the combustion chamber **106** with the second valve **110b** open, an exhaust air flow **236** removes the combustion products from the combustion chamber **106**. According to features of the illustrated embodiment, the injector **102** can selectively dispense coolant **C** directly into the combustion chamber **106** during the exhaust stroke to cool the combustion chamber **106** or otherwise control or limit the peak temperature of the combustion chamber **106**. As described in detail below, under circumstances where the injector **102** dispenses the coolant **C** during an exhaust stroke, the system **100** can adaptively determine which exhaust strokes the injector **102** will dispense the coolant **C**. For example, the system **100** may determine that the injector **102** should dispense the coolant **C** during every third exhaust stroke during operation of the system **100**. In other embodiments, however, the system **100** may determine the need to inject the coolant **C** more frequently (e.g., during each exhaust stroke or during each second exhaust stroke) or less frequently (e.g., during every fourth or greater exhaust stroke). In still further embodiments, the injection of coolant **C** during an exhaust stroke can immediately follow the injection of coolant **C** during a power stroke.

As explained above, systems configured in accordance with embodiments of the disclosure adaptively dispense coolant into the combustion chamber during the power stroke and/or the exhaust stroke portions of the cycle. These systems, however, do not inject the coolant during the intake stroke and/or compression stroke portions of the cycle,

although in certain embodiments these systems could be modified to inject coolant during the intake stroke and/or compression stroke. Moreover, these systems can detect specific conditions that require injecting the coolant during the power stroke and/or the exhaust stroke. In this manner, these systems can adaptively or reactively control the timing of the coolant injection, the amount of injected coolant, the distribution pattern of injected coolant, etc. Moreover, the operating conditions can include, for example, the temperature in the combustion chamber as well as other properties that can be correlated or that otherwise relate to the combustion chamber temperature. Other factors that influence the adaptive control of the coolant injection can include the engine's power demand, type of coolant, coolant density, coolant viscosity, combustion chamber geometry including the piston geometry, resonance, piston position and speed, etc. An additional factor can include the amount of surplus air in the combustion chamber that forms an insulative envelope around the combustion. For example, these systems can adaptively inject the coolant in response to determining that an insufficient insulative surplus air envelope exists in the combustion chamber thereby resulting in one or more quench regions in the combustion chamber. Moreover, although features of the embodiments described herein are described with reference to the intake, compression, power, and exhaust strokes or portions of a cycle, one of ordinary skill in the art will appreciate that these strokes can be portions of four stroke or two stroke engines, in addition to other types of engines. Accordingly, embodiments of the present disclosure are not limited solely to engines that operate in a four stroke configuration.

Systems configured in accordance with embodiments of the disclosure that selectively and adaptively cool the combustion chamber by injection coolant during a power or exhaust stroke provide several advantages. One advantage, for example, is that the selective cooling improves the volumetric efficiency of the air fuel charge, as well as the specific capacity rating of the cycle. Additional benefits include preventing fouling of surfaces in the combustion chamber, as well as preventing pre-ignition of the fuel by reducing the operating temperatures. Moreover, such embodiments can eliminate parasitic losses resulting from conventional cooling components of an engine. For example, a system or engine configured in accordance with embodiments of the disclosure may eliminate the need for a radiator, water pump, water jacket, air pump, heat exchanger fins, or similar heat exchanging components that otherwise draw energy from the system. In addition to eliminating these parasitic energy losses, eliminating these or similar components reduces the weight of the system, as well as the capital investment for manufacturing, sourcing, and installing these components along with elimination or reduction of associated failures and maintenance costs of conventional cooling system components.

Additional benefits include increasing the longevity of the system, and in particular, increasing the longevity of components that are particularly susceptible to wear and fatigue. For example, the selective cooling during the power and/or exhaust strokes as disclosed herein can reduce the operating temperature of the piston, piston rings, oil, valve heads, engine head, etc. Moreover, the piston can reciprocate or otherwise operate in the combustion chamber at a higher frequency to burn more overall fuel resulting in greater power output of the engine under high load conditions. Furthermore, and as noted above, the coolant can be injected during the power and exhaust strokes without creating fouling or other undesirable effects in the combustion chamber. For example, when the injector dispenses the coolant in a layered or strati-

fied charge, an insulative layer of air in the combustion chamber can protect the surfaces of components in the combustion chamber. Another advantage resulting from embodiments of the present disclosure is the ability to limit the peak combustion chamber temperature to a predetermined value, such as 2200 degrees C. or less, for example, to avoid the formation of oxides of nitrogen. A further benefit of the methods and systems described herein is that they stop, or at least reduce, the formation of oxides of nitrogen at the source (i.e., in the combustion chamber), in contrast to conventional methods that focus on cleaning harmful emissions from the exhaust.

FIG. 3 is a schematic diagram of a system 300 configured in accordance with another embodiment of the disclosure. The system 300 includes several features that are generally similar in structure and function to the corresponding features of the system 100 described above with reference to FIGS. 1-2E. For example, the system 300 includes an engine 301 with a piston 308 that moves relative to a combustion chamber 306 through intake, compression, power, and exhaust events of two or four stroke operation. For purposes of illustration, the system also includes one or more air flow valves 310 (identified individually as a first air flow valve 310a and a second air flow valve 310b) that are operable to allow air flow into and out of the combustion chamber 306. In the illustrated embodiment, however, the system 300 also includes an injection and ignition subassembly 303. More specifically, the subassembly 303 includes a first injector 302a, a second injector 302b, and an igniter 305. In certain embodiments, the first injector 302a can dispense a first fuel into the combustion chamber 306 and the second injector 302b can dispense a coolant into the combustion chamber 306. Moreover, the igniter 305 can ignite the fuel and/or coolant that the first and second injectors 302a, 302b dispense into the combustion chamber 306. Although FIG. 3 illustrates the first injector 302a, the second injector 302b, and the igniter 305 as separate components, in certain embodiments one or more of these components can be integral parts of a single component. For example, the first injector 302a and the second injector 302b can be a single injector separate from the igniter 305. In other embodiments, however, one of the first and second injectors 302a, 302b can be combined with the igniter 305 and separate from the corresponding first or second injector 302a, 302b. In still further embodiments, the igniter 305 can be omitted from the system 300 and the ignition can be compression based. In still further embodiments, the igniter 305 can be a glow plug or similar component to at least partially aid in a compression based ignition system.

FIG. 4 is a flow diagram of a routine or method 450 for cooling a combustion chamber of an engine in accordance with an embodiment of the disclosure. The routine 450 can be controlled or performed by an engine management computer, engine control unit (ECU), Application-Specific-Integrated-Circuit (ASIC), processor, computer, and/or other suitable programmable engine control device. The method 450 can be used to cool a combustion chamber in which a piston or other reciprocating energy transfer device moves through a cycle including an intake, compression, power, and exhaust stroke as generally described above. For example, the method 450 includes injecting fuel into a combustion chamber (block 452). As described in detail above with reference to FIGS. 1-2E, an integrated injector/igniter can dispense the fuel into the combustion chamber during the intake and/or compression strokes of the piston during a cycle. More specifically, for example, under high load or torque requirements the injector can dispense at least a portion of the fuel into the combustion chamber during the intake stroke to develop a homogenous

charge of fuel and air. At times that higher fuel economy is desired and/or under lower power or torque requirements the injector can dispense the fuel during the compression stroke in a stratified or layered pattern. The method **450** also includes generating an ignition event to ignite the fuel in the combustion chamber (block **454**). In certain embodiments, the injector that dispensed the fuel into the combustion chamber can also generate the ignition event to ignite the fuel. In other embodiments, however, a separate ignition source can be used to ignite the fuel air charge in the combustion chamber. Moreover, the ignition event can be generated as the piston reaches TDC in the compression stroke, as well as before and/or after the piston reaches TDC in the compression stroke.

The method **450** further includes monitoring a temperature of the combustion chamber (block **456**). Monitoring the temperature can include, for example, directly monitoring the temperature of the combustion chamber with one or more sensors carried by the injector or by other components of the combustion chamber. In other embodiments, monitoring the temperature of the combustion chamber can include detecting or monitoring combustion chamber properties such as pressure, optical and/or acoustical properties, etc. that can be correlated to the combustion chamber temperature. The method **450** additionally includes determining if the combustion chamber temperature is at or above a predetermined value (decision block **458**). In certain embodiments, for example, it may be desirable to determine if the temperature in the combustion chamber reaches 2200 degrees C., which is the threshold for forming oxides of nitrogen. In other embodiments, however, the predetermined value of the temperature can be greater than or less than 2200 degrees C.

When the system determines that the temperature is below or at the predetermined value, the method includes continuing to operate through the intake, compression, power, and exhaust strokes of the cycle, and injecting and igniting fuel as described above. However, when the combustion chamber temperature is above or approaching the predetermined value, the method further comprises adaptively introducing a coolant into the combustion chamber during only one of a power stroke and/or an exhaust stroke of the cycle (block **460**). The method can also include dispensing the coolant during the power stroke and/or the exhaust stroke if the system determines that the zone of combustion exceeds the surplus air insulation envelope and approaches a quench region. In certain embodiments, the injector that dispenses the fuel and/or that ignites the fuel can also dispense the coolant. As also noted above, the coolant can include any fluid (e.g., gas or liquid) that produces cooling in the combustion chamber by transferring heat away from components of the combustion chamber. For example, the coolant can include non-combusting fluid. In other embodiments, however, the coolant can include a fuel that ignites and/or combusts at a lower temperature than the fuel that is introduced into the combustion chamber during the intake and/or compression strokes. In still further embodiments, the coolant can be a hydrogenous (e.g., a hydrogen containing component) coolant.

In addition to adaptively injecting the coolant in response to the combustion chamber temperature, the method **450** can also include adaptively controlling a frequency of the bursts of coolant into the combustion chamber. The method **450** can further include adaptively controlling a distribution pattern or spray of the coolant into the combustion chamber. For example, if the system determines that the combustion chamber is approaching a temperature limit or a quench zone or a portion of the combustion chamber that has a relatively higher temperature, the system can adaptively control the frequency,

direction, amount, and/or pattern of the coolant distribution to target the region of the elevated temperature. More specifically, several of the injectors as described in the patent applications incorporated by reference above disclose features for adaptively actuating or controlling valves of injectors, which can be used in injectors according to embodiments of the present disclosure. After injecting the coolant into the combustion chamber to lower the peak temperature of combustion, and/or of combustion chamber components, the method **450** can return to block **452** and repeat.

In still further embodiments, the method can include injecting the coolant into the combustion chamber under predetermined conditions other than the combustion chamber temperature. For example, when an engine is under a predetermined power load, such as a high power load or high torque load resulting from rapid acceleration, towing, ascending a hill, etc., the method can include injecting the coolant during every power stroke and/or exhaust stroke. Under relatively lower power or torque loads the method can include injecting the coolant less frequently (e.g., during every fourth or greater power stroke).

2. Additional Embodiments of Systems and Methods for Adaptively Cooling Combustion Chambers

According to additional embodiments of the disclosure, a method of controlling a temperature in a combustion chamber in an engine can include injecting coolant into the combustion chamber during a power stroke and/or exhaust stroke during a predetermined operational condition of the engine. In these embodiments, for example, the coolant injection can be based on the operational condition of the engine, rather than or in addition to the temperature of the combustion chamber. More specifically, a method of controlling a temperature in a combustion chamber can include introducing fuel into the combustion chamber of an engine, wherein an energy transfer device such as a rotor, piston, or other component moves at least partially within the combustion chamber through intake, compression, power, and exhaust events, and causing the fuel to combust in the combustion chamber. The method can further include monitoring the engine for a predefined operational condition of the engine. In certain embodiments, the predefined operational condition can include an increased power or torque requirement. For example, the predefined operational condition can include accelerating, ascending a hill, towing a trailer or other load, and/or other high power or high torque requirements. When the engine operates in the predefined operational condition, the method further includes introducing coolant into the combustion chamber only during at least one of the power stroke and the exhaust stroke.

According to additional embodiments, the method can further include monitoring a temperature of the combustion chamber in addition to the operational condition of the engine, and when the temperature reaches a predetermined value, introducing coolant into the combustion chamber only during at least one of the power stroke and the exhaust stroke. Moreover, introducing coolant into the combustion chamber can include introducing a coolant that does not combust in the combustion chamber. Furthermore, introducing fuel into the combustion chamber can include introducing fuel that generates a first temperature of combustion in the combustion chamber, and introducing coolant into the combustion chamber can include introducing coolant that generates a second temperature of combustion in the combustion chamber, the second temperature being less than the first temperature. In addition, introducing coolant into the combustion chamber can include introducing a coolant at least partially containing hydrogen.

According to further embodiments of the present disclosure, methods and systems can be directed to injecting a coolant or temperature controlling fluid into the combustion chamber during a power stroke and/or exhaust stroke when the temperature is below an ideal operating temperature. For example, in certain situations, an ideal operating temperature of a combustion chamber may be less than a maximum operating temperature or other predefined maximum temperature, such as 2200 degrees C., which is the threshold temperature for the formation of oxides of nitrogen (NO_x). Although operating at or near 2200 degrees C. may be beneficial, in certain embodiments the operating temperature can be controlled to be lower for the purpose of obtaining more specific power out of the engine by improving the volumetric efficiency and specific capacity rating of the combustion in the combustion chamber. This control of the combustion chamber can be achieved by injecting the coolant or other temperature controlling fluid only during the power stroke and/or exhaust stroke.

FIG. 5 is a schematic diagram of a system 500 including a turbine 506 configured in accordance with another embodiment of the disclosure. The turbine 506 illustrated in FIG. 5 can be operated with a coolant or temperature controlling fluid as disclosed above. More specifically, in the illustrated embodiment the system 500 includes a fuel source 501 that is coupled to an injector 502. The fuel source can store one or more fuels and coolants. The injector 502 can include any of the features described above, including the features of any of the injectors described in the applications incorporated herein by reference and directed to adaptively injecting multiple fuels and/or coolants, as well as igniting the fuels and coolants. For example, the injector 502 is configured to inject a fuel or coolant thereby generating an injection event 504 (e.g., injected fuel and/or coolant). In some embodiments, the injection event 504 can also include ignition of the fuel and/or coolant thereby producing a combustion event.

In the illustrated embodiment, the turbine 506 includes multiple rotors 510 and stators 512 (identified individually as first through sixth rotors 510a, 510b, 510c, 510d, and 510f and first through fourth stators 512a, 512b, 512c, and 512d). The rotors 510 and corresponding stators 512 are carried by a shaft 508 (e.g., drive shaft, output shaft, etc.) that can transfer rotational energy from the rotors 510 during operation. The turbine 500 may be a stand-alone system that drives one or more loads such as a generator or compressor. In other embodiments, the turbine 500 may be utilized, for example, as a turbocharger for another engine such as engine 100 or 300 as described above with reference to FIGS. 1-3.

For example, the injection event 504 can generate combustion that drives or rotates the rotors 510. During operation, the rotors 510 or other portions of the turbine 506 can develop hot or elevated temperature sections that lead to inefficiencies of the turbine 506 and/or increased or premature wear of components of the turbine 506. According to embodiments of the present disclosure, rather than injecting a fuel and igniting the fuel for the injection event 504, the injector 502 can be configured to inject a coolant or temperature controlling fluid directly into a hot section of one or more of the rotors 510. As described above, a coolant can include a combustible fuel or other fluid that ignites and combusts at a lower temperature than other fuels that are used during operation. Accordingly, the direct injection of the coolant at or near the rotors 510 can provide beneficial and adaptive cooling of the turbine during operation for improved power output and increased rotor 510 and other component wear.

In additional embodiments, the coolant that is introduced at the turbine 506, and more specifically at the rotors 510, can

include a coolant that is exhausted from a combustion chamber of an internal combust chamber, including for example, the combustion chambers described above regarding operation of engines 100 or 300. For example, in any of the embodiments of combustions chambers described above with reference to FIGS. 1-4, exhaust from the combustion chamber can include excess air or excess fuel such as hydrogen, as well as other liquid and gaseous coolants. These exhaust coolants can be introduced into the turbine 506 when the turbine 506 is downstream or in a cascaded configuration with one or more upstream combustion chambers. As such, exhaust coolants from a combustion chamber can accordingly be introduced into the hot sections of the turbine 506, including for example, at the rotors 510, to reduce operating temperatures for improved performance and increased longevity.

FIG. 6 is a schematic diagram of a system 600 configured in accordance with yet another embodiment of the disclosure. According to several features of the illustrated embodiment, the system 600 is configured for cooling one or more electrical generating or conditioning components with a coolant, and subsequently cooling a combustion chamber with the same coolant via direct injection as described above with reference to FIGS. 1-4. For example, hybrid, electrical drive, and regenerative drive or braking systems can include several electricity generating components such as alternators, transformers, batteries, electrical generators, fuel cells, etc. Similar to the embodiments described above, the coolant can include any temperature controlling fluid or gas, including, for example, hydrogen.

In the illustrated embodiment, the system 600 includes a coolant source 601 coupled to an electrical generating component 604 via a coolant inlet conduit or line 602. The electrical generating component 604 can include one or more electrical circuits 606. The system 600 can further include a management clutch system 608 inline or coupled to the braking and/or electrical generating component, as well as at least a portion of an internal combustion engine 612 including one or more combustion chambers, energy transferring devices, injector, etc. as described above with reference to FIGS. 1-4. The management clutch system 608 is configured to manage or distribute power to one or more power output components of the system 600, and is intended to be representative of at least one hybrid engine component that can benefit from the upstream cooling from the electrical generating component 604 to the engine 612. The system 600 also includes a coolant delivery conduit, rail, or line 610 fluidly coupled to the electrical generating component 604 and/or the management clutch system 608. The coolant line 610 is also fluidly coupled to the engine 612 to deliver the coolant from the electrical generating component 604 and/or the management clutch system 608 to the engine 612. The system 600 further includes an output shaft 614 (portions of which are identified individually as 614A and 614B) that transfers or delivers output energy from the electrical generating component 604 and/or engine 612 to an energy transfer component, such as one or more drive wheels 616 (identified individually as a first drive wheel 616A and a second drive wheel 616B). The clutch management system 608 is configured to allow or manage various operational conditions of the drive wheels 616. For example, in certain embodiments, the clutch management system 608 can allow for an electric drive and/or an engine on each of the drive wheels 616 to be at the same or at a different RPM, as well as for an electric drive to be on one of the drive wheels 616 and an engine drive to be on the other drive wheel 616. The clutch management system 608 can further allow or manage regenerative braking by the electrical generating component 604 on either of the drive wheels 616.

In operation, the electrical generating component **604** and/or the management clutch system **608** generate heat. As the temperature of these components increases or during other predetermined operational conditions, the coolant inlet line **602** delivers coolant to the electrical generating component **604** and/or the management clutch system **608** to cool or otherwise control the operating temperature of these components. The coolant can circulate through or around these components, and then be delivered downstream to the engine **612** (or, for example a turbine system such as the turbine **500** discussed above with reference to FIG. **5**) via the coolant delivery line **610**. At the engine **612**, the coolant can be injected as described above with reference to FIGS. **1-4**, including, for example, only during at least one of the exhaust and power strokes of a piston moving relative to a combustion chamber, to thereby limit or control the operating temperature of the engine **612**. The temperature of the coolant will still be sufficient for cooling or other temperature control in the engine **612** even after cooling the electrical generating component **604** and/or the management clutch system **608** due to the high operating temperatures of the combustion chambers in the engine **612** (or of similar engines or the turbine **500** discussed above). As such, the engine **612** operates as a heat sink for the heat generating electrical components. Such configurations can be useful, for example, in systems such as hybrid vehicles, vehicles with fuel cells, vehicles with electrical generators, stationary engines with electrical generators, etc.

FIG. **7** is a flow diagram of a method **700**, such as a cascading method or coolant recycling method, for cooling one or more electrical generating components and for cooling a combustion chamber of an engine in accordance with embodiments of the disclosure. In the illustrated embodiment, the method **700** includes activating a system (block **702**). The system can include any suitable electrical generating components described above with reference to FIG. **6**. For example, and referring to FIG. **7**, the system can include any electrical generating components that are typically included in at least one of an electric drive system (block **704a**), a heat engine drive system (block **704b**), and/or an electric and heat engine drive system (block **704c**), as well as other suitable drive systems with electrical generating components. The method **700** further includes circulating a coolant or temperature controlling fluid to one or more electric drive components or electrical generating components (block **706**). In certain embodiments, circulating the coolant to one or more electric drive components can include circulating the coolant to multiple electric drive components arranged in series or in parallel, thereby circulating the coolant in a cascading fashion between one or more electric drive components.

The method **700** further includes circulating or introducing the coolant into a heat engine drive system (block **708**). The heat engine drive system can include, for example, any internal combustion engine with energy transferring components (e.g., two or four stroke piston engines, rotary combustion engines, gas turbine engines, and/or any combination of these or other suitable engines). Moreover, the coolant that is introduced into the heat engine drive system includes the same coolant that previously circulated through the one or more electric drive components upstream from the heat engine drive system. In certain embodiments, the method **700** can further include circulating the coolant (e.g., exhaust coolant) from the heat drive engine to one or more additional heat drive engines, electrical drive systems, and/or combinations of heat drive and electrical drive engines (block **710**).

From the foregoing, it will be appreciated that specific embodiments of the disclosure have been described herein for

purposes of illustration, but that various modifications may be made without deviating from the spirit and scope of the disclosure. For example, the methods and systems described herein for combustion chamber cooling are applicable to a variety of fuel cells and/or engines including internal combustion engines such as rotary combustion engines, two-stroke and four-stroke piston engines, free-piston engines, etc. Moreover, these methods and systems can provide for operation of such engines by insulation of combustion with surplus oxidant such as air to substantially achieve adiabatic combustion. In one embodiment, this can be achieved by first filling the combustion chamber with oxidant, and then adding fuel at the same location that ignition occurs to provide one or more stratified charges of fuel combustion within excess oxidant to minimize heat transfer to combustion chamber surfaces. Accordingly, the disclosure is not limited except as by the appended claims.

To the extent not previously incorporated herein by reference, the present application incorporates by reference in their entirety the subject matter of each of the following materials: U.S. Patent Application No. 61/237,476, filed on Aug. 27, 2009 and titled ELECTROLYZER AND ENERGY INDEPENDENCE TECHNOLOGIES; U.S. patent application Ser. No. 12/707,651, filed on Feb. 17, 2010 and titled ELECTROLYTIC CELL AND METHOD OF USE THEREOF; U.S. Patent Application No. 61/237,479, filed on Aug. 27, 2009 and titled FULL SPECTRUM ENERGY; U.S. Patent Application No. 61/178,442, filed on May 14, 2009 and titled ENERGY INDEPENDENCE TECHNOLOGIES; U.S. patent application Ser. No. 12/707,653, filed on Feb. 17, 2010 and titled APPARATUS AND METHOD FOR CONTROLLING NUCLEATION DURING ELECTROLYSIS; U.S. patent application Ser. No. 12/707,656, filed on Feb. 17, 2010 and titled APPARATUS AND METHOD FOR GAS CAPTURE DURING ELECTROLYSIS; U.S. patent application Ser. No. 09/969,860, filed on Oct. 1, 2001 and titled METHOD AND APPARATUS FOR SUSTAINABLE ENERGY AND MATERIALS; U.S. patent application Ser. No. 12/857,553, filed on Aug. 16, 2010 and titled SUSTAINABLE ECONOMIC DEVELOPMENT THROUGH INTEGRATED PRODUCTION OF RENEWABLE ENERGY, MATERIALS RESOURCES, AND NUTRIENT REGIMES, U.S. patent application Ser. No. 12/857,541, filed on Aug. 16, 2010 and titled SYSTEMS AND METHODS FOR SUSTAINABLE ECONOMIC DEVELOPMENT THROUGH INTEGRATED FULL SPECTRUM PRODUCTION OF RENEWABLE ENERGY; U.S. patent application Ser. No. 12/857,554, filed on Aug. 16, 2010 and titled SYSTEMS AND METHODS FOR SUSTAINABLE ECONOMIC DEVELOPMENT THROUGH INTEGRATED FULL SPECTRUM PRODUCTION OF RENEWABLE MATERIAL RESOURCES USING SOLAR THERMAL; U.S. patent application Ser. No. 12/857,502, filed on Aug. 16, 2010 and titled ENERGY SYSTEM FOR DWELLING SUPPORT; Ser. No. 13/027,235 filed on Feb. 14, 2011 and titled DELIVERY SYSTEMS WITH IN-LINE SELECTIVE EXTRACTION DEVICES AND ASSOCIATED METHODS OF OPERATION; and U.S. Patent Application No. 61/401,699, filed on Aug. 16, 2010 and titled COMPREHENSIVE COST MODELING OF AUTOGENOUS SYSTEMS AND PROCESSES FOR THE PRODUCTION OF ENERGY, MATERIAL RESOURCES AND NUTRIENT REGIMES.

We claim:

1. A method of limiting a peak temperature of a combustion chamber in an engine, the method comprising:
 - in a first portion of a cycle of the engine

15

injecting fuel directly into the combustion chamber during at least one of an intake stroke and a compression stroke of the first cycle; and
 igniting the fuel in the combustion chamber to cause combustion;
 monitoring a temperature of the combustion chamber resulting from the combustion; and
 in at least one of the first portion or a second portion of the cycle of the engine
 when the temperature reaches a predetermined value,
 injecting coolant directly into the combustion chamber only during an exhaust stroke of the cycle.

2. The method of claim 1 wherein:
 injecting fuel directly into the combustion chamber comprises injecting a first fuel that generates a first temperature of combustion in the combustion chamber; and
 injecting the coolant directly into the combustion chamber comprises injecting a second fuel that generates a second temperature of combustion in the combustion chamber, wherein the second temperature is less than the first temperature.

3. The method of claim 1 wherein injecting coolant directly into the combustion chamber comprises injecting a fluid or gas that does not combust in the combustion chamber.

4. The method of claim 1 wherein injecting coolant directly into the combustion chamber comprises injecting a hydrogenous coolant directly into the combustion chamber.

5. The method of claim 1 wherein introducing injecting coolant directly into the combustion chamber comprises injecting coolant during each of the power stroke and the exhaust stroke of the cycle.

6. The method of claim 1 wherein the predetermined value of the temperature is 2200 degrees C.

7. The method of claim 1 wherein:
 injecting fuel directly into the combustion chamber comprising injecting fuel with an injector; and
 igniting the fuel in the combustion chamber comprises igniting the fuel with an ignition feature carried by the injector.

8. The method of claim 1, further comprising:
 determining a predefined operational mode of the engine, the predefined operational mode comprising an acceleration or high load operational condition of the engine; and
 when the engine operates in the predefined operational mode, injecting coolant directly into the combustion chamber only during at least one of the power stroke and an exhaust stroke of the cycle.

9. A method of cooling a combustion chamber in an engine, the method comprising:
 introducing fuel into the combustion chamber of the engine, wherein an energy transfer device moves at least partially within the combustion chamber through an intake stroke, a compression stroke, a power stroke, and an exhaust stroke;
 causing the fuel to combust in the combustion chamber;
 monitoring a temperature of the combustion chamber; and

16

when the temperature reaches a predetermined value, introducing coolant into the combustion chamber only during the exhaust stroke of the energy transfer device.

10. The method of claim 9 wherein introducing the coolant into the combustion chamber comprises introducing a coolant that does not combust in the combustion chamber.

11. The method of claim 9 wherein introducing coolant into the combustion chamber comprises introducing a coolant that combusts in the combustion chamber at a lower temperature than the fuel.

12. The method of claim 9 wherein:
 introducing the fuel into the combustion chamber comprising introducing the fuel with an injector; and
 causing the fuel to combust comprises generating an ignition event with an ignition feature carried by the injector.

13. The method of claim 9 wherein:
 introducing the fuel into the combustion chamber comprising introducing the fuel with an injector; and
 introducing coolant into the combustion chamber comprises introducing the fuel with the injector.

14. The method of claim 9, further comprising:
 monitoring the engine for a predefined operational condition of the engine; and
 when the engine operates in the predefined operational condition, introducing coolant into the combustion chamber only during at least one of the power stroke and the exhaust stroke.

15. An internal combustion engine system comprising:
 a combustion chamber;
 an energy transfer device movable relative to the combustion chamber through a cycle comprising an intake stroke, a compression stroke, a power stroke, and an exhaust stroke;
 an injector configured to inject fuel into the combustion chamber during at least one of the intake stroke and the compression stroke;
 an ignition feature configured to ignite the fuel in the combustion chamber; and
 a sensor configured to detect a temperature of the combustion chamber, wherein when the temperature reaches a predetermined value, the injector is configured to inject coolant directly into the combustion chamber only during the exhaust stroke.

16. The system of claim 15 wherein the ignition feature is carried by the injector.

17. The system of claim 15 wherein the coolant does not combust in the combustion chamber.

18. The system of claim 15 wherein the fuel generates a first temperature of combustion in the combustion chamber and the coolant generates a second temperature of combustion in the combustion chamber, and wherein the second temperature is less than the first temperature.

19. The system of claim 15 wherein the coolant at least partially contains hydrogen.

20. The system of claim 15 wherein the predetermined value of the temperature is 2200 degrees C.

* * * * *