

US008344903B2

(12) **United States Patent**  
**Ogasawara et al.**

(10) **Patent No.:** **US 8,344,903 B2**  
(45) **Date of Patent:** **Jan. 1, 2013**

(54) **INSTRUMENTAL DEVICE**

(56) **References Cited**

(75) Inventors: **Yukio Ogasawara**, Niigata (JP); **Shuichi Nomizu**, Niigata (JP); **Toshiyuki Ohtake**, Niigata (JP)

(73) Assignee: **Nippon Seiki Co., Ltd.**, Niigata (JP)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 224 days.

(21) Appl. No.: **12/865,593**

(22) PCT Filed: **Dec. 16, 2008**

(86) PCT No.: **PCT/JP2008/072801**

§ 371 (c)(1),  
(2), (4) Date: **Jul. 30, 2010**

(87) PCT Pub. No.: **WO2009/096105**

PCT Pub. Date: **Aug. 6, 2009**

(65) **Prior Publication Data**

US 2010/0328091 A1 Dec. 30, 2010

(30) **Foreign Application Priority Data**

Jan. 30, 2008 (JP) ..... 2008-019709

(51) **Int. Cl.**

**G08B 5/24** (2006.01)

**B60Q 1/00** (2006.01)

**H01R 12/00** (2006.01)

**G01D 11/28** (2006.01)

(52) **U.S. Cl.** ..... **340/815.78**; 439/57; 340/461;  
116/288

(58) **Field of Classification Search** ..... 439/157  
See application file for complete search history.

**U.S. PATENT DOCUMENTS**

5,437,185	A *	8/1995	Panzica	73/493
6,677,723	B2 *	1/2004	Shimazaki	318/696
7,193,729	B1 *	3/2007	Li	356/614
7,347,160	B2 *	3/2008	Honma et al.	116/288
2007/0190832	A1 *	8/2007	Totsuka	439/157

**FOREIGN PATENT DOCUMENTS**

DE	43 21 146	A1	1/1995
JP	56-036180	Y2	10/1978
JP	61-35995	Y2	7/1980
JP	02-034626	Y2	3/1986

\* cited by examiner

*Primary Examiner* — Albert Wong

*Assistant Examiner* — Pameshanand Mahase

(74) *Attorney, Agent, or Firm* — McDermott Will & Emery LLP

(57) **ABSTRACT**

An instrumental device is provided which includes a variable display portion and a pointer moving around the variable display portion and achieves excellent response and resistance to vibration without complicating the shape of a member. The instrumental device has a display plate **21** having a variable display portion **21b**, a pointer **23** moving around the variable display portion **21b**, and pointer drive means **25**, **26** provided on the back-face side of the display plate **21** for moving the pointer **23**. The instrumental device includes a guide rail portion **22** provided in the display plate **21** to surround the periphery of the variable display portion **21b**, the pointer **23** being located on the guide rail portion **22**, a holding portion **24** holding the pointer **23** movably along the guide rail portion **22**, a first magnet **24c** provided in the pointer **23** or the holding portion **24**, and a second magnet **25a** provided in the pointer drive means **25**, **26** such that the second magnet **25a** is opposite to the first magnet **24c**,

wherein the pointer **23** is rotated in association with rotation drive of the pointer drive means **25**, **26** by attraction force of the first and second magnets **24c**, **25a**.

**5 Claims, 5 Drawing Sheets**




FIG.1




FIG.2  
A—A




FIG.3




FIG.4






FIG.5




FIG.6





FIG. 7



## 1

## INSTRUMENTAL DEVICE

## RELATED APPLICATIONS

This application is the U.S. National Phase under 35 U.S.C. §371 of International Application No. PCT/JP2008/072801, filed on Dec. 16, 2008, which in turn claims the benefit of Japanese Application No. 2008-019709, filed on Jan. 30, 2008, the disclosures of which Applications are incorporated by reference herein.

## TECHNICAL FIELD

The present invention relates to an instrument device which includes a variable display portion and a pointer moving around the variable display portion.

## BACKGROUND ART

There have been conventionally instrumental devices in which a pointer points at an indicating portion on a dial (display plate) to display predetermined information. In such an instrumental device, the pointer is directly secured to a rotation shaft of pointer drive means such as a stepping motor, and the pointer is rotated in association with rotation drive of the pointer drive means and thus caused to point at the indicating portion.

Some of the instrumental devices include a large variable display portion such as a liquid crystal display portion at the center of a display plate such that the variable display portion displays predetermined information, and also includes a pointer moving around the variable display portion such that the pointer displays predetermined information. Such a configuration is disclosed, for example in Patent Document 1.

An instrumental device disclosed in Patent Document 1 is formed to use a pointer having a bent shape which bypasses a variable display portion from a back-face side to a front-face side of a display plate.

Patent Document 1: DE4321146A1

## DISCLOSURE OF THE INVENTION

## Problems that the Invention is to Solve

The instrumental device of the configuration as disclosed in Patent Document 1, however, has the problem in which the complicated structure of the pointer increases the length and weight of the pointer to prevent rotation of the pointer with excellent response. In addition, since the pointer is simply secured to the pointer drive means, the problem of poor resistance to vibration is presented when the device is used for a vehicle instrument used in harsh environments. Thus, the instrumental devices have potential for improvement.

The present invention has been made in view of the above-mentioned problems, and it is an object thereof to provide an instrumental device which includes a variable display portion and a pointer moving around the variable display portion and achieves excellent response and resistance to vibration without complicating the shape of a member.

## Means for Solving the Problems

To solve the problems, the present invention is characterized by an instrumental device having a display plate having a variable display portion, a pointer moving around the variable display portion, and pointer drive means provided on the back-face side of the display plate for moving the pointer,

## 2

including a guide rail portion provided in the display plate to surround the periphery of the variable display portion, the pointer being located on the guide rail portion, a holding portion holding the pointer movably along the guide rail portion, a first magnet provided in the pointer or the holding portion, and a second magnet provided in the pointer drive means such that the second magnet is opposite to the first magnet, wherein the pointer is rotated in association with rotation drive of the pointer drive means by attraction force of the first and second magnets.

The present invention is characterized by including a regulating portion provided for the holding portion and regulating the position of the pointer located on the guide rail portion, and a guide portion provided for the guide rail portion and having a shape conforming to the regulating portion.

The present invention is characterized in that the regulating portion is formed of a protrusion portion protruding from the holding portion.

The present invention is characterized in that the regulating portion is formed of a rotation member rotating along the guide portion.

The present invention is characterized in that each of the regulating portion and the guide portion has an inclined surface, the inclined surfaces thereof abutting each other.

## Advantage of the Invention

The present invention relates to an instrumental device which includes a variable display portion and a pointer moving around the variable display portion and achieves excellent response and resistance to vibration without complicating the shape of a member.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 A front view showing a first embodiment of the present invention.

FIG. 2 A section view showing the first embodiment of the present invention.

FIG. 3 A diagram showing a guide rail portion in the first embodiment of the present invention.

FIG. 4 An enlarged section view of main portions to show the first embodiment of the present invention.

FIG. 5 An enlarged section view of main portions to show a second embodiment of the present invention.

FIG. 6 An enlarged section view of main portions to show a third embodiment of the present invention.

FIG. 7 An enlarged section view of main portions to show a fourth embodiment of the present invention.

DESCRIPTION OF REFERENCE NUMERALS  
AND SIGNS

21 display plate

21a light-transmitting substrate

21b liquid crystal display portion (variable display portion)

22 guide rail portion

22a hollow portion

22b, 22c guide portion

23 pointer

23a pointer base portion

23b pointing portion

24 holding portion

24a mounting portion

24b, 24e to 24g regulating portion

24c first magnet

24d first yoke



3

25 arm member  
 25a second magnet  
 25b second yoke  
 26 stepping motor  
 27 circuit substrate

### BEST MODE FOR CARRYING OUT THE INVENTION

In the following, a first embodiment in which the present invention is applied to a vehicle combination meter will be described with reference to the accompanying drawings.

In FIG. 1, reference numeral 1 shows a housing. The housing 1 has a shade member and a case body to accommodate four indicators, that is, a speed meter 2, a rotation meter 3, a fuel meter 4, and a water-temperature meter 5. The speed meter 2 is larger than the rotation meter 3, the fuel meter 4, and the water-temperature meter 5, and is placed between the rotation meter 3, and the fuel meter 4 and the water-temperature meter 5. The speed meter 2 has a display plate 21 and a pointer 23. The rotation meter 3, the fuel meter 4, and the water-temperature meter 5 have dials 31, 41, 51, and pointers 32, 42, 52, respectively. The dials 31, 41, 51 are provided by forming indicating portions 3a, 4a, 5a three-dimensionally on substrates made of light-transmitting resin (for example, polycarbonate) and forming light-shield portions through printing except for character portions 3b, 4b, 5b, respectively. The pointers 32, 42, 52 are rotated by a stepping motor (not shown) to point at the indicating portions 3a, 4a, 5a of the dials 31, 41, 51, respectively.

FIG. 2 is an enlarged section view showing main portions. The speed meter 2 has the display plate 21, a guide rail portion 22, the pointer 23, a holding portion 24, an arm member 25, and the stepping motor 26. Reference numeral 27 shows a circuit substrate on which the stepping motor 26 is mounted.

The display plate 21 is formed of a light-transmitting substrate 21a and a liquid crystal display portion (variable display portion) 21b.

The light-transmitting substrate 21a is made of light-transmitting resin (for example, acrylic or polycarbonate). On the light-transmitting substrate 21a, an indicating portion 2a is provided three-dimensionally to be positioned around the liquid crystal display portion 21b in accordance with the moving range of the pointer 23, and a character portion 2b is formed through cutting or the like.

The liquid crystal display portion 21b is provided by sealing-in liquid crystal between a pair of light-transmitting substrates having a transparent electrode film formed thereon to provide a liquid crystal cell and then bonding a polarizing plate onto both surfaces of the liquid crystal cell. For example, a liquid crystal display of dot-matrix type is used. The liquid crystal display portion 21b can display variable contents and can selectively display various types of information such as a total driving distance, fuel economy, and alarm information.

The guide rail portion 22 is provided to surround the periphery of the liquid crystal display portion 21b on the display plate 21 and is provided, for example, by forming light-transmitting resin into an arc shape as shown in FIG. 3. The guide rail portion 22 has a hollow portion 22a capable of accommodating the pointer 23 and has a guide portion 22b of hollow shape at its bottom portion where a regulating portion of a holding portion 24, later described, is placed, as shown in FIG. 4. The guide rail portion 22 is covered with a decoration ring 2c provided on the front-face side of the display plate 21 such that a user cannot visually recognize the guide rail portion 22.

4

As shown in FIGS. 2 and 4, the pointer 23 is made of light-transmitting resin such as polycarbonate, and is formed of a pointer base portion 23a, one end portion of which is located in the guide rail portion 22, and a pointing portion 23b which is extended from the other end portion of the pointer base portion 23a and points at the indicating portion 2a. The pointer 23 is moved around the liquid crystal display portion 21b along the guide rail portion 22 to point at the indicating portion 2a to display predetermined information (vehicle speed in the present embodiment).

The holding portion 24 is made of light-shield resin material, for example ABS resin, and has a mounting portion 24a for holding the pointer 23 movably along the guide rail portion 22 in the guide rail portion 22 and the regulating portion 24b formed in the bottom portion of the mounting portion 24a. The regulating portion 24b is a protrusion portion which protrudes downward from the mounting portion 24a and is placed in the guide portion 22b provided for the guide rail portion 22 and formed in the hollow shape conforming to the shape of the regulating portion 24b to determine the position of the pointer 23 with reference to the guide rail portion 22. It is also possible that the shapes of the regulating portion 24b and the guide portion 22b can be adjusted to determine the angle formed by the guide rail portion 22 and the pointer 23 at a predetermined angle.

A first magnet 24c and a first yoke 24d are located to be positioned around the pointer 23 in the mounting portion 24a of the holding portion 24. The first magnet 24c and the first yoke 24d may be located directly on the pointer 23.

The first magnet 24c is located to be positioned around the pointer base portion 23a accommodated in the guide rail portion 22. The first magnet 24c and a second magnet 25a, later described, attract each other.

The first yoke 24d is provided closer to a surface of the first magnet 24c that is not opposite to the second magnet 25a (the non-opposite surface). The first yoke 24d constitutes a magnet circuit which suppresses leakage flux from the non-opposite surface of the first magnet 24c to improve the magnet efficiency.

The arm member 25 has the second magnet 25a and a second yoke 25b at one end and has the other end fitted to a rotation shaft 26a of the stepping motor 26. Pointer drive means in the present embodiment is formed of the arm member 25 and the stepping motor 26.

The second magnet 25a is placed at the position opposite to the first magnet 24c with the display plate 21 interposed between them to form a pair with the first magnet 24c. The second magnet 25a may be provided with a method in which the arm member 25 is formed by using resin material (for example, engineering plastic), the second magnet 25a is formed by using a different member from the arm member 25, and then insert molding or outsert molding is performed for integral formation, or with a method in which the arm member 25 is formed by using plastic magnet and the portion thereof opposite to the first magnet 24c is magnetized.

The second yoke 25b is provided closer to a surface of the second magnet 25a that is not opposite to the first magnet 24c (the non-opposite surface). The second yoke 25b constitutes a magnet circuit which suppresses leakage flux from the non-opposite surface of the second magnet 25a to improve the magnet efficiency.

In the present embodiment, the first magnet 24c is provided in the pointer 23 placed in the guide rail portion 22, and the second magnet 25a is provided in the arm member 25 secured to the rotation shaft 26a of the stepping motor 26 such that the second magnet 25a is opposite to the first magnet 24c with the display plate 21 interposed between them. Since the first



## 5

magnet **24c** and the second magnet **25a** attract each other by the magnetic force, the pointer **23** can be moved along the guide rail portion **22** in association with the rotation drive of the stepping motor **26**. Therefore, even when the variable display portion is provided at the center of the display plate, the pointer is not increased in size or complicated due to the bypassing of the variable display portion as in the conventional method in which the pointer is directly secured to the stepping motor, so that the pointer **23** can be moved with excellent response.

In addition, the regulating portion **24b** which determines the position of the pointer **23** located on the guide rail portion **22** is provided for the holding portion **24** which holds the pointer **23**, and the guide portion **22b** conforming to the regulating portion **24b** is provided for the guide rail portion **22**. This can reduce displacement of the pointer **23** from the indicating portion **2a** to enable pointing at the indicating portion **2a** with high accuracy. Furthermore, the attraction force of the first and second magnets **24c**, **25a** supplies the holding portion **24** with a certain tension to the guide rail portion **22**, which can prevent small movements of the pointer **23** within the guide rail portion **22** to improve resistance to vibration.

For the shape of the regulating portion in the present invention, various shapes or members can be applied in addition to that in the first embodiment.

FIG. 5 shows a second embodiment of the present invention. The second embodiment differs from the abovementioned first embodiment in that a regulating portion **24e** provided for a holding portion **24** is formed of a roller member which rotates along a guide portion **22b** provided for a guide rail portion **22**. The regulating portion **24e** formed of the roller member can suppress displacement of a pointer **23** and smoothly move the pointer **23** to improve response.

FIG. 6 shows a third embodiment of the present invention. The third embodiment differs from the abovementioned first embodiment in that a regulating portion **24f** provided for a holding portion **24** is formed of a ball member which rotates along a guide portion **22b** provided for a guide rail portion **22**. The regulating portion **24f** formed of the ball member can suppress displacement of a pointer **23** and smoothly move the pointer **23** to improve response.

FIG. 7 shows a fourth embodiment of the present invention. The fourth embodiment differs from the abovementioned first embodiment in that a regulating portion **24g** provided for a holding portion **24** is formed of a linear protrusion portion which has an inclined surface, and in that a guide portion **22c** provided for a guide rail portion **22** is formed of a V-shaped groove portion which has an inclined surface abutting on the regulating portion **24g**. The abutting inclined surface may be on any of left and right sides in FIG. 7. The abutment of the regulating portion **24g** and the guide portion **22b** with the inclined surfaces can prevent small movements of the regulating portion **24g** within the guide portion **22c** to suppress displacement of a pointer **23** to improve resistance to vibration.

## 6

While the first and second magnets **24c**, **25a** are permanent magnets, the second magnet **25a** may be an electromagnet, for example. A display with an organic EL element may be used as the variable display element in addition to the liquid crystal display portion **21b**. While the stepping motor **26** is included as the pointer drive means, it goes without saying that a cross-coil movement may be used, for example, instead of the stepping motor **26**.

## INDUSTRIAL APPLICABILITY

The present invention relates to an instrumental device and is preferable for an instrumental device which includes a variable display portion and a pointer moving around the variable display portion.

The invention claimed is:

1. An instrumental device having a display plate having a variable display portion, a pointer moving around the variable display portion, and pointer drive means provided on a back-face side of the display plate for moving the pointer, comprising:

a guide rail portion provided in the display plate to surround a periphery of the variable display portion, the pointer being located on the guide rail portion;  
a holding portion holding the pointer movably along the guide rail portion;  
a first magnet provided in the pointer or the holding portion; and

a second magnet provided in the pointer drive means such that the second magnet is opposite to the first magnet, wherein:

the pointer is moved in association with rotation drive of the pointer drive means by attraction force of the first and second magnets,

the pointer drive means is formed of an arm member and a stepping motor,

the arm member is secured to a rotation shaft of the stepping motor,

the second magnet is formed on the arm member, and the second magnet is opposite to the first magnet.

2. The instrumental device according to claim 1, further comprising a regulating portion provided for the holding portion and regulating a position of the pointer with reference to the guide rail portion, and a guide portion provided for the guide rail portion and having a shape conforming to the regulating portion.

3. The instrumental device according to claim 2, wherein the regulating portion is formed of a protrusion portion protruding from the holding portion.

4. The instrumental device according to claim 2, wherein the regulating portion is formed of a rotation member rotating along the guide portion.

5. The instrumental device according to claim 2 wherein each of the regulating portion and the guide portion has an inclined surface, the inclined surfaces thereof abutting each other.

\* \* \* \* \*