

US008362660B2

(12) **United States Patent**
Hunter

(10) **Patent No.:** **US 8,362,660 B2**
(45) **Date of Patent:** **Jan. 29, 2013**

- (54) **ELECTRIC GENERATOR**
- (75) Inventor: **Ian W. Hunter**, Lincoln, MA (US)
- (73) Assignee: **Nucleus Scientific, Inc.**, Lincoln, MA (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 398 days.

4,503,751 A	3/1985	Pinson	
4,507,579 A	3/1985	Turner	
4,981,309 A *	1/1991	Froeschle et al.	280/6.157
5,036,930 A	8/1991	Bisel et al.	
5,276,372 A	1/1994	Hammer	
5,631,507 A *	5/1997	Bajric et al.	310/67 A
5,685,798 A	11/1997	Lutz et al.	
5,701,039 A *	12/1997	Parison et al.	310/12.26
6,113,119 A	9/2000	Laurent et al.	

(Continued)

- (21) Appl. No.: **12/590,496**
- (22) Filed: **Nov. 9, 2009**

FOREIGN PATENT DOCUMENTS

EP	0 435 461 A2	7/1991
EP	0 616 412 A1	9/1994

(Continued)

- (65) **Prior Publication Data**
US 2011/0109174 A1 May 12, 2011

OTHER PUBLICATIONS

Muetze, A., and Tan, Y. C., Performance Evaluation of Electric Bicycles, Fourth IAS Annual Meeting, Conference Record of the 2005 [online] 2005 [retrieved on Jul. 8, 2009] Retrieved from the Internet URL: <http://www.ieeexplore.ieee.org>.

(Continued)

- (51) **Int. Cl.**
H02K 7/06 (2006.01)
H02K 33/00 (2006.01)
H02K 35/00 (2006.01)
- (52) **U.S. Cl.** **310/20**; 310/12.01; 310/17; 310/24; 290/1 R; 290/45; 322/3
- (58) **Field of Classification Search** 310/12, 310/20-24, 17; 290/1 R, 45; 322/3; *H02K 7/06*, *H02K 33/00*, *35/00*
See application file for complete search history.

Primary Examiner — John K Kim
(74) *Attorney, Agent, or Firm* — Hamilton, Brook, Smith & Reynolds, P.C.

(56) **References Cited**


U.S. PATENT DOCUMENTS

3,118,432 A *	1/1964	Peterson	123/222
3,289,886 A *	12/1966	Goldsholl et al.	222/1
3,479,541 A	11/1969	Robinson	
3,575,341 A	4/1971	Tarver	
3,964,450 A *	6/1976	Lockshaw	123/54.3
4,228,373 A	10/1980	Funderburg	
4,345,174 A *	8/1982	Angus	310/24
4,384,221 A	5/1983	Brandly	
4,473,763 A	9/1984	McFarland	
4,486,667 A	12/1984	Srogi	

(57) **ABSTRACT**

An electric generator device includes a magnetic stator assembly, opposed coils, and a rotary-to-linear converter (e.g., cam). The coils are configured to reciprocate relative to the magnetic stator assembly or to linearly translate in a common direction relative to the magnetic stator assembly. The coils are coupled to the cam and, upon rotary or linear motion of the cam, reciprocate or linearly translate relative to the magnetic stator assembly. The reciprocation or linear translation of the coils creates an electric current flowing through the coils, which may then be harvested.

24 Claims, 52 Drawing Sheets



U.S. PATENT DOCUMENTS

6,291,901	B1 *	9/2001	Cefo	290/1 R
6,321,863	B1	11/2001	Vanjani	
6,328,123	B1	12/2001	Niemann et al.	
6,552,450	B2	4/2003	Harty et al.	
6,852,061	B2	2/2005	Schoon	
6,909,223	B2	6/2005	Miyazawa	
6,948,578	B2	9/2005	Prucher	
6,974,399	B2	12/2005	Lo	
7,059,437	B2	6/2006	Heinen	
7,108,090	B2	9/2006	Turner	
7,150,340	B2	12/2006	Beck et al.	
7,156,196	B2	1/2007	Katsaros	
7,249,643	B2	7/2007	Etzioni et al.	
7,327,054	B2	2/2008	Ng et al.	
7,347,427	B2	3/2008	Heinen	
7,357,743	B2	4/2008	Mao et al.	
7,557,473	B2	7/2009	Butler	
2003/0034697	A1 *	2/2003	Goldner et al.	310/17
2003/0234585	A1 *	12/2003	Tu et al.	310/12
2004/0100100	A1 *	5/2004	Wilson	290/1 R
2004/0198170	A1	10/2004	Tilbor et al.	
2005/0164528	A1	7/2005	Furguth	
2005/0173851	A1	8/2005	Lloyd	
2005/0252706	A1	11/2005	Thomas	
2006/0071561	A1	4/2006	Chiu et al.	
2007/0090697	A1	4/2007	Bittner	
2008/0023237	A1	1/2008	Houle	
2008/0093913	A1	4/2008	Katsaros	
2009/0091196	A1	4/2009	Cooper	
2010/0253465	A1	10/2010	Yeh	
2011/0108339	A1	5/2011	Hunter	
2011/0109051	A1	5/2011	Hunter	
2011/0109174	A1 *	5/2011	Hunter	310/20
2011/0109413	A1	5/2011	Hunter et al.	

FOREIGN PATENT DOCUMENTS

EP	1 587 135	A1	10/2005
EP	1 607 251	A1	12/2005
EP	1 848 014	A1	10/2007
GB	2 065 983	A	7/1981
GB	2 344 223	A	5/2000
JP	04 175530	A	6/1992
JP	2006 050853	A	2/2006
WO	WO 02/095912	A1	11/2002
WO	WO 2008/010669	A1	1/2008

WO	WO 2011/057051	A1	5/2011
WO	WO 2011/057052	A1	5/2011
WO	WO 2011/057070	A2	5/2011
WO	WO 2011/057071	A1	5/2011

OTHER PUBLICATIONS

Zapworld, ZAPPY3 Takes Scooters to the Next Dimension [online] 2004 Retrieved from the Internet URL: <http://www.zapworld.com/node/93>.

Frost & Sullivan, "Overview of Electric Vehicles Market and Opportunities for Supply of Electric Motors," 13 pages (Jul. 26, 2009). Unpublished U.S. Appl. No. 12/590,495, filed Nov. 9, 2009, Ian W. Hunter.

Unpublished U.S. Appl. No. 12/590,493, filed Nov. 9, 2009, Hunter and Fofonoff.

Unpublished U.S. Appl. No. 12/590,494, filed Nov. 9, 2009, Tan W. Hunter.

Invitation to Pay Additional Fees and, Where Applicable, Protest Fee and Annex to Form PCT/ISA/206 Communication Relating to the Results of the Partial International Search Report from PCT/US2010/055616, 8 pages, Date of mailing Feb. 11, 2011.

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, International Search Report and Written Opinion in International Application No. PCT/US2010/055581, 12 pages, mailed Feb. 22, 2011.

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, International Search Report and Written Opinion in International Application No. PCT/US2010/055582, 13 pages, mailed Feb. 21, 2011.

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, International Search Report and Written Opinion in International Application No. PCT/US2010/055619, 9 pages, mailed Jan. 31, 2011.

Notification of Transmittal of The International Search Report and The Written Opinion of the International Searching Authority, for International Application PCT/US2010/055616, 19 pages, mailed on May 27, 2011.

U.S. Office Action mailed May 2, 2012 for U.S. Appl. No. 12/590,495.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 1E




FIG. 1F




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 2E




FIG. 2F




FIG. 2H




FIG. 2G




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 12D




FIG. 13A




FIG. 13B




FIG. 14A




FIG. 14B




FIG. 14C




FIG. 15




FIG. 16A




FIG. 16B




FIG. 16C




FIG. 16D




FIG. 16E




FIG. 17A




FIG. 17B




FIG. 18




FIG. 19A




FIG. 19B




FIG. 19c




FIG. 20A




FIG. 20B




FIG. 20C




FIG. 20D




FIG. 20E




FIG. 20F




FIG. 20G




FIG. 21A




FIG. 21B




FIG. 22A

FIG. 22B

FIG. 22C




FIG. 23A




FIG. 23B




FIG. 24A

FIG. 24B

FIG. 24C




FIG. 24F

FIG. 24E

FIG. 24D

1

ELECTRIC GENERATOR

BACKGROUND OF THE INVENTION

Electric generators convert mechanical energy to electrical energy by forcing electric charges to move through an electrical circuit, which is typically a coiled wire. There are two main types of electric generators: direct-current generators, which produce electric current that flows in one direction, and alternating-current generators, which produce electric current that reverses direction. Both types of generators work based on the same principles.

SUMMARY OF THE INVENTION

With greater interest in clean energy there is more interest in the efficient generation of electricity. An electric generator device includes a rotary-to-linear converter, a magnetic stator assembly, and opposed coils. Each coil is arranged to reciprocate relative to the magnetic stator assembly and is coupled to the rotary-to-linear converter, which may be, for example, a cam, Scotch yolk, crank, or other mechanical device for converting rotary motion into linear motion. Upon rotation, the rotary-to-linear converter drives the coils in opposed reciprocation, resulting in electric current flowing through the coils, which may then be harvested by drawing current from the coils.

The coils may linearly translate in a common direction, along with the converter, relative to the magnetic stator assembly, which also results in electric current flowing through the coils. The linear motion may occur with or without the rotary motion.

The magnetic stator assembly may include a single magnetic stator that is shared by the coils or may include multiple magnetic stators, each magnetic stator corresponding to a coil. A magnetic stator may include a single magnet or multiple magnets, and the coils may surround the single or multiple magnets, in which case the multiple magnets are inner magnets. The stator may further include multiple additional magnets arranged parallel to the first magnets and arranged outside of the coils, in which case the multiple additional magnets are outer magnets. In such a configuration, followers may be coupled to the coils at locations not covered by the outer magnets. For example, the coils may be rectangle-shaped, and four outer magnet assemblies may be arranged outside of the coils and along the four sides of the coils, but not covering the corners of the coils. The followers may then be connected to the corners of the coils, through intermediate structures, such as, for example, housings that surround the coils. The rectangle-shaped coils may be manufactured by stamping or etching a plurality of coil segments, such as U-shaped segments, and assembling the coil segments into a coil.

In configurations including a cam, the cam may be part of a disc and the magnetic stator assembly may be arranged parallel with the plane of the disc. Further, the coils may be coupled to the cam using followers, and rotary motion of the disc may cause rotary motion of the cam, causing reciprocation of the coils along the magnetic stator assembly and generation of electricity. The opposed coils may be arranged to reciprocate 180 degrees out of phase with each other to cancel each other's vibrations. The cam of the device may include an inner surface and an outer surface, and each of the coils may be coupled to the cam using a pair of followers, where a first of each pair of followers interfaces the inner surface and a second of each pair of followers interfaces the outer surface. In one configuration, the cam may include a

2

protrusion with inner and outer surfaces, where the inner surface faces inward and the outer surface faces outward. Alternatively, the cam may include a groove with inner and outer surfaces, where the inner surface faces outward and the outer surface faces inward. In such a configuration, each pair of cam followers is arranged inside the groove. The cam may take a variety of forms. For example, the cam may include an even number of lobes, each of which may be in the form of a portion of an Archimedes spiral.

This application relates to U.S. patent application titled "ELECTRIC MOTOR" by inventor Ian W. Hunter, U.S. patent application Ser. No. 12/590,495, U.S. patent application titled "ELECTRIC COIL AND METHOD OF MANUFACTURE" by inventors Ian W. Hunter and Timothy A. Fofonoff, U.S. patent application Ser. No. 12/590,493, and U.S. patent application titled "TUNABLE PNEUMATIC SUSPENSION" by inventor Ian W. Hunter, U.S. patent application Ser. No. 12/590,494. These applications are being filed concurrently with the present application, and the contents of these applications are incorporated herein by reference in their entirety.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing will be apparent from the following more particular description of example embodiments of the invention, as illustrated in the accompanying drawings in which like reference characters refer to the same parts throughout the different views. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating embodiments of the present invention.

FIGS. 1A and 1B illustrate example rotary devices.

FIG. 1C illustrates an example magnetic stator assembly.

FIGS. 1D-1F illustrate cross-sections of example rotary devices.

FIGS. 2A-2C illustrate components of an example rotary device in action.

FIG. 2D illustrates an example shape of a cam.

FIGS. 2E-2H illustrate an example rotary device in action and coupled to a wheel.

FIGS. 3A and 3B illustrate an example rotary device with an additional cam and magnetic stator components.

FIG. 4A illustrates a mount attached to the magnetic stator assembly of an example rotary device.

FIG. 4B illustrates a simplified cross-section of an example rotary device attached to the chassis of a vehicle.

FIGS. 5A-5D illustrate a support structure coupling a magnetic stator assembly and mount of an example rotary device with electromagnetic actuators and coils of the device through a plurality of shafts.

FIG. 6A illustrates a rotary bearing coupling a support structure of an example rotary device with a cam of the device.

FIG. 6B illustrates a wheel structure coupling a cam of an example rotary device with a wheel of a vehicle.

FIG. 7 illustrates a horizontal cross-section of an example rotary device.

FIG. 8 illustrates a horizontal cross-section of an example rotary device from a top-down view.

FIG. 9 illustrates an inner structure of a magnetic stator assembly of an example rotary device.

FIG. 10 illustrates a horizontal cross-section of an example rotary device.

FIG. 11 illustrates a horizontal cross-section of an example rotary device.

FIG. 12A illustrates a vertical cross-section of an example rotary device showing how a support structure of an example rotary device may be arranged.

FIGS. 12B-12D illustrate an example tunable pneumatic suspension.

FIGS. 13A and 13B illustrate an example rotary device at different vertical positions.

FIGS. 14A-14C illustrate the construction of an example coil of an electromagnetic actuator.

FIG. 15 illustrates a wheel that includes an example rotary device.

FIGS. 16A and 16B illustrate different views of an example rotary device.

FIGS. 16C and 16D illustrate two rotationally offset cams.

FIG. 16E illustrates an example shape of a cam.

FIGS. 17A and 17B illustrate a disc of an example rotary device coupled to a rim of a wheel.

FIG. 18 illustrates two support structures coupling respective magnetic stator assemblies with electromagnetic actuators through a plurality of shafts and fluid dampers.

FIGS. 19A-19C illustrate an example arrangement of magnetic stators.

FIGS. 20A-20G illustrate the construction of an example coil of an electromagnetic actuator.

FIGS. 21A and 21B illustrate a side view and a top view of two rotary devices with respective wheels.

FIGS. 22A-22C illustrate various different rotations of the wheels.

FIGS. 23A and 23B illustrate vertical movement of the wheels.

FIGS. 24A-24F illustrate a top view of a vehicle having four pairs of rotary devices with respective wheels.

DETAILED DESCRIPTION OF THE INVENTION

A description of example embodiments of the invention follows.

FIG. 1A shows an example rotary device 100 inside a wheel. The device includes a magnetic stator assembly 120, opposed electromagnetic actuators 110a, 110b, and a linear-to-rotary converter (e.g., cam) 105. The device may be attached to the chassis of a vehicle, for example, at a point on the far side of the wheel (not shown). The rotary device depicted inside the wheel may be attached to the wheel via the cam 105 using a circular plate, for example, which has been removed to show the inside of the wheel. Such a plate may be attached to both the rim of the wheel and the cam 105 using fasteners, such as bolts. The wheel and cam support plate rotate relative to a hub 145 about a bearing 150. It is important to note that the cam 105 is shown as an oval shape, but may take other forms, such as, for example, a cam having multiple lobes.

FIG. 1B shows the example rotary device 100 from the side of the wheel 140 and with the tire of the wheel 140, and some other components, removed. The core of the rotary device includes the cam 105, two opposed electromagnetic actuators 110a, 110b, and magnetic stator assembly 120. The electromagnetic actuators 110a, 110b each include a coil 115a, 115b that is arranged to reciprocate relative to the magnetic stator assembly 120. One electromagnetic actuator 110a is shown having a housing 155a surrounding its coil 115a and the other electromagnetic actuator 110b is shown with its housing removed to show its coil 115b.

The magnetic stator assembly 120 depicted in FIG. 113 is oriented vertically and may include a plurality of magnetic stators 125a, 125b. Each of the magnetic stators 125a, 125b may include a single magnet or multiple magnets. As current

is applied to the coils 115a, 115b of the electromagnetic actuators 110a, 110b (e.g., alternating current), the actuators 110a, 110b are forced to reciprocate vertically along the magnetic stator assembly 120 due to the resulting electromagnetic forces. As known in the art, when a coil carrying an electrical current is placed in a magnetic field, each of the moving charges of the current experiences what is known as the Lorentz force, and together they create a force on the coil. As depicted, the rotary device 100 may include a plurality of shafts 130a, 130b, coupled to a bearing support structure 165. The electromagnetic actuators 110a, 110b may slide along the shafts using, for example, linear bearings. Other bearings that may be used include air bearings, silicon nitride bearings, graphite bearings, and linear recirculating ball bearings. Attached to each electromagnetic actuator 110a, 110b may be a pair of followers 135a-d used to interface with the cam 105. To reduce friction, the followers 135a-d may spin to roll over the surfaces of the cam 105. The followers 135a-d may be attached to the electromagnetic actuators 110a, 110b via, for example, the actuators' housings. As the electromagnetic actuators 110a, 110b reciprocate, the force exerted by the followers 135a-d on the cam 105 drives the cam 105 in rotary motion.

FIG. 1C illustrates an example magnetic stator assembly 120 with two magnetic stators 125a, 125b. The magnetic stators 125a, 125b each include multiple magnets. For example, magnetic stator 125a includes, on one surface of the stator 125a, eight magnets 160a-h.

FIGS. 1D-1F illustrate simplified cross-sections of example rotary devices. The device of FIG. 1D is within a wheel 140 of a vehicle and includes a hub (or mount) 145 coupled to a magnetic stator assembly 120 having two magnetic stators 125a, 125b. Also shown are two electromagnetic actuators (including coils) 110a, 110b that reciprocate relative to the magnetic stator assembly 120 along shafts 130a, 130b (shown as dashed lines). The shafts 130a, 130b are coupled to a bearing support structure 165, keep the components of the device in vertical alignment, and prevent the wheel 140 from falling off of the device. A cam plate 170 coupled to the wheel 140 is rotably coupled to the bearing support 165 through a bearing 150. Affixed to the cam plate 170 is a cam 105 used to drive the plate 170 and, thus, the wheel 140 in rotary motion. The cam 105 is driven by the reciprocation of the electromagnetic actuators 110a, 110b using followers 135a-d that are coupled to the electromagnetic actuators 110a, 110b and that interface with the cam 105. Also included in the example device is a fluid damper 175a coupling the bearing support 165 and the mount 145. The fluid damper 175a suspends the mount 145 above the ground and may allow for some movement between the bearing support 165 and the mount 145, depending on the amount of resistance of the damper. For example, if the damper is a pneumatic damper, higher gas pressures inside the chambers of the damper allow for less movement than lower air pressures.

FIG. 1E illustrates that in the absence of the fluid damper 175a, the electromagnetic forces caused by the electromagnetic actuators 110a, 110b and magnetic stators 125a, 125b may suspend the mount 145 above the ground. If, however, electrical current is removed from the electromagnetic actuators 110a, 110b, the associated electromagnetic forces will also be removed and the mount 145 may drop toward the ground, along with the magnetic stator assembly 120 and vehicle chassis, as illustrated in FIG. 1F.

FIGS. 2A-2C illustrate components of the rotary device 100 in action, including the rotary device's electromagnetic actuators 110a, 110b (with associated coils 115a, 115b and

5

followers **135a-d**) and cam **105** moving relative to the magnetic stator assembly **120** (including associated magnetic stators **125a, 125b**). The housings by which the followers are attached to the coils are not shown in these figures. As illustrated by FIGS. **2A-2C**, the reciprocal movement of the coils **115a, 115b** in opposition drives the cam **105** to rotate, which, in turn, may cause a wheel attached to the cam **105** to rotate. The coils **115a, 115b** are shown in FIG. **2A** as being at almost their furthest distance apart. FIG. **2B** shows that as the coils **115a, 115b** move closer to each other, the coils **115a, 115b** drive the cam **105** to rotate in a clockwise direction, thereby causing any attached wheel to also rotate clockwise. In the example device, the force exerted on the cam **105** is caused by the outer followers **135a, 135c** squeezing-in on the cam **105**. FIG. **2C** shows that the coils **115a, 115b** are yet closer together causing further clockwise movement of the cam **105**.

After the coils **115a, 115b** have reached their closest distance together and the cam **105**, in this case, has rotated ninety degrees, the coils **115a, 115b** begin to move away from each other and drive the cam **105** to continue to rotate clockwise. As the coils **115a, 115b** move away from each other, the inner followers **135b, 135d** exert force on the cam **105** by pushing outward on the cam **105**. Again, it is important to note that the cam **105** is shown in the figures as an oval shape, but the cam **105** may be shaped in a more complex pattern, such as, for example, a shape having an even number of lobes, as illustrated in FIG. **2D**. The sides of each lobe may be shaped in the form of a sine wave or a portion of an Archimedes spiral, for example. The number of lobes determines how many cycles the coils must complete to cause the cam to rotate full circle. A cam with two lobes will rotate full circle upon two coil cycles. A cam with four lobes will rotate full circle upon four coil cycles. Additionally, more lobes in a cam creates a higher amount of torque. In addition to driving the cam in rotational motion, the electromagnetic actuators may act as generators by drawing current from the coils as the cam rotates. This also has the effect of reducing the rotational movement of the cam when energy is absorbed from the rotational movement of the cam. In an application of the device in a vehicle, drawing current from the coils may act as a regenerative braking mechanism for the vehicle. Because the devices may act as generators, rotation of the wheel caused by an outside force may recharge the batteries of a vehicle. For example, the vehicle may be positioned so that at least one of its wheels is placed on a recharging device that causes the wheel to rotate. Such a recharging device may be similar to a dynamometer, which may be placed on or in a floor. But while a vehicle causes a dynamometer to rotate, it is the rotation of the recharging device that causes the vehicle's wheel to rotate, thereby causing the electromagnetic actuators to act as generators and to charge the vehicle's batteries. The recharging device may be powered by, for example, electricity or fuel.

In some devices, heat produced by the reciprocation of the coils **115a, 115b** may be reduced by spraying a liquid coolant, such as, for example, water, on the coils **115a, 115b**. This may be accomplished by spraying liquid through openings **146** in the magnets of the magnetic stators **125a, 125b** and onto the coils **115a, 115b** as they pass by the openings **146**. The liquid coolant may be transported to the openings **146** through channels in the magnetic stator assembly **120**. The sprayed liquid may then be collected for reuse or may be allowed to convert to a gas and be vented from the rotary device.

FIGS. **2E-2H** also illustrate components of an example rotary device in action, but with a wheel **140** that is attached to the cam **105** through a plate, or similar structure (not shown). A white circle appears on the wheel **140** to show the wheels position at different points during reciprocation of the

6

electromagnetic actuators **110a, 110b**. As illustrated by the white circle in **2E-2H**, the wheel **140** rotates along with the rotating cam **105**.

FIG. **3A** illustrates a rotary device similar to the device of FIGS. **2A-2C**, but with an additional cam **106** on the other side of the magnetic stator assembly **120**. Reciprocation of the coils **115a, 115b** acts to also drive the second cam **106** in rotary motion, and the second cam **106** may be attached to the other side of a wheel using, for example, another circular plate. Also shown is that the magnetic stator assembly **120** of the example device may be in the shape of a long extended box-shaped core of magnetically permeable material, with a magnetic stator **125a, 125b** at either end. In the example device, each magnetic stator **125a, 125b** includes magnets on all four sides of the magnetic stator assembly **120**. The box-shaped core, on which the magnetic stators **125a, 125b** are affixed in the example device, may act as a return path for the magnetic flux of the magnetic stators **125a, 125b**. Also shown in FIG. **3A** is that the coils **115a, 115b** of the electromagnetic actuators may have a rectangular shaped cross-section and arranged to surround the magnetic stators **125a, 125b**. This arrangement allows for efficient utilization of the electromagnetic forces between the coils **115a, 115b** and the magnetic stators **125a, 125b**.

FIG. **3B** illustrates the rotary device of FIG. **3A**, but with additional magnets **325a, 325b** arranged outside of the coils **115a, 115b**. According to the example device, each end of the magnetic stator assembly **120** includes an additional four magnet arrays, one on each side of a rectangular cross-section coil **315a, 315b**. The additional magnets **325a, 325b** enables the creation of more electromagnetic force. Also shown in FIG. **3B** is an additional magnetic return path **320** for the additional magnets **325a, 325b**.

FIG. **4A** illustrates a mount **145** to which the magnetic stator assembly **120**, including magnets and return paths, may be attached. The mount may be part of, or further attached to, for example, a chassis of a vehicle (not shown). Specifically, the mount **145** includes outer and inner hub plates **445a, 445b**, the latter of which may be bolted to the chassis of a vehicle. Delivery of electrical current to the coils **115a, 115b** may be accomplished using electricity-conducting flexures (not shown in FIG. **4A**) that extend from the mount **145** to the coils **115a, 115b**. The flexures allow current to be delivered to the coils **115a, 115b** even as the coils reciprocate along the magnetic stator assembly **120**. Thus, the flexures may electrically couple to an electrical supply (not shown in FIG. **4A**), such as a battery, coupled to the mount or located in the chassis of a vehicle, the supply delivering electrical current to the coils **115a, 115b**.

FIG. **4B** illustrates a simplified cross-section of an example rotary device attached to the chassis of a vehicle **405**. FIG. **4B** is similar to FIGS. **1D-1F**, but with some components removed for clarity. The figures shows a mount **145** coupled to the chassis of a vehicle **405** and a magnetic stator assembly **120**. Also shown are a cam **105**, cam plate **170**, wheel **140**, bearing **150**, and electromagnetic actuators **110a, 110b**. Coupled to the mount **145** is an electrical unit **410**, which is used to deliver electricity to the electromagnetic actuators **110a, 110b** through a pair of flexures **415a, 415b**. Also coupled to the mount **145** is a battery **420** for storing electrical energy. Although the electrical unit **410** and the battery **420** are shown as being coupled to the mount **145**, the electrical unit **410**, battery **420**, or both may, instead, be coupled to the support structure **165** (FIG. **1D**).

According to the example rotary device, the electrical unit **410** may be controlled by a controller **430** on the chassis of the vehicle **405** and through a fiber-optic cable **435** running

between the controller **430** and the electrical unit **410**. The example rotary device also includes a bidirectional power line **440** connecting the electrical unit **410** and the battery **420**. During operation as a motor, power may flow from the battery **420** to the electrical unit **410** and on to the electromagnetic actuators **110a**, **110b**. During operation as a generator, power may flow from the electromagnetic actuators **110a**, **110b** to the electrical unit **410** and on to the battery **420**. The vehicle may also include a charger **425** for charging the battery **420** using an external power source (not shown), such as an electrical outlet or gasoline engine in the case of a hybrid vehicle. During such charging, power flows from the external power source to the charger **425** and on to the battery **420** through line **427**, the electrical unit **410**, and the bidirectional power line **440**. Thus, the battery **420** may be charged by either an external power source or by the rotary device acting as a generator.

Through delivery of electricity to the electromagnetic actuators **110a**, **110b**, the electrical unit **410** may control the reciprocation of the coils. For example, when at speed, the electrical unit **410** may control the constant reciprocation of the coils. In vehicular embodiments, the controller **430** may be operated by a driver (not shown) of a vehicle and, in response to actions by the driver, the controller **430** may send commands to the electrical unit **410** to cause the rotary device to accelerate, decelerate, or change direction, for example. In addition, the electrical unit **410** may be configured to provide an electrical component to the electromagnetic actuators **110a**, **110b** to drive their coils in the same direction, thereby creating a vertical translational movement of the wheel **140**. Any translational movement of the wheel **140**, caused by the rotary device or not, may be sensed by the electrical unit **410**. In some configurations, the electrical unit **410** may be configured to absorb energy from the translational movement of the wheel by causing the electromagnetic actuators **110a**, **110b** to act as electrical generators and dampers. This energy may be transferred to the battery **420** for storage.

FIG. **5A** illustrates a bearing support structure **165**. A rotary bearing (not shown) that supports the cam plate and, thus, the wheel is mounted to a flange **585**. The bearing support **165** and the electromagnetic actuators **110a**, **110b** with coils **115a**, **115b** are kept in vertical alignment using a plurality of shafts **130a-d**. If the rotary device is employed in the wheel of a vehicle, the support structure **165** allows the magnetic stator assembly **120**, mount **145**, and chassis of the vehicle (not shown) to remain suspended above the ground without electrical power. In the absence of the support structure **165**, the magnetic stator assembly **120**, mount **145**, and vehicle chassis may drop toward the ground when current is not applied to the coils **115a**, **115b**. Thus, both the support structure **165** and the electromagnetic actuators **110a**, **110b** can provide suspension for the vehicle, but the electromagnetic actuators **110a**, **110b** require electrical power to lift the magnetic stator assembly **120**, mount **145**, and vehicle chassis off the ground. The support structure **165**, on the other hand, may use fluid dampers (not shown) for suspension.

The support structure **165** also enables the use of multiple flexures in series for delivering electricity to the coils. For example, one set of flexures may run between the mount **145** and the support structure **165**, and another set of flexures may run between the support structure **165** and the coils **115a**, **115b**. Use of multiple flexures is advantageous when the bearing support **165** moves in a vertical direction. During such vertical movement of the bearing support **165** and reciprocation of the coils **115a**, **115b**, one set of flexures may flex with respect to the vertical movement of the bearing support **165**, and the other set of flexures may flex with respect to the

reciprocation of the coils **115a**, **115b**. If only one set of flexures were used (e.g., connected directly between the mount **145** and the coils **115a**, **115b**), more flex would be required upon vertical movement of the bearing support **165** and reciprocation of the coils **115a**, **115b**, possibly leading to increased stress and wear on the flexures.

FIG. **5B** illustrates the magnetic stator assembly **120**, mount **145**, and vehicle chassis as being raised with respect to the other components of the rotary device. This is accomplished either by adding an electrical component to the coils **115a**, **115b** to cause both coils to move in the same direction (e.g., in this case down relative to the stator assembly and chassis) or by using the fluid dampers (not shown) of the support structure **165**, as described below. The vertical movement of the coils **115a**, **115b** may occur concurrently with, or apart from, opposed coil reciprocation. The effect that the vertical movement has on a vehicle, for example, is to raise or lower the vehicle's ride height or to act as a shock absorber (e.g., going over bumps). To raise a vehicle's ride height, either the fluid dampers or the coils **115a**, **115b** may be used to raise, and keep raised, the chassis of the vehicle with respect to the wheels. To act as a shock absorber, either the fluid dampers or the coils **115a**, **115b** may react to a bump in the road by allowing the wheels to quickly rise with respect to the chassis of the vehicle and then return to their normal position. In addition, all four wheels of a vehicle may be thrust rapidly downwards with respect to the chassis of the vehicle to cause the vehicle to jump off of the ground. Thus, the rotary device may exhibit at least two degrees of movement: rotational movement with opposed reciprocation of the coils and linear movement with movement of the coils in a common direction. These degrees of movement may be performed either separately or together.

FIG. **5C** shows a horizontal cross-section through the device showing the support structure **165** as surrounding, but not coupled to, the mount **145**. Also shown are a plurality of shafts **130a-d** coupled to the support structure to maintain alignment among the components of the rotary device. A plurality of fluid dampers **175a-d**, described below, are also shown.

FIG. **5D** illustrates the side of an example rotary device including one pair of flexures **505a**, **505b** running between components **545a**, **545b** of the mount **145** and the support structure **165**, and another pair of flexures **510a**, **510b** running between the support structure **165** and the electromagnetic actuators **110a**, **110b**.

FIG. **6A** illustrates a rotary bearing **150** used to couple the bearing support structure **165** with one of the cams **105**. An inner race **650a** is coupled to the bearing support **165** and an outer race **650b** couples a wheel structure (not shown), such as a cam plate and, thus, to the cam **105** and outer wheel rim. The wheel structure may be a plate, a plurality of spokes, a lattice, or other appropriate structure as known in the art. The rotary bearing **150** is not coupled directly to the mount **145**, but rather, in the example device, through a fluid damper. Another rotary bearing (not shown) may be used to couple the support structure **165** with the other cam **105** on the other side of the rotary device. Because the rotary bearing **150** rotatably couples the bearing support structure **165** with an outer wheel rim, the support structure **165** and wheel have the same vertical position with respect to each other. Because of its constant vertical position with respect to the wheel, the shafts **130a-d** may be fixed to the support structure **165**, thereby preventing the shafts from coming into contact with the wheel.

FIG. **6B** illustrates a wheel structure **605** coupling a cam **105** of an example rotary device with a wheel rim **140** of a

vehicle. As illustrated, the cam **105** is fixed to the wheel structure **605**, and the wheel structure **605** is fixed (e.g., using bolts) to the wheel **104** rim. Rotation of the cam **105**, thus, causes rotation of the wheel structure **605** and the wheel **104**.

FIG. 7 shows a horizontal cross-section of an example rotary device. The cross-section is cut through one of the electromagnetic actuators **155**. Inside the electromagnetic actuator **155** is shown a coil **115a** and the components of the magnetic stator assembly **120**. According to the illustrated device, the magnetic stator assembly **120** includes an inner magnetic stator component **125a**, including a plurality of magnets, and an outer magnetic stator component **325a**, also including a plurality of magnets. The magnetic stator assembly **120** also includes an inner magnetic flux return path **725a** for the inner magnetic stator component **125a** and includes an outer magnetic flux return path **735a** for the outer magnetic stator component **325a**. As described above, the inner magnetic stator component **125a** and inner magnetic flux return path **725a** are located inside of the coil **115a**, and the outer magnetic stator component **325a** and outer magnetic flux return path **735a** are located outside of the coil **115a**. Also shown in the cross-section is the housing of the electromagnetic actuator **155**, which surrounds the coil **115a** and magnetic stator assembly **120** and slides along the long axis of the magnetic stator assembly **120** by sliding along a plurality of shafts **130a-d**. The housing of the electromagnetic actuator **155** may hold the coil **115a** using, for example, four bolts that run through the corners of the rectangular-shaped coil **115a**.

FIG. 8 shows another cross-section of the example rotary device, but from a top-down view. As in FIG. 7, the cross section shows a coil **115a**, inner magnetic stator component **125a**, outer magnetic stator component **325a**, inner magnetic flux return path **725a**, outer magnetic flux return path **735a**, electromagnetic actuator housing **155a**, and shafts **130a-d**. The inner magnetic stator component **125a** and inner magnetic flux return path **725a** are mounted to an inner structure **820** of an example magnetic stator assembly. As can be seen, a bolt may be inserted through bolt holes **815** at the corners of the coil **115a** to fix the coil **115a** to the housing **155a**.

FIG. 9 illustrates an inner structure **820** of an example magnetic stator assembly. A mount **145** (FIG. 4A) may be attached at point **910** to, for example, couple the structure **820** to the chassis of a vehicle. Channels **905a-d** may be used to transport a cooling fluid within the magnetic stator assembly to spray on the coils through the magnets.

FIG. 10 shows a cross-section of the example rotary device. The cross-section is cut through the middle of the device and shows the inner structure **820** of the magnetic stator assembly, mount **145**, inner magnetic flux return path **725a**, and outer magnetic flux return path **735a**. The cross-section also shows a channel **1005** used to access the inner part of the magnetic stator assembly for running wires or cooling fluid, for example.

FIG. 11 shows another cross-section of a rotary device as in FIG. 10, but at a point slight higher than the cross-section of FIG. 10. In addition to the channel **1005** for running wires or cooling lines, the cross-section shows channels **1105a-d** for inserting fasteners, such as screws.

FIG. 12A shows a vertical cross-section of the example rotary device. The cross-section shows how the support structure illustrated in FIGS. 5A and 5B may be slidably coupled to the magnetic stator assembly and the mount **145** using additional shafts **1230a**, **1230b** and fluid dampers **175a**, **175b**. As illustrated in FIG. 12A, the support structure **165** may be coupled to the lower rod of a fluid damper **175a**. Specifically, a connecting arm **1215a** pinned at point **1225a** to the lower end of the rod **1220a** is joined to the support at point **1205**. An

upper rod of the fluid damper **175a** may be connected to the mount **145** of the device, which may be part of a vehicle's chassis. The mount **145** joins suspension arm **1240a** at point **1210**. The shaft **1230a**, fixed to the support **165**, slides through the suspension arm **1240a** at opposite ends. The upper rod of the damper **175a** is pinned to the suspension arm **1240a** at point **1235a**.

The fluid dampers **175a**, **175b** may be a pneumatic suspension, such as a piston with opposing gas chambers. The pressure of the gas in each chamber above and below the piston may also be dynamically adjusted to either change the position of the magnetic stator assembly and the mount **145** (e.g., move up or down) or to change the stiffness of the dampers **175a**, **175b**. To change the position of the magnetic stator assembly and the mount **145**, pressure in the gas chambers may be adjusted so that the chambers have different pressures. For example, if the fluid dampers **175a**, **175b** each include a top and bottom chamber, more pressure would be applied to the top chamber to move the magnetic stator assembly and the mount **145** in the upward direction, and more pressure would be applied to the bottom chamber to move the magnetic stator assembly and the mount **145** in the downward direction. To change the stiffness of the dampers **175a**, **175b**, equal pressure may be added to or removed from the top and bottom chambers. If the rotary device is used in the wheel of a vehicle, changing the position of the magnetic stator assembly and the mount **145** can change the ride height of the vehicle, and changing the stiffness of the dampers **175a**, **175b** can change the stiffness of the vehicle's suspension.

The cross-section of FIG. 12A also shows the inside of the magnetic stator assembly. An example arrangement of the coil **115b** of an electromagnetic actuator, inside magnetic stator component **125b**, and outside magnetic stator component **325b** can be seen through the cross-section. Also visible is the magnetic flux return path **735b** for the outside magnetic stator component **325b**.

FIGS. 12B-12D illustrate an example tunable pneumatic suspension. FIG. 12B shows that the suspension **175a** includes a piston **1276** and opposed chambers **1277a**, **1277b** applying respective opposed pneumatic pressures to opposite faces **1278a**, **1278b** of the piston **1276**. The example suspension **175a** includes a top chamber **1277a** and a bottom chamber **1277b**. Also shown is a pneumatic controller **1279** that independently controls the pneumatic pressures in the chambers **1277a**, **1277b**.

The pressures of the chambers **1277a**, **1277b** may be adjusted to change the relative positions of the piston **1276** and the chambers **1277a**, **1277b** by differing the pressures. For example, as shown in FIG. 12C, a higher pressure in the bottom chamber **1277b** of the suspension **175a**, as compared to the top chamber **1277a**, exerts more force on the bottom face **1278b** of the piston **1276**, causing the piston **1276** and the bottom chamber **1277b** to move away from each other. As shown in FIG. 12D, a higher pressure in the top chamber **1277a**, as compared to the bottom chamber **1277b**, exerts more force on the top face **1278a** of the piston **1276**, causing the piston **1276** and the top chamber **1277a** to move away from each other. If the suspension **175a** is part of a vehicle, this movement can change the ride height of the vehicle, the direction of the vehicle's movement depending on whether the chambers **1277a**, **1277b** or the piston **1276** are coupled to the chassis of the vehicle. Either the chambers **1277a**, **1277b** or the piston **1276** may be grounded, while the other is coupled to the chassis of the vehicle.

In addition to changing the position of the piston **1276**, the pressures of the chambers **1277a**, **1277b** may be adjusted to

change the stiffness of the suspension **175a** by adding or removing equal pressures to or from the chambers **1277a**, **1277b**. Adding equal pressure to both chambers **1277a**, **1277b** increases the stiffness of the suspension **175a**, and removing equal pressures from both chambers **1277a**, **1277b** decreases the stiffness of the suspension **175a**. If the suspension **175a** is part of a vehicle, changing the stiffness of the suspension **175a** can change the stiffness of the vehicle's ride.

FIG. **13A** illustrates an example rotary device incorporating many of the above-described features. The rotary device includes, for example, a cam **105**, two opposed electromagnetic actuators (including an example housing **155a** and coil **115b**), a magnetic stator assembly (including an example inner magnetic stator component **125b**, outer magnetic stator component **325b**, and outer magnetic flux return path **735b** for the outer magnetic stator component **325b**), mount **145**, suspension arms **1240a**, **1240b**, followers **135a-d**, support structure **165**, rotary bearing **150**, shafts **130a**, **130b**, **1230a**, **1230b**, and fluid dampers **175a**, **175b**.

FIG. **13B** illustrates the rotary device of FIG. **13A**, but where the fluid dampers **175a**, **175b** have been used to raise the magnetic stator assembly and the mount **145** by, for example, applying more pressure to a top chamber within each of the fluid dampers **175a**, **175b**. As illustrated in FIG. **13B**, the fluid dampers **175a**, **175b**, suspension arms **1240a**, **1240b**, magnetic stator assembly and the mount **145** are in a vertically higher position than illustrated in FIG. **13A**.

FIGS. **14A-14C** illustrate the construction of an example coil from one of the electromagnetic actuators. Instead of being made from one continuous piece of material, the coil may include multiple flat coil segments stacked together and electrically coupled in series. FIG. **14A** illustrates four coil segments that are combined into one coil **1400**. The coil of a given electromagnetic actuator may include a number of such coils. FIG. **14B** illustrates one of the coil segments **1401**. FIG. **14C** illustrates an exploded view **1405** of the coil of FIG. **14A**. Each segment **1410a-d** of the example coil may be a flat, U-shaped piece of metal formed by, for example, a stamping or etching process. The segments **1410a-d** may be assembled in the configuration shown in FIG. **14C** to form a full coil.

FIG. **14C** shows four U-shaped coil segments **1410a-d** that are stacked on top of each other, where each segment is rotated 270 degrees (or 90 degrees depending on the direction of rotation) with respect to the coil segment it follows in the stack of coil segments. In stacking the segments **1410a-d** in rotated positions, the segments **1410a-d** may be positioned so that a starting end **1425** of an upper coil segment **1410b** in the stack interfaces a finishing end **1420** of an immediately lower coil segment **1410a** in the stack. The coil including the four U-shaped coil segments **1410a-d**, for example, loops around three times to finish at the same relative position (e.g., ends **1415** and **1450**) that it started.

Electric current may flow through the coil, for example, from a starting end of a bottom-most coil segment in the stack to a finishing end of a top-most coil segment in the stack. In the example coil, when assembled, electrical current **1455** may flow through the coil, for example, from a starting point **1415** to an ending point **1450**. The current **1415** may begin at point **1415** and flow counter-clockwise around segment **1410a** to point **1420**. At point **1420**, the current continues to point **1425** as points **1420** and **1425** are in electrical contact with each other once assembled, as shown, for example, in FIG. **14A**. From point **1425**, the current **1415** flows counter-clockwise around segment **1410b** to point **1430**, where the current continues to point **1435** as described above. From point **1435**, the current **1415** flows counter-clockwise around segment **1410c** to point **1440**, where the current continues to

point **1445**, and flows counter-clockwise around segment **1410d** to point **1450**. If combined with other segments, the current may continue to flow from one segment to a subsequent segment in a longer coil. Overall, a method of manufacturing such an electric coil includes fabricating the multiple flat coil segments, stacking the multiple coil segments together where each coil segment is rotated with respect to the coil segment it follows, and fastening the coil segments together to form the electric coil.

To prevent the electrical current from straying from the above-described path, each segment may be coated with an electrically-insulating layer of material, except for the surfaces between which the current is meant to propagate, such as the top surface of point **1420** and the bottom surface of point **1425**. Alternatively, instead of being coated, layers of electrically-insulating material may be inserted between the coil segments. When the coil segments **1410a-d** are assembled in the form illustrated in FIG. **14A**, fasteners, such as bolts, may be inserted through the openings shown at points **1415**, **1420**, **1425**, **1430**, **1435**, **1440**, **1445**, and **1450**. The segments **1410a-d** may also be joined by soldering or brazing in addition to, or instead of, preloading the mechanical and electrical connections with fasteners. When the segments **1410a-d** are assembled, there may remain gaps between some of the above points. To allow the fasteners to tightly secure the coil segments **1410a-d** together, electrically-insulating spacers may be inserted between the points to fill the gaps. For example, when the segments **1410a-d** are assembled, a gap may remain between points **1415** and **1450**, and one or more spacers may be inserted between points **1415** and **1450** to fill the gap. On the other hand, no gap should exist between points **1420** and **1425**. The fasteners may also be insulated using, for example, heat shrink tubing.

The coil segments **1410a-d** may be mechanically and electrically joined together using bolts that pass through openings included in the segments **1410a-d**, where the openings are positioned outside the coil path so that a continuous, helical, flat coil may be formed. Fabricating coil segments at a constant thickness may be simple and inexpensive, but, at a constant thickness, the coil segment connections may occur outside the coil path so that intermediate segments do not overlap with the connection points. The shape of the connection points **1415**, **1420**, **1425**, **1430**, **1435**, **1440**, **1445**, **1450** may be chosen so that there is adequate contact area for a good mechanical connection that produces an acceptable contact resistance between the segments. The coil segments may be electroplated, with gold or nickel for example, to further reduce the contact resistance.

The connection points **1415**, **1420**, **1425**, **1430**, **1435**, **1440**, **1445**, **1450** may be raised or lowered so that the coil path continues in a smooth manner, without any sudden ledges or stress points, and with the connection centered at the level of connection. For example, for the connection between segments **1410a** and **1410b**, point **1420** may be lowered and point **1425** may be raised, as illustrated in FIG. **14C**. The amount that the points are raised or lowered by may be one-half of the thickness of the segments **1410a-d**. The overall helical path may be set by slight inclines, or a continuous incline, included in supporting structures immediately above and below the coil. The supporting structures may be clamped-down on the coil when the bolts are tightened, and can also include starting levels for the four bolts so that the coil may be formed with smooth transitions and minimal deformation in the segments **1410a-d** when the bolts are tightened. A similar approach is possible where three bolts are used and segments repeat more frequently, possibly forming a triangular shaped coil. Use of a greater number of bolts is

also possible. The segments may also be fabricated so that a circular path is formed, rather than a rectangular one.

Instead of including raised and lowered sections in the coil segments **1410a-d**, the connection points **1415**, **1420**, **1425**, **1430**, **1435**, **1440**, **1445**, **1450** may be of half-thickness, where two segments join together to yield the coil path thickness, and the path would continue smoothly. This type of connection may overlap with intermediate segments to a larger degree. Additionally, in some devices, added stress and deformation caused by not raising and lowering the connection points **1415**, **1420**, **1425**, **1430**, **1435**, **1440**, **1445**, **1450** in the segments **1410a-d** may be acceptable, and the tensioning in the bolts may be used to give the segments **1410a-d** their final shape.

FIG. **15** illustrates another example rotary device **1500** inside a wheel. As with the devices described above, the device **1500** may be attached to the chassis of a vehicle. The device **1500** includes a cam **1505**, two opposed electromagnetic actuators **1510a**, **1510b**, a magnetic stator assembly **1520** (including magnetic stators **1515a**, **1515b**), a support structure **1525**, and fluid dampers **1530a**, **1530b**. The rotary device depicted inside the wheel may be attached to the wheel via the cam **1505** as described below.

FIG. **16A** illustrates the example rotary device **1500** with the tire of the wheel, and some other components, removed. The device **1500** is similar to the devices described above, but includes a central disc **1635** sandwiched between to pairs of electromagnetic actuators **1510a**, **1510b**, **1610a**, **1610b** and two magnetic stator assemblies **1520**, **1620**. Each of the magnetic stator assemblies **1520**, **1620** includes two magnetic stators **1515a**, **1515b**, **1615a**, **1615b**, which include magnetic flux return paths **1640a-d** and magnets (e.g., **1630a**, **1630b**). The housings surrounding the coils of the electromagnetic actuators **1510a**, **1510b**, **1610a**, **1610b** are not shown. Each coil reciprocates along four arrays of magnets, which, as described above, may include multiple magnets. Two of the magnet arrays are located inside the coil (e.g., inner magnetic stator component **1630b**) and two are located outside the coil (e.g., outer magnetic stator component **1630a**). Each set of magnets are mounted to a magnetic flux return path **1640a-d**.

The disc **1635** includes two cams, one on either side of the disc **1635**. Each cam of the example device is in the form of a groove that includes an inner surface **1605a** and an outer surface **1605b**. Coupled to electromagnetic actuators **1510a** and **1510b** are two pairs of followers **1625a**, **1625b**, the different followers of each pair interfacing with a respective surface **1605a**, **1605b** of the cam. Electromagnetic actuators **1610a** and **1610b** are similarly coupled to followers. As the coils move towards each other, one of the followers of each electromagnetic actuator **1510a**, **1510b** exerts force on the inner surface **1605a** of the cam. As the coils move away from each other, the other follower exerts force on the outer surface **1605b** of the cam.

FIG. **16B** illustrates a different view of the example rotary device **1500**. It should be apparent that each pair of electromagnetic actuators (pair **1510a**, **1510b** and pair **1610a**, **1610b**) are at different phases of reciprocation. This is because, in the example device, the cams on either side of the disc **1635** are rotationally offset from each other by, for example, forty-five degrees. This helps to prevent the actuators from stopping at a point on the cams from which it would be difficult to again start. Thus, if one pair of actuators stops on a “dead-spot” of its respective cam, the other pair of actuators would not be at a dead-spot. Alternatively, if the cams were not offset from each other, or if only one cam were used, a controller may control the rotation of the cam so that the actuators do not stop on a dead spot. FIG. **16B** also

illustrates an arrangement of the coils and magnetic stator components. For example, magnetic stators components **1630b** and **1630c** are located inside the coil of actuator **1610a**, and magnetic stators components **1630a** and **1630d** are located outside the coil.

FIG. **16C** illustrates two rotationally offset cams **1505**, **1606**. The cams **1505**, **1606** may be part of or mounted on a disc **1635**. One cam **1505** may be on one side of the disc **1635**, and the other cam **1606** may be on the opposite side, as indicated by the dashed line. In some devices the cam may be offset by forty-five degrees, for example. The cams **1505**, **1606** may have any even number of lobes. Cams having two lobes, for example, may be offset by forty-five degrees. Cams having four lobes, for example, may be offset by twenty-two and a half degrees.

FIG. **16D** illustrates a vertical cross-section of a disc **1635** with two rotationally offset cams, each having in inner surface **1605a**, **1605c** and an outer surface **1605b**, **1605d**. Due to the offset, the inner surfaces **1605a**, **1605c** are not in line with each other. Likewise, the outer surfaces **1605b**, **1605d** are also not in line with each other.

FIG. **16E** illustrates that the inner and outer surfaces **1605a**, **1605b** of a cam may be shaped in a complex pattern, such as, for example, a shape having an even number of lobes. As noted above, the sides of each lobe may be shaped in the form of a sine wave or portions of an Archimedes spiral, for example. The inner and outer surfaces **1605a**, **1605b** illustrated in FIG. **16E** each have four lobes.

FIG. **17A** illustrates how the disc **1635** of the example rotary device may be coupled to the rim **1705** of a wheel. The rim **1705** may consist of one piece to which the disc **1635** may be affixed using fasteners, such as bolts, along an inner ring **1715**. Alternatively, the rim **1705** may include two parts **1710a**, **1710b** that bolt together along ring **1715**. When fastened together, the two parts **1710a**, **1710b** form a full rim **1705** with inner ring **1715**. A tire may then be mounted to the rim **1705**. FIG. **17B** shows how the disc **1635** may be fastened to the inner ring **1715** of the disc **1635**.

FIG. **18** illustrates two support structures **1525**, **1825** coupling respective magnetic stator assemblies **1520**, **1620** with electromagnetic actuators **1510a**, **1510b**, **1610a**, **1610b** through a plurality of shafts and fluid dampers **1530a**, **1530b**, **1830a**. Support structure **1525** is slidably coupled to magnetic stator assembly **1520** using fluid dampers **1530a**, **1530b**. Fluid damper **1530a** may be coupled to the support structure **1525**, for example, at point **1810** and coupled to magnetic stator assembly **1820a** at point **1805**. Likewise, support structure **1825** is slidably coupled to magnetic stator assembly **1620** using fluid damper **1830a** and a corresponding fluid damper (now shown) on the far side of the device.

FIGS. **19A-19C** illustrate an example arrangement of the components of a magnetic stator assembly. Referring to FIG. **19A**, magnet array **1910a** is an outer magnet array and magnet array **1910b** is an inner magnet array. The overall magnetic flux return path **1640a** supports the magnet arrays. The particular geometric shape of the example return path **1640a** allows the return path **1640a** to be formed using a cost-effective extrusion process. Specifically, four flux paths may be joined together at a center junction and two end junctions, and many such structures may be cut from a single extrusion. Also illustrated is a base structure **1920a** on which the magnetic stator components may be mounted.

FIG. **19B** illustrates a component **1905** used to deliver liquid coolant to the magnets, which may be sprayed onto the coils as they pass by the magnets. Liquid coolant may be transported from the base structure **1920a** to the magnet arrays **1910a**, **1910b** through a component **1905** that is fas-

tened along the edge of the return path **1640a**. The liquid may flow through an opening **1915** in the base structure **1920a**, through a channel **1917** of the component **1905**, and into a chamber **1925** located in a gap formed by parts of the return path **1640a**. From inside the chamber **1925**, the liquid coolant may be directed through openings (e.g., holes) in the magnet arrays **1910a**, **1910b** and sprayed onto the coils as they reciprocate by the openings.

FIG. **19C** illustrates four magnetic stators that are coupled to a central mount **1945**. If the rotary device is employed in the wheel of a vehicle, for example, the mount **1945** may be coupled to the chassis of the vehicle.

FIGS. **20A-20G** illustrate the construction of an example coil from one of the electromagnetic actuators. FIG. **20A** shows an entire coil **2000** from an electromagnetic actuator. It should be noted that the coil **2000** may consist of many smaller coils. FIG. **20B** illustrates four coil segments that are combined into one coil **2005**. A number of such segments may be combined to form the larger coil **2000** of FIG. **20A**. FIG. **20C** is an exploded view **2010** of the coil **2005** of FIG. **20B**. Each segment **2015**, **2020**, **2025**, **2030** of the example coil may be a flat piece of metal formed by, for example, a stamping or etching process. The segments **2015**, **2020**, **2025**, **2030** may be assembled in the configuration shown in FIG. **20C** to form a full coil. When assembled, electrical current **2075** may flow through the coil, for example, from starting point **2035** to ending point **2070**. For example, the current **2075** may begin at point **2035** and flow counter-clockwise around segment **2015** to point **2040**. At point **2040**, the current continues to point **2045** as points **2040** and **2045** are in electrical contact with each other when the segments are combined. From point **2045**, the current **2075** flows counter-clockwise around segment **2020** to point **2050**, where the current continues to point **2055** as described above. From point **2055**, the current **2075** flows counter-clockwise around segment **2025** to point **2060**, where the current continues to point **2065**, and flows counter-clockwise around segment **2030** to point **2070**.

As described above, to prevent the electrical current from straying from the above-described path, each segment may be coated with an electrically-insulating layer of material, except for the surfaces between which the current is meant to propagate, such as the top surface of point **2040** and the bottom surface of point **2045**. When the coil segments are assembled in the form illustrated in FIG. **20B**, fasteners, such as bolts, may be inserted through the openings of the segments. When the segments are assembled, there may remain gaps between some of the above points. To allow the fasteners to tightly secure the segments together, electrically-insulating spacers may be inserted between the points to fill the gaps.

FIG. **20D** shows one coil segment **2015**. FIG. **20E** shows a second coil segment **2020** stacked on top of segment **2015**. FIG. **20E** shows a third coil segment **2025** stacked on top of segments **2015** and **2020**, and FIG. **20G** shows a fourth coil segment **2030** stacked on top of segments **2015**, **2020**, and **2025**, resulting in a full coil as illustrated in FIG. **20B**.

FIG. **21A** illustrates a side view of two rotary devices with respective wheels **2105a**, **2105b**. FIG. **21B** illustrates a top view of the same two devices and wheels **2105a**, **2105b**. The two devices are used in tandem and may be used in vehicular applications. For example, a vehicle may include four pairs of devices, one pair at each corner of the vehicle. Each device includes a magnetic stator assembly, opposed coils, and linear-to-rotary converter (hidden from view). The devices are coupled to respective wheels **2105a**, **2105b** and are held together with a central mounting structure **145**. The mounting structure **145** may include, or be coupled to, a vertical shaft **2110** for coupling to the chassis of a vehicle. The shaft **2110**

may allow rotation of the two wheels **2105a**, **2105b** relative to the chassis of the vehicle and about the shaft **2110**.

FIGS. **22A-22C** illustrate example rotations of the wheels **2105a**, **2105b**. FIG. **22A** shows that the rotary devices may create propulsion for the vehicle by causing both wheels **2105a**, **2105b** to rotate in the same direction. FIG. **22B** shows that the rotary devices may cause the two wheels to turn with respect to the vehicle by rotating the wheels **2105a**, **2105b** at differential rates. The difference in wheel rotation rates creates propulsion for the vehicle and causes the vehicle to move along a curved path. FIG. **22C** shows that the rotary devices may cause the two wheels to turn with respect to the vehicle by rotating the wheels **2105a**, **2105b** in opposite directions when the vehicle is not in motion.

FIGS. **23A** and **23B** illustrate example vertical movement of the wheels **2105a**, **2105b**. FIG. **23A** shows that one of the devices may cause its respective wheel **2105b** to move in a vertical direction off of the ground. The wheel **2105b** may also be rapidly shook in the vertical direction to remove liquid from the surface of the wheel **2105b**. Additionally, both wheels **2105a**, **2105b** may move up or down together to lower or raise the ride height of the vehicle. The two wheels **2105a**, **2105b** may even be thrust downward with sufficient force to cause the vehicle to jump. FIG. **23B** shows that the shaft **2110** may be coupled to the chassis of the vehicle so as to allow for angular movement of the shaft **2110** relative to the chassis by, for example, using a pivot **2305** or similar component to couple the shaft **2110** with the chassis. In this configuration, different vertical movements of the two wheels **2105a**, **2105b** causes the wheels **2105a**, **2105b** to tilt, or camber. For example, one wheel **2105a** may move downward and the other wheel **2105b** may move upward, causing the wheels **2105a**, **2105b**, as well as the mount **145** and shaft **2110** to tilt. Alternatively, a pivot, or similar component, may be used to couple the shaft **2110** with the mount **145**, causing the wheels **2105a**, **2105b** and the mount **145** to tilt, but not the shaft **2110**.

FIGS. **24A-24F** illustrate a top view of a vehicle **2405** having four pairs of rotary devices with respective pairs of wheels **2410a-d**. FIG. **24A** shows the vehicle **2405** with four pairs of rotary devices and respective wheels **2410a-d**, one pair at each corner of the vehicle **2405**. The vehicle may also be configured with different wheel arrangements, such as two pairs of rotary devices and respective wheels at the front corners of the vehicle. In such an arrangement, the wheels at the rear corners of the vehicle may be conventional vehicle wheels. As shown in FIG. **24A**, all of the wheel pairs **2410a-d** may be oriented in the forward direction to provide forward propulsion for the vehicle. FIG. **24B** shows that the two front pairs of wheels **2410a**, **2410b** may be turned to the right, for example, to cause the moving vehicle **2405** to turn to the right. FIG. **24C** shows that the rear pairs of wheels **2410c**, **2410d** may be turned in a complimentary direction, for example, to the left, to improve the turning radius of the vehicle **2405**. FIG. **24D** shows that each of the wheel pairs **2410a-d** may be oriented in a direction that is tangential to a circular path to cause the vehicle **2405** to rotate about its center. FIG. **24E** shows that each of the wheel pairs **2410a-d** may be oriented in the same direction, other than the forward direction, to cause the vehicle **2405** to move, for example, diagonally or sideways. FIG. **24F** shows that each of the wheel pairs **2410a-d** may be pointed toward, or away from, the center of the vehicle to prevent any movement of the vehicle, obviating the need for a parking brake. The independent movements of each wheel may be controlled by a respective electrical unit **410** (FIG. **4B**) and all movements may be coordinated by a central controller **430** (FIG. **4B**) in communication with the electrical units.

While this invention has been particularly shown and described with references to example embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the scope of the invention encompassed by the appended claims. For example, in addition to being used in a motor vehicle, the disclosed devices may also be used in trains, planes, robots, and force-reflecting human interfaces.

What is claimed is:

1. An electric generator device comprising:
 - a rotary-to-linear converter;
 - a magnetic stator assembly including a core having one or more magnets producing magnetic fields;
 - opposed coils circumscribing the core, each coil arranged to reciprocate relative to the magnetic stator assembly and each coil coupled to the rotary-to-linear converter, the rotary-to-linear converter driving the coils in reciprocation upon rotation within the rotary-to-linear converter, resulting in electric current flowing through the coils as the coils move through the magnetic fields produced by the one or more magnets; and
 - an electronic unit configured to receive power flow from the coils,
 - wherein the magnetic stator assembly includes multiple inner magnets and the coils surround the multiple inner magnets,
 - wherein the magnetic stator assembly further includes multiple outer magnets arranged parallel to the inner magnets and arranged outside of the coils, and
 - wherein followers are coupled to the coils at locations of the coils not covered by the outer magnets.
2. An electric generator device as in claim 1 wherein the electronic unit harnesses electricity by drawing current from the coils as a consequence of the rotary motion within the rotary-to-linear converter.
3. An electric generator device as in claim 1 wherein the electronic unit harnesses electricity by drawing current from the coils as the rotary-to-linear converter translates relative to the magnetic stator assembly.
4. An electric generator device as in claim 1 wherein the magnetic stator assembly includes a magnetic stator shared by the reciprocating coils.
5. An electric generator device as in claim 1 wherein the magnetic stator assembly includes multiple magnetic stators, each magnetic stator corresponding to a reciprocating coil.
6. An electric generator device as in claim 1 wherein the coils are arranged to reciprocate 180 degrees out of phase with each other.
7. An electric generator device as in claim 1, wherein (i) the coils are rectangle-shaped, (ii) the outer magnets include four magnets arranged outside of the coils along the four sides of the coils, and (iii) the followers are connected to the corners of the coils.
8. An electric generator device comprising:
 - a rotary-to-linear converter;
 - a magnetic stator assembly including a core having one or more magnets producing magnetic fields;
 - opposed coils circumscribing the core, each coil arranged to reciprocate relative to the magnetic stator assembly and each coil coupled to the rotary-to-linear converter, the rotary-to-linear converter driving the coils in reciprocation upon rotation within the rotary-to-linear converter, resulting in electric current flowing through the coils as the coils move through the magnetic fields produced by the one or more magnets; and
 - an electronic unit configured to receive power flow from the coils,

wherein the rotary-to-linear converter comprises a cam, wherein (i) the cam is part of a disc, (ii) the magnetic stator assembly is arranged in parallel with the plane of the disc, (iii) the coils are coupled to the cam using followers; and (iv) rotary motion of the disc causes rotary motion of the cam to cause reciprocation of the coils along the magnetic stator assembly and to generate electricity.

9. An electric generator device comprising:

- a rotary-to-linear converter;
- a magnetic stator assembly including a core having one or more magnets producing magnetic fields;
- opposed coils circumscribing the core, each coil arranged to reciprocate relative to the magnetic stator assembly and each coil coupled to the rotary-to-linear converter, the rotary-to-linear converter driving the coils in reciprocation upon rotation within the rotary-to-linear converter, resulting in electric current flowing through the coils as the coils move through the magnetic fields produced by the one or more magnets; and
- an electronic unit configured to receive power flow from the coils,
- wherein the rotary-to-linear converter comprises a cam, wherein (i) the cam includes an inner surface and an outer surface and (ii) each of the coils is coupled to the cam using a pair of followers, a first of each pair of followers interfacing with the inner surface, and a second of each pair of followers interfacing with the outer surface.

10. An electric generator device as in claim 9 wherein the cam includes a protrusion that includes the inner surface and the outer surface, the inner surface facing inward and outer surface facing outward.

11. An electric generator device as in claim 9 wherein (i) the cam includes a groove that includes the inner surface and the outer surface, the inner surface facing outward and outer surface facing inward and (ii) each pair of followers are arranged inside the groove.

12. An electric generator device comprising:

- a rotary-to-linear converter;
- a magnetic stator assembly including a core having one or more magnets producing magnetic fields;
- opposed coils circumscribing the core, each coil arranged to reciprocate relative to the magnetic stator assembly and each coil coupled to the rotary-to-linear converter, the rotary-to-linear converter driving the coils in reciprocation upon rotation within the rotary-to-linear converter, resulting in electric current flowing through the coils as the coils move through the magnetic fields produced by the one or more magnets; and
- an electronic unit configured to receive power flow from the coils,
- wherein the rotary-to-linear converter comprises a cam, and
- wherein the cam includes an even number of lobes.

13. An electric generator device as in claim 12 wherein a portion of each of the lobes is a portion of an Archimedes spiral.

14. The electric generator device of claim 1 further comprising a wheel rim, wherein during operation the rotary-to-linear converter converts rotary motion of the wheel rim to the reciprocating movements of the coils.

15. The electric generator device of claim 14 further comprising a support member attached to the wheel rim and coupled to the rotary-to-linear converter.

16. The electric generator device of claim 14, wherein the magnetic stator assembly and the coils are contained within a volume encircled by the wheel rim.

19

17. An electric generator device comprising:
 a magnetic stator assembly including a first magnetic stator core portion having an axis that is oriented radially relative to a rotational axis and a second magnetic stator core portion having an axis that is oriented radially relative to the rotational axis, said first magnetic stator core portion including one or more magnets generating magnetic fields and said second magnetic stator core portion including one or more magnets also generating magnetic fields;
 a first coil arranged around the first magnetic stator core portion;
 a second coil arranged around the second magnetic stator core portion;
 a rotary-to-linear converter to which the first and second coils are coupled and which during operation converts rotary movement about the rotational axis to linear reciprocating movement of the first and second coils along the first and second magnetic stator core portions, respectively, in radial directions relative to the rotational axis and passing through the magnetic fields produced by the one or more magnets of the first and second magnetic stator core portions; and
 an electronic unit configured to receive power flow from the coil,
 wherein the axis of the first magnetic stator core portion is parallel to the axis of the second magnetic stator core portion and wherein during operation the rotary-to-linear converter causes the first coil and the second coil to move in opposition to each other.

18. The electric generator device of claim 17, further comprising a wheel rim, wherein during operation the rotary-to-linear converter converts rotary motion of the wheel rim to the linear reciprocating movements of the first-mentioned coil and the second coil.

19. The electric generator of claim 18 further comprising a support member attached to the wheel rim and coupled to the rotary-to-linear converter.

20. The electric generator device of claim 19, wherein the support member comprises a disc plate.

21. An electric generator device comprising:
 a magnetic stator assembly including a first magnetic stator core portion having an axis that is oriented radially relative to a rotational axis and a second magnetic stator core portion having an axis that is oriented radially relative to the rotational axis, said first magnetic stator core portion including one or more magnets generating magnetic fields and said second magnetic stator core portion including one or more magnets also generating magnetic fields;
 a first coil arranged around the first magnetic stator core portion;
 a second coil arranged around the second magnetic stator core portion;
 a rotary-to-linear converter to which the first and second coils are coupled;

20

an electronic unit configured to receive power flow from the coil; and
 a wheel rim coupled to the rotary-to-linear converter and which during operation rotates about the rotational axis, wherein the magnetic stator assembly, the first coil, and the second coil are contained within a volume encircled by the wheel rim, and
 wherein during operation the rotary-to-linear converter converts rotary motion of the wheel rim to the linear reciprocating movements of the first coil and the second coil along, respectively, the first and second magnetic stator core portions in radial directions relative to the rotational axis and passing, respectively, through the magnetic fields produced by the one or more magnets of the first and second magnetic stator core portions.

22. An electric generator device comprising:
 a magnetic stator assembly including a first magnetic stator core portion having an axis that is oriented radially relative to a rotational axis and a second magnetic stator core portion having an axis that is oriented radially relative to the rotational axis, said first magnetic stator core portion including one or more magnets generating magnetic fields and said second magnetic stator core portion including one or more magnets also generating magnetic fields;
 a first coil arranged around the first magnetic stator core portion;
 a second coil arranged around the second magnetic stator core portion;
 a rotary-to-linear converter to which the first and second coils are coupled;
 an electronic unit configured to receive power flow from the coil; and
 a wheel rim coupled to the rotary-to-linear converter and which during operation rotates about the rotational axis, wherein the linear-to-rotary converter comprises a cam and cam followers coupled to the first coil and the second coil, respectively, wherein the cam followers travel along the cam during operation, and
 wherein during operation the rotary-to-linear converter converts rotary motion of the wheel rim to the linear reciprocating movements of the first coil and the second coil along, respectively, the first and second magnetic stator core portions in the radial directions relative to the rotational axis and passing through the magnetic fields produced by the one or more magnets of the first and second magnetic stator core portions.

23. The electric generator device of claim 22, wherein the cam is formed by a groove within the support member and the cam followers ride within the groove.

24. The electric generator device of claim 22, wherein the cam is formed by a ridge member on the support member and the cam followers ride against the ridge member.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 8,362,660 B2
APPLICATION NO. : 12/590496
DATED : January 29, 2013
INVENTOR(S) : Hunter et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the Title Page

Item (12):


“Hunter” should read -- Hunter, et al. --.

Item (75) Inventor is corrected to read:

-- Ian W. Hunter, Lincoln (MA);

Timothy A. Fofonoff, Lincoln (MA) --.

Signed and Sealed this
Fourth Day of June, 2019



Andrei Iancu
Director of the United States Patent and Trademark Office