



US008371505B1

(12) **United States Patent**  
**Zolotov**

(10) **Patent No.:** **US 8,371,505 B1**  
(45) **Date of Patent:** **Feb. 12, 2013**

(54) **SYSTEM AND METHOD FOR  
COMPENSATING FOR MOTION RELATIVE  
TO A BARCODE**

7,712,670 B2 \* 5/2010 Sauerwein et al. .... 235/472.02  
8,146,821 B2 \* 4/2012 Barkan et al. .... 235/462.24  
2005/0236488 A1 10/2005 Kricorissian

\* cited by examiner

(75) Inventor: **Serguei Zolotov**, Ottawa (CA)

(73) Assignee: **Psion, Inc.**, Mississauga, Ontario (CA)

*Primary Examiner* — Seung Lee

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(74) *Attorney, Agent, or Firm* — Perry & Currier, Inc.

(21) Appl. No.: **13/209,486**

(22) Filed: **Aug. 15, 2011**

(51) **Int. Cl.**  
**G03B 7/08** (2006.01)

(52) **U.S. Cl.** ..... **235/462.24**

(58) **Field of Classification Search** ..... 235/454,  
235/462.01, 462.23–462.25, 472.01–472.03  
See application file for complete search history.

(57) **ABSTRACT**


A barcode decoding system and method for compensating for motion of between an image sensor and a barcode to improve decoding of the barcode. The barcode decoding system includes an imager for capturing an image of the barcode, a motion sensor for collecting acceleration data and a processor that is configured to determine a velocity of the image sensor during the exposure period based on the acceleration data and a periodic motion model. The determined velocity is used to adjust the edge detection algorithm used to detect the barcode features in order to decode the barcode. The orientation of the captured barcode can also be determined in order to determine the velocity in a direction perpendicular to the barcode features.


(56) **References Cited**

**U.S. PATENT DOCUMENTS**


5,841,121 A \* 11/1998 Koenck ..... 235/472.01  
7,407,096 B2 \* 8/2008 McQueen et al. .... 235/383

**19 Claims, 6 Drawing Sheets**





**FIG. 1**



**FIG. 2**




FIG. 3




FIG. 4




FIG. 5




FIG. 6

1

**SYSTEM AND METHOD FOR  
COMPENSATING FOR MOTION RELATIVE  
TO A BARCODE**

FIELD

The present disclosure relates generally to a system and method for reading barcodes, more specifically the disclosure relates to barcode reading devices using image sensors.

BACKGROUND

Barcode symbols provide a fast and accurate means of representing information about an object. Decoding or reading a barcode is accomplished by translating the pattern of barcode features, such as bars and spaces in linear (1D) barcodes or blocks or other features in a two-dimensional (2D) barcode, into the corresponding numbers or characters. Barcodes are widely used for encoding information and tracking purposes in retail, shipping and industrial settings.

Barcodes are typically read by a handheld barcode reading device that includes a camera or imager (these terms being used interchangeably herein) for capturing an image of the barcode. Since the reading device is handheld, the quality of the captured image can suffer due to hand movement of the reading device relative to the barcode during the image capture period. For example, movement in the direction perpendicular to the bars and spaces with a linear barcode can result in a blurring that causes misdetection of the edges between the bars and spaces in decoding the barcode. For 2D barcodes, motion in any direction can induce image blur that results in misdetection of the barcode feature. The image blurring problem can be exasperated when using low cost image sensors that require longer exposure periods to capture images with suitable signal to noise ratios or when attempting to capture an image of a barcode under less than ideal lighting condition which also requires a relatively longer exposure period.

Optical stabilization techniques are often used to reduce blurring associated with the motion of a camera during exposure to compensate for movement of the imaging device. Optical stabilization varies the optical path to the image sensor of the camera in response to movement. This technology can be implemented in the lens itself, or by moving the sensor as the final element in the optical path. The key element of all optical stabilization systems is that they stabilize the image projected on the sensor before the sensor converts the image into digital information. Optical stabilization techniques typically require additional sensors, such as gyroscopes and accelerometers, and devices to move lenses or sensors in the optical path. These additional sensors and devices create a number of potential disadvantages in a handheld device, such as increasing the expense of the handheld device, increasing the number of moving parts in the handheld device, possibly reducing the overall reliability, and increasing the power consumption within the handheld device.

Another known technique used to minimize motion blur relies on using an accelerometer to detect pauses in hand motion. This technique only allows the camera to attempt to capture an image during a detected pause in motion. This technique requires knowledge of the expected motion pattern of hand jitter in order to correctly detect the pauses. This technique is used by some cell phone cameras, one example being the Glogger VS2 software available for Nokia phones running on Symbian OS. Published U.S. Patent Application 20050236488 to Kricorissian, and assigned to the assignee of the present invention, discusses another implementation of a delay-based system. These approaches have proven not to be

2

practicable for barcode readers because they often create an unacceptable delay when capturing the image of the barcode. Furthermore, these approaches may still result in blurring of the captured image in lower light environments or when using a low-cost image sensor where a longer exposure time is required since these approaches do not prevent blurring or compensate for blur causing movement, but instead merely attempt to avoid capturing the image of the barcode when movement is occurring.

An alternative approach to reduce image blurring is to reduce exposure times. However, imagers used in barcode reading devices are typically lower cost image sensors that require relatively longer exposure times. In the scanning environments where barcode reading devices are typically used, the light levels are often not sufficient to use reduced exposure times to eliminate image blurring. Providing supplementary lighting, such as a flash or other light source, can reduce the exposure time, but would result in increased power consumption by the handheld device with a commensurate reduction in the useful operating time of the battery powered handheld device.

SUMMARY

Accordingly, there is a need for a system and method for compensating for motion between an image sensor and barcode when capturing an image of the barcode.

According to a first aspect, there is provided a method for compensating for motion between an image sensor and a barcode, the method comprising the steps of capturing an image of the barcode using the image sensor; determining a velocity between the image sensor and the barcode based on acceleration data provided by a motion sensor, the velocity determined for an exposure period of the image sensor to capture the image; selecting at least one parameter for edge detection processing of the barcode based on the determined velocity to compensate for blurring of the image due to the determined velocity; and detecting edges of features of the barcode in the captured image using the at least one parameter to decode the barcode. Preferably, the motion sensor and image sensor are included in a handheld barcode scanner. Also preferably, the step of determining the velocity comprises calculating a previous velocity of the image sensor, and adjusting the previous velocity with the acceleration data to determine the velocity. Also preferably, the determined velocity is calculated using a motion model, such as a periodic or quasi-periodic motion model. Also preferably, the method further includes the step of determining the velocity in a direction substantially perpendicular to edges of features of barcode.

According to a second aspect of the present invention, there is provided a barcode decoding system for capturing and decoding a barcode, the system comprising: an image sensor for capturing an image of the barcode; a motion sensor for collecting acceleration data for motion between the image sensor and the barcode; and a processor configured to determine a velocity of the motion between the image sensor and the barcode based on the acceleration data, the velocity determined for an exposure period of the image sensor to capture the image, the processor further configured to select at least one parameter for edge detection processing of the barcode based on the determined velocity to compensate for blurring of the image due to the determined velocity, and the processor further configured to detect edges of features of the barcode using the at least one parameter to decode the barcode.



## BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments of the present invention will now be described, by way of example only, with reference to the attached drawings, wherein:

FIG. 1 is a perspective view of a handheld computing device;

FIG. 2 is a rear view of the handheld computing device of FIG. 1 illustrating motion of the handheld computing device relative to a barcode;

FIG. 3 is a block diagram of a barcode decoding system illustrating the interconnection of the functional subsystems;

FIG. 4 is a series of four graphs illustrating the effects of the velocity between an image sensor of a barcode scanner and a barcode when capturing an image of a linear barcode;

FIG. 5 is a block diagram of relevant elements of a barcode decoding system that provide motion compensation and barcode decoding functionality; and

FIG. 6 is a flowchart illustrating a method for compensating for motion between an image sensor of a barcode scanner relative and a barcode to improve barcode decoding.

## DESCRIPTION OF VARIOUS EMBODIMENTS

It will be appreciated that for simplicity and clarity of illustration, where considered appropriate, numerous specific details are set forth in order to provide a thorough understanding of the embodiments described herein. However, it will be understood by those of ordinary skill in the art that the embodiments described herein may be practiced without these specific details. In other instances, well-known methods, procedures and components have not been described in detail so as not to obscure the embodiments described herein. Furthermore, this description is not to be considered as limiting the scope of the embodiments described herein in any way, but rather as merely describing the implementations of various embodiments described herein.

The embodiments of the systems, devices and methods described herein may be implemented in hardware or software, or a combination of both. Some of the embodiments described herein may be implemented in computer programs executing on programmable computers, each computer comprising at least one processor, a computer memory (including volatile and non-volatile memory), at least one input device, and at least one output device. For example, and without limitation, the programmable computers can include handheld computing devices, or the combination of a portable or fixed computing device with a handheld barcode scanner where either the computing device or the handheld barcode scanner can be programmable. Program code may operate on input data to perform the functions described herein and generate output data.

Reference is first made to FIGS. 1 and 2 which show a handheld computing device 100 having a barcode scanner 102 that provides optical barcode scanning functionality. Handheld computing device 100 can be any of a wide range of digital devices that provides barcode reading functionality including, without limitation, devices which generate digital information, such as computer terminals, RFID readers and optical scanning devices, including dedicated barcode scanning devices, digital photo and document scanners. Handheld computing device 100 is a handheld portable device, such as a mobile computer, mobile phone, handheld terminal, digital camera, scanner or other electronic device configured to capture and decode barcode images. Barcode scanner 102, as described in further detail below, may comprise a set of hard-

ware, firmware, and system software, employed in any suitable combination in order to capture an image of barcode 120 using an image sensor.

Handheld computing device 100 can further include a keyboard 104 for user input, a display screen 106, and an expansion port 108. Examples of expansion port 108 can include a Universal Serial Bus (USB) port or other similar expansion port for coupling compatible peripheral devices such as, but not limited to, a communication and synchronization cradle for handheld computing device 100.

As used herein, the term barcode refers to an optical machine-readable representation of information. Typically, barcodes encode information in the widths and the spacing of parallel lines, sometimes referred to as bars, and may be referred to as linear or 1D (one-dimensional) barcodes or symbologies. Barcode 120 is provided as an example of a linear barcode. Barcodes can also encode information in patterns of squares, dots, hexagons and other geometric shapes or symbols within images termed 2D (two-dimensional) matrix codes or symbologies. Although 2D barcodes use features other than bars, they are generally referred to as barcodes as well. Accordingly, the barcode images discussed herein for use with barcode scanner 102 can refer to either 1D or 2D barcodes. As will be described, the barcodes can be read by an optical scanner or reader referred to collectively as barcode scanner 102. As used herein, the objects used to encode the information, such as bars, squares, etc., are referred to as features. For example, the features of barcode 120 can refer to the either the black or white bars that comprise barcode 120. Barcodes can also be black-and-white or color.

Arrow 122 is used to represent motion of barcode scanner 102 and handheld computing device 100 relative to barcode 120. It is difficult for a user to maintain handheld computing device 100 steady while capturing barcode 120 and this movement can induce motion blur in the captured image that could affect the ability of handheld computing device 100 to decode barcode 120.

Referring now to FIG. 3, a block diagram of a barcode decoding system 300 is shown illustrating the interconnection of the functional subsystems. Handheld computing device 100 can include barcode decoding system 300 to provide barcode decoding and other functions. Barcode decoding system 300 comprises a processor 302 that controls general operation of the system. Processor 302 interacts with functional device subsystems, which can include subsystems such as display screen 106, flash memory 304, random access memory (RAM) 306, auxiliary input/output (I/O) subsystems 308, serial port 310, keyboard 104, speaker 312, short-range communications subsystem 314, such as Bluetooth™ for example, and expansion port 108. Barcode decoding system 300 can include a power source such as battery module (not shown) that can be removable and replaceable. While the illustrated embodiment of barcode decoding system 300 includes the functional subsystems described above, it will be apparent to those of skill in the art that barcode decoding system 300 can omit some of these subsystems and/or can include additional subsystems as required to meet an intended field of use for barcode decoding system 300.

Barcode decoding system 300 can have the capability of communicating at least data, and possibly any of data, audio and voice communications, to and from other devices connected by a communication network, as well as data acquisition sources within a communication network. Barcode decoding system 300 can include wired or wireless communication capability. In the wireless configuration, barcode decoding system 300 typically includes radio frequency (RF)

## 5

communication subsystem **316**, which includes a receiver, a transmitter, and associated components, such as one or more embedded or internal antennae, and a processing module such as a digital signal processor (DSP) or the like. As will be apparent to those skilled in field of communications, the particular design of RF communication subsystem **316** depends on the specific communication networks in which barcode decoding system **300** is intended to operate, and can include communication functionalities such as radio-frequency identification (RFID), Wi-Fi WLAN based on IEEE 802.11 standards, Zigbee, Z-Wave, GSM EDGE, 1EVDO, HSPDA, and the like.

Still with regard to FIG. **3**, operating system software can be executed by processor **302** that is stored in a persistent storage such as flash memory **304**, or alternatively, in other read-only memory (ROM) or similar storage elements (not shown). Those skilled in the art will appreciate that an operating system, specific device applications, or parts thereof, may be temporarily loaded into a volatile store such as RAM **306**.

Processor **302**, in addition to its operating system functions, can also enable execution of software applications on barcode decoding system **300**. A predetermined set of applications, which control basic device operations, or more customized, advanced device operations, may be installed on barcode decoding system **300** during its manufacture, such as during the components configuration process.

Display screen **106** of barcode decoding system **300** may be used to visually present a software application's graphical user interface (GUI) to a user via display screen **106**. Display screen **106** can employ a touch screen display, in which case the user can manipulate application data by modifying information on the GUI using direct touches by a finger or stylus. Depending on the type of handheld computing device **100**, the user may have access to other types of input devices, such as, for example, a scroll wheel, trackball or light pen.

A graphical user interface presented on display screen **106** of barcode decoding system **300** may enable an operator or administrator to interact with handheld computing device **100**. It is further contemplated that barcode decoding system **300** may be communicatively coupled to a remotely located database (not shown).

Barcode decoding system **300** further comprises barcode scanner **102**. Barcode scanner **102** can be integrated with handheld computing device **100** as shown in FIGS. **1** and **2**. In other embodiments, barcode scanner **102** can comprise a secondary handheld enclosure that can includes motion sensor **318** and some of other the subsystems illustrated in FIG. **3**. For example, barcode scanner **102** can be a pistol scanner that is communicatively tethered to barcode decoding system **300**. The pistol scanner can include motion sensor **318** and image sensor **320**, and the pistol scanner can further include a trigger and logic to control the operation of the pistol scanner. The pistol scanner can be tethered to barcode decoding system **300** either by wire, such as a USB link, or through a wireless protocol that communicates with short-range communication subsystem **314** of handheld computing device **100**. The term "handheld barcode scanner" as used herein can refer to either barcode scanner **102** integrated within handheld computing device **100** or a secondary handheld enclosure with barcode scanner **102** that can connect to the subsystems of barcode decoding system **300**.

Barcode scanner **102** can comprise any suitable combination of software, firmware and hardware to implement scanning of barcode **120** using image sensor **320**. Image sensor **320** can further include a light source and a lens (not shown). The light source and lens can be controlled by image sensor

## 6

**320** or processor **302**. The lens can be a fixed focus lens with a suitable depth of field, or can be an auto-focus lens. Image sensor **320** can be a CCD, CMOS or other suitable image sensor.

If barcode scanner **102** is implemented in a secondary handheld enclosure, barcode scanner **102** can further include a motion sensor **318** that can provide acceleration data with respect to the motion of barcode scanner **102**. Acceleration data is used by barcode scanner **102** to recover the velocity of barcode scanner **102**. If barcode scanner **102** is integrated with handheld computing device **100**, motion sensor **318** can be a separate subsystem connecting to barcode decoding system **300** in order to provide acceleration data with respect to the motion of barcode scanner **102**. In some embodiments, motion sensor **318** can be an accelerometer that provides linear/translational acceleration data in one or more planes of movement according to the axes of the accelerometer (e.g. x, y, and z). In other embodiments, motion sensor **318** can be a gyroscope that has axes to measures pitch, yaw and roll and provides acceleration data in the form of degrees per second. Using the distance from barcode **120**, which can be estimated based on focal length or other factors, angular acceleration data from the gyroscope can be used to approximate translational acceleration data similar to that obtained from an accelerometer. A gyroscope can also provide positional orientation information relative to a reference position. Acceleration data may be provided from both an accelerometer and a gyroscope to provide more accurate acceleration data. Motion sensor **318** can be implemented as a MEMS sensor and can include either an accelerometer, a gyroscope, or a combination thereof in a single part. Velocity can be determined from the acceleration data provided by motion sensor **318** as will be described further below.

Acceleration data can further include timestamp data that may be used to determine velocity. Depending on where acceleration data is processed, motion sensor **318** can provide acceleration data to processor **302** or directly to barcode scanner **102**.

In most cases it is assumed that barcode **120** is static (or moving an insignificant amount) and the motion of barcode scanner **102** and image sensor **320** with respect to barcode **120** causes image blur in the capture image. However, in some embodiments, barcode **120** may be moving with respect to a static barcode scanner **102**. In that case, motion sensor **318** can be used to provide movement information of barcode **120** to capture motion of barcode **120** as opposed to motion of barcode scanner **102** and image sensor **320**. For example, if image sensor **320** is statically mounted to capture images of barcode **120** placed on a moving object, such as a conveyor or platform, motion sensor **318** can capture this movement and provide it to barcode decoding system **300**. For example, motion sensor **318** can provide acceleration data of a conveyor or platform that barcode decoding system **300** can use to determine the velocity between image sensor **320** and barcode **120** (i.e. the velocity of the conveyor or platform in this case).

Referring now to FIG. **4**, a series of four graphs are shown that illustrate the effects of the velocity between image sensor **320** and barcode **120** when capturing an image of a linear barcode. Each graph illustrates reading the start/stop pattern of a standard C39 barcode at a different velocity,  $v$ , with respect to image sensor **320**. The vertical axes represents increasing level of brightness/lightness (i.e. upper level representing white and lower levels representing black).

The C39 barcode standard uses a fixed ratio between the widest and thinnest black and white bars that barcode decoding system **300** interprets to decode the codeword. The C39

start/stop pattern illustrated in FIG. 4 is made up of the following sequence of bars: narrow black; wide white; narrow black; narrow white; wide black; narrow white; wide black; narrow white; and narrow black. Conventionally, how accurate this array of widths is recreated by image sensor 320 of barcode scanner 102 affects the accuracy of interpreting the codeword and the entire barcode 102. Motion between image sensor 320 and barcode 120 can result in motion blur in the captured image that causes errors when decoding barcode 120. The motion blur is proportional to the velocity of the motion. Other barcode standards can encode information using other known methods and are similarly prone to errors from motion as described below.

First graph 400 illustrates the case where the velocity of barcode 120 with respect to image sensor 320 is zero, i.e.  $v=0$ . Detection of black and white bars of barcode 120 can be performed fairly accurately using an edge detection algorithm if the image of barcode 120 has a high signal to noise ratio so that there is sufficient contrast. The vertical lines in the signal indicate a strong contrast between the black and white bars.

Graphs 401, 402, and 403 illustrate effects of increasing velocity (i.e.  $v=1$ ;  $v=2$ ; and  $v=3$ , where higher values for  $v$  indicate greater velocities) between barcode 120 and image sensor 320. The velocity in each graph is related to the slope of each edge of the black and white bars of barcode 120 such that a larger velocity or slope represents a blurrier edge between white and black bars in the image. With a fairly low speed, an edge detection algorithm can still perform relatively well as the signal to noise ratio is still relatively good since a moving target can help average and cancel noise from sources such as dirt in the optical path, light distortion, print quality, cross-talk, bad pixels, etc. Motion causes these noise sources to be distributed and averaged over multiple pixels of image sensor 320. An edge detection algorithm can be adjusted for a lower or higher velocity as will be described below. An edge detection algorithm adjusted for a lower velocity may fail at a higher velocity due to a lower signal amplitude while an edge detection algorithm adjusted to work at a higher velocity may fail at a lower velocity since it is more susceptible noise. Failure to properly adjust the edge detection algorithm for the appropriate velocity will result in failure to detect edges of the black and white bars and failure to decode barcode 120. Alternatively, a different or variation of the edge detection algorithm can be selected based on velocity.

Graphs 400, 401, 402, and 403 illustrate how the upper and lower detection limits of an edge detection algorithm, shown as horizontal lines, can be adjusted to accurately detect the edges of features of barcode 120. Selecting a higher detection threshold, such as that shown in graph 400 where the upper detection limit for detecting a black to white transition is near the maximum signal level and the lower detection limit for detecting a white to black transition is near the minimum signal level, helps to filter noise from the captured image and performs well in high contrast and/or low velocity conditions. Graphs 401, 402, and 403 illustrate selecting a lower detection threshold where the upper detection limit and lower detection limit are adjusted to accurately capture the width of the bars from the signal. The upper detection limit captures a white bar and the lower detection limit captures a black bar. Although the lower detection threshold has less distance between the upper and lower detection limits that may make the detection algorithm more susceptible to noise, a lower detection threshold can be used for higher relative velocity conditions where noise in the optical path is averaged over multiple pixels of image sensor 320.

Edge detection processing based on thresholds is provided as an example of how knowledge of the velocity between barcode 120 and image sensor 320 can be used to adjust the edge detection processing. Other edge detection algorithms that use a different edge detection mechanism can also be adjusted based on the velocity information. Some edge detection algorithms use a derivative of the scan to determine the edges of the features of barcode 120 (i.e. where the second derivative is zero indicates a change in contrast between the features of barcode 120). Since higher velocities can effectively cancel spurious noise, these derivative-based edge detection algorithms can also use the velocity between image sensor 320 and barcode 120 to adjust the edge detection processing such that the algorithm can be adjusted to be more sensitive to changes in the derivatives to determine the edges of the features of barcode 120. Accordingly, other edge detection algorithms can be adjusted based on the velocity between the image sensor 320 and barcode 102 to either compensate for the cancelled spurious noise in the captured image or the less prominent edges of features of barcode 120 in the captured image.

Referring now to FIG. 5, a block diagram 500 of relevant elements of barcode decoding system 300 that provide motion compensation and barcode decoding functionality is shown. Image sensor 320 and motion sensor 318 can be implemented as separately packaged parts, provided only that, motion sensor 318 must move with image sensor 320. Remaining elements, such as barcode orientation extractor 502, velocity vector calculator 504, and edge detection decoder 506, can be implemented either together or separately, and, at least in part, as software code executed on processor 302 or implemented in custom logic, such as an ASIC or programmable logic device, including but not limited to FPGAs or DSPs. The term "processor" as used herein can refer to a microprocessor, such as processor 302, or a custom logic solution, such as an ASIC or FPGA.

Image sensor 320 captures an image of barcode 120. Typically, the capture operation is initiated through a user's interaction with handheld computing device 100 or barcode scanner 102. The captured image typically includes barcode 120 and the surrounding background.

The captured image from image sensor 320 is then provided to barcode orientation extractor 502 that determines the orientation of barcode 120 in the captured image. Barcode orientation extractor 502 processes the captured image to determine the orientation of barcode 120 within the captured image based on, for example, the skew of barcode 120 or the angle of features of barcode 120. The determined orientation of the captured image of barcode 120 is provided to velocity vector calculator 504.

Velocity vector calculator 504 uses acceleration data provided from motion sensor 318 to determine velocity, as will be described below. Velocity vector calculator 504 uses the determined orientation and the determined velocity, to determine the velocity of barcode scanner 102 in a direction perpendicular to barcode features (i.e. the long side of bar in a 1D barcode or the side of a cell in a 2D barcode).

Barcode orientation extractor 502 can determine the orientation of bars of a 1D barcode or the squares or rectangles of a 2D barcode using any suitable image processing algorithm as will occur to those skilled in the art. In one embodiment, image processing can convert the captured image to binary using dynamic thresholding and then use chain-code processing to effectively outline the features of barcode 120 in the captured image. The result of chain-code processing for each feature of barcode 120 will be the smallest wrapping rect-

angle. The orientation of these rectangles can then provide the best statistical orientation of the features of barcode **120**.

Alternatively, barcode orientation extractor **502** can use image processing based on the correlation of multiple scan directions. First, the image processing algorithm can detect the location of barcode **120** within the captured image. Next, several short scans are performed at different angles through the detected location to detect the edges of the features of barcode **120**. Scans at angles that have the highest mutual correlation correspond to the angle that is perpendicular to the features of barcode **120** to determine orientation.

In other embodiments, barcode orientation extractor **502** can also be provided with position data from motion sensor **318** to determine the position of barcode scanner **102** in free space (relative to a reference position) to assist with determining the orientation of barcode **120** based on a presumed or statistical orientation of barcode **102**. For example, if the majority of barcodes are parallel with the horizon, this information can assist the orientation extraction process. Barcode orientation extractor **502** can also provide a preprocessed image to edge detection decoder **506** such that the image has been de-skewed and/or background information removed.

Velocity vector calculator **504** determines the velocity of image sensor **320** that is associated with motion sensor **318**. The velocity is preferably calculated for the exposure period of image sensor **320** when capturing the image of barcode **120**. The exposure period includes the time that image sensor **320** is collecting light to capture the image. As used herein, the term “exposure period” can also include the time immediately prior to or after capturing the image such that the velocity can be calculated using either prior or post measurements, an average or any other combination thereof.

Determining the velocity of image sensor **320** uses data from motion sensor **318** and then determines the velocity with respect to a direction perpendicular to the edges of features of barcode **120**. Velocity can be calculated by applying digital integration to the translational acceleration data from motion sensor **318**. Velocity vector calculator can also use the distance between the image sensor **320** and barcode **120** in calculating velocity if motion sensor **318** includes a gyroscope that provides angular acceleration (i.e. pitch, yaw or roll in degrees per second). The distance can be derived from the variable or managed focus information from image sensor **320**.

If barcode **120** is a linear barcode, velocity vector calculator **504** determines the velocity of image sensor **320** in a direction perpendicular to the edges of the bars that comprise barcode **120** in the captured image. With a 2D barcode, velocity vector calculator can determine a velocity in directions perpendicular to the edges of the 2D barcode features. Most current 2D barcode have orthogonal features (i.e. squares or rectangles) but other variations can use triangles, hexagons or other geometric shapes that can require determining the velocity in more than two directions.

Velocity vector calculator **504** uses acceleration data provided by motion sensor **318** to adjust a previously calculated velocity of image sensor **320**. Velocity can be continuously updated by acceleration data from motion sensor **318**. Velocity vector calculator **504** can use a motion model, such as a periodic (or quasi-periodic) motion model that simulates motion of the human hand, to assist with determining the velocity from the acceleration data. Generally, velocity information cannot be obtained strictly from acceleration data without knowledge of an initial velocity. Using a motion model allows velocity vector calculator **504** to recover velocity from acceleration data. For example, in a simplified pendulum motion model when acceleration changes from one

direction to an opposite direction, the simplified pendulum motion model provides that the object had a velocity of zero some time between the change in direction of acceleration. A motion model can be selected based on acceleration data or position information from motion sensor **318** so that velocity can be determined accurately based on acceleration data. For example, position data based on acceleration data from motion sensor **318** can also be used to select an appropriate motion model based on the orientation of how barcode scanner **102** is being held by an operator.

Periodic motion models are based on the fact that most motion activities in the human body are happening at 8 Hertz and below. Periodic motion appears in hand jitter patterns that are a common source of image blur with a handheld image sensor **320**. Typically, image sensor **320** captures an image in 10-20 ms in average light condition (e.g. an office environment with a brightness of approximately 300 lux) this provides a capture time that is less than  $\frac{1}{8}$  of the period of human body motion. Using a periodic motion model, velocity vector calculator **504** can interpolate a constant velocity (assuming no acceleration between image parts) during the period that the image was captured by image sensor **320**.

One example of a motion model can include a pendulum-like motion where acceleration and velocity are shifted relative to each other by a quarter period and their amplitudes are proportional to each other. Other embodiments can include other motion models or more complicated motion models that better fit the acceleration data received by velocity vector calculator **504**. For example, in some embodiments velocity vector calculator **504** can select a motion model or frequency based on received acceleration data from motion sensor **318**. Preferably, at least two periods of periodic motion are used to select a frequency. The received acceleration data can include acceleration data for past image captures and can be associated with a user profile so that a motion model may be refined for a particular user.

Edge detection decoder **506** processes the captured image using an edge detection algorithm to determine the edges of the features of barcode **120** in order to decode barcode **120**. Edge detection decoder **506** determines at least one parameter for edge detection processing of the barcode **120** based on the velocity (including direction(s)) received from velocity vector calculator **504**. Edge detection decoder **506** can make this determination based on the velocity perpendicular to the features of barcode **120** provided by velocity vector calculator **504**. Edge detection decoder **506** determines the amount of motion-induced image blur using the determined velocity received from velocity vector calculator **504** and any one or combination of the following factors including, but not limited to: size of features of barcode **120**; the resolution of image sensor **320**; and the focal distance of the lens. The amount of velocity induced blur is used to select parameters to adjust and/or select the edge detection algorithm.

For example, edge detection decoder **506** can use the resolution of image sensor **320** and the determined velocity to determine that 2.5 pixels are affected by gradient shading due to the determined velocity provided by velocity vector calculator **504**. If the minimum size of features of barcode **120** is 10 pixels, then no adjustment, or a very minimal adjustment, would be required to adjust for the motion-induced image blur. However, if the minimum size of features of barcode **120** is 3 pixels then edge detection decoder **506** may select parameters to adjust the upper and lower detection limits of the edge detection algorithm. The appropriate parameter(s) is/are selected to adjust the edge detection algorithm (or to select the appropriate edge detection algorithm) to accurately detect the

edges of features of barcode **120** to compensate for the motion-induced image blur from the determined velocity.

Edge detection algorithms typically operate to detect a change in contrast at a point in the image (e.g. between a black and white bar in barcode **120**) and then compares that change in contrast to a detection limit to determine whether an edge exists. Edge detection decoder **506** can adjust these detection limits based on the velocity of barcode scanner **102**.

As demonstrated in FIG. **4**, higher velocities can require a lower detection threshold. Once the edges of the features of the barcode **120** are detected, the barcode features can be identified in order to decode barcode **120**.

The detection thresholds as illustrated in FIG. **4** are provided as one example of a parameter for edge detection processing. Other parameters used to adjust edge detection processing can include edge position, edge shape or edge pattern. For example, the edge shape can be affected by noise from image sensor **320** or noise inherent in barcode **120** that may be due to dirt in the optical path, light distortion, print quality, etc. that the algorithm needs to separate from the motion-induced image blur. Edge pattern information can be used to tune the algorithm based on a start/stop pattern or a fixed ratio between the bars and spaces. Another parameter could be used to select an appropriate edge detection algorithm such as, for example, using a differential edge detection algorithm.

Referring now to FIG. **6**, a flowchart **600** is shown illustrating an example method for compensating for motion between image sensor **320** of barcode scanner **102** and barcode **120** to improve barcode decoding. At step **602**, an image of barcode **120** is captured using image sensor **320** of barcode scanner **102**. Capturing the image is typically initiated by a user of handheld computing device **100** through a user interface interaction, such as pressing a key of keyboard **104** or specifically tasked button or trigger of barcode scanner **102**.

At step **604**, the velocity of barcode scanner **102** is determined during the period of time the image was captured by image sensor **320**. Depending on the construction of image sensor **320**, ambient lighting conditions and the type and printing of barcode **120**, image sensor **320** can take from 10 to 60 milliseconds to capture the image. The velocity is determined from the acceleration data provided by motion sensor **318**. Acceleration data is used along with a motion model in order to determine the velocity. The velocity of image sensor **320** is continually adjusted between (or just prior to) capture events based on the acceleration data and the motion model.

At step **606** the orientation of features of barcode **120** in the captured image is determined. The captured image can be processed to determine the orientation by detecting the skew or angle of barcode **120** and its features. Orientation information is used to determine the orientation of features of the barcode in the captured image with respect to the axes of measurement of motion sensor **318** in order to determine velocity in a direction along barcode **120**. This is calculated in step **608** where the orientation and velocity are used to determine the velocity of image sensor **320** in a direction substantially perpendicular to edges of the features of barcode **120**. With a 2D barcode, a plurality of velocities can be determined such that each velocity is substantially perpendicular to one of a plurality of edge of features of the barcode. With orthogonal 2D barcodes this involves calculating two velocities that are perpendicular to each other but other 2D barcodes can use non-orthogonal shapes (e.g. triangles) as barcode features that can require determining three different velocities. This can involve mapping a velocity vector calculated in step **604** to the direction of the edges of the features of barcode **120**.

Once the velocity/velocities is/are determined with respect to the edges of the features of barcode **120** in the captured

image, in step **610** at least one parameter is selected for edge detection processing of barcode **120** based on the determined velocity to compensate for blurring of the captured image due motion between image sensor **320** of barcode scanner **102** and barcode **120**. The parameter can include a sensitivity threshold that is selected based on the determined velocity so that a lower sensitivity is selected for higher velocities. Other parameters of edge detection processing that can be adjusted based on velocity can include any one of edge position, edge shape, or an edge pattern.

At step **612** the edge detection processing commences using the provided parameters to process the captured image of barcode **120** to detect the edges of the features of barcode **120** in order to identify barcode symbols for decoding.

While the embodiments have been described herein, it is to be understood that the invention is not limited to the disclosed embodiments. The invention is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims, and scope of the claims is to be accorded an interpretation that encompasses all such modifications and equivalent structures and functions.

The invention claimed is:

**1.** A method for compensating for motion between an image sensor and a barcode, the method comprising the steps of:

capturing an image of the barcode using the image sensor; determining a velocity between the image sensor and the barcode based on acceleration data provided by a motion sensor, the velocity determined for an exposure period of the image sensor to capture the image; selecting at least one parameter for edge detection processing of the image of the barcode based on the determined velocity to compensate for blurring of the image due to the determined velocity; and detecting edges of features of the barcode in the captured image using the at least one parameter to decode the barcode.

**2.** The method of claim **1**, wherein the image sensor and motion sensor are included in a handheld barcode scanner.

**3.** The method of claim **2**, wherein determining the velocity further comprises:

calculating a previous velocity of the image sensor; and adjusting the previous velocity based on the acceleration data to determine the determined velocity.

**4.** The method of claim **3**, wherein calculating the previous velocity and adjusting the previous velocity are based on a motion model.

**5.** The method of claim **4**, wherein the motion model is any one of a periodic motion model and a quasi-periodic motion model.

**6.** The method of claim **3** further comprising: determining orientation of features of the barcode in the image with respect to axes of the motion sensor, and wherein determining the velocity is based on the orientation of features of the barcode and the axes of the motion sensor to determine the velocity in a direction substantially perpendicular to edges of features of barcode.

**7.** The method of claim **6**, wherein the barcode is a 2D barcode having features with edges in a secondary direction, the method further comprising:

determining a second velocity based on the orientation of features of the barcode and the acceleration data from the two or more axes of the motion sensor to determine the second velocity substantially perpendicular to edges in the secondary direction.

## 13

8. The method of claim 2 wherein the at least one parameter is a detection threshold that is selected based on the velocity, wherein a lower detection threshold is selected for a higher velocity.

9. The method of claim 8 wherein the at least one parameter is any one of an edge detection algorithm, an edge position, an edge shape, or an edge pattern.

10. A barcode decoding system for capturing and decoding a barcode, the system comprising:

an image sensor for capturing an image of the barcode;  
a motion sensor for collecting acceleration data for motion between the image sensor and the barcode; and

a processor configured to determine a velocity of the motion between the image sensor and the barcode based on the acceleration data, the velocity determined for an exposure period of the image sensor to capture the image, the processor further configured to select at least one parameter for edge detection processing of the image of the barcode based on the determined velocity to compensate for blurring of the image due to the determined velocity, and the processor further configured to detect edges of features of the barcode in the image using the at least one parameter to decode the barcode.

11. The system of claim 10, further comprising a handheld barcode scanner housing the image sensor and motion sensor.

12. The system of claim 11, wherein the processor is further configured to calculate a previous velocity of the handheld computing device; and adjust the previous velocity with the acceleration data to determine the determined velocity.

13. The system device of claim 12, wherein calculating the previous velocity and adjusting the previous velocity are based on a motion model.

## 14

14. The system device of claim 13, wherein the motion model is any one of a periodic motion model and a quasi-periodic motion model.

15. The system computing device of claim 12, wherein the processor is further configured to determine orientation of features of the barcode in the image with respect to the axes of the motion sensor, and determine the velocity based on the orientation of features of the barcode and the axes of the motion sensor to determine the velocity in a direction substantially perpendicular to edges of features of barcode.

16. The system computing device of claim 15, wherein the barcode is a 2D barcode having features with edges in a secondary direction, the processor is further configured to determine a second velocity based on the orientation of features of the barcode and acceleration data from the two or more axes of the motion sensor to determine the second velocity substantially perpendicular to edges in the secondary direction.

17. The system computing device of claim 11, wherein the at least one parameter is a detection threshold that is selected based on the velocity, wherein a lower detection threshold is selected for a higher velocity.

18. The system computing device of claim 11, wherein the at least one parameter is any one of an edge detection algorithm, an edge position, an edge shape, or an edge pattern.

19. The system computing device of claim 11, wherein the motion sensor is any one of an accelerometer and a gyroscope.

\* \* \* \* \*