



US008387150B2

(12) **United States Patent**
Schnell

(10) **Patent No.:** **US 8,387,150 B2**
(45) **Date of Patent:** **Feb. 26, 2013**

(54) **SEGMENTED MEDIA CONTENT RIGHTS MANAGEMENT**

(75) Inventor: **Patrik Schnell**, Issaquah, WA (US)

(73) Assignee: **Microsoft Corporation**, Redmond, WA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1097 days.

(21) Appl. No.: **12/163,991**

(22) Filed: **Jun. 27, 2008**

(65) **Prior Publication Data**

US 2009/0328228 A1 Dec. 31, 2009

(51) **Int. Cl.**

- G06F 7/04** (2006.01)
- G06F 17/30** (2006.01)
- G06F 21/00** (2006.01)
- G06F 11/30** (2006.01)
- G06F 12/14** (2006.01)
- G06F 15/16** (2006.01)
- H04N 7/16** (2011.01)
- H04N 7/167** (2011.01)
- H04N 7/173** (2011.01)
- G03G 21/00** (2006.01)

(52) **U.S. Cl.** **726/26; 726/28; 726/29; 726/30; 726/31; 726/32; 726/33; 399/366; 380/241; 380/242; 705/51; 705/54; 705/58; 705/59; 713/187; 725/118; 725/148; 709/232**

(58) **Field of Classification Search** **726/26**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 7,017,177 B1 * 3/2006 Funakoshi 725/118
- 7,174,568 B2 * 2/2007 Chatani et al. 726/27

- 7,251,832 B2 7/2007 Vernon
- 7,412,061 B2 * 8/2008 Peinado et al. 380/277
- 7,430,610 B2 * 9/2008 Pace et al. 709/233
- 7,457,415 B2 * 11/2008 Reitmeier et al. 380/210
- 7,548,653 B2 * 6/2009 Olshansky et al. 382/232
- 7,581,255 B2 * 8/2009 Alkove et al. 726/26
- 7,587,736 B2 * 9/2009 Summers et al. 725/95
- 7,613,182 B2 * 11/2009 Lecomte et al. 370/389
- 7,643,478 B2 * 1/2010 Lecomte et al. 370/389
- 7,664,856 B2 * 2/2010 Bowra et al. 709/225
- 7,668,866 B2 * 2/2010 Liu et al. 713/176
- 7,697,475 B2 * 4/2010 Wendling et al. 370/329
- 7,774,281 B2 * 8/2010 Okamoto et al. 705/59
- RE41,707 E * 9/2010 Funakoshi 725/118
- 7,801,305 B2 * 9/2010 Lecomte et al. 380/217
- 7,801,306 B2 * 9/2010 Reitmeier et al. 380/217
- 7,823,212 B2 * 10/2010 Yamamichi et al. 726/30
- 7,853,532 B2 * 12/2010 Nagao 705/59
- 7,874,015 B2 * 1/2011 Aaron 726/30

(Continued)

OTHER PUBLICATIONS

“PCT Search Report and Written Opinion”, Application No. PCT/US2009/048290, (Dec. 30, 2009), 11 pages.


(Continued)

Primary Examiner — Carolyn B Kosowski
(74) *Attorney, Agent, or Firm* — Wolfe-SBMC

(57) **ABSTRACT**

Segmented media content rights management is described. A media device can receive segments of protected media content from media content streams that each include a different version of the protected media content. A media content file can be generated to include the segments of the protected media content that are sequenced to render the protected media content for viewing. A file header object can be instantiated in a file header of the media content file, where the file header object includes DRM-associated features, such as one or more DRM licenses, properties, and/or attributes that correspond to the media content file to provision all of the segments of the protected media content together.

15 Claims, 4 Drawing Sheets



U.S. PATENT DOCUMENTS

7,886,073	B2 *	2/2011	Gahm et al.	709/231
7,974,280	B2 *	7/2011	Lecomte et al.	370/389
7,984,505	B2 *	7/2011	Read	726/26
7,992,190	B2 *	8/2011	Mevisen et al.	726/2
8,010,806	B2 *	8/2011	Takashima et al.	713/193
8,015,310	B2 *	9/2011	Gahm et al.	709/231
8,027,936	B2 *	9/2011	Ito	705/51
8,055,785	B2 *	11/2011	Liu et al.	709/231
8,055,900	B2 *	11/2011	Iwamura et al.	713/176
8,175,978	B2 *	5/2012	Endoh	705/59
2003/0126619	A1 *	7/2003	Moon	725/120
2004/0022389	A1 *	2/2004	Shen-Orr et al.	380/210
2004/0143760	A1	7/2004	Alkove et al.	
2005/0114672	A1 *	5/2005	Duncan et al.	713/182
2005/0144141	A1 *	6/2005	Nagao	705/59
2006/0010500	A1	1/2006	Elazar et al.	
2006/0075226	A1 *	4/2006	Aksu et al.	713/165
2006/0179153	A1	8/2006	Lee et al.	
2007/0011344	A1	1/2007	Paka	
2007/0083476	A1 *	4/2007	Gomes et al.	705/59
2007/0112680	A1	5/2007	van Niekerk et al.	
2007/0156598	A1 *	7/2007	Yoon et al.	705/52
2007/0204064	A1	8/2007	Mail	
2007/0233601	A1	10/2007	Nakada	
2007/0274520	A1 *	11/2007	Ogata	380/201
2008/0010653	A1	1/2008	Ollikainen et al.	
2008/0016581	A1	1/2008	Cho	
2008/0021959	A1	1/2008	Naghi	
2008/0060085	A1 *	3/2008	Samzelius et al.	726/30
2008/0267399	A1 *	10/2008	Medvinsky et al.	380/201
2009/0003600	A1 *	1/2009	Chen et al.	380/217

2009/0150961	A1 *	6/2009	Kabuto et al.	725/118
2009/0290709	A1 *	11/2009	MacDonald et al.	380/200
2009/0328228	A1 *	12/2009	Schnell	726/26
2009/0328237	A1 *	12/2009	Rodriguez et al.	726/32
2010/0054712	A1 *	3/2010	Wollmershauser et al. ..	386/123
2010/0154065	A1 *	6/2010	Cohen et al.	726/28
2010/0218232	A1 *	8/2010	Rodriguez et al.	725/118
2011/0154426	A1 *	6/2011	Doser et al.	725/118

OTHER PUBLICATIONS

Chu, C-C et al., "Mobile DRM for Multimedia Content in P2P Networks", <http://ieeexplore.ieee.org/iel5/10599/33506/01593212.pdf?tp=&isnumber=&arnumber=1593212>.

Hartung, Frank et al., "Digital Rights Management and Watermarking Content for M-Commerce Applications", <http://ieeexplore.ieee.org/iel5/35/19115/00883493.pdf?tp=&isnumber=&arnumber=1593212>.

Kim, Gunhee et al., "Intellectual Property Management on MPEG-4 Video for Hand-Held Device and Mobile Streaming Service", <http://ieeexplore.ieee.org/iel5/30/30482/014057711.pdf?tp=&isnumber=&arnumber=1405711>.

Kim, Gunhee et al., "Mobile Management DRM (Digital Rights Management) for Hand-Held Devices", <http://ieeexplore.org/iel5/9776/30841/01429718.pdf?tp=&isnumber=&arnumber=1429718>.

Cheng, Jacqui "Microsoft Lanuches PlayReady Interoperable DRM Platform for Mobile Devices", <http://arstechnica.com/news.ars/post/20070212-8816.html>, (Feb. 12, 2007).

* cited by examiner




Fig. 1

108





Fig. 2

**Fig. 3**




Fig. 4

1**SEGMENTED MEDIA CONTENT RIGHTS
MANAGEMENT****BACKGROUND**

Users are able to access and/or obtain media content digitally, such as through subscription and pay-per-view services. Digital media content that is available from a content distribution service is licensed for security and to protect it from unauthorized sharing, copying, and/or distribution of the media content. Digital rights to restrict the use of media content can be in the form of a license that is associated with the media content.

In a digital rights management (DRM) system, various devices that obtain or download digital media content can perform actions on the protected media content as permitted by a DRM license. For example, the various devices can include any type of portable communication device, mobile phone, music device, or television client device which can perform actions such as to render, playback, copy, print, execute, consume, and/or other actions on the protected media content. The DRM license provides the rights and restrictions of the actions performed on the protected media content.

SUMMARY

This summary is provided to introduce simplified concepts of segmented media content rights management. The simplified concepts are further described below in the Detailed Description. This summary is not intended to identify essential features of the claimed subject matter, nor is it intended for use in determining the scope of the claimed subject matter.

Segmented media content rights management is described. In embodiment(s), a media device can receive segments of protected media content from media content streams that each include a different version of the protected media content. A media content file can be generated to include the segments of the protected media content that are sequenced to render the protected media content for viewing. A file header object can be instantiated in a file header of the media content file, where the file header object includes DRM-associated features, such as one or more DRM licenses, properties, and/or attributes that correspond to the media content file to provision all of the segments of the protected media content together.

In other embodiment(s), segments of the protected media content that are received as different versions of the protected media content can be identified, and then replaced with replacement segments that are a same version of the protected media content. The media content file can then be generated to include the replacement segments that are the same version of the protected media content. The replacement segments that are the same version of the protected media content and included in the media content file can also be provisioned by one or more DRM licenses that are included in the file header object. A segment of protected media content in the media content file can include a segment header and corresponding segment data that together form a file fragment. A file fragment can include one or more track objects where each track object includes additional DRM-associated features that correspond to the file fragment.

In other embodiment(s), a content distributor can distribute segments of protected media content from media content streams that each include a different version of the protected media content. The segments of the protected media content can then be sequenced in a media content file to render the

2

protected media content for viewing at a media device. A license server can provide DRM-associated features, such as one or more DRM licenses, properties, and/or attributes that are included with a file header object in a file header of the media content file. The DRM-associated features correspond to the media content file to provision all of the segments of the protected media content together.

BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments of segmented media content rights management are described with reference to the following drawings. The same numbers are used throughout the drawings to reference like features and components:

FIG. 1 illustrates an example system in which embodiments of segmented media content rights management can be implemented.

FIG. 2 illustrates another example system in which embodiments of segmented media content rights management can be implemented.

FIG. 3 illustrates example method(s) for embodiments of segmented media content rights management.

FIG. 4 illustrates various components of an example device that can implement embodiments of segmented media content rights management.

DETAILED DESCRIPTION

Embodiments of segmented media content rights management provide that a media device, such as a television client device or portable music device, can receive segments of protected media content from media content streams that each include a different version of the same media content. The different versions of the same media content (e.g., a movie) can be distributed with varying parameters, such as different resolutions, quality, bit rate, and the like. For example, a movie may be distributed from a content distributor in several different versions, or formats, to accommodate the different rendering capabilities of the various types of media devices that a consumer or subscriber utilizes to watch the movie. The movie can be distributed in high-definition for a television client device that can render high-definition video for display on an HDTV, for example. The movie can also be distributed in standard-definition for processing and display on a portable computer, for example. In addition, the movie can be distributed in a low-definition or other minimal resolution format for display on a portable hand-held device.

A content distributor can segment the different media content streams at a uniform interval across all of the different media content streams, such as in two-second "slices", which may be referred to as segmented streaming. A client device or media device can then acquire or receive segments of the media content from any of the different media content streams. For example, a laptop computer may be connected via a cable modem to receive segments of a movie in high-definition from a media content stream. While watching the movie, a user may then move outside and connect the laptop computer wirelessly to continue watching the movie. Because of a decrease in available bandwidth, the laptop computer can continue to receive segments of the movie in standard-definition from a different media content stream. If the signal degrades further, the laptop computer can then continue to receive segments of the movie in a low-definition format from yet another different media content stream. The media device (e.g., the laptop computer in this example) will then have received segments of the protected media content

(e.g., the movie) in different versions from any number of the different media content streams.

In various embodiments described herein, a media content file can be generated at the media device that includes the segments of the protected media content from the different media content streams. The segments are sequenced in the media content file to render the protected media content for viewing as a contiguous file. To preclude having to obtain or acquire a multitude of digital rights management (DRM) keys, or having different DRM licenses for each different segment and/or stream of protected media content, a file header object can be instantiated in a file header of the media content file, and the file header object includes DRM-associated features, such as one or more DRM licenses, properties, attributes, and/or other information that corresponds to the media content file to provision all of the segments of the protected media content together. The media device can then seamlessly render all of the segments of a movie without managing a multitude of DRM licenses for the different versions of the media content segments.

When a media device has obtained all of the segments of the protected media content, such as a movie, the media device can save the protected media content and/or communicate the media content file to another device as a renderable file. In other embodiments, the segments of the protected media content that are received as different versions of the protected media content can be identified, and then replaced with replacement segments that are a same version of the protected media content. For example, the standard-definition and low-definition segments of media content can be replaced with high-definition segments of the media content. In another example, the segments of the protected media content that are the different versions can be replaced with a least number of replacement segments.

The media content file can then be generated (e.g., regenerated, updated, etc.) to include the replacement segments that are the same version of the protected media content. The replacement segments can all be the same version of the protected media content and included in the media content file. The replacement segments can also be provisioned by the DRM-associated features, such as one or more DRM licenses, properties, attributes, and/or other information that is included in the file header object.

While features and concepts of the described systems and methods for segmented media content rights management can be implemented in any number of different environments, systems, and/or various configurations, embodiments of segmented media content rights management are described in the context of the following example systems and environments.

FIG. 1 illustrates an example system 100 in which various embodiments of segmented media content rights management can be implemented. In this example, system 100 includes a content distributor 102 that communicates or otherwise provides media content to any number of various media devices via communication network(s) 104. The various media devices can include wireless media devices 106 as well as other media devices 108 (e.g., wired and/or wireless client devices) that are implemented as components in various client systems 110. In a media content distribution system, the content distributor 102 facilitates the distribution of media content, protected media content, content metadata, and/or other associated data to multiple viewers, users, customers, subscribers, viewing systems, and devices.

The communication network(s) 104 can be implemented to include any type of data network, voice network, broadcast network, an IP-based network, a wide area network (e.g., the Internet), and/or a wireless communications network 112 that

facilitates media content distribution, as well as data and/or voice communications between the content distributor 102 and any number of the various media devices. The communication network(s) 104 can also be implemented using any type of network topology and/or communication protocol, and can be represented or otherwise implemented as a combination of two or more networks. Any one or more of the arrowed communication links facilitate two-way communications, such as from the content distributor 102 to a media device 108 (e.g., a television client device) and vice-versa.

The content distributor 102 can include media content servers 114 that are implemented to receive media content for distribution to subscriber media devices. The content distributor 102 can receive media content 116 from various content sources, such as a content provider, an advertiser, a national television distributor, and the like. The content distributor 102 can communicate or otherwise distribute media content 116 and/or other data to any number of the various wireless media devices 106 and other media devices 108.

The media content 116 (e.g., to include recorded media content) can include any type of audio, video, and/or image media content received from any type of media content source. As described throughout, “media content” can include television programs (or programming), advertisements, commercials, music, movies, video clips, and on-demand media content. Other media content can include interactive games, network-based applications, and any other audio, video, and/or image content (e.g., to include program guide application data, user interface data, advertising content, closed captions data, content metadata, search results and/or recommendations, and the like).

In this example, the content distributor 102 includes a digital rights management (DRM) system 118 that can encrypt the media content 116 to form protected media content 120. The protected media content 120 can include any type of media content that is purchased, downloaded, or otherwise obtained, such as music, a movie, an application, a game, pictures, a video clip, and the like. The DRM system 118 includes content server(s) 122 that distribute the protected media content 120 to the various wireless media devices 106 and other media devices 108. The DRM system 118 also includes a domain controller 124 and a license server 126.

The domain controller 124 can manage device membership in a domain and issue domain certificates and private keys to devices that are members of the domain. The domain controller 124 can maintain a current list of media devices that are part of a particular user’s domain, as well as the public and private key pairs that have issued for the domain. The license server 126 can issue DRM licenses which provision the rights and restrictions of actions performed on the protected media content 120 by the various media devices. In an implementation, the domain controller 124 and the license server 126 can be managed by separate entities, or can be implemented together in a domain. Although the content servers 122, domain controller 124, and license server 126 are described as distributed, independent components of the DRM system 118, any one or more of the server(s) and controller(s) can be implemented together as a multi-functional component or entity of the system. In various implementations, domain membership can also be managed by a network operator, a third party entity, or by a user.

In this example, the content distributor 102 also includes storage media 128 to store or otherwise maintain various data and media content, such as media content 116, protected media content 120, media content metadata, and/or subscriber information. The storage media 128 can be imple-

mented as any type of memory, random access memory (RAM), read only memory (ROM), any type of magnetic or optical disk storage, and/or other suitable electronic data storage. In addition, content distributor **102** can be implemented with any number and combination of differing components as further described with reference to the example device shown in FIG. **4**.

The wireless media devices **106** can include any type of device implemented to receive and/or communicate wireless data and voice communications, such as any one or combination of a mobile phone **130** (e.g., cellular, VoIP, WiFi, etc.), a portable computer device **132**, a media device **134** (e.g., a personal media player, portable media player, etc.), and/or any other wireless media device that can receive media content in any form of audio, video, and/or image data. Each of the client systems **110** include a respective client device and display device **136** that together render or playback any form of audio, video, and/or image content, media content, protected media content, and/or television content.

A display device **136** can be implemented as any type of a television, high definition television (HDTV), LCD, or similar display system. A client device in a client system **110** can be implemented as any one or combination of a television client device **138** (e.g., a television set-top box, a digital video recorder (DVR), etc.), a computer device **140**, a gaming system **142**, an appliance device, an electronic device, and/or as any other type of client device that can be implemented to receive television content or media content in any form of audio, video, and/or image data in a media content distribution system.

Any of the wireless media devices **106** and/or other media devices **108** can be implemented with one or more processors, communication components, memory components, signal processing and control circuits, a DRM platform, and a media content rendering system. A media device may also be associated with a user or viewer (i.e., a person) and/or an entity that operates the device such that a media or client device describes logical devices that include users, software, and/or a combination of devices.

In this example system **100**, the content server(s) **122** of the DRM system **118** distribute the protected media content **120** to the various wireless media devices **106** and other media devices **108** as media content streams **144** that each include a different version of the same protected media content. For example, a movie that is subject to DRM can be distributed with varying parameters, such as different resolutions, quality, bit rate, and the like. The movie can be distributed by the content server(s) **122** in several different versions, or formats, to accommodate the different rendering capabilities of the various types of wireless media devices **106** and other media devices **108**. The protected media content **120** can be distributed in high-definition with media content stream **146** for television client device **138** that can render high-definition video for display on an HDTV (e.g., display device **136**). The protected media content **120** can also be distributed in standard-definition with media content stream **148** for processing and display on portable computer device **132**. In addition, the protected media content **120** can also be distributed with media content stream **150** in a low-definition or other minimal resolution format for display on a portable hand-held media device **134**.

The content distributor **102**, or a component or system thereof, can segment the different media content streams at a uniform interval “t” (e.g., time in this example) across all of the different media content streams **144**, such as in two-second “slices”, which may be referred to as segmented streaming. A media device can then acquire or receive seg-

ments **152** of the protected media content **120** from any of the different media content streams **144**. For example, the portable computer device **132** may be connected via a cable modem to receive segments (e.g., “segment 1”) of a movie in high-definition from media content stream **146**.

While watching the movie, a user may then move outside and connect the portable computer device **132** wirelessly to continue watching the movie. Because of a decrease in available bandwidth, the computer device **132** can continue to receive segments (e.g., “segments 2-3”) of the movie in standard-definition from a different media content stream **148**. If the signal degrades further, the computer device **132** can then continue to receive segments (e.g., “segment 4”) of the movie in a low-definition format from yet another different media content stream **150**. If the signal improves, the computer device **132** can continue to receive segments (e.g., “segment 5”) of the movie in standard-definition from the media content stream **148**, and so on. The media device (e.g., the portable computer device in this example) will then have received segments of the protected media content **120** in different versions from any number of the different media content streams **144**.

In one or more embodiments, a media content file **154** can be generated at the media device that receives the various segments of the protected media content **120**. The media content file **154** includes a file header **156**, a file index **158**, and multiple file fragments **160** that are formed by a segment header and corresponding segment data. For example, segment header “1” and corresponding segment data “1” together form file fragment **160** which includes the “segment 1” of the protected media content **120** in high-definition from media content stream **146**. The segments 1-5 et al. from the different media content streams **144** of protected media content **120** are sequenced in the media content file **154** to render the protected media content for viewing as a contiguous file. The media content file **154** is further described with reference to the media content file shown in FIG. **2**.

FIG. **2** illustrates an example system **200** in which various embodiments of segmented media content rights management can be implemented. In this example, system **200** includes the content distributor **102** and an example of a wired and/or a wireless media device **202**, such as portable media device **134** and television client device **138** as described with reference to FIG. **1**. System **200** also includes an example of a DRM system **204** that is implemented apart from the content distributor **102** (e.g., on a separate server or as a third-party service) which can implement the various embodiments described herein. The content distributor **102**, DRM system **204**, and media device **202** can all be implemented for communication with each other via the communication network (s) **104** and/or the wireless communications network **112**.

Media device **202** can be implemented with processing, communication, and memory components, as well as signal processing and control circuits. Media device **202** may also be associated with a user or owner (i.e., a person) and/or an entity that operates the device such that a media device describes logical devices that include users, software, and/or a combination of devices. In this example, the media device **202** includes one or more processors **206** (e.g., any of microprocessors, controllers, and the like), media content inputs **208**, and protected media content **210** (e.g., received media content, media content that is being received, recommended media content, recorded media content, etc.). The media content inputs **208** can include any type of wireless, broadcast, and/or over-the-air inputs via which media content and/or protected media content is received.

Media device **202** can also include a device manager **212** and/or DRM platform **214** (e.g., a control application, software application, signal processing and control module, etc.) that can be implemented as computer-executable instructions and executed by the processors **206** to implement various embodiments and/or features of segmented media content rights management as described herein. Media device **202** can also include a content rendering system **216** to receive and render the protected media content **210**. In addition, media device **202** can be implemented with any number and combination of differing components as further described with reference to the example device shown in FIG. 4.

Media device **202** can itself include a removable component that is associated with a DRM license (e.g., the DRM license is cryptographically bound to the removable component). The removable component can be a token of the media device **202**, and the DRM license is cryptographically bound to the token of the device. The removable component can be implemented as a flash card, a Subscriber Identity Module (SIM) card, as a smart card, and/or as any other type of token of the media device **202** that is associated with the DRM license. The removable component can include a USIM (User Subscriber Identity Module) which is a logical entity on a card to store subscriber and/or authentication information. For example, the DRM license may have various, associated license identifiers, such as a customer identifier, service identifier, and/or a domain identifier that, in any combination, authenticate the media device **202** to a domain controller and/or to a license server of a DRM system and/or segmented media content rights management. The DRM license provides the rights and restrictions of the actions performed on the protected media content **210**, such as to render, playback, copy, print, execute, consume, and/or other actions on the protected media content.

System **200** also includes the media content file **154** described as an example of the protected media content **210**, and as described with reference to FIG. 1. To preclude having to obtain or acquire a multitude of digital rights management (DRM) keys, or having different DRM licenses for each different segment and/or stream of protected media content, a file header object **218** can be instantiated in the file header **156** of the media content file **154**, and the file header object **218** includes DRM-associated features **220**, such as one or more DRM licenses, properties, attributes, and/or other information that corresponds to the media content file **154** to provision all of the segments of the protected media content together. The media device **202** can then seamlessly render all of the segments of a movie, for example, without managing a multitude of DRM licenses for the different versions of the media content segments.

In addition, a file fragment that is formed by a segment header and corresponding segment data, such as file fragment **160**, includes one or more track objects **222**. Each track object can also include DRM-associated features, such as one or more DRM licenses, properties, attributes, and/or other information that is included in a track object. A file fragment **160** can include or be associated with an audio track, a video track, and/or a combination thereof, and a track object **222** corresponds to the audio track, video track, or combination of audio track(s) and/or video track(s) of a file fragment.

When the media device **202** has obtained all of the segments of the protected media content **210**, such as a movie, the media device can save the protected media content and/or communicate the media content file **154** to another device as a renderable file. In one or more embodiments, the segments of the protected media content **210** that are received as different versions of the protected media content can be identi-

fied, and then replaced with replacement segments that are a same version of the protected media content. For example, the standard-definition and low-definition segments of media content can be replaced with high-definition segments of the media content. In another example, the segments of the protected media content that are the different versions can be replaced with a least number of replacement segments.

The DRM platform **214** and/or the content rendering system **216** can then generate (e.g., re-generated, updated, etc.) the media content file **154** to include the replacement segments that are the same version of the protected media content. The replacement segments call all be the same version of the protected media content and included in the media content file. The replacement segments can also be provisioned by the DRM-associated features, such as one or more DRM licenses, properties, attributes, and/or other information that is included in the file header object.

The file header object **218** can be implemented as a DRM object and include file-level properties that are common for the various segments of the protected media content. In an implementation, a file header object can include:

Field Name	Field Type	Field Description
Size	unsigned int(32)	Size of the Box
Type	unsigned int(32)	Type of Box (4CC)
Usertype	unsigned int(8)[16]	Type of Box (GUID)
Version	unsigned int(8)	Version of Box definition
Flags	unsigned int(24)	Bit field of flags
DataSize	unsigned int(32)	Specifies the size in bytes of the Data field.
Data	unsigned int(8)	The content protection data for the object.

A track object **222** can also be implemented as a DRM object and include DRM properties and attributes for a particular file fragment. A track object can contain information to decrypt elementary streams (e.g., streams that are divided up into sequences of samples called encryption runs). An encryption run can shares the same encryption algorithm, mode, and key. The encryption algorithm and mode can be expressed as indexes into tables. In one instance, the encryption algorithm index is 0 (i.e., "zero"), which indicates that the encryption run is not encrypted. In an implementation, a track object can include:

Field Name	Field Type	Field Description
Size	unsigned int(32)	Size of the Box
Type	unsigned int(32)	Type of Box (4CC)
Usertype	unsigned int(8)[16]	Type of Box (GUID)
Version	unsigned int(8)	Version of Box definition
Flags	unsigned int(24)	Bit field of flags
EncryptionRun	unsigned int(8)	Number of runs in fragment
AlgorithmID	unsigned int(4)	Index into encryption algorithm table
ModeID	unsigned int(4)	Index into encryption mode table
KID	unsigned int(8)[16]	Key ID for the key used to encrypt the run
SampleCount	unsigned int(32)	Number of samples in run
SampleID	unsigned int(64)	First sample Id of run

An algorithm defined for a track object is AES with algorithm ID=0x1 and the mode defined is counter mode with Mode ID=0x1. In a case where the algorithm ID=0x0 the entire run of samples is not encrypted and the Mode Id is 0x0 and KID is all zeros.

Example method **300** is described with reference to FIG. **3** in accordance with one or more embodiments of segmented media content rights management. Generally, any of the functions, methods, procedures, components, and modules described herein can be implemented using hardware, software, firmware, fixed logic circuitry, manual processing, or any combination thereof. A software implementation of a function, method, procedure, component, or module represents program code that performs specified tasks when executed on a computing-based processor. Example method **300** may be described in the general context of computer-executable instructions. Generally, computer-executable instructions can include software, applications, routines, programs, objects, components, data structures, procedures, modules, functions, and the like.

The method(s) may also be practiced in a distributed computing environment where functions are performed by remote processing devices that are linked through a communication network. In a distributed computing environment, computer-executable instructions may be located in both local and remote computer storage media, including memory storage devices. Further, the features described herein are platform-independent such that the techniques may be implemented on a variety of computing platforms having a variety of processors.

FIG. **3** illustrates example method(s) **300** of segmented media content rights management, and is described with reference to a media device that receives segmented, protected media content. The order in which the method is described is not intended to be construed as a limitation, and any number of the described method blocks can be combined in any order to implement the method, or an alternate method.

At block **302**, segments of protected media content are received from media content streams that each include a different version of the protected media content. For example, media device **202** receives segments **152** of protected media content **120** from media content streams **144** that each include a different version of the protected media content.

At block **304**, a media content file is generated that includes the segments of the protected media content that are sequenced to render the protected media content for viewing. For example, content rendering system **216** at media device **202** generates media content file **154** that includes the segments **152** of the protected media content **120** that are sequenced to render the protected media content for viewing. In an embodiment, a segment of protected media content in the media content file **154** includes a segment header and corresponding segment data that together form a file fragment **160** which includes one or more track objects **222**. Each of the track objects **222** can include DRM-associated features, such as one or more DRM licenses, properties, attributes, and/or other information that corresponds to the file fragment. A file fragment **160** can include an audio track, a video track, and/or a combination thereof, and a track object **222** corresponds to the audio track, video track, or combination of audio track(s) and/or video track(s) of the file fragment.

At block **306**, a file header object is instantiated in a file header of the media content file and includes DRM-associated features that correspond to the media content file. For example, DRM platform **214** at media device **202** instantiates file header object **218** in the file header **156** of the media content file **154**, and the file header object **218** includes one or more DRM-associated features that correspond to the media content file. The file header object **218** can include the one or more DRM-associated features, such as one or more DRM licenses, properties, attributes, and/or other information to

provision all of the segments of the protected media content together in the media content file.

At block **308**, segments of the protected media content are identified that are received as different versions of the protected media content. For example, the content rendering system **216** at media device **202** identifies the segments of the protected media content that are received as different versions of the protected media content. At block **310**, the segments that are the different versions of the protected media content are replaced with replacement segments that are a same version of the protected media content. For example, the content rendering system **216** replaces the segments that are the different versions of the protected media content with replacement segments that are a same version of the protected media content.

At block **312**, the media content file is generated to include the replacement segments that are the same version of the protected media content. For example, the content rendering system **216** generates the media content file **154** to include the replacement segments that are the same version of the protected media content. The replacement segments that are the same version of the protected media content are provisioned by one or more DRM licenses that are associated with the media content file and included in the file header object.

FIG. **4** illustrates various components of an example device **400** that can be implemented as any form of a communication, computing, electronic, and/or media device to implement various embodiments of segmented media content rights management. For example, device **400** can be implemented as a computer device, server device, media device, content distributor, and/or as a DRM system as shown in FIG. **1** and/or FIG. **2**.

Device **400** includes protected media content **402** and one or more communication interfaces **404** that can be implemented for any type of data and/or voice communication via communication network(s). Device **400** also includes one or more processors **406** (e.g., any of microprocessors, controllers, and the like) which process various computer-executable instructions to control the operation of device **400**, and to implement embodiments of segmented media content rights management. Alternatively or in addition, device **400** can be implemented with any one or combination of hardware, firmware, or fixed logic circuitry that is implemented in connection with signal processing and control circuits which are generally identified at **408**.

Device **400** also includes computer-readable media **410**, such as one or more memory components, examples of which include a removable card, SIM card, random access memory (RAM), non-volatile memory (e.g., any one or more of a read-only memory (ROM), flash memory, EPROM, EEPROM, etc.), and a disk storage device. A disk storage device can include any type of magnetic or optical storage device, such as a hard disk drive, a recordable and/or rewritable compact disc (CD), any type of a digital versatile disc (DVD), and the like.

Computer-readable media **410** provides data storage mechanisms to store the protected media content **402**, as well as various device applications **412** and any other types of information and/or data related to operational aspects of device **400**. For example, an operating system **414** can be maintained as a computer application with the computer-readable media **410** and executed on the processors **406**. The device applications **412** can also include a device manager **416** and a DRM platform **418** that can be implemented as a component of the device and configured to implement the DRM techniques described herein. In this example, the device applications **412** are shown as software modules and/

11

or computer applications that can implement various embodiments of segmented media content rights management as described herein.

Device 400 can also include an audio, video, and/or image processing system 420 that provides audio data to an audio rendering system 422 and/or provides video or image data to an external or integrated display system 424. The audio rendering system 422 and/or the display system 424 can include any devices or components that process, display, and/or otherwise render audio, video, and image data. In an implementation, the audio rendering system 422 and/or the display system 424 can be implemented as integrated components of the example device 400. Although not shown, device 400 can include a system bus or data transfer system that couples the various components within the device. A system bus can include any one or combination of different bus structures, such as a memory bus or memory controller, a peripheral bus, a universal serial bus, and/or a processor or local bus that utilizes any of a variety of bus architectures.

Although embodiments of segmented media content rights management have been described in language specific to features and/or methods, it is to be understood that the subject of the appended claims is not necessarily limited to the specific features or methods described. Rather, the specific features and methods are disclosed as example implementations of segmented media content rights management.

The invention claimed is:

1. A media device, comprising at least a memory and a processor to implement:

a media content input configured to receive segments of protected media content from media content streams that each include a different standard for rendering the protected media content, the different standard for rendering the protected media content including at least a high-definition standard for rendering the protected media content and a low-definition standard for rendering the protected media content;

a content rendering system configured to:

identify the segments of the protected media content that are received with different standards for rendering the protected media content;

replace the segments that have the different standards for rendering the protected media content with replacement segments that have a same standard for rendering the protected media content; and

generate a media content file that includes the replacement segments that are sequenced to render the protected media content for viewing; and

a digital rights management (DRM) platform configured to instantiate a file header object in a file header of the media content file, the file header object including DRM-associated features that correspond to the media content file to provision all of the segments of the protected media content together.

2. A media device as recited in claim 1, wherein the DRM-associated features include one or more DRM licenses in the file header object to provision all of the segments of the protected media content together in the media content file.

3. A media device as recited in claim 1, wherein a segment of the segments of the protected media content in the media content file includes a segment header and corresponding segment data that together form a file fragment which includes one or more track objects, each track object including additional DRM-associated features that correspond to the file fragment.

4. A media device as recited in claim 2, wherein the file fragment includes at least one of an audio track or a video

12

track, and wherein a track object of the one or more track objects corresponds to at least one of the audio track or the video track.

5. A media device as recited in claim 1, wherein the replacement segments that are the same standard for rendering the protected media content are provisioned by one or more DRM licenses that are associated with the media content file and included in the file header object.

6. A content distributor, comprising at least a memory and a processor to implement:

a content server configured to distribute segments of protected media content from media content streams that each include a different standard for rendering the protected media content, the segments of the protected media content being sequenced in a media content file to render the protected media content for viewing at a media device, the different standards for rendering the protected media content including at least a high-definition standard for rendering the protected media content and a low-definition standard for rendering the protected media content, and the content server further configured to receive a request to replace the segments that have the different standards for rendering the protected media content with replacement segments that have a same standard for rendering the protected media content in the media content file; and

a license server configured to provide DRM-associated features that are included with a file header object in a file header of the media content file, the DRM-associated features corresponding to the media content file to provision all of the segments of the protected media content together.

7. A content distributor as recited in claim 6, wherein the DRM-associated features include one or more DRM licenses in the file header object to provision all of the segments of the protected media content together in the media content file.

8. A content distributor as recited in claim 6, wherein a segment of the segments of the protected media content includes a segment header and corresponding segment data that together form a file fragment which includes one or more track objects, each track object including additional DRM-associated features that correspond to the file fragment.

9. A content distributor as recited in claim 8, wherein the file fragment includes at least one of an audio track or a video track, and wherein a track object of the one or more track objects corresponds to at least one of the audio track or the video track.

10. A content distributor as recited in claim 6, wherein the replacement segments that have the same standard for rendering the protected media content are provisioned by one or more DRM licenses that are associated with the media content file and included in the file header object.

11. A method, comprising:

receiving segments of protected media content from media content streams that each include a different standard for rendering the protected media content, the different standards for rendering the protected media content including at least a high-definition standard for rendering the protected media content and a low-definition standard for rendering the protected media content;

identifying the segments of the protected media content that are received with different standards for rendering the protected media content;

replacing the segments that are received with the different standards for rendering the protected media content with replacement segments that have a same standard for rendering the protected media content;

13

generating a media content file that includes the replacement segments that are sequenced to render the protected media content for viewing; and

instantiating a file header object in a file header of the media content file, the file header object including 5 DRM-associated features that correspond to the media content file to provision all of the segments of the protected media content together.

12. A method as recited in claim **11**, wherein the DRM-associated features include one or more DRM licenses in the file header object to provision all of the segments of the protected media content together in the media content file. 10

13. A method as recited in claim **11**, wherein a segment of the segments of the protected media content in the media content file includes a segment header and corresponding

14

segment data that together form a file fragment which includes one or more track objects, each track object including additional DRM-associated features that correspond to the file fragment.

14. A method as recited in claim **13**, wherein the file fragment includes at least one of an audio track or a video track, and wherein a track object of the one or more track objects corresponds to at least one of the audio track or the video track.

15. A method as recited in claim **11**, wherein the replacement segments that are the same standard for rendering the protected media content are provisioned by one or more DRM licenses that are associated with the media content file and included in the file header object.

* * * * *