

US008395532B2

(12) **United States Patent**
Chauvin et al.

(10) **Patent No.:** **US 8,395,532 B2**
(45) **Date of Patent:** ***Mar. 12, 2013**

(54) **DATA COLLECTION SYSTEM FOR ELECTRONIC PARKING METERS**

(75) Inventors: **Gregory Emile Chauvin**, Brookside (CA); **Neil Stuart Erksine**, Halifax (CA); **George Allan MacKay**, New Glasgow (CA)

(73) Assignee: **J.J. Mackay Canada Limited (CA)**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/454,976**

(22) Filed: **Apr. 24, 2012**

(65) **Prior Publication Data**

US 2012/0223841 A1 Sep. 6, 2012

Related U.S. Application Data

(63) Continuation of application No. 12/430,733, filed on Apr. 27, 2009, now Pat. No. 8,184,019.

(60) Provisional application No. 61/048,133, filed on Apr. 25, 2008.

(51) **Int. Cl.**
G08G 1/14 (2006.01)

(52) **U.S. Cl.** **340/932.2**; 340/928; 235/381; 705/13

(58) **Field of Classification Search** 340/932.2, 340/928; 235/380, 486, 381; 705/13
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,189,991 A 7/1916 Mugler 70/120
D107,577 S 12/1937 McGay D10/42

2,161,046 A	6/1939	Hitzeman	194/205
2,261,353 A	11/1941	Gaetano	70/120
2,289,838 A	7/1942	Herschede et al.	194/226
D152,294 S	1/1949	Siegel et al.	D20/10
2,546,433 A	3/1951	Dick	368/6
2,547,272 A	4/1951	Lawson et al.	116/282
D166,059 S	2/1952	Yoss	D10/42
D166,753 S	5/1952	Jones	D10/42
2,599,881 A	6/1952	Woodruff	368/92
D181,359 S	11/1957	Jones	D10/42
2,832,506 A	4/1958	Hatcher	221/103

(Continued)

FOREIGN PATENT DOCUMENTS

CA	2260925	1/1998
CA	2346908	4/2000

(Continued)

OTHER PUBLICATIONS

International Search Report, PCT/US2010/047907, dated Apr. 26, 2011 (3 pgs).

(Continued)


Primary Examiner — Brent Swarthout

(74) *Attorney, Agent, or Firm* — Hayes Soloway P.C.

(57) **ABSTRACT**

There is disclosed a single space parking meter that includes a low powered radio for communicating with a mobile access point. There is also provided a parking meter management system comprising a single space parking meter and a mobile access point. The mobile access point comprises a coin collection cart, and a mobile data collection terminal including a wireless radio for communicating with the wireless radio of the single space parking meter. Also disclosed is a method of managing single space parking meters comprising the steps of collecting and storing meter information in a single space parking meter, receiving at a main electronics board of the single space parking meter a transmit signal, and transmitting the meter information to a mobile access point using a low powered radio of the single space parking meter.

15 Claims, 12 Drawing Sheets



U.S. PATENT DOCUMENTS

2,956,525 A	10/1960	Blauvelt	109/59	5,805,083 A	9/1998	Sutton et al.	340/932.2
2,985,978 A	5/1961	Breen et al.	40/333	5,841,369 A	11/1998	Sutton et al.	340/932.2
3,056,544 A	10/1962	Sollenberger et al.	232/16	5,852,411 A	12/1998	Jacobs et al.	340/932.2
3,204,438 A	9/1965	Sollenberger	70/417	D404,025 S	1/1999	Van Horne et al.	D14/331
3,486,324 A	12/1969	Andersson	368/90	5,903,520 A	5/1999	Dee et al.	368/90
3,637,277 A	1/1972	Krug et al.	312/217	5,911,763 A	6/1999	Quesada	70/120
3,941,989 A	3/1976	McLaughlin et al.	235/156	D413,311 S	8/1999	Blalock	D14/420
3,975,934 A	8/1976	Babai et al.	70/120	5,966,345 A	10/1999	Dee et al.	368/90
3,982,620 A	9/1976	Kortenhaus	194/1 N	6,037,880 A	3/2000	Manion	340/932.2
3,991,595 A	11/1976	Bahry et al.	70/120	6,052,453 A	4/2000	Sagady et al.	379/146
4,237,710 A	12/1980	Cardozo	70/108	6,082,153 A	7/2000	Schoell et al.	70/1.5
4,249,648 A	2/1981	Meyer	194/102	6,111,522 A	8/2000	Hiltz et al.	340/932.2
4,264,963 A	4/1981	Leach	364/707	6,116,403 A	9/2000	Kiehl	194/217
4,306,219 A	12/1981	Main et al.	340/825.54	6,195,015 B1	2/2001	Jacobs et al.	340/693.9
4,317,180 A	2/1982	Lies	364/707	RE37,193 E	5/2001	Ward et al.	194/217
4,317,181 A	2/1982	Teza et al.	364/707	6,230,868 B1	5/2001	Tuxen et al.	194/217
4,323,847 A	4/1982	Karbowski	324/327	6,275,170 B1	8/2001	Jacobs et al.	340/932.2
4,409,665 A	10/1983	Tubbs	364/707	D448,910 S	10/2001	Kit et al.	D99/28
4,432,447 A	2/1984	Tanaka	194/100	6,309,098 B1	10/2001	Wong	368/94
4,460,080 A	7/1984	Howard	194/100 A	6,312,152 B2	11/2001	Dee et al.	368/90
4,474,281 A	10/1984	Roberts et al.	194/1 N	6,354,425 B1	3/2002	Tuxen et al.	194/350
4,479,191 A	10/1984	Nojima et al.	364/707	6,373,442 B1	4/2002	Thomas et al.	343/767
4,483,431 A	11/1984	Pratt	194/97	D461,728 S	8/2002	Tuxen et al.	D10/42
4,574,936 A	3/1986	Klinger	194/318	6,457,586 B2	10/2002	Yasuda et al.	209/534
4,639,021 A	1/1987	Hope	292/7	6,477,875 B2	11/2002	Field et al.	70/491
4,678,994 A	7/1987	Davies	324/236	6,505,774 B1	1/2003	Fulcher et al.	
4,742,903 A	5/1988	Trummer	194/317	6,747,575 B2	6/2004	Chauvin et al.	340/932.2
4,749,074 A	6/1988	Ueki et al.	194/317	6,791,473 B2	9/2004	Kibria et al.	340/932.2
D296,795 S	7/1988	Bouve	D20/10	D497,393 S	10/2004	Herbst	D20/99
4,763,769 A	8/1988	Levasseur	194/217	6,823,317 B1	11/2004	Ouimet et al.	705/13
4,809,838 A	3/1989	Houserman	194/317	6,874,340 B1	4/2005	Berman	7/161
4,812,805 A	3/1989	Lachat et al.	340/825.05	6,889,899 B2	5/2005	Silberberg	235/384
4,823,928 A	4/1989	Speas		6,929,179 B2	8/2005	Fulcher et al.	235/381
4,825,425 A	4/1989	Turner	368/7	7,014,355 B2	3/2006	Potter, Sr. et al.	368/90
4,845,484 A	7/1989	Ellsberg	340/825.35	7,027,773 B1	4/2006	McMillin	455/41.2
4,848,556 A	7/1989	Shah et al.	194/212	7,029,167 B1	4/2006	Mitschele	368/90
4,851,987 A	7/1989	Day	364/200	7,071,839 B2	7/2006	Patel et al.	340/933
4,872,149 A	10/1989	Speas	368/90	7,104,447 B1	9/2006	Lopez et al.	235/384
4,875,598 A	10/1989	Dahl	221/4	7,183,999 B2	2/2007	Matthews et al.	345/1.1
4,880,097 A	11/1989	Speas	194/239	7,222,031 B2	5/2007	Heatley	
4,895,238 A	1/1990	Speas	194/319	7,237,716 B2	7/2007	Silberberg	235/384
4,967,985 A	11/1990	Speas	194/200	7,253,747 B2	8/2007	Noguchi	340/932.2
4,976,630 A	12/1990	Schuder et al.	439/260	7,319,974 B1	1/2008	Brusseaux	705/13
4,989,714 A	2/1991	Abe	194/317	7,330,131 B2	2/2008	Zanotti et al.	340/932.2
5,027,935 A	7/1991	Berg et al.	194/318	7,393,134 B2	7/2008	Mitschele	368/90
5,060,777 A	10/1991	Van Horn et al.	194/317	D575,168 S	8/2008	King et al.	D10/42
5,065,156 A	11/1991	Bernier	340/932.2	D587,141 S	2/2009	King et al.	D10/42
5,076,414 A	12/1991	Kimoto	194/317	D602,225 S	10/2009	Lute et al.	D99/28
5,109,972 A	5/1992	Van Horn et al.	194/217	D615,274 S	5/2010	Kim et al.	D99/28
5,119,916 A	6/1992	Carmen et al.	194/210	D617,799 S	6/2010	Odhe et al.	D14/420
5,155,614 A *	10/1992	Carmen et al.	398/202	7,748,620 B2	7/2010	Gomez et al.	235/383
5,158,166 A	10/1992	Barson	194/319	7,772,720 B2	8/2010	McGee et al.	307/66
5,222,076 A	6/1993	Ng et al.	375/9	7,854,310 B2	12/2010	King et al.	194/350
D340,038 S	10/1993	Venne et al.	D14/420	7,874,482 B2	1/2011	Mitschele	235/384
5,259,491 A	11/1993	Ward II	194/350	8,184,019 B2 *	5/2012	Chauvin et al.	340/932.2
5,266,947 A	11/1993	Fujiwara et al.	340/932.2	2001/0012241 A1	8/2001	Dee et al.	368/90
5,287,384 A	2/1994	Avery et al.	375/1	2001/0047278 A1	11/2001	Brookner et al.	705/1
5,293,979 A	3/1994	Levasseur	194/317	2001/0051531 A1	12/2001	Singhal et al.	455/556
5,351,798 A	10/1994	Hayes	194/318	2002/0030606 A1	3/2002	Chauvin et al.	340/932.2
5,360,095 A	11/1994	Speas	194/217	2002/0062172 A1	5/2002	Bench et al.	700/232
5,402,475 A	3/1995	Lesner, Jr. et al.	379/106	2002/0134645 A1	9/2002	Alexander et al.	194/351
5,407,049 A	4/1995	Jacobs	194/200	2003/0092387 A1	5/2003	Hjelmvik	455/41
5,439,089 A	8/1995	Parker	194/317	2003/0117904 A1	6/2003	Lank et al.	
5,442,348 A	8/1995	Mushell	340/932.2	2003/0128136 A1	7/2003	Spier et al.	340/932.2
5,454,461 A	10/1995	Jacobs	194/200	2003/0144972 A1	7/2003	Cordery et al.	705/401
5,475,373 A	12/1995	Speas	340/815.58	2003/0179107 A1	9/2003	Kibria et al.	340/932.2
5,489,014 A	2/1996	Menoud	194/211	2003/0222792 A1 *	12/2003	Berman et al.	340/932.2
5,500,517 A	3/1996	Cagliostro	235/486	2004/0011099 A1	1/2004	Andersson	70/371
5,563,491 A	10/1996	Tseng	320/2	2004/0039632 A1	2/2004	Han et al.	705/13
5,614,892 A	3/1997	Ward, II et al.	340/870.02	2004/0068434 A1	4/2004	Kanekon	
5,617,942 A	4/1997	Ward, II et al.	194/217	2004/0181496 A1	9/2004	Odinotski et al.	705/418
5,642,119 A	6/1997	Jacobs	342/69	2004/0243526 A1	12/2004	Krygler et al.	705/418
D381,976 S	8/1997	Sandor et al.	D14/420	2004/0264302 A1	12/2004	Ward, II	368/90
5,659,306 A	8/1997	Bahar	340/932.2	2005/0155839 A1	7/2005	Banks et al.	194/302
5,710,743 A	1/1998	Dee et al.	368/90	2005/0192911 A1	9/2005	Mattern	705/401
D391,238 S	2/1998	Sakata	D14/420	2006/0114159 A1	6/2006	Yoshikawa et al.	
5,740,050 A	4/1998	Ward, II	364/464.28	2006/0136131 A1	6/2006	Dugan et al.	701/300
5,748,103 A	5/1998	Flach et al.	340/870.07	2006/0149684 A1	7/2006	Matsuura et al.	705/65
				2006/0152349 A1 *	7/2006	Ratnakar	340/426.1

2006/0152385	A1	7/2006	Mandy	340/932.2
2007/0016539	A1	1/2007	Groft et al.	705/418
2007/0017265	A1	1/2007	Andersson	70/379
2007/0044523	A1	3/2007	Davis	70/34
2007/0094153	A1	4/2007	Ferraro	705/67
2007/0136128	A1*	6/2007	Janacek et al.	705/13
2007/0171069	A1	7/2007	Allen	340/572.1
2008/0071611	A1	3/2008	Lovett	705/13
2008/0093454	A1	4/2008	Yamazaki et al.	
2008/0158010	A1	7/2008	Nath et al.	340/932.2
2008/0165030	A1	7/2008	Kuo et al.	340/932.2
2008/0238715	A1*	10/2008	Cheng et al.	340/870.03
2008/0277468	A1	11/2008	Mitschele	235/384
2008/0291054	A1	11/2008	Groft	340/932.2
2009/0049875	A1	2/2009	Buhl et al.	70/52
2009/0102726	A1	4/2009	Imano et al.	
2009/0109062	A1	4/2009	An	340/932.2
2009/0192950	A1	7/2009	King et al.	705/418
2009/0199966	A1	8/2009	Coleman et al.	
2010/0026522	A1*	2/2010	Ward, II	340/932.2
2010/0030629	A1	2/2010	Ward, II	705/13
2010/0328104	A1	12/2010	Groft	340/932.2
2011/0037562	A1	2/2011	Braukmann et al.	
2011/0057815	A1	3/2011	King et al.	235/382
2011/0060653	A1	3/2011	King et al.	705/14.58
2011/0093314	A1	4/2011	Redmann et al.	
2011/0122036	A1	5/2011	Leung et al.	
2011/0203901	A1	8/2011	King et al.	194/211
2011/0205087	A1	8/2011	Kell et al.	340/932.2
2011/0261548	A1	10/2011	Gandhi	

FOREIGN PATENT DOCUMENTS

CA	2352968	1/2001
CA	2377010	12/2001
CN	2395344	9/2000
CN	2544352	4/2003
JP	2002099640	4/2002
JP	2005267430	9/2005
KR	20050038077	4/2005
MX	2008007047	8/2008
WO	WO98/04080	1/1998
WO	WO01/69541	9/2001

OTHER PUBLICATIONS

International Search Report, PCT/US2010/047906, dated Mar. 30, 2011 (3 pgs).
 International Search Report, PCT/IB06/054574, dated Oct. 27, 2008 (2 pgs).
 Office Action, dated Dec. 13, 2011 in U.S. Appl. No. 12/973,109 (27 pgs).
 Office Action, dated Sep. 14, 2011 in U.S. Appl. No. 12/430,733 (7 pgs).
 Office Action, dated Dec. 7, 2011 in U.S. Appl. No. 12/355,734 (31 pgs).
 Office Action, dated Sep. 15, 2011 in U.S. Appl. No. 12/355,740 (6 pgs).

Office Action, dated Dec. 20, 2011 in U.S. Appl. No. 12/355,740 (12 pgs).
 Office Action, dated Jun. 29, 2011 in U.S. Appl. No. 12/059,909 (21 pgs).
 Office Action, dated Jul. 27, 2011 in U.S. Appl. No. 12/059,909 (34 pgs).
 Office Action, dated Apr. 11, 2011 in U.S. Appl. No. 12/095,914 (3 pgs).
 Request for Continued Examination, dated Sep. 27, 2011 in U.S. Appl. No. 12/059,909 (18 pgs).
 Request for Continued Examination, dated Mar. 30, 2012 in U.S. Appl. No. 12/355,734 (32 pgs).
 StreetSmart Technology, LLC, "Technical Specifications and System Features for the StreetSmart Solution" Brochure (8 pgs).
 Meter Solutions, Single-Space Meters brochure, downloaded from www.duncansolutions.com website, revised Apr. 2006 (2 pgs).
 Anonymous, "The Originators of Metered Parking, Series II, APM-E Mechanism, Service Manual," POM Incorporated, May 23, 2006 revision (22 pgs).
 POM APM Solar Powered Meter advertisements, undated (5 pgs).
 POM APM photographs (33 pgs).
 Byrd, Dennis, "City officials plug solar-powered parking meters, Electronic eye ends free parking," Lawrence Journal World, Apr. 30, 1989, p. 11C (1pg).
 Byrd, Dennis, Parking Meter Manufacturer Sees Bright Future for New Sun-Powered Devices, Los Angeles Times, May 14, 1989 (2 pgs).
 International Preliminary Report on Patentability, issued for application No. PCT/US2010/047907, dated Mar. 15, 2012 (6 pgs).
 International Preliminary Report on Patentability, issued for application No. PCT/US2010/047906, dated Mar. 6, 2012 (5 pgs).
 International Preliminary Report on Patentability, issued for application No. PCT/IB2006/054574, dated Mar. 10, 2009 (5 pgs).
 Office Action issued for U.S. Appl. No. 12/973,109, dated Apr. 30, 2012 (24 pgs).
 Office Action issued for U.S. Appl. No. 12/355,734, dated Apr. 6, 2012 (36 pgs).
 Information Disclosure Statement by Applicant filed for U.S. Appl. No. 12/355,734 on May 23, 2012 (22 pgs).
 Information Disclosure Statement by Applicant filed for U.S. Appl. No. 12/355,740 on May 23, 2012 (25 pgs).
 Information Disclosure Statement by Applicant filed for U.S. Appl. No. 12/875,959 on May 24, 2010 (22 pgs).
 Information Disclosure Statement by Applicant filed for U.S. Appl. No. 12/875,975 on May 24, 2012 (22 pgs).
 Request for Continued Examination (RCE) and Information Disclosure Statement by Applicant filed for U.S. Appl. No. 12/973,109 on May 31, 2012 (43 pgs).
 Office Action issued for related U.S. Appl. No. 13/410,831, dated Nov. 6, 2012 (46 pgs).

* cited by examiner




FIG. 1




FIG. 2a




FIG. 2b




FIG. 2c




FIG. 3a




FIG. 3b




FIG. 3c




FIG. 4a




FIG. 4b




FIG. 4c




FIG. 4d




FIG. 5a




FIG. 5b




FIG. 6a




FIG. 6b




FIG. 6c




FIG. 7

DATA COLLECTION SYSTEM FOR ELECTRONIC PARKING METERS

This application is a Continuation of application Ser. No. 12/430,733 filed Apr. 27, 2009, now U.S. Pat. No. 8,184,019 which claims priority to Provisional Application Ser. No. 61/048,133 filed Apr. 25, 2008.

TECHNICAL FIELD

The present disclosure relates generally to parking meters, and more particularly to improved data collection for single space electronic parking meters.

BACKGROUND

Parking meters can be used as a revenue stream as well as for the management and flow of vehicles and traffic in a municipality. However, in order to increase that revenue stream, the parking meters must be managed efficiently. Various parking meters have been developed for improving the efficiencies of parking meters. This has resulted in parking meters storing information relating to the operation of the parking meter, such as fees collected, errors, coin jams, etc. This parking meter information is then collected and analyzed to improve the revenue stream. This may include adding additional parking meters to high use areas, increase the cost of parking in high use areas, etc.

Parking meters may be classified broadly as multi-space parking meters, or single space parking meters. Multi-space parking meters are larger units in which a parking ticket can be purchased and then must be displayed on the vehicle, or the user may enter a parking space number corresponding to a parking spot for which parking is being purchased and pays for their parking. Multi-space meters are typically used to provide parking metering to a group of parking spaces, a portion of or all of a street block, or to a portion of or all of a parking lot. The multi-space units are generally large in size and typically are powered either by a connection to the power grid, or by a battery in combination with a solar panel. This allows the multi-space meters to power peripheral devices, such as cellular radios for communicating parking meter information to a monitoring location.

In single space parking meters, which are a common aspect of the fixed infrastructure in many cities and municipalities, the parking meters may not normally have radios, but they do capture and generate quantities of data which would be beneficial for managers attempting to manage the parking meters or increase the revenue stream generated from the parking meters. Unfortunately, capturing this data from the street is manually labor intensive. To do so a data collector such as a collections officer is typically given a hand-held device such as a portable data terminal (PDT) and sent out to each parking meter which is probed in turn and the data is captured. Each parking meter may take between 10 seconds and 30 seconds to complete the data capture cycle. The probing is typically carried out either via infrared communication between the parking meter and the hand-held device at an approximate distance of 6 inches, or via a physical blade probe that is inserted into the coin slot of the parking meter. Once the parking meter information is downloaded onto the hand-held device, it is returned from the field, and the parking meter data is uploaded to a computer system and the manager can then view and report on the parking meter data. It may be necessary to repeat this data collection cycle each week or so in order for the parking meter system to be effectively managed. Some managers may have the parking meter data collected

concurrent with the physical coin collection; however, this can make the coin collections much more time consuming and tedious for the collections officer. In some instances, the collections officer collecting the coins and the data concurrently will either forget to collect the data, or forget to collect the coins. Where a collections officer is sent to collect the parking meter data separately from a collections officer collecting the coins, the collected information may not be as useful. From an auditing/reconciliation standpoint the data is not as useful, as it is more difficult to analyze or reconcile the collected parking meter data in relation to the coins collected when the data and coins are not collected coincidentally.

Some single space parking meters may wirelessly communicate parking meter information to a monitoring location using cellular radios. A drawback of using cellular radios in a single space parking meter is the power consumption. Available power in a single space parking meter is considerably less than in a larger multi-space parking meter, which may be connected to the power grid. Also, data communications over a cellular network can become expensive where there are large numbers of parking meters involved, as each parking meter will need a cellular radio and a corresponding account activated under a telecommunication services provider. Also, most commercial data plans are scaled up in price relative to the amount of data that is transmitted and can become expensive when relatively large amounts of data are to be communicated. Additionally, the minimum data plans offered by telecommunication service providers may be excessive relative to the data transmission requirements for some sites.

Other single space parking meters communicate parking meter information wirelessly to a proximal wireless fixed access point, such as a wireless router, located up to several hundred feet away, or one or two city street blocks away. These single space parking meters may use various communication technologies. In addition to cellular radio technology there are also a variety of alternative, low power, low cost wireless radio frequency (RF) based technologies that can be deployed and used in the parking meter and remote access point equipment that can achieve the required transmission distances. Unlike the cellular radios, many of these wireless RF technologies, such as Wi-Fi (802.11), Zigbee radios that adhere to IEEE 802.15.4 wireless standards, as well as many other proprietary license free radio systems, do not require individual radio registration and licensing nor require payment of "airtime" fees. The wireless fixed access point communicates wirelessly with the single space parking meters, and may communicate with a monitoring location and/or the Internet either via cellular radio/modem, or via hard wire connection such as a cable modem. However, some wireless communications, or line of sight technologies, between the single space parking meters and the fixed access point may suffer from less than ideal reliability or power consumption, especially when transmitting over longer distances such as those required for communicating with a fixed access point, as obstacles such as large vehicles and surrounding infrastructure may sometimes block or impede communications paths.

There is therefore a need for an improved data collection system for electronic parking meters, which addresses or mitigates one or more of the defects described above.

SUMMARY OF THE INVENTION

In accordance with an embodiment of the present disclosure, there is provided a parking meter management system comprising a single space parking meter and a mobile access point. The mobile access point comprises a coin collection

cart, and a mobile data collection terminal including a wireless radio for communicating with the wireless radio of the single space parking meter.

In accordance with a further embodiment of the present disclosure, there is provided a method of managing single space parking meters comprising the steps of collecting and storing meter information in a single space parking meter, receiving at a main electronics board of the single space parking meter a transmit signal, and for transmitting the meter information to a mobile access point using a low powered radio of the single space parking meter.

In accordance with a further embodiment of the present disclosure, there is provided a parking meter comprising a payment mechanism for receiving payment for a parking space, a memory for storing parking meter information including information on the payment received, a transmitter for transmitting information to a receiver and a processor for executing instructions. The executed instructions provide a transmitting unit for transmitting the parking meter information stored in the memory using the transmitter, and a trigger unit for triggering the transmission of the parking meter information when a trigger event that is associated with the receiver being within a transmission range is received.

In accordance with a further embodiment of the present disclosure, there is provided a parking meter management system comprising a parking meter for storing and transmitting parking meter information, a coin collection cart for receiving coins retrieved from a plurality of parking meters including the parking meter, and a receiver for receiving the parking meter information wherein the trigger unit of the parking meter triggers the transmission of the parking meter information when the receiver is within a transmission range.

In accordance with a further embodiment of the present disclosure, there is provided a method of transmitting parking meter information comprising storing parking meter information in a memory of the parking meter, detecting at the parking meter an occurrence of a trigger event indicating that a receiver is within a transmission range of the parking meter, and triggering the transmission of the parking meter information stored in the memory.

BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments of the system and method for managing single space parking meters will now be described by way of example with reference to the following drawings in which:

FIG. 1 depicts a schematic of an environment in which embodiments of the present disclosure may be practiced;

FIG. 2a depicts a front view of an illustrative type of single space parking meter in accordance with the present disclosure;

FIG. 2b depicts a side view of the single space parking meter of FIG. 2a;

FIG. 2c depicts a top overhead view of the single space parking meter of FIG. 2a;

FIG. 3a depicts a front view of another illustrative type of single space parking meter in accordance with the present disclosure;

FIG. 3b depicts a side view of the single space parking meter of FIG. 3a;

FIG. 3c depicts a top overhead view of the single space parking meter of FIG. 3a;

FIG. 4a depicts a perspective schematic of an illustrative meter mechanism in accordance with the present disclosure having an interconnect disconnected to a peripheral port;

FIG. 4b depicts a perspective schematic of the meter mechanism of FIG. 4a in accordance with the present disclosure having an interconnect connected to a peripheral port;

FIG. 4c depicts a front view schematic of the meter mechanism of FIG. 4a in accordance with the present disclosure;

FIG. 4d depicts a rear view schematic of the meter mechanism of FIG. 4a in accordance with the present disclosure;

FIG. 5a depicts a top view of an illustrative radio board in accordance with the present disclosure;

FIG. 5b depicts a bottom view of the radio board of FIG. 5a in accordance with the present disclosure;

FIG. 6a depicts a schematic of a parking meter management system in accordance with the present disclosure;

FIG. 6b depicts in a schematic a hand-held data collection terminal for use in the parking meter management system of FIG. 6a;

FIG. 6c depicts in a schematic a parking meter in accordance with the parking meter management system of FIG. 6a; and

FIG. 7 depicts in a flow chart an illustrative method of transmitting parking meter information.

DETAILED DESCRIPTION

There is described herein a low power radio board for connecting to a single space parking meter comprising a main electronics board for controlling the single space parking meter, the main electronics board includes a peripheral port for connecting peripherals to. The low power radio board comprises a low power radio electrically connected to a connector to be coupled to the peripheral port of the main electronics board, the low power radio board shaped to fit within a housing of the single space parking meter adjacent an opening in the housing of the single space parking meter. It is noted that the low power radio board does not have to be on a separate board, as it could also be integrated into the main electronics board as an integrated feature,

There is further described herein a single space parking meter comprising an outer housing that includes a vault door. The outer housing encloses a parking meter mechanism comprising a coin chute, a main electronics board, a display located in an opening of the outer housing, and a wireless radio electrically connected to, or integrated into, the main electronics board. The parking meter further comprises a coin vault and a vault door sensor coupled to the main electronics board.

FIG. 1 depicts in a schematic an environment 100 in which embodiments of the present disclosure may be practiced. FIG. 1 depicts an illustrative city location in which parking meters are used. The environment 100 comprises a building 101 and a plurality of streets 102a, 102b that use parking meters to enforce parking restrictions. Two types of parking meters are depicted in FIG. 1, multi-space (MS) parking meter 105 and single space meters 110.

The street 102a comprises multiple parking spots in a parking enforcement zone 107 corresponding to the MS parking meter 105. The MS parking meter 105 is a multi-space type meter that is used to purchase a ticket for a parking space of the parking enforcement zone 107, depicted schematically as a rectangle. The parking enforcement zone 107 may comprise multiple parking spots. The MS parking meter 105 may collect and communicate parking meter information by way of a wireless wide area network cellular link, shown schematically as 109. The MS meter is shown as communicating with a network cloud 125. It is understood by those of ordinary skill in the art that the network cloud 125 schematically represents communicating the parking meter information

5

back to a monitoring location (not shown) using a network or networks. For example, the MS parking meter **105** may communicate with the monitoring location by connecting to the Internet using a cellular network. The connection to the Internet may allow the MS parking meter **105** to upload parking meter information to the monitoring location, which may include a computer system or server. The uploaded parking meter information may then be displayed on a web site or through other applications that can connect to the computer system or server to access the parking meter information.

The street **102b** comprises multiple parking spots each with an associated parking meter **110**. Parking meters **110** are each individual single space parking meters which each may comprise a low power radio configuration as described further herein. The single space parking meters **110** may also collect and communicate parking meter information to the monitoring location. However, the single space meters are each provided with low power radios not cellular radios, and so are not able to communicate in the same manner as described above for the MS meters **105**. As shown schematically by **112**, the single space meters **110** may communicate with a fixed access point **115**. Additionally or alternatively the single space meters **110** may communicate with a mobile access point **120**, as depicted by **117**.

The fixed access point **115** provides a gateway between the single space meters **110** and the network cloud **125** to provide communication between the single space meters and the monitoring location. The fixed access point **115** may be powered in a similar manner as the MS parking meter **105**. The fixed access point **115** comprises a radio (or multiple radios) for communicating with the low powered radios of the single space meters **110**. The fixed access point **115** also comprises a wide area radio transceiver for communicating with the network cloud **125**. The transceiver may be a wired or wireless connection as depicted by **119**.

The mobile access point **120** also provides a gateway between the single space meters **110** and the monitoring location. The mobile access point **120** may comprise a handheld device, or other terminal device, with a radio for communicating with the low powered radios of the single space meters **110**. The information may be transferred to the monitoring location by various methods. For example, the handheld device of the mobile access point **120** may comprise an additional wide area radio transceiver for communicating with the monitoring location through the network cloud **125**. The additional radio may provide access to the Internet through a cellular network or other WWAN. Additionally or alternatively the hand-held device of the mobile access point **120** may connect to the monitoring location by a cradle or other type of wired connection, or alternatively it may communicate with the monitoring location when the mobile access point **120** is near the monitoring location using the radio normally used to communicate with the low powered radio of the single space meters **110**. Such radio communication between the mobile access point **120** and the monitoring location may be effected using Wi-Fi (802.11 a/b/g/n), Zigbee or other similar protocols.

The single space parking meters **110** may communicate with both the fixed access point **115** and the mobile access point **120**. The communication between the access points **115**, **120**, single space parking meters **110** and the monitoring location may provide communication for a parking meter system. The parking meter system may also include the MS parking meter **105**.

It is understood that various methods of communicating the parking meter information between the access points **115**, **120** and the monitoring location are possible and within the

6

scope of the present disclosure. Additionally, it is understood that the monitoring location referred to above may comprise a computer or plurality of computers that provide functionality to parking enforcement managers for auditing and managing the parking meters. The computer or computers of the monitoring location may utilize Web-based applications to perform such auditing and managing. It is understood that the computer or plurality of computers each comprise a memory for storing instructions and at least one processor for executing the instructions stored in the memory. The instructions stored in the memory, when executed by the processor or processors, may provide the functionality or parts of the functionality used by parking enforcement managers or others. Additionally, if the single space meters **110** are provided with the ability for receiving information from the monitoring location, the software of the computers or servers of the monitoring location may be used to provide functionality for setting or adjusting single space meter **110** control settings, such as for example the pay rate for the single space meter **110**.

FIGS. **2a**, **2b** and **2c** depict an illustrative embodiment of a single space meter **200** configured with a low powered radio. The single space meter **200** may be used as one or more of the single space parking meters **110** in the environment **100**. The single space meter **200** may comprise an outer housing assembly that may have an upper housing **202** and a lower housing **205**. The outer housing may enclose a single space meter mechanism. The single space meter mechanism fits into the outer housing assembly that includes the upper housing **202** and the lower housing **205**. The single space meter mechanism may comprise a display **207** such as a seven segment display or a liquid crystal display (LCD) for displaying parking messages including the amount of parking time remaining. A low powered radio **217** which is located on a radio board **215** which may be fixed to the single space meter mechanism, or alternatively housed within either the upper **202** or lower **205** housing or possibly in a separate housing fixed to the outer housing (not shown). The low powered radio **217** is electrically coupled to main board electronics **220** of the single space meter mechanism. The coupling may be made by, for example a cable connection **222** between the main board electronics **220** and the radio board **215**. The low power radio board **215** may also be alternatively integrated into the main board electronics **220** thereby foregoing the requirements of a connection **222** and associated wiring. An opening in the upper housing **202** through which the display **207** is visible is covered with a rugged see through material such as Lexan® or other similar material **209**.

The outer housing comprising the upper and lower **202**, **205** of the single space meter **200** encloses the main board electronics **220** which may form part of the single space meter mechanism. The outer housing may also house a coin slot **213** for purchasing parking time on the single space meter. All coins deposited into the parking meter through the coin slot **213** eventually end up in a coin canister located in the lower housing **205** of the parking meter **200**. The coin canister may also be referred to as a coin vault or simply a vault. The vault is typically accessed by an opening in the lower housing, such as a vault door, which may be locked with a lock **211**.

The main board electronics **220** of the single space parking meter **200** control the operation of the single space meter **200**. The main board electronics **220** may comprise for example a processor and memory for storing operating instructions. The operating instructions may be executed by the processor in order to perform the required functions of the single space meter **200**. These functions may include storing the parking meter information and transmitting the parking meter infor-

mation to the access points **115**, **120**. They may also control the amount of power used by the low powered radio to transmit to the access points **115**, **120** in dependence upon whether the parking meter is configured to communicate with the fixed access point which may be located at a fixed, pre-determined distance or with the mobile access point, which is typically located in the vicinity of, or close proximity to, the parking meter during transmission of the parking meter information. The parking meter information may include information regarding the amount of money collected by the parking meter, as well as other information useful for auditing and managing the parking enforcement plan. The parking meter information may also include diagnostic information for diagnosing or analyzing the state of the single space meter **200**.

The following is a non-exhaustive list of parking meter information that may be collected, stored and possibly transmitted by the low powered radio **217** from the parking meter **200** to the access points **115**, **120**:

- total coin count for different denominations of coins received by the parking meter;
- total count for cashless payments made at the parking meter using for example chip cards, electronic purses or credit cards;
- last collection date indicating the previous date that coins were removed from the parking meter and/or the previous date that parking meter information was collected from the parking meter;
- current collection date stored when coins are collected and/or parking meter information is collected from the parking meter;
- purchase times indicating the dates/times when parking was paid for; and the amount paid;
- operating time indicating the amount of time the processor or main board electronics were in the operating mode and/or in a sleep mode;
- self diagnostic tests results indicating the results of self diagnostic tests run by the parking meter;
- time and durations of any errors or malfunctions encountered by the parking meter; and
- state of the vault door, for example open, closed and/or locked.

In addition to controlling the single space parking meter **200**, the instructions stored in memory and executed by the processor or main board electronics **220** may be used when the single space parking meter **200** transmits the collected parking meter information to the mobile access point **120** or the fixed access point **115**. The functionality provided by the instructions executed by the processor can be configured to transmit the parking meter information on the occurrence of various trigger events. The transmit trigger events may differ depending on the type of access point the single space parking meter **200** is communicating with, which can be set as a parameter or value of the processor instructions. For example, if the processor or main board electronics **220** is configured to communicate with the fixed access point **115**, the transmitting trigger event may be a periodically scheduled event provided by the processor executing the instructions. The processor may be configured to transmit the parking meter information at scheduled times over the day, such as four times periodically throughout the day. Periodically sending the parking meter information throughout the day may lead to a reduction in the amount of memory required on the parking meter **200**, which can reduce the amount of power consumed by the single space parking meter **200**. The single space parking meter **200** may also transmit at non-scheduled times, coincident with operational events affecting the serviceability of the

single space meter **220**. These trigger events may include parking meter **200** events such as a jammed meter, low battery condition, or other out of service conditions that requires attention by service or maintenance workers. This helps ensure that managers are made aware of service issues of parking meters as they happen. This information may be used to coordinate the activities of the maintenance and service staff, and ensure that the parking meters **200** of the parking meter management system is kept at a high operational performance. During times when the parking meter **200** is not transmitting parking meter information, the low powered radio **217** and radio board **215** may be turned off under the control of the processor, thus further reducing the amount of power consumed by the low powered radio **217** and the single space meter **200**.

The parking meter **200** or its processor may also be configured to transmit the parking meter information to the mobile access point **120**. When transmitting the parking meter information to the mobile access point, or a receiver of the mobile access point **120**, the transmit trigger event may be associated with an event that occurs when the receiver or mobile access point **120** is in close proximity to the parking meter. This trigger event may include a signal provided to the parking meter associated with the mobile access point **120** being within range. Although different signals are possible, a convenient signal may be provided by including a switch connected to the processor or main board electronics **220**. The switch may generate the transmit signal to the processor when the vault door in the lower housing **205** is opened to remove the coins. Advantageously, this allows the parking meter information to be collected when collecting coins from the parking meter **200** without requiring additional effort such as the use of a probe. The trigger event may be associated with the mobile access point being in the same vicinity of, or close proximity to, the parking meter since the mobile access point may be carried by a collections officer, maintenance staff, or on the coin collection cart which will place it in close proximity when the vault door is opened in order to transfer the coins to the coin collection cart or for performing maintenance.

A collections officer or person typically uses a coin collection cart. The mobile access point **120** can be provided on the coin collection cart. In this manner when the collections officer unlocks and opens the vault door of the single space meter **200** to remove the coins and transfer them to the coin collection cart, the switch will provide the transmit signal as the trigger event which triggers the transmission of the parking meter information. The low powered radio **217** may transmit the parking meter information to the, mobile access point **120** located on the coin collection cart. The time required to transmit the parking meter information may be as long as 30 seconds. A typical transmission time may be between 3-6 seconds. The actual transmission time depends on the amount and type of data required to send or receive. As such if there is no parking meter information to transmit or very little parking meter information, the time required to transmit may be less than a second. The coin collection cart may be in close proximity to the parking meter **200**, such as for example within 15 feet, or as little as a foot. Since the receiver is typically in close proximity to the transmitter during transmission of the parking meter data, the parking meter information may be transmitted using less power.

If the single space meter **200** is configured to transmit the information on a transmit trigger event, the low powered radio **217** may be off except when it is required to transmit the parking meter information. Advantageously, this further

reduces the amount of power consumed by the low powered radio **217** and the single space meter **200**.

The single space parking meter **200** may record any vault door opening or other such events even if the mobile access point **120** cannot be contacted when such a trigger event occurs. In this fashion should unauthorized openings of the vault door be taking place they may still be captured and recorded in the memory of the parking meter or its main board electronics **220** for transmission at the next opportunity that the mobile access point **120** is contacted. Additionally or alternatively the parking meter **200** may communicate to the fixed access point **115** that a vault open event has occurred while no mobile access point **120** was within transmission range. Although the vault door switch provides a simple transmit trigger event, it is possible to use different means to generate the transmit trigger event. For example, the transmit trigger event could be generated based on an IR receiver, a fingerprint reader, a radio frequency identification (RFID) tag or tag reader. Each of these means could be activated when a collections officer is collecting coins, or a maintenance staff is performing maintenance, and so by associated with the receiver, which may be carried by the collections officer, coin collection cart or maintenance staff, being in close proximity to the transmitter. The means to generate the transmit trigger event may require consideration of power use. For example using a fingerprint reader may be desirable in some situations, even if the fingerprint reader requires a small amount of power to operate.

The upper housing **202** and the lower housing **205** of the single space meter **200** are typically constructed out of metal due to the ruggedness required. A low powered radio located within the metal of the housing may have difficulty in communicating with an access point **115**, **120**. Advantageously, the low powered radio **217**, and the radio board are located adjacent to a lower edge of the opening in the upper housing **202**. As outlined above, this opening is covered by a rugged see through material such as Lexan® **209**. By positioning the low powered radio **217** adjacent this opening **209**, it is possible to maintain the low power characteristics of the low powered radio **217**, as the radio waves will radiate easily through the see through material of the opening **209**.

The above description relates to low powered radios connected to main board electronics that control a parking meter. It is understood that arrangements other than those outlined above are possible. For example the low power radio could be included as part of the main board electronics enclosed within the lower housing. In such an arrangement it may be advantageous to provide a Lexan® cut-out, or other such material that is transparent to radio waves of the low power radio, in the housing adjacent the radio. Alternatively the radio antenna and/or circuit board may be located in place of or in lieu of the traditional infrared receiver/transmitter components found on many electronic parking meter main boards which are also typically mounted behind the clear Lexan® material. Depending on the required ruggedness and life expectancy of the single space meter the Lexan® covering (either of the display opening or separate radio cut-out) may not be formed as part of the meter. This can advantageously allow for the covering or cut-out to be replaced in the field.

FIGS. **3a**, **3b**, and **3c** depict in schematics another illustrative embodiment of a single space parking meter **300**. The single space parking meter **300** is similar to that described above with respect to single space meter **200**, and may be used as one or more of the parking meters **110** of the environment **100**. The single space parking meter **300** comprises an upper housing **302** and lower housing **305** that form an outer housing. The Outer housing encloses a single space meter mecha-

nism that comprises metering mechanicals and electronics, as well as a meter display **307** and the low power radio **317** on the radio board **315**. The metering mechanicals may include a coin chute component **312** for determining the coinage inserted into the single space meter **300**. The coin chute component **312** comprises a coin chute **313** connecting the exterior of the parking meter **300** with a coin vault **330** housed in the lower housing **305** of the single space parking meter **300**. The lower housing **305** includes a vault door **332** that includes a lock **311**. The lock **311** may be electrical, or as is typically found, a mechanical lock. The lower housing **305** may include a vault door switch **334** for determining when the vault door **332** is opened. The vault door switch **334** may provide a signal of a transmit trigger event to the processor when the vault door **332** is opened to remove the deposited coins from the coin vault **330** and transfer them to a coin collection cart. It is understood that the vault door switch **334** may be any type of sensor that can be deployed to detect the open/closed/locked state of the vault door and signal the vault door state to the processor. Preferably the vault door switch or sensor **334** should be able to detect when the vault door is closed as well as locked.

The vault door switch **334** may be electrically connected via interconnect **336** to a memory module **325** that may be located in the lower housing **305**. The memory module **325** may store parking meter configuration information, as well as the physical meter location ID. The memory module **325** may store information such as current meter rate profile or other required zone information. The memory module **325** may be connected to the main electronics board **321** for example by interconnect **323**. The coin chute component **312** may also be connected to the main electronics board **321** by interconnect **324**. The main electronics board **321** is also connected to the radio board **315** for controlling the low powered radio **317** by interconnect **322**. The main electronics board **321** comprises a processor for executing single space meter **300** control programs stored in memory of the main electronics board.

The main electronics board **321** may be provided with sufficient peripheral ports for connecting the main electronics board **321** with multiple components including, for example, the coin chute component **312**, the memory module **325**, the vault switch **334**, which may be connected to the memory module **325** and the radio board **315**. If the main electronics board **321** is provided with sufficient connection ports, the radio board **315** can be simply added as a peripheral by including it within the upper housing **302**, and updating the single space meter **300** control software to include the meter information transmitting functionality, which may include transmit trigger event control software. Alternatively multiple components may share a connection to a single peripheral port connection to the main electronics board **321**.

The radio board **315** and low powered radio **317** may also be added onto a single space meter **300** that has a main electronics board **321** that does not have a peripheral port for attaching the radio board **315**. In this case the radio board may be designed to be connected between the memory module and the main electronics board. The radio board may then simply pass the memory module connection through to the main electronics board. The single space meter **300** control software would be updated to provide the additional functionality possible through the use of the radio board **315**.

The processor of the parking meter **300** may execute instructions to provide the parking meter **300** with a transmitting unit for transmitting the parking meter information to the receiver using the low powered radio **317**. The low powered radio **317** may include a transmitter for transmitting data to a receiver. The low powered radio **317** may also comprise a

11

receiver for receiving data. It is understood that both the transmitter and receiver may be provided by a transceiver. The executed instructions may also provide the parking meter **300** with a trigger unit for triggering the transmission of the parking meter information using the transmitting unit. The trigger unit may trigger the transmission of the parking meter information when a trigger event associated with the receiver being within a transmission range is received by the triggering unit.

In a further alternative embodiment, the radio board may comprise the memory module and so connect to the memory module port on the main electronics board or an available peripheral port of the main electronics board. A possible disadvantage with this arrangement is that if the upper housing is replaced in the field (for example due to a jammed coin chute) it may be necessary to reprogram the single space parking meter parameters such as for example the parking meter rate profile. This is because the memory module that stores the parameters is part of the radio board that is located in the upper housing **302** that is removed and not the components of the parking meter that are located in the lower housing and are not removed. This disadvantage can be mitigated or overcome by providing the low powered radio **317** and processor with receiving functionality so that it may receive and store the parking meter parameters from the access point **115**, **120**, which in turn can be provided by from the monitoring location.

FIGS. **4a**, **4b**, **4c** and **4d** depict in schematics an illustrative embodiment of a parking meter mechanism **400** that can be housed in the upper housing of a single space parking meter such as for example parking meter **300**. The parking meter mechanism **400** comprises a mechanism housing **402**, with a display **404** in an opening in the mechanism housing **402**. The mechanism housing **402** may further house or support a radio board **410** including a low powered radio **412**. The radio board **410** is connected to a peripheral port **416** of a main electronics board **425** by interconnect **414**. The interconnect **414** is shown disconnected from the peripheral port **416** in FIG. **4a** and connected to the peripheral port **416** in FIG. **4b**. The mechanism housing **402** further houses a coin chute **420** such as that described in U.S. Pat. No. 6,227,343 currently owned by J. J. MacKay, and a smart card reader **422** for the purchase of parking time using smart cards, electronic purses or credit cards. The parking meter **400** comprises two payment mechanisms, namely the smart card reader **422** and the coin chute **420**. The parking meter **400** may have only a single payment mechanism, or may include different payment mechanisms such as a bill reader.

FIGS. **5a** and **5b** depict the layout of components for an illustrative radio board, such as radio board **410** of FIGS. **4a-4c**. The components of the illustrative radio board are set forth in the table below.

Reference	Part Description	Manufacturer P/N's
PCB 1	Guardian X SmartCollection Module V1.1 PCB Gerbers	MacKay # S026-011-002
C1	Digital Noise Filter 81 MHz SMD	Panasonic ELK-E221FA
C2	Capacitor Ceramic 1.0 uF 16 V X5R 0603	Kemet C0603C105K4PACTU
C3	Capacitor 0.1 uF 25 V Ceramic Y5V 0603	Kernel C0603C104Z3VACTU
J1	Cable Assembly, Dip-To-Ribbon, 10-Pos	Digi-Key A2MXS-1006G-ND
R1	Resistor, thick film, 100 k Ohm 1/10 w 5% 0603 SMD	Rohm MCR03EZPJ104

12

-continued

Reference	Part Description	Manufacturer P/N's
R2	Resistor, thick film, 0.0 Ohm 1/10 w 5% 0603 SMD	Rohm MCR03EZPJ000
R5	Resistor, thick film, 1.0 m Ohm 1/10 w 5% 0603 SMD	Rohm MCR03EZPJ105
U1	Module 802.15.4/Zigbit 2.4 ghz Chipant	Meshnetics ZDM-A1281-A2
U3	IC Single Buffer/Driver open drain SOT23-5	TI SN74AUP1G07DBVR
A1	Connector, Cardedge 10pin Gold Without Ear	CW Industries CWR-170-10-0000
A2	Polarizing Key (Card Edge)	CW Industries CWN-KEY 2

Additional components may be installed on the radio board in order to facilitate testing and debugging. These components may include:

Reference	Part Description	Manufacturer P/N's
D1	Led Thin 565 nm Grn Diff 0805 SMD	Lumex SML-LXT0805GW-TR
D2	Led Thin 635 nm Red Diff 0805 SMD	Lumex SML-LXT0805IW-TR
J2	Header Pins (Generic)	Common source
J3	Conn Recept 10pos.100 Rt/A Dual	AMP 6-5535512-4
R3, R4	Resistor, thick film, 330 Ohm 1/10 w 5% 0603 SMD	Rohm MCR03EZPJ331

FIG. **6a** depicts in a schematic an illustrative parking meter management system in accordance with the present disclosure. The parking meter management system **600** comprises at least one single space parking meter **605** in accordance with one of the illustrative embodiments described above. Although only one parking meter **605** is depicted it is understood that the parking meter management system **600** may comprise any number of parking meters in accordance with the present disclosure. The parking meter management system **600** further comprises a mobile access point **610** which comprises a coin collection cart **612** and a data collection terminal **614** which may be a hand held terminal having a receiver for receiving the parking meter transmitted by a transmitter of the parking meter **605**. The parking meter management system **600** may further comprise a parking management and reporting central host system **620**, which may include parking meter management software for reporting and managing the meter information retrieved from the single space meters. The parking management and reporting central host system may be located on one or more computers comprising processors executing instructions stored in memory that provide the parking management and reporting functionality.

A collection officer would generally push or pull the coin collection cart **610** to each single space parking **605** of the parking meter system **600**. The collection officer opens the vault door and removes the coins from the parking meter **605** and transfers them to the coin collection cart **610**. If the parking meter **605** uses a vault switch to provide a signal for initiating transmission of the parking meter information then the parking meter begins transferring the parking meter information to the coin collection cart which the collection officer has brought in close proximity to the meter in order to transfer the coins. When the collection officer opens the vault door to transfer the coins, the vault switch sends a signal to the processor. The signal may be used as a trigger event for triggering the transmission of the parking meter information to the

receiver of the terminal **614**. If the parking meter **605** uses another means as the trigger event associated with the parking meter being within a transmission range of the receiver, then the signal will similarly be provided to initiate the transmission of the parking meter information when the coin collection cart or the receiver of the collection terminal is within the transmission range. The transmission of the parking meter information from the parking meter to the mobile access point **610**, comprising the coin collection cart and a receiver, may require less power as a result of the close proximity of the receiver in the terminal **614** on the collection cart **612** to the parking meter **605**. The time required by the collection officer to open the vault door, remove the coins from the vault, transfer the coins to the collection cart and close/lock the vault door is typically longer than the time required to transmit the parking meter information to the mobile access point. As such, the collection officer does not need to alter their coin collection routine.

The parking meter may be provided with a transmission status indicator for indicating that the transmission of the parking meter information is complete. The transmission status indicator may include for example, an audible indicator such as a tone or series of tones, or a visual indicator such as a light emitting diode or other indicator.

FIG. **6b** depicts in a schematic an illustrative hand-held data collection terminal **614** that may be used in the parking meter system **600** of FIG. **6a**. The hand-held terminal **614** may include a peripheral radio **630** which may include a receiver for communicating with the transmitters of the low powered radios of the parking meters. The terminal **614** depicted is a Jett-XL® hand-held computer made by Two Technologies, Inc. Other types of terminals can be used if they include a radio for communicating with the low powered radios or transmitters of the parking meters.

The mobile access point **610** may comprise the hand-held terminal **614**. As depicted in FIG. **6a**, the hand-held terminal **614** may be affixed or coupled to the coin collection cart **612**. Alternatively, the mobile access point **610** comprising the hand-held terminal **614** may be carried by the collection officer pushing/pulling a collection cart **612**.

FIG. **6c** depicts in a schematic an illustrative parking meter in accordance with the parking meter management system **600** of FIG. **6a**. The parking meter **605** comprises an electronic meter mechanism **400** such as the one described with reference to FIGS. **4a**, **4b**, **4c**. The meter mechanism **400** may comprise the wireless radio board **410**, the peripheral port connector **416**, and a housing wiring harness **414**. The housing wiring harness **414** may provide all of the interconnects, for example interconnects **322**, **324**, **323**, and **336** of FIG. **3b**, necessary for connecting the peripheral components housed in the housing of the parking meter to the peripheral port **416** of the parking meter mechanism **400**. The parking meter mechanism **400** may be housed in an upper housing **302** of the parking meter **605**. The upper housing **302** may be connected to the lower housing **305**. The lower housing **305** may comprise the memory module **325**, which may form part of the housing wiring harness **414**, a vault door **332**, and a vault door switch **334**. The vault door switch **334** may provide a signal to the parking meter mechanism indicating that the vault door **332** is open, closed or locked. The signal may be passed to parking meter mechanism via the housing wiring harness **414** connected to the peripheral port connector **416**.

FIG. **7** depicts in a flow chart an illustrative method of transmitting parking meter information. The method **700** stores parking meter information (**702**) in a memory of the parking meter. The parking meter then detects a trigger event has occurred that is associated with the receiver being within

a transmission range of the parking meter (**704**). Once the trigger event occurs, the parking meter triggers the transmission of the stored parking meter information (**706**).

The single space parking meter described above with reference to FIG. **6c** allows the parking meter mechanism to be connected to a housing wiring harness **414** which may provide an interconnect to a vault door switch of the parking meter as well as to the radio board of the parking meter. The peripheral port connector **416** of the parking meter mechanism provides an environmentally suitable and robust connector that provides a reliable connection between the parking meter mechanism and the housing wiring harness **414**. The peripheral port connector **416** also provides a connector interface to the housing wiring harness **414** that allows meter maintenance staff to easily connect and remove the parking meter mechanism from the housing wiring harness **414** and the outer housing. The parking meter mechanism has the ability to utilize the housing wiring harness **414** to monitor the open/closed/locked status of the vault door of the housing, or more particularly the vault door switch, that it is installed into, as well as to detect when the electrical connection to the housing wiring harness **414** has been broken. The parking meter mechanism may also use the housing wiring harness **414** to provide power to, as well as to read/write data to, a memory device **325** that is remote or separate from the meter main board, but electrically attached to the meter main board via the housing wiring harness **414**. The parking meter mechanism may automatically load configuration data found on the memory module **325** attached to the housing wiring harness **414**. The configuration information may include the current post/location ID, as well as current zone/rate profile identifier or details, and any other configuration data that would be required by the parking meter mechanism to operate at the correct and proper prevailing rates, time limit and conditions appropriate for that parking zone/area. The parking meter mechanism may also automatically create a time stamped maintenance data record each time the mechanism is attached to or removed from a housing wiring harness **414**. The parking meter mechanism may also automatically create a time stamped maintenance data record when there is no response from the memory module **325** after some programmable period of time has elapsed, or a programmable number of attempts has elapsed, or a combination of both.

A single space parking meter in accordance with the present description may have the ability to automatically communicate wirelessly with a receiver that may be carried on the body of a maintenance staff or collections officer or may be carried or mounted to a coin collection cart. Regardless of how the receiver is carried, the parking meter begins transmitting parking meter information when a trigger event associated with the receiver being in close proximity occurs, such as for example a foot to 15 feet. The wireless communication between the parking meter and the mobile access point is preferably not impacted or degraded by paint or scratches on the Lexan® window of the parking meter housing.

Furthermore, the parking meter and the mobile access point may comprise identification information used to verify the communications to ensure that the parking meter only communicates with and/or exchanges data with approved or authorized data collection devices. The parking meter and the mobile access points may each create a time stamped maintenance data record of all data collection events. The parking meter may also create a time stamped maintenance record of all detected vault door openings regardless of the presence of the mobile access point. Audit and maintenance data may be automatically transferred to the mobile access point when the

15

physical coin collection is being carried out, which may be signaled by a vault door switch indicating that the vault door is open.

The data collection carried out during the physical coin collection may be done automatically without any interaction required between the coin collector and the mobile access point. The mobile access point may be able to continue to communicate with the single space meter after the physical coin collection has completed in order to ensure that all of the parking meter information has been transferred. The parking meter may also communicate to the mobile access point that the physical vault door has been placed into the closed and/or locked position following the initial vault door opening. The parking meter may be able to automatically upload and store new rate/profile/configuration information from the mobile access point during the coin collection, either before or after the transmission of the parking meter information. The parking meter may also be able to automatically synchronize its time of day clock with the mobile access point in order to recalibrate and or check its clock. The parking meter may provide a visual indicator to the collections officer or maintenance staff that an audit and/or data transfer is underway and/or is completed, which may include a visual and/or audible indicator that the transmission is underway and/or was successfully completed or not.

In addition to the wireless communication with the mobile access point, the parking meter may also be configured to allow the parking meter to automatically communicate with the remote collection device when a small intelligent probe is inserted, for example into the coin slot, or verifying a maintenance staff's fingerprint or RFID tag. This may allow maintenance staff who are non-collections staff, to easily initiate some data collection tasks, such as transfer of error messages or operating parameters. The mobile access point may normally be attached to the collection cart but may be alternatively carried by the collections officer or maintenance staff. Depending on the battery life of the mobile access point, it may run out of power if carried by the collection staff. The mobile access point if attached to the collection cart may be able to also utilize a second battery pack attached to the collection cart to extend the operating time. Regardless of if the mobile access point is carried by a maintenance staff or collections officer or on the coin collection cart, the battery on the data collection device may be swappable in the field without the loss of data, and the mobile access point may automatically continue its data collection mode without further collector/maintenance officer intervention.

The mobile access point may have a keyboard and a display allowing event data, such as the collection can ID containing the coins to be transferred from the vault of the parking meter to the coin collection cart, to be entered/captured manually. The mobile access point may have the ability to support cellular communications through the addition of a cellular card, in addition to the low power radio, and if so installed, the mobile access point may be configurable to allow and or provide regular scheduled data transmissions to the back end host system while the collectors or maintainers are still in the field. The mobile access points may support 802.11 a/b/g/n (Wi-Fi) communications, such that when the collection carts with attached devices are returned to a meter/collection depot and docked into their charging cradles the collected parking meter information can be automatically and wirelessly transferred to the back end host system. Additionally or alternatively the mobile access points may transfer the collected parking meter information to the back-end host system using a wired connection.

16

While the above description has described illustrative parking meters, methods of transmitting parking meter information and a parking meter management system, it is understood that modifications and adaptations are possible to provide additional features, or remove un-required or un-desired features, as would be understood by one of ordinary skill in the art. Furthermore, the functionality provided by individual components may be combined into fewer components, or may be provided by additional components as would be understood by one of ordinary skill in the art.

What is claimed is:

1. A parking meter comprising:
 - an outer housing; and
 - a parking meter mechanism enclosed within the outer housing, the parking meter mechanism comprising:
 - a transceiver for transmitting and receiving information;
 - a memory for storing instructions; and
 - a processor for executing instructions, the instructions when executed by the processor configuring the parking meter to:
 - detect a trigger event comprising a radio frequency identification (RFID) tag being in close proximity to the parking meter mechanism; and
 - transmit configuration information comprising a unique identifier associated with a location of the parking meter using the transceiver upon detection of the trigger event;
 - receive information with the transceiver subsequent to transmitting the configuration information, wherein the received information comprises information on one or more parameters of the parking meter; and
 - modify the one or more parameters of the parking meter based on the received information.
2. The parking meter of claim 1, wherein the information is transmitted to a monitoring location.
3. The parking meter of claim 2, wherein the information is transmitted to the monitoring location using a cellular infrastructure.
4. The parking meter of claim 2, wherein the information is transmitted from the parking meter to an access point and from the access point to the monitoring location.
5. The parking meter of claim 1, wherein the received information is received from a monitoring location.
6. A parking meter mechanism comprising:
 - a transceiver for transmitting and receiving information;
 - a memory for storing instructions; and
 - a processor for executing instructions, the instructions when executed by the processor configuring the parking meter to:
 - detect a trigger event comprising a radio frequency identification (RFID) tag being in close proximity to the parking meter mechanism; and
 - transmit configuration information comprising a unique identifier associated with a location of the parking meter using the transceiver upon detection of the trigger event;
 - receive information with the transceiver subsequent to transmitting the configuration information, wherein the received information comprises information on one or more parameters of the parking meter; and
 - modifying the one or more parameters of the parking meter based on the received information.
7. The parking meter mechanism of claim 6, wherein the information is transmitted to a monitoring location.

17

8. The parking meter mechanism of claim 7, wherein the information is transmitted to the monitoring location using a cellular infrastructure.

9. The parking meter mechanism of claim 7, wherein the information is transmitted from the parking meter to an access point and from the access point to the monitoring location.

10. The parking meter mechanism of claim 6, wherein the received information is received from a monitoring location.

11. A method of transmitting information at a parking meter, the method comprising:

detecting at a parking meter mechanism a radio frequency identification (RFID) tag in close proximity to the parking meter mechanism; and

transmitting configuration information comprising a unique identifier associated with a location of the parking meter using a transceiver of the parking meter upon detection of the RFID tag in close proximity to the parking meter;

18

receiving information with the transceiver subsequent to transmitting the configuration information, wherein the received information comprises information on one or more parameters of the parking meter; and
 5 modifying the one or more parameters of the parking meter based on the received information.

12. The method of claim of 11, wherein transmitting the information comprises transmitting the information to a monitoring location.

10 13. The method of claim 12, wherein transmitting the information to the monitoring location comprises transmitting the information using a cellular infrastructure.

14. The method of claim 11, wherein the received information is received from a monitoring location.

15 15. The method of claim 14, wherein the received information is received over a cellular infrastructure.

* * * * *