



US008422875B2

(12) **United States Patent**  
**Marcus**

(10) **Patent No.:** **US 8,422,875 B2**  
(45) **Date of Patent:** **\*Apr. 16, 2013**

(54) **REMOTE VIEW AND CONTROLLER FOR A CAMERA**

(75) Inventor: **Brian I. Marcus**, San Francisco, CA (US)

(73) Assignee: **Forever Ventures LLC**, Richardson, TX (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 34 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/323,625**

(22) Filed: **Dec. 12, 2011**

(65) **Prior Publication Data**

US 2012/0083313 A1 Apr. 5, 2012

**Related U.S. Application Data**

(63) Continuation of application No. 12/125,828, filed on May 22, 2008, now Pat. No. 8,078,045, which is a continuation of application No. 11/189,359, filed on Jul. 26, 2005, now Pat. No. 7,379,664.

(51) **Int. Cl.**  
**G03B 17/00** (2006.01)

(52) **U.S. Cl.**

USPC ..... **396/56**; 396/58; 396/59; 348/211.8; 348/211.13

(58) **Field of Classification Search** ..... 396/56, 396/58, 59; 348/211.8, 211.13  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,809,759	B1 *	10/2004	Chiang	.....	348/211.2
6,819,867	B2 *	11/2004	Mayer et al.	.....	396/56
7,379,664	B2 *	5/2008	Marcus	.....	396/56
7,755,668	B1 *	7/2010	Johnston et al.	.....	348/211.4
8,078,045	B2 *	12/2011	Marcus	.....	396/56
2003/0165192	A1 *	9/2003	Kitta	.....	375/240.01
2004/0135879	A1 *	7/2004	Stacy et al.	.....	348/14.02
2006/0114987	A1 *	6/2006	Roman	.....	375/240.01


\* cited by examiner

*Primary Examiner* — Clayton E LaBalle  
*Assistant Examiner* — Warren K Fenwick

(57) **ABSTRACT**

A device operable with a camera is disclosed which includes a display screen, remote from the camera, and a processor for receiving an image signal of the field of view of the camera and for displaying an image of the field of view of the camera on the display screen. The device communicates with and controls certain camera functions to allow a photographic or video image to be framed and taken from a location remote from the camera.

**15 Claims, 10 Drawing Sheets**






Fig. 1




Fig. 2




Fig. 3




Fig. 4









Fig. 6










Fig. 9







Fig. 12





*Fig. 13*



*Fig. 14*




Fig. 15





Fig. 16



## REMOTE VIEW AND CONTROLLER FOR A CAMERA

### PRIORITY CLAIM

This application is a continuation of U.S. patent application Ser. No. 12/125,828, filed May 22, 2008 entitled "Remote View And Controller For A Camera," which application has been allowed and is to issue as U.S. Pat. No. 8,078,045 on Dec. 13, 2011, which application is a continuation of U.S. patent application Ser. No. 11/189,359 filed Jul. 26, 2005 entitled "Remote View And Controller For A Camera," which application has issued as U.S. Pat. No. 7,379,664 on May 27, 2008.

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

This invention relates generally to the field of photography, and in particular to a view and camera controller that is remote from the camera.

#### 2. Description of the Related Art

Whether single lens reflex ("SLR") or digital formats, cameras have become common household items. Camera technology has evolved to the point where cameras fit within the palm of a hand and may be easily and conveniently carried and accessed for taking photographs. However, a drawback to conventional cameras is typically a person needs to be behind a camera to line up the camera view, zoom to the proper perspective, frame the photo, and take the photo. Consequently that person may not be able to be in the photo.

In populated areas, this drawback is often overcome by imposing on strangers by asking them to take a photograph. In addition to the imposition, the stranger is often ill-equipped to operate the camera and/or take advantage of the various camera features. Similarly, the stranger may not understand what the photograph is to encompass as far as zoom and background.

Additionally, when in private, or in an otherwise unpopulated area, imposing on others to take the photograph may not be an option. In that instance, a person taking the photograph may not also be in the photograph. One solution to this problem is the inclusion of a timer in some cameras. In this instance, a person may set up the photograph view, zoom and frame, and then set a timer to give the individual time to move from behind the camera to be within the photograph. However, timers are still inconvenient to use, and the subject moving from behind the camera into the photo may not properly position themselves in the desired position within the photograph.

Mobile telephones, personal digital assistants and computers are also become household devices. Conventionally, mobile telephones and other devices have not been used to view an image seen by a camera, nor have mobile telephones and the like been used to control camera operation.

### SUMMARY OF THE INVENTION

Embodiments of the present invention relate to a device operable with a camera, video camcorder, webcam, mobile telephone or other image-capturing device (all hereinafter referred to as a "camera"). The device includes a display screen, remote from the camera, and a processor for receiving an image signal of the field of view of the camera and for displaying an image of the field of view of the camera on the display screen. In embodiments, the device may communicate with an actuation table on which the camera is mounted

for pivoting the actuation table and camera left and right and up and down to properly frame a photo or image being captured by the camera. In embodiments, the actuation table may be omitted and the camera itself responds electronically and/or mechanically to the communication from the device to properly frame the photo or image. The device may further include a zoom control for zooming the camera field of view in and out, as well as a button causing the camera to take a picture.

In embodiments, the device may be a dedicated component. In an alternative embodiment, the device may be a multipurpose device configured to receive and display an image from the camera field of view, and to control certain camera functions. Such multipurpose devices include but are not limited to a mobile telephone, a personal digital assistant, hand-held computer, laptop computer, desktop computer, a tablet computer and/or another camera.

### BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will now be described with reference to the drawings.

FIG. 1 is the perspective view of a camera taking a photograph with a remote view and control device according to embodiments of the invention.

FIG. 2 is a front view of the view and control device according to embodiments of the invention.

FIG. 3 is a front view of a camera and actuation table according to embodiments of the present invention.

FIG. 4 is a side view of a camera and actuation table according to embodiments of the present invention.

FIG. 5 is a front view of the interior of an actuation table according to embodiments of the present invention.

FIG. 6 is a top view of the interior of an actuation table according to embodiments of the present invention.

FIG. 7 is a front view of the interior of a drive housing according to embodiments of the present invention.

FIG. 8 is a front view of an embodiment of a support structure for use as an alternative to a tripod.

FIGS. 8A and 8B are views of a camera having a lens capable of left/right tilt and/or up/down tilt relative to a camera housing in which the lens is supported.

FIG. 9 is a block diagram of a camera, actuation table and view and control unit according to embodiments of the present invention.

FIG. 10 is a view of a camera and handheld device configured as a view and control unit according to a further embodiment of the present invention.

FIG. 11 is a front view of a mobile telephone for performing as a view and control unit according to an embodiment of the present invention.

FIG. 12 is a block diagram of a camera and handheld device configured as a view and control unit according to a further embodiment of the present invention.

FIG. 13 is a block diagram for loading software to configure a hand-held device as a view and control unit.

FIG. 14 is block diagram of the software operation according to embodiments of the present invention.

FIG. 15 is a block diagram of the operation of a telephone including a view and control mode according to an embodiment of the present invention.

FIG. 16 is a diagram of a camera and several devices which may be configured to operate as a view and control unit according to embodiments of the present invention.

### DETAILED DESCRIPTION

The present invention will now be described with reference to FIGS. 1 through 16, which embodiments of the present

invention relate to a camera view and controller unit (“VCU”). It is understood that the present invention may be embodied in many different forms and should not be construed as being limited to the embodiments set forth herein. Rather these embodiments are provided so that this disclosure will be thorough and complete and will fully convey the invention to those skilled in the art. Indeed, the invention is intended to cover alternatives, modifications and equivalents of these embodiments, which are included within the scope and spirit of the invention as defined by the appended claims. Furthermore, in the following detailed description of the present invention, numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will be clear to those of ordinary skill in the art that the present invention may be practiced without such specific details.

Referring now to the perspective view of FIG. 1, there are shown subjects **100** in front of a camera **102**. One of the subjects is holding a VCU **104** as explained hereinafter. Camera **102** may include any components known for inclusion in a camera, plus a communication system for communicating with VCU **104** as explained hereinafter. Camera **102** may be a digital camera, but it is contemplated that camera **102** is a SLR camera, video camcorder, webcam, mobile telephone or other image-capturing device in alternative embodiments. Camera **102** may operate with a flash, or not, and may have any known lens for use with cameras. Camera **102** may have a built in lens, or be configured to work with a variety of detachable lenses.

Referring to FIGS. 1 and 2, VCU **104** allows a subject **100** to stand in front of camera **102**, i.e., within the field of view of the camera, while at the same time viewing the camera field of view and controlling camera function and operation. In particular, VCU **104** may include an LCD screen **106** for showing the field of view seen by the camera, and zoom in/out pushbutton **108**, pan left/right pushbutton **110** and pan up/down pushbutton **112**. The buttons **108**, **110** and **112** are provided for changing a perspective of the camera by zooming the camera lens in or out, tilting the camera left or right or tilting the camera up or down, respectively. The actions affected by each of the buttons **108**, **110** and **112** are communicated to camera **102** via wireless protocols explained hereinafter.

VCU **104** may have a form factor so as to be held comfortably in a single hand, though the length, width and depth of the unit may vary in alternative embodiments. The VCU **104** may be approximately the same size or smaller than the camera **102**. VCU may have an outer housing formed of metal, plastic or other durable, protective material.

When standing in front of the camera mounted on a tripod or otherwise supported on a surface, the camera’s field of view may not be positioned as desired for a particular photograph or video image. It may be desired to tilt the camera left or right and/or up or down, so as to properly capture the subjects **100** as well as the desired background. Camera **102** may therefore be mounted on an actuation table **114** as shown for example in FIGS. 3 and 4. An embodiment of actuation table **114** is described hereinafter, but it is understood that a variety of mechanisms may be provided for pivoting camera **102** about two axes in order to tilt the camera left and right and up and down.

Conventional cameras may be mounted on a tripod **120** as shown in FIG. 1. Actuation table **114** may include an opening on its bottom surface to attach to the tripod in the same manner as camera **102** attaches to the tripod. For example, a bottom surface of actuation table **114** may include a threaded bore (not shown) for screwing onto tripod **120**. It is under-

stood that actuation table **114** may include any mounting scheme used to mount cameras to tripods.

Similarly, actuation table may include a vertical shaft **150** emanating from a top of the actuation table onto which the camera **102** may be affixed. Camera **102** may affix to vertical shaft **150** in the same manner as camera **102** affixes to tripod **120**. For example, vertical shaft **150** may include a threaded end for mating within a threaded bore formed within a bottom surface of camera **102**. It is understood that vertical shaft **150** may include any mounting scheme used to mount tripods to cameras.

Internal components for pivoting camera **102** about two axes according to one embodiment are shown in FIGS. 5-7. Perpendicular x, y, z axes are indicated in FIGS. 5 and 6, with an x-y plane being a horizontal plane and z being a vertical axis (it is understood that the actuation table and camera **102** need not be mounted along these axes). Mounted on the bottom of camera **102** in an x-y plane, the actuation table is capable of pivoting camera **102** about the x axis to tilt camera **102** up and down, and about the z axis to tilt camera **102** left and right.

An embodiment of actuation table **114** includes a horizontal shaft **152** extending along the x-axis and fixedly mounted within the actuation table, to opposed internal ends of the actuation table. A drive housing **154** is pivotally mounted to horizontal shaft **152**. Vertical shaft **150** is pivotally mounted within the drive housing and extends along the z-axis from the drive housing **154**. Referring to FIG. 7, drive housing **154** includes an x-axis drive **158** and a z-axis drive **160**. X-axis drive **158** may be a reversible motor of known construction, including bearings **162** for rotationally supporting x-axis drive **158** on horizontal shaft **152**, and a stator for receiving an electric current. The horizontal shaft **152** may be a rotor running through the drive’s stator. Upon current to the stator, x-axis drive **158** controllably pivots drive housing **154** about the x-axis, to tilt the actuation table **114** and camera **102** up or down.

Z-axis drive **160** may be a reversible motor of known construction, including bearings **166** for rotationally supporting vertical shaft **150** within drive housing **154**, and a stator for receiving an electric current. The vertical shaft **150** may be a rotor running through the drive’s stator. Upon current to the stator, z-axis drive **160** pivots vertical shaft **150** about the z-axis, to tilt the actuation table **114** and camera **102** left or right, independently of the x-axis drive **158**.

Drive housing **154** may include a variety of other components in alternative embodiments. One or both of drives **158**, **160** may additionally or alternatively include one or more gears or a planetary gear system to pivot the housing **154** and/or vertical shaft **150** about its respective axis. Drive housing may additionally include electromagnetic interference (EMI) shielding to shield the respective drives **158**, **160** from each other. The size of the drives **158**, **160** may vary in alternative embodiments of the invention.

Those of skill in the art would appreciate other drive mechanisms for achieving independent pivoting of camera **102** about the x and z axes. For example, it is contemplated that camera **102** be affixed to the actuation table with a ball and socket arrangement between the table and camera. The movement of the camera on the ball of the actuation table may be controlled with various drives and control mechanisms. While the embodiment of actuation table **114** may be mounted horizontally beneath camera **102**, it is conceivable some manner of actuation table **114** may be mounted vertically to a vertical surface of camera **102**. Again, various known drive mechanisms would be known to those of skill in the art for such an embodiment.

The present invention may operate without the tripod **120**. In such an embodiment, a bottom portion of actuation table **114** may simply rest on an arbitrary surface selected by the subject. For such embodiments, the camera **102** may be mounted to the actuation table **114**, and may pivot about a pair of axes, as described above.

The arbitrary surface selected by the user may not be flat. Therefore, in a further embodiment shown in FIG. **8**, the actuation table may have an adaptive surface **180** on its lower surface. Adaptive surface **180** may have a shape capable of conforming to an arbitrary surface on which the actuation table and camera may be positioned. This allows the actuation table and camera to be supported on an arbitrary surface in a stable and controlled position. Adaptive surface **180** may for example be deformable, and have a plurality of beads within an interior cavity as is known in the art, which beads allow the surface **180** to adapt in shape to arbitrary surfaces. Other configurations for allowing a lower surface of actuation table **114** to conform to an arbitrary surface are known.

In a further embodiment, it is understood the actuation table **114** may be omitted. In such embodiments the camera **102** may be stationarily positioned on a tripod or an arbitrary surface. In such embodiments, the left/right and up/down fields of view may be set and do not change. Alternatively, the left/right and up/down fields may be adjusted electronically as explained hereinafter. Where the actuation table is omitted, the bottom portion of the camera may be supported directly on an arbitrary surface. Alternatively, the adaptive surface **180** may be provided on a bottom surface of camera **102** to support the camera in a stable and controllable position.

It is conceivable that, instead of an actuation table, camera **102** itself is capable of adjusting the field of view up or down and/or left or right. This can be accomplished optically, electronically, mechanically or some combination of optics, electronics, and mechanics. In a first embodiment, the camera may include a wide view lens that receives a wide view which is captured on the image sensor. The VCU is used to instruct the camera to adjust/shift the field of view in a particular direction (i.e., up or down, left or right, zoom in or out). The camera's optics and/or electronics cause the lens to refocus as instructed by the VCU. The camera advantageously re-allocates the image capturing elements (typically referred to as pixels) to capture the selected image with a high degree of clarity and focus.

In such embodiments, the VCU display **106** may display an image generally the size and composition of a photograph or video image if taken at that time. As indicated, the actual image capturing element may have captured a larger image than displayed. As the captured image is larger than the field of view image, the field of view of the image may be electronically adjusted/shifted up or down, left or right, or zoomed in or out using the actuators on the VCU **104**.

Alternatively, the VCU display **106** may display the entire captured image, i.e., a larger view than the size of a photograph or video image. In such an embodiment, the display may further include a graphical rectangle or other visual indicator generally representing the boundary of a photograph or video image field of view if taken at that time. The position of the graphical rectangle can be adjusted/shifted up or down, left or right, or zoomed in or out on the display **106** using the actuators on the VCU **104** to electronically adjust/shift the field of view of the image up or down, left or right, or in or out.

In another embodiment, the camera may include additional image capturing elements that allows the camera's optics to capture a portion or portions of an image around the periphery of the camera's nominal field of view. As the VCU instructs

the camera to adjust/shift in a particular direction (i.e., up, down, left or right, zoom in or out), the camera utilizes those additional image capturing elements to capture the portions of the images that are added as a result of the adjustment or shift.

In other embodiment, the camera may utilize the image capturing elements that become obsolete as a result of an instructed adjustment. As the VCU instructs the camera to adjust/shift in a particular direction (i.e., up, down, left, right, zoom in or out) and away from its nominal field of view, the camera's optics and microprocessor can advantageously utilize those image capturing elements that will become unused when the field of view adjust/shift in a particular direction to capture the portions of the images that are added as a result of the adjustment/shift.

It is understood that some combination of additional image capturing elements and obsolete image capturing elements may be use to achieve the design goals of the present invention.

In another embodiment, motors may be used. For example, a lens capable of left/right tilt and/or up/down tilt relative to a camera housing in which the lens is supported. An example of such an embodiment is shown in FIGS. **8A** and **8B**. In FIGS. **8A** and **8B**, the camera and lens are shown in phantom for clarity of a lens actuation assembly **180**. Lens actuation assembly **180** may include a plate **182** with an aperture for detachably receiving the camera lens. Plate **182** may be pivotally mounted to a frame **184** via a shaft **186** so as to pivot around the z-axis. The shaft **186** may be pivotally mounted within a reversible drive **188** to controllably affect rotation of the plate **182** and the camera lens about the z-axis to tilt the lens left and right relative to the camera housing **190**.

The frame **184** is in turn fixedly mounted to a shaft **192** pivotally mounted within housing **190** to a support **194** at one end and a second reversible drive **196** mounted to the housing **190** at its opposite end. The reversible drive **196** controllably affects rotation of shaft **192**, frame **184** and the camera lens about the x-axis to tilt the lens up and down relative to the camera housing **190**. Those of skill in the art would appreciate other assemblies for tilting the lens with respect to the camera housing.

Referring again to FIG. **2**, VCU **104** may include zoom pushbutton **108**, left/right pushbutton **110** and up/down pushbutton **112**. Upon actuation of pushbutton **108**, a signal may be sent to camera **102** as explained hereinafter to elongate or shorten the position of the camera lens to affect a zoom in or zoom out of the field of view. Apart from the manner in which the signal may be sent to affect a lens zoom, the pushbutton **108** may operate in the same manner as the zoom button on a conventional camera.

Upon actuation of pushbutton **110**, a signal may be sent to actuation table **114** as explained hereinafter actuating z-axis drive **160** to tilt the actuation table **114** and camera **102** left or right. Pushing on the left side of pushbutton **110** may tilt the camera to left, and pushing on the right side of pushbutton **110** may tilt the camera to the right. These directions may be reversed in alternative embodiments. The pushbutton **110** may be selectively actuated until the desired left/right field of view is captured by the camera **102**.

Similarly, upon actuation of pushbutton **112**, a signal may be sent to actuation table **114** as explained hereinafter actuating x-axis drive **158** to tilt the actuation table **114** and camera **102** up or down. Pushing on the top side of pushbutton **112** may tilt the camera up, and pushing on the bottom side of pushbutton **112** may tilt the camera down. These directions may be reversed in alternative embodiments. The pushbutton

**112** may be selectively actuated until the desired up/down field of view is captured by the camera **102**.

While pushbuttons are shown, those of skill in the art would appreciate that the above described functions of push-buttons **108-112** may be accomplished by various other mechanisms, such as dials, slide levers, switches, other types of buttons, etc.

In conventional cameras, a field of view image as seen by a camera is transmitted and displayed on an LCD screen on a back side of the camera. As explained hereinafter, this same field of view image is transmitted to VCU **104** and displayed on LCD **106**. Thus, in embodiments, the LCD screen **106** on VCU **104** shows the same image as shown on the LCD screen on the back of the camera. As the field of view image of the camera is adjusted by pushbuttons **108, 110** and/or **112** as explained above, the image shown on LCD **106** changes accordingly.

Once the proper zoom, left/right pan and up/down pan has been selected for a photo, as shown by the field of view displayed on LCD screen **106**, a button **118** on VCU **104** may be actuated to send a signal to camera **102** to take a picture (i.e., capture the image shown on LCD screen **106** and save to memory). It is known that the lens may be autofocused on an image seen by the lens upon partially depressing the picture-taking button in a conventional camera. In the same manner, partially depressing button **118** may send a signal to the camera **102** causing the lens to autofocus on the image seen by the camera **102**.

Those of skill in the art will appreciate that the arrangement of components **106, 108, 110, 112** and **118** on VCU **104** shown in FIG. **2** is one of many possible arrangement of those components on VCU **104**. VCU **104** includes a back surface (not shown), opposite the surface shown in FIG. **2**. The back surface may be blank, or may include an inscription, corporate logo or a plurality of aesthetic designs. Alternatively, one or more of the buttons **108, 110, 112** and **118** may be provided on the back surface, or on one of the edges between the front and back surface, in alternative embodiments.

FIG. **9** is a block diagram of a camera **102**, actuation table **114** and VCU **104** according to an embodiment of the present invention. FIG. **9** shows an embodiment of the invention where camera **102** is a digital camera, and includes components provided within a conventional digital camera. FIG. **9** is a simplified block diagram of components within the camera **102**, and it is understood that a variety of other components found within conventional digital cameras may be provided in addition to or instead of some of the components shown within camera **102** in alternative embodiments.

However, in general, digital camera may include an image processor **200** which receives image data from an image sensor **202**, which captures an image through a lens **204**. Image sensor **202** may be a charge coupled device (CCD) capable of converting light into an electric charge. Other devices, including complementary metal oxide semiconductor (CMOS) sensors, may be used for capturing information relating to an image. An analog-to-digital converter (not shown) may be employed to convert the data collected by the sensor **202**. The zoom for the image is controlled by a motor **206** and zoom **208** in a known manner upon receipt of a signal from the processor **200**. The image may be captured by the image sensor upon actuation of the shutter **210** via a motor **212** in a known manner upon receipt of a signal from the processor **200**.

Images captured by the image sensor **202** may be stored by the image processor **200** in memory **216**. A variety of digital memory formats are known for this purpose. In one embodiment, memory **216** may be a removable flash memory card,

such as those manufactured by SanDisk Corporation of Sunnyvale, Calif. Formats for memory **216** include, but are not limited to: built-in memory, Smart Media cards, Compact Flash cards, Memory Sticks, floppy disks, hard disks, and writeable CDs and DVDs.

A USB connection **218** may be provided for allowing connection of the camera **102** to another device, such as for example a computer. It is understood that other types of connections may be provided, including serial, parallel, SCSI and an IEEE 1394 ("Firewire") connections. The connection **218** allows transfer of digital information between the memory **216** and another device. The digital information may be digital photographs, video images, or software such as application programs, application program interfaces, updates, patches, etc.

A user interface **220** of known design may also be provided on camera **102**. The user interface may include various buttons, dials, switches, etc. for controlling camera features and operation. The user interface may include a zoom button or dial for affecting a zoom of lens **204** via the image processor **200**. The user interface **220** may further include a mechanism for selecting a mode of operation of the camera **102** (i.e., stored picture review mode, picture taking mode, video mode, autofocus, manual focus, flash or no flash, etc.). The user interface may also cause various menu items to be displayed on LCD screen **230** described hereinafter for controlling camera functions such as deleting stored photos, changing picture resolution, etc.).

The image captured by the image sensor **202** may be forwarded by the image processor **200** to an LCD **230** positioned on the camera **102** via an LCD controller interface **232**. LCD **230** and LCD controller **232** are known in the art. The LCD controller interface **232** may be part of processor **200** in embodiments.

Camera **102** further includes a communications interface **240** for transmitting signals between camera **102** and VCU **104**. The interface **240**, and complimentary communications interface **260** on VCU **104** and communications interface **280** on actuation table **114**, may operate according to a variety of known wireless communication protocols for wirelessly communicating signals between camera **102**, actuation table **114** and VCU **104**.

In an embodiment, the wireless communication protocol may be the Bluetooth short-range wireless protocol which uses radio waves to allow local connectivity between the camera **102**, actuation table **114** and VCU **104** in an ad hoc wireless network. The Bluetooth protocol operates using radio waves in the 2.45 GHz frequency band (the Industrial-Scientific-Medical (ISM) band). The Bluetooth consortium of companies also developed de facto standards for the interface and the software that controls it to ensure interoperability of devices from different manufacturers that are using Bluetooth communications. Further details of the Bluetooth communications system are set forth in the papers, "Ericsson's Bluetooth Modules," by Arfwedson and Sneddon, Ericsson Review No. 4, 1999, pp. 198-205, and "Bluetooth—The Universal Radio Interface for Ad Hoc, Wireless Connectivity," by Jaap Haartsen, Ericsson Review No. 3, 1998, pp. 110-117, which papers are incorporated by reference in their entirety herein. Further details relating to the Bluetooth communications system may also be found in the Bluetooth Specification at the Bluetooth website ([www.bluetooth.com](http://www.bluetooth.com)), which specification is also incorporated by reference in its entirety herein. Bluetooth has been shown capable of transmitting images. For example, Error Resilient Image Transmission over a Bluetooth Network, by Kelly et al., NUI, GALWAY FAC-

ULTY OF ENGINEERING RESEARCH DAY 2004, which is also incorporated by reference in its entirety herein, describes one methodology.

Communications interface **240** sends and receives transmissions via an antenna **242**. Through communications interface **240**, the image that the image processor **200** sends to the LCD controller **232** for display on LCD **230** may also be sent wirelessly to the VCU **104** for display on LCD **106**. Thus, the image seen by the camera lens **204** to be captured in a photograph or video is seen on LCD **106** on VCU **104**.

Image processor **200** may be configured to automatically send the image signal of the image seen by lens **204** to the VCU **104** when camera **102** is in use. Alternatively, once the VCU **104** is active, the VCU **104** may send a VCU present signal to the image processor **200** in camera **102**, whereupon the image processor **200** may send the image signal to the VCU **104**. When communicating with the VCU, the image processor **200** may send the image signal only to the VCU (so that the LCD **230** on camera **102** is inactive), or the image processor **200** may send the image signal to both the VCU **104** and the LCD **230**.

Similarly, the communications interface **240** allows the camera **102** to receive transmissions from the VCU **104** via the communications interface **240**. For example, signals initiated in the VCU **104** for zooming in and out, and for snapping a photo may be received wirelessly in image processor **200** via the communications interface **240**.

While interaction and communications with VCU **104** are carried out in camera **102** by image processor **200**, it is understood that image processor **200** may handle only camera functions, and interaction and communication with VCU **104** be carried out by a second processor within camera **102**. Such a second processor would cooperate and communicate with image processor **200** to communicate the image signal to VCU **104** and communicate control signals from the VCU **104** to camera **102**.

While embodiments of the invention operate according to the Bluetooth specification, it is understood that the communications interfaces in the camera **102**, VCU **104** and actuation table **114** may operate according to other wireless protocols, such as for example Wireless USB, 802.11, radio frequency (RF), infrared (IR), IrDA from the Infrared Data Association and home RF technologies. Typically, as the camera **102** is taking a picture of the person holding the VCU **104**, a clear line of sight may be established between the camera **102** and VCU **104**.

The wireless signals sent via the various communications interfaces described herein may be sent via various protocols, including pulse modulation and quadrature amplitude modulation (QAM). Other protocols are contemplated. In embodiments, a first camera **102** and VCU **104** set may be used in the presence of other camera **102** and VCU **104** sets. Therefore, in embodiments, during a configuration process, the camera **102** and VCU **104** may be tuned to each other, i.e., communications between camera **102** and VCU **104** may be tuned to a particular frequency. In embodiments, the tuning step may be omitted and communications would occur at a set frequency.

Camera **102** may further include a power source **222**, such as a rechargeable battery as is known in the art.

It is understood that not all of the conventional components necessary or optionally included for conventional operation of camera **102** are described above. Other components, known in the art, may additionally or alternatively be included in camera **102**.

VCU **104** may include a VCU processor **246** for controlling operation of the VCU **104** and for communicating with camera **102** and actuation table **114**. Processor **246** may

include any of various known configurations, and may be implemented in hardware, software (firmware) or a combination of hardware and software. The processor may have an associated read-only memory (ROM) (not shown) for storing a software operating system and other software. The processor may additionally have an associated volatile memory (not shown), such as random access memory (RAM) and/or dynamic random access memory (DRAM) to use as temporary storage during operation of the VCU **104**.

VCU Processor **246** may communicate with a user interface **248**, including pushbuttons **108-112** and **118** described above. User interface **248** may optionally include a variety of other buttons, dials, switches, etc. for controlling camera features and operation. The user interface **248** may include a mechanism for selecting a mode of operation of the camera **102**. Depending on the mode of operation selected, the VCU **104** may be used to review pictures stored on camera **102** or in memory **250** in VCU **104** (explained hereinafter), or it may be used to take pictures as explained above. A video mode may be provided such that, upon actuation of button **118** on VCU **104**, the camera **102** captures a video image which may be stored in memory **216** on camera **102** and/or memory **250** in VCU **104**. The user interface may further have mechanisms for selecting camera modes such as autofocus, manual focus, flash or no flash, etc. The user interface **248** may also cause various menu items to be displayed on the VCU LCD screen **106** for controlling camera and VCU functions, such as deleting stored photos (from camera **102** and/or VCU **104**), changing picture resolution, etc.

For the manual focus mode, the user interface **248** may further include an actuator, such as a dial, which, when rotated on VCU **104**, changes the focal length between the lens **204** and the image sensor **202** in camera **102** to focus the image. The actuator may for example be a dial mounted on a surface of VCU **104** opposite LCD screen **106**, and may be sized to emulate the size of an annular lens assembly mounted in camera **102**.

The user interface may further include a keypad for entering textual and other character information, which information may be saved with an associated image. This textual information may be used in the operation of VCU **104** or camera **102**, or may be transmitted to a remote location as explained hereinafter. The user interface may further include pointing device, such as a track ball, for controlling a cursor which may be graphically presented on LCD **106** in certain modes of operation.

In embodiments, the VCU **104** controls camera **102** to take a picture which is then stored on camera **102**. In addition to storing the image on camera **102**, the image captured by the camera **102** may also be stored on memory **250** in VCU **104**. A variety of digital memory formats may be used for this purpose. In one embodiment, memory **250** may be a removable flash memory card, such as those manufactured by SanDisk Corporation of Sunnyvale, Calif. Formats for memory **250** include, but are not limited to: built-in memory, Smart Media cards, Compact Flash cards, Memory Sticks, floppy disks, hard disks, and writable CDs and DVDs.

VCU **104** may be coupled to another device, such as a computer, to transfer data, such as photograph and video images stored on memory **250**, as well as software application programs, application program interfaces and updates. A USB connection **252** may be provided for this purpose. It is understood that other types of connections may be provided, including serial, parallel, SCSI and an IEEE 1394 ("Firewire") connections. The connection **252** may be used to connect the VCU to further devices in alternative embodiments.



As indicated above, the images received in lens **204** may be digitized and forwarded to the image processor **200**, from where the digitized image may be sent as an image signal via the communications interfaces **240, 260** to LCD **106** on VCU **104**. An LCD controller interface **254** may be provided for receiving the signal from image processor **200** and interpreting it for display on LCD **106**. LCD **106** and LCD controller **254** may be of known construction. The LCD controller interface **254** may be part of processor **246** in embodiments.

As indicated above, VCU **104** may further include a communications interface **260** that sends and receives transmissions via an antenna **256**. Actuation of the buttons **108** and **118**, as well as other mechanisms provided as part of user interface **248**, generates signals that are sent to the VCU processor **246**, which in turn forwards those signals to image processor **200** in camera **102** via the communications interfaces **260** and **240**. Similarly, actuation of the buttons **110** and **112** generates signals that are sent to the VCU processor **246**, which in turn forwards those signals to drive controller(s) **270** in actuation table **114** as explained hereinafter via the communications interfaces **260** and **280**.

Moreover, communications interface **260** may send and receive transmissions to/from components other than camera **102** and actuation table **114** in embodiments of the invention. For example, the VCU **104** may communicate with a host computer to transfer data, such as photographic and video images, as well as software such as application programs, APIs, updates, patches, etc. Communications interface **260** may also be used to communicate with other devices, such as a variety of computing devices including hand-held computers, personal digital assistants (PDAs), mobile telephones, digital cameras and other view and control units **104**. Communications interface **260** may be used to connect VCU **104** to a variety of networks, including local area networks (LANs), wide area networks (WANs) and the Internet.

Thus, in embodiments of the invention, a photographic or video image may be taken with camera **102**, and immediately thereafter sent via the communications interface **260** to a remote processing device, website, email account or other network location. Text may also be sent via the keypad of the user interface **248**.

Embodiments have been described above where communication between VCU **104**, camera **102** and actuation table **114** is done wirelessly. In a further embodiment of the invention, it is understood that the VCU **104** and camera **102**, VCU **104** and actuation table **114**, and/or camera **102** and actuation table **114** may be joined together by one or more electrical wires and/or cables. In such embodiments, transmissions between the VCU **104**, camera **102** and/or actuation table **114** may be carried out via the electrical wires and/or cables. The wires and cables may connect to connector **252** on VCU **104**.

VCU **104** may further include a power source **258**, such as a rechargeable battery as is known in the art. Moreover, VCU **104** may include a power up/power down switch (not shown) for activating and shutting down the VCU **104**.

Actuation table **114** may be used in certain embodiments of the present invention to control at least portions of a field of view of camera **102**. Signals generated by actuation of push-buttons **110, 112** are sent from the VCU processor **246** through communications interface **260** to actuation table **114** via communications interface **280** and an associated antenna **272**. Transmissions received in communication interface **280** are forwarded to drive controller(s) **270** which control the operation of the x-axis drive **158** and z-axis drive **160** explained above in a known manner.

Actuation table **114** may further include a power source **274**, such as a rechargeable battery as is known in the art.

Alternatively, the actuation table **114** may be electrically coupled to camera **102** when the camera and actuation table are affixed together. In such embodiments, the actuation table power source **274** may be omitted, and the actuation table instead receive power from the camera power source **222**.

In embodiments where actuation table **114** is electrically coupled to the camera **102**, communication interface **280** on the actuation table **114** may be omitted, and all signals for actuating actuation table **114** be received from the VCU **104** though the camera **102**. In a further alternative embodiment where actuation table **114** is electrically coupled to the camera **102**, communication interface **240** on the camera **102** may be omitted, and all signals for the camera **102** may be received from the VCU **104** though actuation table **114**.

In embodiments not including an electrical coupling of actuation table and camera **102**, all signals from VCU **104** may go first to camera **102**, which in turn forwards the signals to actuation table **114**, via the various communications interfaces. Similarly, in embodiments not including an electrical coupling of actuation table and camera **102**, all signals from VCU **104** may go first to actuation table **114**, which in turn forwards the signals to camera **102**, via the various communications interfaces.

It is understood that actuation table **114** may be omitted in alternative embodiments.

The VCU **104** may have a variety of shapes, sizes and configurations, including a display and one or more actuators for framing the field of view of an image, actuating the camera shutter, and/or performing a variety of other camera functions. VCU **104** need not be hand-held in embodiments. It may have straps and attach to a wearer's wrist, head, waist, other body parts or otherwise as an appurtenance to the wearer's body.

In operation, the VCU **104** may be held by a subject in the field of view of the camera **102**, as shown in FIG. **1**, and the VCU **104** operated to frame the camera field of view as desired (left/right pan, up/down pan, in/out zoom). Once the proper field of view is established, the subject may hide the VCU **104** or place the VCU in a pocket, or otherwise out of the field of view of the camera **102** so that the VCU **104** does not appear in the photo. A preset or user-configurable time delay may be provided so that a picture is taken a predetermined period of time after button **118** on VCU **104** is pressed. Thus, the subject would have time to locate the VCU **104** out of the field of view. The time delay may be set by the user interface **248** on the VCU **104** and/or on the user interface **220** on the camera **102**. The time delay may be omitted in alternative embodiments, and the picture taken immediately upon actuation of button **118**.

In an alternative embodiment, the VCU **104** may be held and operated by an operator who is not to be in the picture. The VCU **104** may be used for example by a photographer lining up and setting the scene of a photograph. Thus, the photographer need not walk back and forth between the subjects/subject matter of the photo and the viewfinder behind the camera.

Moreover, the present invention may be used to obtain a view from a camera not otherwise obtainable if the camera needed to be positioned at a location where the user needed see the view either through the viewfinder or on the camera LCD. That is, in conventional cameras, to obtain an image with a desired contents, the camera needs to be positioned somewhere where the user can look through the view finder or look at the LCD display. However, through the present invention, the camera may be held high with one hand, or placed on top of a wall, or otherwise positioned somewhere where the

user cannot look through the view finder or look at the camera LCD display, and the VCU held and operated in the other hand.

The VCU **104** may cooperate with camera **102** in a variety of uses in alternative embodiments. The camera **102** may be positioned in an unobtrusive or hidden position, and then operated with VCU **104**. A camera may be positioned somewhere not otherwise accessible to an operator (such as for example at off-limits to sporting, political and celebrity events), and operated with VCU **104** by an operator.

In embodiments described above, the VCU **104** may be a dedicated component for the use and operation described above. In a further embodiment described with respect to FIGS. **10-16**, VCU **104** may in fact be a conventional device configured to operate in accordance with the principals of the present invention. For example, a mobile telephone or other computing device such as a computer or PDA may be loaded with software and/or hardware allowing the device to perform as a view and control unit having all of the functionality of VCU **104** described above. In a further alternative embodiment, another digital camera may be loaded with software and/or hardware to provide the second camera with a mode where the second camera acts not as a picture taking device, but as a VCU as described above. Each of these devices may be conventional devices, but configured with hardware and/or software to provide a mode, referred to herein as VCU mode, where the device operates as a view and control unit for a camera.

FIGS. **10** through **12** illustrate an embodiment where a mobile telephone **300** is configured to operate as a view and control unit sending and receiving signals to a camera **102** as described above. Telephone **300** may have a conventional hardware configuration and may operate to perform all of the functions conventionally known for mobile telephones. Additionally, as explained hereinafter, a software application program and other software components may be loaded onto telephone **300** to allow the telephone to act as a view and control unit in accordance with the present invention.

The components of a telephone **300** for use with the present invention are known. However, some of the components are shown in the block diagram of FIG. **12** and described hereinafter. FIG. **12** also shows a camera **102** and an actuation table **114**, as described above, operating with telephone **300**. The signals transmitted to and from camera **102** and actuation table **114** may be as described above.

Telephone **300** may include a processor **302**, which may be part of or include a digital baseband and/or an analog baseband for handling digital and analog signals. As is known, processor **302** may include a variety of electronics for handling incoming and outgoing digital voice and data signals.

RF Transceiver **306** and switch **308** are provided for receiving and transmitting analog signals, such as an analog voice signal, via an antenna **310**. In embodiments, transceiver **304** performs the quadrature modulation and demodulation, as well as up- and down-conversion from dual-band (800 and 1900 MHz) RF to baseband. The various communication interfaces described herein may include a transceiver and/or switch as in transceiver **306** and switch **308**.

Telephone **300** may further include a user interface **312** including a variety of actuators in the form of buttons, dials, switches, etc. (an example shown in FIG. **11**) for controlling telephone features and operation. When used in VCU mode, at least some of these buttons, dials, switches, etc. are assigned functions for controlling camera features and operation. In embodiments, the user interface may include buttons, dials, switches, etc. that are dedicated for use within VCU mode and serve no other function. The user interface **312** may

include mechanisms for controlling most or all manner of camera features and operations, some of which have been described above with respect to user interface **248** on VCU **104**.

Telephone **300** may further include memory **314**, for storing telephone numbers, address, etc. Memory **314** may additionally store photographic or video images taken with the telephone **300**, or with camera **102** when telephone **300** is operating in VCU mode. A variety of digital memory formats may be used for this purpose. In one embodiment, memory **314** may be a removable flash memory card, such as those manufactured by SanDisk Corporation of Sunnyvale, Calif. Formats for memory **314** include, but are not limited to: built-in memory, Smart Media cards, Compact Flash cards, Memory Sticks, floppy disks, hard disks, and writeable CDs and DVDs.

Telephone **300** may further include a connection **316** for connecting telephone **300** to another device. Connection **316** may be a USB connection, but it is understood that other types of connections may be provided, including serial, parallel, SCSI and an IEEE 1394 ("Firewire") connections.

Telephone **300** may further include a camera **318** as is known in the art. Camera **318** may have some, all and/or additional components than those described above with respect to camera **102**. In the embodiments described with respect to FIGS. **10** through **12**, telephone **300** is acting as a view and control unit for controlling a camera **102**. However, as telephone **300** itself has a camera, in a further embodiment, a mobile telephone **300** may be used as a camera, which mobile telephone is controlled by a separate VCU **104**. Instead of VCU **104** in such an embodiment, the telephone camera may instead be controlled by a second telephone **300**, or other processing device configured with a VCU mode according to embodiments of the present invention. As used herein, the term "camera" may thus include a mobile telephone.

When telephone **300** is in its conventional camera mode, an image captured by a lens in the telephone is forwarded to processor **302** (or to some dedicated camera processor), which in turn displays that image on an LCD screen **320** in the telephone. An LCD controller interface **322** may be provided for receiving the signal from the processor **302** and interpreting it for display on LCD **320**. LCD **320** and LCD controller **322** may be of known construction. The LCD controller interface **322** may be part of processor **302** in embodiments.

Telephone **300** may include a speaker **330** of known construction for reproducing voice signals, as well as for outputting various ring tones, interactive voice menus and other stored or received audio files. A microphone **332** of known construction may further be provided for receiving voice signals.

Telephone **300** may further include a communication interface **340** capable of wireless communication with communication interface **240** on camera **102** and communication interface **280** on actuation table **114**, via an antenna **342**. A conventional telephone **300** may include a communication interface **340** operating according to various wireless protocols, including Bluetooth, RF and IR.

Actuation of various buttons, dials, etc. on telephone user interface shown in FIG. **11** (explained in greater detail below) generates signals that are sent to the digital processor **302**, which in turn forwards those signals to image processor **200** in camera **102** via the communications interfaces **340** and **240**. Similarly, in embodiments operating with an actuation table **114**, actuation of various buttons, dials, etc. on telephone user interface shown in FIG. **11** generates signals that are sent to the digital processor, which in turn forwards those

signals to the drive controller(s) 270 in actuation table 114 via the communications interfaces 340 and 280.

Moreover, communications interface 340 may send and receive transmissions to/from components other than camera 102 and actuation table 114 in embodiments of the invention. For example, the telephone (when in VCU mode or otherwise) may communicate with a host computer to transfer data, such as photographic and video images, as well as software such as application programs, APIs, updates, patches, etc. Communications interface 340 may also be used to communicate with other devices, such as hand-held computing devices including hand-held computers, PDAs, other mobile telephones, digital cameras and view and control units 104 according to embodiments of the invention. Communications interface 340 may be used to connect telephone 300, and camera 102, to a variety of networks, including local area networks (LANs), wide area networks (WANs) and the Internet.

Thus, in embodiments of the invention, a photographic or video image may be taken with camera 102, and immediately thereafter sent via the telephone 300 to a remote processing device, website, email account or other network location. Text may also be sent via the keypad of the user interface 312.

It is understood that telephone 300 may have a variety of other configurations and additional or alternative components in alternative embodiments of the invention.

Configuring telephone 300 to include a VCU mode will now be explained with reference to the flowchart of FIG. 13. Using components conventionally provided in telephone 300, telephone 300 may be configured to include a VCU mode for communicating with and controlling camera 102. In step 400, software enabling the VCU mode in telephone 300 is loaded in telephone 300. The software may be loaded onto telephone 300 by a variety of known methods. The software may be downloaded wirelessly via communication interface 340 or RF transceiver 306. Wireless downloading of software to telephone 300 is well known. For example, the software may be downloaded after the user dials an access telephone number. Software may alternatively be loaded from a storage medium, for example via connection 316. As a further alternative, the software may be programmed into ROM in the initial configuration of telephone 300. The software may be stored in memory 314, or some other memory associated with processor 302. As an alternative or in addition to loading software onto telephone 300, hardware such as an integrated circuit chip may be loaded into telephone 300 to provide telephone 300 with a VCU mode in accordance with the present invention.

Once the software and/or hardware are loaded onto telephone 300, no further configuration may be required to operate in VCU mode. Alternatively, the telephone may present a menu on the user interface 312 giving the user various options for configuring the operation of telephone 300 in VCU mode in step 402. Such configuration may allow the user to select which keys perform the various functions of the VCU mode. A user may also be prompted in step 404 to enter the camera model as part of the configuration process or thereafter. Certain aspects of the software may be customized for different cameras. The camera model may also be asked for earlier in the process, such as before or during the loading of the software and/or hardware onto the telephone 300.

Once loaded, the software/hardware enables the VCU mode as explained with respect to FIG. 14. The software assigns a key on user interface 312 for launching the VCU mode in step 410. Referring to an example of telephone 300 shown in FIG. 11, a camera key 350 is conventionally provided to enter the telephone camera mode. The software/

hardware may configure telephone 300 such that pressing camera key 350 once enters the telephone camera mode, but pressing the camera key 350 twice (or a predetermined number of times), launches the VCU mode. Other keys may be assigned to launch the VCU mode.

The software/hardware further assigns keys for sending signals to the actuation table 114 to pan left and right (step 412) and pan up and down (step 414) when in VCU mode. For example, the left/right and up/down arrows of circular key 352 may be used to accomplish the left/right and up/down actuation of actuation table 114 and camera 102. Other key assignments are possible for performing these functions. Similarly, the software assigns keys for sending signals to the camera 102 to zoom in and out (step 416) and for capturing an image (step 418). The software further configures menu items which may be presented when a menu in the VCU mode is selected. A variety of other key assignments may be made for performing other camera functions in the VCU mode. It is understood that the assignment of keys when in VCU mode as described above may occur when the software/hardware is loaded onto telephone 300, or when the VCU mode is launched (though the assignment of the VCU mode launch key would need to occur before VCU mode is launched).

Operation of telephone 300 will now be explained with respect to FIG. 15. Those of skill in the art would appreciate that at least some of the steps shown in FIG. 15 would also apply to operation of VCU 104 described above. The normal mode, indicated by step 440, may be any of the various modes or functions telephone 300 may perform when not in VCU mode. These modes include conversing with others, sending text messages, accessing the Internet, accessing stored contact information, etc. The software first checks for launching of the VCU mode in step 442. If no VCU mode is detected, the software returns to step 440 and continues to operate in normal mode.

If the VCU mode has been launched, the software determines whether image signals have been received from camera 102 in step 446. The processor 302 may include an internal clock, and the software may have a predetermined period of time to detect an image signal from camera 102 after launch of the VCU mode. If no signal is detected in step 446, and the predetermined period of time has not yet expired in step 448, the software returns to step 446 to see if a signal is detected. If no signal is detected in step 446, and the predetermined period of time has expired in step 448, the software displays a message in step 450, for example on LCD 320, that no camera has been detected. The software then returns telephone 300 to normal operation in step 440.

If the software detects receipt of the image signal in step 446, the software assigns the various key functions for VCU mode in step 452. If the assignments are already made, the assignments are enabled in step 452. In step 454, the digital processor switches the image feed supplied to LCD 320 from the telephone camera to the image signal received from camera 102. Thus, as shown in FIG. 11, the telephone LCD 320 would display the image seen by camera 102. In step 456, the software then performs the one or more functions selected by the user for controlling camera 102 and taking a picture with camera 102 as described above. In step 460, the software checks whether telephone 300 is still being used in VCU mode. If not, the software returns to normal mode (step 440). Otherwise, the software continues to display the image feed from camera 102 (step 454) and performs additional VCU mode functions selected by a user (step 456).

One embodiment of a telephone 300 for performing according to the present invention is shown in FIGS. 10 through 12. However, it is understood that any number of

other devices may be used for viewing an image seen by camera 102 and for controlling the image. Such devices may include a communications interface (wireless or otherwise) and a method for displaying an image seen by the camera. FIG. 16 is an illustration of a camera 102 connected to a variety of devices, including telephone 300, PDA (or hand-held computer) 470, laptop computer 472, desktop computer 474, another camera 476 and tablet computer 478. In embodiments, the camera 102 would be connected to one of these devices. However, in alternative embodiments, the camera 102 may be connected to two or more of the devices shown in FIG. 16, or multiple ones of the devices shown in FIG. 16. Other devices are contemplated. When camera 102 is connected to a second camera 476 capable of operating in VCU mode, the second camera 476 may be the same as or different than the camera 102. When the same, the operation of camera 476 in VCU mode may be the same as normal operation of the camera 476, except that operation of the various features of camera 476 controls operation of the various corresponding functions in camera 102.

Although the invention has been described in detail herein, it should be understood that the invention is not limited to the embodiments herein disclosed. Various changes, substitutions and modifications may be made thereto by those skilled in the art without departing from the spirit or scope of the invention as described and defined by the claims to be added hereinafter.

I claim:

1. A method implemented on a camera controlled by a hand-held mobile device, comprising the steps of:

- (a) transmitting, via a short range wireless signal, an image signal from the camera to the hand-held mobile device relating to an image captured by the camera;
- (b) receiving in the camera, from the hand-held mobile device via a short range wireless signal, a first instruction to change an image generated by the camera; and
- (c) receiving in the camera, from the hand-held mobile device via a short range wireless signal, a second instruction to store an image captured by the camera.

2. The method of claim 1, wherein said step (a) comprises the step of transmitting the image signal via one of the Bluetooth, Wireless USB, 802.11, short range radio frequency and infrared wireless protocols.

3. The method of claim 1, wherein said step (b) comprises the step of receiving an instruction for the camera to pan left, right, up or down.

4. The method of claim 1, wherein said step (b) comprises the step of receiving an instruction for the camera to zoom in or out.

5. The method of claim 1, wherein the image captured by the camera, corresponding to the image signal transmitted to the hand-held device, is further displayed on a display of the camera.

6. The method of claim 1, wherein the hand-held device is a mobile telephone.

7. The method of claim 6, wherein mobile telephone is a first telephone, and the camera is a second mobile telephone.

8. One or more processor readable storage devices having processor readable code embodied on said processor readable storage devices, said processor readable code for programming one or more processors of a camera to perform a method comprising the steps of:

- (a) transmitting, via a short range wireless signal, an image signal from the camera to a mobile, hand-held device relating to an image captured by the camera;
- (b) receiving in the camera, from the hand-held device via a short range wireless signal, a first instruction for the camera to change one or more of the camera settings that determine the image generated by the camera; and
- (c) receiving in the camera, from the hand-held device via a short range wireless signal, a second instruction for the camera to store the image captured by the camera.

9. The method of claim 8, wherein said steps (b) and (c) comprise the steps of receiving via one of the Bluetooth, Wireless USB, 802.11, short range radio frequency and infrared wireless protocols.

10. The method of claim 8, wherein said step (b) comprises the step of communicating an instruction to the camera to pan left, right, up or down.

11. The method of claim 8, wherein said step (b) comprises the step of communicating an instruction to the camera to zoom in or out.

12. The method of claim 8, wherein the hand-held mobile device is a mobile telephone, the method further comprising the step of assigning a function to one or more of the keys of the phone for the one or more keys of the phone to perform one of steps (b) or (c) when actuated.

13. One or more processor readable storage devices having processor readable code embodied on said processor readable storage devices, said processor readable code for programming one or more processors of a first mobile telephone to perform a method comprising the steps of:

- (a) transmitting, via a short range wireless signal, an image signal from a camera of the first mobile telephone to a second mobile telephone relating to an image captured by the camera;
- (b) receiving in the camera, from the second mobile telephone via a short range wireless signal, an instruction for the camera to perform at least one of the steps of panning left, right, up or down and zooming in or out; and
- (c) receiving in the camera, from the second mobile telephone via a short range wireless signal, a second instruction for the camera to store the image captured by the camera.

14. The method of claim 13, wherein said step (a) comprises the step of transmitting a video signal.

15. The method of claim 12, wherein said steps (b) and (c) comprise the steps of communicating via one of including one of the Bluetooth, Wireless USB, 802.11, short range radio frequency and infrared wireless protocols.

\* \* \* \* \*