

US008435133B2

(12) **United States Patent**
Huang

(10) **Patent No.:** **US 8,435,133 B2**
(45) **Date of Patent:** **May 7, 2013**

(54) **PANEL GRIP WITH CUT-OUTS AND INSERTS**

(76) Inventor: **Ben Huang**, Huntington Beach, CA
(US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 952 days.

(21) Appl. No.: **12/511,033**

(22) Filed: **Jul. 28, 2009**

(65) **Prior Publication Data**

US 2010/0022322 A1 Jan. 28, 2010

Related U.S. Application Data

(63) Continuation of application No. 11/417,623, filed on May 3, 2006, now Pat. No. 7,566,375.

(60) Provisional application No. 60/762,364, filed on Jan. 25, 2006.

(51) **Int. Cl.**
A63B 53/14 (2006.01)

(52) **U.S. Cl.**
USPC **473/300**

(58) **Field of Classification Search** 473/300-303, 473/201, 568; D21/756; D8/DIG. 6, DIG. 7, D8/DIG. 8; 16/421, 430, DIG. 18; 156/187, 156/293, 256; 43/18.1 R, 23

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

571,025 A 11/1896 Spamer
834,711 A 10/1906 Clarke et al.
979,266 A 12/1910 Dean

1,008,604 A 11/1911 Lake
1,017,565 A 2/1912 Lard
1,139,843 A 5/1915 Brown
1,345,505 A 7/1920 Persons
1,435,088 A 11/1922 Smith
1,480,056 A 1/1924 Flint
1,522,635 A 1/1924 Kraeuter
1,528,190 A 3/1925 Howe
1,617,972 A 2/1927 Wallace
1,701,856 A 2/1929 Kraeuter
1,890,037 A 11/1930 Johnson
1,943,399 A 1/1934 Smith
2,000,295 A 5/1935 Oldham
2,086,062 A 7/1937 Bray
2,103,889 A 12/1937 Brisick
2,115,119 A 4/1938 Park
2,149,911 A 3/1939 East

(Continued)

FOREIGN PATENT DOCUMENTS

CN 2090283 12/1991
CN 2139008 Y 7/1993

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 13/208,297, filed Aug. 11, 2011, pending.


(Continued)

Primary Examiner — Stephen L. Blau
(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson & Bear, LLP

(57) **ABSTRACT**

A grip for the handle of an article having at least a sheet with a cut-out and an insert. The insert is positioned within or against the cut-out of the sheet to define a panel. The panel is then attached to an underlisting sleeve. The grip allows the use of multiple color panels and inserts and the placement of various materials in various grip areas.

13 Claims, 15 Drawing Sheets



U.S. PATENT DOCUMENTS							
2,206,056	A	7/1940	Sheesley	5,671,923	A	9/1997	Huang
2,221,421	A	11/1940	Curry	5,690,566	A	11/1997	Bracho
2,225,839	A	12/1940	Moore	5,695,418	A	12/1997	Huang
2,449,575	A	9/1948	Wilhelm	5,730,662	A	3/1998	Rens
2,523,637	A	9/1950	Stanfield et al.	5,730,669	A	3/1998	Huang
2,671,660	A	3/1954	Goodwin	5,753,568	A	5/1998	Shimano et al.
2,690,338	A	9/1954	Brocke	5,772,524	A	6/1998	Huang
2,772,090	A	11/1956	Brandon	5,781,963	A	7/1998	Maru et al.
2,934,285	A	4/1960	Niehaus	5,797,813	A	8/1998	Huang
2,984,486	A	5/1961	Jones	5,803,828	A	9/1998	Huang
3,028,283	A	4/1962	Lundgren et al.	5,813,921	A	9/1998	Huang
3,059,816	A	10/1962	Goldstein	5,816,933	A	10/1998	Huang
3,073,055	A	1/1963	Edwards et al.	5,816,934	A	10/1998	Huang
3,087,729	A	4/1963	Sullivan	5,827,129	A	10/1998	Huang
3,095,198	A	6/1963	Gasche	5,839,983	A	11/1998	Kramer
3,140,873	A	7/1964	Goodwin	5,851,632	A	12/1998	Chen et al.
3,157,723	A	11/1964	Hochberg	5,857,929	A	1/1999	Huang
3,252,706	A	5/1966	Rosasco, Sr.	5,867,868	A	2/1999	Ward
3,311,375	A	3/1967	Onions	5,890,260	A	4/1999	Gaunt
3,366,384	A	1/1968	Lamkin et al.	5,890,972	A	4/1999	Huang
3,368,811	A	2/1968	Finney	5,895,329	A	4/1999	Huang
3,503,784	A	3/1970	Okayama et al.	5,910,054	A	6/1999	Huang
3,606,325	A	9/1971	Lamkin et al.	5,924,941	A	7/1999	Hagey
3,697,315	A	10/1972	Mine	5,997,421	A	12/1999	Huang
3,857,745	A	12/1974	Grausch et al.	6,036,607	A	3/2000	Finegan
3,876,320	A	4/1975	Phillipson	6,048,275	A	4/2000	Gedeon
3,922,402	A	11/1975	Shimamura et al.	6,148,482	A	11/2000	Maraman, Jr.
3,973,348	A	8/1976	Shell	6,197,392	B1	3/2001	Jones
3,992,021	A	11/1976	Tobin	6,226,836	B1	5/2001	Yasui
4,012,039	A	3/1977	Yerke	6,244,975	B1	6/2001	Huang
4,015,851	A	4/1977	Pennell	6,261,191	B1	7/2001	Chen
4,052,061	A	10/1977	Stewart	6,314,617	B1	11/2001	Hastings
4,133,529	A	1/1979	Gambino	6,360,475	B1	3/2002	Lepage et al.
4,137,360	A	1/1979	Reischl	6,361,450	B1	3/2002	Huang
4,216,251	A	8/1980	Nishimura et al.	6,386,989	B1	5/2002	Huang
4,284,275	A	8/1981	Fletcher	D463,520	S	9/2002	Ulrich
4,347,280	A	8/1982	Lau et al.	6,449,803	B1	9/2002	McConchie
4,358,499	A	11/1982	Hill	6,503,153	B2	1/2003	Wang
4,373,718	A	2/1983	Schmidt	6,506,128	B1	1/2003	Bloom, Jr.
4,448,922	A	5/1984	McCartney	6,511,732	B1	1/2003	Chao
4,453,332	A	6/1984	Wightman	6,551,198	B2	4/2003	Huang
4,535,649	A	8/1985	Stahel	6,558,270	B2	5/2003	Kwitek
4,582,459	A	4/1986	Benit	6,627,027	B2	9/2003	Huang
4,613,537	A	9/1986	Krüpper	6,629,382	B2	10/2003	Irrgang et al.
4,651,991	A	3/1987	McDuff	6,629,901	B2	10/2003	Huang
4,662,415	A	5/1987	Proutt	6,635,688	B2	10/2003	Simpson
4,765,856	A	8/1988	Doubt	6,652,398	B2	11/2003	Falone et al.
4,878,667	A	11/1989	Tosti	6,656,054	B2	12/2003	Ulrich
4,919,420	A	4/1990	Sato	6,656,057	B2	12/2003	Manual et al.
4,941,232	A	7/1990	Decker et al.	6,663,500	B2	12/2003	Huang
4,971,837	A	11/1990	Martz et al.	6,666,777	B1	12/2003	Lamkin et al.
5,024,866	A	6/1991	Goode	6,676,534	B2	1/2004	Huang
5,055,340	A	10/1991	Matsumura et al.	6,695,713	B2	2/2004	Huang
5,118,107	A	6/1992	Bucher	6,709,346	B1	3/2004	Wang
5,123,646	A	6/1992	Overby et al.	6,733,401	B1	5/2004	Huang
5,127,650	A	7/1992	Schneller	6,762,243	B2	7/2004	Stender et al.
5,261,665	A	11/1993	Downey	6,827,656	B1	12/2004	Hoefflich et al.
5,322,290	A	6/1994	Minami	6,843,732	B1	1/2005	Huang
5,343,776	A	9/1994	Falco	6,857,971	B2	2/2005	Huang
5,374,059	A	12/1994	Huang	6,908,400	B2	6/2005	Chu et al.
5,396,727	A	3/1995	Furuya et al.	6,973,750	B1	12/2005	Kim
5,427,376	A	6/1995	Cummings et al.	6,974,626	B2	12/2005	Horacek
5,469,601	A	11/1995	Jackson	7,008,582	B2	3/2006	Chen
5,474,802	A	12/1995	Shimoda et al.	7,025,690	B2	4/2006	Nam
5,480,146	A	1/1996	Comer	7,048,644	B2	5/2006	Wang
5,485,996	A	1/1996	Niksich	7,137,904	B2	11/2006	Huang
5,511,445	A	4/1996	Hildebrandt	7,140,973	B2	11/2006	Rohrer
5,537,773	A	7/1996	Matsubara et al.	D534,602	S	1/2007	Norton et al.
5,570,884	A	11/1996	Carps	D534,603	S	1/2007	Norton et al.
5,571,050	A	11/1996	Huang	D534,604	S	1/2007	Norton et al.
5,577,722	A	11/1996	Glassberg	D534,605	S	1/2007	Norton et al.
5,584,482	A	12/1996	Huang	D534,607	S	1/2007	Norton et al.
5,595,544	A	1/1997	Roelke	D534,975	S	1/2007	Norton et al.
5,611,533	A	3/1997	Williams	D536,048	S	1/2007	Chen
5,624,116	A	4/1997	Yeh	D538,868	S	3/2007	Norton et al.
5,626,527	A	5/1997	Eberlein	D538,869	S	3/2007	Wang et al.
5,634,859	A	6/1997	Nesbitt	7,186,189	B2	3/2007	Huang
5,645,501	A	7/1997	Huang	7,195,568	B2	3/2007	Huang
				7,219,395	B2	5/2007	Bigolin

7,344,447	B2	3/2008	Chang	U.S. Appl. No. 13/526,323, filed Jun. 18, 2012, pending.
7,344,448	B2	3/2008	Huang	U.S. Appl. No. 29/436,610, filed Nov. 7, 2012, pending.
7,347,792	B2	3/2008	Huang	European Search Report, European Application No. EP 06254204.8 dated Jun. 5, 2007.
7,374,498	B2	5/2008	Huang	The Random House College Dictionary, Revised Edition, 1975, p. 1233, definition of skive.
7,404,770	B2	7/2008	Huang	U.S. Appl. No. 10/167,216, filed Jun. 11, 2002, now U.S. Patent No. 7,137,904, issued Nov. 21, 2006.
7,438,646	B2	10/2008	Huang	U.S. Appl. No. 10/348,389, filed Jan. 21, 2003, now U.S. Patent No. 6,733,401, issued May 11, 2004.
7,448,957	B2	11/2008	Huang	U.S. Appl. No. 10/392,480, filed Mar. 18, 2003, now U.S. Patent No. 6,857,971, issued Feb. 22, 2005.
7,448,958	B2	11/2008	Huang	U.S. Appl. No. 10/746,764, filed Dec. 23, 2003, now U.S. Patent No. 6,843,732, issued Jan. 18, 2005.
7,458,903	B2	12/2008	Wang et al.	U.S. Appl. No. 10/608,598, filed Jun. 27, 2003, (U.S. Pub. No. 2004-0266546 A1), abandoned.
7,470,199	B2	12/2008	Huang	U.S. Appl. No. 10/785,379, filed Feb. 24, 2004, now U.S. Patent No. 7,374,498, issued May 20, 2008.
7,491,133	B2	2/2009	Huang	U.S. Appl. No. 10/827,095, filed Apr. 19, 2004, now U.S. Patent No. 7,195,568, issued Mar. 27, 2007.
7,527,564	B2	5/2009	Huang	U.S. Appl. No. 10/875,035, filed Jun. 23, 2004, now U.S. Patent No. 7,585,230, issued Sep. 8, 2009.
7,566,375	B2	7/2009	Huang	U.S. Appl. No. 11/029,328, filed Jan. 5, 2005, (U.S. Pub. No. 2005-0148401 A1), abandoned.
7,585,230	B2	9/2009	Huang	U.S. Appl. No. 11/062,046, filed Feb. 18, 2005, now U.S. Patent No. 7,470,199, issued Dec. 30, 2008.
7,770,321	B2	8/2010	Huang	U.S. Appl. No. 11/131,832, filed May 18, 2005, now U.S. Patent No. 7,527,564, issued May 5, 2009.
2002/0028264	A1	3/2002	Hoopman et al.	U.S. Appl. No. 11/172,770, filed Jul. 1, 2005, now U.S. Patent No. 7,186,189, issued Mar. 6, 2007.
2002/0028325	A1	3/2002	Simpson	U.S. Appl. No. 11/412,196, filed Apr. 25, 2006, (U.S. Pub. No. 2006-0264268 A1), abandoned.
2002/0142858	A1	10/2002	Chen	U.S. Appl. No. 11/416,364, filed May 1, 2006, now U.S. Patent No. 7,438,646, issued Oct. 21, 2008.
2002/0142900	A1	10/2002	Wang	U.S. Appl. No. 12/425,187, filed Apr. 16, 2009, (U.S. Pub. No. 2009-0258722 A1), abandoned.
2002/0151373	A1	10/2002	Beauregard	U.S. Appl. No. 11/413,411, filed Apr. 28, 2006, now U.S. Patent No. 7,344,448, issued Mar. 18, 2008.
2002/0173371	A1	11/2002	Lamkin et al.	U.S. Appl. No. 11/438,808, filed May 22, 2006, now U.S. Patent No. 7,347,792, issued Mar. 25, 2008.
2003/0040384	A1	2/2003	Falone et al.	U.S. Appl. No. 11/417,643, filed May 3, 2006, now U.S. Patent No. 7,448,957, issued Nov. 11, 2008.
2003/0045370	A1	3/2003	Jaw	U.S. Appl. No. 11/417,623, filed May 3, 2006, now U.S. Patent No. 7,566,375, issued Jul. 28, 2009.
2003/0062654	A1	4/2003	Lamkin	U.S. Appl. No. 11/417,555, filed May 3, 2006, now U.S. Patent No. 7,404,770, issued Jul. 29, 2008.
2003/0139223	A1	7/2003	Ulrich et al.	U.S. Appl. No. 11/417,401, filed May 3, 2006, now U.S. Patent No. 7,491,133, issued Feb. 17, 2009.
2003/0148836	A1	8/2003	Falone et al.	U.S. Appl. No. 11/682,264, filed Mar. 5, 2007, (U.S. Pub. No. 2007-0149307 A1), pending.
2003/0150081	A1	8/2003	Wang	U.S. Appl. No. 11/417,696, filed Mar. 5, 2006, now U.S. Patent No. 7,448,958, issued Nov. 11, 2008.
2003/0216192	A1	11/2003	Chu	U.S. Appl. No. 12/045,639, filed Mar. 10, 2008, (U.S. Pub. No. 2008-0229646 A1), pending.
2003/0228930	A1	12/2003	Huang	U.S. Appl. No. 11/689,452, filed Mar. 21, 2007, (U.S. Pub. No. 2008-0230174 A1), pending.
2004/0029645	A1	2/2004	Chen	U.S. Appl. No. 12/123,384, filed May 19, 2008, (U.S. Pub. No. 2008-0283178 A1), pending.
2004/0029646	A1	2/2004	Chu et al.	U.S. Appl. No. 11/838,670, filed Aug. 14, 2007, (U.S. Pub. No. 2009-0048036 A1), pending.
2004/0031128	A1	2/2004	Chen	U.S. Appl. No. 12/055,289, filed Mar. 25, 2008, (U.S. Pub. No. 2009-0025852 A1), pending.
2004/0109980	A1	6/2004	Chen et al.	U.S. Appl. No. 12/426,896, filed Apr. 20, 2009, (U.S. Pub. No. 2009-0258721 A1), pending.
2004/0123429	A1	7/2004	Wang	U.S. Appl. No. 12/753,804, filed Apr. 2, 2010, pending.
2004/0185958	A1	9/2004	Huang	U.S. Appl. No. 12/753,669, filed Apr. 2, 2010, pending.
2004/0248664	A1	12/2004	Billings	U.S. Appl. No. 12/753,799, filed Apr. 2, 2010, pending.
2005/0123723	A1	6/2005	Wang	U.S. Appl. No. 12/753,773, filed Apr. 2, 2010, pending.
2005/0229285	A1	10/2005	Chung	U.S. Appl. No. 12/767,736, filed Apr. 26, 2010, pending.
2005/0276925	A1	12/2005	Su	U.S. Appl. No. 12/848,052, filed Jul. 30, 2010, pending.
2005/0287329	A1	12/2005	Lai	U.S. Appl. No. 12/862,673, filed Aug. 24, 2010, pending.
2006/0172815	A1	8/2006	Chu	U.S. Appl. No. 12/948,637, filed Nov. 17, 2010, pending.
2006/0252571	A1	11/2006	Wang	U.S. Appl. No. 12/960,261, filed Dec. 3, 2010, pending.
2006/0287123	A1	12/2006	Wang	
2007/0149307	A1	6/2007	Huang	
2008/0039226	A1	2/2008	Chi	
2008/0120893	A1	5/2008	Keys et al.	
2008/0172839	A1	7/2008	Wang	


FOREIGN PATENT DOCUMENTS

CN	2163667	Y	5/1994	
CN	2288744		8/1998	
CN	1332022	A	7/2000	
CN	2438768		7/2001	
CN	2444645		8/2001	
CN	ZL 02254450.X		9/2002	
CN	2596752		1/2004	
CN	2659497		12/2004	
DE	36 44 674	A1	7/1988	
DE	92 18 550	U1	8/1994	
FR	2 731 402	A3	9/1996	
GB	2 192 550	A	1/1988	
JP	53-12061		2/1978	
JP	55-43008		3/1980	
JP	60-61067		4/1985	
JP	3112575		5/1991	
JP	7-41731		2/1995	
JP	3076015		12/2000	
JP	3081404		8/2001	
JP	2002-028264		1/2002	

OTHER PUBLICATIONS

A. Zosel, Adhesion and tack of polymers: Influence of mechanical properties and surface tension, *Colloid & Polymer Science* 263:541-553 (1985) in 13 pages.
 U.S. Appl. No. 09/901,747, filed Jul. 9, 2001, (U.S. Pub. No. 2001/0046905), abandoned.
 U.S. Appl. No. 13/403,764, filed Feb. 23, 2012, pending.
 U.S. Appl. No. 29/416,672, filed Mar. 26, 2012, pending.

U.S. Appl. No. 12/753,804, filed Apr. 2, 2010, pending.
 U.S. Appl. No. 12/753,669, filed Apr. 2, 2010, pending.
 U.S. Appl. No. 12/753,799, filed Apr. 2, 2010, pending.
 U.S. Appl. No. 12/753,773, filed Apr. 2, 2010, pending.
 U.S. Appl. No. 12/767,736, filed Apr. 26, 2010, pending.
 U.S. Appl. No. 12/848,052, filed Jul. 30, 2010, pending.
 U.S. Appl. No. 12/862,673, filed Aug. 24, 2010, pending.
 U.S. Appl. No. 12/948,637, filed Nov. 17, 2010, pending.
 U.S. Appl. No. 12/960,261, filed Dec. 3, 2010, pending.






FIG. 2

FIG. 3




FIG. 4









FIG. 5










FIG. 10




FIG. 12




FIG. 11









FIG. 13






FIG. 20




FIG. 21




FIG. 22

FIG. 23




FIG. 24




FIG. 25









FIG. 26

FIG. 27








FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36

FIG.37




FIG.38



FIG. 39




FIG. 40





FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45





FIG. 46



PANEL GRIP WITH CUT-OUTS AND INSERTS

RELATED U.S. APPLICATION DATA

This application is a continuation application of U.S. application Ser. No. 11/417,623, filed May 3, 2006, now U.S. Pat. No. 7,566,375, which claims the benefit of U.S. Provisional Application No. 60/762,364, filed Jan. 25, 2006.

INCORPORATION BY REFERENCE

This application hereby incorporates by reference U.S. patent application Ser. No. 11/172,770, filed Jul. 1, 2005, pending, U.S. Pat. Nos. 6,244,975, 6,627,027, 6,695,713, 6,843,732, 6,857,971, and 7,566,375, and U.S. Provisional Application No. 60/762,364, filed Jan. 25, 2006, each in its entirety.

BACKGROUND OF THE INVENTION

1. Field of the Invention

This application relates to an improved grip for shafts. In particular, this application relates to an improved grip for the shafts of golf clubs.

2. Description of the Related Art

Applicant has previously developed resilient grips which successfully reduce impact shock to the muscle and arm joints of the users of golf clubs and also provide a feeling of tackiness between the player's hands and the grip. See, for example, U.S. Pat. No. 5,797,813 granted to Applicant on Aug. 25, 1998, U.S. Pat. No. 6,843,732 granted to Applicant on Jan. 18, 2005, and U.S. Pat. No. 6,857,971 granted to Applicant on Feb. 22, 2005.

The earliest of these grips utilize a polyurethane-felt strip which is spirally wrapped around an underlisting sleeve that is slipped onto and adhered to a golf club shaft. The sides of the strips are formed with overlapping heat depressed recessed reinforcement edges. While such grips have proven satisfactory in reducing impact shock, the fabrication is labor intensive, particularly since the strip must be wrapped manually about the underlisting sleeve within specific pressure parameters. Additionally, it is difficult to accurately align the adjoining side edges of the strip as such strip is being spirally wrapped about the underlisting sleeve. These wrapped grips can become twisted during the wrapping process, allow for only limited display of decorative designs, and allow for only a limited placement of colors.

Applicant's U.S. Pat. No. 6,857,971 sought to overcome two of the aforementioned disadvantages of existing spirally wrapped grips while providing the same resistance to shock afforded by such grips, as well as providing tackiness. Specifically, this patent discloses forming a structurally integral grip from a single polyurethane-felt panel having a configuration corresponding to the exterior shape of an underlisting sleeve. While this design removes the twisting problems associated with the wrapping process and offers more area to display decorative designs, it is limited in its ability to accommodate multiple color schemes which are so popular in today's modern world of golf.

Applicant's U.S. Pat. No. 6,843,732 sought to overcome the aforementioned disadvantages while still providing tackiness by incorporating multiple initially distinct two layer panels. Such a design allows grips made according to the teachings of U.S. Pat. No. 6,843,732 to accommodate multiple color combinations that would not have been possible with the single panel grips or the spirally wrapped grips of old.

While such grips have continued to prove satisfactory in reducing impact shock, they allow for only limited display of decorative designs and limited placement of colors.

SUMMARY OF THE INVENTION

Embodiments of the golf club grip of the present invention overcome the aforementioned disadvantages of existing spirally wrapped grips and the single panel grips while providing the same resistance to shock afforded by such grips, as well as providing tackiness. Desirably, a structurally integral grip is formed from at least a sheet with a cut-out and an insert.

One embodiment is a grip for use on the shaft of a golf club, including a preferably resilient underlisting sleeve and a panel with an outer surface, a first portion defining an outer surface and circumscribing a cut-out, and an insert positioned within the cut-out. The insert includes an outer surface. The outer surface of the panel includes the outer surface of the first portion and the outer surface of the insert. The panel is attached to the underlisting sleeve such that the outer surface of the panel defines an outer surface of the grip.

In some embodiments, the insert and the panel each include different durometer materials or colors.

In some embodiments, the panel includes a top side, a bottom side, a first substantially vertical side, and a second substantially vertical side. The panel is preferably wrapped about the underlisting sleeve such that the first and second sides join to form a substantially vertical seam. Though not required, the first and second vertical sides may be skived. In some embodiments, the sides are skived parallel to each other. In other embodiments, the sides are skived anti-parallel to each other. The skived sides may abut each other and/or overlap each other. The panel may include a friction enhancing pattern on its outer surface. The intersections between portions of the panel may include one or more adhesives.

Another embodiment is a grip for use on the shaft of a golf club, including a preferably resilient underlisting sleeve and a panel including a cut-out and an insert abutting the cut-out. The panel also preferably includes a recessed channel along at least a portion of the intersection between the cut-out and the insert. The panel is preferably attached to the underlisting sleeve. In some embodiments, the channel is melted and may include a deposit of polyurethane.

Another embodiment is a method of making a grip for use on the shaft of a golf club comprising the steps of: providing a resilient underlisting sleeve; providing a sheet comprising an outer surface; forming a cut-out in the sheet so that the sheet includes a first portion circumscribing the cut-out; providing an insert comprising an outer surface; positioning the insert within the cut-out; attaching the sheet to the underlisting sleeve such that the outer surface of the sheet defines a portion of the outer surface of the grip; and attaching the insert to the underlisting sleeve such that the outer surface of the insert defines a portion of the outer surface of the grip. The method may also include joining the sheet and the insert to form a panel and attaching the panel to the underlisting sleeve to attach the sheet and the insert to the underlisting sleeve.

Yet another embodiment is a method of making a grip for use on the shaft of a golf club comprising the steps of: providing a resilient underlisting sleeve; providing a sheet; forming a cut-out in the sheet; providing an insert; positioning the insert such that it abuts the cut-out; forming a recessed channel along at least a portion of the intersection between the cut-out and the insert; attaching the sheet to the underlisting sleeve; and attaching the insert to the underlisting sleeve. The method may also include joining the sheet and the insert to

form a panel and attaching the panel to the underlisting sleeve to attach the sheet and the insert to the underlisting sleeve.

Another embodiment is a method of making a grip for use on the shaft of a golf club comprising the steps of: providing a resilient underlisting sleeve; providing a first backing sheet; providing a second sheet; forming a cut-out in the second sheet; providing an insert; arranging the second sheet and the insert on the first backing sheet; joining the second sheet and the insert along the intersection of the cut-out and the insert to define a panel; removing the backing sheet; and attaching the panel to the underlisting sleeve.

Other embodiments include a grip and a method of making a grip for use with other impact imparting implements, including, but not limited to, tennis rackets, polo clubs, hockey sticks, badminton rackets, hammers, and the like. Further, such grips could also be adapted for use with other handles that are grasped by a user's hand wherein the features of the herein described invention could be useful and beneficial, including bicycle grips, walking sticks, tow rope handles for use with wakeboarding, water skiing, and the like, and other types of handles.

Embodiments of the present invention may be manufactured at considerably less cost than existing spirally wrapped grips since it eliminates the intensive labor of spirally wrapping a strip around an underlisting sleeve within specific pressure parameters. Additionally, embodiments should not twist either during manufacture or after it is adhered to an underlisting sleeve. My new grip desirably has an appearance similar to conventional molded rubber grips so as to appeal to professional golfers and low-handicap amateurs, and also provides a greater area for the application of decorative designs. Further, embodiments of the present invention can also accommodate multiple color combinations, thus appealing to golfers and college programs who wish to display their school colors while playing the sport they love. Embodiments of the present invention are easy to install. Furthermore, embodiments of the present invention allow us to place various materials in various grip areas. For example, one or more different materials can be used where there is more expected contact between the user's hand and the grip, such as where the base of the hand in the palm area contacts the grip or where the pads of the fingers contact the grip. The choice of materials can be made to adjust various parameters of the grip, such as tackiness, feel, and/or durability.

BRIEF DESCRIPTION OF THE DRAWINGS

Further objects, features, and advantages of the invention will become apparent from the following detailed description taken in conjunction with the accompanying figures showing illustrative embodiments of the invention, in which:

FIG. 1 is a front rear view of a first sheet and inserts used in a panel grip according to one embodiment;

FIG. 2 is a horizontal cross-sectional view taken along the line designated 2-2 in FIG. 1;

FIG. 3 is an enlarged view of the encircled area designated 3 in FIG. 2;

FIG. 4 is a front view of a backing sheet used in a panel grip according to one embodiment;

FIG. 5 is a horizontal cross-sectional view taken along the line designated 5-5 in FIG. 4;

FIG. 6 is a perspective view of a first sheet and inserts being coupled to a backing sheet according to one embodiment;

FIG. 7 is a perspective view of a panel according to one embodiment;

FIG. 8 is a horizontal cross-sectional view taken along the line designated 8-8 in FIG. 7;

FIG. 9 is an enlarged view of the encircled area designated 9 in FIG. 8;

FIG. 10 is a horizontal cross-sectional view showing a mold which may be utilized in forming a panel member of a panel grip according to one embodiment;

FIG. 11 is an enlarged view of the encircled area designated 11 in FIG. 10;

FIG. 12 is an enlarged view of a pattern that may be formed by the mold shown in FIGS. 10 and 11;

FIG. 13 is a front view of a panel member of a panel grip according to one embodiment;

FIG. 14 is an enlarged view of the encircled area designated 14 in FIG. 13;

FIG. 15 is a horizontal cross-sectional view taken along the line designated 15-15 in FIG. 14;

FIG. 16 is a horizontal cross-sectional view of a panel member of a panel grip during a step according to one embodiment;

FIG. 17 is a side view showing a first longitudinal side of a panel member being skived according to one embodiment;

FIG. 18 is a side view showing a second longitudinal side of a panel member being skived parallel to the first side according to one embodiment;

FIG. 19 is a side view showing the top and bottom sides of a panel member of one embodiment being skived anti-parallel to each other;

FIG. 20 is a front view of an underlisting sleeve member of a panel grip according to one embodiment;

FIG. 21 is a vertical cross-sectional view taken along the line designated 21-21 in FIG. 20;

FIG. 22 is an enlarged view of the encircled area designated 22 in FIG. 21;

FIG. 23 is an enlarged view of the encircled area designated 23 in FIG. 21;

FIG. 24 is a rear view showing adhesive being applied to a panel member of a panel grip according to one embodiment;

FIG. 25 is a front view showing adhesive being applied to the exterior of an underlisting sleeve according to one embodiment;

FIG. 26 is a rear view showing a panel member being coupled to an underlisting sleeve according to one embodiment;

FIG. 27 is a rear view of showing another step in a panel member being coupled to an underlisting sleeve according to one embodiment;

FIG. 28 is a rear view of a panel member coupled to an underlisting sleeve according to one embodiment;

FIG. 29 is a cross-sectional view taken along the line designated 29-29 in FIG. 26;

FIG. 30 is a cross-sectional view taken along the line designated 30-30 in FIG. 27;

FIG. 31 is a cross-sectional view taken along the line designated 31-31 in FIG. 28;

FIG. 32 is an enlarged view of the encircled area designated 32 in FIG. 28;

FIG. 33 is an enlarged view of the encircled area designated 33 in FIG. 28;

FIG. 34 is a horizontal side view showing a mold which may be utilized in forming a panel grip according to one embodiment;

FIG. 35 is a vertical cross-sectional view taken along the line designated 35-35 in FIG. 34;

FIG. 36 is an enlarged view of the encircled area designated 36 in FIG. 35;

FIG. 37 is a front view of a panel grip according to one embodiment;

5

FIG. 38 is a side view of a panel grip according to one embodiment;

FIG. 39 is a perspective front view of an underlisting sleeve member of a panel grip according to one embodiment;

FIG. 40 is a side view of the underlisting sleeve shown in FIG. 39;

FIG. 41 is a cross-sectional view taken along the line designated 41-41 in FIG. 39;

FIG. 42 is a vertical cross-sectional view taken along the line designated 42-42 in FIG. 40;

FIG. 43 is a vertical cross-sectional view taken along the line designated 43-43 in FIG. 40;

FIG. 44 is a perspective front view of a grip according to one embodiment;

FIG. 45 is a rear view of the grip shown in FIG. 44;

FIG. 46 is a cross-sectional view taken along the line designated 46-46 in FIG. 44;

FIG. 47 is a perspective view of a golf club provided with a panel grip according to one embodiment;

FIG. 48 is a perspective view of a golf club provided with a panel grip according to one embodiment.

Throughout the figures, similar reference numerals and characters are generally used to denote like features, elements, components, or portions of the illustrated embodiments. Moreover, while the subject invention will now be described in detail with reference to the figures, it is done so in connection with the illustrative embodiments. It is intended that changes and modifications can be made to the described embodiments without departing from the true scope and spirit of the subject invention as defined by the appended claims.

DETAILED DESCRIPTION

Referring to the drawings, in FIG. 47, a panel grip G embodying the present invention is shown attached the shaft SC of a golf club C. In FIG. 48, a putter grip PG embodying the present invention is shown attached to the shaft SP of a putter PC. Referring now to the remaining drawings, a grip includes a sheet coupled to an insert to form a panel which is then wrapped about and coupled to a resilient underlisting sleeve of a conventional construction. Throughout the application, the term top is used to refer to that which is closest to the bottom end of the club opposite the club head, i.e. the end closest to the golfer if that golfer were to be swinging or stroking the club. Similarly, the term bottom is used to define that which is furthest from the butt end of the club.

Grip G preferably includes a panel P (FIG. 13) and an underlisting sleeve U (FIG. 20). As shown in FIG. 1, panel P includes a first sheet 2 and one or more inserts (32, 34, 36, 38, 40). In the illustrated embodiment, a first portion of sheet 2 circumscribes a cutout 12. A second portion of sheet 2 defines a first side cutout 14. A third portion of sheet 2 defines a second side cutout 16. A fourth portion of sheet 2 defines a top cutout 18. Finally, in the illustrated embodiment, a fifth portion of sheet 2 defines a bottom cutout 20. The sheet, including each of the portions of the sheet, defines an outer surface.

Inserts 32, 34, 36, 38, 40 are shaped to correspond with cutouts 12, 14, 16, 18, 20, respectively. Each of the inserts defines an outer surface. The outer surface of the grip desirably comprises the outer surface of the sheet and the outer surfaces of the inserts. Notches 56 and 58 define the midline of the finished panel P. These notches, or other centering indicia, are used to arrange the panel P on the underlisting sleeve U, as explained in other applications and issued patents incorporated herein in their entireties, such as, for example, U.S. Pat. No. 6,843,732, issued on Jan. 18, 2005.

6

Referring to FIG. 14, panel P preferably includes an off-set symmetrical sheet and cutout arrangement. A symmetrical arrangement would be an arrangement of the sheet and cutouts such that a line drawn through the centering notches 56 and 58 would divide the panel P into two equal, or symmetrical, halves. In the illustrated off-set symmetrical arrangement, one side is extended further than the other. In FIG. 1, the left hand side of sheet 2 and inserts 34, 38, and 40 extend further to the left. This off-set is useful to accommodate parallel skived or cut sides as is described in greater detail in U.S. Pat. No. 6,843,732. Once the left side of the panel P is skived, the portion of the panel which defines the outer surface of the grip will preferably be generally symmetrical.

Panel P is formed by coupling a first sheet 2 and one or more inserts 32, 34, 36, 38, 40. In the illustrated embodiment, sheet 2 and the inserts 32, 34, 36, 38, 40 are shaped such that when brought into mating contact, the combination thereof substantially forms the panel P. The panel P is preferably sized to generally correspond to the outer surface area of the underlisting sleeve U. In other embodiments, the sheet and inserts are coupled together and subsequently die cut or otherwise further manipulated such that they ultimately form a panel P that generally corresponds to the outer surface area of the underlisting sleeve U. Formation of such inserts and various materials that may be used therein are disclosed in greater detail in U.S. patent application Ser. No. 11/172,770, filed Jul. 1, 2005.

FIG. 1 illustrates sheet 2 and the corresponding inserts 32, 34, 36, 38, 40. Sheet 2 preferably includes cutouts 12, 14, 16, 18, 20. Sheet 2 is preferably cut, sliced, and or otherwise removed and separated from a larger sheet of material (not shown). Sheet 2 may also be formed according to practices well known to those of skill in the art. Cutouts 12, 14, 16, 18, 20 are preferably formed by similar means.

Similarly, inserts 32, 34, 36, 38, 40 are preferably removed and separated from larger sheets of material. Advantageously, sheet 2 and inserts 32, 34, 36, 38, 40 may include materials of one or more differing properties and may be positioned to maximize the benefit of one or more of those properties. For example, there may be locations of increased wear on the grip G during use. Cutouts may be strategically placed in these areas of increased wear and corresponding inserts may be placed in those areas. These inserts may include materials of increased strength, durability, or durometer, which may make them better suited to absorb the forces imparted to those areas of the grip. As those of skill in the art will appreciate from the foregoing, these inserts may have different levels of tackiness and that the inserts could be selected based on tackiness.

It also may be desirable to include certain areas of a different color. In such an instance, cutouts may be formed and correspondingly shaped inserts may be used in those locations with different colors. As illustrated in FIG. 13, the panel P may include one or more friction enhancing patterns. Sheet 2 or inserts 32, 34, 36, 38, 40 may include these one or more friction enhancing patterns prior to being formed into panel P, or may be manipulated to include these patterns after being formed into panel P. In the earlier case, the patterns may be formed when the components are cut from the larger sheets or they may be formed in a separate step. These different colors may be used on cutouts with the same physical properties and/or cutouts having the same physical properties may share the same color.

Panel P also preferably comprises multiple layers. Referring to FIG. 3, in one embodiment, panel P, including the sheet 2 and inserts 32, 34, 36, 38, 40 comprises an inner strength layer 4 and an outer tactile layer 6. Preferably, outer tactile layer 6 comprises polyurethane. Other materials than

polyurethane could be used and still achieve some advantages. In particular, other polymeric compounds can be used to create the outer layer and achieve some advantages. In addition, additional materials such as waterproofing coatings may be incorporated on the outer surface of the outer tactile layer **6** without departing from the invention disclosed herein. Inner strength of layer **4** preferably comprises a felt. Alternative embodiments of this invention may use other fabric or textile layers in lieu of, or in conjunction, with felt. In another embodiment, the inner strength layer **4** may comprise a polymer, more preferably ethylene vinyl acetate (EVA).

The outer surface of inner strength layer **4** is preferably bonded to the inner surface of outer tactile layer **6**. For purposes of this disclosure, the definition of bonding is intended to have a broad meaning, including commonly understood definitions of bonding, adhering, fixing, attaching, sewing, coupling, and gluing. When polyurethane is used in outer layer **6**, such polyurethane is preferably coagulated to define pores (not shown). The polyurethane may be coagulated and bonded directly to inner strength layer **4**, or may be first coagulated on an intermediary layer (not shown) and later attached to inner strength layer **4**. Such a process is described in greater detail in, for example, U.S. patent application Ser. No. 11/172,770.

Referring to FIGS. **6** and **7**, sheet **2** and inserts **32**, **34**, **36**, **38**, **40** are preferably arranged on a backing sheet **60**. Backing sheet **60** is preferably an adhesive **61** coated plastic. The adhesive **61** used is preferably strong enough to maintain the relative positions of the sheet and the inserts; however, it is preferably removable prior to bonding the panel **P** to the underlisting sleeve **U**. In some embodiments, backing sheet **60** is removed after the sheet and the inserts have been joined, as shown in FIG. **16**. Alternatively, backing sheet may comprise a thin layer of material intended to remain on the grip. For example, a thin sheet of felt or other strength material may be used and permanently joined or bonded to the backs of the sheet **2** and the inserts **32**, **34**, **36**, **38**, **40**.

As shown in FIG. **6**, sheet **2** and inserts **32**, **34**, **36**, **38**, **40** are preferably arranged on backing sheet **60**. As shown in FIGS. **7-9**, the sheet and the inserts are preferably held in position by backing sheet **60** such that their sides are in contact with each other to form intersections **62**. These intersections **62** may include one or more adhesives to bond or join the sides of the inserts to the sides of the sheet. If a multiple layered panel is desired, and the inner layer includes felt, an adhesive with the chemical formula toluene (CH_5CH_3), ethyl acetate ($\text{C}_4\text{H}_8\text{O}_2$), methyl ethyl ketone ($\text{C}_4\text{H}_8\text{O}$), and acetone ($\text{C}_3\text{H}_6\text{O}$) may be used between the layers of felt along at least a portion of the intersection. If an outer layer of polyurethane is used, the adhesive between the polyurethane layers along at least a portion of the intersection may be a polyurethane deposit.

As shown in FIGS. **10-14**, a mold **M** is preferably used to form a friction enhancing pattern on the outer surface of the panel **P**. An example of such a friction enhancing pattern is shown in FIG. **12**. As shown in detail in FIG. **15**, mold **M** may also form a channel **64** along a portion or the entire intersections **62** between the sheet **2** and the inserts **32**, **34**, **36**, **38**, **40**. The mold **M** preferably uses heat to melt a portion of the outer surface of the panel **P**. Along the intersections **62**, this heat preferably melts the polyurethane, if used, so that the polyurethane joins the outer surface of the insert to the outer surface of the sheet to form the unitary panel **P**.

As described in other patents, for example U.S. Pat. No. 6,843,732, an additional deposit of polyurethane may be placed along the intersections **62**. This additional deposit may be placed in a portion or the entire channel **64**, if formed in the

panel **P**, or along a portion or the entire outer surface of the intersections **62**. As previously disclosed, this deposit may be buffed or otherwise smoothed such that the surface of the grip is substantially smooth. Alternatively, the deposit need not be smoothed.

Once the sheet **2** and the inserts **32**, **34**, **36**, **38**, **40** have been joined to form panel **P**, backing sheet **60** may be removed as shown in FIG. **16**. FIGS. **17-48** show further manipulation of panel **P** and its application to an underlisting **U** or putter underlisting **PU** to form a grip **G** or a putter grip **PG**, respectively.

A similar method may be employed to form a spiral wrap grip with one or more inserts. In addition, one or more inserts may be positioned within the cutouts. In such an embodiment, two or more inserts would, for example, replace insert **32** in cutout **12**.

As shown in FIGS. **17-19**, the sides of panel **P** are preferably skived. It will be noted from FIGS. **17** and **18** that the skiving on the first and second sides of panel **P** are preferably parallel to one another. Such a configuration of skiving may be advantageously used to form a substantially longitudinal overlapping intersection of the first and second skived longitudinal sides, as shown in FIGS. **29-31**. Alternatively, first and second sides of panel **P** may be skived anti-parallel in a similar manner to the skiving of top and bottom sides of panel **P** shown in FIG. **19**. With anti-parallel longitudinal side edges, the substantially longitudinal intersection may be formed by overlapping the edges. Alternatively, the intersection may be sewn or otherwise joined.

Generally, the outer surface of the panel **P** is in direct contact with the hand of the user using a grip **G**. However, as one of skill in the art would appreciate, an additional coating layer over the panel **P** may be included. It should be understood that the outer surface of a grip embodying the present invention may also be coated, in whole or in part, by means of a brush, nozzle, spray, or the like with a thin layer of polyurethane and/or other material (not shown) to protect such surface, add tackiness thereto, and increase the durability thereof. The additional coating layer is preferably transparent, or semi-transparent, such that some or all of the pattern on the outer surface of the panel **P** created by the cutouts and inserts remains visible. The additional coating layer may be somewhat opaque, as long as a portion of the panel **P** is observable through the additional coating layer. If an additional coating layer is included over the outer surface of the grip, this layer may be further enhanced with a friction enhancing pattern as is known to those of skill in the art. The additional coating layer may be incorporated into a previously formed grip **G** or may be applied to the panel **P** prior to attachment to the underlisting sleeve **U**. If used, the additional coating layer would be in direct contact with the user's hand rather than the outer surface of the grip. However, even when an additional coating layer is included, the outer surface of the panel **P** is considered to be the outer surface of the grip.

Embodiments of the golf club grip provide the advantages over the existing wrapped and single panel grips described hereinbefore. Additionally, such grip has the appearance of a molded, one-piece grip familiar to professional and low-handicap golfers. Although some of such golfers are reluctant to use a non-traditional wrapped club grip, they are willing to play with a structurally integral grip of these embodiments since such grip affords the shock absorbing and tackiness qualities of a wrapped grip. Further, many individual golfers and high school, college, and professional teams like the camaraderie and unification that can be achieved by putting team colors on their golf grips without sacrificing comfort, durability, or tackiness because of paint embossment. These

9

embodiments allow the application of the multiple colors to golf club and putter grips to allow these teams and individuals to express their spirit and enthusiasm in a way never before possible.

It will be understood that the foregoing is only illustrative of the principles of the invention, and that various modifications, alterations, and combinations can be made by those skilled in the art without departing from the scope and spirit of the invention.

What is claimed is:

1. A grip for use on the handle of an article, the grip comprising:

a resilient underlisting sleeve defining an outer surface;
a first panel portion comprising a polymeric outer layer and a polymeric inner layer, said first panel portion defining a cut-out and an inner surface;

a second panel portion comprising an insert defined by a material having a different characteristic than said first panel portion, said second panel portion defining an inner surface and comprising a polymeric outer layer and a polymeric inner layer;

wherein said first panel portion surrounds said second panel portion on all sides so that said insert abuts the cut-out;

a first adhesive portion surrounding an outer edge of said insert on all sides and positioned between an inner edge of said cut-out and said insert, said first adhesive portion securing said first panel portion to said second panel portion so that said inner surface of said first panel portion and said inner surface of said second panel portion cooperate to form an inner surface of a panel; and

a second adhesive portion securing said inner surface of said panel to the outer surface of said underlisting sleeve, wherein said panel being wrapped around said underlisting sleeve such that said first panel portion extends

10

around the periphery of said second panel portion in both the circumferential and longitudinal directions along the surface of the grip and the polymeric inner layer of the first panel portion at the periphery of the cut-out abuts the polymeric inner layer at the periphery of the second panel portion.

2. A grip as in claim 1, wherein the characteristic is durometer.

3. A grip as in claim 1, wherein the characteristic is color.

4. A grip as in claim 1, wherein the panel further comprises a top side, a bottom side, a first substantially vertical side, and a second substantially vertical side, the panel wrapped about the underlisting sleeve such that the first and second sides join to form a substantially vertical seam.

5. A grip as in claim 4, wherein the seam further comprises a channel.

6. A grip as in claim 5, wherein the channel along the seam further comprises a deposit of polyurethane.

7. A grip as in claim 4, wherein the vertical sides are joined by adhesive.

8. A grip as in claim 1, wherein the grip further comprises an outer surface comprising a friction enhancing pattern.

9. A grip as in claim 1, wherein said first panel portion defines a first recessed portion and said second panel portion defines a second recessed portion, wherein said first recessed portion and said second recessed portion cooperate to form a recessed channel surrounding said insert on all sides.

10. A grip as in claim 9, wherein the channel is melted.

11. A grip as in claim 9, wherein the channel further comprises a deposit of polyurethane.

12. A grip as in claim 1, wherein the polymeric inner layer of the first panel portion comprises ethylene vinyl acetate.

13. A grip as in claim 1, wherein the polymeric inner layer of the second panel portion comprises ethylene vinyl acetate.

* * * * *