

US008435284B2

(12) **United States Patent**  
**Eidenschink et al.**

(10) **Patent No.:** **US 8,435,284 B2**  
(45) **Date of Patent:** **May 7, 2013**

(54) **TELESCOPING BIFURCATED STENT**

(75) Inventors: **Tracee Eidenschink**, Wayzata, MN  
(US); **Michael P. Meyer**, Richfield, MN  
(US); **Matt Heidner**, Maple Grove, MN  
(US); **Daniel Gregorich**, St. Louis Park,  
MN (US)

(73) Assignee: **Boston Scientific Scimed, Inc.**, Maple  
Grove, MN (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 1646 days.

4,454,887 A	6/1984	Kruger	128/772
4,552,554 A	11/1985	Gould et al.	604/51
4,681,570 A	7/1987	Dalton	604/282
4,689,174 A	8/1987	Lupke	156/470
4,730,616 A	3/1988	Frisbie et al.	128/348.1
4,769,005 A	9/1988	Ginsburg et al.	604/53
4,774,949 A	10/1988	Fogarty	
4,896,670 A	1/1990	Crittenden	606/194
4,900,314 A	2/1990	Quackenbush	604/282
4,905,667 A	3/1990	Foerster et al.	128/4
4,957,508 A	9/1990	Kaneko et al.	632/12
4,983,166 A	1/1991	Yamawaki	604/96
4,994,071 A	2/1991	Gregor	606/194
5,054,501 A	10/1991	Chuttani et al.	128/772
5,122,125 A	6/1992	Deuss	604/282
5,147,317 A	9/1992	Shank et al.	604/164

(Continued)

(21) Appl. No.: **11/300,210**

(22) Filed: **Dec. 14, 2005**

(65) **Prior Publication Data**

US 2007/0135904 A1 Jun. 14, 2007

(51) **Int. Cl.**  
**A61F 2/06** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **623/1.35**; 623/1.15; 623/1.11

(58) **Field of Classification Search** ..... 623/1.15,  
623/1.16, 1.18, 1.19, 1.2, 1.35; 606/108  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,596,754 A	8/1926	Moschelle	
1,861,769 A	6/1932	Wappler	
2,845,959 A	8/1958	Sidebotham	
3,872,893 A	3/1975	Roberts	138/121
4,309,994 A	1/1982	Grunwald	128/214 R
4,410,476 A	10/1983	Redding et al.	264/173
4,413,989 A	11/1983	Schjeldahl et al.	604/96
4,421,810 A	12/1983	Rasmussen	428/109

**FOREIGN PATENT DOCUMENTS**

CA	2220864	7/1999
DE	9014845	2/1991

(Continued)

**OTHER PUBLICATIONS**

Chevalier, M.D., Bernard, "Placement of Coronary Stents in Bifurcation Lesions by the "Culotte" Technique," *The American Journal of Cardiology*, vol. 82, pp. 943-949 (Oct. 15, 1998).

(Continued)


*Primary Examiner* — Darwin Erez  
*Assistant Examiner* — Jing Ou

(74) *Attorney, Agent, or Firm* — Vidas, Arrett & Steinkraus,  
P.A.

(57) **ABSTRACT**

A bifurcated stent that uses telescoping rings to support or form the side branch lumen. This design allows the bifurcation branch to extend easily, to a useful distance, and to be deployed along oblique angles. Best of all, this design avoids the need to deploy a bent stent.

**11 Claims, 15 Drawing Sheets**





U.S. PATENT DOCUMENTS									
5,156,620	A	10/1992	Pigott	623/1	6,013,054	A	1/2000	Jiun Yan	604/96
5,217,440	A	6/1993	Frassica	604/282	6,013,091	A	1/2000	Ley et al.	83/150
5,219,355	A	6/1993	Parodi et al.	606/191	6,016,810	A	1/2000	Ravenscroft	128/898
5,244,619	A	9/1993	Burnham	264/173	6,017,324	A	1/2000	Tu et al.	604/96
5,320,605	A	6/1994	Sahota	604/101	6,017,363	A	1/2000	Hojeibane	623/1
5,337,733	A	8/1994	Bauerfeind et al.	128/4	6,030,414	A	2/2000	Taheri	623/1
5,342,387	A	8/1994	Summers	606/198	6,033,433	A	3/2000	Her	623/1
5,350,395	A	9/1994	Yock	606/194	6,033,434	A	3/2000	Borghi	623/1
5,387,235	A	2/1995	Chuter	623/1	6,033,435	A	3/2000	Penn et al.	623/1
5,404,887	A	4/1995	Prather	128/772	6,039,758	A	3/2000	Quiachon et al.	623/1
5,417,208	A	5/1995	Winkler	128/642	6,045,557	A	4/2000	White et al.	606/108
5,443,497	A	8/1995	Venbrux	623/1	6,048,360	A	4/2000	Khosravi et al.	623/1
5,445,624	A	8/1995	Jimenez	604/280	6,048,361	A	4/2000	Von Gepen	623/1
5,456,712	A	10/1995	Maginot	623/1	6,051,020	A	4/2000	Goicoechea et al.	623/1
5,458,605	A	10/1995	Klemm	606/108	6,056,722	A	5/2000	Jayaraman	604/102
5,476,471	A	12/1995	Shifrin et al.	606/151	6,056,775	A	5/2000	Borghi et al.	623/1.16
5,487,730	A	1/1996	Marcadis et al.	604/96	6,059,824	A	5/2000	Taheri	623/1
5,489,271	A	2/1996	Andersen	604/102	6,068,655	A	5/2000	Seguin et al.	623/1
5,496,292	A	3/1996	Burnham	604/282	6,071,298	A	6/2000	Lashinski et al.	606/198
5,575,771	A	11/1996	Walinsky	604/96	6,086,611	A	7/2000	Duffy et al.	623/1
5,578,074	A	11/1996	Mirigian	623/1	6,090,133	A	7/2000	Richter et al.	623/1
5,591,228	A	1/1997	Edoga	623/1	6,093,203	A	7/2000	Uflacker	612/1.12
5,599,300	A	2/1997	Weaver et al.	604/54	6,096,073	A	8/2000	Webster et al.	623/1.16
5,607,444	A	3/1997	Lam et al.	606/194	6,099,497	A	8/2000	Adams et al.	604/96.01
5,609,605	A	3/1997	Marshall et al.	606/191	6,099,558	A	8/2000	White	623/1.16
5,609,627	A	3/1997	Goicoechea et al.	623/1	6,099,560	A	8/2000	Penn et al.	623/1.35
5,613,980	A	3/1997	Chauhan	606/194	6,102,938	A	8/2000	Evans et al.	623/1
5,617,878	A	4/1997	Taheri	128/898	6,113,579	A	9/2000	Eidenschink	604/264
5,618,299	A	4/1997	Khosravi et al.	606/198	6,117,117	A	9/2000	Mauch	604/284
5,632,762	A	5/1997	Myler	606/194	6,117,156	A	9/2000	Richter et al.	606/194
5,632,763	A	5/1997	Glastra	606/194	6,129,738	A	10/2000	Lashinski et al.	606/194
5,632,772	A	5/1997	Alcime et al.	623/1	6,129,754	A	10/2000	Kanesaka	623/1
5,636,641	A	6/1997	Fariabi	600/585	6,132,459	A	10/2000	Piplani et al.	623/1.13
5,639,278	A	6/1997	Dereume et al.	623/1	6,142,973	A	11/2000	Carleton et al.	604/96
5,669,905	A	9/1997	Scheldrup	606/32	6,143,002	A	11/2000	Vietmeier	606/108
5,669,924	A	9/1997	Shaknovich	606/108	6,159,238	A	12/2000	Killion et al.	623/1.11
5,669,932	A	9/1997	Fischell et al.	606/198	6,165,195	A	12/2000	Wilson et al.	606/194
5,672,153	A	9/1997	Lax et al.	604/22	6,165,213	A	12/2000	Goicoechea et al.	623/1.34
5,676,697	A	10/1997	McDonald	623/1	6,168,621	B1	1/2001	Vrba	623/1.2
5,683,450	A	11/1997	Goicoechea et al.	623/1	6,183,509	B1	2/2001	Dibie	623/1.35
5,693,086	A	12/1997	Goicoechea et al.	623/1	6,197,046	B1	3/2001	Piplani et al.	623/1.11
5,697,971	A	12/1997	Fischell et al.	623/1	6,197,049	B1	3/2001	Shaolian et al.	623/1.35
5,707,348	A	1/1998	Krogh	602/41	6,203,568	B1	3/2001	Lombardi et al.	623/1.13
5,709,713	A	1/1998	Evans et al.	623/1	6,210,380	B1	4/2001	Mauch	604/284
5,720,735	A	2/1998	Dorros	604/284	6,210,429	B1	4/2001	Vardi	623/1.11
5,735,872	A	4/1998	Carpenter et al.	606/198	6,210,431	B1	4/2001	Power	623/1.11
5,749,825	A	5/1998	Fischell et al.	600/3	6,210,433	B1	4/2001	Larre	623/1.15
5,749,890	A	5/1998	Shaknovich	606/198	6,217,527	B1	4/2001	Selmon et al.	600/285
5,755,734	A	5/1998	Richter et al.	606/194	6,221,080	B1	4/2001	Power	606/108
5,755,735	A	5/1998	Richter et al.	606/194	6,221,090	B1	4/2001	Wilson	606/194
5,755,770	A	5/1998	Ravenscroft	623/1	6,221,098	B1	4/2001	Wilson et al.	623/1.11
5,755,771	A	5/1998	Penn et al.	623/1	6,231,563	B1	5/2001	White et al.	604/523
5,755,772	A	5/1998	Evans et al.	623/1	6,231,598	B1	5/2001	Berry et al.	
5,755,773	A	5/1998	Evans et al.	623/1	6,238,430	B1	5/2001	Klumb et al.	623/1.11
5,755,778	A	5/1998	Kleshinski	623/1	6,248,122	B1	6/2001	Klumb et al.	606/194
5,776,101	A	7/1998	Goy	604/104	6,251,133	B1	6/2001	Richter et al.	623/1.16
5,782,906	A	7/1998	Marshall et al.	604/194	6,254,593	B1	7/2001	Wilson	606/1.11
5,797,951	A	8/1998	Mueller		6,258,073	B1	7/2001	Mauch	604/284
5,800,508	A	9/1998	Goicoechea et al.	623/1	6,258,115	B1	7/2001	Dubrul	606/200
5,800,520	A	9/1998	Fogarty et al.	623/1	6,258,116	B1	7/2001	Hojeibane	623/1.16
5,824,036	A	10/1998	Lauterjung	623/1	6,261,273	B1	7/2001	Ruiz	604/284
5,824,040	A	10/1998	Cox et al.	623/1	6,261,305	B1	7/2001	Marotta et al.	606/200
5,827,320	A	10/1998	Richter et al.	606/194	6,261,316	B1	7/2001	Shaolian et al.	623/1.11
5,851,464	A	12/1998	Davila et al.	264/103	6,264,662	B1	7/2001	Lauterjung	606/108
5,855,600	A	1/1999	Alt	623/1	6,264,686	B1	7/2001	Rieu et al.	623/1.16
5,868,777	A	2/1999	Lam	606/194	6,273,909	B1	8/2001	Kugler et al.	623/1.13
5,893,887	A	4/1999	Jayaraman	623/1	6,287,277	B1	9/2001	Yan	604/96.01
5,906,640	A	5/1999	Penn et al.	623/1	6,290,673	B1	9/2001	Shanley	604/102.02
5,916,263	A	6/1999	Goicoechea et al.	623/1	6,293,968	B1	9/2001	Taheri	623/1.15
5,921,995	A	7/1999	Kleshinski	606/153	6,302,906	B1	10/2001	Goicoechea et al.	623/1.11
5,938,696	A	8/1999	Goicoechea et al.	623/1	6,302,908	B1	10/2001	Parodi	623/1.31
5,961,490	A	10/1999	Adams	604/96	6,306,164	B1	10/2001	Kujawski	623/1.25
5,961,548	A	10/1999	Shmulewitz	623/1	6,312,461	B1	11/2001	Unsworth et al.	623/1.19
5,968,089	A	10/1999	Krajicek	623/1	6,319,278	B1	11/2001	Quinn et al.	623/1.13
5,972,017	A	10/1999	Berg et al.	606/198	6,322,587	B1	11/2001	Quiachon et al.	623/1.23
5,984,929	A	11/1999	Bashiri	606/108	6,325,819	B1	12/2001	Pavcnik et al.	623/1.11
5,984,955	A	11/1999	Wisselink	623/1	6,325,822	B1	12/2001	Chouinard et al.	623/1.15
5,993,481	A	11/1999	Marcade et al.	623/1	6,325,826	B1	12/2001	Vardi	623/1.35
					6,334,864	B1	1/2002	Amplatz et al.	606/200



6,334,870	B1	1/2002	Ehr	623/1.16	2002/0156517	A1	10/2002	Perouse	623/1.11
6,346,089	B1	2/2002	Dibie	623/1.15	2002/0165604	A1	11/2002	Shanley	623/1.15
6,355,060	B1	3/2002	Lenker et al.	623/1.34	2002/0173835	A1	11/2002	Bourang et al.	623/1.11
6,361,544	B1	3/2002	Wilson et al.	606/194	2002/0173840	A1	11/2002	Brucker et al.	623/1.16
6,361,555	B1	3/2002	Wilson	623/1.11	2002/0183763	A1	12/2002	Callol et al.	606/108
6,383,213	B2	5/2002	Wilson et al.	623/1.11	2002/0193872	A1	12/2002	Trout, III et al.	623/1.34
6,387,120	B2	5/2002	Wilson et al.	623/1.11	2002/0193873	A1	12/2002	Brucker	623/1.11
6,395,018	B1	5/2002	Castaneda	623/1.13	2003/0009209	A1	1/2003	Hojeibane	623/1.11
6,436,104	B2	8/2002	Hojeibane	606/108	2003/0028233	A1	2/2003	Vardi et al.	623/1.11
6,436,134	B2	8/2002	Richter	623/1.15	2003/0050688	A1	3/2003	Fischell et al.	623/1.15
6,468,301	B1	10/2002	Amplatz et al.	623/1.13	2003/0055378	A1	3/2003	Wang et al.	604/103.07
6,508,836	B2	1/2003	Wilson et al.	623/1.35	2003/0055483	A1	3/2003	Gumm	623/1.11
6,514,228	B1	2/2003	Hamilton	604/96.01	2003/0074047	A1	4/2003	Richter	623/1.11
6,517,515	B1	2/2003	Eidenschink	604/101.05	2003/0093109	A1	5/2003	Mauch	606/194
6,517,558	B2	2/2003	Gittings et al.	606/153	2003/0097169	A1	5/2003	Brucker et al.	623/1.11
6,520,988	B1	2/2003	Colombo et al.	623/1.35	2003/0114912	A1	6/2003	Sequin et al.	623/1.11
6,537,284	B1	3/2003	Priddy	606/108	2003/0125791	A1	7/2003	Sequin et al.	623/1.11
6,540,779	B2	4/2003	Richter et al.	623/1.35	2003/0125802	A1	7/2003	Callol et al.	623/1.35
6,579,308	B1	6/2003	Jansen	623/1.12	2003/0135259	A1	7/2003	Simso	623/1.12
6,579,309	B1	6/2003	Loos	623/1.16	2003/0181923	A1	9/2003	Vardi	606/108
6,579,312	B2	6/2003	Wilson et al.	623/1.35	2003/0195606	A1	10/2003	Davidson	623/1.15
6,582,394	B1	6/2003	Reiss	604/96	2004/0006381	A1	1/2004	Sequin et al.	623/1.12
6,596,020	B2	7/2003	Vardi et al.	623/1.11	2004/0015227	A1	1/2004	Vardi et al.	623/1.16
6,599,315	B2	7/2003	Wilson	623/1.11	2004/0044396	A1	3/2004	Clerc et al.	623/1.13
6,599,316	B2	7/2003	Vardi	623/1.15	2004/0059406	A1	3/2004	Cully et al.	623/1.11
6,645,242	B1	11/2003	Quinn	623/1.16	2004/0088007	A1	5/2004	Eidenschink	607/1
6,689,156	B1	2/2004	Davidson et al.	623/1.11	2004/0117003	A1	6/2004	Ouriel et al.	623/1.35
6,692,483	B2	2/2004	Vardi et al.	604/529	2004/0133268	A1	7/2004	Davidson et al.	623/1.35
6,694,877	B1	2/2004	Brucker	623/1.16	2004/0138732	A1	7/2004	Suhr et al.	623/1.11
6,695,877	B2	2/2004	Brucker et al.	623/1.16	2004/0138737	A1	7/2004	Davidson	623/1.15
6,706,062	B2	3/2004	Vardi et al.	623/1.15	2004/0148006	A1	7/2004	Davidson et al.	623/1.11
6,749,628	B1	6/2004	Callol et al.	623/1.15	2004/0172121	A1	9/2004	Eidenschink et al.	623/1.11
6,776,793	B2	8/2004	Brown et al.	623/1.15	2004/0186560	A1	9/2004	Alt	623/1.35
6,811,566	B1	11/2004	Penn et al.	623/1.15	2004/0225345	A1	11/2004	Fischell et al.	623/1.11
6,835,203	B1	12/2004	Vardi	623/1.16	2004/0267352	A1	12/2004	Davidson et al.	623/1.16
6,858,038	B2	2/2005	Heuser	623/1.35	2005/0004656	A1	1/2005	Das	623/1.16
6,884,258	B2	4/2005	Vardi et al.	623/1.11	2005/0010278	A1	1/2005	Vardi	623/1.16
6,896,699	B2	5/2005	Wilson et al.	623/1.35	2005/0015108	A1	1/2005	Williams et al.	606/194
6,932,837	B2	8/2005	Amplatz et al.	623/1.15	2005/0015135	A1	1/2005	Shanley	623/1.11
6,955,687	B2	10/2005	Richter et al.	623/1.35	2005/0060027	A1	3/2005	Khenansho et al.	623/1.35
6,955,688	B2	10/2005	Wilson et al.	623/1.35	2005/0096726	A1	5/2005	Sequin et al.	623/1.12
6,962,602	B2	11/2005	Vardi et al.	623/1.11	2005/0102021	A1	5/2005	Osborne	623/1.13
7,018,400	B2	3/2006	Lashinski et al.	623/1.11	2005/0102023	A1	5/2005	Yadin	623/1.16
7,056,323	B2	6/2006	Mareiro et al.	606/108	2005/0119731	A1	6/2005	Brucker et al.	623/1.35
7,060,091	B2	6/2006	Killion et al.	623/1.15	2005/0125076	A1	6/2005	Ginn	623/23.65
2001/0002443	A1	5/2001	Parodi		2005/0131526	A1	6/2005	Wong	
2001/0002927	A1	6/2001	Detampel		2005/0149161	A1	7/2005	Eidenschink et al.	623/1.11
2001/0002943	A1	6/2001	Nagayama et al.		2005/0154442	A1	7/2005	Eidenschink et al.	623/1.11
2001/0003161	A1	6/2001	Vardi et al.		2005/0154444	A1	7/2005	Quadri	623/1.16
2001/0004705	A1	6/2001	Killion et al.		2005/0183259	A1	8/2005	Eidenschink et al.	29/508
2001/0004706	A1	6/2001	Hojeibane		2005/0209673	A1	9/2005	Shaked	623/1.11
2001/0004707	A1	6/2001	Dereume et al.		2005/0228483	A1	10/2005	Kaplan	623/1.11
2001/0004823	A1	6/2001	Cronin et al.		2006/0036315	A1	2/2006	Yadin et al.	623/1.35
2001/0007954	A1	7/2001	Shaolian et al.		2006/0041303	A1	2/2006	Israel	623/1.11
2001/0012927	A1	8/2001	Mauch	604/284	2006/0079956	A1	4/2006	Eigler et al.	623/1.35
2001/0016766	A1	8/2001	Vardi et al.		2006/0173528	A1	8/2006	Feld et al.	623/1.15
2001/0016767	A1	8/2001	Wilson et al.		2007/0073376	A1	3/2007	Krolik et al.	623/1.11
2001/0016768	A1	8/2001	Wilson et al.						
2001/0020173	A1	9/2001	Klumb et al.						
2001/0020184	A1	9/2001	Dehdashtian et al.						
2001/0025195	A1	9/2001	Shaolian et al.						
2001/0027291	A1	10/2001	Shanley						
2001/0027338	A1	10/2001	Greenberg	623/1.13					
2001/0029396	A1	10/2001	Wilson et al.						
2001/0037116	A1	11/2001	Wilson et al.	606/108					
2001/0037138	A1	11/2001	Wilson et al.	623/1.11					
2001/0039448	A1	11/2001	Dibie	623/1.16					
2001/0049552	A1	12/2001	Richter et al.	623/1.15					
2001/0056297	A1	12/2001	Hojeibane	623/1.16					
2002/0013618	A1	1/2002	Marotta et al.	623/1.15					
2002/0013619	A1	1/2002	Shanley	623/1.15					
2002/0022874	A1	2/2002	Wilson	623/1.11					
2002/0026232	A1	2/2002	Marotta et al.	623/1.16					
2002/0035392	A1	3/2002	Wilson	623/1.11					
2002/0042650	A1	4/2002	Vardi et al.	623/1.35					
2002/0052648	A1	5/2002	McGuckin, Jr. et al.	623/1.35					
2002/0072790	A1	6/2002	McGuckin, Jr. et al.	623/1.12					
2002/0111675	A1	8/2002	Wilson	715/530					
2002/0156516	A1	10/2002	Vardi et al.	623/1.11					
FOREIGN PATENT DOCUMENTS									
DE					29701758		3/1997		
DE					29708803		7/1997		
EP					0347023		12/1989		
EP					0479730		4/1992		
EP					0647148		4/1995		
EP					0686379		12/1995		
EP					0804907		11/1997		
EP					0751752		6/1998		
EP					0479557		7/1998		
EP					0876805		11/1998		
EP					0880949		12/1998		
EP					0891751		1/1999		
EP					0895759		2/1999		
EP					0904745		3/1999		
EP					0937442		8/1999		
EP					0783873		4/2000		
EP					1031328		8/2000		
EP					1031329		8/2000		
EP					0883384		12/2000		
EP					0862392		8/2001		



EP	0808140	12/2001	WO	0121095	3/2001
EP	0884028	2/2002	WO	0121109	3/2001
EP	1190685	3/2002	WO	01021244	3/2001
EP	0897700	7/2002	WO	0130433	5/2001
EP	0684022	2/2004	WO	0135715	5/2001
EP	1157674	7/2005	WO	0135863	5/2001
EP	1031330	11/2005	WO	0139697	6/2001
EP	1070513	6/2006	WO	0139699	6/2001
FR	2678508	1/1993	WO	0141677	6/2001
FR	2740346	4/1997	WO	0143665	6/2001
FR	2756173	5/1998	WO	0143809	6/2001
FR	2760351	9/1998	WO	0145785	6/2001
GB	2337002	11/1999	WO	0149342	7/2001
WO	88/06026	8/1988	WO	0154621	8/2001
WO	92/19308	11/1992	WO	0154622	8/2001
WO	9521592	8/1995	WO	0158385	8/2001
WO	96/29955	10/1996	WO	0160284	8/2001
WO	9634580	11/1996	WO	0170294	9/2001
WO	9641592	12/1996	WO	0170299	9/2001
WO	9707752	3/1997	WO	0174273	10/2001
WO	9715346	5/1997	WO	0189409	11/2001
WO	9716217	5/1997	WO	02/00138	1/2002
WO	97/26936	7/1997	WO	02/053066	7/2002
WO	9741803	11/1997	WO	02/068012	9/2002
WO	97/45073	12/1997	WO	03/007842	1/2003
WO	9746174	12/1997	WO	03/055414	7/2003
WO	9819628	5/1998	WO	03/063924	8/2003
WO	98/31306	7/1998	WO	2004/026174	4/2004
WO	9836709	8/1998	WO	2004/026180	4/2004
WO	9837833	9/1998	WO	2005/009295	2/2005
WO	9847446	10/1998	WO	2005/014077	2/2005
WO	9847447	10/1998	WO	2006/028925	3/2006
WO	9848879	11/1998			
WO	9853759	12/1998			
WO	9903426	1/1999			
WO	9904726	2/1999			
WO	9913808	3/1999			
WO	99/15103	4/1999			
WO	9915108	4/1999			
WO	9915109	4/1999			
WO	9924104	5/1999			
WO	9934749	7/1999			
WO	9936002	7/1999			
WO	9936015	7/1999			
WO	9944539	9/1999			
WO	9956661	11/1999			
WO	9965419	12/1999			
WO	0007523	2/2000			
WO	0010485	3/2000			
WO	0010489	3/2000			
WO	0013613	3/2000			
WO	0016719	3/2000			
WO	0027307	5/2000			
WO	0027463	5/2000			
WO	0028922	5/2000			
WO	0032266	6/2000			
WO	0145594	6/2000			
WO	0044307	8/2000			
WO	0044309	8/2000			
WO	0047134	8/2000			
WO	0048531	8/2000			
WO	0049951	8/2000			
WO	0051523	9/2000			
WO	0057813	10/2000			
WO	00/71054	11/2000			
WO	0067673	11/2000			
WO	0071055	11/2000			
WO	0074595	12/2000			

OTHER PUBLICATIONS

Nakamura M.D., Shigeru, "Techniques for Palmaz-Schatz Stent Deployment in Lesions with a Large Side Branch," *Catheterization and Cardiovascular Diagnosis*, vol. 34, pp. 353-361 (1995).

Caputo, Ronald P., "Stent Jail: A Minimum-Security Prison," *The American Journal of Cardiology*, vol. 77, pp. 1226-1230 (Jun. 1, 1996).

Colombo, M.D., Antonio, "'Kissing' Stent for Bifurcational Coronary Lesion," *Catheterization and Cardiovascular Diagnosis*, vol. 30, pp. 327-330 (Dec. 1993).

Carrie, M.D., Didier, "'T'-Shaped Stent Placement: A Technique for the Treatment of Dissected Bifurcation Lesions," *Catheterization and Cardiovascular Diagnosis*, vol. 37, pp. 311-313 (Mar. 1996).

Katoh, M.D., Osamu, "New Double Wire Technique to Stent Ostial Lesions," *Catheterization and Cardiovascular Diagnosis*, vol. 40, pp. 400-402 (Apr. 1997).

Lewis, M.D., Bruce E., "Acute procedural results in the treatment of 30 coronary artery bifurcation lesions with a double-wire atherectomy technique for side-branch protection," *American Heart Journal*, vol. 127:6, pp. 1600-1607 (Jun. 1994).

Yamashita, M.D.,PhD., Takehiro, "Bifurcation Lesions: Two Stents Versus One Stent—Immediate and Follow-up Results," *Journal of the American College of Cardiology*, vol. 35:5, pp. 1145-1151 (Apr. 2000).

Satler, M.D., Lowell F., "Bifurcation Disease: To Treat or Not to Treat," *Catheterization and Cardiovascular Interventions*, vol. 50, pp. 411-412 (2000).

U.S. Appl. No. 9/325,996, filed Jun. 4, 1999, Vardi et al.

U.S. Appl. No. 9/614,472, filed Jul. 11, 2000, Davidson et al.

U.S. Appl. No. 9/663,111, filed Sep. 15, 2000, Davidson et al.

TRIO™ 14 PTCA Catheter, Re-engineering Over the Wire Balloon Technology, Company Brochure Copyright 1994.




FIG. 1




FIG. 2






FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7




FIG. 8






FIG. 9




FIG. 10




FIG. 11






FIG. 12




FIG. 13




FIG. 14




FIG. 15






FIG. 16




FIG. 17




FIG. 18






FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23



**1****TELESCOPING BIFURCATED STENT****CROSS-REFERENCE TO RELATED  
APPLICATIONS**

Not Applicable

**STATEMENT REGARDING FEDERALLY  
SPONSORED RESEARCH**

Not Applicable

**BACKGROUND OF THE INVENTION****1. Field of the Invention**

In some embodiments this invention relates to implantable medical devices, their manufacture, and methods of use. Some embodiments are directed to delivery systems, such as catheter systems of all types, which are utilized in the delivery of such devices.

**2. Description of the Related Art**

A stent is a medical device introduced to a body lumen and is well known in the art. Typically, a stent is implanted in a blood vessel at the site of a stenosis or aneurysm endoluminally, i.e. by so-called "minimally invasive techniques" in which the stent in a radially reduced configuration, optionally restrained in a radially compressed configuration by a sheath and/or catheter, is delivered by a stent delivery system or "introducer" to the site where it is required. The introducer may enter the body from an access location outside the body, such as through the patient's skin, or by a "cut down" technique in which the entry blood vessel is exposed by minor surgical means.

Stents, grafts, stent-grafts, vena cava filters, expandable frameworks, and similar implantable medical devices, collectively referred to hereinafter as stents, are radially expandable endoprostheses which are typically intravascular implants capable of being implanted transluminally and enlarged radially after being introduced percutaneously. Stents may be implanted in a variety of body lumens or vessels such as within the vascular system, urinary tracts, bile ducts, fallopian tubes, coronary vessels, secondary vessels, etc. Stents may be used to reinforce body vessels and to prevent restenosis following angioplasty in the vascular system. They may be self-expanding, expanded by an internal radial force, such as when mounted on a balloon, or a combination of self-expanding and balloon expandable (hybrid expandable).

Stents may be created by methods including cutting or etching a design from a tubular stock, from a flat sheet which is cut or etched and which is subsequently rolled or from one or more interwoven wires or braids.

Within the vasculature, it is not uncommon for stenoses to form at a vessel bifurcation. A bifurcation is an area of the vasculature or other portion of the body where a first (or parent) vessel is bifurcated into two or more branch vessels. Where a stenotic lesion or lesions form at such a bifurcation, the lesion(s) can affect only one of the vessels (i.e., either of the branch vessels or the parent vessel) two of the vessels, or all three vessels. Many prior art stents however are not wholly satisfactory for use where the site of desired application of the stent is juxtaposed or extends across a bifurcation in an artery or vein such, for example, as the bifurcation in the mammalian aortic artery into the common iliac arteries.

The art referred to and/or described above is not intended to constitute an admission that any patent, publication or other information referred to herein is "prior art" with respect to this invention. In addition, this section should not be con-

**2**

strued to mean that a search has been made or that no other pertinent information as defined in 37 C.F.R. §1.56(a) exists.

All US patents and applications and all other published documents mentioned anywhere in this application are incorporated herein by reference in their entirety.

Without limiting the scope of the invention a brief summary of some of the claimed embodiments of the invention is set forth below. Additional details of the summarized embodiments of the invention and/or additional embodiments of the invention may be found in the Detailed Description of the Invention below.

A brief abstract of the technical disclosure in the specification is provided as well only for the purposes of complying with 37 C.F.R. 1.72. The abstract is not intended to be used for interpreting the scope of the claims.

All U.S. patents and applications and all other published documents mentioned anywhere in this application are incorporated herein by reference in their entirety.

**BRIEF SUMMARY OF THE INVENTION**

This invention contemplates a number of embodiments where any one, any combination of some, or all of the embodiments can be incorporated into a stent and/or a stent delivery system and/or a method of use. In the context of these embodiments, the term telescoping means to extend away from a stent wall in a direction different from that of the longitudinal axis of a stent. Telescoping includes but is not limited each or any combination of: extending along a linear, varied, or curved path; extending at an oblique angle from the longitudinal axis of the stent; as well as extending along a path parallel to the longitudinal axis of the stent.

At least one embodiment of the invention is directed to a bifurcated stent being expandable from an unexpanded state to an expanded state, with a diameter smaller in the unexpanded state having a substantially tubular primary body defining a primary circumferential plane, a primary outer surface, a primary lumen and having a primary longitudinal axis extending therethrough; and a side branch assembly engaged to the primary body having at least one ring member, which is positioned substantially within the primary circumferential plane in the unexpanded state and defining a secondary circumferential plane, a secondary lumen, and having a secondary longitudinal axis extending therethrough, in the expanded state. The secondary lumen is in fluid communication with the primary lumen and forms an oblique angle with the primary longitudinal axis.

At least one embodiment of the invention is directed to a stent containing a bifurcation branch formed out of at least one ring connected to the stent. When deployed, this stent bridges vessel bifurcations by telescoping and aligning at least one ring into the vessel bifurcation. This bifurcation branch is an additional stent channel forking away from the first channel defined by the main body of the stent. The bifurcation branch is in fluid communication with the first channel and is formed by one or more rings in fluid communication with the main stent body. The rings are connected to the stent and (if there is more than one ring) to each other by connectors. In some embodiments, a telescoping ring bifurcation branch is configured to extend farther than a petal shaped stent bifurcation branch.

At least one embodiment of the invention is directed to a stent containing a bifurcation branch of two or more interconnected rings in fluid communication with the main stent body in which at least one ring is in an unextended state when the branch is not telescoped. When the branch is telescoped, the unextended ring(s) assume an extended state.



At least one embodiment of the invention is directed to a bifurcation branch of one or more rings in fluid communication with the main stent body in which the ring-ring or ring-stent connectors have a first length when the branch is untelescoped and a second length when the stent is telescoped. These different connector lengths allow for the rings to have a low profile when untelescoped and to allow for the rings to form a bifurcation branch of a large length when telescoped. This embodiment encompasses but is not limited to any stent connector known to people of ordinary skill in the art which has a longer length when expanded than when unexpanded.

At least one embodiment of the invention is directed to a bifurcation branch of one or more rings in fluid communication with the main stent body in which the ring-ring or ring-stent connectors have a bent structure when untelescoped that substantially straightens when telescoped.

At least one embodiment of the invention is directed to a bifurcation branch of one or more rings in fluid communication with the main stent body in which a ring-ring or ring-stent connectors is a flexible sinusoidal connector

At least one embodiment of the invention is directed to a bifurcation branch of one or more rings in fluid communication with the main stent body in which a ring-ring or ring-stent connector is a pivot mechanism whose rotational motion changes the distance spanned by the connector.

At least one embodiment of the invention is directed to a bifurcation branch of one or more rings in fluid communication with the main stent body in which a ring-ring or ring-stent connector is a spring whose extension changes the distance spanned by the connector.

At least one embodiment of the invention is directed to a stent containing a bifurcation branch of two or more interconnected rings where when the branch is untelescoped, the rings are in an unexpanded state and are positioned concentrically adjacent to each other within or adjacent to the circumferential plane of the ring directly connected to the main stent body.

At least one embodiment of the invention is directed to a stent containing a bifurcation branch of at least one ring which has the configuration of an at least a partially self overlapping loop when unextended and contains a self extending mechanism. This mechanism expands the rings by removing the loop overlap when forming a stent bifurcation branch.

At least one embodiment of the invention is directed to a stent with a ring bifurcation branch containing a current detachment mechanism. In this embodiment, a locking mechanism restrains the telescoping and/or the ring extension from expanding until an electrical current is applied. Once applied, the current causes the mechanism to detach from the rings allowing the rings to expand and/or to telescope and form a bifurcation branch.

At least one embodiment of the invention is directed to a stent with a ring bifurcation branch in which a ring may extend until either a pre-defined circumference is reached or until the extension is blocked by an anatomical feature.

At least one embodiment of the invention is directed to a stent with a ring bifurcation branch in which a ring contains a ratchet configuration which allows it to either increase or decrease its circumference by moving a locking mechanism along a ring's perimeter in one direction. Because the ratchet configuration prevents the locking mechanism from moving in the reverse direction, it prevents any change in circumference size in the opposite direction.

At least one embodiment of the invention is directed to a stent with a ring bifurcation branch in which a ring or connector is made out of metal(s), polymer(s), and/or combinations thereof.

At least one embodiment of the invention is directed to a stent with a ring bifurcation branch in which the ring bifurcation is fed into the side body vessel by a support wire.

At least one embodiment of the invention is directed to a stent with a ring bifurcation branch in which when the final shape of the bifurcation branch is assumed, the branch is locked into place with a single or multiple tongue and groove latch mechanism.

At least one embodiment of the invention is directed to a stent with a ring bifurcation branch in which the branch is formed before the stent is expanded.

At least one embodiment of the invention is directed to a stent with a ring bifurcation branch in which the branch is formed after the stent is expanded.

At least one embodiment of the invention is directed to a stent with a ring bifurcation branch in which the branch is formed at substantially the same time that the stent is expanded.

This invention also encompasses embodiments where at least one ring member has an unexpanded circumference in the unexpanded state and an expanded circumference in the expanded state, wherein the expanded circumference is greater than the unexpanded circumference, where adjacent ring members are engaged one to the other by at least one connector, and where at least one connector has a first end, a second end and a length therebetween, each end being flexibly engaged to one of the rings.

This invention also encompasses embodiments where in the unexpanded state the plurality of rings are concentrically arranged relative to one another, where in the unexpanded state the ring members are positioned laterally adjacent to one another, where at least one of the expanded state and the unexpanded state at least two ring members have differing circumferences, and where the secondary lumen comprises a length and a diameter, the diameter tapering along at least a portion of the length.

This invention also encompasses embodiments where at least one connector comprises a polymeric sheath, where the polymeric sheath is at least partially constructed out of PTFE, where at least one ring member comprises a ratchet mechanism, in the expanded state the ratchet mechanism preventing the expanded circumference from reverting to a circumference smaller than the expanded circumference, where at least one ring member is constructed and arranged to self expand from the unexpanded circumference to the expanded circumference, where at least one ring member is engaged to the primary body by at least one engagement region, the at least one engagement region having an engaged state and a released state, in the engaged state the at least one ring member being retained in the unexpanded state and in the released state the at least one ring member being released to expand to the expanded state.

At least one embodiment of the invention is directed to a stent delivery system having an unexpanded state and an expanded state, a catheter having an elongated shaft connected to a distal end; and a stent, the stent having a generally tubular main body, the main body having a diameter, the main body defining an interior, a side branch opening, and a side branch assembly adjacent to the side branch opening, the side branch assembly comprising at least one ring, there being a distance between the main body and the at least one ring, in the unexpanded state the diameter of the main body being less than the diameter of the main body in the expanded state, in



## 5

the unexpanded state the distance being less than the distance in the expanded state; wherein the in the unexpanded state, the stent is disposed the distal end of the catheter.

BRIEF DESCRIPTION OF THE SEVERAL  
VIEWS OF THE DRAWINGS

The invention is best understood from the following detailed description when read in connection with accompanying drawings, in which:

FIG. 1 is an image of an unexpanded stent containing an unextended ring type telescoping bifurcation branch.

FIG. 2 is an image of an expanded stent containing an extended ring type telescoping bifurcation branch.

FIG. 3 is a close up view of an unextended ring type telescoping bifurcation branch.

FIG. 4 is a close up view of an extended ring type telescoping bifurcation branch.

FIG. 5 is an image of a single unextended telescoping ring.

FIG. 6 is an image of a single extended telescoping ring.

FIG. 7 is an image of an expanded stent containing an extended ring type telescoping bifurcation branch with a PTFE covering.

FIG. 8 is an image of an unexpanded stent containing an ratcheting unextended ring type telescoping bifurcation branch.

FIG. 9 is an image of an expanded stent containing an extended ratcheting ring type telescoping bifurcation branch.

FIG. 10 is an image of a single unextended ratcheting telescoping ring.

FIG. 11 is an image of a single extended ratcheting telescoping ring.

FIG. 12 is an image of a single unextended telescoping ring with a single tongue and groove locking mechanism.

FIG. 13 is an image of a single extended telescoping ring with a single tongue and groove locking mechanism.

FIG. 14 is an image of a single unextended telescoping ring with a multiple tongue and groove locking mechanism.

FIG. 15 is an image of a single extended telescoping ring with a multiple tongue and groove locking mechanism.

FIG. 16 is an image of the stent with added unengaged support structure.

FIG. 17 is an image of the stent with added engaged support structure.

FIG. 18 is an image of a stent delivery system with the expanded stent upon a catheter.

FIG. 19 is a close up view of an unextended ring type telescoping bifurcation branch in which the rings have a cloverleaf shape.

FIG. 20 is an image of the two ends of a single unextended telescoping ring with a single tongue and groove locking mechanism in which a portion of the mechanism has a thrombic material on its surface to glue the ring ends together.

FIG. 21 is an image of the end of the two ends of a single unextended telescoping ring with a "plus" shaped single tongue and groove locking mechanism.

FIG. 22 is an image of the end of the two ends of a single unextended telescoping ring with a conical shaped single tongue and groove locking mechanism.

FIG. 23 is an image of a single unextended telescoping ring with wire stops.

DETAILED DESCRIPTION OF THE INVENTION

The invention will next be illustrated with reference to the figures wherein the same numbers indicate similar elements in all figures. Such figures are intended to be illustrative rather

## 6

than limiting and are included herewith to facilitate the explanation of the apparatus of the present invention.

For the purposes of this disclosure, like reference numerals in the figures shall refer to like features unless otherwise indicated.

Depicted in the figures are various aspects of the invention. Elements depicted in one figure may be combined with, or substituted for, elements depicted in another figure as desired.

Referring now to FIG. 1 there is shown an embodiment of the invention featuring an undeployed substantially tubular stent 10 in an unexpanded state placed on a catheter shaft 20 positioned within a body vessel, the body vessel having a first vessel lumen 25 and a second vessel lumen 30 which forms bifurcation from the first vessel lumen 25. The stent 10 deployed within the first vessel lumen 25 and is oriented along a primary longitudinal axis 1 which is forms an angle oblique to the secondary longitudinal axis 2 running along the length of the second vessel lumen 30. Positioned adjacent to the second vessel lumen 30 is a ring type side branch assembly 40 engaged to the primary stent body 15 by at least one connector 42 at an engagement region 93. The surface of the primary stent body defines a primary circumferential plane 95. In the unexpanded state, the side branch assembly 40 is positioned substantially along the primary circumferential plane 95. For the purposes of this application, the term "oblique" refers to an angle of greater than zero degrees, such as an angle of between about 1 and about 180 degrees. An oblique angle explicitly includes angles of about 90 degrees.

Side branch assembly 40 in FIG. 1 features a number of unextended rings or ring members 41 connected by inter-ring connectors 43. Although this drawing shows five interconnected concentric ring members 41, this invention is not limited to this number or configurations and encompasses any similar device with one or more ring members 41. In one possible embodiment, the unextended ring members 41 can have dissimilar circumferences and/or can fit into each other in a concentric "target" like configuration. This invention is not limited to a concentric arrangement of the ring members and encompasses any and all possible configurations known to people of ordinary skill in the art including stacked ring members and overlapping "olympic" ring arrangements. This invention also contemplates ring members that have the same or different circumferences when in the unextended state.

Although FIG. 1 illustrates the rings as having a generally oval or circular shape, this invention encompasses possible embodiments in which at least one ring of the side branch assembly has a non-oval or non-circular shape. Some other possible shapes for the rings include but are not limited to ellipse, cloverleaf (as illustrated in FIG. 19), and angular. In addition any given ring need not have a uniform or symmetrical shape and can have an irregular region. Rings of different shapes or sizes can be combined to form the side branch assembly.

This invention encompasses a number of mechanisms for extending the ring members 41. One mechanism involves constructing the ring members to be biased towards naturally extending and then blocking this extension with a releasable restraint. One mechanism for releasing the restraint is by locating the restraint at the engagement region 93 and connecting it to a current detachment mechanism which will release the restraint when an electrical current is received. Similarly the side branch assembly 40 can also be constructed biased to telescope naturally and be held back by a releasable restraint.

One method of releasing a biased stent 10 and/or side branch assembly 40 is to remove a restraining sheath from the stent when ready for deployment. Another method is to use a



current detachment mechanism that will release a restraint and allow the ring members 41 to extend upon the receipt of an electrical current which degrades the integrity of a portion of the restraint. Current detachment mechanisms which are suitable for use in the present application may be similar to such mechanism that are known to be used in the deployment of GDC coils. Examples of such mechanisms are shown and described in U.S. Pat. Nos. 5,578,074, 5,669,905, 5,984,929, and 6,579,308; the entire contents of each being incorporated herein by reference.

In some embodiment specially shaped balloons or the use of two or more balloons can be used to extend ring members or to telescope the side branch assembly 40.

Referring now to FIG. 2 there is shown an embodiment of the invention in which the stent 10 is in the expanded state and the ring type side branch assembly 40 is telescoped and is completely deployed. In the deployed state the primary stent body 15 defines a primary lumen 91, has a diameter 4 which is greater than the diameter the stent 10 had in the unexpanded state, and defines a primary circumferential plane, a primary outer surface, and a primary lumen extending about and along the primary longitudinal axis 1. The deployed side branch assembly 40 has at least one telescoped ring member 41 extended into the second vessel lumen 30, and forms a second stent lumen 92 having a second circumferential plane 96 in fluid communication with the primary lumen 91 of the primary stent body 15. This second stent lumen 92 extends about and along a secondary longitudinal axis 2 at an oblique angle to the primary longitudinal axis 1.

This deployment can be accomplished by one or multiple balloons, self expansion, or by any other commonly known mechanism. The side branch assembly 40 can be telescoped before, after, or at substantially the same time that the ring members themselves are extended, and telescoping can occur before, after, or at substantially the same time as the expansion of the primary stent body 10. The ring bifurcation branch can also be telescoped by being fed into the side branch vessel 30 by guide wire 73 (not shown). Once in place, the separate guide wire 73 could have a separate locking mechanism to keep the rings in place. In this illustration all but one of the ring members 41 are extended to a larger circumference than they possessed when untelescoped. As mentioned before, all the ring members 41 need not be of differing circumferences or sizes before telescoping and this invention encompasses devices where any of the ring members 41 are designed to keep constant, increase, or decrease their circumference when telescoped. The side branch assembly 40 projects into the second vessel lumen 30 along a second longitudinal axis 2 which forms an angle with the primary longitudinal axis 1 and can be bent, curved, straight, or possess any number of configurations. The design of the side branch assembly 40 allows for the design of longer side branches branch than can be easily designed with petal type stent configurations.

In this illustration, the ring-ring connectors 43 are longer than they were when the bifurcation branch was untelescoped. This invention contemplates embodiments in which the ring-ring 43 and the ring-stent 42 connectors can also have particular characteristics to facilitate telescoping of the side branch assembly 40. These characteristics include: increasing connector lengths by using one or any combination of commonly known stent connector structures including S shaped connectors, bent connectors, flexible sinusoidal connectors, spring shaped connectors; bending and stretching connectors by constructing them out of flexible or expandable materials, spring shaped connectors, straightening curved connectors; and facilitating connector movement by including pivot mechanisms or engaging the connectors to the ring

members or primary stent body by rotating loops or rings. Connector rotation can also facilitate increasing the ring-ring distance.

Referring now to FIGS. 3 and 4 there are shown close up images of the ring type telescoping side branch assembly 40 made up of ring members 41 attached to the primary stent body 15 by connectors 42. The ring members 41 are also connected to each other by at least one inter-ring connector 43. FIG. 3 features an example of untelescoped ring members and FIG. 4 telescoped ring members.

FIG. 3 includes an untelescoped ring branch assembly 40 in which the unextended ring members 41 are positioned concentrically adjacent to each and within the primary circumferential plane 95. This is only one possible configuration and the ring members 41 can be of uniform size and or be positioned in a non-concentric configurations including laterally adjacent positioning. When the stent 10 is deployed in a body vessel, each ring member can have its circumference extend, contract, or remain constant as the vessel dimensions require. The ring members 41 can be designed to alter their circumference to either a pre-defined circumference or until they are blocked by the vessel walls. The length and shape of connectors 43 or 42 is one way of affecting how far the side branch assembly 40 can extend into the secondary vessel lumen 92. This invention also contemplates secondary lumens 92 having at least partially irregular circumferences and can be tapered (where the circumferences of a series of adjacent ring members 41 gradually and generally change in size).

FIG. 5 illustrates an embodiment of an extendable ring member 41 with an overlapping loop configuration. In this embodiment, the ring member 41 has a first ring end 60 and the second ring end 65 adjacent to each other. While unextended, the ring member 41 has an overlap region 45 which reduces the circumference. As the ring member extends, the length of the overlapping region 45 decreases, increasing the circumference. An optional cover 75 can be placed over the overlap region but is not a required component of this embodiment.

FIG. 6 illustrates an embodiment of an extended ring 41 where some of or all of the overlapped portion of FIG. 5 are no longer overlapping thus increasing the ring's circumference. The extent of the circumferential increase caused by the rings expansion can be controlled by the use of wire stops or stopping welds. FIG. 23 illustrates an unexpanded ring in which a wire stop 36 and a stopping weld 37 is added to the ring. As the ring expands and the overlap region 45 decreases, the wire stop 36 moves closer to the opposite ring end (60 or 65). At some point the wire stop 36 becomes caught and stops further ring expansion. In one possible embodiment, the wire stop 36 is stopped when it becomes caught on a stopping weld 37 which can be in the form of a cavity, a hook or other catching region of the cover 75. Although this illustration shows two wire stops on the ends (60, 65) of the rings one or more wire stops can be installed on any region of the ring. In addition, the wire stops can function with or without stopping welds 37 or a cover 75.

FIG. 7 illustrates an embodiment of the invention in which the rings 41 of the ring bifurcation branch 40 are engaged to a polymeric sheath 70. This sheath can be constructed out of a number of materials including PTFE (poly(tetrafluoroethylene)) and can be constructed with a variety of flexibility, structural strength, rigidity, and porosity characteristics. The sheath can be positioned within or without the ring members' circumference or the ring members can be an integrated component embedded within at least a portion of the sheath material. This embodiment also contemplates a plurality of sheath



layers made up of different materials, having different characteristics, or different positions. The sheath can be designed to fold open as the side branch **40** telescopes during deployment.

There are a number of possible mechanisms that can be used to lock an extended ring member into its final configuration and to assure that the ring member only extends (or contracts) in the desired direction and does not assume an undesired circumference. One of these mechanisms, illustrated in FIGS. **8**, **9**, **10** and **11** is a ratcheting ring. The ratcheting ring utilizes a locking mechanism used today to fix the circumference of rings locking wires together or sealing waste disposal bags, is commonly referred to as "cable ties", "tie wraps", or "zip ties" and is well known to people of ordinary skill in the art.

A side branch assembly **40** with this locking mechanism is illustrated in FIGS. **8** and **9**. These figures show ring members **41** with ratchet teeth **50** disposed about at least a portion of the ring member's perimeter and a locking mechanism **51**. When extending forces such as balloon pressure or self expansion cause the circumference of the ring member to change, the ratchet teeth **50** are capable of traversing the locking mechanism **51** in one direction but not in another fixing the resulting change in circumference. This mechanism can prevent an increase or a decrease in the size of the ring member **41** circumference. FIG. **8** illustrates unextended ratchet rings attached to an unexpanded stent body **15** and FIG. **9** illustrates extended ratchet rings telescoped into a second vessel body **30**.

FIG. **10** illustrates a close up view of a ratchet ring **41**. In it a ring member **41** has disposed about its circumference at least one ratchet tooth **50**. Ratchet teeth can be triangular, or angled in such a way that locking mechanism **51** can easily rotate about the perimeter in one direction but is blocked from moving in the opposite direction by the tooth/teeth **50**. As a result, the ring member **41** can be adjusted to assume a desired circumference and it will not revert back to its original circumference. FIG. **11** illustrates a ratchet ring after it has extended to a larger circumference.

Now referring to FIGS. **12** and **13**, there is shown an expandable ring member **41** with a single tongue groove locking mechanism. FIG. **12** illustrates the ring member **41** in an unextended state wherein there is an overlap region **45** reducing the ring member's circumference. When this ring member **41** extends as shown in FIG. **13**, the locking tongue **22** located on the first end **60** engages the groove **68** located on the ring member's second end **61**. In the extended state, by reducing or eliminating the overlap region **45** the ring member's circumference increases. The locking mechanisms **22** and **68**, prevent the ring from contracting once the extended circumference has been assumed.

There are a number of additional possible embodiments of the expandable ring member **41** with a single tongue groove locking mechanism. In one possible embodiment (as illustrated in FIG. **20**), at least a portion of the locking mechanism has an adhesive or thrombogenic material **71** on its surface capable of at least partially binding the interlocked ends **60**, **61** of the ring together. Although FIG. **20** illustrates the thrombogenic materials on specific regions of both ring ends, this embodiment encompasses thrombogenic materials on any region of either or both ring ends. In a second possible embodiment (as illustrated in FIG. **21**), the locking mechanism **22** comprises a pin with a plus shaped extension **76** which fits into and engages a groove **68** with a plus shaped socket **77**. In a third possible embodiment (as illustrated in FIG. **22**), the locking mechanism **22** comprises a pin with a

conical shaped extension **52** which fits into and engages a groove **68** with a cone shaped socket **53**.

Now referring to FIGS. **14** and **15**, there is shown an expandable ring with a multiple tongue groove locking mechanism. FIG. **14** illustrates the ring **41** in an unextended state wherein there is an overlap region **45** reducing the ring's circumference. When this ring extends as shown in FIG. **15**, the locking tongue **22** located on the first end **60** engages the grooves **88**. These grooves allow for a number of possible extended states with a reduced or eliminated overlap region **45**. The locking mechanisms **22** and **88** prevent the ring from contracting once the desired extended circumference has been assumed.

Referring now to FIGS. **16** and **17** are an embodiment of the stent in which there is added at least one structural support **34** with a support locking mechanism **33**. The support locking mechanism **33** can be a hook located at the end of the structural support **34** or can be located at any position along the length of the structural support **34**. The structural support **34** can be a wire or any flexible or curved material. In FIG. **16** the ring side branch assembly **40** has not yet telescoped so the structural support **55** has not yet engaged with the locking position **35** on the stent main body **15**. In FIG. **17** at least one ring member **41** has been telescoped and the locking mechanism **33** has engaged the locking position **35**. This structural support **34** can be used to both telescope the ring members **41** by pushing them out into the second vessel lumen **30** or they can be used to provide additional support connecting the side branch assembly **40** to the stent main body **10**. In addition the support structure can replace the stent-ring or ring-ring connectors.

Referring now to FIG. **18** there is shown a longitudinal cross-sectional view of an example of a stent delivery system **78** capable of delivering a bifurcated stent **10** with a side branch assembly having at least one ring member **41** and at least one ring-ring and/or ring-stent connector **43** to form a second fluid lumen **30**. The stent delivery system **78** includes a stent **10** disposed around the distal end of a catheter shaft **20**. The distal end of the catheter shaft **20** is inserted through the first vessel lumen **25** of the main stent body **20**. In this illustration the stent delivery system **78** is representative of a simple over-the-wire (OTW) or single-operator-exchange (SOE) angioplasty balloon catheter according to the invention. Such balloon catheters are discussed, for example, in commonly assigned U.S. Pat. Nos. 6,113,579, 6,517,515 and 6,514,228, each of which is incorporated by reference herein in its entirety. In this embodiment, the system also features a conventional OTW-type manifold assembly **72** connected to proximal end of catheter shaft assembly **20**. The catheter shaft assembly **20** includes an outer tube **74** coaxially disposed about inner tube **73** which defines a guide wire lumen **77** and a distal end about which is disposed balloon **79**. During deployment, the balloon **79** is inflated, thus expanding the stent at the lesion site. This is only an illustration of such a catheter assembly and is not intended to limit the scope of the present invention. This invention also encompasses stent delivery systems which do not contain a balloon expanding attributes such as self expanding stents or fixed wire systems. Numerous structures are known to those of skill in the art, any of which may be employed herein.

In some embodiments the stent, its delivery system, or other portion of an assembly may include one or more areas, bands, coatings, members, etc. that is (are) detectable by imaging modalities such as X-Ray, MRI, ultrasound, etc. In some embodiments at least a portion of the stent and/or adjacent assembly is at least partially radiopaque. In some embodiments the delivery system of the side deployment



## 11

mechanism includes balloon inflation, self expansion, and guide wire pushing or pulling.

In some embodiments at least a portion of the stent is configured to include one or more mechanisms for the delivery of a therapeutic agent. Often the agent will be in the form of a coating or other layer (or layers) of material placed on a surface region of the stent, which is adapted to be released at the site of the stent's implantation or areas adjacent thereto.

A therapeutic agent may be a drug or other pharmaceutical product such as non-genetic agents, genetic agents, cellular material, etc. Some examples of suitable non-genetic therapeutic agents include but are not limited to: anti-thrombogenic agents such as heparin, heparin derivatives, vascular cell growth promoters, growth factor inhibitors, Paclitaxel, etc. Where an agent includes a genetic therapeutic agent, such a genetic agent may include but is not limited to: DNA, RNA and their respective derivatives and/or components; hedgehog proteins, etc. Where a therapeutic agent includes cellular material, the cellular material may include but is not limited to: cells of human origin and/or non-human origin as well as their respective components and/or derivatives thereof. Where the therapeutic agent includes a polymer agent, the polymer agent may be a polystyrene-polyisobutylene-polystyrene triblock copolymer (SIBS), polyethylene oxide, silicone rubber and/or any other suitable substrate.

This completes the description of the preferred and alternate embodiments of the invention. The above disclosure is intended to be illustrative and not exhaustive. This description will suggest many variations and alternatives to one of ordinary skill in this art. The various elements shown in the individual figures and described above may be combined, substituted, or modified for combination as desired. All these alternatives and variations are intended to be included within the scope of the claims where the term "comprising" means "including, but not limited to".

Further, the particular features presented in the dependent claims can be combined with each other in other manners within the scope of the invention such that the invention should be recognized as also specifically directed to other embodiments having any other possible combination of the features of the dependent claims. For instance, for purposes of claim publication, any dependent claim which follows should be taken as alternatively written in a multiple dependent form from all prior claims which possess all antecedents referenced in such dependent claim if such multiple dependent format is an accepted format within the jurisdiction (e.g. each claim depending directly from claim 1 should be alternatively taken as depending from all previous claims). In jurisdictions where multiple dependent claim formats are restricted, the following dependent claims should each be also taken as alternatively written in each singly dependent claim format which creates a dependency from a prior antecedent-possessing claim other than the specific claim listed in such dependent claims below.

The invention claimed is:

1. A bifurcated stent being expandable from an unexpanded state to an expanded state, wherein in the unexpanded state the stent has a diameter less than that of the diameter in the expanded state, the bifurcated stent comprising:

a substantially tubular primary body defining a primary circumferential plane, a primary outer surface, a primary lumen and having a primary longitudinal axis extending therethrough;

a side branch assembly engaged to the primary body, the side branch assembly comprising a plurality of ring members, adjacent ring members being engaged one to the other by at least one connector, in the unexpanded

## 12

state the plurality of ring members being positioned substantially within the primary circumferential plane, in the expanded state the plurality of ring members being positioned external to the primary circumferential plane and defining a secondary lumen, and having a secondary longitudinal axis extending therethrough, the secondary lumen being in fluid communication with the primary lumen, the secondary longitudinal axis forming an angle with the primary longitudinal axis,

wherein the plurality of ring members are generally circular, and

wherein the ring members have an unexpanded circumference in the unexpanded state and at least two of the plurality of ring members have substantially the same unexpanded circumference.

2. The stent of claim 1 wherein the ring members have an expanded circumference in the expanded state, wherein the expanded circumference is greater than the unexpanded circumference.

3. The stent of claim 2 wherein the ring members are constructed and arranged to self expand from the unexpanded circumference to the expanded circumference.

4. The stent of claim 2 wherein the ring members are engaged to the primary body by at least one engagement region, the at least one engagement region having an engaged state and a released state, in the engaged state the at least one ring member being retained in the unexpanded state and in the released state the at least one ring member being released to expand to the expanded state.

5. The stent of claim 1 wherein the at least one connector has a first end, a second end and a length therebetween, each end being flexibly engaged to one of the rings.

6. The stent of claim 1 wherein the at least one of the expanded state and the unexpanded state of at least two ring members have differing circumferences.

7. The stent of claim 1 wherein the secondary lumen comprises a length and a diameter, the diameter tapering along at least a portion of the length.

8. A bifurcated stent being expandable from an unexpanded state to an expanded state, wherein in the unexpanded state the stent has a diameter less than that of the diameter in the expanded state, the bifurcated stent comprising:

a substantially tubular primary body defining a primary circumferential plane, a primary outer surface, a primary lumen and having a primary longitudinal axis extending therethrough;

a side branch assembly engaged to the primary body, the side branch assembly comprising a plurality of ring members, adjacent ring members being engaged one to the other by at least one connector, in the unexpanded state the plurality of ring members being positioned substantially within the primary circumferential plane, in the expanded state the plurality of ring members being positioned external to the primary circumferential plane and defining a secondary lumen, and having a secondary longitudinal axis extending therethrough, the secondary lumen being in fluid communication with the primary lumen, the secondary longitudinal axis forming an angle with the primary longitudinal axis,

wherein the ring members have an unexpanded circumference in the unexpanded state and at least two of the plurality of ring members have substantially the same unexpanded circumference.

9. The stent of claim 8, wherein the connectors are substantially straight in both the unexpanded state and the expanded state.



10. The stent of claim 8, wherein the at least one of the expanded state and the unexpanded state of at least two ring members have differing circumferences.

11. The stent of claim 8, wherein in the unexpanded state the plurality of ring members are concentrically arranged relative to one another.

\* \* \* \* \*