



US008439154B1

(12) **United States Patent**
Lewis et al.

(10) **Patent No.:** **US 8,439,154 B1**
(45) **Date of Patent:** ***May 14, 2013**

(54) **AIR-FILM VIBRATION DAMPING
APPARATUS FOR WINDOWS**

(75) Inventors: **Thomas M. Lewis**, Hamilton, OH (US);
Michael L. Parin, Mishawaka, IN (US)

(73) Assignee: **Damping Technologies, Inc.**,
Mishawaka, IN (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **13/331,999**

(22) Filed: **Dec. 20, 2011**

Related U.S. Application Data

(62) Division of application No. 11/580,791, filed on Oct.
13, 2006, now Pat. No. 8,082,707.

(51) **Int. Cl.**
F16F 7/00 (2006.01)
B64C 1/14 (2006.01)

(52) **U.S. Cl.**
USPC **181/207**; 181/208; 244/129.3; 296/96.14;
52/204.593; 52/786.13

(58) **Field of Classification Search** 52/204.593,
52/786.11, 786.12, 786.13, 171.2, 171.3;
244/129.3; 181/207, 208; 296/96.14
See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

2,379,194 A * 6/1945 Shonts et al. 52/208
2,409,808 A * 10/1946 Sowle 52/309.3
2,444,976 A 7/1948 Brown 359/361

2,473,616 A 6/1949 Basil 244/129.3
2,912,724 A 11/1959 Wilkes 52/302.3
3,191,240 A 6/1965 Slaman et al. 52/204.5
3,343,317 A 9/1967 Cripe 52/208
3,429,530 A * 2/1969 Heinrich 244/129.3
3,553,913 A * 1/1971 Eisenberg 52/172

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 047 725 A1 3/1982
FR 889568 1/1943
GB 2 026 622 A 2/1980
JP 61181794 8/1986

OTHER PUBLICATIONS

Chow, L.C. And Pinnington, R.J., "Practical Industrial Method of
Increasing Structural Damping in Machinery, I: Squeeze-Film
Damping With Air," Journal of Sound and Vibration, 1987, vol.
118(1), pp. 123-139.

(Continued)


Primary Examiner — Robert Canfield

(74) *Attorney, Agent, or Firm* — Frederick H. Gribbell

(57) **ABSTRACT**

An improved vibration damping apparatus is provided for use
with window structures, including windows used in vehicles,
aircraft, and spacecraft. The vibration damping system
includes at least two separate layers of solid material that are
typically substantially clear at visible wavelengths, in which
the two layers are spaced-apart by a predetermined distance to
form a space or gap therebetween. This gap will be of a size
and shape to enhance vibration damping when it is filled with
a gaseous compound, such as air. The air-film vibration
damping system created by the above structure can be applied
to an external pane of a window structure, or to the interior
pane of a window structure, or perhaps to both an exterior
pane and an interior pane of the same window structure, if
desired.

11 Claims, 7 Drawing Sheets



U.S. PATENT DOCUMENTS

3,953,630	A	4/1976	Roberts et al.	428/38	6,260,317	B1 *	7/2001	Fisher	52/306
4,114,342	A *	9/1978	Okawa	52/786.13	6,328,532	B1	12/2001	Hahnle	
4,316,404	A	2/1982	Medlin	89/36.08	6,514,040	B2	2/2003	Lewis et al.	
4,333,292	A	6/1982	Musgrave	52/404.2	6,787,204	B2	9/2004	Chaussade et al.	428/34
4,456,335	A *	6/1984	Mumford	349/16	6,793,990	B1	9/2004	Sakaguchi et al.	428/34
4,460,314	A	7/1984	Fuller		6,802,162	B1 *	10/2004	Fisher	52/306
4,622,249	A	11/1986	Bowser		6,830,791	B1 *	12/2004	Misonou et al.	428/34
4,776,763	A	10/1988	Light		6,886,297	B1 *	5/2005	Crandell	52/172
4,829,729	A	5/1989	Derner et al.		6,905,094	B2	6/2005	Dazet et al.	244/129.3
4,932,608	A	6/1990	Heidish et al.		7,266,930	B1 *	9/2007	Fisher	52/306
4,941,302	A	7/1990	Barry	52/171.3	7,552,896	B2	6/2009	Coak	244/129.3
5,005,557	A	4/1991	Bachli	126/572	7,721,844	B1	5/2010	Lewis et al.	181/207
5,009,218	A	4/1991	Bachli	126/714	7,763,334	B2 *	7/2010	Berkowitz	428/34
5,119,608	A *	6/1992	Glover et al.	52/171.3	7,845,142	B2 *	12/2010	Theios	52/786.1
5,120,584	A	6/1992	Ohlenforst et al.	428/34	7,856,770	B2 *	12/2010	Grassmuck et al.	52/204.593
5,154,953	A	10/1992	De Moncuit et al.	428/34	8,033,505	B2 *	10/2011	Wieting	244/129.3
5,169,694	A	12/1992	Endo et al.	428/34	8,082,707	B1 *	12/2011	Lewis et al.	52/204.593
5,227,206	A	7/1993	Bachli	428/34	2003/0234322	A1	12/2003	Bladt et al.	244/129.3
5,232,344	A	8/1993	El-Aini		2004/0238690	A1	12/2004	Wood et al.	244/129.3
5,255,473	A *	10/1993	Kaspar et al.	49/501	2006/0118676	A1 *	6/2006	Novak et al.	244/129.1
5,271,581	A	12/1993	Irish	244/129.3	2007/0069080	A1	3/2007	Rassaian et al.	
5,343,619	A	9/1994	Lardellier		2007/0148379	A1 *	6/2007	Theios et al.	428/34
5,407,321	A	4/1995	Rimkunas et al.						
5,584,662	A	12/1996	Mannava et al.						
5,636,484	A *	6/1997	DeBlock	52/204.5					
5,732,517	A *	3/1998	Milikovsky	52/171.3					
5,766,755	A	6/1998	Chaussade et al.	428/332					
5,820,343	A	10/1998	Kraft et al.						
5,820,348	A	10/1998	Fricke						
5,846,057	A	12/1998	Ferrigno et al.						
6,155,789	A	12/2000	Mannava et al.						
6,199,933	B1	3/2001	Gielda	296/96.14					
6,203,269	B1	3/2001	Lorber et al.						
6,224,339	B1	5/2001	Rhodes et al.						
6,224,341	B1	5/2001	Fricke						
6,238,187	B1	5/2001	Dulaney et al.						

OTHER PUBLICATIONS

Fox, M.J.H. and Whitton, P.N., "The Damping of Structural Vibration By Thin Gas Films," Journal of Sound and Vibration, 1980, vol. 73(2), pp. 279-295.

Chow, L.C. And Pinnington, R.J., "Practical Industrial Method of Increasing Structural Damping in Machinery, II: Squeeze-Film Damping With Liquids," Journal of Sound and Vibration, 1989, vol. 128(2), pp. 333-347.

Jones, D.I.G., Lewis, T., and Michael, C., "Partial Coverage Air Film Damping of Cantilever Plates," Journal of Sound and Vibration, 1997, vol. 208(5), pp. 869-875.

* cited by examiner




FIG. 1 (PRIOR ART)




FIG. 2 (PRIOR ART)




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6




FIG. 7







FIG. 8



1

AIR-FILM VIBRATION DAMPING
APPARATUS FOR WINDOWSCROSS-REFERENCE TO RELATED
APPLICATIONS

The present application is a divisional to application Ser. No. 11/580,791, titled "AIR-FILM VIBRATION DAMPING APPARATUS FOR WINDOWS," filed on Oct. 13, 2006, now U.S. Pat. No. 8,082,707.

TECHNICAL FIELD

The present invention relates generally to vibration damping equipment and is particularly directed to air-film damping devices of the type which can damp mechanical and/or acoustic vibrations in windows. The invention is specifically disclosed as an aircraft window damping system that employs air-film damping technology to increase damping in the window structure.

BACKGROUND OF THE INVENTION

Windows of vehicles and aircraft typically have a relatively large surface area and, therefore, have good acoustic radiation efficiency. The resonance response of such window structures results in significant vibration and acoustic energy which typically contributes significantly to the interior noise in automobiles or other vehicles, and in aircraft cabins. Particularly for aircraft, turbulent air flow at the exterior surfaces of the fuselage skin and the exterior surfaces of the windows tends to excite these resonances.

In typical conventional aircraft, the windows have low-to-moderate inherent damping. An efficient countermeasure for the resonance response of a structure is to increase the effective damping, and in the case of windows, the optical quality of the window typically should be substantially maintained. It may be permissible to degrade the optical quality by a small amount, or perhaps for small surface areas, but in general the optical quality should not noticeably vary if damping is added to a window structure.

One conventional aircraft window is depicted in FIG. 1, generally designated by the reference numeral 10. This window structure 10 has an outer pane 12 that comprises stretched acrylic material, about 0.31 inches in thickness. A second pane 14 is also made of stretched acrylic material, and in this structure it is about 0.19 inches in thickness. Between the two panes 12 and 14 is an air gap, generally designated by the reference numeral 18. In this particular window structure the air gap is about 0.26 inches across, which is the distance that these two panes are spaced-apart from one another.

The edges of these two panes 12 and 14 are coated and sealed by silicone material, at 16. The window 10 is an example of a structure seen in some contemporary commercial passenger aircraft. In conventional windows as depicted in FIG. 1, the thicker pane 12 is the exterior pane for the window, while the thinner pane 14 faces the interior of the fuselage or cabin. In many of the conventional windows such as this, the interior pane 14 has a vent hole that tends to equalize the pressure on both sides of the pane 14.

A second type of aircraft window is depicted in FIG. 2, generally designated by the reference numeral 20. A first pane of material at 22 is made of thermal tempered glass, about 0.50 inches in thickness. This is the thicker pane, which could face (be in contact with) the environment to the exterior of the aircraft, or it could be used as the inner window structure, i.e., as the interior cabin pane. A second pane of thermal tempered

2

glass is located at 24, and in this conventional window 20, the pane 24 is about 0.19 inches in thickness. Even though this pane 24 is less thick, it may be used as an exterior pane if desired, and it can be coated with a rain repellent coating on its outermost surface.

Instead of an air gap, a vinyl interlayer 26 separates the two glass panes 22 and 24. In this window 20, the vinyl interlayer is about 0.38 inches in thickness. There are also two urethane interlayers 28 that are about 0.02 inches in thickness. One of the urethane interlayers is between the outer pane 24 and the vinyl interlayer 26, while a second urethane interlayer is between the interior glass pane 22 and the vinyl interlayer 26. This window structure 20 also includes a conductive heating film 23 that is located on the inboard surface of the glass ply (or pane) 24.

The conventional window 20 includes other supporting structures that hold together the layers described above. A stainless steel Z-bar is positioned at 30, and tends to hold in place the outer glass pane 24 and the vinyl interlayer 26, in which a layer of sealant is disposed therebetween. The sealant layer is generally disposed at 32, and may comprise a type of sealant known as "PR 1425."

An aluminum spacer member 40 is used as a support for the entire window structure 20. A silicone gasket 34 is placed on the outer surface of the Z-bar 30 and the aluminum spacer member 40. A metal insert 42 is placed within the vinyl interlayer 26, and makes contact with the aluminum spacer member 40. An edge filler structure made of phenolic is illustrated at 44, which tends to hold the inner pane 22 in place with the spacer member 40 and the vinyl interlayer 26.

Both of the conventional windows described above do not use any particular form of air-film vibration damping. The window structure 10 of FIG. 1 has a large air gap 18 which would not be particularly useful for air-film vibration damping, while the window structure 20 of FIG. 2 has no particular air gap at all.

It would be an improvement to add a form of vibration damping (or acoustic radiation damping) to the windows of vehicles and aircraft (or spacecraft for that matter). The higher the speed of the vehicle/aircraft/spacecraft, the more important that sufficient vibration damping of window structures may become.

SUMMARY OF THE INVENTION

Accordingly, it is an advantage of the present invention to provide a vibration damping system that can reduce the acoustic energy and/or vibrational energy of window structures, including windows used in vehicles, aircraft, spacecraft, and even vessels.

It is another advantage of the present invention to provide a vibration damping system in which a space is formed between two layers of material in a window structure, in which this space has predetermined dimensions to enhance air-film vibration damping of acoustic energy and/or vibrational energy in the window structure.

It is still another advantage of the present invention to provide a vibration damping system for window structures which uses a gaseous material as a vibration damping medium, within a space of predetermined dimensions that is part of the window structure.

It is a further advantage of the present invention to provide a vibration damping system for window structures using a gaseous material within a space of predetermined dimensions, and in which at least a portion of the window structure

3

is essentially optically clear, whereas a portion of the window structure may not be substantially clear at optical wavelengths.

It is still a further advantage of the present invention to provide a vibration damping system for window structures that includes a predetermined space between at least two layers of window structure material, in which one of the window structures exhibits an opening that extends completely therethrough for pressure equalization.

It is yet a further advantage of the present invention to provide a vibration damping system for window structures that includes a space of a predetermined dimension between at least two window structures, in which the space has a gaseous material therewithin, and in which the gaseous material is pressurized.

Additional advantages and other novel features of the invention will be set forth in part in the description that follows and in part will become apparent to those skilled in the art upon examination of the following or may be learned with the practice of the invention.

To achieve the foregoing and other advantages, and in accordance with one aspect of the present invention, a vibration damping system is provided, which comprises: a first window structure; a second window structure that is spaced-apart from the first window structure by a first distance, in an arrangement by which at least portions of the first and second window structures are substantially parallel to one another; wherein the first window structure comprises a single layer of material that is substantially transparent at optical wavelengths for humans; wherein the second window structure comprises two separate layers of material that are both substantially transparent at visible optical wavelengths for humans, the two separate layers being spaced-apart from one another by a second distance in an arrangement by which at least portions of the two separate layers are substantially parallel to one another, thereby forming a space between the two separate layers of material of the second window structure in which the space includes a gaseous material; and wherein the second distance is significantly less than the first distance, and the second distance is of a size that provides air-film vibration damping for the second window structure.

In accordance with another aspect of the present invention, a vibration damping system is provided, which comprises: a first window structure; a second window structure that is spaced-apart from the first window structure by a first distance, in an arrangement by which the first and second window structures are substantially parallel to one another; wherein the first window structure comprises a first grouping of two separate layers of material that are both substantially transparent at visible optical wavelengths for humans, the first grouping of two separate layers being spaced-apart from one another by a second distance in an arrangement by which at least portions of the first grouping of two separate layers are substantially parallel to one another, thereby forming a first space between the first grouping of two separate layers of material of the first window structure in which the first space includes a gaseous material; wherein the second window structure comprises a second grouping of two separate layers of material that are both substantially transparent at visible optical wavelengths for humans, the second grouping of two separate layers being spaced-apart from one another by a third distance in an arrangement by which at least portions of the second grouping of two separate layers are substantially parallel to one another, thereby forming a second space between the second grouping of two separate layers of material of the second window structure in which the second space includes a gaseous material; and wherein the second distance

4

is significantly less than the first distance, the third distance is significantly less than the first distance, the second distance is of a size that provides air-film vibration damping for the first window structure; and the third distance is of a size that provides air-film vibration damping for the second window structure.

In accordance with yet another aspect of the present invention, a vibration damping system is provided, which comprises: a window structure that comprises two separate layers of material that are both substantially transparent at visible optical wavelengths for humans, the two separate layers being spaced-apart from one another by a first distance in an arrangement by which at least portions of the two separate layers are substantially parallel to one another, thereby forming a space between the two separate layers of material of the window structure in which the space includes a gaseous material; wherein the first distance is less than one-quarter inch (6.3 mm) so as to provide air-film vibration damping for the window structure.

Still other advantages of the present invention will become apparent to those skilled in this art from the following description and drawings wherein there is described and shown a preferred embodiment of this invention in one of the best modes contemplated for carrying out the invention. As will be realized, the invention is capable of other different embodiments, and its several details are capable of modification in various, obvious aspects all without departing from the invention. Accordingly, the drawings and descriptions will be regarded as illustrative in nature and not as restrictive.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings incorporated in and forming a part of the specification illustrate several aspects of the present invention, and together with the description and claims serve to explain the principles of the invention. In the drawings:

FIG. 1 is a view looking parallel to the plane of a conventional aircraft window, in cross-section.

FIG. 2 is a view looking parallel to the plane of a different style conventional aircraft window, in cross-section.

FIG. 3 is a view in cross-section of a test fixture holding a window constructed according to the principles of the present invention, looking down the plane of the window.

FIG. 4A is a graph showing a frequency response of vibrational mobility of a first curve showing the response of a conventional window as a measured baseline, and a second curve showing the response of a first example window constructed according to the principles of the present invention as a "measured damped-outboard" structure.

FIG. 4B is a graph showing a frequency response of vibrational mobility of a second curve showing the response of a conventional window as a measured baseline, and a second curve showing the response of a second example window constructed according to the principles of the present invention as a "measured damped-inboard" structure.

FIG. 5 is a cross-section view of a window constructed according to the principles of the present invention, looking down the plane of the window structure, in which an intermediate window pane is positioned near an exterior window pane, thereby forming a vibration damping system using air-film vibration damping according to the present invention.

FIG. 6 is a cross-section view of a window constructed according to the principles of the present invention, looking down the plane of the window structure, in which an intermediate window pane is positioned near an interior window

5

pane, thereby forming a vibration damping system using air-film vibration damping according to the present invention.

FIG. 7 is a cross-section view of a window constructed according to the principles of the present invention, looking down the plane of the window structure, in which a first intermediate window pane is positioned proximal to an exterior window pane to form a first vibration damping system, and a second intermediate pane is positioned proximal to an interior window pane, thereby forming a second vibration damping system, both using air-film vibration damping according to the present invention.

FIG. 8 is a cross-section view of a window constructed according to the principles of the present invention, in which an intermediate layer of material is positioned against an interior window structure, but is also positioned in a spaced-apart relationship to an exterior window pane, thereby forming an air-film vibration damping system according to the present invention.

FIG. 9 is a cross-section view of a window constructed according to the principles of the present invention, in which an intermediate layer of material is positioned proximal to an exterior window pane to form an air-film vibration damping system therewith, in which the intermediate layer is not perfectly planar.

FIG. 10 is a cross-section view of a window constructed according to the principles of the present invention, in which an intermediate layer of material is positioned proximal to an exterior window pane to form an air-film vibration damping system therewith, in which the intermediate layer is not perfectly planar, and in which the intermediate layer does not exhibit the same thickness throughout.

FIG. 11 is a cross-section view of a window constructed according to the principles of the present invention, in which an intermediate layer of material is positioned proximal to an exterior window pane to form an air-film vibration damping system therewith, in which the intermediate layer is not perfectly planar, and the intermediate layer is configured to bend in an opposite direction as compared to that of FIG. 9.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Reference will now be made in detail to the present preferred embodiment of the invention, an example of which is illustrated in the accompanying drawings, wherein like numerals indicate the same elements throughout the views.

Referring now to FIG. 3, a window structure generally designated by the reference numeral 100 is depicted in a configuration in which it could be used as a window in an aircraft fuselage. In FIG. 3, a test fixture is used to hold various portions of the window structure together, in which the test fixture simulates the side or edge structural members of an aircraft window as part of the fuselage of the aircraft.

A first window pane 112 is constructed substantially in parallel to a second spaced-apart window pane (or platelet) 114. The spaced-apart relationship results in a gap 118 between the two surfaces that face each other of the window panes 112 and 114. In this example embodiment, the window pane 112 is made of cast acrylic sheet material, about 0.36 inches in thickness, and the window pane 114 is made of cast acrylic sheet of about 0.105 inches in thickness. Note, however, that the thickness of pane 114 can be made either lesser or greater, for use in the present invention. For example, the thickness of pane 114 could be in the range of 0.050 inches (1.27 mm) to 1.00 inches (25.4 mm); thicknesses outside this range are also possible.

6

The gap 118 will have a dimension "G" that is related to appropriate air-film vibration damping of acoustic energy and/or mechanical vibrations that otherwise would be generated in these window structures. In one exemplary embodiment, this gap 118 could be as small as 0.006 inches; however, other gap dimensions also will work well for this invention. For example, the dimension G of gap 118 could be in the range of 0.001 inches (0.025 mm) to 0.050 inches (1.27 mm), inclusive; gap distances outside this range are also possible, for example up to one-quarter inch (6.3 mm). In FIG. 3, the dimension G of the gap 118 is controlled by an aluminum shim 122 that is provided as part of the test fixture.

The rest of the test fixture in FIG. 3 comprises a first aluminum boundary frame 120 and a second aluminum boundary frame 124, that are both held together and abutted by a rather large nut and bolt, in which the bolt is depicted at 130 and the nut at 132.

It will be understood that the types of materials used for windows according to the vibration damping system of the present invention can vary considerably as desired by the system designer, without departing from the principles of the present invention. Moreover, the aluminum members of the test fixture depicted in FIG. 3 are simply used to provide rigid support for the window structure members, and other sizes and shapes of materials could be used, and moreover other types of materials could be used, all without departing from the principles of the present invention. Several examples are discussed below.

It will also be understood that the gaseous compound(s) used within the "air gap" 118 do not necessarily have to be atmospheric air. For example, in jet aircraft flying at high altitudes, the "air gap" may have a pressure equalizer structure (e.g., a small opening) to the internal cabin pressure, and in that situation the gas within air gap 118 would comprise the enriched oxygen used in pressurized aircraft cabins. Even if the "air gap" is completely sealed, the gas used therein may comprise elements or compounds that do not meet the normal definition of atmospheric air, but would still fall within the principles of the present invention. Therefore, in this patent document, a reference to the "air" within this space or "air gap" are not restricted to typical "air" compounds.

Referring now to FIG. 4A, a graph of mobility (in inches per second per pound) versus frequency (in Hz) is illustrated for a first example window structure constructed according to the principles of the present invention. The overall graph is generally depicted by the reference numeral 50, in which one of the curves (i.e., reference numeral 52) represents the mobility of a baseline window structure that is constructed according to conventional means and materials, and a second curve 54 that represents the mobility of a damped window structure that is similar to that depicted in FIG. 3, along with the test fixture of FIG. 3. In the graph 50, a specific test was performed assuming that the window structure 114 was associated with an one of the panes of an aircraft window in an aircraft fuselage.

As can be seen from inspecting the curves 52 and 54 of graph 50, there is a significant reduction of the vibrational mobility in the frequency range of zero Hertz to 6,000 Hz, particularly in the range between 1,000 Hz and 6,000 Hz. This range is indicated by the reference numeral 60 on FIG. 4A. The lower frequencies, in the range from zero to 1,000 Hz, also exhibit improvement in the measured vibrational mobility characteristics of this window structure, which is represented by the reference numeral 62 on FIG. 4A.

The graph 50 does not extend higher than 6,000 Hz, however, the air-film vibration damping technology of the present invention can significantly increase the vibration damping in

such window structures at higher frequencies as well, including through a frequency range of zero Hz through 15,000 Hz, inclusive. This provides significant reduction of vibration and acoustic noise in a major portion of the human hearing range. The air-film vibration damping system provides a damping mechanism related to the relative transverse cyclic motion (due to modal velocities) between upper and lower structure surfaces, above and below a thin gap that is filled with a gaseous substance, such as air. The transverse cyclic motion forces the gas to cyclically flow within the gap, and the air flow essentially becomes viscous if the gap dimensions are chosen appropriately. The cyclic pressure variations arising from this air flow provide the damping mechanism. Similar air-film vibration damping systems have been successfully demonstrated in other types of structures, including aircraft turbine engine fan blades (see U.S. Pat. No. 6,514,040 co-assigned to Damping Technologies, Inc. of Mishawaka, Ind., which is incorporated herein by reference in its entirety). It should be noted that the typical speech interference level (SIL) frequency range is 355 Hz to 5,600 Hz. As can be seen from the above, the air-film vibration damping provided by the vibration damping system of the present invention can be of major benefit for a large portion of this SIL range.

Referring now to FIG. 4B, a graph of mobility (in inches per second per pound) versus frequency (in Hz) is illustrated for a second example window structure constructed according to the principles of the present invention. The overall graph is generally depicted by the reference numeral 80, in which one of the curves (i.e., reference numeral 82) represents the mobility of a baseline window structure that is constructed according to conventional means and materials, and a second curve 84 that represents the mobility of a damped window structure that is similar to that depicted in FIG. 3, along with the test fixture of FIG. 3. In the graph 80, a specific test was performed assuming that the window structure 114 was associated with one of the panes of an aircraft window in an aircraft fuselage. Note that this graph 80 is based on a window structure with different dimensional characteristics (as discussed below) than the window structure that was the basis for the graph 50 (of FIG. 4A). Moreover, the window material for panes 112 and 114 was clear polycarbonate for the test results of graph 80.

As can be seen from inspecting the curves 82 and 84 of graph 80, there is a significant reduction of the vibrational mobility in the frequency range of zero Hertz to 6,000 Hz. The attenuation in vibrational mobility ranges from a factor of about 5.0 to a factor of about 10.0, as a reduction in this mobility for resonances in the low frequency range. Similar attenuation also can be seen for particular high-order dynamics in the FRF (frequency response function) spectrum. It is anticipated that such attenuation will yield significant benefits in the sound pressure radiated from the window structure.

The graph 80 does not extend higher than 6,000 Hz, however, the air-film vibration damping technology of the present invention can significantly increase the vibration damping in such window structures at higher frequencies as well, including through a frequency range of zero Hz through 15,000 Hz, inclusive. As discussed above, this provides significant reduction of vibration and acoustic noise in a major portion of the human hearing range.

Referring now to FIG. 5, a window vibration damping structure generally designated by the reference numeral 200 is illustrated as having a first pane of glass (or other substantially transparent material) 210, a second pane of glass (or other substantially transparent material) 212, and a third intermediate layer of material 214. In this FIG. 5, the pane 210

is considered to be the exterior structure, and is in communication with outside air (i.e., the exterior environment) represented by the reference numeral 224. The inner pane is at 212, and if this window structure 200 is part of an aircraft fuselage, the space at reference numeral 226 would be the interior cabin air within the fuselage.

In FIG. 5, the intermediate layer 214 is positioned proximal to the outer pane 210, and is spaced-apart by a gap at reference numeral 220. There is a larger gap 222 between the interior pane 212 and the intermediate pane or structure 214. The gap between the outer pane 210 and the intermediate pane 214 is referred to as "G1", the gap between the intermediate pane 214 and the interior pane 212 is referred to as "G2", and the overall gap between the two main window structural members 210 and 212 is given by the gap dimension "G3".

The thickness of the exterior pane (or window structure) 210 is given by the dimension "d1" on FIG. 5, the thickness of the interior pane (or window structure) 212 is given by the dimension "d2", while the thickness of the intermediate pane (or structure) 214 on FIG. 5 is given by the dimension "d3".

In a first exemplary embodiment of the present invention, the thickness of the pane 210 could be about 0.36 inches (i.e., dimension d1), and the thickness of the interior pane 212 could also have a thickness of about 0.36 inches (the dimension d2). The thickness of the intermediate member 214 could have a dimension of about 0.105 inches (2.7 mm), i.e., at dimension d3. The gap G1 could have a dimension of about 0.005 to 0.006 inches (0.127 mm to 0.152 mm), and the overall "gap" G3 could be about 0.5 inches. This would then leave a gap dimension G2 of about 0.389 to 0.390 inches.

With these dimensions (of the first exemplary embodiment), this type of structure could provide results similar to the frequency response illustrated in the graph 50 of FIG. 4A, for a window size of about 20×20 inches. The "gap" dimension G1 represents a predetermined dimension or distance that creates a narrow space or volume that is designed to provide additional vibration damping characteristics by the installation of the intermediate member 214 in fairly close proximity to the exterior glass or acrylic (or other substance) member 210.

In actual use, the intermediate (or third) layer of material 214 would likely have a vent hole (e.g., at 216) to allow pressure to equalize on both sides of its structure, i.e., the areas at reference numerals 220 and 222. As can be seen from the above dimensional information, this layer 214 will typically be fairly "thin" in construction, and thus will not be expected to carry a differential pressure loading. The relative "thinness" of element 214 will usually aid in providing the air-film damping characteristic for this window structure 200.

In a second exemplary embodiment of the present invention, the thickness of the pane 210 could be about 0.36 inches (i.e., dimension d1), and the thickness of the interior pane 212 could also have a thickness of about 0.36 inches (the dimension d2). The thickness of the intermediate member 214 could have a dimension of about 0.210 to 0.214 inches (5.3 mm to 5.4 mm), i.e., at dimension d3. The gap G1 could have a dimension of about 0.016 inches (0.41 mm), and the overall "gap" G3 could be about 0.5 inches. This would then leave a gap dimension G2 of about 0.270 to 0.274 inches.

With these dimensions (of the second exemplary embodiment), this type of structure could provide results similar to the frequency response illustrated in the graph 50 of FIG. 4B, for a window size of about 11×16 inches. As above, the "gap" dimension G1 represents a predetermined dimension or distance that creates a narrow space or volume that is designed to provide additional vibration damping characteristics by the

installation of the intermediate member **214** in fairly close proximity to the exterior member **210**.

It will be understood that all of the dimension described above in reference to FIG. **5** could be substantially different for various different types of materials used, or for various differences in overall dimensions for window size, or for application in a vehicle as compared to an aircraft or a spacecraft, for example. Obviously, the faster the vehicle or aircraft/spacecraft, the stronger the structural members must be, particularly the outer pane or window member **210**. This could significantly impact the other structural members, including their dimensions (such as their thicknesses) as well as their spaced-apart relationships with each other, including the gap dimension **G1**.

It will also be understood that the intermediate member or layer **214** would typically be made of a substantially transparent material at human optical wavelengths. However, certain portions of member **214** would not necessarily need to be optically transparent, perhaps at areas along its outer edges, for example.

Referring now to FIG. **6**, another window structure is generally designated by the reference numeral **250**. In FIG. **6**, the exterior window structural member is at **260**, while the interior window structural member is at **262**. An intermediate member **264** is located proximal to the interior window structural member **262** in this configuration. The air-film vibration damping characteristics will be provided by a gap or volume at **270**, which relates to a dimension **G11** with regard to its actual distance. A larger gap at **272** represents the distance between the intermediate member **264** and the outer structural member **260**. The exterior air (or environment) is at **274**, while the interior air (or environment) is at **276**.

In FIG. **6**, a dimension **d11** represents the thickness of the outer window structural member **260**, a dimension **d12** represents the thickness of the interior window structural member **262**, while a dimension **d13** represents the thickness of the intermediate member **264**. The gap dimension **G11** is most important with regard to the vibration damping characteristics of this window structure **250**, and a gap at **G12** represents more of a thermal barrier. An overall gap dimension **G13** represents the distance between the main window structural members **260** and **262**.

In FIG. **6**, the air-film vibration damping characteristics will be effective for the interior window member **262**, rather than the exterior window member **260**; there are differences in the implementations of the air film damping systems of structures **200** and **250**. In the case of structure **200**, the outer pane structure would be heavily damped via air film damping; in the case of structure **250**, the inner pane structure would be heavily damped via air film damping. Even if all of the materials and dimensions were identical to the window structure **200** illustrated in FIG. **5**, the acoustic frequency response with respect to the cabin interior and vibrational amplitude response would not necessarily be precisely the same, between these two structures **250** and **200**, although they may have quite similar characteristics for their specific damped components.

In actual use, the intermediate layer of material **264** would likely have a vent hole (e.g., at **266**) to allow pressure to equalize on both sides of its structure, i.e., the areas at reference numerals **270** and **272**. As can be seen from the above dimensional information, this layer **264** will typically be fairly "thin" in construction, and thus will not be expected to carry a differential pressure loading. Moreover, the innermost pane structure **262** might also be vented, to avoid carrying any kind of pressure loading; this assumes that the outermost pane structure **260** will be the pressure load-bearing member of

this window structure **250**, which probably is typical in many aircraft fuselages. It will be understood that all of the various embodiments described herein may, or may not, have one or more vent holes (whether illustrated or not) through one or more of the window pane elements (or layers), including the element/layer that provides the air-film damping characteristic.

Referring now to FIG. **7**, a window structural assembly **300** is depicted as having two main window structural members **310** and **312**, and two intermediate members **314** and **316**. The exterior environment is depicted at **326**, while the interior environment is depicted at **328**.

The two intermediate members **314** and **316** provide the capability of further damping the acoustic energy or vibrational energies of both main window structures **310** and **312**. The outer window member **310** has an air-film vibration damping gap **320** with a gap dimension **G21** between itself and the first intermediate member **314**. The second intermediate member **316** provides an air-film vibration damping gap **322** that has a dimension **G22** on FIG. **7** between itself and the second main member **312**. There is a gap area (or volume) **324** between the two intermediate members **314** and **316**. That gap dimension is designated **G23**, and the overall gap dimension **G24** represents the distance between the two main structural members **312** and **310**.

The thickness of the outer member **310** is given as **d21**, the thickness of the interior member **312** is given by the dimension **d22**. The thickness of the two intermediate members **314** and **316** are given by the dimensions **d23** and **d24**, respectively. There is nothing in the present invention that says the thicknesses of the two intermediate members **314** and **316** must be equal in this configuration, nor do the distances in the gaps **G21** and **G22** necessarily need to be equal. Each of the window structural members **310** and **312** can have its own predetermined gap dimension to the respective intermediate members **314** and **316**, and thus be "tuned" to have superior vibration damping characteristics regardless as to the other main window member.

Referring now to FIG. **8**, another alternative window structure is generally designated by the reference numeral **350**. There are two main window members, an exterior window member **360** and an interior window member **362**. An intermediate layer **364** is illustrated as being in contact with the interior window member **362**. The exterior environment is at **374**, while the interior environment is at **376**.

The only "gap" in the design of FIG. **8** is the space **370**, which has a gap dimension designated **G41**. This would necessarily have to provide both air-film vibration damping characteristics as well as thermal insulation characteristics, and so this design of FIG. **8** may not be suitable for a large number of various applications involving vehicles or aircraft/spacecraft that travel through extremes of temperature. The thickness of the exterior window **360** is given at **d31**, the thickness of the interior window structure **362** is given at **d32**, and the thickness of the intermediate layer **364** is given at **d33**.

Referring now to FIG. **9**, another alternative window structure is generally designated by the reference numeral **400**. An exterior window structural member **410** is in contact with the external environment **424**, while an interior window structural member **412** is in contact with an interior environment **426**. An intermediate member **414** provides air-film vibration damping characteristics with respect to the external window member **410**. In FIG. **9**, the intermediate member **414** is not planar along its entire surface area (or distance as seen in FIG. **9**) and has a gap dimension **G41** providing the air-film vibration damping in a space **420**. Toward one end of the window structure, the gap distance **G41** is not maintained and inter-

11

mediate member **414** comes close to, or makes contact with, the surface of the exterior window member **410**.

The exterior window member **410** has a thickness of dimension **d41**, the interior window member **412** has a thickness dimension **d42**, and the intermediate member **414** has a thickness dimension **d43**. Another gap (or space) **422** has a dimension **G42**, while the overall larger gap **G43** represents the distance between the two main structural window members **410** and **412**. The vibration damping characteristics of this embodiment **400** may be somewhat different than those of the embodiment **200** in FIG. 5, and this alternative construction may also prove useful for other reasons.

Referring now to FIG. 10, yet another alternative embodiment **450** of a window structure is provided, in which an exterior member **460** is in contact with the exterior environment **474**, an interior member **462** is in contact with the interior environment **476**, and there is an intermediate member **464** that does not exhibit a constant thickness. A gap (or space) **470** provides air-film vibration damping characteristics with respect to the exterior member **460**, and this gap has a dimension **G51**. The thickness of the exterior member **460** is given as **d51**, while the effective thickness of the intermediate member **464** is given by the dimension **d53**. This is the lesser thickness dimension of member **464**, illustrated in FIG. 10; the thicker portion of intermediate member **464** allows a different type of structural support to be used, and which may come into physical contact with one of the surfaces of the exterior member **460**, if desired.

The interior member **464** has a thickness dimension **d52**, and a thermal barrier gap (or space) **472** has a dimension **G52**. The overall distance between the two structural main members **460** and **462** is given by the dimension or gap **G53**.

Referring now to FIG. 11, still another alternative embodiment **500** is illustrated as having a main exterior member **510** that is in contact with the exterior environment **524**, a main interior member **512** that is in contact with the interior environment **526**, and an intermediate member **514** that provides an air-film vibration damping characteristic with respect to the exterior member **510**. Intermediate member **514** provides a spaced-apart gap **G61** in a space **520** between members **510** and **514**. This allows for air-film vibration damping to take place. The outer window member **510** has a thickness dimension **d61**, the interior window member **512** has a thickness dimension **d62**, and the intermediate member **514** has a thickness **d63**. This can be seen in FIG. 11, intermediate member **514** is not planar over its entire surface area (or length across the figure), but zigs a bit farther away from the exterior window member **510**, which may allow for it to be more easily mounted into the window frame of the fuselage of an aircraft, for example.

The gap dimension **G61** provides the air-film vibration damping characteristic, and a gap **G62** can provide thermal insulation, for a volume (or space) **522**. The overall gap dimension **G63** is between the two main structural window members **510** and **512**.

It will be understood that the principles of the present invention can apply to various types of window structures, including window structures that have a large air gap between two substantially transparent window pane members, and also window structures that have some type of solid material between two window pane members, such as an interlayer of a substantially transparent solid material. For the present invention to be effective, however, there must be some type of space or gap between at least two of the window structure members, and this space or gap would typically be filled with some gaseous compound to provide the "air-film" vibration damping effect.

12

It will also be understood that the panes of the inventive window structure may or may not include one or more through-holes to provide equalization of air pressure on both sides. Such through-holes could potentially even be located in a relatively thin layer of material that is provided specifically as a boundary for the space (or gap) that provides the air-film vibration damping effect of the present invention. Of course, if one of the window structure layers includes a through-hole that would be in communication with the space (or gap) that is providing the vibration damping characteristic, then the effects of this through-hole must be accounted for by the system designer.

It will yet be further understood that the additional layer of material that provides the space (or gap) for the air-film vibration damping characteristic would typically be substantially clear or transparent at wavelengths of visible light to the human eye. However, not every portion of the window structure would necessarily need to comprise a material having a substantially transparent characteristic. This would be true for all of the window members, and the use of a non-transparent material at certain areas may particularly be useful around the edges of the window structures, or in certain corners, if desired by the system designer.

It will still be further understood that the material used within the space or gap that is providing the air-film vibration damping characteristic of the overall window structure or system does not necessarily have to be air, but could be virtually any type of gaseous compound that would provide the proper physical characteristics to enhance the vibration damping effect. If air is not used, then other gaseous materials such as argon or neon could be used, or perhaps other materials such as a gas that is high in nitrogen content, or high in one of the other noble gases.

As used herein, the term "proximal" can have a meaning of closely positioning one physical object with a second physical object, such that the two objects are perhaps adjacent to one another, although it is not necessarily required that there be no third object positioned therebetween. In the present invention, there may be instances in which a "male locating structure" is to be positioned "proximal" to a "female locating structure." In general, this could mean that the two male and female structures are to be physically abutting one another, or this could mean that they are "mated" to one another by way of a particular size and shape that essentially keeps one structure oriented in a predetermined direction and at an X-Y (e.g., horizontal and vertical) position with respect to one another, regardless as to whether the two male and female structures actually touch one another along a continuous surface. Or, two structures of any size and shape (whether male, female, or otherwise in shape) may be located somewhat near one another, regardless if they physically abut one another or not; such a relationship could still be termed "proximal." Moreover, the term "proximal" can also have a meaning that relates strictly to a single object, in which the single object may have two ends, and the "distal end" is the end that is positioned somewhat farther away from a subject point (or area) of reference, and the "proximal end" is the other end, which would be positioned somewhat closer to that same subject point (or area) of reference.

All documents cited in the Detailed Description of the Invention are, in relevant part, incorporated herein by reference; the citation of any document is not to be construed as an admission that it is prior art with respect to the present invention.

The foregoing description of a preferred embodiment of the invention has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit

13

the invention to the precise form disclosed. Any examples described or illustrated herein are intended as non-limiting examples, and many modifications or variations of the examples, or of the preferred embodiment(s), are possible in light of the above teachings, without departing from the spirit and scope of the present invention. The embodiment(s) was chosen and described in order to illustrate the principles of the invention and its practical application to thereby enable one of ordinary skill in the art to utilize the invention in various embodiments and with various modifications as are suited to particular uses contemplated. It is intended to cover in the appended claims all such changes and modifications that are within the scope of this invention.

The invention claimed is:

1. A vibration damping system, comprising:

a first window structure;

a second window structure that is spaced-apart from said first window structure by a first distance, in an arrangement by which at least portions of said first and second window structures are substantially parallel to one another;

wherein said first window structure comprises a single layer of material that is substantially transparent at optical wavelengths for humans;

wherein said second window structure comprises two separate layers of material that are both substantially transparent at visible optical wavelengths for humans, said two separate layers being spaced-apart from one another by a second distance in an arrangement by which at least portions of said two separate layers are substantially parallel to one another, thereby forming a space between said two separate layers of material of said second window structure in which said space includes a gaseous material;

wherein said gaseous material is used as a vibration damping medium; and

wherein said second distance is less than about 0.016 inches (0.41 mm), and said second distance is of a size that provides air-film vibration damping for said second window structure.

2. The vibration damping system as recited in claim 1, wherein at least one of said first and second window structures exhibits an opening that extends completely there-through, used for pressure equalization.

3. The vibration damping system as recited in claim 1, wherein at least one of said first and second window structures exhibits a first area that is not substantially transparent at optical wavelengths for humans, and exhibits a second area that is substantially transparent at optical wavelengths for humans.

4. The vibration damping system as recited in claim 3, wherein said first area extends along at least a portion of an

14

outer perimeter of said at least one of said first and second window structures, and said first area is used for mounting said at least one of said first and second window structures to a support structure that essentially hides said first area from view.

5. The vibration damping system as recited in claim 4, wherein said support structure comprises a portion of one of: (a) a fuselage of an aircraft; (b) a hull of a spacecraft; (c) a body of a vehicle; and (d) a hull of a vessel.

6. A method for dampening vibrations in a structure, said method comprising:

(a) providing a first window structure of a material that is substantially transparent at optical wavelengths for humans;

(b) providing a second window structure that is spaced-apart from said first window structure by a first distance, in an arrangement by which at least portions of said first and second window structures are substantially parallel to one another, said second window structure comprising two separate layers of material that are both substantially transparent at visible optical wavelengths for humans, said two separate layers being spaced-apart from one another by a second distance in an arrangement by which at least portions of said two separate layers are substantially parallel to one another, thereby forming a space between said two separate layers of material of said second window structure in which said space includes a gaseous material; and

(c) providing air film vibration damping between said two separate layers of material by causing said gaseous material to cyclically flow within said space due to cyclic pressure variations arising from movement of surfaces of said two separate layers of material.

7. The method of claim 6, wherein said cyclic pressure variations arising from surfaces of said two separate layers of material occur by way of relative transverse cyclic motion of said surfaces.

8. The method of claim 6, wherein said gaseous material comprises one of: (a) air; (b) substantially pure argon; (c) substantially pure neon; and (d) a controlled mixture of gases that includes at least oxygen.

9. The method of claim 6, further comprising the step of: pressurizing said gaseous material.

10. The method of claim 6, further comprising the step of: equalizing pressure between said space and an interior environment by providing an opening that extends completely through at least one of said two separate layers of the second window structure.

11. The method of claim 6, wherein: said two separate layers of material both exhibit a substantially uniform thickness over their entire area.

* * * * *