

US008490792B2

(12) **United States Patent**
D'Amato

(10) **Patent No.:** **US 8,490,792 B2**
(45) **Date of Patent:** ***Jul. 23, 2013**

(54) **PACKAGE**

(75) Inventor: **Gianfranco D'Amato**, Arzano Napoli (IT)

(73) Assignee: **Seda S.p.A.**, Arzano Napoli (IT)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 26 days.

This patent is subject to a terminal disclaimer.

1,520,870 A	12/1924	Koch
1,549,417 A	8/1925	Hendrich
1,615,319 A	1/1927	Wynn
1,654,318 A	12/1927	Benson
1,685,494 A	9/1928	Koch
1,706,910 A	3/1929	Wright et al.
1,756,243 A	4/1930	Benson
1,759,407 A	5/1930	Kingsbury
1,814,671 A	7/1931	Dufour
2,053,726 A	9/1936	Marshall
2,134,427 A	10/1938	Biderman
2,156,328 A	5/1939	Barbieri
2,157,054 A	5/1939	Gammeter

(Continued)

(21) Appl. No.: **11/998,619**

(22) Filed: **Nov. 30, 2007**

(65) **Prior Publication Data**

US 2008/0164268 A1 Jul. 10, 2008

(30) **Foreign Application Priority Data**

Dec. 5, 2006 (DE) 20 2006 018 406 U

(51) **Int. Cl.**
B65D 3/22 (2006.01)

(52) **U.S. Cl.**
USPC **206/459.5**; 206/831; 229/403; 229/400

(58) **Field of Classification Search**
USPC 206/831, 459.5, 459.1, 217; 220/592.2, 220/660, 737-739; 229/403, 400, 402; 283/105, 283/100, 103; 40/306, 310, 312
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

23,200 A	3/1859	Stimpson
1,031,514 A	7/1912	Bjorkstam et al.

FOREIGN PATENT DOCUMENTS

AR	047625	2/2006
AT	141212 T	8/1996

(Continued)

OTHER PUBLICATIONS

Statement of Case in Opposition to New Zealand Patent Application No. 543602, Mar. 22, 2007, 79 pages.

(Continued)


Primary Examiner — Steven A. Reynolds

(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**

A package includes a container having an opening, a bottom and at least one inner wall. The package further includes at least one outer wall formed from a two-dimensional pre-cut part having a removable wall section that is a removable card which discloses an information. The pre-cut part includes an access section that is formed at a peripheral edge of the pre-cut part so as to provide an open space adjacent to the removable wall section when the pre-cut part is connected to itself to form the outer wall of the package.

11 Claims, 12 Drawing Sheets



U.S. PATENT DOCUMENTS					
2,288,602	A	5/1939 Benton	4,089,358	A	5/1978 Korson
2,170,060	A	8/1939 Meyer	4,102,454	A	7/1978 Karevaara et al.
2,216,331	A	10/1940 Swallow et al.	4,124,120	A	11/1978 Day
2,226,340	A	12/1940 Flood	4,129,065	A	12/1978 Corse et al.
2,235,963	A	3/1941 McGirr et al.	4,171,085	A	10/1979 Doty
2,240,599	A	5/1941 Amberg	4,187,768	A	2/1980 Suzuki
2,266,828	A	12/1941 Sykes	4,211,024	A	7/1980 Nickell
2,416,813	A	3/1947 Barbieri	4,231,476	A	11/1980 Compton et al.
2,462,497	A	2/1949 Heyman	4,261,501	A	4/1981 Watkins et al.
2,493,633	A	1/1950 Mart	4,292,194	A	9/1981 Perazzoni et al.
2,540,565	A	2/1951 Barbieri	4,308,679	A	1/1982 Ray, III et al.
2,563,352	A	8/1951 Morse	4,318,235	A	3/1982 Augeri
2,591,578	A	4/1952 McNealy et al.	4,324,338	A	4/1982 Beall
2,661,889	A	12/1953 Phinney	4,327,136	A	4/1982 Thompson et al.
2,666,542	A	1/1954 Price	4,344,814	A	8/1982 McLaren
2,675,954	A	4/1954 Vogel	4,345,393	A *	8/1982 Price et al. 40/312
2,689,424	A	9/1954 Clagett	4,368,818	A	1/1983 Day et al.
2,692,722	A	10/1954 Johnson	4,409,045	A	10/1983 Busse
2,695,744	A	11/1954 Gattuso	4,409,122	A	10/1983 Kleuskens et al.
2,721,686	A	10/1955 Reifsnnyder et al.	4,514,242	A	4/1985 MacLaughlin et al.
2,725,733	A	12/1955 Howlett	4,548,348	A	10/1985 Clements
2,740,575	A	4/1956 Fontaine	4,551,365	A	11/1985 Bonis
2,828,903	A	4/1958 Adkins	4,560,075	A	12/1985 Lu
2,863,585	A	12/1958 Meshberg	4,571,233	A	2/1986 Konzal
2,888,861	A	6/1959 Meyer-Jagenberg	4,574,987	A	3/1986 Halligan et al.
2,899,098	A	8/1959 Gits	4,581,003	A	4/1986 Ito et al.
2,982,465	A	5/1961 Fallert	4,684,553	A	8/1987 Sasaki et al.
3,065,875	A	11/1962 Negoro	4,706,873	A *	11/1987 Schulz 229/400
3,079,027	A	2/1963 Edwards	4,771,911	A	9/1988 Morony et al.
3,082,900	A	3/1963 Goodman	4,775,523	A	10/1988 Sparacio et al.
3,109,252	A	11/1963 Schellenberg	4,789,073	A	12/1988 Fine
3,118,351	A	1/1964 Meyer-Jagenberg	4,792,042	A	12/1988 Koehn et al.
3,139,213	A	6/1964 Edwards	4,813,862	A	3/1989 Bowers et al.
RE25,618	E	7/1964 Goodman	4,838,424	A	6/1989 Petzelt
3,208,631	A	9/1965 Edwards	4,850,496	A	7/1989 Rudell et al.
3,225,954	A	12/1965 Herrick et al.	4,863,014	A	9/1989 Summons et al.
3,232,512	A	2/1966 Wanderer	4,936,448	A	6/1990 Holloway
3,298,893	A	1/1967 Allen	4,955,503	A	9/1990 Propes
3,355,046	A	11/1967 Jolly	4,993,580	A	2/1991 Smith
3,357,053	A	12/1967 Lyon et al.	4,997,691	A	3/1991 Parkinson
3,372,830	A	3/1968 Edwards	5,007,578	A *	4/1991 Simone 229/400
3,401,862	A	9/1968 Wanderer	5,021,274	A	6/1991 Beck et al.
3,428,214	A	2/1969 Leon	5,025,981	A	6/1991 Schellenberg
3,443,714	A	5/1969 Edwards	5,062,568	A	11/1991 Hill et al.
3,456,860	A	7/1969 Janninck	5,076,463	A	12/1991 McGraw
3,471,075	A	10/1969 Wolf	5,078,313	A	1/1992 Matheson et al.
3,485,412	A	12/1969 Hawley	5,092,485	A	3/1992 Lee
3,526,316	A	9/1970 Kalogris	5,135,132	A	8/1992 Potochnik
3,531,015	A	9/1970 Makin	5,145,107	A *	9/1992 Silver et al. 229/403
3,580,468	A	5/1971 McDevitt	5,226,585	A	7/1993 Varano
3,583,596	A	6/1971 Brewer	5,253,781	A	10/1993 Van Melle et al.
3,612,346	A	10/1971 Schneider et al.	5,363,982	A	11/1994 Sadlier
3,645,758	A	2/1972 MacManus	5,385,260	A	1/1995 Gatcomb
3,700,018	A	10/1972 Goglio	5,395,005	A	3/1995 Yoshida
3,737,093	A *	6/1973 Amberg et al. 206/447	5,425,497	A	6/1995 Sorensen
3,739,975	A *	6/1973 Davidow 229/116.3	5,425,498	A	6/1995 Hallam et al.
3,747,830	A	7/1973 Goldman	5,460,323	A	10/1995 Titus
3,749,277	A	7/1973 Kinney	5,484,167	A *	1/1996 Donaldson et al. 283/67
3,765,559	A	10/1973 Sauey et al.	5,489,063	A	2/1996 Buchalski et al.
3,766,975	A	10/1973 Todd	5,524,817	A *	6/1996 Meier et al. 229/403
D231,068	S	4/1974 Douglas	5,542,599	A	8/1996 Sobol
3,827,620	A	8/1974 Ludder	5,547,124	A	8/1996 Mueller
3,836,207	A	9/1974 Belart	5,551,592	A	9/1996 Barton et al.
3,846,207	A	11/1974 MacDaniel et al.	5,553,735	A	9/1996 Kimura
3,850,361	A	11/1974 Day et al.	5,573,141	A	11/1996 Chen
3,878,282	A	4/1975 Bonis et al.	5,586,689	A	12/1996 D'Amato et al.
3,884,350	A	5/1975 Johansson	5,593,053	A	1/1997 Kaufman et al.
3,908,523	A	9/1975 Shikaya	5,603,450	A	2/1997 Whitnell
3,926,361	A	12/1975 Hilderbrand	5,628,453	A	5/1997 MacLaughlin
3,927,766	A	12/1975 Day	5,660,326	A	8/1997 Varano et al.
3,934,749	A	1/1976 Andrulionis	5,660,898	A	8/1997 Calvert
3,955,697	A	5/1976 Valyi	5,671,353	A	9/1997 Tian et al.
3,980,107	A	9/1976 Barnes et al.	5,674,546	A	10/1997 Barnes et al.
4,007,670	A	2/1977 Albano et al.	5,678,725	A	10/1997 Yamada et al.
4,018,904	A	4/1977 Muraoka	5,685,480	A	11/1997 Choi
4,040,537	A	8/1977 Edwards	5,697,550	A	12/1997 Varano et al.
4,049,122	A	9/1977 Maxwell	5,713,512	A	2/1998 Barrett
4,070,953	A	1/1978 Richards et al.	5,752,653	A *	5/1998 Razzaghi 229/403
			RE35,830	E	6/1998 Sadlier

US 8,490,792 B2

5,769,262 A	6/1998	Yamada et al.	6,746,743 B2	6/2004	Knoerzer et al.
5,769,311 A	6/1998	Morita	6,749,913 B2	6/2004	Watanabe et al.
5,772,111 A	6/1998	Kirsch	6,763,344 B1	7/2004	Osentoski et al.
5,794,843 A	8/1998	Sanchez	6,775,670 B2	8/2004	Besette et al.
5,820,016 A	10/1998	Stropkay	6,811,843 B2	11/2004	DeBraai et al.
5,823,948 A	10/1998	Ross, Jr. et al.	6,852,381 B2	2/2005	DeBraai et al.
5,839,599 A	11/1998	Lin	6,908,651 B2	6/2005	Watanabe et al.
5,839,653 A	11/1998	Zadravetz	6,921,179 B2	7/2005	Diak Ghanem
5,894,948 A	4/1999	Yeh	6,926,197 B2	8/2005	Hed et al.
5,903,889 A	5/1999	de la Huerga et al.	6,989,198 B2	1/2006	Masuda et al.
5,913,449 A	6/1999	Branch et al.	7,100,770 B2	9/2006	D'Amato
5,918,761 A	7/1999	Wissinger	7,117,579 B2	10/2006	Schellenberg
5,944,208 A	8/1999	Gale	7,172,086 B2	2/2007	McKendry et al.
5,950,917 A	9/1999	Smith	7,175,585 B2	2/2007	Okushita et al.
5,953,419 A	9/1999	Lohstroh et al.	7,195,805 B2	3/2007	Breining et al.
5,954,217 A	9/1999	Brkovic et al.	D546,625 S	7/2007	Gluck
5,956,400 A	9/1999	Chaum et al.	D547,122 S	7/2007	Gluck
5,964,400 A	10/1999	Verano et al.	D550,033 S	9/2007	Bodum
5,975,344 A	11/1999	Stevens	D550,034 S	9/2007	Bodum
5,996,887 A *	12/1999	Cai et al. 229/400	D551,502 S	9/2007	Bodum
6,036,801 A	3/2000	Yamada et al.	D553,437 S	10/2007	Bodum
6,047,488 A *	4/2000	Tuskiewicz 40/306	D553,439 S	10/2007	Bodum
6,050,443 A	4/2000	Tung	D553,440 S	10/2007	Bodum
6,056,144 A	5/2000	Strange et al.	D553,442 S	10/2007	Bodum
6,065,632 A	5/2000	Moore, Jr.	D553,909 S	10/2007	Bodum
6,068,181 A *	5/2000	Cai 229/116.1	D553,910 S	10/2007	Bodum
6,076,699 A	6/2000	Seager et al.	D553,911 S	10/2007	Bodum
6,085,970 A	7/2000	Sadlier	7,281,650 B1	10/2007	Milan
6,109,518 A *	8/2000	Mueller et al. 229/403	D557,561 S	12/2007	Flowers et al.
6,116,503 A	9/2000	Varano	D557,563 S	12/2007	Bodum
6,126,584 A	10/2000	Zadravetz	D557,564 S	12/2007	Bodum
6,145,656 A	11/2000	Marco	7,306,113 B2	12/2007	El-Saden et al.
6,148,342 A	11/2000	Ho	D562,075 S	2/2008	Mehta
6,161,720 A	12/2000	Castle	D563,172 S	3/2008	Bodum
6,193,098 B1	2/2001	Mochizuki et al.	7,344,038 B2 *	3/2008	Elansary 215/12.1
6,196,454 B1	3/2001	Sadlier	D577,260 S	9/2008	Bodum
6,210,766 B1	4/2001	McLaughlin	7,451,910 B2	11/2008	Frost et al.
6,224,954 B1	5/2001	Mitchell et al.	7,451,911 B2	11/2008	Stepanek, Jr.
6,237,845 B1	5/2001	Hashimoto et al.	D581,738 S	12/2008	Bodum
6,253,995 B1	7/2001	Blok et al.	D581,739 S	12/2008	Bodum
6,257,485 B1 *	7/2001	Sadlier et al. 229/403	7,458,504 B2	12/2008	Robertson et al.
6,260,021 B1	7/2001	Wong et al.	7,481,356 B2	1/2009	Stahlecker et al.
6,260,756 B1 *	7/2001	Mochizuki et al. 229/402	7,536,767 B2	5/2009	Hollis et al.
6,263,330 B1	7/2001	Besette et al.	D594,277 S	6/2009	Snell
6,265,040 B1	7/2001	Neale et al.	D595,090 S	6/2009	Benson
6,286,754 B1	9/2001	Stier et al.	7,552,841 B2	6/2009	Hollis et al.
6,287,247 B1	9/2001	Dees et al.	D597,791 S	8/2009	Lion et al.
6,315,150 B1	11/2001	Takai et al.	D597,792 S	8/2009	Lion et al.
6,315,192 B1 *	11/2001	Marlow 229/401	7,597,246 B2	10/2009	Stepanek, Jr.
6,332,538 B1	12/2001	Pritchard	7,631,781 B2	12/2009	Chen
6,343,735 B1	2/2002	Cai	7,677,435 B2	3/2010	Stahlecker
6,367,652 B1	4/2002	Toida et al.	7,694,843 B2	4/2010	Hollis et al.
6,378,763 B1	4/2002	Nelson et al.	7,699,216 B2	4/2010	Smith et al.
6,378,766 B2	4/2002	Sadlier	7,717,325 B2	5/2010	Puls et al.
6,382,449 B1	5/2002	Kazmierski et al.	2001/0013537 A1	8/2001	Sadlier
6,401,955 B1	6/2002	Yang et al.	2001/0032100 A1	10/2001	Mahmud et al.
6,419,108 B1	7/2002	Toida et al.	2001/0041991 A1	11/2001	Segal et al.
6,422,456 B1	7/2002	Sadlier	2002/0010679 A1	1/2002	Felsher
6,424,996 B1	7/2002	Killcommons et al.	2002/0043555 A1	4/2002	Mader
6,449,621 B1	9/2002	Pettovello	2002/0148832 A1	10/2002	Breining et al.
6,457,585 B1	10/2002	Huffer et al.	2002/0156650 A1	10/2002	Klein et al.
6,463,417 B1	10/2002	Schoenberg	2002/0172818 A1	11/2002	DeBaal et al.
6,557,102 B1	4/2003	Wong et al.	2003/0029876 A1	2/2003	Giraud
6,557,751 B2	5/2003	Puerini	2003/0088441 A1	5/2003	McNerney
6,562,270 B1	5/2003	Gannon et al.	2003/0116576 A1 *	6/2003	Lang-Boecker 220/738
6,568,587 B1	5/2003	Yamada et al.	2003/0121189 A1	7/2003	Williams
6,574,629 B1	6/2003	Cooke, Jr. et al.	2003/0121963 A1 *	7/2003	Van Handel 229/403
6,574,742 B1	6/2003	Jamroga et al.	2003/0140044 A1	7/2003	Mok et al.
6,598,786 B1	7/2003	Guo	2003/0226882 A1	12/2003	Porchia et al.
6,611,846 B1	8/2003	Stoodley et al.	2004/0034550 A1	2/2004	Menschik et al.
6,612,456 B1	9/2003	Hundley et al.	2004/0069311 A1	4/2004	Sasaki et al.
6,648,176 B1	11/2003	Donovan	2004/0094612 A1 *	5/2004	D'Amato 229/403
6,651,060 B1	11/2003	Harper et al.	2004/0112949 A1	6/2004	Hed et al.
6,663,926 B1	12/2003	Okushita et al.	2004/0133797 A1	7/2004	Arnold
6,678,703 B2	1/2004	Rothschild et al.	2004/0139222 A1	7/2004	Slik et al.
6,678,764 B2	1/2004	Parvulescu et al.	2004/0154156 A1	8/2004	Schellenberg
6,688,487 B2	2/2004	Oakes et al.	2004/0199765 A1	10/2004	Kohane et al.
6,691,134 B1	2/2004	Babula et al.	2004/0226948 A1	11/2004	Okushita et al.
6,738,798 B1	5/2004	Ploetz et al.	2005/0006385 A1	1/2005	D'Amato

US 8,490,792 B2

2005/0029337	A1	2/2005	Van Handel	CA	1152011	8/1983
2005/0040218	A1	2/2005	Hinchey et al.	CA	1239885	8/1988
2005/0045643	A1	3/2005	Ghanem	CA	1249232	1/1989
2005/0115975	A1	6/2005	Smith et al.	CA	1257209	7/1989
2005/0184074	A1	8/2005	Simmons et al.	CA	2021035	A1 1/1991
2005/0199697	A1	9/2005	Nugent	CA	2026197	8/1991
2005/0205651	A1	9/2005	Marx	CA	2060135	7/1992
2005/0236468	A1	10/2005	Sadlier	CA	2150306	2/1996
2005/0258225	A1	11/2005	Martin	CA	2043958	7/1996
2005/0269390	A1	12/2005	Martin	CA	2250677	4/2000
2006/0038001	A1	2/2006	Stepanek	CA	2286498	A1 4/2000
2006/0118608	A1*	6/2006	Stahlecker 229/403	CA	2176080	8/2001
2006/0131316	A1	6/2006	Bresler	CA	2228749	10/2001
2006/0144915	A1	7/2006	Sadlier	CA	2141730	5/2002
2006/0186012	A1	8/2006	D'Amato	CA	2197976	5/2002
2006/0226210	A1*	10/2006	Stahlecker 229/403	CA	2432791	6/2002
2006/0237465	A1	10/2006	D'Amato	CA	2165509	7/2002
2006/0283855	A1	12/2006	Hollis et al.	CA	2436505	A1 8/2002
2006/0289610	A1	12/2006	Kling	CA	2233356	11/2002
2007/0262129	A1	11/2007	Zadravetz	CA	2431542	12/2002
2007/0284426	A1	12/2007	Lo	CA	2431869	12/2002
2008/0006643	A1	1/2008	Ma	CA	2219845	4/2003
2008/0023536	A1	1/2008	Frost et al.	CA	2244689	9/2003
2008/0023537	A1	1/2008	Frost et al.	CA	2271581	12/2003
2008/0023538	A1	1/2008	Robertson et al.	CA	2121491	7/2004
2008/0029588	A1	2/2008	Messerschmid et al.	CA	2542905	A1 1/2005
2008/0078825	A1	4/2008	Puls et al.	CA	2564012	11/2005
2008/0087677	A1	4/2008	Robertson et al.	CA	114070	2/2006
2008/0087715	A1	4/2008	Robertson et al.	CA	2520024	3/2006
2008/0087716	A1	4/2008	Sadlier	CA	2262802	6/2006
2008/0093434	A1	4/2008	Van Handel	CA	2549450	12/2006
2008/0105692	A1	5/2008	Hikomori	CA	2608826	12/2006
2008/0105693	A1	5/2008	Hechmati	CA	2262458	1/2007
2008/0121681	A1	5/2008	Wiedmeyer	CA	2613109	1/2007
2008/0128433	A1	6/2008	Stauffer et al.	CA	2621453	3/2007
2008/0128481	A1	6/2008	Robertson	CA	113773	4/2007
2008/0156857	A1	7/2008	Johnston	CA	119089	5/2007
2008/0169297	A1	7/2008	Kelly	CA	119090	5/2007
2008/0264937	A1	10/2008	D'Amato	CA	119091	5/2007
2008/0272118	A1	11/2008	Wang	CA	119092	5/2007
2008/0280743	A1	11/2008	Stahlecker et al.	CA	2629190	5/2007
2008/0302800	A1	12/2008	Chou	CA	118452	7/2007
2008/0308620	A1	12/2008	Stepanek, Jr.	CA	113355	9/2007
2008/0314909	A1	12/2008	Takeo et al.	CA	115931	10/2007
2009/0020597	A1	1/2009	D'Amato	CA	116240	10/2007
2009/0110782	A1	4/2009	Mellor	CA	116241	10/2007
2009/0121007	A1	5/2009	Van Handel	CA	116438	10/2007
2009/0159653	A1	6/2009	Stahlecker	CA	119239	10/2007
2009/0166402	A1	7/2009	D'amato	CA	120446	10/2007
2009/0170680	A1	7/2009	D'amato	CA	2545497	11/2007
2009/0184020	A1	7/2009	Messerschmid et al.	CA	2588413	11/2007
2009/0218390	A1	9/2009	Chang	CA	2657721	A1 1/2008
2009/0230178	A1	9/2009	Stahlecker et al.	CA	116480	2/2008
2009/0294456	A1	12/2009	Messerschmid	CA	2598153	2/2008
2009/0294520	A1	12/2009	Stepanek, Jr.	CA	120610	3/2008
2009/0321440	A1	12/2009	Fedusa et al.	CA	2520677	4/2008
2009/0321508	A1	12/2009	Fu et al.	CA	2664625	4/2008
2010/0025283	A1	2/2010	Oshima et al.	CA	2665633	4/2008
2010/0044424	A1	2/2010	Van Handel	CA	114549	5/2008
2010/0065622	A1	3/2010	Chang	CA	121962	5/2008
2010/0072268	A1	3/2010	Johnson et al.	CA	2610053	5/2008
2010/0160130	A1	6/2010	Messerschmid	CA	122120	6/2008
2010/0187296	A1	7/2010	Puls et al.	CA	122879	7/2008
				CA	2267361	10/2008
				CA	2598691	5/2009
				CA	2347777	7/2009
				CA	2706374	7/2009
				CA	2311825	10/2009
				CA	2405786	11/2009
				CA	2394475	1/2010
				CA	128485	2/2010
				CH	678938	A5 11/1991
				CN	1082987	A 3/1994
				CN	1128744	A 8/1996
				CN	1237133	A 12/1999
				CN	1272089	A 11/2000
				CN	1288427	A 3/2001
				CN	2430371	5/2001
				CN	2484866	Y 4/2002
FOREIGN PATENT DOCUMENTS						
AT	263709	T	4/2004			
AU	4557993	A	3/1994			
AU	2008264158	A1	8/2009			
AU	2009200641	A1	10/2009			
BE	410215	A	7/1935			
BE	897862	A1	3/1984			
BR	PI0900078	A2	9/2009			
CA	742539		9/1966			
CA	837922		3/1970			
CA	844949		6/1970			
CA	1007182		3/1977			
CA	1082657		7/1980			
CA	1125680		6/1982			
CA	1125681		6/1982			

US 8,490,792 B2

Page 5

CN	2526274	Y	12/2002	EP	1 876 106	1/2008
CN	1489541	A	4/2004	EP	1 894 847	3/2008
CN	1781813	A	6/2006	EP	1 921 023	5/2008
CN	101489771	A	7/2009	EP	1 939 099	7/2008
CN	101492107	A	7/2009	EP	1975083 A2	10/2008
CN	101531070	A	9/2009	EP	1 990 184	11/2008
DE	652737	C	11/1937	EP	2 049 326	4/2009
DE	18806777		5/1963	EP	2043853 A1	4/2009
DE	11 91 285	A	4/1965	EP	2080715 A1	7/2009
DE	2001499		7/1970	EP	2108506 A2	10/2009
DE	8301046	U1	5/1983	EP	2 128 041	12/2009
DE	3335833	A1	4/1984	EP	2 147 871	1/2010
DE	9115069	U1	1/1992	EP	2 199 222	6/2010
DE	9215015	U1	1/1993	EP	2 202 178	6/2010
DE	59002814		10/1993	ES	2045882 T3	1/1994
DE	4226313		2/1994	ES	2093443 T3	12/1996
DE	4393650		11/1995	ES	2218361 T3	11/2004
DE	44 21 870	A1	1/1996	FR	791981 A	12/1935
DE	59303454		9/1996	FR	14 90 636	6/1967
DE	19517392		11/1996	FR	2160489 A1	6/1973
DE	19517394		11/1996	FR	2533894 A1	4/1984
DE	19840841	A1	3/2000	FR	2825981	6/2001
DE	10056811	A1	7/2001	FR	2813861 A1	3/2002
DE	10054727	A1	5/2002	GB	321176 A	10/1929
DE	20110390	U1	10/2002	GB	0445661 A	4/1936
DE	20310623	U1	11/2003	GB	484990 A	5/1938
DE	60102661	T2	8/2004	GB	1 261 533	1/1968
DE	102004056932	A1	5/2006	GB	1261531 A	1/1972
DE	102005017741	A1	10/2006	GB	1261532 A	1/1972
DE	102006025612	A1	11/2007	GB	1261533 A	1/1972
DE	102007024243	A1	1/2008	GB	1 554 241	10/1979
DE	102007024254	A1	1/2008	GB	2 044 076	10/1980
DE	102007030864	A1	1/2008	GB	2 055 737	3/1981
DE	102008005403	A1	7/2009	GB	2 061 699	5/1981
DE	102008014878	A1	9/2009	GB	2 073 581	10/1981
EA	200900031	A1	8/2009	GB	2074124 A	10/1981
EP	0074936	A2	3/1983	GB	2 077 177	12/1981
EP	0 108 264		10/1983	GB	2 078 094	1/1982
EP	0102149	A2	3/1984	GB	2130168 A	5/1984
EP	0 371 918		6/1990	GB	2333087 A	7/1999
EP	0408515	A1	1/1991	GB	2420267	5/2006
EP	0512179	A1	11/1992	GB	2425041 A	10/2006
EP	0653983	A1	5/1995	GB	2426045 A	11/2006
EP	0 659 647		6/1995	GB	2445287 A	7/2008
EP	0 683 033		11/1995	HK	1034700 A1	4/2004
EP	0 688 720		12/1995	HK	1063172 A1	8/2006
EP	0 695 692		2/1996	IT	1366725	2/2006
EP	0 765 821		4/1997	IT	MI0020060589	6/2006
EP	0 812 668		12/1997	JP	50-67002	10/1948
EP	0929455	A1	7/1999	JP	52-76459	11/1950
EP	0934202	A1	8/1999	JP	50052003 A	5/1975
EP	0 940 240		9/1999	JP	50120802 A	10/1975
EP	1 029 656		8/2000	JP	51140989	12/1976
EP	1031514	A1	8/2000	JP	53060441	5/1978
EP	1 060 879		12/2000	JP	55134046	10/1980
EP	1057733	A1	12/2000	JP	56156777 A	11/1981
EP	1 157 943		11/2001	JP	58-81159	5/1983
EP	1203728	A2	5/2002	JP	59-94076	5/1984
EP	1227042		7/2002	JP	60-154235	8/1985
EP	1227042	A1	7/2002	JP	60-242490	12/1985
EP	1227043	A1	7/2002	JP	62-143663	6/1987
EP	1 254 842		11/2002	JP	2509655 Y2	8/1989
EP	1 317 380		6/2003	JP	02-307738	12/1990
EP	1 404 580		4/2004	JP	3023014 U	3/1991
EP	1 404 590		4/2004	JP	4-32908	2/1992
EP	1 418 272		5/2004	JP	4097833 A	3/1992
EP	1 463 670		10/2004	JP	04097833 A	3/1992
EP	1479512	A2	11/2004	JP	4-45215	4/1992
EP	1 486 424		12/2004	JP	4-68848	6/1992
EP	1 512 527		3/2005	JP	5-84621	11/1993
EP	1 547 762		6/2005	JP	06048474 A	2/1994
EP	1 637 457		3/2006	JP	07-149338	6/1995
EP	1656300		5/2006	JP	8-207924	8/1996
EP	1 670 688		6/2006	JP	8-310571	11/1996
EP	1712490	A2	10/2006	JP	9-132224	5/1997
EP	1714912	A1	10/2006	JP	10-175627	6/1998
EP	1 719 715		11/2006	JP	10-278931	10/1998
EP	1 739 029		1/2007	JP	10-338277	12/1998
EP	1785370	A1	5/2007	JP	11314286 A	11/1999

JP 11321936 A 11/1999
 JP 11342982 A 12/1999
 JP 2000033931 A 2/2000
 JP 2000095228 A 4/2000
 JP 2000103478 A 4/2000
 JP 2000103479 A 4/2000
 JP 2000118520 A 4/2000
 JP 3063644 5/2000
 JP 2000-203664 7/2000
 JP 2000190943 A 7/2000
 JP 2000203664 A 7/2000
 JP 2000-238739 9/2000
 JP 2000-281044 10/2000
 JP 2000281044 A 10/2000
 JP 2001-2051 1/2001
 JP 01-98355 4/2001
 JP 2001097355 A 4/2001
 JP 2001171642 A 6/2001
 JP 2001180647 A 7/2001
 JP 2001293802 A 10/2001
 JP 2001294282 A 10/2001
 JP 3248718 A 2/2002
 JP 3274412 A 4/2002
 JP 2002-128049 5/2002
 JP 2003276721 A 10/2003
 JP 2003276738 10/2003
 JP 2004090928 A 3/2004
 JP 2004090929 A 3/2004
 JP 2004-1892 4/2004
 JP 2004-98663 4/2004
 JP 2004-99079 4/2004
 JP 2004161375 A 6/2004
 JP 2004522654 T 7/2004
 JP 2004-314987 11/2004
 JP 2004315065 A 11/2004
 JP 2006143331 A 6/2006
 JP 2006290366 10/2006
 JP 2006298391 11/2006
 JP 2008-529549 8/2008
 JP 2009173346 A 8/2009
 KR 2006056859 5/2006
 NL 42544 C 2/1938
 NZ 506739 11/2001
 NZ 519160 12/2003
 SG 0117419 A1 12/2005
 TR 200400866 T4 6/2004
 TW 393427 B 6/2000
 TW 399609 Y 7/2000
 WO WO9202421 2/1992
 WO WO 9308084 4/1993
 WO 9403326 A1 2/1994
 WO 9832601 A2 7/1998
 WO 9911526 A1 3/1999
 WO 9922686 A1 5/1999
 WO 9959883 A1 11/1999
 WO 0017058 A1 3/2000
 WO 0028288 A1 5/2000
 WO WO 01/38180 5/2001
 WO 0204300 A1 1/2002
 WO WO 02/30783 4/2002
 WO 0247523 A1 6/2002
 WO 02060767 8/2002
 WO 03057577 7/2003
 WO WO 2004/049924 6/2004
 WO WO 2004/103845 12/2004
 WO WO 2005/012114 2/2005
 WO WO 2005/047126 5/2005
 WO 2005054082 A1 6/2005
 WO WO 2005/053487 6/2005
 WO 2005075319 A1 8/2005
 WO 2005100167 A1 10/2005
 WO WO 2005/102847 11/2005
 WO 2007028623 A1 3/2007
 WO WO 2007/036928 A3 4/2007
 WO 2007054179 A2 5/2007

WO 2007054318 A1 5/2007
 WO WO 2007/078446 A2 7/2007
 WO WO 2007/090415 A1 8/2007
 WO WO 2007/091068 A2 8/2007
 WO WO 2007/094838 A2 8/2007
 WO WO 2007/126783 A1 11/2007
 WO 2008009371 A1 1/2008
 WO 2008009372 A1 1/2008
 WO WO 2008/009372 1/2008
 WO WO 2008/014230 1/2008
 WO WO 2008009371 1/2008
 WO WO 2008/022180 A2 2/2008
 WO WO 2008/026161 A2 3/2008
 WO WO 2008/042378 A1 4/2008
 WO WO 2008/045708 A1 4/2008
 WO WO 2008/045944 A2 4/2008
 WO 2008067865 A1 6/2008
 WO WO 2008/107657 A1 9/2008
 WO WO 2008/119938 A1 10/2008
 WO WO 2008/123783 A1 10/2008
 WO WO 2008/146115 A1 12/2008
 WO WO 2009/021305 A2 2/2009
 WO WO 2009/032837 A1 3/2009
 WO WO 2009/034323 A2 3/2009
 WO WO 2009/039632 A1 4/2009
 WO WO 2009/059352 A1 5/2009
 WO WO 2009/074285 A2 6/2009
 WO 2009092557 A1 7/2009
 WO WO 2009/082660 A1 7/2009
 WO WO 2009/092557 7/2009
 WO WO 2009092557 7/2009
 WO WO 2009/118772 A1 10/2009
 WO WO 2010/008629 A1 1/2010
 WO WO 2010/011627 A1 1/2010
 WO WO 2010/019146 A1 2/2010
 WO WO 2010/031764 A2 3/2010
 WO WO 2010/034869 A1 4/2010
 WO WO 2010/036645 A1 4/2010
 WO WO 2010/067047 A1 6/2010

OTHER PUBLICATIONS

Statement of Case in Support of Notice of Opposition to Grant of Patent (Section 21) in New Zealand Patent Application No. 543602, Mar. 28, 2007, 16 pages.
 International Search Report from International Application No. PCT/EP2006/009933, dated Oct. 4, 2007, 5 pages.
 International Search Report mailed Jan. 15, 2007, in PCT/EP2006/008753.
 International Search Report from Corresponding International Application No. PCT/EP2005/005406, dated Aug. 25, 2005, 2 pages.
 Search Report for DE 203 19 691.0 mailed Aug. 24, 2004.
 Notice of Opposition dated Jan. 27, 2012 for EP Application No. 07018949.3.
 Opposition against grant of a patent of the Russian Federation No. 2402471 for the invention "A Package" mailed May 5, 2011.
 Decision—Minutes of the oral proceedings before the Opposition Division in EP-B-1785370, Dated Nov. 2, 2010.
 EPO Communication dated Oct. 20, 2010, based on EP1976683.
 Notice of Reasons for Rejection from the Japanese Patent Office in Japanese Patent Appln. No. 2008-539346, Dated Feb. 18, 2011.
 Second Office Action from The State Intellectual Property Office of P.R. China, dated Mar. 21, 2011, for Appln. No. 200480025553.7, issued as 2011031600528500.
 European Search Report dated Sep. 30, 2010, based on EP10008013.
 European Search Report dated Sep. 30, 2010, based on EP10008011.
 European Search Report dated Sep. 30, 2010, based on EP10008012.
 Office Action dated Jul. 1, 2011, corresponding to Mexican Appln. No. 51543.
 European Office Action dated Jan. 17, 2011 with English Summary, based on U.S. Appl. No. 10/630,377.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

1
PACKAGE

RELATED APPLICATIONS

Applicant claims, under 35 U.S.C. §119, the benefit of priority of the filing date of Dec. 5, 2006, of German patent application, Serial No. 20 2006 018 406.6, a copy of which is enclosed. The entire contents of the priority application are incorporated herein by reference.

The present invention refers to a multi-layered package and particularly to a container comprising a container opening and a container bottom, wherein preferably at least one outer wall comprises a predetermined removable wall section revealing an information.

The state of the art discloses packages, which are provided with a label designated to reveal at first hidden information to the public. For this purpose, the user grasps the label or at least part of same and peels it off. Due to the peeling off, the information became public hidden and it may be located on the inner side of the label or on the outer side of a layer that was originally located underneath same. The information may also be a piece hidden behind the label, e.g. a sticker.

Different types of packages are known from DE 697 12 370T2 and DE 698 07 259T2.

In a package according to DE 697 12 370 T2 a multi-layered label is arranged on the surface of the package, wherein one label or a plurality of labels are arranged in parallel on the surface, which are affixed or may be peeled off from the label.

Further, a different type of multi-layered package is known from practice, wherein a drinking container, namely a cup, is combined with an insulating casing. Both predominantly consist of cardboard and are manufactured separately. The insulating casing has a corrugated surface for the purpose of insulation and is loosely slid over the cup from the bottom before filling the cup. The casing may serve as a carrier of an information, e.g. advertisement. Since it is not durably connected to the cup, it can be removed therefrom.

This package is a simple solution, however, it has the disadvantage that the casing is separated from the drinking container and must be assembled by the sales personnel of a sales stand before handing it out to the customer so that both a separate storage as well as assembly work is required to bring the package to the final form.

The invention is based on the object to provide a cost-effective and simpler package of the above-mentioned type at the same time. This object is solved by the characterizing features of the main claim.

The removable wall section is formed as a card and is firstly an integrated component of at least the outer wall. Due to appropriate measures it is prepared to unhinge from the package particularly easy and without interference of the other components when grasped by the user. When the wall section itself serves as a carrier of information, and if maybe furthermore it is desired to obtain it in a predetermined shape during a certain using period, it may be built from a relatively resistant material. Advantageously, the outer wall of the package is made of the same material.

In this regard, paper, cardboard, plastic or the like are known, wherein the material these materials may be coated if this is essential for the purpose of the package. This applies especially for food and their respective packages.

Thus, the wall section itself may serve as a carrier of information. Alternatively, after unhinging the same, it may expose the information which it has originally covered. To facilitate the unhinging of the wall section for the user it is

2

possible to choose the material of the wall section and/or the outer wall so that the user may remove the wall section from the composite.

For the purpose of disclosing the information, the wall section may either be partially or completely removed. In the first case, it is still connected with the wall. In the other case, it is completely separated from the wall. While removing the wall section, in both cases a window is opened within the outer wall for the viewer.

The package may be used for serving people, especially in gastronomy (for example in snack bars), to contain food or beverages. Since in this application area the production costs are very important, the package may be formed of paper, cardboard, plastic or the like.

Minimally, the package exists of two walls, i.e. an inner and an outer wall, which are advantageously separated from each other for the purpose of insulation. Due to the space, an insulation space is formed between the walls, which may also be separated from the surrounding to hold the fluid contained therein, in particular air.

During use, the good insulation values that arise bring the advantage that freshly brewed coffee may be filled in such a double-wall package, especially a cup. The user is then able to grasp the package with the hand, even though the coffee still has a high temperature.

The wall section formed as a card may also be relatively stiff, like the outer wall of the package, to facilitate the unhinging of the outer wall and to provide it with a certain durability for the prospective use.

Furthermore, the package, and especially a package having a wall section provided on the outer wall, provides a further information carrier, which requires cooperation of the consumer in that the consumer identifies the wall section, understands its function and opens the wall section to reach the additional information.

Thus, this embodiment of the invention solves two reluctant objects, namely the optimization of the insulation and the provision of an initially covered and inaccessible additional information.

The removable wall section is formed as part of the package which still ensures a sufficient insulation of the product located within the package. Furthermore, the outer wall at the same time serves as a second wall of the double-walled cup and also ensures dimensional stability when the wall section is removed to reach the additional information. Caused by the spacing of the two walls, the wall section can furthermore especially simply be removed, since it is not connected to the inner wall. This facilitates handling of the wall section to the user.

Due to the fact that the wall sections is also formed as part of the package, rising costs in the production process can be avoided, since additional working steps to produce and attach the wall section do not accrue.

Advantageously, a predetermined braking line may determine the size, shape and position of the wall section. This enables a fast and clean separation of the wall section from the outer wall in the size, shape and position desired by the manufacturer.

The shape of the wall section may substantially be square, rectangular, round, oval or trapezoidal. These shapes have proven to be especially simple and cost-effective in manufacture and enable a simple removal from the cup wall. Of course, other shapes are also conceivable.

In an advantageous embodiment of the invention, the wall section is rectangular and has a length L and a width B. The length L extends in the peripheral direction and the width B extends in the direction of the envelope. With this arrange-

ment of the wall section in the direction of the alignment axes of the cup, the wall section may be removed or separated particularly easy and simple from the outer wall.

In a further embodiment of the invention, the predetermined breaking line may be supplemented by a bending line, which connects both ends of the predetermined braking line with one another. Thereby it can be prevented that the wall section is completely separated from the cup wall. Thus, the wall section remains attached on the cup.

In an especially advantageous embodiment of the invention, the predetermined breaking line of the wall section may substantially be formed as a perforation. The perforation allows a quick separation of the wall section from the outer wall. If a part of the predetermined breaking line does not have a perforation, the separated surface of the wall section is smooth in this area and does not have any perforation webs.

In an advantageous embodiment of the invention, the wall section may be provided with an imprint at an inner and/or outer side. Therefore, advertisement may be applied e.g. on one side of the wall section and on the other side of the wall section, a collection card, or a valued customer bonus card may be imprinted.

In an advantageous embodiment of the invention, a substantially peripheral imprint may be arranged on the outer side of the inner wall. Thereby it can be ensured that the imprint is visible in any arrangement of the cups with respect to each other through the open wall section. A precise placing of the outer cup with respect to the inner cup can therefore be dispensed with.

In an especially advantageous embodiment of the invention, at least the outer wall of the cup may be composed of a two-dimensional pre-cut part, which can be connected with itself. This structure represents a cost-effective and fast production of the cup with the removable wall section.

In a favorable embodiment of the invention, the wall section may extend at the outer wall around the circumferential direction of the cup. Since the cup is enclosed when being used by a hand of a user in the peripheral direction of the cup, and thus the cup bottom and the cup opening are aligned vertically, removal of the wall section from the outer wall is facilitated to the user by the positioning in the circumferential direction.

In an advantageous embodiment of the invention, the wall section may adjoin an edge of the pre-cut part extending in the envelope direction of the cup. This facilitates removal of the wall section if the pre-cut part is connected with itself, since the portion of the wall section adjoining the edge projects due to the material properties and can therefore easily be held by the user.

In a further embodiment of the invention, the wall section may project over the edge of the pre-cut part in an overlapping manner and form a handle. If the wall section shall be removed, this flap can be gripped very easily and accelerate the removal process.

In an especially preferred embodiment of the invention, an access section may adjoin the wall section at an overlapping portion of the pre-cut part. This access section may be formed such that a portion is cut out in the central portion of the end edge of the pre-cut part, said portion being formed by two edges extending substantially in parallel with respect to another, standing vertically on the end edge, and by the adjoining wall section. If the pre-cut part is connected with itself, the material of the pre-cut part does not overlap in the area of the access section, and caused by the recess produced thereby with respect to the circumferential wall of the cup, the wall sections can more easily be lifted by the fingers of the user and be separated.

In a further embodiment of the invention, the pre-cut part may have a holder adjacent to the wall section to open the wall section more easily. This holder may be a handle attached at the wall section, such as a flap. By such a device, the gripping and removal of the wall section is significantly facilitated for the user.

In an especially advantageous embodiment of the invention, the length L of the wall section may be larger than the width B , wherein the length L extends in the peripheral direction. The ratio of the two dimensions with respect to one another may have an influence on the tear-off behavior of the wall section. Since the length L is larger than the width B , and the length L extends in the circumferential direction, the advantage also results that the tear-off position is improved for the needs of the user.

In a further embodiment of the invention, the wall section may be arranged in a manner inclined at an angle α . Caused by the inclined arrangement of the wall section, the tear-off behavior of the wall section may on the one hand be improved and furthermore, any number of orientations of the imprint on the inner wall can be carried out, said imprint always being visible through the opening of the wall section.

On the other hand, the length L of the wall section may also be arranged in the direction towards the surface line of the cup so that the user is capable of removing the wall section also if the package has a position other than the above described position of use.

It is favorable if the axis of symmetry of the wall section in the peripheral direction of the package forms a point of intersection with an edge of the wall section, said edge adjoining the access section and being particularly rounded. The position of the wall section and of the point of intersection with respect to the axis of symmetry is variable depending on the angle α . Since the wall section is rounded in this area, the unsymmetrical arrangement can optically not be recognized. Furthermore, an advantageous tear-off position of the wall section can be produced by this arrangement.

An embodiment of the invention will now be described by means of the following drawings.

FIG. 1 shows a first embodiment of the package.

FIG. 2 shows a package according to FIG. 1 with a wall section being formed as part of the outer wall, said wall section being partially detached.

FIG. 3 shows a package according to FIGS. 1 and 2, wherein the wall section is detached and removed from the outer wall.

FIG. 4 shows a two-dimensional pre-cut part of an outer wall for a package according to FIG. 1 to 3, wherein the access section was cut out.

FIG. 5 shows a second embodiment of the package.

FIG. 6 shows a third embodiment of the package.

FIG. 7 shows a fourth embodiment of the package.

FIG. 8 shows a fifth embodiment of the package, and

FIG. 9 shows a sixth embodiment of the package.

FIG. 10 shows a seventh embodiment of the package.

FIG. 11 shows an eighth embodiment of the package.

FIG. 12 shows a ninth embodiment of the package.

FIG. 1 shows a front view of a package according to the invention in the form of a cup, having an inner wall 3 and an outer wall 2 and a wall section 4 formed as part of the outer wall 2. The inner wall 3 is composed of a two-dimensional pre-cut part, which is connected with itself. The outer wall 2 is composed of a two-dimensional pre-cut part 6, which is connected in an overlapping portion 9 with itself during manufacture of the cup. The inner wall 3 is arranged with its lower end at a spacing to the lower end of the outer wall 2, wherein this lower end is formed as container bottom 11

5

through a bottom portion. The outer dimensions of the inner wall 3 are smaller than the outer dimensions of the outer wall 2 so that the inner wall 3 is arranged in the outer wall 2 and the insulation space 20 between the inner wall 3 and the outer wall 2 serves for the thermal insulation of the double-walled cup 1 and is filled by a fluid and particularly by gas. The cup 1 has a container opening 10 opposite to the container bottom 11. At this container opening 10 an outwardly crimped mouth roll is arranged, which is formed as part of the inner wall 3 and which encircles the outer wall 2. The inner wall 3 and the outer wall 2 are connected to one another in the area of the container opening and taper at a predetermined angle in the direction of the container bottom 11 so that the shape of a truncated cone is produced in whose bottom portion the inner wall 3 and the outer wall 2 are also connected. Caused by this structure, the double-walled cup obtains a dimensionally stable shape.

The outer wall 2 has a wall section 4 in form of a card, which in a preferred embodiment has a perforated predetermined breaking line 5. This predetermined breaking line 5 is attached during the manufacture of the two-dimensional pre-cut part 6. The size, shape and position of the wall section 4 at the outer wall 2 is optionally variable. The predetermined breaking line 5 may also be a predetermined breaking line 5 whose weakening portion separates the wall section 4 from the outer wall 2. An access section 8 may be arranged at an edge 7 of the pre-cut part 6 in the overlapping portion of the pre-cut part 6. As may be seen in FIG. 5, the pre-cut part 6 is cut out in the area of the access section 8.

If during manufacture of the cup 1, the pre-cut part 6 is connected with itself, so that the edges 7 form an overlapping portion 9, the wall section 4 provided in the outer wall 2 in form of a card, projects in the area of the access section 8. This projecting portion serves for opening the wall section 4 with the fingers of the user more easily. By slightly lifting this portion, the perforation of the predetermined breaking line 5 is damaged and an aimed separation of the wall section 4 along the predetermined breaking line 5 is carried out in the case of a further effect of power.

The portion which serves for lifting the wall section 4 does not have a perforation in the area of the access section 8.

The wall section 4 in form of a card is imprinted on one side and/or on both sides. FIG. 1 shows the imprinted outer wall 2 of the cup with an imprinted wall section 4.

FIG. 2 shows the partially separated wall section 4 at the outer wall 2 of the cup 1. The wall section 4 has a perforated predetermined breaking line. The separation of the wall section 4 formed as a card, from the outer wall 2 does not damage the inner wall 3 of the cup 1. The side of the wall section 4 located in the interior of the cup 1 is also imprinted. For a user the imprint only becomes visible if the wall section 4 is removed from the outer wall 2 of the cup 1.

If the predetermined breaking line 5 of the wall section 4 is not formed along the entire periphery, a separation process does not completely remove the wall section 4 from the outer wall 2 of the cup 1. The wall section 4 remains connected to the outer wall 2 at least in parts.

In the following FIGS. 3 to 9 different embodiments of the wall section 4 according to FIG. 1 are shown. In these Figures, as well as in all other Figures, identical parts are characterized by identical reference numerals and they are only mentioned partially in connection with a Figure.

FIG. 3 shows a preferred embodiment of the wall section 4 formed as a card in the outer wall 2 of the cup 1. The wall section 4 has the dimension length L and width B, wherein the length L is larger than the width B. The length L extends in the peripheral direction U of the cup 1. The two shorter edges

6

have a rounded shape, whereby on the one hand the outer appearance of the wall section 4 is influenced and on the other hand gripping the wall section 4 by the user is facilitated. The wall section 4 is arranged such that the long edges extend in parallel to the container opening 1. The wall section 4 may, however, also be arranged at any angle with respect to the container opening 10.

FIG. 4 shows a two-dimensional pre-cut part 6 of the outer wall 2, which is connected with itself and which together with an inner wall 3 forms a double-walled cup 1. The wall section 4 in the form of a card is formed by means of a predetermined breaking line 5 in the pre-cut part 6. An access section 8 is cut out at the edge 7 of the pre-cut part so that the access section 8 forms two edges extending perpendicular with respect to the edge 7 and adjoining the wall section 4. The material of the access section 8 is removed from the pre-cut part 6. The axis of symmetry of the wall section 4 in the peripheral direction U of the package 1 forms a point of intersection 13 with an edge of the wall section 4 that adjoins with the access section 8. The wall section 4 projects over the edge 7 of the pre-cut part 6 in an overlapping manner and forms a flap serving as a holder 22.

FIG. 5 shows a wall section 4 as in FIG. 4 whose long edges extend in the direction of the envelope direction M of a cup 1. This embodiment does not have an access section 8 in the overlapping portion 9.

In FIG. 6 the wall section is arranged peripherally in the peripheral direction U of the cup 1. The distance of the wall section 4 to the container opening 10 and to the container bottom 11 is optional.

In a further embodiment the wall section 4, as shown in FIG. 7, has an oval shape. The size and position of the oval contour are optionally arranged at the outer wall 2 of the cup 1.

FIG. 8 shows a further embodiment of the wall section 4 with a dimension length L and width B. The length L in this embodiment is larger than the width B so that a rectangular wall section 4 is produced. The length L may also be equally large as the width B so that a square wall section 4 is produced. The corners of the wall section 4 are rounded.

FIG. 9 shows a further embodiment of the wall section 4 according to FIG. 8, wherein the length L extends in the peripheral direction U and the width B extends in the envelope direction M. The edges of the wall section 4 are rounded.

The inner wall 3 and the outer wall 2 are arranged in any orientation with respect to one another and are connected to one another through the mouth roll 12 at the container opening 10 as well as at the container bottom 11. The inner wall 3 has a peripheral imprint so that this imprint can always be seen as soon as the wall section 4 is removed from the outer wall 2.

In a preferred embodiment, the wall section 4 formed as a card is imprinted on both sides. On the outer wall 2 of the cup 1, which is gripped by user, advertisement or the reference to a certain action is imprinted. After the wall section 4 is separated from the outer wall 2, the user can also look at the side of the wall section 4 which was up to then located in the cup. On the rear side of the wall section 4, advertisement or a collector card for bonus points may for instance be imprinted. The wall section 4 separated from the cup 1 then serves as a collector card for bonus points, which are for instance arranged on the outer wall 2 of the cup 1 in the form of stickers.

It must also be noted that further options for the shape and the imprint of the wall section 4 are possible. One option is for instance that the shape corresponds to a company logo or has any other geometric shape.

7

The outer wall **2** is substantially made of paper, cardboard or the like and can therefore be imprinted more easily, wherein this imprintability can even be improved by a plastic foil e.g. of polyethylene attached on the outer side. The inner wall **3** is substantially formed of paper, cardboard or the like and additionally has a plastic layer for sealing the package.

Starting from the explained embodiment, the package may be modified in several ways. For example, the form of the package, and especially of a container, may vary so that an oval, rectangular or cylindrical container is formed (FIGS. **10**, **11** and **12**).

Furthermore, the inner and/or the outer wall may be formed of a fluid tight material, as for example plastic.

The wall section may be located in a corner area of a rectangular container so that an edge of the wall section protrudes beyond and forms an overlap, which facilitates the separating of the wall section.

In a rectangular container according to FIG. **11**, an overlap of the two-dimensional blank may be located on a lateral surface of the prism as well as in the corner areas, which may also comprise a radius.

The invention claimed is:

1. A multi-layered container comprising one inner wall, one outer wall, an opening and a bottom, the outer wall comprises a predetermined removable wall section which discloses an information, the removable wall section comprising a rounded short edge having a corner at each end, the short edge being connected to a longer edge at each of the corners, the inner wall and the outer wall being spaced apart from each other to form an annular insulation space comprising a continuous gas-filled gap between the inner wall and the outer wall, said inner and outer walls are connected to each other only in an area of the container opening and the container bottom, and the removable wall section is a one-piece removable card that is not in contact with the inner wall, extends at the outer wall in a peripheral direction of the container and can be adjoined at an edge of a pre-cut part, said

8

edge extending in a direction from the bottom of the container toward the opening in the container and the removable wall section projects over the edge of the pre-cut part in an overlapping manner and forms a flap serving as a holder.

2. The multi-layered container as claimed in claim **1**, wherein an access section is adjacent to the removable wall section at an overlapping portion of the pre-cut part.

3. The multi-layered container as claimed in claim **2**, wherein the length (L) of the removable wall section is larger than the width (B), and wherein the length (L) extends in the peripheral direction of the container.

4. The multi-layered container as claimed in claim **2**, wherein the removable wall section is arranged inclined with respect to the peripheral direction (U) at an angle α .

5. The multi-layered container as claimed in claim **2**, wherein the length (L) of the removable wall section is arranged in a direction of an envelope line (M).

6. The multi-layered container as claimed in claim **2**, wherein an axis of symmetry of the removable wall section in the peripheral direction (U) of the container forms a point of intersection with the edge of the wall section, said edge adjoining the access section, wherein the point of intersection with respect to the axis of symmetry of the access section is variable depending on the angle α .

7. The multi-layered container of claim **1** wherein the removable wall section is rigid.

8. The multi-layered container of claim **1** wherein at least the outer wall is formed of paper, cardboard or plastic.

9. The multi-layered container of claim **1** wherein a size, shape and position of the removable wall section is determined by a predetermined breaking line.

10. The multi-layered container of claim **1** wherein the information comprises an imprint.

11. The multi-layered container of claim **1** wherein the container is a beverage container.

* * * * *