



US008529603B2

(12) **United States Patent**
Gerbec et al.

(10) **Patent No.:** **US 8,529,603 B2**
(45) **Date of Patent:** ***Sep. 10, 2013**

(54) **SYSTEM AND METHOD FOR DYNAMIC VERTEBRAL STABILIZATION**

(75) Inventors: **Daniel E. Gerbec**, Logan, UT (US); **T. Wade Fallin**, Hyde Park, UT (US)

(73) Assignee: **Stryker Spine** (FR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 16 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/356,947**

(22) Filed: **Jan. 24, 2012**

(65) **Prior Publication Data**

US 2012/0123479 A1 May 17, 2012

Related U.S. Application Data

(63) Continuation of application No. 11/589,648, filed on Oct. 30, 2006, now Pat. No. 8,137,385.

(60) Provisional application No. 60/732,265, filed on Oct. 31, 2005.

(51) **Int. Cl.**
A61B 17/70 (2006.01)

(52) **U.S. Cl.**
USPC **606/255**

(58) **Field of Classification Search**
USPC 606/246, 250–263; 411/544
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

895,492 A * 8/1908 Neate 267/166.1
3,599,245 A 8/1971 Blatchford
3,778,610 A * 12/1973 Wolf 362/418

4,097,071 A * 6/1978 Crawford et al. 285/94
4,181,208 A * 1/1980 Davis 192/207
4,369,769 A 1/1983 Edwards
4,408,601 A * 10/1983 Wenk 606/282
4,479,623 A * 10/1984 Maraghe et al. 244/129.5

(Continued)

FOREIGN PATENT DOCUMENTS

DE 2821678 11/1979
DE 94 19 900 U1 4/1996

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 11/087,434.

(Continued)

Primary Examiner — Mary Hoffman


(74) *Attorney, Agent, or Firm* — Lerner, David, Littenberg, Krumholz & Mentlik, LLP

(57)

ABSTRACT

An intervertebral stabilization device and method is disclosed. The device preferably includes a planar spring enclosed within a housing. The housing is joined to an articulation component at either end, and the articulation components have couplings connectable to anchoring components which are securable to adjacent vertebrae. The planar spring can flex and retract providing relative motion between the adjacent vertebrae. The articulation components are ball and socket joints which allow the entire assembly to flexibly follow the curvature of the spine. A fusion rod with articulation components and couplings at either end may be substituted for the spring device. The couplings enable interchangeability between a fusion rod assembly and spring assembly, so that dynamic stabilization can occur at one vertebral level and fusion at the adjacent vertebral level. An overhung spring assembly with a sideways displaced housing which allows for a shorter pedicle to pedicle displacement is also disclosed.

19 Claims, 29 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,743,260	A	5/1988	Burton		6,699,246	B2	3/2004	Zucherman et al.
4,919,403	A *	4/1990	Bartholomew	267/165	6,699,247	B2	3/2004	Zucherman et al.
4,947,835	A	8/1990	Hepburn et al.		6,761,719	B2	7/2004	Justis et al.
5,034,011	A	7/1991	Howland		6,761,720	B1	7/2004	Senegas et al.
5,036,837	A *	8/1991	Mitchell et al.	606/241	6,770,094	B2	8/2004	Fehling et al.
5,092,866	A	3/1992	Breard et al.		6,783,527	B2	8/2004	Drewry et al.
5,180,393	A	1/1993	Commarmond		6,796,983	B1	9/2004	Zucherman et al.
5,236,460	A	8/1993	Barber		6,802,844	B2	10/2004	Ferree
5,254,967	A *	10/1993	Biasutti et al.	337/165	6,835,205	B2	12/2004	Atkinson et al.
5,282,863	A	2/1994	Burton		6,835,207	B2	12/2004	Zacouto et al.
5,375,823	A	12/1994	Navas et al.		7,022,138	B2	4/2006	Mashburn
5,407,397	A *	4/1995	Foley	474/135	7,029,475	B2	4/2006	Panjabi
5,415,661	A	5/1995	Holmes		7,291,150	B2	11/2007	Graf
5,480,401	A	1/1996	Navas et al.		7,309,357	B2 *	12/2007	Kim
5,520,627	A *	5/1996	Malewicz	602/26	7,377,921	B2 *	5/2008	Studer et al.
5,522,214	A *	6/1996	Beckett et al.	60/517	7,731,734	B2	6/2010	Clement et al.
5,540,688	A	7/1996	Navas et al.		7,879,074	B2	2/2011	Kwak et al.
5,562,737	A	10/1996	Graf et al.		2001/0007073	A1	7/2001	Zucherman et al.
5,609,634	A	3/1997	Voydeville et al.		2001/0012938	A1	8/2001	Zucherman et al.
5,645,599	A	7/1997	Samani		2001/0016743	A1	8/2001	Zucherman et al.
5,672,175	A	9/1997	Martin		2001/0021850	A1	9/2001	Zucherman et al.
5,704,936	A	1/1998	Mazel		2001/0031965	A1	10/2001	Zucherman et al.
5,709,686	A *	1/1998	Talos et al.	606/281	2001/0039452	A1	11/2001	Zucherman et al.
5,725,582	A	3/1998	Bevan et al.		2002/0091446	A1	7/2002	Zucherman et al.
5,733,284	A	3/1998	Martin		2002/0116000	A1	8/2002	Zucherman et al.
5,749,873	A	5/1998	Fairley		2002/0133155	A1	9/2002	Ferree
5,830,166	A *	11/1998	Klopf	602/16	2002/0143331	A1	10/2002	Zucherman et al.
5,836,948	A	11/1998	Zucherman et al.		2002/0151978	A1	10/2002	Zacouto et al.
5,860,977	A	1/1999	Zucherman et al.		2002/0183746	A1	12/2002	Zucherman et al.
5,876,404	A	3/1999	Zucherman et al.		2003/0009226	A1	1/2003	Graf
RE36,221	E	6/1999	Breard et al.		2003/0065330	A1	4/2003	Zucherman et al.
5,934,354	A	8/1999	Price et al.		2003/0109880	A1	6/2003	Shirado et al.
5,961,516	A	10/1999	Graf et al.		2003/0171749	A1	9/2003	Le Couedic et al.
6,048,342	A	4/2000	Zucherman et al.		2003/0191470	A1	10/2003	Ritland
6,068,630	A	5/2000	Zucherman et al.		2003/0220642	A1	11/2003	Freudiger
6,074,390	A	6/2000	Zucherman et al.		2003/0220643	A1	11/2003	Ferree
6,090,112	A	7/2000	Zucherman et al.		2004/0002708	A1	1/2004	Ritland
6,149,652	A	11/2000	Zucherman et al.		2004/0006341	A1	1/2004	Shaolian et al.
6,152,926	A	11/2000	Zucherman et al.		2004/0006343	A1	1/2004	Sevrain
6,156,038	A	12/2000	Zucherman et al.		2004/0024458	A1	2/2004	Senegas et al.
6,176,881	B1	1/2001	Schar et al.		2004/0049189	A1	3/2004	Le Couedic et al.
6,183,471	B1	2/2001	Zucherman et al.		2004/0049190	A1	3/2004	Biedermann et al.
6,190,387	B1	2/2001	Zucherman et al.		2004/0073215	A1 *	4/2004	Carli
6,235,030	B1	5/2001	Zucherman et al.		2004/0078082	A1	4/2004	Lange
6,238,397	B1	5/2001	Zucherman et al.		2004/0082954	A1	4/2004	Teitelbaum et al.
6,241,730	B1 *	6/2001	Alby	606/256	2004/0087950	A1	5/2004	Teitelbaum
6,267,764	B1	7/2001	Elberg		2004/0106995	A1	6/2004	Le Couedic et al.
6,280,444	B1	8/2001	Zucherman et al.		2004/0116927	A1	6/2004	Graf
6,290,700	B1	9/2001	Schmotzer		2004/0117017	A1	6/2004	Pasquet et al.
6,293,949	B1	9/2001	Justis et al.		2004/0143264	A1	7/2004	McAfee
6,296,644	B1	10/2001	Saurat et al.		2004/0147928	A1	7/2004	Landry et al.
6,332,882	B1	12/2001	Zucherman et al.		2004/0153071	A1	8/2004	Zucherman et al.
6,332,883	B1	12/2001	Zucherman et al.		2004/0167520	A1	8/2004	Zucherman et al.
6,371,464	B1 *	4/2002	Porche et al.	267/166.1	2004/0172025	A1	9/2004	Drewry et al.
6,379,355	B1	4/2002	Zucherman et al.		2004/0181282	A1	9/2004	Zucherman et al.
6,402,750	B1	6/2002	Atkinson et al.		2004/0181285	A1	9/2004	Simonson
6,419,676	B1	7/2002	Zucherman et al.		2004/0215191	A1	10/2004	Kitchen
6,419,677	B2	7/2002	Zucherman et al.		2004/0220568	A1	11/2004	Zucherman et al.
6,423,065	B2	7/2002	Ferree		2004/0225289	A1	11/2004	Biedermann et al.
6,440,169	B1	8/2002	Elberg et al.		2004/0236327	A1	11/2004	Paul et al.
6,443,183	B1 *	9/2002	Roorda	137/529	2004/0236328	A1	11/2004	Paul et al.
6,451,019	B1	9/2002	Zucherman et al.		2004/0236329	A1	11/2004	Panjabi
6,451,020	B1	9/2002	Zucherman et al.		2004/0236343	A1	11/2004	Taylor et al.
6,478,796	B2	11/2002	Zucherman et al.		2004/0243239	A1	12/2004	Taylor
6,500,178	B2	12/2002	Zucherman et al.		2004/0267260	A1	12/2004	Mack et al.
6,514,256	B2	2/2003	Zucherman et al.		2005/0010293	A1	1/2005	Zucherman et al.
6,582,400	B1	6/2003	Hawk et al.		2005/0010298	A1	1/2005	Zucherman et al.
6,582,433	B2	6/2003	Yun		2005/0033295	A1	2/2005	Wisniewski
6,585,769	B1	7/2003	Muhanna et al.		2005/0049708	A1	3/2005	Atkinson et al.
6,616,669	B2	9/2003	Ogilvie et al.		2005/0056979	A1	3/2005	Studer et al.
6,626,944	B1	9/2003	Taylor et al.		2005/0065514	A1	3/2005	Studer
6,652,527	B2	11/2003	Zucherman et al.		2005/0065515	A1	3/2005	Jahng
6,652,534	B2	11/2003	Zucherman et al.		2005/0065516	A1	3/2005	Jahng
6,652,585	B2	11/2003	Lange		2005/0071006	A1	3/2005	Kirschman
6,695,842	B2	2/2004	Zucherman et al.		2005/0085815	A1	4/2005	Harms et al.
					2005/0090822	A1	4/2005	DiPoto
					2005/0113927	A1	5/2005	Malek
					2005/0141405	A1	6/2005	Ootera et al.
					2005/0143737	A1	6/2005	Pafford et al.

2005/0143823	A1	6/2005	Boyd et al.	FR	2 799 949	4/2001
2005/0154390	A1	7/2005	Biedermann et al.	FR	2 809 304	11/2001
2005/0171543	A1	8/2005	Timm et al.	FR	2 810 533	A1 12/2001
2005/0177156	A1	8/2005	Timm et al.	FR	2 843 538	2/2004
2005/0182400	A1	8/2005	White	GB	2382304	5/2003
2005/0182401	A1	8/2005	Timm et al.	JP	10277070	10/1998
2005/0203519	A1	9/2005	Harms et al.	WO	94/21185	9/1994
2005/0222569	A1	10/2005	Panjabi	WO	95/05783	3/1995
2005/0245930	A1	11/2005	Timm et al.	WO	97/32533	9/1997
2005/0261682	A1 *	11/2005	Ferree 606/61	WO	98/22033	5/1998
2005/0267485	A1	12/2005	Cordes et al.	WO	99/21500	5/1999
2005/0288670	A1	12/2005	Panjabi et al.	WO	99/21501	5/1999
2006/0009767	A1	1/2006	Kiester	WO	01/08574	A1 2/2001
2006/0015100	A1	1/2006	Panjabi et al.	WO	01/28442	4/2001
2006/0036240	A1	2/2006	Colleran et al.	WO	01/45576	6/2001
2006/0058792	A1	3/2006	Hynes	WO	01/52758	A1 7/2001
2006/0064090	A1 *	3/2006	Park 606/61	WO	01/56481	8/2001
2006/0084988	A1 *	4/2006	Kim 606/61	WO	01/64144	9/2001
2006/0085074	A1	4/2006	Raiszadeh	WO	01/91657	12/2001
2006/0155279	A1	7/2006	Ogilvie	WO	01/91658	12/2001
2006/0184171	A1 *	8/2006	Biedermann et al. 606/61	WO	01/95818	12/2001
2006/0189983	A1	8/2006	Fallin et al.	WO	02/03882	1/2002
2006/0189984	A1	8/2006	Fallin et al.	WO	02/07621	1/2002
2006/0189985	A1 *	8/2006	Lewis 606/61	WO	02/07622	1/2002
2006/0229608	A1 *	10/2006	Foster et al. 606/61	WO	02/07623	1/2002
2006/0235398	A1	10/2006	Farris et al.	WO	02/30336	4/2002
2006/0293663	A1 *	12/2006	Walkenhorst et al. 606/61	WO	02/051326	7/2002
2007/0016193	A1 *	1/2007	Ritland 606/61	WO	02/067792	9/2002
2007/0016204	A1	1/2007	Martinez et al.	WO	02/067793	9/2002
2007/0050032	A1 *	3/2007	Gittings et al. 623/17.12	WO	02/102259	12/2002
2007/0123865	A1 *	5/2007	Schlapfer et al. 606/61	WO	03/015646	2/2003
2007/0173818	A1	7/2007	Hestad et al.	WO	03/045262	6/2003
2008/0140076	A1 *	6/2008	Jackson 606/60	WO	03/077806	9/2003
2008/0177319	A1	7/2008	Schwab	WO	2004/024011	3/2004
2008/0195154	A1 *	8/2008	Brown et al. 606/257	WO	2004017817	3/2004
2008/0195156	A1	8/2008	Ainsworth et al.	WO	2004019762	3/2004
2008/0208260	A1	8/2008	Truckai et al.	WO	2004024010	3/2004
2008/0262554	A1 *	10/2008	Hayes et al. 606/278	WO	2004032794	4/2004
2010/0114318	A1	5/2010	Gittings et al.	WO	2004039239	5/2004

FOREIGN PATENT DOCUMENTS

DE	10320417	12/2004	WO	2004039243	5/2004
EP	322334	6/1989	WO	2004041066	5/2004
EP	669109	8/1995	WO	2004073533	9/2004
EP	0 677 277	10/1995	WO	2004098423	11/2004
EP	768843	4/1997	WO	2004098452	11/2004
EP	1239785	9/2002	WO	2004105577	12/2004
EP	1343424	9/2003	WO	2004105580	12/2004
EP	1399078	3/2004	WO	2004110287	12/2004
FR	2 680 461	A1 2/1993	WO	2005/030066	4/2005
FR	2 704 137	10/1994			
FR	2 717 370	9/1995			
FR	2 738 143	3/1997			
FR	2 778 089	A1 11/1999			

OTHER PUBLICATIONS

U.S. Appl. No. 11/589,512.
U.S. Appl. No. 12/070,256.

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23




Fig. 24




Fig. 25




Fig. 26




Fig. 27




Fig. 28




Fig. 29

SYSTEM AND METHOD FOR DYNAMIC VERTEBRAL STABILIZATION

CROSS REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. patent application No. 11/589,648, filed Oct. 30, 2006, and claims the benefit of the filing date of U.S. Provisional Patent Application No. 60/732,265, filed Oct. 31, 2005, the disclosures of which are hereby incorporated herein by reference.

BACKGROUND OF THE INVENTION

The present invention relates to orthopedic medicine, and more particularly to systems and methods for restricting relative motion between vertebrae.

Unfortunately millions of people experience back pain, and such is not only uncomfortable, but can be particularly debilitating. For example, many people who wish to participate in sports, manual labor, or even sedentary employment are unable to do so because of pains that arise from motion of or pressure on the spinal column. These pains are often caused by traumatic, inflammatory, metabolic, synovial, neoplastic and degenerative disorders of the spine.

In a normal spinal column, intervertebral discs that separate adjacent vertebrae from each other serve to provide stiffness that helps to restrain relative motion of the individual vertebrae in flexion, extension, axial rotation, and lateral bending. However, a damaged disc may provide inadequate stiffness along one or more modes of spinal motion. This inadequate stiffness may result in excessive relative vertebral motion when the spine is under a given load, as when the patient uses the muscles of the back. Such excessive relative motion may cause further damage to the disc, thereby causing back pain and ultimately, requiring replacement of the disc and/or other operations to decompress nerves affected by central, lateral or foraminal stenosis.

Heretofore, some stabilization devices have been proposed to restrict, but not entirely prevent, relative motion between adjacent vertebrae. These devices often contain linear springs that are too long to be easily positioned between adjacent vertebrae. Thus, they are often impossible to implant on motion segments where there is a short pedicle-to-pedicle displacement. Furthermore, known spinal implants typically have components that are either flexible, allowing limited relative motion between adjacent vertebrae, or rigid, providing fusion between vertebrae. Thus, they do not provide for interchangeability between flexible and rigid components. Accordingly, symptoms that would normally indicate stabilization and fusion of adjacent motion segments cannot be adequately treated, and vice versa. In other words, revision of an implant to provide fusion in place of stabilization is typically not feasible. Finally, many devices, when implanted in multiple levels along the spine, do not flexibly follow the natural curvature of the spine. Such devices may therefore cause discomfort, or restrict spinal motion in an unpredictable and unnatural manner.

Therefore, there exists a need for a system and method which corrects the above-noted shortcomings and allows for dynamic vertebral stabilization to restore normal movement and comfort to a patient.

SUMMARY OF THE INVENTION

A first aspect of the present invention is a stabilization system for controlling relative motion between a first vertebra

and a second vertebra. In accordance with this first aspect, an embodiment stabilization system may include a first stabilizer having a first coupling adapted to be attached to a first anchoring member, a second coupling adapted to be attached to a second anchoring member and a resilient member configured to be coupled to the first and second couplings to transmit resilient force between the first and second couplings, the resilient member including a planar spring, wherein at least a portion of the planar spring flexes out-of-plane in response to relative motion between the vertebrae.

In other embodiments of the first aspect, the first stabilizer may further include a casing including a hollow first member and a hollow second member, wherein the resilient member is positioned within a cavity defined by engagement of the first and second hollow members. The resilient member is may also be positioned inside the casing such that the casing limits relative motion of the vertebrae by limiting deflection of the planar spring. The system may also include the first anchoring member and the second anchoring member, where the first and second anchoring members include a yoke polyaxially coupled to a fixation member implantable in a portion of either the first or second vertebra. The system may also include a first rigid connector including first and second couplings adapted to be attached to one of the first and second anchoring members, wherein the couplings are substantially rigidly connected together. In other embodiments, the path followed by the planar spring may be generally spiral-shaped, wherein the planar spring includes a central portion attached to the first coupling and a peripheral portion attached to the second coupling. The first stabilizer may further include a first articulation component configured to articulate to permit polyaxial relative rotation between one of the first or second couplings. The first articulation component may include a semispherical surface and a socket within which the semispherical surface is rotatable to permit polyaxial motion between the resilient member and the first anchoring member. The resilient member may be coupled to the first and second couplings such that the resilient member is able to urge the first and second couplings to move closer together and is also able to urge the couplings to move further apart.

The stabilization system may include a second component comprising a third coupling and a fourth coupling, wherein the third coupling is adapted to be attached to the first anchoring member such that the first anchoring member is capable of simultaneously retaining the first and third couplings. The second component may be a rigid connector, wherein the third and fourth couplings are substantially rigidly connected together, or the second component may be a second stabilizer comprising a second resilient member configured to exert resilient force between the third and fourth couplings.

Another aspect of the present invention is another stabilization system for controlling relative motion between a first vertebra and a second vertebra. In accordance with this second aspect, the stabilization system may include a first stabilizer having a first coupling adapted to rest within a yoke of a first anchoring member, a second coupling adapted to rest within a yoke of a second anchoring member, a resilient member coupled to the first and second couplings to transmit resilient force between the first and second couplings, the resilient member including a planar spring, wherein at least a portion of the planar spring flexes out-of-plane in response to relative motion between the vertebrae and a first articulation component configured to articulate to permit relative rotation between the first stabilizer and one of the first or second couplings.

Still another aspect of the present invention is a stabilization system for controlling relative motion between a first

3

vertebra and a second vertebra. The stabilization system according to this aspect may include a first stabilizer having a first coupling adapted to be attached to a first anchoring member, a second coupling adapted to be attached to a second anchoring member, a resilient member configured to be coupled to the first and second couplings to transmit resilient force between the first and second couplings, the resilient member including a planar spring, wherein at least a portion of the planar spring flexes out-of-plane in response to relative motion between the vertebrae, a first articulation component configured to articulate to permit relative rotation between the first and second couplings and a first rigid connector including third and fourth couplings adapted to be attached to the first and second anchoring members, wherein the third and fourth couplings are substantially rigidly connected together.

Yet another aspect of the present invention is a method for controlling relative motion between a first vertebra and a second vertebra. In accordance with this aspect, the method may include the steps of positioning a planar spring of a first stabilizer attaching a first coupling of the first stabilizer to the first vertebra and attaching a second coupling of the first stabilizer to the second vertebra, wherein, after attachment of the couplings to the vertebrae, the planar spring is positioned to transmit resilient force between the vertebrae via flexure of at least a portion of the planar spring out-of-plane.

Yet another aspect of the present invention is another method for controlling relative motion between a first vertebra and a second vertebra. In accordance with this aspect, the method may include selecting a component selected from the group consisting of a first stabilizer and a first rigid connector, wherein the first stabilizer comprises a first coupling, a second coupling adapted to be attached to a second anchoring member secured to the second vertebra, a resilient member configured to transmit resilient force between the first and second couplings, and a first articulation component configured to articulate to permit relative rotation between the first and second couplings, wherein the first rigid connector comprises a first coupling and a second coupling substantially rigidly connected to the first coupling, attaching a first coupling of the selected component to a first anchoring member secured to the first vertebra and attaching a second coupling of the selected component to a second anchoring member secured to the second vertebra.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete appreciation of the subject matter of the present invention and the various advantages thereof can be realized by reference to the following detailed description in which reference is made to the accompanying drawings in which:

FIG. 1 is a perspective view of a dynamic stabilization assembly according to one embodiment of the invention.

FIG. 2 is an enlarged perspective view a stabilizer of the dynamic stabilization assembly of FIG. 1.

FIG. 3 is an exploded perspective view of the stabilizer of FIG. 2.

FIG. 4 is a further exploded perspective view of the stabilizer of FIG. 2.

FIG. 5 is a partially exploded perspective view of the stabilizer of FIG. 2 having two end caps.

FIG. 6 is a perspective view of the stabilizer of FIG. 2, illustrating attachment of one end cap to an end coupling.

FIG. 7 is a perspective view of the stabilizer of FIG. 2 with attached end caps.

FIG. 8 is a partially exploded perspective view of the dynamic stabilization assembly of FIG. 1.

4

FIG. 9 is a perspective view of two of the stabilizers of FIG. 2, placed end to end, with two end caps being detached therefrom.

FIG. 10 is a perspective view of two of the stabilizers of FIG. 2, placed end to end, with two end caps being attached thereto.

FIG. 11 is a perspective view of two stabilizers of FIG. 2, placed end to end, illustrating the coupling of the ends of the stabilizers to each other.

FIG. 12 is a perspective view of the stabilizer of FIG. 2, coupled end-to-end with a second stabilizer for multi-level vertebral stabilization.

FIG. 13 is a perspective view of the two stabilizers of FIG. 12, illustrating how the articulation components may be used to provide an overall curvature to the assembled modules.

FIG. 14 is a perspective view of the stabilizer of FIG. 2, coupled end-to-end with a rigid connector and an end cap for single level vertebral joint stabilization with joint immobilization at an adjacent level.

FIG. 15 is an exploded perspective view of the stabilizer and rigid connector of FIG. 14, illustrating the coupling of the stabilizer and the rigid connector to each other.

FIG. 16 is a perspective view of the stabilizer and rigid connector of FIG. 14, illustrating how the articulation components may be used to provide an overall curvature to the assembled modules.

FIG. 17 is a perspective view of another dynamic stabilization assembly according to an alternative embodiment of the invention.

FIG. 18 is an enlarged perspective view of a stabilizer and end couplings of the dynamic stabilization assembly of FIG. 17.

FIG. 19 is an exploded perspective view of the stabilizer of FIG. 18.

FIG. 20 is an exploded perspective view of the stabilizer and end couplings of FIG. 18.

FIG. 21 is a partially exploded perspective view of the dynamic stabilization assembly of FIG. 17.

FIG. 22 is a perspective view of an overhung stabilizer and articulating component of an overhung dynamic stabilization assembly designed for shorter pedicle-to-pedicle displacements.

FIG. 23 is an exploded perspective view of the overhung stabilizer of FIG. 22.

FIG. 24 is a partially exploded perspective view of an overhung dynamic stabilization assembly including the components of FIG. 22.

FIG. 25 is another partially exploded perspective view of the overhung dynamic stabilization assembly of FIG. 24.

FIG. 26 is a perspective view of a fully assembled overhung dynamic stabilization assembly of FIG. 24.

FIG. 27 is a perspective view of the dynamic stabilization assembly including the stabilizer of FIG. 22, along with the overhung stabilization assembly of FIG. 24.

FIG. 28 is an exploded perspective view of the dynamic stabilization assembly of FIG. 27.

FIG. 29 is a further exploded perspective view of the dynamic stabilization assembly of FIG. 27.

DETAILED DESCRIPTION

The present invention relates to systems and methods for stabilizing the relative motion of spinal vertebrae. Those of ordinary skill in the art will recognize that the following description is merely illustrative of the principles of the invention, which may be applied in various ways to provide many different alternative embodiments. This description is

5

understandably set forth for the purpose of illustrating the general principles of this invention and is not meant to limit the inventive concepts in the appended claims.

Referring to FIG. 1, one embodiment of a single level dynamic stabilization system 10 is shown. The dynamic stabilization system 10 preferably includes a stabilizer 12, a pair of fixation members 14, a pair of yokes 16 securable to the fixation members 14, and a pair of set screws 18. The fixation members 14, yokes 16, and set screws 18 may be any of a variety of types known and available in the art, or may optionally be specially designed for operation with the stabilizer 12. Each fixation member 14 with its corresponding yoke 16 and set screw 18 provides an anchoring member 19 designed to anchor the stabilizer 12 to a pedicle or other portion of a vertebra (not shown). In the embodiments described and illustrated herein, the fixation members 14 are represented as pedicle screws. However, they could also be other types of screws fixed to other parts of the vertebrae, pins, clips, clamps, adhesive members, or any other device capable of anchoring the stabilizer to the vertebrae. Additionally, each yoke 16 may be unitarily formed with a fixation member 14 as illustrated herein, or each yoke 16 may be a separate entity and be polyaxially securable to a fixation member 14.

The stabilizer 12 is illustrated alone in FIG. 2. As shown in that figure, stabilizer 12 includes a central spring casing 22, and a short arm 26 extending from the spring casing 22 on one side to an articulation component 24. On the opposite side, a longer arm 27 extends from the spring casing 22 to another articulation component 25. An end coupling 28 is also preferably located on the outside of each articulation component 24, 25. It is noted that the particular construction of stabilizer 12 depicted in FIG. 2 may vary. For example, the short arm 26 and longer arm 27 may be flipped to opposite sides.

Referring to FIG. 3, an exploded view of the stabilizer 12 is shown, thereby illustrating the inner components of the stabilizer. For example, a planar spring 20 is shown encased within the spring casing 22. The planar spring 20 is preferably coiled in a planar spiral-like shape and has a threaded inner ring surface 30 and an outer ring surface 32. In addition, the spring casing 22 is made up of two concentric hollow members, an inner hollow member 40 and an outer hollow member 42, with the planar spring 20 being disposed within the inner hollow member 40. A circular bore 44 occupies the center of the inner hollow member 40, creating a round opening from an inside surface 46 to an outside surface 48. A protruding circular lip 49 may also surround the bore 44 where it exits the outside surface 48. An inner wall of the lip 49 is preferably threaded. Similarly, a circular bore 54 occupies the center of the outer hollow member 42, creating a round opening from an inside surface 56 to an outside surface 58. A protruding circular lip 59 may also surround the bore 54 where it exits the outside surface 58.

Shown adjacent to the inner hollow member 40 is the short arm 26, which has a threaded outer surface 76 on the end closest to the inner hollow member 40. This end terminates at a flat end 36. Both surface 76 and flat end 36 are best shown in FIG. 4. On the opposite end of the short arm 26 is the articulation component 24, which terminates at the end coupling 28. Adjacent to the outer hollow member 42 is the long arm 27, which has a threaded terminal segment 78 on the end closest to the outer hollow member 42. The terminal segment terminates at a flat end 37 (best shown in FIG. 4). On the opposite end of the long arm 27 is the articulation component 25, which terminates at the end coupling 28.

When assembled, the short arm 26 fits inside the bore 44 of the inner hollow member 40. The threads on the outer surface 76 engage with the threads on the inner wall 52, thereby

6

securing the pieces together. As mentioned above, the planar spring 20 fits inside the inner hollow member 40. In addition, the long arm 27 fits through the bore 54 of the outer hollow member 42, with the threaded terminal segment 78 engaging the threaded inner ring surface 30 of the planar spring 20. The inner hollow member 40 fits concentrically within the outer hollow member 42, with the planar spring 20 also being disposed inside. Inside of the hollow members 40, 42, the flat ends 36, 37 of the arms 26, 27 are preferably adjacent to one another but not touching.

When assembled with the hollow members 40, 42 and the arms 26, 27, the planar spring 20 can, if acted upon, flex out of the plane within which it is coiled. When the longer arm 27, to which the planar spring 20 is engaged, moves toward or away from the short arm 26, the spiral-like shape of the planar spring 20 preferably extends out of its plane. When the longer arm 27 returns to its original position, the planar spring 20 also preferably recoils back to its plane. During this extension and recoil, the inside surface 46 of the inner hollow member 40, and the inside surface 56 of the outer hollow member 42 act as barriers to limit the movement of the planar spring 20.

Use of the planar spring 20, as opposed to a longer helical spring, keeps the overall length of the stabilizer 12 relatively short. In alternative embodiments, a planar spring according to the invention need not have a spiral-like shape, but can rather be a cantilevered leaf spring, a flexible disc, or the like. Further, in other alternative embodiments, a planar spring need not be used; rather, a different type of spring or a conventional helical spring may be used.

FIG. 4 illustrates the articulation components 24, in an exploded view. As is mentioned above, the articulation component 24 is located adjacent to and couples with the inner hollow member 40, and the articulation component 25 is located adjacent to and couples with the outer hollow member 42. Each articulation component 24, 25 preferably comprises a semispherical surface 60, a cup 62, which are both enclosed by the end coupling 28. The cup 62 is preferably dish shaped, with a cylindrical support wall 64 and two ends. On one end of the cup 62 is a depression 66, and on the opposite side of the cup 62 is a flat end 68. The semispherical surface 60 preferably has a round side 70 which rotatably fits inside the depression 66, so that each of the articulation components 24, 25 thus takes the form of a ball-and-socket joint. The opposite side of each semispherical surface 60 is a connecting side 72 which narrows into a neck 74. The neck 74 preferably widens into either the short arm or the long arm 27, which extends away from the semispherical surface 60 on the opposite side from the round side 70. As is discussed above, the outer wall 76 of the short arm 26 is threaded, as is the terminal segment 78 of the long arm 27. In alternative embodiments, articulation components may be omitted, or may be formed by any other type of mechanical joints known in the art.

The end coupling 28 has a support wall 102 which forms the outer sides of the cup, and a base 104. A circular hole 106 occupies the center of the base 104, and where the edge of the hole 106 meets the base 104, a circular rim 108 preferably surrounds the hole 106. The inside diameter of the rim 108 is preferably less than the diameter of the semispherical surface 60 of the articulation components 24 and 25, so that when assembled the semispherical surface 60 will fit into the end coupling 28 but not be capable of passing through the hole 106. At the opposite end from the base 104, the support wall 102 terminates in a flat edge 110. Protruding from the edge 110 in the same plane as the support wall 102, such that they form continuations of the support wall 102, is a plurality of irregularly shaped teeth 112. Between each tooth 112 and the adjacent tooth is a notch 114.

When assembled, the round side 70 of each semispherical surface 60 rotatably rests in the depression 66 of the cup 62, and the arm 26 or 27 extends away from the joining side 72 of the semispherical surface 60. The generally cup-shaped end coupling 28 fits over each semispherical surface, arm and cup assembly. Each arm 26, 27 extends from its semispherical surface 60 through its respective hole 106. As described above, the arms then extend into the spring casing 22, the long arm 27 connecting to the planar spring 20 and the short arm 26 connecting to the inner hollow member 40. Rotation of either semispherical surface 60 results in movement of its arm 26, 27. When the short arm 26 moves, the flat end 37 of the opposite arm 27 may optionally contact the flat end 36 of the short arm 26 to acts as a stop to limit excessive movement. Similarly, when the long arm 27 moves, the flat end 36 of the opposite short arm 26 may stop excessive movement via contact with the flat end 37 of the long arm 27. Thus the articulation components 24, 25 secure the arms 26, 27 in a rotatable manner to the spring casing 22 to permit the stabilizer 12 to obtain a variable curvature.

The assembled stabilizer 12 can be rotated into locking engagement with end caps or end couplings of other stabilizers for multi-level application. In fact, FIG. 5 illustrates one coupled stabilizer 12, having a coupled end cap 120 and an uncoupled end cap 120. Each end cap 120 preferably has a general cup-shape, much like each end coupling 28. Each end cap 120 preferably includes a support wall 122 which forms the outer sides of the cup, and a solid base 124 which forms the bottom of the cup. The inside diameter of the end cap 120 is sized to fit around either arm 26, 27. At an opposite end from the base 124, the support wall 122 terminates in a flat edge 130. Protruding from the edge 130 in the same plane as the support wall 122, such that they form continuations of the support wall 122, are a plurality of irregularly shaped teeth 132. Between each tooth 132 and the adjacent tooth is a notch 134.

Referring to FIG. 6, an end cap 120 is illustrated in partial engagement to a stabilizer 12. When an end cap 120 is to be attached to an end coupling 28, the end cap 120 is preferably lined up with the end coupling 28 so that the teeth 112, 132 are pointed toward one another. The end cap 120 is then rotated and moved toward the end coupling 28 so that the teeth 132 fit into the notches 114, while the teeth 112 fit into the notches 134. When the teeth 112, 132 are fully seated in the notches 114, 134 such that the teeth 132 touch the edge 110 and the teeth 112 touch the edge 130, the end cap 120 is further rotated until the teeth 112, 132 interlock with each other and the end cap 120 is locked in place. A stabilizer 12 with two end caps 120 each fully engaged on opposite ends of the stabilizer 12 is depicted in FIG. 7. In this depiction, the end caps 120 have been fully rotated so that the teeth 132 of the end caps 120 are interlocked with the teeth 112 of both end couplings 28.

FIG. 8 shows an exploded view of the dynamic stabilization system 10 with a fully assembled stabilizer 12, two anchoring members 19 with yokes 16 and fixation members 14, and two set screws 18. In this design, each fixation member 14 preferably has a pointed end 140 which aids in screwing the member into a corresponding vertebra when implanted. The opposite end of the fixation member 14 is preferably unitarily formed with a U-shaped yoke 16, so that the bottom of the U is a head 142 of the fixation member 14. Each yoke 16 has two curved opposing support walls 144. Alternating between the support walls 144 are two opposing gaps 146, which form a cavity 148 therebetween that occu-

pies the interior of the yoke 16. The inner surfaces 150 of the support walls 144 are also preferably threaded to engage a set screw 18.

According to the embodiment depicted, in use, the stabilizer 12 is inserted into the yokes 16 of two anchoring members 19 whose fixation members 14 have previously been anchored in the pedicles, or other portion, of the corresponding vertebrae. The stabilizer 12 is laid lengthwise into the yokes 16 such that the long axis of the stabilizer 12 is perpendicular to the long axes of the fixation members 14, and so that the spring casing 22 lies between the anchoring members 19. Each end coupling 28/end cap 120 pair preferably rests on the head 142 within the cavity 148. Each end cap preferably occupies the gaps 146, and the two articulation components 24, 25 lie adjacent to, but outside of, the two interior gaps 146.

The end couplings 28 and attached end caps 120 are preferably secured within the yokes 16 of the anchoring members 19 through the use of the set screws 18. One set screw 18 is screwed into the top of each yoke 16 so that its threads engage with the threaded inner surfaces 150 of the support walls 144. The set screws 18 are then tightened to hold the stabilizer 12 in place. As described above, an alternative embodiment of the invention includes yokes 16 which are separate entities from the fixation members 14, and are polyaxially securable to the fixation members 14. If such separate polyaxially securable yokes 16 are included, tightening of the set screws 18 may also press the end couplings 28 and end caps 120 against the heads 142 of the fixation members 14, thereby restricting further rotation of the polyaxially securable yokes 16 with respect to the fixation members 14 to secure the entire assembly. Those of ordinary skill in the art would readily recognize this operation.

Referring to FIG. 9, two assembled stabilizers 12 are illustrated positioned end-to-end with two end caps 120 positioned at the outer ends of the stabilizers 12. Two stabilizers 12 may be interlocked with each other end-to-end and implanted when it is desirable to stabilize the relative motion of three adjacent vertebrae. FIG. 10 depicts a similar assembly, with two stabilizers 12 being illustrated end-to-end, and one end cap 120 being secured to each outer end coupling 28 in a similar fashion to that previously depicted in FIG. 7. On the inner ends of each stabilizer 12, the teeth 112 of each end coupling 28 are aligned to fit into the notches 114 of the facing end coupling 28. FIG. 11 depicts the two stabilizers 12 in an end-to-end fashion and partially interlocked together. The teeth 112 of each facing end coupling 28 are in the notches 114 of the opposite end coupling 28, and the stabilizers 12 have been partially turned so that the teeth 112 are partially interlocked. In FIG. 12, the two stabilizers 12 are shown completely interlocked end-to-end. The end couplings 28 of the two stabilizers 12 are rotated into locking engagement with each other and an end cap 120 is locked onto each unoccupied external end coupling 28. The entire dynamic stabilization assembly has four articulation components 24, 25, which will permit considerable differentiation in orientation between the three fixation members 14 that would be used to attach the stabilizers 12 to three adjacent vertebrae (not shown). In fact, in FIG. 13, two interlocked stabilizers 12 are illustrated with the articulation components 24, 25 in an articulated position so that the stabilizers 12 no longer lie in a straight line, but instead the multi-level dynamic stabilization assembly approximates a curve. This enables the assembly to conform to the desired lordotic curve of the lower spine or to other spinal curvatures, such as those caused by or used to correct scoliosis. Additional levels can be added if desired.

Referring to FIG. 14, a stabilizer 12 is depicted secured end-to-end to a rigid connector 160 to provide dynamic sta-

bilization across one level, and posterior immobilization and/or fusion across the adjacent level. The rigid connector 160 has a rod 162 and an end coupling 164. The end coupling 164 is toothed and notched so that it may engage the end coupling 28 on the stabilizer 12. This is not unlike the other couplings discussed above. In addition, and like that discussed above, the rod 162 may be secured in the yoke 16 of a fixation member 14 with a set screw 18. Similarly, the interlocked end coupling 164/end coupling 28 combination may be secured in the yoke 16 of an anchoring member 19 in a manner similar to the previously described securing of the end couplings and end caps. Additional rigid connectors 160 or stabilizers 12 with associated anchoring members 19 can be added if additional levels are desired.

FIG. 15 depicts an exploded view of the system depicted in FIG. 14, having one stabilizer 12, an end cap 120, and one rigid connector 160. The end coupling 164 has teeth 166 protruding from one end, and notches 167 between the teeth. When the rigid connector 160 is attached to the stabilizer 12, the teeth 166 of the end coupling 164 fit into the notches 114 of the end coupling 28. Simultaneously, the teeth 112 of the end coupling 28 fit into the notches 167 of the end coupling 164. The stabilizer 12 and the rigid connector 160 are rotated in opposite directions so that the teeth 112, 166 interlock and the stabilizer 112 and the rigid connector 160 are locked together. The end cap 120 is interlocked onto the remaining open coupling 28 of the stabilizer 12 as previously described. FIG. 16 depicts one stabilizer 12 interlocked with a rigid connector 160 and an end cap 120, and in a position with components 24, 25 being articulated to allow the assembly to approximate a curve.

Thus, like the above described systems, dynamic stabilization across one level and posterior immobilization and/or fusion across the adjacent level may be accomplished while simultaneously following the desired curvature of the spine. In some cases, it may be desirable to allow immobilization and/or fusion across one level, and dynamic stabilization across the adjacent level on each end. In such a case, a rigid connector 160 with an end coupling 164 at each end could be used, allowing a stabilization module 12 to couple to each end of the rigid connector 160.

Referring to FIG. 17, an alternative embodiment of a stabilization system 168 is depicted. In this system, a stabilizer 170 is secured to two anchoring members 19. As in the previous embodiment, the anchoring members 19 each preferably include two yokes 16 connected with two fixation members 14, and two set screws 18 are preferably used to hold the stabilizer 170 in place.

As seen in FIG. 18, the stabilizer 170 has a spring casing 172 and two articulation components 174, 175. A two-piece end housing 178 also preferably extends from either articulation component 174, 175. As shown in FIG. 19, the spring casing 172 preferably houses a planar spring 180. The planar spring 180 has a first side 182 and a second side 183. Extending from the first side 182 is an arm 184 which narrows into a neck 186 and terminates in a semispherical surface 188. The spring casing 172 has an outer hollow member 190 and an inner hollow member 192. The inner hollow member 192 is of a shallow dish shape, and has a circular plate 194 which forms the base of the hollow member, with a threaded outer rim 196 which encircles the outside of the plate 194. An inner rim 198 encircles a round hole 200 in the center of the plate 194.

Similarly, the outer hollow member 190 is of a deep dish shape with an interior cavity 202. It has a circular plate 204 which forms the base of the hollow member, and a support member 206 which forms the side wall of the hollow member. An inner surface 208 of the support member 206 is threaded,

but a neck 210 extends from the outside of the plate 204 and terminates in a semispherical surface 212. This latter element is different from both inner hollow member 192 and that which is included in the above described embodiments of the present invention.

When assembled, the planar spring 180 preferably fits into the cavity 202 of the outer hollow member 190, with the second side 183 adjacent to the plate 204 of the hollow member 190. The inner hollow member 192 fits over the planar spring 180, so that the arm 184 and the semispherical surface 188 extend through the hole 200 in the inner hollow member 192. Thereafter, the threads on the outer rim 196 engage with the threads on the inner surface 208 of the outer hollow member 190, joining the hollow members 190, 192 to form the casing 172. The spring 180 is thusly captured inside the casing 172, which prevents it from moving axially. When the arm 184 moves toward or away from the outer hollow member 190, the planar spring 180 extends out of its plane. When the arm 184 returns to its original position, the planar spring 180 recoils back towards its plane. During this extension and recoiling, the plate 194 of the inner hollow member 192 and the plate 204 of the outer hollow member 190 act as barriers to limit the movement of the planar spring 180. The arm 184 is encircled by the inner rim 198, which acts as a bearing surface to prevent radial movement of the arm relative to the inferior hollow member 192.

As seen in FIG. 20, a coupling in the form of a two-part end housing 178 fits over each semispherical surface 188, 212. Each end housing 178 has a first wall 220 and a second wall 222. The first wall 220 is shaped like a segment of a cylindrical body that is split lengthwise, and has an inner surface 224 and rounded outer surface 226. At each lengthwise end of the first wall 220, a rounded first hollow 228 is indented into the inner surface 224. Indented into the inner surface 224, between the hollows 228, are two receiving holes 230. The second wall 222 is also shaped like a segment of a cylindrical body and has an inner surface 234 and an outer surface 236. Unlike the first wall 220, the outer surface 236 is not rounded but is squared off so it is flat. The inner surface 234 has a rounded second hollow 238 indented into each lengthwise end. Each pair of rounded hollows 228, 238 cooperates to define a socket sized to receive the corresponding ball 188 or 212. Two pin holes 240 extend from the outer surface 236 through the wall 222 to the inner surface 234, such that two pins 242 can fit through the pin holes 240 and into the receiving holes 230 in the first wall 220. The pins 242 and receiving holes 230 releasably hold the walls 220, 222 together around the semispherical surfaces 188, 212, and prevent shearing of the walls. In other embodiments of the invention, the pins 242 and receiving holes 230 could be replaced by posts and brackets, or a snap mechanism or other mechanisms capable of releasably joining the walls 220, 222.

The assembled stabilizer 170 fits into the yokes 16 of two anchoring members 19, as is best shown in FIG. 17 (shown disassembled in FIG. 21). In the fully assembled state, the end housings 178 are preferably situated perpendicular to the fixation members 14, so that the end housings 178 fit between support walls 144 of anchoring member 19, and the rounded outer surface 226 is cradled on a curved floor 142 between walls 144. Two set screws 18 are thereafter engaged in the threads 150 and tightened. The tightening of the set screws 18 creates pressure on the end housings 178, holding the housings closed around the semispherical surfaces 188, 212. As described in the previous embodiment, each anchoring member 19 may comprise a unitary piece which includes both the fixation member 14 and the yoke 16, or the fixation member 14 and the yoke 16 may be separate pieces. In such an

11

embodiment where the fixation member **14** and yokes **16** are separate pieces, tightening of the set screws **18** may also press the end housings **178** against the heads **142** of the fixation members **14**, thereby restricting further rotation of the yokes **16** with respect to the fixation members **14** to secure the entire assembly.

Like the above embodiment, two stabilizers **170** can be secured end-to-end in accordance with this latter embodiment. When two stabilizers **170** are to be used together, the stabilizers are partially assembled as shown in FIG. **19** and described previously. The semispherical surface **212** or **188** from one stabilizer **170** is preferably placed in the empty hollow **228** of the first wall **220** of the second stabilizer **170** before the second wall **222** is joined to the first wall **220**. When the second wall **222** is joined to the first wall **220**, the semispherical surfaces **212**, **188** are captured in the socket sections **228**, **238** and the modules are joined. A stabilizer **170** can also be employed in combination with a rigid connector to provide dynamic stabilization across one level and posterior fusion across the adjacent level. Additional levels may be added as desired. Multiple stabilization/fusion levels can include two or more sequential rigid connectors, or rigid connectors sequentially interspersed with stabilizers.

Referring to FIG. **22**, a portion of an “overhung” dynamic stabilization system is shown. This system can be used when an offset between adjacent fixation members is desired and/or when a short pedicle-to-pedicle displacement must be accommodated. In this embodiment, a stabilizer **250** includes a housing **252**, an articulation component **254** and an arm **256** which extends from the joint. A tunnel **258** provides an opening for placement of the stabilizer **250** over an anchoring member (best shown in FIG. **26**), and two set screws **259** are used to press a flexible stop **260** against the anchoring member, securing the stabilizer **250** in place.

FIG. **23** depicts an exploded view of the stabilizer **250** in more detail. As shown in that figure, the housing **252** has a chamber **262** which holds the articulation component **254**. A threaded cap **264** is screwed into the housing **252** closing off one end of the chamber **262**. A planar spring **266** with a threaded inner ring **268** is positioned within the cap **264**. Releasably screwed to the inner ring **268** is a socket **270** with a threaded end stud **272**. A cup **274** terminates the socket **270** at the end opposite the threaded end stud **272**. A semispherical surface **276** is connected to the arm **256**, and the semispherical surface **276** rotatably rests in the cup **274**. A tubular sleeve **278** surrounds the socket **270**, semispherical surface **276** and arm **256**. The sleeve **278** has a central bore **280** through which the arm **256** protrudes. The sleeve **278** also has two grooves **282** which run lengthwise down opposite outer sides of the sleeve. When the sleeve **278**, along with the enclosed socket **270**, semispherical surface **276** and arm **256** are in the chamber **262**, the sleeve is held in place by two pins **284**. The pins **284** are inserted through two pin holes **286** which perforate the outer wall of the housing **252**. The inserted pins **284** fit into the grooves **282**, and prevent the sleeve **278** and its enclosed contents from moving axially.

An unassembled stabilization system **248** is shown in FIG. **24**. The system **248** includes the overhung stabilizer **250**, an anchoring member **19**, an anchoring member **288**, an articulation component **24**, an end coupling **28** and an end cap **120**. As described in previous embodiments, the anchoring member **19** has a fixation member **14**, a yoke **16** and a set screw **18**. The anchoring member **288** comprises a fixation member **14** and an extension post **290**. Once again, the fixation members **14** may comprise pedicle screws, screws fixed to other parts of the vertebrae, pins, clips, clamps, adhesive members, or any other device capable of anchoring the stabilizer to the

12

vertebrae. Additionally, each yoke **16** may be unitarily formed with a fixation member **14** as illustrated herein, or each yoke **16** may be a separate entity and be polyaxially securable to a fixation member **14**. The articulation component **24** has a tubular joining arm **292** extending from an end coupling **28**. The joining arm **292** is shaped to fit over the end of the arm **256** which protrudes from the articulation component **254**.

FIG. **25** illustrates the stabilization system **248** in a partially assembled state. The stabilizer **250** is joined to the articulation component **24** and end coupling **28**, with the joining arm **292** fitting over the end of the arm **256** which protrudes from the articulation component **254** through the use of a press fit or other attachment mechanism. The end cap **120** fits on the opposite end of the end coupling **28**, in the manner previously described. The fully assembled stabilization system **248** is shown in FIG. **26**. In this assembly, the end coupling **28** and end cap **120** fit in the yoke **16** of the anchoring member **19**, and are held in place by tightening the set screw **18**, in the same manner set forth previously. The assembled stabilizer **250** is placed over the anchoring member **288**, with the extension post **290** on the anchoring member **288** extending posteriorly through the tunnel **258**. The set screws **259** are engaged in the outer wall of the housing **252** adjacent to the extension post **290**. When the set screws **259** are tightened, they push against the flexible stop **260**, which in turn pushes against the post **290**, holding the stabilizer **250** in place on the extension post **290**. Finally, the joining arm **292** connects the articulation component **24** to the articulation component **254**, thus pivotably connecting the stabilizer **250**, secured to the anchoring member **288**, to the anchoring member **19**.

When the system **248** is fully assembled and anchored to two adjacent vertebrae, motion between the two vertebrae can cause the planar spring **266** to flex out of its plane. Referring back to FIG. **23**, when the two adjacent vertebrae move closer together and the distance between them shortens, the planar spring **266** returns to its plane. When the two adjacent vertebrae move apart and the distance between them lengthens, the planar spring **266** flexes in the opposite direction along the spiral path, toward the sleeve **278**. As the planar spring **266** flexes, the sleeve **278** which holds the articulation component **254** slides along the chamber **262**. The grooves **282** allow the sleeve **278** to slide back and forth past the pins **284**, but the pins **284** restrict axial movement of the sleeve **278** and serve as stops to prevent the sleeve **278** from moving completely out of the chamber **262**.

Referring to FIG. **27**, a multi-level dynamic stabilization system is shown which includes a stabilizer **12** as per FIGS. **1-8**, and an overhung stabilizer **250** as per FIGS. **22-26**. The stabilizer **12** is mounted on two anchoring members **19** and connected via the joining arm **292** to the overhung stabilizer **250** which is mounted on an anchoring member **288**. The resulting dynamic stabilization system provides stabilization across two adjacent vertebral levels. The overhung stabilizer **250** allows one of the levels to have a relatively short pedicle-to-pedicle displacement. FIG. **28** illustrates the stabilizers **12**, **250**, two anchoring members **19** and one anchoring member **288** in an exploded view. Each anchoring member **19** includes a fixation member **14**, a yoke **16** and a set screw **18**, as set forth previously. The anchoring member **288** includes a fixation member **14** with an extension post **290**, as set forth previously.

Referring to FIG. **29**, the stabilizers **12**, **250** and the anchoring members **19**, **288** are shown in a further exploded view. The stabilizer **12** has two end couplings **28**, one end coupling **28** connecting with one end cap **120** thereby forming a cou-

13

pling mountable in a yoke 16. The second end coupling 28 of the stabilizer 12 preferably couples with the end coupling 28 that connects to the joining arm 292, forming a coupling mountable in another yoke 16. The joining arm 292 fits over the arm 256 of the stabilizer 250, thus connecting the stabilizer 250 to the stabilizer 12. The stabilizer 250 is mountable on the anchoring member 288, in the manner set forth previously. When assembled, this two level system has two articulation components 24, one articulation component 25, and one articulation component 254, providing pivotability between the stabilized vertebrae. Additionally, an overhung stabilizer 250, a stabilizer 12, and/or a stabilizer 170 such as that depicted in FIGS. 17-21 can be implanted in combination with a rigid connector 160 such as that depicted in FIGS. 14-16.

Although the invention herein has been described with reference to particular embodiments, it is to be understood that these embodiments are merely illustrative of the principles and applications of the present invention. It is therefore to be understood that numerous modifications may be made to the illustrative embodiments and that other arrangements may be devised without departing from the spirit and scope of the present invention as defined by the appended claims.

The invention claimed is:

1. A stabilization system for controlling relative motion between a first vertebra and a second vertebra, the stabilization system comprising:

a first stabilizer including:

an arm having a long axis and being coupled to a housing, wherein the housing is adapted to engage with a first anchoring member; and

a resilient member coupled to the arm, the resilient member including a planar spring, at least a portion of which is configured to flex out-of-plane in a first direction in response to movement of the vertebrae towards one another and out-of-plane in a second opposing direction in response to movement of the vertebrae away from one another, the planar spring being predisposed to resist such flexion out-of-plane, wherein the housing includes an opening offset from the long axis of the arm, the opening being adapted to receive the first anchoring member.

2. The stabilization system of claim 1, wherein the housing includes a chamber and the resilient member is positioned inside the chamber.

3. The stabilization system of claim 2, wherein the first stabilizer further includes a first articulation component configured to articulate to permit polyaxial relative rotation of the arm.

4. The stabilization system of claim 3, wherein the first articulation component includes a semispherical surface and a socket within which the semispherical surface is rotatable.

5. The stabilization system of claim 1, further comprising first and second anchoring members adapted to engage with the arm and the first and second vertebra, respectively, wherein the first anchoring member is offset from the second anchoring member in a direction extending transverse to the long axis of the arm.

6. A stabilization system for controlling relative motion between a first vertebra and a second vertebra, the stabilization system comprising:

a first stabilizer including:

an arm having a long axis and being coupled to a housing, wherein the housing is adapted to engage with a first anchoring member connectable to the first vertebrae; and

14

a resilient member coupled to the arm, the resilient member including a planar spiral spring, wherein at least a portion of the planar spiral spring is predisposed to resist flexion when being moved out-of-plane in response to relative motion between the vertebrae,

and wherein the housing includes an opening offset from the long axis of the arm, the opening being adapted to receive the first anchoring member.

7. The stabilization system of claim 6, wherein the arm is adapted to attach to a first coupling, the first coupling being configured to engage with a second anchoring member connectable to the second vertebra.

8. The stabilization system of 7, wherein the second anchoring member includes a yoke and a fixation member polyaxially coupled to the yoke, the first coupling being positioned within the yoke of the second anchoring member.

9. The stabilization system of claim 6, wherein the housing includes a chamber and the resilient member is positioned inside the chamber.

10. The stabilization system of claim 9, wherein at least a portion of the planar spiral spring of the first stabilizer is configured to flex out-of-plane in a first direction in response to movement of the vertebrae towards one another, and out-of-plane in a second opposing direction in response to movement of the vertebrae away from one another.

11. The stabilization system of claim 6, wherein a portion of the arm is engaged to a center of the planar spiral spring of the first stabilizer.

12. The stabilization system of claim 11, wherein a threaded section extends from the portion of the arm and the planar spiral spring includes a threaded inner ring, the threaded section being engaged with the threaded inner ring.

13. A stabilization system for controlling relative motion between a first vertebra and a second vertebra, the stabilization system comprising:

a first stabilizer including:

an arm having a long axis and being coupled to a housing, wherein the housing is adapted to engage with a first anchoring member connectable to the first vertebra; and a resilient member coupled to the arm, the resilient member including a planar spring, at least a portion of the spring being predisposed to resist flexion when being moved out-of-plane in response to relative motion between the first and second vertebrae,

wherein the first stabilizer includes a first articulation component configured to articulate to permit polyaxial relative rotation of the arm, and wherein the housing includes an opening offset from the long axis of the arm, the opening being adapted to receive the first anchoring member.

14. The stabilization system of claim 13, wherein the housing includes a chamber and the resilient member of the first stabilizer is positioned inside the chamber.

15. The stabilization system of claim 13, wherein the first articulation component includes a semispherical surface and a socket within which the semispherical surface is rotatable.

16. The stabilization system of claim 13, further comprising a second stabilizer, the stabilizer including:

a first coupling adapted to be attached to a second anchoring member connectable to the second vertebra; a second coupling adapted to be attached to a third anchoring member connectable to the third vertebra; and a resilient member configured to be coupled to the first and second couplings to transmit resilient force between the first and second couplings, the resilient member including a planar spring.

17. The stabilization system of claim 16, wherein at least one of the planar springs of the first and second stabilizers is configured to flex out-of-plane in a first direction in response to movement of the vertebrae towards one another, and out-of-plane in a second opposing direction in response to move- 5 ment of the vertebrae away from one another, the planar spring being predisposed to resist such flexion out-of-plane.

18. The stabilization system of claim 16, further comprising a rigid connector having third and fourth couplings that are substantially rigidly connected, the third coupling being 10 adapted to engage with the third anchoring member and the fourth coupling being adapted to engage with a fourth anchoring member connectable to a fourth vertebra.

19. The stabilization system of claim 16, wherein the second and third anchoring members are substantially aligned 15 along an axis extending through the first and second couplings, and the first anchoring member is offset from the second and third anchoring members in a direction extending transverse to the axis.

* * * * *