

US008539744B2

(12) **United States Patent**  
**Dietrich**

(10) **Patent No.:** **US 8,539,744 B2**  
(45) **Date of Patent:** **Sep. 24, 2013**

(54) **CROP LIFTER AND CROP ACCESSORY ATTACHMENT**

(76) Inventor: **Dave Dietrich**, Assiniboia (CA)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 17 days.

(21) Appl. No.: **13/137,989**

(22) Filed: **Sep. 22, 2011**

(65) **Prior Publication Data**

US 2012/0060462 A1 Mar. 15, 2012

**Related U.S. Application Data**

(60) Continuation-in-part of application No. 12/081,440, filed on Apr. 16, 2008, now abandoned, which is a division of application No. 10/558,199, filed as application No. PCT/CA2005/000012 on Jan. 6, 2005, now Pat. No. 7,650,738.

(51) **Int. Cl.**  
*A01D 34/00* (2006.01)

(52) **U.S. Cl.**  
USPC ..... **56/312**

(58) **Field of Classification Search**  
USPC ..... 56/307, 312, 314, 17.3, 17.4; 292/32, 292/341.11, 341.13; 267/53; 403/87, 91, 403/103, 104  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

658,133 A \* 9/1900 Ullmann ..... 56/312  
723,880 A \* 3/1903 Koch ..... 56/312  
727,576 A 5/1903 Blocki  
791,022 A 5/1905 Gaterman

843,164 A 2/1907 McCutchan  
868,739 A \* 10/1907 Webber ..... 56/313  
1,123,632 A 1/1915 Weisgarber  
1,202,084 A 10/1916 Merkel  
1,204,441 A 11/1916 Holland-Letz  
1,834,008 A 12/1931 Swanson  
1,942,286 A 1/1934 John  
1,979,010 A 10/1934 Paradise  
2,205,497 A 12/1935 Crumb et al.  
2,099,471 A 11/1937 Edgington  
2,141,299 A 12/1938 Hume et al.  
2,141,300 A 12/1938 Hume et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

CA 407654 9/1942  
CA 548220 11/1957  
CA 719825 10/1965

**OTHER PUBLICATIONS**

U.S. Appl. No. 12/081,440, filed Apr. 16, 2008; Dietrich.

*Primary Examiner* — Thomas B Will


*Assistant Examiner* — Joan D Misa

(74) *Attorney, Agent, or Firm* — Nixon & Vanderhye P.C.

(57) **ABSTRACT**

A crop lifter for attachment to a cutting header includes a lifter member adapted for attachment to the header and a lifting finger attached to the lifter member by a quick-attach mechanism such that a leading end of the lifting finger is ahead of and below the knife. The lifting finger is structurally weak compared to the lifting member such that the lifting finger will readily move when striking an obstruction, thereby preventing damage to the lifter member or header. The crop lifter or similar crop accessory can have a latch member at a rear end thereof, and a cooperating latch member attached to the header. The accessory latches to the header and a releasable latch lock prevents forward movement of the accessory that would disengage the latch.

**10 Claims, 5 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

2,287,304 A 6/1942 Hall  
 2,290,404 A \* 7/1942 Kent ..... 56/312  
 2,294,646 A 9/1942 Henry  
 2,484,704 A 10/1949 Girodat  
 2,892,298 A 8/1957 Chaney  
 3,579,967 A 5/1971 Schumacher  
 3,616,631 A 11/1971 Quam  
 3,633,350 A 1/1972 Schumacher  
 3,834,139 A 9/1974 Schumacher et al.  
 4,120,138 A 10/1978 Schumacher  
 4,295,328 A 10/1981 Schumacher  
 4,361,196 A 11/1982 Hoyle, Jr.  
 4,477,253 A 10/1984 Euvrard  
 5,290,030 A 3/1994 Medbury

5,511,977 A 4/1996 Futch, Jr.  
 5,906,091 A 5/1999 Gemar  
 6,244,026 B1 6/2001 Minnihan et al.  
 6,386,528 B1 5/2002 Thorn et al.  
 6,442,919 B1 9/2002 Schumacher  
 6,655,120 B2 12/2003 Schumacher et al.  
 6,691,499 B2 \* 2/2004 Schumacher et al. .... 56/312  
 6,708,477 B2 3/2004 Schumacher et al.  
 7,306,410 B2 12/2007 Borschert et al.  
 7,650,738 B2 1/2010 Dietrich  
 2001/0037635 A1 11/2001 Figliuzzi  
 2002/0093234 A1 7/2002 Thorn et al.  
 2002/0166314 A1 11/2002 Schumacher et al.  
 2003/0005678 A1 1/2003 Schumacher et al.  
 2003/0050131 A1 3/2003 Grace

\* cited by examiner




FIG. 1 (PRIOR ART)




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 8




FIG. 7




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14






FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25



## CROP LIFTER AND CROP ACCESSORY ATTACHMENT

This application is a Continuation-In-Part of application Ser. No. 12/081,440 now abandoned, filed Apr. 16, 2008, which is a Divisional of application Ser. No. 10/558,199, filed Aug. 11, 2006, (now U.S. Pat. No. 7,650,738), which is a 371 (national stage) of PCT/CA05/000012 filed Jan. 6, 2005, the entire contents of which are hereby incorporated herein by reference in this application.

This invention is in the field of cutting headers such as are used in agriculture for cutting crops for harvest and the like, and in particular with crop lifters and like accessories such as are mounted on such headers to increase crop gathering and retention in the harvesting machine.

### BACKGROUND

For various reasons crops sometimes are lying so close to the ground that it is difficult to cut them with a conventional harvest header. Some crops are inherently short, while others may be taller, but are prone to fall down when they reach maturity. Heavy rain or hail can also cause crop to be lying close to the ground at harvest time.

Typically the knife on cutting headers comprises a knife bar extending along the front lower edge of the header, with a plurality of triangular knife sections attached to the bar such that the apex of the triangle extends forward from the bar. The exposed side edges of the knife sections are sharpened. Guards are attached to the front lower edge of the header and serve to protect the knife sections from breakage when contacting stones and like obstructions. The guards comprise pointed guard fingers extending forward, and the knife moves back and forth along the edge of the header in a slot cut laterally through the guard fingers. In addition to protecting the knife, the guard fingers also enable the knife sections to cut the crop. As the knife section moves back and forth it pushes crop against the sides of those portions of the guard finger that are above and below the slot, shearing the crop stalks.

A conventional knife is a few inches above the ground when the header is in its lowest position, such that very short or downed crop material will pass under the knife and be lost. Many different kinds of "crop lifters", as they have come to be known have been developed over the last century and more. Typically these crop lifters are attached to the header and/or the forward extending point of the guard finger, and provide an arm of various designs that rides along the ground ahead of the knife. A lifting finger extends at a shallow angle from the front of the arm back and over the knife. As the header moves down the field, the arm rides along the ground and under the downed crop stalks, which then are lifted and pass over the lifting finger to the knife, where they are cut and continue moving onto the header from where they can be passed to the harvester, swather table, or the like.

U.S. Pat. Nos. 700,029 and 791,022 to Gatermann, 2,734,332 to Fisher, 2,892,298 to Chaney, 2,960,814 to Babcock, and Canadian Patent Number 407,654 to Young disclose such a crop lifter that is pivotally attached to the header so as to be able to move up and down to follow the ground. The Babcock and Fisher devices float on the ground, while the others are biased toward the ground by springs. U.S. Pat. No. 4,120,138 to Schumacher illustrates a crop lifter that is fixed to the header instead of pivoting, but is made of spring steel so that same may move up and down to follow the ground.

The leading ends of the lifting fingers on these devices is fixed in relation to the arm such that the leading end is at a

fixed distance above the ground, but quite close to the ground in order to lift as much crop as possible. Generally speaking crop stalks that pass under the leading end will be lost, and those that pass over will be harvested.

Most commonly in the prior art the leading end of the lifting finger is generally the leading end of the arm, and is therefore upturned to provide a ski effect and ride over the ground instead of digging in. In the Chaney and Fisher devices, the leading end is ahead of the arm and is pointing generally down very close to the ground to collect the lowest lying crop possible. In the Fisher device, an adjustment is provided to vary the angle of the lift finger, and the lift finger can also be longitudinally adjusted relative to the arm to vary the distance from the leading end of the lifting finger to the ground.

If even a small obstruction is contacted by the Chaney or Fisher devices, they will not ride over it, but will be required to push it to the side, making them more subject to damage. A problem with conventional lifters of substantially all types is that breakage, bending, and deformation is not uncommon as a result of contact with obstructions or ground variations in the field. Repair of such damage is time consuming, requiring removal of the bolts or like fasteners attaching the lifter, and repair if possible by straightening with a press, welding, or the like. Often replacement is necessary at fairly significant expense.

Demonstrating another alternative crop lifter, United States Patent Application Publication 2001/0037635 of Figliuzzi discloses a crop lifter that provides a lifting finger that extends rearward and upward from the point of a guard finger. In one illustrated embodiment the point of the guard finger is extended substantially forward from a conventional location.

Generally cutting headers are used in taller crops as well as on the short and downed crops described above. In such crops the header is raised a substantial distance above the ground. Often in such taller crops however there will be crop stalks that have fallen over due to insect damage, weather, or the like and are closer to the ground than the desired cutting height. It is problematic to operate conventional crop lifters below the cutting height to lift these downed stalks.

Crop lifters interfere somewhat with normal operations of the header when harvesting taller crops with the header raised a substantial distance above the ground. During turns in particular, because the crop lifters generally extend a considerable distance ahead of the header, some crop stalks are pushed over and not cut. It is common practice therefore to remove the crop lifters when using the header on taller crops. In view of this, and the further requirement as discussed above to remove the lifters for repair and replacement, there is also considerable prior art directed to providing a crop lifter that is easily installed and removed.

U.S. Pat. No. 3,579,967 to Schumacher discloses a quick attachment mechanism for a crop lifter. A rear end of a springy arm of the crop lifter defines a notch that fits into an annular groove in a nut that attaches the guard to the header. The extreme rear end of the notched portion is bent down, such that the notch can only be inserted into the groove when the front end of the arm is tilted downward. After insertion, the front end of the arm is raised, and a hook is placed over the guard finger to lock the arm in tension and in the raised position. With the arm so raised, the bent portion at the rear of the arm prevents the arm from moving forward and disengaging the grooved nut.

U.S. Pat. Nos. 4,295,328 and 6,442,919 and U.S. Patent Application Publication 2003/0005678 of Schumacher disclose quick attachment mechanisms for crop lifters that use the bent rear notch and provide alternate mechanisms using



3

springs, clips and the like to hold the arm in the raised position by releasably securing the arm to the guard finger.

Canadian Patent Numbers 548,220 to A. Claas and 719,825 to R. Claas disclose a quick attachment mechanism for a crop lifter that attaches only to the guard finger with a spring biased clamp.

#### SUMMARY OF THE INVENTION

It is an object of the present invention to provide a crop lifter that overcomes problems in the prior art. It is also an object of the present invention to provide a crop accessory attachment mechanism that overcomes problems in the prior art.

The crop lifter includes a structurally weak portion adapted to move by bending or breaking when striking an obstruction, thereby preventing damage to the crop lifter. The structurally weak portion can be quickly replaced.

The present invention provides a crop lifter, sunflower pan, or like crop accessory that attaches quickly to the header. A mid-portion of the apparatus engages a guard finger and a rear end of the apparatus is attached to the header with a latch. A latch member on the rear end of an arm or accessory engages a cooperating latch member attached to the header, and the rear end of the arm or accessory comprises a lock mechanism to hold the arm or accessory in place.

The present invention provides, in a first embodiment, a crop lifter adapted for attachment to a cutting header having a knife and cooperating guards mounted along a lower front edge thereof. The crop lifter comprises a lifter member adapted for attachment to the header and a lifting finger attached to the lifter member by a quick-attach mechanism such that a leading end of the lifting finger is ahead of and below the knife. A carrying portion extends rearward from the leading end of the lifting finger to guide lifted crop to the knife for cutting. The lifting finger is structurally weak compared to the lifting member such that the lifting finger will readily move when striking an obstruction, thereby preventing damage to the lifter member.

The present invention provides, in a second embodiment, a crop accessory adapted for attachment to a cutting header having a knife mounted along a lower front edge thereof and guards attached to the lower front edge with guard bolts. The crop accessory comprises a header latch member adapted for attachment to a guard bolt on the header. An accessory latch member at a rear end of the accessory is adapted to move rearward into engagement with the header latch member such that the rear end of the accessory is maintained in substantially fixed vertical and lateral relationship to the header. A guard finger aperture is defined on the accessory forward of the accessory latch member and oriented such that a forward extending guard finger of a guard enters the guard finger aperture when the accessory latch member is moved rearward into engagement with the header latch member, and a releasable latch lock is operative to prevent forward movement of the accessory latch member with respect to the header latch member.

#### DESCRIPTION OF THE DRAWINGS

While the invention is claimed in the concluding portions hereof, preferred embodiments are provided in the accompanying detailed description which may be best understood in conjunction with the accompanying diagrams where like parts in each of the several diagrams are labeled with like numbers, and where:

4

FIG. 1 is a schematic top view of a cutting header of the prior art;

FIG. 2 is an exploded side view of a crop lifter of the invention;

FIG. 3 is a side view of the assembled crop lifter of FIG. 2;

FIG. 4 is a side view of an alternate embodiment of the crop lifter;

FIG. 5 is a perspective view of the locking portion of the lifting finger;

FIG. 6 is a side view of the twist and lock mechanism showing the lifting finger in a first orientation for insertion into the bore of the mounting bracket;

FIG. 7 is a side view of the twist and lock mechanism of FIG. 6 showing the lifting finger in a second orientation for locking same into the bore of the mounting bracket;

FIG. 8 is a side view of an alternate embodiment of a locking portion of a lifting finger;

FIG. 9 is a side view of an alternate embodiment of the crop lifter;

FIG. 10 is a side view of a crop lifter attached to a header with a releasable latch mechanism;

FIG. 11 is a side view of a header latch member of the latching mechanism of FIG. 10;

FIG. 12 is a schematic section view showing the legs of the arm latch member engaged in a groove on each side of the shaft of the header latch member;

FIG. 13 is a schematic top view of a sunflower pan incorporating a releasable latch mechanism of the invention for attachment to a header;

FIG. 14 is a side view of the sunflower pan of FIG. 13;

FIGS. 15 and 16 are side views of a further alternate embodiment of the crop lifter illustrating the latching engagement of the arm to the header;

FIG. 17 is a schematic top view of a latch lock that could be used with the embodiment of FIG. 9 or 10 shown in the open position with the header and arm latch members fully engaged;

FIG. 18 is a schematic top view of the latch lock of FIG. 17 shown in the closed position with the header and arm latch members fully engaged;

FIG. 19 is a schematic top view of a latch lock that could be used with the embodiment of FIG. 9 or 10 comprising a spring catch shown in the closed position adjacent to the header latching member;

FIG. 20 is a schematic top view of the latch lock of FIG. 19 shown in the closed position with the header and arm latch members fully engaged;

FIG. 21 is a schematic top view of the latch lock of FIG. 19 shown with the spring elements forced to an open position;

FIG. 22 is a schematic side view of an alternate latch lock for use with the embodiment of FIG. 9 or 10 comprising an alternate spring catch shown in the closed position with the header and arm latch members fully engaged;

FIG. 23 is a bottom view of the rear end of an alternate spring element for use with the embodiment of FIG. 22 where the recessed portion is provided by an aperture through the spring element;

FIG. 24 is a perspective view of an alternate embodiment of the header and arm latch members;

FIG. 25 is a side view of an alternate crop lifter wherein the guard finger aperture is located at the front end of the arm, and the rear end of the arm latches to the header.

#### DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

FIG. 1 illustrates a cutting header 2 of the prior art having a knife 4 and cooperating guards 6 mounted along a lower



5

front edge thereof. The guards **6** have guard fingers **8** extending forward from the knife **4**. The header is designed to travel along a field in an operating travel direction T.

A crop lifter **10** of the invention for attachment to the header **2** is illustrated in FIGS. **2** and **3**. The crop lifter **10** comprises a lifter member **12** adapted for attachment to the header **2** and a lifting finger **14** attached to the lifter member **12** by a twist and lock quick-attach mechanism **16** such that a leading end **18** of the lifting finger **14** is ahead of and below the knife **4**. A rear carrying portion **20** of the crop lifter **10** extends rearward from the lifting front portion immediately behind the leading end **18** of the lifting finger **14** to carry lifted crop to the knife **4** for cutting.

In the illustrated embodiment of FIGS. **2** and **3** the carrying portion **20** is provided by a rear portion of the lifting finger **14**. In operation the leading end **18** of the lifting finger **14** will pass under low lying crop stalks and the stalks will then be lifted by the front portion of the lifting finger **14** and carried by the rear carrying portion **20** of the lifting finger **14** to the knife **4**.

In the embodiments illustrated in FIGS. **2-4**, the lifter member **12** consists solely of a bore member or mounting bracket **22** attached to one of the guard fingers **8**. In the embodiment of FIGS. **2** and **3**, the guard finger **8** defines a finger hole **24** extending therethrough, and the mounting bracket **22** defines a bracket hole **26**. The mounting bracket **22** is attached to the guard finger **8** by a bolt **28** extending laterally through the bracket hole **26** and finger hole **24** as illustrated in FIG. **3**. The mounting bracket **22** can be pivoted up and down to vary a distance between the leading end **18** of the lifting finger **14** and ground level, and a pivot lock mechanism is operative to fix the mounting bracket **22**, and thus the lifting finger **14**, at desired pivotal location with respect to the guard finger **8**. The pivot lock mechanism can be provided by a stop pin **25** placed through a hole **21** in the mounting bracket **22** and a selected one of a plurality of stop holes **23** in the guard finger **8** to prevent movement of the mounting bracket **22** up or down and thus prevent movement of the leading end **18** of the lifting finger **14**. Similarly the pivot lock mechanism can be provided simply by bolt **28**, which could be loosened to pivot the mounting bracket **22** up or down to achieve a desired orientation and then tightened to clamp the mounting bracket to the guard finger **8** and fix the lifting finger **14** at the desired orientation. Adjustment of the relative elevations of the leading end **18** of the lifting finger **14** and the guard finger **8** can thus be made to suit different crop conditions.

Guards **6** having guard fingers **8** that define finger holes **24** can be manufactured as original equipment or after-market options. Such guards **6** would be attractive in that they would not interfere with the conventional operation of the machine, but would allow for easy installation of the crop lifter **10** of the invention.

In the alternate embodiment of FIG. **4**, the mounting bracket **22** is attached to the guard finger **8** by a spring biased clamp **30**, such as is known in the prior art of Claasen. Thus in the embodiments of FIGS. **2-4**, the crop lifter **10** is very simple and economical, and readily mounted to the header **2**.

The lifting finger **14** is made from a resilient plastic, nylon, or similar material so that it is structurally weak compared to the lifting member **12** such that the lifting finger **14** will readily move, by breaking or bending when striking an obstruction, thereby preventing damage to the lifter member **12**. The lifting fingers **14** can also be somewhat flexible so they are less likely to dig stones or the like out of the ground, but will flex around such obstructions. Such raised stones can cause damage to the machine.

6

The lifting fingers **14** are relatively inexpensive, and the twist and lock quick-attach mechanism **16** allows for very quick removal of broken lifting fingers **14** and replacement with new ones. Thus, compared to prior art crop lifters, maintenance time and expense is greatly reduced. The lifting fingers **14** can also be made to flex and bend readily to resist breakage, although sometimes they may become badly bent and require replacement prior to breaking.

The lifting fingers **14** can also be easily cut with snips or the like to the desired length so that the leading end **18** thereof is located at the desired picking height relative to the ground. The lifting fingers **14** can be cut to a length such that they actually touch or rake the soil surface if desired, allowing the lifter **10** to lift crop stalks that are laying flat on the ground.

The lifting finger **14** can have a larger diameter at a front portion thereof to resist breakage, and also the front portion can be very long if desired so that the lifting fingers will reach substantially below the header. The lifting fingers will then lift fallen or leaning stalks in a higher crop where the header is operated at a considerable height above the ground to minimize the amount of material entering the harvesting machine, but where there are some stalks that have fallen and would conventionally be missed.

Details of one embodiment of a twist and lock quick-attach mechanism **16** are illustrated in FIGS. **5-7**. The illustrated twist and lock quick-attach mechanism **16** comprises a bore **40** defined by the mounting bracket **22** and oriented substantially aligned with the operating travel direction T and sloping upward from a front end thereof to a rear end thereof as illustrated in FIG. **2**. The bore **40** and a cooperating locking portion **42** of the lifting finger **14** are configured such that the locking portion **42** of the lifting finger **14** can slide longitudinally in the bore **40** when oriented in a first orientation to be inserted into the bore **40**, as seen in FIG. **6**, and are configured such that the locking portion **42** locks in the bore **40** when twisted a quarter turn about a finger axis FA to a second orientation shown in FIG. **7**.

The locking portion **42** of the lifting finger **14** comprises front and rear lobes **44, 46** extending radially from the surface of the lifting finger **14**. The bore has a flattened rear portion **48** and configured such that the lifting finger **14** can be inserted into the bore **40** in the first orientation and the rear lobe will pass through the flattened portion **48** at the rear end of the bore **40**. When fully inserted the front lobe **44** bears against a front end of the bore **40** and the lifting finger **14** can be twisted a quarter turn about the finger axis FA to the second orientation with the rear lobe **46** bearing against the flattened portion **48** at the rear end of the bore **40**.

Thus the lifting finger **14** is readily installed and removed by twisting same one quarter turn about the finger axis FA.

FIG. **8** illustrates an alternate embodiment where the cooperating locking portion **42A** of the lifting finger **14A** are configured such that the locking portion **42A** of the lifting finger **14A** can slide longitudinally in a bore. The bore and locking portion **42A** are configured such that the locking portion **42A** of the lifting finger **14A** can slide longitudinally into the bore and such that movement of the locking portion **42A** out of the bore is resisted by friction forces between walls of the bore and the locking portion **42A** of the lifting finger **14A**. In the illustrated embodiment of FIG. **8** the outer surface of the locking portion **42A** comprises protrusions **41A** extending outward therefrom to increase friction between the locking portion **42A** and walls of the bore. Conveniently the bore and locking portion **42A** will be cylindrical to allow insertion and removal with a twisting action.

FIG. **9** illustrates an alternate embodiment of the crop lifter **110** wherein the lifter member **112** comprises an arm **150**, and



in the illustrated embodiment the arm 150 is further adapted to ride along the ground. The arm 150 is attached at a rear end thereof to the header 2 by conventional guard bolts 160 and includes an aperture member 162 at a middle portion thereof that defines a guard finger aperture oriented to engage the point of a guard finger 108 when the rear end of the arm 150 is attached to the guard bolt 160. The arm 150 has an upwardly curved forward end 154. The quick-attach mechanism 116 is pivotally attached about a pivot axis PA to an upper portion of the forward end 154 of the arm 150 such that the lifting finger 114 can be pivoted up and down to vary a distance between the leading end 118 of the lifting finger 114 and ground level.

In the illustrated embodiment of FIG. 9 the lifting finger 114 extends only forward of the quick-attach mechanism 116. The carrying portion 120 of the crop lifter 110 to guide lifted crop to the knife for cutting is provided by the upward and rearward extending portion 156 of the arm 150. Alternately, another finger member extending in the required direction could be attached to the arm 150 by another quick-attach mechanism, or a through finger such as illustrated in FIGS. 2 and 3 could be used.

FIG. 10 illustrates a crop lifter 10 that can be quickly installed on a header 2 by sliding the lifter arm 50 rearward such that a guard finger 8 of a guard 6 attached to the header 2 engages a guard finger aperture in an aperture member 62 on the lifter 10 and the rear end of the lifter arm 50 moves into latching engagement with the header 2. The rear end of the lifter 10 is then locked to the header 2 to prevent forward movement of the lifter 10. Releasing the latch lock 66 at the rear end of the lifter arm 50 allows the lifter 10 to be moved forward and removed from the header 2.

In the crop lifter of FIG. 10, a mounting bracket 63 is pivotally attached to the aperture member 62 by a bolt 65 extending laterally through a hole in a lug 67 extending up from the front end of the aperture member 62, and a lifting finger 69 is secured in the mounting bracket 63. As in FIG. 3 above, the mounting bracket 63 can be pivoted up and down to vary a distance between the leading end of the lifting finger 63 and ground level, and then locked at the desired orientation. The nut 71 on the bolt 65 could be loosened to pivot the mounting bracket 63 up or down to achieve a desired orientation and then tightened to clamp the mounting bracket 63 to the lug 67 and fix the lifting finger 69 at the desired orientation. Alternately, or in addition, a stop pin 73 can be positioned through a projecting tab 75 of the mounting bracket 63 and through a selected one of a plurality of stop holes 77 in the lug 67 to block movement up or down of the mounting bracket 63, and thereby lock the mounting bracket 63 with respect to the aperture member 62, and thus the guard finger 8, and fix the lifting finger 69 at a selected one of a plurality of angular orientations.

A header latch member 70 is adapted for attachment to a guard bolt 60 on the header 2. An arm latch member 72 is located at a rear end of the arm 50 and is adapted to move rearward into engagement with the header latch member 70 such that the rear end of the arm 50 is maintained in substantially fixed vertical and lateral relationship to the header 2.

In the illustrated embodiment of FIG. 10, as shown in FIG. 11, the header latch member 70 defines an annular groove 74 such that there is a groove on each side thereof, and the arm latch member 72 at the rear end of the arm 50 comprises two legs 76, as shown in FIG. 12, configured to engage the annular groove 74 on each side thereof with the shaft 71 of the header latch member 70 between the legs 76. Providing an annular groove 74 allows the header latch member 70 to be oriented in any direction and still have grooves on each side thereof to

engage the legs 76. Thus with the legs 76 engaged in the annular groove 74, the rear end of the arm 50 is vertically and laterally fixed with respect to the header 2.

As the arm 50 is moved rearward to engage the arm latch member 72 with the header latch member 70 the guard finger 8 enters the guard finger aperture defined by the aperture member 62 on the arm 50 forward of the arm latch member 72. Thus when the latch members 70, 72 are fully engaged, the guard finger 8 is fully engaged in the aperture member 62 and the lifter 10 is thus secured to the header 2. The releasable latch lock 66 is operative to prevent forward movement of the arm latch member 72 with respect to the header latch member 70 and so maintains the lifter 10 secured to the header 2.

In the embodiment of FIG. 10 the latch lock 66 comprises a spring catch maintained in a closed position by a bias force and configured to be pushed open as the arm latch member 72 is moved rearward into engagement with the header latch member 70. The spring catch is configured to close when the latch members 72, 70 are fully engaged to prevent forward movement of the arm 50. The spring catch comprises a spring element 84 attached to the arm 50 and defining a recessed portion, provided by an aperture 86, at the arm latch member 72. The spring element 84 is biased toward the arm latch member 72, and has a lip 88 extending rearward and outward from a rear end thereof. The spring element 84 is configured such that the spring element 84 is pushed outward by contact with the header latch member 70 as the arm latch member 72 is moved rearward into engagement with the header latch member 70, and moves inward when the latch members are fully engaged and the aperture 86 aligns with the top of the header latch member 70. The spring element 84 thus maintains the header latch member 70 in the aperture 86 and prevents forward movement of the arm 50.

As illustrated in FIG. 11, the header latch member 70 is attached to the header at a proximate end thereof 70A thereof. As seen in FIG. 10, the vertical location of the header latch member 70 is adjusted by providing shims 73 between the header 2 and the header latch member 70 as required so that the bottom of the groove 74 is aligned with the top of the guard finger 8 such that the arm 50 can move rearward with the legs 76 in the groove 74 on each side of the shaft 71 of the header latch member 70. The guard bolt 60 extends through the shims 73 and into a threaded aperture through the header latch member 70 which acts as a nut for securing the bolt 60, and is tightened with a wrench on a hexagonal portion 77 thereof.

The illustrated header latch member 70 comprises a sloped outer wall 75 sloping outward and rearward from a distal end 70B opposite the proximate end 70A. The illustrated header latch member 70 has conical walls so that no alignment is required, and the rear wall will always slope outward.

The edge of the aperture 86 in the spring element 84 engages the outer wall 75, and the spring element 84 exerts a force toward the proximate end 70A of the header latch member 70 such that during vibration between the spring element 84 and the header latch member 70, such as will normally be encountered in operation, the edge of the aperture 86 in the spring element moves rearward down the sloped outer wall 75, thereby tightening the arm latch member 72 to the header latch member 70.

The illustrated latch mechanism can be used to similarly attach other crop accessories to a header. FIGS. 13 and 14 illustrate, for example, a sunflower pan 91 with an accessory latch member corresponding to the arm latch member 72 of FIG. 10, provided for example by a slot in the rear end of the sunflower pan 91, and also a spring element 84 and aperture 86. The header latch member is mounted in the same fashion



on the header, and the sunflower pan **91** is moved rearward such that guard fingers on the header enter guard finger apertures in aperture members **62** on the bottom of the sunflower pan **91** and the aperture **86** falls over the header latch member. It is contemplated that any number of like crop accessories could be attached with such a mechanism.

FIGS. **15** and **16** also illustrate an alternate crop lifter **210** that can be quickly installed and removed from a header **202** by sliding the lifter arm **250** rearward such that a guard finger **208** of a guard **206** attached to the header **202** engages a guard finger aperture in an aperture member **262** defined by the lifter **210** and the rear end of the lifter **210** moves into latching engagement with the header **202**. The rear end of the lifter **210** is then locked to the header **202** to prevent forward movement of the lifter **210**. Releasing the latch lock **266** at the rear end of the lifter **210** allows the lifter **210** to be moved forward and removed from the header **202**.

The crop lifter **210** comprises a header latch member **270** adapted for attachment to a guard bolt **260** on an underside of the header **202**, as opposed to the mounting on top of the header as in the embodiment of FIG. **10**. An arm **250** is adapted to ride along the ground. An arm latch member **272** is located at a rear end of the arm **250** and is adapted to move rearward into engagement with the header latch member **270** such that the rear end of the arm **250** is maintained in substantially fixed vertical relationship to the header **202**.

In the illustrated embodiment of FIGS. **15-22** the header latch member **270** defines an annular groove **274** such that there is a groove on each side thereof, and the arm latch member **272** comprises two legs, as illustrated in FIG. **17**, configured to engage the annular groove **274** on each side thereof. Providing an annular groove allows the header latch member **270** to be oriented in any direction and still have grooves on each side thereof to engage the legs **276**. Thus with the legs **276** engaged in the annular groove **274**, the rear end of the arm **250** is vertically and laterally fixed with respect to the header **202**.

FIG. **24** illustrates an alternate embodiment wherein the header latch member **370** defines a forward facing aperture **375** and wherein the arm latch member **372** comprises a dowel **377** configured to slide into the aperture **375**.

As the arm **250** is moved rearward to engage the header and arm latch members **270**, **272** the guard finger **208** enters the guard finger aperture defined by the aperture member **262** on the arm **250** forward of the arm latch member **272**. Thus when the latch members **270**, **272** are fully engaged, the guard finger **208** is fully engaged in the aperture member **262** and the lifter **210** is thus secured to the header **202**. The releasable latch lock **266** is operative to prevent forward movement of the arm latch member **272** with respect to the header latch member **270** and so maintains the lifter **210** secured to the header.

Alternate embodiments of the latch lock **266** are illustrated in FIGS. **17-22**. In the embodiment of FIGS. **17** and **18** the latch lock **266** comprises a lock plate **280** pivotally attached to a top of the arm **250** forward of the arm latch member **272** and movable from the closed position of FIG. **18** where the lock plate **280** is rearward of the header latch member **270**, to the open position of FIG. **17** where the lock plate **280** is on one side of the header latch member **270**. The lock plate **280** is maintained in the closed position by a detent **282** between the arm **250** and the lock plate **280** comprising a bump and corresponding recess.

In the embodiment of FIGS. **19-22** the latch lock **266**, **466** comprises a spring catch maintained in a closed position by a bias force and configured to be pushed open as the arm latch member **272**, **472** is moved rearward into engagement with

the header latch member **270**, **470**. The spring catch is configured to close when the latch members **270**, **470** and **272**, **472** are fully engaged to prevent forward movement of the arm **250**, **450**.

In the embodiment of FIGS. **19-21** the spring catch comprises a pair of spring elements **284** mounted to the arm **250** above a rear portion of the arm **250**, one spring element **284** located on each side of an axis AA of the arm **250**. The spring elements **284** are configured to resist movement away from the axis AA. A lip **288** at a rear end of each spring element **284** behind the arm latch member **272** extends rearward and away from the axis AA. The spring elements **284** are configured such that they are pushed away from the axis AA by the header latch member **270** contacting the lips **288** as the arm latch member **272** is moved rearward into engagement with the header latch member **270**. The spring elements **284** then move toward the axis AA rearward of the header latch member **270** when the latch members **270**, **272** are fully engaged, thereby preventing forward movement of the arm **250**.

The embodiment of FIGS. **19-21** further comprises a pin **290** extending upward through a pin aperture in the rear portion of the arm **250**. The pin **290** has a head on a bottom end thereof below the arm **250** (not illustrated), and a release member **292** attached to the pin **290** above the arm **250** between the spring elements **284**. The release member **292** is oblong shaped such that rotation of the pin **290** causes the release member **292** to bear against the spring elements **284** to force the spring elements **284** apart, as illustrated in FIG. **21**, and allow the arm **250** to be moved forward to move the arm latch member **272** out of engagement with the header latch member **270** and thereby release the arm **250**. The release member **292** thus allows the operator to readily remove the arm **250** by rotating the head of the pin **290** with a wrench or the like on the easily accessible bottom of the arm **250**. When used in the embodiment of FIG. **10** where the latching mechanism is on the top of the header, the mechanism is also easily accessible. Alternatively, the lips **288** could be omitted, and the release member **292** could be operated to force the spring elements **284** apart to allow the arm latch member **272** to move into engagement with the header latch member **270**, then operated to allow the spring elements to move together to maintain engagement.

In the alternate embodiment of a crop lifter **410** of the invention shown in FIG. **22**, the latch lock **466** comprises a spring element **484** attached to a bottom rear portion of the arm **450** such that the spring element **484** resists downward movement. The spring element **484** defines a recessed portion **486** under the arm latch member **472**, and has a lip **488** extending rearward and downward from a rear end thereof. The spring element **484** is configured as illustrated such that the spring element **484** is pushed downward by the header latch member **470** as the arm latch member **472** is moved rearward into engagement with the header latch member **470**, and then moves upward when the latch members **470**, **472** are fully engaged to maintain a bottom portion of the guard bolt **460** in the recessed portion **486** and prevent forward movement of the arm **450**.

A bottom view of an alternate spring element **584** is illustrated in FIG. **23** for use in the place of the spring element **484** of FIG. **22**. In place of the recessed portion **486**, the spring element **584** provides an aperture **586** through the spring element **584**, as in the spring element **84** of FIGS. **10** and **13**. Thus the bottom portion of the guard bolt extends into or through the aperture **586**, and is maintained in position. A lip **588** extends rearward and downward from the rear end of the spring element **584**. If it was desired to omit the lip **588**, a tool could be provided to pry the spring element **584** away from



## 11

the arm to allow the latch members to engage, and then released to hold them together.

It is contemplated that a magnetic attachment could be used to lock an accessory to the header as well.

FIG. 25 illustrates an alternate crop lifter 610, very similar to the embodiment of FIG. 10 except that here the header latch member 670 is mounted on the bottom of the header, and an alternate latch lock is used. The aperture member 662 is located at the upturned front end of the arm 650, and the arm latch member 672 at the rear end of the arm 650 latches to the header latch member 670 as described above. The crop lifter 610 is illustrated using a spring catch of FIGS. 19-21, with spring elements 684 on top of the arm 650, however alternate latch locks could be used as well. The crop lifter 610 uses a mounting bracket 622 similar to that of FIGS. 2, 8 and 10 pivotally mounted to the front end of the arm 650 on aperture member 662 and incorporating a quick-attach mechanism 616 such as that illustrated in FIGS. 5-7 to attach the lifting finger 614.

Compared to the prior art mechanisms for quick attachment of a lifter that hook into the annular groove and are latched to the guard finger, the lifter of the present invention latches to the header, and only a conventional stationary aperture member is required to engage the guard finger, such that moving parts are removed from the cutting area of the header.

By positioning the header latch member and accessory latch member above the header as illustrated in FIG. 10 instead of below the header, the latch mechanism is not exposed to the soil passing under the header which can wear the mechanism. The mechanism on top of the header does not appear to interfere with crop flow over the cutting edge of the header.

The foregoing is considered as illustrative only of the principles of the invention. Further, since numerous changes and modifications will readily occur to those skilled in the art, it is not desired to limit the invention to the exact construction and operation shown and described, and accordingly, all such suitable changes or modifications in structure or operation which may be resorted to are intended to fall within the scope of the claimed invention.

I claim:

1. A crop lifter adapted for attachment to a cutting header having a knife and cooperating guards mounted along a lower front edge thereof, the crop lifter comprising:

a mounting bracket adapted for pivotal attachment to a guard finger of the header;

a lifting finger attached to the mounting bracket such that a leading end of the lifting finger is ahead of and below the

## 12

knife and such that pivoting the mounting bracket up and down with respect to the guard finger varies a distance between the leading end of the lifting finger and ground level;

a pivot lock mechanism operative, during field operations, to fix the mounting bracket at a selected one of a plurality of pivotal positions with respect to the guard finger to prevent upward and downward movement of the leading end of the lifting finger in response to forces exerted on the lifting finger during field operations.

2. The crop lifter of claim 1 wherein the guard finger defines a finger hole extending laterally therethrough, and wherein the mounting bracket is attachable to the guard finger by a bolt through the finger hole and through corresponding holes in the mounting bracket.

3. The crop lifter of claim 2 wherein the pivot lock mechanism is provided by a nut tightened on to the bolt to clamp the mounting bracket to the guard finger.

4. The crop lifter of claim 2 wherein the pivot lock mechanism is provided by a pin placed through a hole in the mounting bracket and a selected one of a plurality of stop holes in the guard finger.

5. The crop lifter of claim 1 comprising an aperture member adapted for attachment to the guard finger, and wherein the mounting bracket is pivotally attached to the aperture member.

6. The crop lifter of claim 5 wherein the aperture member defines a hole extending laterally therethrough, and wherein the mounting bracket is attachable to the guard finger by a bolt through the hole and through corresponding holes in the mounting bracket.

7. The crop lifter of claim 5 wherein the pivot lock mechanism is provided by a nut tightened on to the bolt to clamp the mounting bracket to the guard finger.

8. The crop lifter of claim 5 wherein the pivot lock mechanism is provided by a stop pin placed through a hole in one of the mounting bracket and the aperture member, and a selected one of a plurality of stop holes in the other of the mounting bracket and the aperture member.

9. The crop lifter of claim 1 wherein the lifting finger includes a carrying portion extending rearward from the leading end of the lifting finger to guide lifted crop to the knife for cutting.

10. The crop lifter of claim 1 wherein the lifting finger is structurally weak compared to the lifting member such that the lifting finger will readily move when striking an obstruction, thereby preventing damage to the lifter member.

\* \* \* \* \*