



US008551021B2

(12) **United States Patent**
Voeller et al.

(10) **Patent No.:** **US 8,551,021 B2**
(45) **Date of Patent:** **Oct. 8, 2013**

(54) **GUIDEWIRE WITH AN IMPROVED FLEXURAL RIGIDITY PROFILE**

(75) Inventors: **Virgil F. Voeller**, St. Louis Park, MN (US); **Clay Northrop**, Salt Lake City, UT (US); **Ted Layman**, Park City, UT (US)

(73) Assignee: **Boston Scientific Scimed, Inc.**, Maple Grove, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 371 days.

(21) Appl. No.: **13/077,579**

(22) Filed: **Mar. 31, 2011**

(65) **Prior Publication Data**

US 2011/0245808 A1 Oct. 6, 2011

Related U.S. Application Data

(60) Provisional application No. 61/319,720, filed on Mar. 31, 2010.

(51) **Int. Cl.**
A61B 5/00 (2006.01)

(52) **U.S. Cl.**
USPC **600/585**

(58) **Field of Classification Search**
USPC **600/585**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,553,227 A 9/1925 Anton et al.
1,866,888 A 7/1932 Hawley
2,275,827 A 3/1942 Plensler
2,413,805 A 1/1947 Vickers

2,441,166 A 5/1948 Raspert
2,561,890 A 7/1951 Stoddard
2,722,614 A 11/1955 Fryklund
2,857,536 A 10/1958 Light
2,864,017 A 12/1958 Waltscheff
2,871,793 A 2/1959 Michie et al.
3,249,776 A 5/1966 Anderson et al.
3,322,984 A 5/1967 Anderson
3,334,253 A 8/1967 Hill
3,363,470 A 1/1968 Yavne

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 215 173 3/1987
EP 0 377 453 7/1990

(Continued)

OTHER PUBLICATIONS

“H.A. Rothbart, Helical Compression Springs”, Mechanical Design and Systems Handbook, 1964, p. 33-13 (one sheet).


Primary Examiner — Max Hindenburg

(74) *Attorney, Agent, or Firm* — Seager, Tufte & Wickhem, LLC

(57) **ABSTRACT**

Medical devices and methods for making and using the same are disclosed. An example medical device may include a guidewire. The guidewire may include a core wire having a distal portion. A tubular member may be disposed over the distal portion. The tubular member may have a plurality of slots formed therein and may have a longitudinal axis. The tubular member may include a variably spaced slot section that has a flexural rigidity that varies from a first flexural rigidity to a second flexural rigidity. The transition from the first flexural rigidity to the second flexural rigidity may be a function of a fourth power equation. The first flexural rigidity may be in the range of about 1×10^{-6} to about 9×10^{-5} lbs-inches². The second flexural rigidity may be in the range of about 1×10^{-3} to about 5×10^{-3} lbs-inches².

20 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,452,227 A	6/1969	Welch	5,106,455 A	4/1992	Jacobsen et al.
3,452,742 A	7/1969	Muller	5,109,830 A	5/1992	Cho
3,463,953 A	8/1969	Maxwell	5,125,395 A	6/1992	Adair
3,512,019 A	5/1970	Durand	5,135,531 A	8/1992	Shiber
3,544,868 A	12/1970	Bates	5,144,959 A	9/1992	Gambale et al.
3,625,200 A	12/1971	Muller	5,147,317 A	9/1992	Shank et al.
3,686,990 A	8/1972	Margolien	5,181,668 A	1/1993	Tsuji et al.
3,841,308 A	10/1974	Tate	5,205,830 A	4/1993	Dassa et al.
3,890,977 A	6/1975	Wilson	5,211,183 A	5/1993	Wilson
3,906,938 A	9/1975	Fleischhacker	5,228,441 A	7/1993	Lundquist
4,000,672 A	1/1977	Sitterer et al.	5,228,453 A	7/1993	Sepetka
4,003,369 A	1/1977	Heilman et al.	5,238,004 A	8/1993	Sahatjian et al.
4,020,829 A	5/1977	Willson et al.	5,242,759 A	9/1993	Hall
4,142,119 A	2/1979	Madey	5,243,996 A	9/1993	Hall
4,215,703 A	8/1980	Willson	5,250,069 A	10/1993	Nobuyoshi et al.
4,330,725 A	5/1982	Hintz	5,254,106 A	10/1993	Feaster
4,425,919 A	1/1984	Alston, Jr. et al.	5,254,107 A	10/1993	Soltesz
4,476,754 A	10/1984	Ducret	5,256,144 A	10/1993	Kraus et al.
4,482,828 A	11/1984	Vergues et al.	5,257,974 A	11/1993	Cox
4,538,622 A	9/1985	Samson et al.	5,259,393 A	11/1993	Corso, Jr. et al.
4,545,390 A	10/1985	Leary	5,267,979 A	12/1993	Appling et al.
4,563,181 A	1/1986	Wijayarathna et al.	5,267,982 A	12/1993	Sylvanowicz
4,574,670 A	3/1986	Johnson	5,279,562 A	1/1994	Sirhan et al.
4,580,551 A	4/1986	Siegmund et al.	5,284,128 A	2/1994	Hart
4,583,404 A	4/1986	Bernard et al.	5,300,032 A	4/1994	Hibbs et al.
4,635,270 A	1/1987	Gürs	5,304,131 A	4/1994	Paskar
4,665,906 A	5/1987	Jervis	5,306,252 A	4/1994	Yutori et al.
4,676,249 A	6/1987	Arenas et al.	5,308,435 A	5/1994	Ruggles et al.
4,721,117 A	1/1988	Mar et al.	5,315,906 A	5/1994	Ferenczi et al.
4,737,153 A	4/1988	Shimamura et al.	5,315,996 A	5/1994	Lundquist
4,763,647 A	8/1988	Gambale	5,318,529 A	6/1994	Kontos
4,774,949 A	10/1988	Fogarty	5,322,064 A	6/1994	Lundquist
4,781,092 A	11/1988	Gaiser	5,329,923 A	7/1994	Lundquist
4,781,186 A	11/1988	Simpson et al.	5,333,620 A	8/1994	Moutafis et al.
4,786,220 A	11/1988	Fildes et al.	5,334,145 A	8/1994	Lundquist et al.
4,790,331 A	12/1988	Okada et al.	5,336,205 A	8/1994	Zenzen et al.
4,800,890 A	1/1989	Cramer	5,341,818 A	8/1994	Abrams et al.
4,811,743 A	3/1989	Stevens	5,345,937 A	9/1994	Middleman et al.
4,827,941 A	5/1989	Taylor et al.	5,345,945 A	9/1994	Hodgson et al.
4,831,858 A	5/1989	Yoshizawa et al.	5,354,623 A	10/1994	Hall
4,832,047 A	5/1989	Sepetka et al.	5,358,493 A	10/1994	Schweich et al.
4,846,186 A	7/1989	Box et al.	5,358,796 A	10/1994	Nakamura et al.
4,846,193 A	7/1989	Tremulis et al.	5,365,942 A	11/1994	Shank
4,867,173 A	9/1989	Leoni	5,365,943 A	11/1994	Jansen
4,875,489 A	10/1989	Messner et al.	5,368,049 A	11/1994	Raman et al.
4,884,579 A	12/1989	Engelson	5,368,564 A	11/1994	Savage
4,911,148 A	3/1990	Sosnowski et al.	5,368,661 A	11/1994	Nakamura et al.
4,917,102 A	4/1990	Miller et al.	5,376,084 A	12/1994	Bacich et al.
4,922,164 A	5/1990	Jacobsen et al.	5,381,782 A	1/1995	DeLaRama et al.
4,922,777 A	5/1990	Kawabata	5,406,960 A	4/1995	Corso, Jr.
4,932,959 A	6/1990	Horzewski et al.	5,409,015 A	4/1995	Palermo
4,934,380 A	6/1990	Toledo	5,411,476 A	5/1995	Abrams et al.
4,953,553 A	9/1990	Tremulis	5,425,723 A	6/1995	Wang
4,954,022 A	9/1990	Underwood et al.	5,437,288 A	8/1995	Schwartz et al.
4,955,384 A	9/1990	Taylor et al.	5,438,993 A	8/1995	Lynch et al.
4,955,862 A	9/1990	Sepetka	5,439,000 A	8/1995	Gunderson et al.
4,960,410 A	10/1990	Pinchuk	5,441,483 A	8/1995	Avitall
4,964,409 A	10/1990	Tremulis	5,441,489 A	8/1995	Utsumi et al.
4,966,163 A	10/1990	Kraus et al.	5,447,812 A	9/1995	Fukuda et al.
4,968,306 A	11/1990	Huss et al.	5,454,787 A	10/1995	Lundquist
4,973,321 A	11/1990	Michelson	5,460,187 A	10/1995	Daigle et al.
4,985,022 A	1/1991	Fearnot et al.	5,470,330 A	11/1995	Goldenberg et al.
4,989,608 A	2/1991	Ratner	5,476,701 A	12/1995	Berger
4,990,143 A	2/1991	Sheridan	5,477,856 A	12/1995	Lundquist
4,994,069 A	2/1991	Ritchart et al.	5,496,294 A	3/1996	Hergenrother et al.
4,998,923 A	3/1991	Samson et al.	5,497,785 A	3/1996	Viera
5,007,434 A	4/1991	Doyle et al.	5,507,301 A	4/1996	Wasicek et al.
5,009,137 A	4/1991	Dannatt	5,507,729 A	4/1996	Lindenberg et al.
5,040,543 A	8/1991	Badera et al.	5,507,751 A	4/1996	Goode et al.
5,050,606 A	9/1991	Tremulis	5,507,766 A	4/1996	Kugo et al.
5,052,404 A	10/1991	Hodgson	5,514,128 A	5/1996	Hillsman et al.
5,059,177 A	10/1991	Towne et al.	5,520,194 A	5/1996	Miyata et al.
5,063,935 A	11/1991	Gamble	5,520,645 A	5/1996	Imran et al.
5,065,769 A	11/1991	De Toledo	5,531,719 A	7/1996	Takahashi
5,095,915 A	3/1992	Engelson	5,533,985 A	7/1996	Wang
			5,546,958 A	8/1996	Thorud et al.
			5,551,444 A	9/1996	Finlayson
			5,554,139 A	9/1996	Okajima
			5,562,619 A	10/1996	Mirarchi et al.

US 8,551,021 B2

5,569,197 A	10/1996	Helmus et al.	6,042,553 A	3/2000	Solar et al.
5,569,200 A	10/1996	Umeno et al.	6,045,547 A	4/2000	Ren et al.
5,569,218 A	10/1996	Berg	6,048,339 A	4/2000	Zirps et al.
5,571,073 A	11/1996	Castillo	6,056,702 A	5/2000	Lorenzo
5,573,520 A	11/1996	Schwartz et al.	6,063,101 A	5/2000	Jacobsen et al.
5,584,821 A	12/1996	Hobbs et al.	6,063,200 A	5/2000	Jacobsen et al.
5,599,326 A	2/1997	Carter	6,066,361 A	5/2000	Jacobsen et al.
5,599,492 A	2/1997	Engelson	6,071,305 A	6/2000	Brown et al.
5,601,539 A	2/1997	Corso, Jr.	6,106,485 A	8/2000	McMahon
5,605,162 A	2/1997	Mirzaee et al.	6,106,488 A	8/2000	Fleming et al.
5,605,543 A	2/1997	Swanson	6,139,510 A	10/2000	Palermo
5,622,184 A	4/1997	Ashby et al.	6,165,292 A	12/2000	Abrams et al.
5,630,806 A	5/1997	Inagaki et al.	6,171,296 B1	1/2001	Chow
5,637,089 A	6/1997	Abrams et al.	6,183,410 B1	2/2001	Jacobsen et al.
5,641,818 A	6/1997	Sweet	6,193,686 B1	2/2001	Estrada et al.
5,656,011 A	8/1997	Uihlein et al.	6,197,014 B1	3/2001	Samson et al.
5,658,264 A	8/1997	Samson et al.	6,203,485 B1	3/2001	Urick
5,664,580 A	9/1997	Erickson et al.	RE37,148 E	4/2001	Shank
5,666,968 A	9/1997	Imran et al.	6,214,042 B1	4/2001	Jacobsen et al.
5,666,969 A	9/1997	Urick et al.	6,228,073 B1	5/2001	Noone et al.
5,669,926 A	9/1997	Aust et al.	6,248,082 B1	6/2001	Jafari
5,676,659 A	10/1997	McGurk	6,251,092 B1	6/2001	Qin et al.
5,676,697 A	10/1997	McDonald	6,254,549 B1	7/2001	Ramzipoor
5,682,894 A	11/1997	Orr et al.	6,260,458 B1	7/2001	Jacobsen et al.
5,690,120 A	11/1997	Jacobsen et al.	6,273,404 B1	8/2001	Holman et al.
5,720,300 A	2/1998	Fagan et al.	6,273,876 B1	8/2001	Klima et al.
5,722,609 A	3/1998	Murakami	6,273,879 B1	8/2001	Keith et al.
5,728,063 A	3/1998	Preissman et al.	6,290,656 B1	9/2001	Boyle et al.
5,741,429 A	4/1998	Donadio, III et al.	6,296,616 B1	10/2001	McMahon
5,746,701 A	5/1998	Noone	6,296,631 B2	10/2001	Chow
5,769,830 A	6/1998	Parker	6,302,870 B1	10/2001	Jacobsen et al.
5,772,609 A	6/1998	Nguyen et al.	6,325,790 B1	12/2001	Trotta
5,782,809 A	7/1998	Umeno et al.	6,338,725 B1	1/2002	Hermann et al.
5,788,653 A	8/1998	Lorenzo	6,346,091 B1	2/2002	Jacobsen et al.
5,788,654 A	8/1998	Schwager	6,352,515 B1	3/2002	Anderson et al.
5,788,707 A	8/1998	Del Toro et al.	6,355,005 B1	3/2002	Powell et al.
5,792,124 A	8/1998	Horrigan et al.	6,355,027 B1	3/2002	Le et al.
5,797,856 A	8/1998	Frisbie et al.	6,368,315 B1	4/2002	Gillis et al.
5,800,454 A	9/1998	Jacobsen et al.	6,368,316 B1	4/2002	Jansen et al.
5,807,075 A	9/1998	Jacobsen et al.	6,375,628 B1	4/2002	Zadno-Azizi et al.
5,807,249 A	9/1998	Qin et al.	6,375,774 B1	4/2002	Lunn et al.
5,810,885 A	9/1998	Zinger	6,379,369 B1	4/2002	Abrams et al.
5,813,996 A	9/1998	St. Germain et al.	6,383,146 B1	5/2002	Klint
5,827,225 A	10/1998	Ma Schwab	6,390,993 B1	5/2002	Cornish et al.
5,827,242 A	10/1998	Follmer et al.	6,398,758 B1	6/2002	Jacobsen et al.
5,833,632 A	11/1998	Jacobsen et al.	6,428,489 B1	8/2002	Jacobsen et al.
5,836,926 A	11/1998	Peterson et al.	6,428,512 B1	8/2002	Anderson et al.
5,843,050 A	12/1998	Jones et al.	6,431,039 B1	8/2002	Jacobsen et al.
5,843,244 A	12/1998	Pelton et al.	6,440,088 B1	8/2002	Jacobsen
5,851,203 A	12/1998	van Muiden	6,478,778 B1	11/2002	Jacobsen et al.
5,895,378 A	4/1999	Nita	6,488,637 B1	12/2002	Eder et al.
5,897,537 A	4/1999	Berg et al.	6,491,648 B1	12/2002	Cornish et al.
5,902,254 A	5/1999	Magram	6,491,671 B1	12/2002	Larson, III et al.
5,902,290 A	5/1999	Peacock, III et al.	6,503,244 B2	1/2003	Hayman
5,902,499 A	5/1999	Richerzhagen	6,508,803 B1	1/2003	Horikawa et al.
5,904,657 A	5/1999	Unsworth et al.	6,524,301 B1	2/2003	Wilson et al.
5,906,618 A	5/1999	Larson, III	6,530,934 B1	3/2003	Jacobsen et al.
5,911,715 A	6/1999	Berg et al.	6,547,779 B2	4/2003	Levine et al.
5,911,717 A	6/1999	Jacobsen et al.	6,553,880 B2	4/2003	Jacobsen et al.
5,916,177 A	6/1999	Schwager	6,556,873 B1	4/2003	Smits
5,916,178 A	6/1999	Noone	6,579,246 B2	6/2003	Jacobsen et al.
5,916,194 A	6/1999	Jacobsen et al.	6,602,207 B1	8/2003	Mam et al.
5,931,830 A	8/1999	Jacobsen et al.	6,602,280 B2	8/2003	Chobotov
5,935,108 A	8/1999	Katoh et al.	6,610,046 B1	8/2003	Usami et al.
5,947,940 A	9/1999	Beisel	6,623,448 B2	9/2003	Slater
5,951,539 A	9/1999	Nita et al.	6,636,758 B2	10/2003	Sanchez et al.
5,955,640 A	9/1999	Paludetto et al.	6,638,266 B2	10/2003	Wilson et al.
5,971,975 A	10/1999	Mills et al.	6,652,508 B2	11/2003	Griffin et al.
5,980,471 A	11/1999	Jafari	6,673,025 B1	1/2004	Richardson et al.
5,997,487 A	12/1999	Kolehmainen et al.	6,682,493 B2	1/2004	Mirigian
6,001,068 A	12/1999	Uchino et al.	6,689,120 B1	2/2004	Gerdts
6,004,279 A	12/1999	Crowley et al.	6,702,762 B2	3/2004	Jafari et al.
6,007,478 A	12/1999	Siess et al.	6,712,826 B2	3/2004	Lui
6,014,919 A	1/2000	Jacobsen et al.	6,730,095 B2	5/2004	Olson, Jr. et al.
6,017,319 A	1/2000	Jacobsen et al.	6,749,560 B1	6/2004	Konstorum et al.
6,022,343 A	2/2000	Johnson et al.	6,766,720 B1	7/2004	Jacobsen et al.
6,022,369 A	2/2000	Jacobsen et al.	6,777,644 B2	8/2004	Peacock, III et al.
6,024,730 A	2/2000	Pagan	6,811,544 B2	11/2004	Schaer
6,027,461 A	2/2000	Walker et al.	6,837,898 B2	1/2005	Boyle et al.

US 8,551,021 B2

Page 4

6,866,642	B2	3/2005	Kellerman et al.
6,887,235	B2	5/2005	O'Connor et al.
6,918,882	B2	7/2005	Skujins et al.
6,997,937	B2	2/2006	Jacobsen et al.
7,001,369	B2	2/2006	Griffin et al.
7,071,197	B2	7/2006	Leonardi et al.
7,074,197	B2	7/2006	Reynolds et al.
7,153,277	B2	12/2006	Skujins et al.
7,169,118	B2	1/2007	Reynolds et al.
7,182,735	B2	2/2007	Shireman et al.
7,618,379	B2	11/2009	Reynolds et al.
7,850,623	B2	12/2010	Griffin et al.
7,878,984	B2	2/2011	Jacobsen et al.
7,905,913	B2	3/2011	Chew et al.
7,914,466	B2	3/2011	Davis et al.
2002/0019599	A1	2/2002	Rooney et al.
2003/0009208	A1	1/2003	Snyder et al.
2003/0060732	A1	3/2003	Jacobsen et al.
2003/0069522	A1	4/2003	Jacobsen et al.
2003/0216668	A1	11/2003	Howland et al.
2004/0116831	A1	6/2004	Vrba
2004/0142643	A1	7/2004	Miller et al.
2004/0167437	A1	8/2004	Sharrow et al.
2004/0167441	A1	8/2004	Reynolds et al.
2004/0181176	A1	9/2004	Jafari et al.
2005/0115624	A1	6/2005	Walak
2006/0121218	A1	6/2006	Obara et al.
2006/0264904	A1	11/2006	Kerby et al.
2007/0100374	A1	5/2007	Vrba
2008/0021347	A1	1/2008	Jacobsen et al.
2008/0021348	A1	1/2008	Jacobsen et al.
2008/0021400	A1	1/2008	Jacobsen et al.
2008/0021401	A1	1/2008	Jacobsen et al.
2008/0021402	A1	1/2008	Jacobsen et al.
2008/0021403	A1	1/2008	Jacobsen et al.
2008/0021404	A1	1/2008	Jacobsen et al.
2008/0021405	A1	1/2008	Jacobsen et al.
2008/0021406	A1	1/2008	Jacobsen et al.
2008/0021407	A1	1/2008	Jacobsen et al.
2008/0021408	A1	1/2008	Jacobsen et al.
2008/0064989	A1	3/2008	Chen et al.
2008/0077119	A1	3/2008	Snyder et al.
2009/0043283	A1	2/2009	Turnlund et al.
2009/0043372	A1	2/2009	Northrop et al.
2009/0118675	A1	5/2009	Czyscon et al.

2009/0177185	A1	7/2009	Northrop
2009/0254000	A1	10/2009	Layman et al.
2010/0063479	A1	3/2010	Merdan et al.

FOREIGN PATENT DOCUMENTS

EP	0 778 039	6/1997
EP	0 937 481	8/1999
EP	0 790 066	4/2000
EP	0 608 853	4/2003
GB	2257269	1/1993
JP	58-8522	1/1983
JP	62-299277	12/1987
JP	1-135363	5/1989
JP	1-158936	6/1989
JP	2-107268	4/1990
JP	3-122850	12/1991
JP	4-061840	2/1992
JP	5-506806	10/1993
JP	5-309519	11/1993
JP	6-31749	4/1994
JP	6-63224	9/1994
JP	6-312313	11/1994
JP	7-124164	5/1995
JP	7-124263	5/1995
JP	7-136280	5/1995
JP	7148264	6/1995
JP	7037199	7/1995
JP	7185009	7/1995
JP	7275366	10/1995
JP	751067	11/1995
JP	8509141	10/1996
JP	8-317988	12/1996
JP	9-000164	4/1997
JP	9-276413	10/1997
JP	10-118193	5/1998
JP	2000-197704 A	7/2000
WO	WO 90/02520	3/1990
WO	WO 95/32834	12/1995
WO	WO 96/38193	12/1996
WO	WO 97/44086	11/1997
WO	WO 99/11313	3/1999
WO	WO 02/13682	2/2002
WO	WO 2004/047899	6/2004




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 8




Figure 7




Figure 9

1

GUIDEWIRE WITH AN IMPROVED FLEXURAL RIGIDITY PROFILE

CROSS-REFERENCE TO RELATED PUBLICATIONS

This application claims priority under 35 U.S.C. §119 to U.S. Provisional Application Ser. No. 61/319,720 entitled "GUIDEWIRE WITH AN IMPROVED FLEXURAL RIGIDITY PROFILE" filed Mar. 31, 2010, the entirety of which is incorporated herein by reference.

FIELD OF THE INVENTION

The present invention pertains to medical devices, and methods for manufacturing medical devices. More particularly, the present invention pertains to elongated medical devices including a slotted tubular member, components thereof, and methods for manufacturing and using such devices.

BACKGROUND

A wide variety of intracorporeal medical devices have been developed for medical use, for example, intravascular use. Some of these devices include guidewires, catheters, and the like. These devices are manufactured by any one of a variety of different manufacturing methods and may be used according to any one of a variety of methods. Of the known medical devices and methods, each has certain advantages and disadvantages. There is an ongoing need to provide alternative medical devices as well as alternative methods for manufacturing and using medical devices.

BRIEF SUMMARY

Embodiments of the present disclosure provide design, material, manufacturing method, and use alternatives for medical devices and tubular members for use in medical devices. An example medical device may include a guidewire. The guidewire may include a core wire having a distal portion. A tubular member may be disposed over the distal portion. The tubular member may have a plurality of slots formed therein and may have a longitudinal axis. The tubular member may include a variably spaced slot section that has a flexural rigidity that varies from a first flexural rigidity to a second flexural rigidity. The transition from the first flexural rigidity to the second flexural rigidity may be a function of a fourth power equation. The first flexural rigidity may be in the range of about 1×10^{-6} to about 9×10^{-5} lbs-inches². The second flexural rigidity may be in the range of about 1×10^{-3} to about 5×10^{-3} lbs-inches².

Another example guidewire may include a linear-elastic nickel-titanium core wire having a distal portion. A super-elastic nickel-titanium tubular member may be disposed over the distal portion. The tubular member may have a plurality of slots formed therein and may have a longitudinal axis. The tubular member may include a variably spaced slot section that has a flexural rigidity that varies from a first flexural rigidity to a second flexural rigidity. The transition from the first flexural rigidity to the second flexural rigidity may be a function of a fourth power equation. The first flexural rigidity may be in the range of about 1×10^{-6} to about 9×10^{-5} lbs-inches². The second flexural rigidity may be in the range of about 1×10^{-3} to about 5×10^{-3} lbs-inches².

An example method for manufacturing a guidewire may include providing a tubular member having a longitudinal

2

axis, forming a first slot in the tubular member at a first position along the longitudinal axis, forming a second slot in the tubular member at a second position along the longitudinal axis, and forming a plurality of additional slots in the tubular member at a plurality of positions along the longitudinal axis. The first slot, the second slot, and the plurality of additional slots may be variably spaced along the longitudinal axis of the tubular member so as to define a variably spaced slot section that has a flexural rigidity that varies from a first flexural rigidity to a second flexural rigidity. The transition from the first flexural rigidity to the second flexural rigidity may be a function of a fourth power equation. The first flexural rigidity may be in the range of about 1×10^{-6} to about 9×10^{-5} lbs-inches². The second flexural rigidity may be in the range of about 1×10^{-3} to about 5×10^{-3} lbs-inches².

The above summary of some embodiments is not intended to describe each disclosed embodiment or every implementation of the present disclosure. The Figures, and Detailed Description, which follow, more particularly exemplify these embodiments.

BRIEF DESCRIPTION OF THE DRAWINGS

The devices and methods of the present disclosure may be more completely understood in consideration of the following detailed description of various embodiments in connection with the accompanying drawings, in which:

FIG. 1 is a plan view of an example medical device disposed in a blood vessel;

FIG. 2 is a partial cross-sectional side view of an example medical device;

FIG. 3 is a partial cross-sectional side view of another example medical device;

FIG. 4 is graph showing the changes in flexural rigidity and changes in diameter of a core wire relative to the distance from the distal end of the core wire;

FIG. 5 is graph showing the changes in flexural rigidity in an example core wire, an example tubular member, and a guidewire relative to the distance from the distal end of the example guidewire;

FIG. 6 is a side view of example tubular member;

FIG. 7 is a cross-sectional view of a portion of an example tubular member;

FIG. 8 is another cross-sectional view of a portion of an example tubular member; and

FIG. 9 is another cross-sectional view of a portion of an example tubular member.

While the embodiments described herein are amenable to various modifications and alternative forms, specifics thereof have been shown by way of example in the drawings and will be described in detail. It should be understood, however, that the intention is not to limit the devices and methods to the particular embodiments described. On the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention.

DETAILED DESCRIPTION

For the following defined terms, these definitions shall be applied, unless a different definition is given in the claims or elsewhere in this specification.

All numeric values are herein assumed to be modified by the term "about," whether or not explicitly indicated. The term "about" generally refers to a range of numbers that one of skill in the art would consider equivalent to the recited value (i.e., having the same function or result). In many

instances, the terms “about” may include numbers that are rounded to the nearest significant figure.

The recitation of numerical ranges by endpoints includes all numbers within that range (e.g. 1 to 5 includes 1, 1.5, 2, 2.75, 3, 3.80, 4, and 5).

As used in this specification and the appended claims, the singular forms “a”, “an”, and “the” include plural referents unless the content clearly dictates otherwise. As used in this specification and the appended claims, the term “or” is generally employed in its sense including “and/or” unless the content clearly dictates otherwise.

The following detailed description should be read with reference to the drawings in which similar elements in different drawings are numbered the same. The drawings, which are not necessarily to scale, depict illustrative embodiments and are not intended to limit the scope of the invention.

FIG. 1 is a plan view of an example medical device 10, for example a guidewire, disposed in a blood vessel 12. Guidewire 10 may include a distal section 14 that may be generally configured for probing within the anatomy of a patient. Guidewire 10 may be used for intravascular procedures. For example, guidewire 10 may be used in conjunction with another medical device 16, which may take the form of a catheter, to treat and/or diagnose a medical condition. Of course, numerous other uses are known amongst clinicians for guidewires, catheters, and other similarly configured medical devices.

FIG. 2 is a partial cross-sectional view of guidewire 10. It can be seen that guidewire 10 may include a core member or core wire 18 and a tubular member 20 disposed over at least a portion of core wire 18. Tubular member 20 may have a plurality of slots 30 formed therein. Core wire 18 may include a proximal section 22 and a distal section 24. A connector (not shown) may be disposed between and attach proximal section 22 to distal section 24. Alternatively, core wire 18 may be a unitary member without a connector. A shaping member 26 may be coupled to core wire 18 (for example distal section 24 of core wire 18), tubular member 20, or both. Shaping member 26 may be made from a relatively inelastic material so that a clinician can bend or shape the distal end of guidewire 10 into a shape that may facilitate navigation of guidewire 10 through the anatomy. Some examples of suitable materials for core wire 18, tubular member 20, shaping member 26, etc. can be found herein. A coil 27, for example a radiopaque coil, may be disposed over core wire 18 and shaping member 26. A solder bond 29 may join core wire 18, shaping member 26, and coil 27. Other joining structures and/or methods are contemplated. A tip member 28 may also be coupled to core wire 18, tubular member 20, or both that may define an atraumatic distal tip of guidewire 10. In general, tip member 28 may include solder. However, other versions of tip member 28 are contemplated including tip members 28 that comprise or form a polymeric tip.

Core wire 18, for example distal section 24 of core wire 18, may include one or more tapers or tapered sections and a flattened or stamped distal end 25. Core wire 18 may also include one or more constant outer diameter sections. The tapers or tapered sections may be formed by a number of different techniques, for example, by centerless grinding methods, stamping methods, and the like. The centerless grinding technique may utilize an indexing system employing sensors (e.g., optical/reflective, magnetic) to avoid excessive grinding of the core wire 18 section. In addition, the centerless grinding technique may utilize a CBN or diamond abrasive grinding wheel that is well shaped and dressed to avoid grabbing core wire 18 during the grinding process. In some embodiments, core wire 18 is centerless ground using a

Royal Master HI-AC centerless grinder to define one or more tapered sections. In some embodiments, core wire 18 is ground using a CNC profile grinder to define one or more tapered sections.

Although medical device 10 is depicted in FIG. 1 as a guidewire, it is not intended to be limited to just being a guidewire. Indeed, medical device 10 may take the form of other suitable guiding, diagnosing, or treating device (including catheters, endoscopic instruments, laparoscopic instruments, etc., and the like) and it may be suitable for use at other locations and/or body lumens within a patient. For example, FIG. 3 illustrates another example device 110 in the form of a catheter. Catheter 110 may include a generally elongate shaft 131 having a proximal portion 132 and a distal portion 134. A proximal manifold 136 may be disposed at proximal portion 132. Manifold 136 may include a hub 138 and strain relief 140. A tip member 142 may be disposed at distal portion 134. Tip member 142 may include a radiopaque marker member 144. One or more additional marker members 144 may be disposed along other portions of catheter 110, for example along distal portion 134 of shaft 131. Shaft 131 may include a tubular member 120 that may be similar in form and function to other tubular members disclosed herein including tubular member 20 illustrated, for example, in FIG. 2. Tubular member 120 may have a plurality of slots 130 formed therein. A liner 146 may be disposed within tubular member 120. Liner 146 may be similar to an analogous structure disclosed in U.S. Pat. No. 7,001,369 and U.S. Patent Application Publication No. US 2006/0264904, the entire disclosures of which are herein incorporated by reference. Discussion herein pertaining to tubular member 20 and/or guidewire 10 (e.g., as illustrated in FIG. 2) may also be applicable to tubular member 120 and catheter 110, to the extent applicable.

Because of their intended use in the vasculature, some medical devices are designed to have particular physical characteristics such as flexibility (e.g., for the purposes of this disclosure, flexibility may be also be termed or expressed as bending stiffness or flexural rigidity). For example, medical devices may be designed to be flexible enough in order to bend in a manner sufficient to traverse the tortuous anatomy. At the far distal end of the medical device, it may be desirable to tailor the flexibility of the medical device so that the device can effectively reach its target within the vasculature. For example, in order to reach coronary vessels and/or vessels near the heart, which may have bends, or “take-offs” with angles of 90° or more, a guidewire may be designed to be quite flexible at the distal end. However, if the flexibility is too great, the guidewire may not efficiently turn at these take-offs and, instead, may have a tendency to buckle upon itself. Thus, tailoring the flexibility at the distal end of a guidewire (e.g., within about the first four to six inches or so of the guidewire) so that it is able to efficiently advance through coronary artery take-offs while minimizing the likelihood that the guidewire will buckle back upon itself may be desirable.

When designing guidewires, such as polymer tip and/or spring tip guidewires, the core wire may be the major contributor to the overall flexural rigidity of the guidewire. Because the flexural rigidity of core wire may be a function of the diameter of the core, it may be desirable to taper or otherwise size the core wire so that it provides a desired flexural rigidity to the guidewire, for example at the distal end. For example, FIG. 4 is a graph illustrating the flexural rigidity of a core wire and the diameter of the core wire plotted versus the distance from the distal end of the core wire. The scale on the left side of the graph is the flexural rigidity in lbs-inch², defined as EI where E is Young’s modulus of the core wire material (in this example, a stainless steel

5

core wire), I is the area moment of inertia (because the core wire has a round cross-section, the area moment of inertia is $\pi r^4/4$ where r is the radius of the core wire). The scale on the right side of the graph is the diameter of the core wire in inches. The scale at the bottom of the graph is the distance from the distal end of the core wire in inches.

What can be seen in this graph is that a linear taper or transition in diameter of the core wire results in a non-linear change in flexural rigidity. Indeed, a linear taper in the core wire may provide a change in flexural rigidity that follows a non-linear transition that may be defined by a fourth order equation. Stated another way, the change in the flexural rigidity may be a function of a fourth order polynomial. Such a change in flexural rigidity may be desirable because it may provide the core wire with sufficient flexibility to traverse the vasculature and navigate coronary artery take-offs, yet be sufficiently resistant to buckling.

While coronary guidewires having such core wires may have desirable flexibility characteristics, they may not fully transmit torque from the proximal end to the distal end of the guidewire. This may limit a clinician's ability to accurately navigate the guidewire to its intended destination. One way to enhance the torquability in a guidewire may be to include a tubular member about a portion of a core wire such as tubular member **20**, illustrated in FIG. 2, which may efficiently transmit torque along its length. Because tubular member **20** may include slots **30**, it also may be highly flexible. Thus, the combination of a highly flexible core wire (e.g., core wire **18**) and a highly flexible tubular member (e.g., tubular member **20**) may result in a guidewire with desirable flexibility and torque-transmitting characteristics (e.g., guidewire **10**).

Unlike in polymer tip and spring tip guidewires, where the polymeric material and springs coils in the tips may only contribute a negligible amount to the overall flexural rigidity of the guidewire, the structure of tubular member **20** may be such that it does contribute to the overall flexural rigidity of guidewire **10**. Therefore, the flexural rigidity of core wire **18** alone may not determine the overall flexural rigidity of guidewire **10**. Because of this, it may be desirable to tailor the flexural rigidity of tubular member **20** so that tubular member **20** can help contribute to the flexural rigidity of guidewire **10** in a manner that allows guidewire **10** to still efficiently traverse the vasculature while having a tendency to resist buckling.

Tubular member **20** may be fabricated in such a manner that it provides guidewire **10** with desirable flexural rigidity characteristics. For example, tubular member **20** may be designed so that its flexural rigidity changes in a non-linear manner. This may include a change in flexural rigidity that follows a third order to a fifth order equation or, stated another way, is a function of a third order to a fifth order polynomial (e.g., is based on a mathematical equation that is a third order to a fifth order polynomial). For example, the flexural rigidity of the tubular member **20** may follow or otherwise be a function of a fourth order polynomial. This fourth order transition in flexural rigidity may take place along the entire length of tubular member **20** or it may occur in one or more sections of tubular member **20**. For example, the flexural rigidity of tubular member **20** may follow a fourth order transition across the entire length of tubular member, across about the first five inches or so of tubular member **20**, or in a section of tubular member **20** located along a portion of the first four inches or so of tubular member **20**.

As indicated above, in some examples, the flexural rigidity of tubular member **20** may transition according to a fourth power equation or polynomial. Fourth power equations are a subset of fourth order equations or polynomials where the

6

lower power coefficients are zero. Thus, a fourth power equation for flexural rigidity may be represented by the following equation:

$$FR(x)=A+Bx^4$$

where:

FR is the flexural rigidity,

A is the flexural rigidity at the start of the transition,

B is (the flexural rigidity at the end of the transition—the flexural rigidity at the start of the transition)/(length of the transition)⁴, and

x is the position along the transition and is defined as 0 at the start of the transition.

Thus, the flexural rigidity in tubular member **20** may transition across a transition length from a starting flexural rigidity to an ending flexural rigidity, and this transition may be a function of a fourth power equation.

FIG. 5 is a graph depicting flexural rigidity (flexural rigidity, FR, in lbs-inch²) for core wire **18**, tubular member **20**, and guidewire **10**. The scale at the bottom of the graph is the distance from the distal end of guidewire **10** in inches. Here it can be seen that flexural rigidity of core wire **18** changes in a non-linear manner. For example, the flexural rigidity of core wire **18** may be a function of a fourth order polynomial. Tubular member **20** also has a non-linear change in flexural rigidity and this change may be a function of a fourth order polynomial (e.g., a fourth order polynomial). The overall flexural rigidity of guidewire **10** may be essentially the sum of the flexural rigidity of core wire **18** and tubular member **20** and it changes in a non-linear manner (e.g., may be a function of a fourth order polynomial). Such flexibility characteristics may be desirable and may provide guidewire **10** with flexibility characteristics that allow guidewire **10** to traverse the vasculature and navigate coronary artery take-offs, yet be sufficiently resistant to buckling.

The structure of tubular member **20** may vary in a number of different ways so as to provide the desired flexural rigidity (e.g., the desired flexural rigidity along at least a portion of tubular member **20** that varies as a function of a fourth power polynomial). FIG. 6 illustrates tubular member **20** showing slots **30** formed therein and arranged in a pattern that may provide the desired flexural rigidity. For example, tubular member **20** may have a distal uncut or non-slotted section **48** disposed at the distal end of tubular member **20**. Section **48** may lack slots **30** and may have a length in the range of about 0.01 to 0.1 inches, or about 0.02 to 0.03 inches, or about 0.024 inches.

Next to section **48** may be a distal slotted section **50** where slots **30** have an essentially constant spacing. Section **48** may have a length in the range of about 0.1 to 5 inches, or about 0.1 to 1 inches, or about 0.4 to 0.6 inches, or about 0.49 inches. The flexural rigidity of section **50** may also be essentially constant. For example, the flexural rigidity of section **50** may be in the range of about 1×10^{-6} to 9×10^{-5} lbs-inches², or about 5×10^{-6} to 3×10^{-5} lbs-inches², or about 6×10^{-6} to 2.1×10^{-5} lbs-inches². In one example, the flexural rigidity of section **50** may be about 6×10^{-6} lbs-inches². In another example, the flexural rigidity of section may be about 2.1×10^{-5} lbs-inches².

Tubular member **20** may also include a mid-distal uncut or non-slotted section **52**. Section **52** may lack slots **30** and may have a length in the range of about 0.001 to 0.1 inches, or about 0.01 to 0.02 inches, or about 0.012 inches. Tubular member **20** may also include a transition section **54** that is disposed adjacent to section **52**. The spacing of slots **30** in transition section **54** may vary so as to provide section **50** with a flexural rigidity that is a function of a third order to a fifth

order equation (e.g., may be a function of a third order to a fifth order polynomial). For example, transition section **54** may have a transition in flexural rigidity that varies as a function of a fourth power polynomial. Section **54** may have a length in the range of about 1 to 5 inches, or about 1 to 4 inches, or about 1 to 3 inches, or about 2.49 inches.

Tubular member **20** may also include a proximal slotted section **56** where slots **30** have an essentially constant spacing. Section **56** may have a length in the range of about 0.1 to 10 inches, or about 2 to 8 inches, or about 3 to 5 inches, or about 3.95 to 4.25 inches. The flexural rigidity of section **56** may also be essentially constant. For example, the flexural rigidity of section **56** may be in the range of about 1×10^{-4} to 9×10^{-3} lbs-inches², or about 1×10^{-3} to 5×10^{-3} lbs-inches², or about 1×10^{-3} to 3×10^{-3} lbs-inches², or about 1.42×10^{-3} to 2.64×10^{-3} lbs-inches². Next to section **56** may be a proximal uncut section **58**, which may lack slots **30** and may have a length in the range of about 0.01 to 0.1 inches, or about 0.02 to 0.04 inches, or about 0.03 inches.

It can be appreciated that the above description of tubular member **20** is provided as an example. Numerous alternative tubular members are contemplated that may lack one or more of the sections described above, include other sections having similar or different properties, or include other structural features.

As indicated above, the flexural rigidity of section **54** may vary. In some embodiments, the flexural rigidity of section **54** may be a function of a third to a fifth order polynomial. For example, the flexural rigidity of section **54** may be a function of a fourth power polynomial [e.g., $FR(x) = A + Bx^4$]. In some embodiments, the flexural rigidity of section **54** (FR_{54}) may transition from the flexural rigidity of section **50** (FR_{50}) to that of section **56** (FR_{56}). For example, the flexural rigidity of section **54** (FR_{54}) may vary according to the following equation, where x is the position along the longitudinal axis of tubular member **20**, x_s is the distance from the distal end of tubular member **20** to the distal end of section **54**, x_f is the distance from the distal end of the tubular member **20** to the proximal end of section **54**, $(x_f - x_s)$ is the length of section **54**, and where the relative position within section **54** is $(x - x_s)$:

$$FR_{54} = FR_{50} + [(FR_{56} - FR_{50}) / \{(x_f - x_s)^4\}] * (x - x_s)^4$$

$$= FR_{50} + (FR_{56} - FR_{50}) * \{(x - x_s) / (x_f - x_s)\}^4$$

This is just an example. Other equations are contemplated that may provide tubular member **20** with the desired flexural rigidity.

Although the above discussion of the flexural rigidity of section **54** is described as being a function of a third order to a fifth order polynomial (e.g., a fourth power equation or polynomial), this is not intended to be limiting. For example, the entire length of tubular member **20** may have a flexural rigidity that varies according to a third order to a fifth order polynomial (e.g., a fourth power equation or polynomial) or any one or more of the sections of tubular member **20** may vary in flexural rigidity in this or any other manner.

Forming tubular member **20** with the desired fourth power transition in flexural rigidity along a portion or all of its length may include a number of procedural steps. For example, these steps may include providing or otherwise starting with a tube having a known inside diameter, a known outside diameter, and that is made from a known material (e.g., having a known Young's modulus). The design may then include setting a constant ratio of the beam height to ring width or the selection

of a range of beam height to ring width ratios. The term "beam height" generally refers to the length or width of the beam in the radial direction. The term "ring width" generally refers to the length between two adjacent slots **30** and an example of ring width, W_r , is shown in FIG. 6.

The beam height to ring width ratio may be set at a value of about 0.5 to 5, or about 1 to 2, or about 1.3 to 1.7, or at a number of individual values over these ranges. With these parameters set, sample parts can be made to establish a "flexural rigidity profile". For example, one sample part may be made with essentially "shallow" cuts (e.g., the beam height may be relatively high). This sample may represent a "stiff" sample tube or a tube with a relatively high flexural rigidity. A number of distinct samples may also be made with shallow cuts, using a number of different beam height to ring width ratios. Other sample parts may also be made including a part with essentially "deep" cuts (e.g., the beam height may be relatively low, which may result in a more flexible tube or a tube with a relatively low flexural rigidity), again using a number of different beam height to ring width ratios, and a number of intermediate tubes that fall intermediate (in terms of beam height) between the first two parts may also be made. The intermediate parts may also be made with a number of different beam height to ring width ratios.

The flexural rigidity can then be measured in the sample parts. Using available software (e.g., EXCEL®, available from Microsoft Corporation, Redmond, Wash.; DESIGN EXPERT, available from Stat Ease, Minneapolis, Minn.), the measured flexural rigidities, beam heights, and beam height to ring width ratios can be entered into a "designed experiment", which can then generate equations that relate flexural rigidity to beam height, ring width, and beam height to ring width ratio. As an alternative to making physical samples, techniques such as mathematical modeling (e.g., Finite Element Analysis, etc.) can be used to simulate physical samples, and theoretical flexural rigidities can be calculated. This information can be entered into a "designed experiment", as above. If desired, a number of physical samples could be made and measured with respect to flexural rigidity, to confirm and/or correct the accuracy of the mathematical simulation. For the purposes of this disclosure, the equations resulting from the designed experiment will be termed the "mathematical model".

With the known parameters set (e.g., starting flexural rigidity, ending flexural rigidity, and ratio or range of ratios of beam height to ring width), a cut pattern can be established with the desired transition in flexural rigidity (e.g., transitioning as a function of a fourth power equation). If the beam height to ring width ratio is not constant, the mathematical model may include one or more equations that describe the change in the ratio as a function of distance from a starting point (e.g., the starting point at which a transition in beam height to ring width ratio begins). This function may be linear, squared, cubed, polynomial, etc. The mathematical model can be used to determine the beam height (or cut depth) and ring width needed to achieve a flexural rigidity at the start of the transition that is equal to the starting flexural rigidity, using the ratio of beam height to ring width defined by the equation noted above. Because the ring width is equal to the distance between cuts minus the width or kerf of the cutting instrument (e.g., and/or the width of the cut), the distance that the tube is translated relative to the cutting apparatus can be readily determined.

Next, the fourth power equation can be used to calculate what the flexural rigidity should be at the second cut point. Once this value is known, the mathematical model can be used to calculate the particular beam height and ring width

that provides the calculated flexural rigidity. Once a cut is made to define the particular beam height, the process can be repeated (e.g., translate the tube the proper distance that is consistent with the beam height to ring width ratio, calculate the flexural rigidity at the next cut location using the fourth power equation, and using the mathematical model to calculate what beam height will give the calculated flexural rigidity) until the full length of the tube for which the desired transition spans is cut in the desired manner.

FIGS. 7-9 depict a variety of example cross-sectional views taken through different portions of tubular member 20 and cuts formed in tubular member 20 in order to illustrate some additional variations contemplated for the distribution or arrangement of slots 30 in tubular member 20. The description of these figures make use of the words “beam” and/or “beams”. The beams are the portion of tubular member 20, often resembling a beam in appearance, that remains after cutting away a portion of tubular member 20 to form slots 30.

Turning now to FIG. 7, when a suitable cutting apparatus cuts into tubular member 20 to form slots 30, the cutting apparatus cuts through tubular member 20 at a particular angular position (e.g., for convenience sake assume the angular position is located at the right hand side or the 0° position of tubular member 20) to a position called the cut depth CD and defines a slot 60a (depicted in phantom as the portion of tubular member 20 removed by cutting). In this example, the beam height BH is the length of width of the beam in the radial direction. The beam height BH may be related to the cut depth CD and the outer diameter OD of tubular member 20. For example, in at least some cases the “deeper” the cut depth CD, the “shorter” the beam height BH. In fact, the relationship between cut depth CD and beam height BH can be represented by the equation:

$$CD=0.5*(OD-BH)$$

Another cut 60b may be made in tubular member 20 at the same longitudinal position (e.g., from the opposite angular position (e.g., 180°)) of tubular member 20 as shown in FIG. 8. Here it can be seen that a pair of beams 62a/62b is defined.

Along the length of tubular member 20, additional pairs of slots and beams can be formed by making additional cuts. In some embodiments, the cuts can be from the same position (e.g., from the 0° and the 180° positions of tubular member 20). Alternatively, the cuts can begin from a different angular position. For example, the first cut made in tubular member 20 at a subsequent longitudinal position may be rotated a radial distance or angle A from where the first cut was made at the first longitudinal position. Angle A could be a suitable angle such as, for example, about 60 to 120°, or about 75 to 100°, or about 85°. Another cut from the opposite side of tubular member 20 defines a second pair of beams. At other longitudinal positions, cuts can be rotated to the same extent or to different extents.

It can be appreciated that the beam pairs (e.g., beam pairs 62a/62b) may have centers that align with the tube centerline C (i.e., a line drawn between the middle of opposing pairs of beams goes through the tube centerline C). While this can be desirable in some embodiments, other arrangements are contemplated that include beam centers that are offset from the tube centerline C. For example, FIG. 9 depicts a portion of tubular member 20 where beam pairs 64a/64b are offset a distance D from the tube centerline C.

In at least some embodiments, one or more sections of tubular member 20 may include beam pairs that are offset from the tube centerline C. For example, section 50 may include any number of slots 30 (e.g., one, some, or all) that include beams that are offset from the tube centerline C. In

some embodiments, all of the slots 30 are offset from the tube centerline C the same distance. This distance may be about 0.001 to 0.007 inches, or about 0.002 to 0.004 inches, or about 0.003 inches. In other embodiments, the distance that the beams are offset may vary.

Other sections of tubular member 20 may have the same amount of offset (e.g., the distance that the beams are offset from the tube centerline C is the same), a different amount of offset, or a variable amount of offset. For example, in section 54, the offset or distance that the beams are offset from the tube centerline C at or near the distal end of section 54 (e.g., at a first slot which is labeled with reference number 66 in FIG. 6) may be the same as the amount of offset in section 50. Over a number of slots or a distance, the amount of offset may gradually reduce to zero. This transition may occur over a distance of about 0.1 to 1 inches, or about 0.2 to 0.5 inches, or about 0.25 inches. Other distances are contemplated. Other sections or portions of sections of tubular member 20 may also have offsets that are the same or different from those in sections 50/54, or may have different amounts of offset altogether.

The amount of beam offset in section 54 may linearly transition to zero offset (e.g., beams aligned with the tube centerline C). This linear transition may be defined by the following relationship:

$$\text{Offset}(x)=0.003*(1-x/0.25)$$

where:

Offset is the distance from the tube centerline C that the beams are offset,

x is the distance from the start of section 54.

In addition to variation in offset, other variations are contemplated. For example, the distance between adjacent slots 30 may be termed the ring width W_r , as shown in FIG. 6. A ratio may be established between the beam height BH and the ring width W_r . In some embodiments, this ratio may be constant in one or more portions of the entire length of tubular member 20. Alternatively, the ratio of the beam height BH and the ring width W_r may vary. For example, the ratio of the beam height BH and the ring width W_r may vary in section 54. This may include any suitable variation. In some embodiments, the ratio of the beam height BH and the ring width W_r may vary such that the ratio at the proximal end of section 54 is greater than at the distal end. Other variations are contemplated.

In one example, the ratio of the beam height to ring width is constant in section 50 and remains constant over a distal portion of section 54. At a distance of about 0.1 to 3 inches, or about 1 to 3 inches, or about 1.95 to 2.25 inches, or about 1.97 to 2.12 inches, the ratio of the beam height to ring width may begin to vary. For example, the beam height to ring width ratio in section 50 may be about 1 to 3, about 1 to 2, about 1 to 1.7, about 1.2 to 1.5, or about 1.3. The same may be true of the distal portion of section 54. The beam height to ring width ratio may then vary over a length of section 54. The transition may be a linear transition (e.g., the beam height to ring width ratio increases linearly) over a length of about 0.1 to 1 inches, about 0.25 to 1 inches, about 0.3 to 0.6 inches, about 0.38 to 0.53 inches, or otherwise a distance sufficient to extend to the proximal end of section 54. The beam height to ring width ratio at the end of the transition may be about 1 to 2, about 1.3 to 1.8, or about 1.6 to 1.7.

Various embodiments of arrangements and configurations of slots 30 are contemplated that may be used in addition to what is described above or may be used in alternate embodiments. For example, in some embodiments, at least some, if not all of slots 30 are disposed at the same or a similar angle

11

with respect to the longitudinal axis of tubular member **20**. As shown, slots **30** can be disposed at an angle that is perpendicular, or substantially perpendicular, and/or can be characterized as being disposed in a plane that is normal to the longitudinal axis of tubular member **20**. However, in other embodiments, slots **30** can be disposed at an angle that is not perpendicular, and/or can be characterized as being disposed in a plane that is not normal to the longitudinal axis of tubular member **20**. Additionally, a group of one or more slots **30** may be disposed at different angles relative to another group of one or more slots **30**. The distribution and/or configuration of slots **30** can also include, to the extent applicable, any of those disclosed in U.S. Pat. Publication No. US 2004/0181174, the entire disclosure of which is herein incorporated by reference.

Slots **30** may be provided to enhance the flexibility of tubular member **20** while still allowing for suitable torque transmission characteristics. Slots **30** may be formed such that one or more rings and/or tube segments interconnected by one or more segments and/or beams that are formed in tubular member **20**, and such tube segments and beams may include portions of tubular member **20** that remain after slots **30** are formed in the body of tubular member **20**. Such an interconnected structure may act to maintain a relatively high degree of torsional stiffness, while maintaining a desired level of lateral flexibility. In some embodiments, some adjacent slots **30** can be formed such that they include portions that overlap with each other about the circumference of tubular member **20**. In other embodiments, some adjacent slots **30** can be disposed such that they do not necessarily overlap with each other, but are disposed in a pattern that provides the desired degree of lateral flexibility.

Additionally, slots **30** can be arranged along the length of, or about the circumference of, tubular member **20** to achieve desired properties. For example, adjacent slots **30**, or groups of slots **30**, can be arranged in a symmetrical pattern, such as being disposed essentially equally on opposite sides about the circumference of tubular member **20**, or can be rotated by an angle relative to each other about the axis of tubular member **20**. Additionally, adjacent slots **30**, or groups of slots **30**, may be equally spaced along the length of tubular member **20**, or can be arranged in an increasing or decreasing density pattern, or can be arranged in a non-symmetric or irregular pattern. Other characteristics, such as slot size, slot shape, and/or slot angle with respect to the longitudinal axis of tubular member **20**, can also be varied along the length of tubular member **20** in order to vary the flexibility or other properties. In other embodiments, moreover, it is contemplated that the portions of the tubular member, such as a proximal section, or a distal section, or the entire tubular member **20**, may not include any such slots **30**.

As suggested herein, slots **30** may be formed in groups of two, three, four, five, or more slots **30**, which may be located at substantially the same location along the axis of tubular member **20**. Alternatively, a single slot **30** may be disposed at some or all of these locations. Within the groups of slots **30**, there may be included slots **30** that are equal in size (i.e., span the same circumferential distance around tubular member **20**). In some of these as well as other embodiments, at least some slots **30** in a group are unequal in size (i.e., span a different circumferential distance around tubular member **20**). Longitudinally adjacent groups of slots **30** may have the same or different configurations. For example, some embodiments of tubular member **20** include slots **30** that are equal in size in a first group and then unequally sized in an adjacent group. It can be appreciated that in groups that have two slots **30** that are equal in size and are symmetrically disposed around the tube circumference, the centroid of the pair of

12

beams (i.e., the portion of tubular member **20** remaining after slots **30** are formed therein) is coincident with the central axis of tubular member **20**. Conversely, in groups that have two slots **30** that are unequal in size and whose centroids are directly opposed on the tube circumference, the centroid of the pair of beams can be offset from the central axis of tubular member **20**. Some embodiments of tubular member **20** include only slot groups with centroids that are coincident with the central axis of the tubular member **20**, only slot groups with centroids that are offset from the central axis of tubular member **20**, or slot groups with centroids that are coincident with the central axis of tubular member **20** in a first group and offset from the central axis of tubular member **20** in another group. The amount of offset may vary depending on the depth (or length) of slots **30** and can include other suitable distances.

Slots **30** can be formed by methods such as micro-machining, saw-cutting (e.g., using a diamond grit embedded semiconductor dicing blade), electron discharge machining, grinding, milling, casting, molding, chemically etching or treating, or other known methods, and the like. In some such embodiments, the structure of the tubular member **20** is formed by cutting and/or removing portions of the tube to form slots **30**. Some example embodiments of appropriate micromachining methods and other cutting methods, and structures for tubular members including slots and medical devices including tubular members are disclosed in U.S. Pat. Publication Nos. 2003/0069522 and 2004/0181174-A2; and U.S. Pat. Nos. 6,766,720; and 6,579,246, the entire disclosures of which are herein incorporated by reference. Some example embodiments of etching processes are described in U.S. Pat. No. 5,106,455, the entire disclosure of which is herein incorporated by reference. It should be noted that the methods for manufacturing guidewire **10** may include forming slots **30** in tubular member **20** using these or other manufacturing steps.

In at least some embodiments, slots **30** may be formed in tubular member using a laser cutting process. The laser cutting process may include a suitable laser and/or laser cutting apparatus. For example, the laser cutting process may utilize a fiber laser. Utilizing processes like laser cutting may be desirable for a number of reasons. For example, laser cutting processes may allow tubular member **20** to be cut into a number of different cutting patterns in a precisely controlled manner. This may include variations in the slot width, ring width, beam height and/or width, etc. Furthermore, changes to the cutting pattern can be made without the need to replace the cutting instrument (e.g., blade). This may also allow smaller tubes (e.g., having a smaller outer diameter) to be used to form tubular member **20** without being limited by a minimum cutting blade size. Consequently, tubular members **20** may be fabricated for use in neurological devices or other devices where a relatively small size may be desired.

The materials that can be used for the various components of guidewire **10** (and/or other guidewires disclosed herein) and the various tubular members disclosed herein may include those commonly associated with medical devices. For simplicity purposes, the following discussion makes reference to tubular member **20** and other components of guidewire **10**. However, this is not intended to limit the devices and methods described herein, as the discussion may be applied to other similar tubular members and/or components of tubular members or devices disclosed herein.

Tubular member **20** and/or other components of guidewire **10** may be made from a metal, metal alloy, polymer (some examples of which are disclosed below), a metal-polymer composite, ceramics, combinations thereof, and the like, or

other suitable material. Some examples of suitable metals and metal alloys include stainless steel, such as 304V, 304L, and 316LV stainless steel; mild steel; nickel-titanium alloy such as linear-elastic and/or super-elastic nitinol; other nickel alloys such as nickel-chromium-molybdenum alloys (e.g., UNS: N06625 such as INCONEL® 625, UNS: N06022 such as HASTELLOY® C-22®, UNS: N10276 such as HASTELLOY® C276®, other HASTELLOY® alloys, and the like), nickel-copper alloys (e.g., UNS: N04400 such as MONEL® 400, NICKELVAC® 400, NICORROS® 400, and the like), nickel-cobalt-chromium-molybdenum alloys (e.g., UNS: R30035 such as MP35-N® and the like), nickel-molybdenum alloys (e.g., UNS: N10665 such as HASTELLOY® ALLOY B2®), other nickel-chromium alloys, other nickel-molybdenum alloys, other nickel-cobalt alloys, other nickel-iron alloys, other nickel-copper alloys, other nickel-tungsten or tungsten alloys, and the like; cobalt-chromium alloys; cobalt-chromium-molybdenum alloys (e.g., UNS: R30003 such as ELGILOY®, PHYNOX®, and the like); platinum enriched stainless steel; titanium; combinations thereof; and the like; or any other suitable material.

As alluded to herein, within the family of commercially available nickel-titanium or nitinol alloys, is a category designated “linear elastic” or “non-super-elastic” which, although may be similar in chemistry to conventional shape memory and super elastic varieties, may exhibit distinct and useful mechanical properties. Linear elastic and/or non-super-elastic nitinol may be distinguished from super elastic nitinol in that the linear elastic and/or non-super-elastic nitinol does not display a substantial “superelastic plateau” or “flag region” in its stress/strain curve like super elastic nitinol does. Instead, in the linear elastic and/or non-super-elastic nitinol, as recoverable strain increases, the stress continues to increase in a substantially linear, or a somewhat, but not necessarily entirely linear relationship until plastic deformation begins or at least in a relationship that is more linear than the super elastic plateau and/or flag region that may be seen with super elastic nitinol. Thus, for the purposes of this disclosure linear elastic and/or non-super-elastic nitinol may also be termed “substantially” linear elastic and/or non-super-elastic nitinol.

In some cases, linear elastic and/or non-super-elastic nitinol may also be distinguishable from super elastic nitinol in that linear elastic and/or non-super-elastic nitinol may accept up to about 2-5% strain while remaining substantially elastic (e.g., before plastically deforming) whereas super elastic nitinol may accept up to about 8% strain before plastically deforming. Both of these materials can be distinguished from other linear elastic materials such as stainless steel (that can also can be distinguished based on its composition), which may accept only about 0.2 to 0.44 percent strain before plastically deforming.

In some embodiments, the linear elastic and/or non-super-elastic nickel-titanium alloy is an alloy that does not show any martensite/austenite phase changes that are detectable by differential scanning calorimetry (DSC) and dynamic metal thermal analysis (DMTA) analysis over a large temperature range. For example, in some embodiments, there may be no martensite/austenite phase changes detectable by DSC and DMTA analysis in the range of about -60 degrees Celsius (° C.) to about 120° C. in the linear elastic and/or non-super-elastic nickel-titanium alloy. The mechanical bending properties of such material may therefore be generally inert to the effect of temperature over this very broad range of temperature. In some embodiments, the mechanical bending properties of the linear elastic and/or non-super-elastic nickel-titanium alloy at ambient or room temperature are substantially

the same as the mechanical properties at body temperature, for example, in that they do not display a super-elastic plateau and/or flag region. In other words, across a broad temperature range, the linear elastic and/or non-super-elastic nickel-titanium alloy maintains its linear elastic and/or non-super-elastic characteristics and/or properties.

In some embodiments, the linear elastic and/or non-super-elastic nickel-titanium alloy may be in the range of about 50 to about 60 weight percent nickel, with the remainder being essentially titanium. In some embodiments, the composition is in the range of about 54 to about 57 weight percent nickel. One example of a suitable nickel-titanium alloy is FHP-NT alloy commercially available from Furukawa Techno Material Co. of Kanagawa, Japan. Some examples of nickel titanium alloys are disclosed in U.S. Pat. Nos. 5,238,004 and 6,508,803, which are incorporated herein by reference. Other suitable materials may include ULTANIUM™ (available from Neo-Metrics) and GUM METAL™ (available from Toyota). In some other embodiments, a superelastic alloy, for example a superelastic nitinol can be used to achieve desired properties.

In at least some embodiments, portions or all of core wire **18** and/or tubular member **20** may also be doped with, made of, or otherwise include a radiopaque material. Radiopaque materials are understood to be materials capable of producing a relatively bright image on a fluoroscopy screen or another imaging technique during a medical procedure. This relatively bright image aids the user of guidewire **10** in determining its location. Some examples of radiopaque materials can include, but are not limited to, gold, platinum, palladium, tantalum, tungsten alloy, polymer material loaded with a radiopaque filler, and the like. Additionally, other radiopaque marker bands and/or coils may also be incorporated into the design of guidewire **10** to achieve the same result.

In some embodiments, a degree of Magnetic Resonance Imaging (MRI) compatibility is imparted into guidewire **10**. For example, to enhance compatibility with MRI machines, it may be desirable to make core wire **18** and/or tubular member **20**, or other portions of the guidewire **10**, in a manner that would impart a degree of MRI compatibility. For example, core wire **18** and/or tubular member **20**, or portions thereof, may be made of a material that does not substantially distort the image and create substantial artifacts (i.e., gaps in the image). Certain ferromagnetic materials, for example, may not be suitable because they may create artifacts in an MRI image. Core wire **18** and/or tubular member **20**, or portions thereof, may also be made from a material that the MRI machine can image. Some materials that exhibit these characteristics include, for example, tungsten, cobalt-chromium-molybdenum alloys (e.g., UNS: R30003 such as ELGILOY®, PHYNOX®, and the like), nickel-cobalt-chromium-molybdenum alloys (e.g., UNS: R30035 such as MP35-N® and the like), nitinol, and the like, and others.

Referring now to core wire **18**, the entire core wire **18** can be made of the same material along its length, or in some embodiments, can include portions or sections made of different materials. In some embodiments, the material used to construct core wire **18** is chosen to impart varying flexibility and stiffness characteristics to different portions of core wire **18**. For example, proximal section **22** and distal section **24** of core wire **18** may be formed of different materials, for example, materials having different moduli of elasticity, resulting in a difference in flexibility. In some embodiments, the material used to construct proximal section **22** can be relatively stiff for pushability and torqueability, and the material used to construct distal section **24** can be relatively flexible by comparison for better lateral trackability and steer-

ability. For example, proximal section **22** can be formed of straightened **304v** stainless steel wire or ribbon and distal section **24** can be formed of a straightened super elastic or linear elastic alloy, for example a nickel-titanium alloy wire or ribbon.

In embodiments where different portions of core wire **18** are made of different materials, the different portions can be connected using a suitable connecting technique and/or with a connector. For example, the different portions of core wire **18** can be connected using welding (including laser welding), soldering, brazing, adhesive, or the like, or combinations thereof. These techniques can be utilized regardless of whether or not a connector is utilized. The connector may include a structure generally suitable for connecting portions of a guidewire. One example of a suitable structure includes a structure such as a hypotube or a coiled wire which has an inside diameter sized appropriately to receive and connect to the ends of the proximal portion and the distal portion. Other suitable configurations and/or structures can be utilized for connector **26** including those connectors described in U.S. Pat. Nos. 6,918,882 and 7,071,197 and/or in U.S. Patent Pub. No. 2006-0122537, the entire disclosures of which are herein incorporated by reference.

A sheath or covering (not shown) may be disposed over portions or all of core wire **18** and/or tubular member **20** that may define a generally smooth outer surface for guidewire **10**. In other embodiments, however, such a sheath or covering may be absent from a portion of all of guidewire **10**, such that tubular member **20** and/or core wire **18** may form the outer surface. The sheath may be made from a polymer or other suitable material. Some examples of suitable polymers may include polytetrafluoroethylene (PTFE), ethylene tetrafluoroethylene (ETFE), fluorinated ethylene propylene (FEP), polyoxymethylene (POM, for example, DELRIN® available from DuPont), polyether block ester, polyurethane (for example, Polyurethane 85A), polypropylene (PP), polyvinylchloride (PVC), polyether-ester (for example, ARNITEL® available from DSM Engineering Plastics), ether or ester based copolymers (for example, butylene/poly(alkylene ether) phthalate and/or other polyester elastomers such as HYTREL® available from DuPont), polyamide (for example, DURETHAN® available from Bayer or CRISTAMID® available from Elf Atochem), elastomeric polyamides, block polyamide/ethers, polyether block amide (PEBA, for example available under the trade name PEBAX®), ethylene vinyl acetate copolymers (EVA), silicones, polyethylene (PE), Marlex high-density polyethylene, Marlex low-density polyethylene, linear low density polyethylene (for example REXELL®), polyester, polybutylene terephthalate (PBT), polyethylene terephthalate (PET), polytrimethylene terephthalate, polyethylene naphthalate (PEN), polyetheretherketone (PEEK), polyimide (PI), polyetherimide (PEI), polyphenylene sulfide (PPS), polyphenylene oxide (PPO), polyparaphenylene terephthalamide (for example, KEVLAR®), polysulfone, nylon, nylon-12 (such as GRILAMID® available from EMS American Grilon), perfluoro(propyl vinyl ether) (PFA), ethylene vinyl alcohol, polyolefin, polystyrene, epoxy, polyvinylidene chloride (PVdC), poly(styrene-*b*-isobutylene-*b*-styrene) (for example, SIBS and/or SIBS 50A), polycarbonates, ionomers, biocompatible polymers, other suitable materials, or mixtures, combinations, copolymers thereof, polymer/metal composites, and the like. In some embodiments the sheath can be blended with a liquid crystal polymer (LCP). For example, the mixture can contain up to about 6 percent LCP.

In some embodiments, the exterior surface of the guidewire **10** (including, for example, the exterior surface of core wire

18 and/or the exterior surface of tubular member **20**) may be sandblasted, beadblasted, sodium bicarbonate-blasted, electropolished, etc. In these as well as in some other embodiments, a coating, for example a lubricious, a hydrophilic, a protective, or other type of coating may be applied over portions or all of the sheath, or in embodiments without a sheath over portion of core wire **18** and/or tubular member, or other portions of device **10**. Alternatively, the sheath may comprise a lubricious, hydrophilic, protective, or other type of coating. Hydrophobic coatings such as fluoropolymers provide a dry lubricity which improves to guidewire handling and device exchanges. Lubricious coatings improve steerability and improve lesion crossing capability. Suitable lubricious polymers are well known in the art and may include silicone and the like, hydrophilic polymers such as high-density polyethylene (HDPE), polytetrafluoroethylene (PTFE), polyarylene oxides, polyvinylpyrrolidones, polyvinylalcohols, hydroxy alkyl celluloses, algin, saccharides, caprolactones, and the like, and mixtures and combinations thereof. Hydrophilic polymers may be blended among themselves or with formulated amounts of water insoluble compounds (including some polymers) to yield coatings with suitable lubricity, bonding, and solubility. Some other examples of such coatings and materials and methods used to create such coatings can be found in U.S. Pat. Nos. 6,139,510 and 5,772,609, which are incorporated herein by reference.

The coating and/or sheath may be formed, for example, by coating, extrusion, co-extrusion, interrupted layer co-extrusion (ILC), or fusing several segments end-to-end. The same may be true of tip member **28**. The layer may have a uniform stiffness or a gradual reduction in stiffness from the proximal end to the distal end thereof. The gradual reduction in stiffness may be continuous as by ILC or may be stepped as by fusing together separate extruded tubular segments. The outer layer may be impregnated with a radiopaque filler material to facilitate radiographic visualization. Those skilled in the art will recognize that these materials can vary widely without deviating from the scope of the present invention.

The disclosures of U.S. Patent Application Publication Nos. US 2009/0118675, US 2009/0254000, and US 2009/0177185, the entire disclosures of which are herein incorporated by reference, may pertain to this disclosure. The disclosure of U.S. Pat. No. 6,106,488, the entire disclosure of which is herein incorporated by reference, may also pertain to this disclosure.

It should be understood that this disclosure is, in many respects, only illustrative. Changes may be made in details, particularly in matters of shape, size, and arrangement of steps without exceeding the scope of the invention. The invention's scope is, of course, defined in the language in which the appended claims are expressed.

What is claimed is:

1. A guidewire, comprising:

a core wire having a distal portion; and

a tubular member disposed over the distal portion, the tubular member having a plurality of slots formed therein and having a longitudinal axis;

wherein the tubular member includes a variably spaced slot section that has a flexural rigidity that varies from a first flexural rigidity to a second flexural rigidity, and wherein the transition from the first flexural rigidity to the second flexural rigidity is a function of a fourth order equation;

wherein the first flexural rigidity is in the range of about 1×10^{-6} to about 9×10^{-5} lbs-inches²; and

wherein the second flexural rigidity is in the range of about 1×10^{-3} to about 5×10^{-3} lbs-inches².

17

2. The guidewire of claim 1, wherein the second flexural rigidity is in the range of about 1×10^{-3} to about 3×10^{-3} lbs-inches².

3. The guidewire of claim 1, wherein the second flexural rigidity is in the range of about 1.42×10^{-3} to about 2.64×10^{-3} lbs-inches².

4. The guidewire of claim 1, wherein the tubular member has a distal end and wherein the tubular member includes a first non-slotted section disposed at the distal end, the first non-slotted section being free of slots.

5. The guidewire of claim 4, wherein the tubular member includes a first constantly spaced slot section that includes slots that have a constant spacing along the longitudinal axis, the first constantly spaced slot section being disposed adjacent to the first non-slotted section.

6. The guidewire of claim 5, wherein the tubular member includes a second constantly spaced slot section that includes slots that have a constant spacing along the longitudinal axis.

7. The guidewire of claim 6, wherein the variably spaced slot section is disposed between the first constantly spaced slot section and the second constantly spaced slot section.

8. The guidewire of claim 7, wherein the tubular member includes a second non-slotted section disposed between the first constantly spaced slot section and the variably spaced slot section, the second non-slotted section being free of slots.

9. The guidewire of claim 8, wherein the tubular member has a proximal end and wherein the tubular member includes a third non-slotted section disposed at the proximal end, the third non-slotted section being free of slots.

10. The guidewire of claim 1, wherein the slots define a beam height for a pair of beams at a longitudinal position along tubular member, wherein a distance between two longitudinally adjacent slots defines a ring width, and wherein the ratio of the beam height to ring width is constant along at least a portion of the tubular member.

11. The guidewire of claim 10, wherein the ratio of beam height to ring width is constant in a first portion of the tubular member and wherein the ratio of beam height to ring width varies in a second portion of the tubular member.

12. The guidewire of claim 11, wherein the ratio of beam height to ring width varies along the variably spaced slot section.

13. The guidewire of claim 1, wherein the slots define beams in the tubular member and wherein at least some of the beams are offset from a centerline of the tubular member.

14. The guidewire of claim 13, wherein the beams are aligned with the centerline along a portion of the tubular member and wherein the beams are offset from the centerline along a second portion of the tubular member.

15. The guidewire of claim 14, wherein the variably spaced slot section includes beams that are offset a distance from the centerline of the tubular member.

18

16. The guidewire of claim 15, wherein the variable spaced slot section includes a transition where the beams that are offset from the centerline transition from being offset by the distance to beams that are aligned with the centerline of the tubular member.

17. A guidewire, comprising:

a linear-elastic nickel-titanium core wire having a distal portion;

a super-elastic nickel-titanium tubular member disposed over the distal portion, the tubular member having a plurality of slots formed therein and having a longitudinal axis;

wherein the tubular member includes a variably spaced slot section that has a flexural rigidity that varies from a first flexural rigidity to a second flexural rigidity, and wherein the transition from the first flexural rigidity to the second flexural rigidity is a function of a fourth order equation;

wherein the first flexural rigidity is in the range of about 1×10^{-6} to about 9×10^{-5} lbs-inches²; and

wherein the second flexural rigidity is in the range of about 1×10^{-3} to about 5×10^{-3} lbs-inches².

18. The guidewire of claim 17, wherein the tubular member includes a first constantly spaced slot section and a second constantly spaced slot section that each include slots that are spaced a constant distance along the longitudinal axis.

19. The guidewire of claim 18, wherein the variably spaced slot section is disposed between the first constantly spaced slot section and the second constantly spaced slot section.

20. A method for manufacturing a guidewire, comprising: providing a tubular member having a longitudinal axis; forming a first slot in the tubular member at a first position along the longitudinal axis;

forming a second slot in the tubular member at a second position along the longitudinal axis;

forming a plurality of additional slots in the tubular members at a plurality of positions along the longitudinal axis; and

wherein the first slot, the second slot, and the plurality of additional slots are variably spaced along the longitudinal axis so as to define a variably spaced slot section wherein the tubular member includes a variably spaced slot section that has a flexural rigidity that varies from a first flexural rigidity to a second flexural rigidity, wherein the transition from the first flexural rigidity to the second flexural rigidity is a function of a fourth order equation, wherein the first flexural rigidity is in the range of about 1×10^{-6} to about 9×10^{-5} lbs-inches², and wherein the second flexural rigidity is in the range of about 1×10^{-3} to about 5×10^{-3} lbs-inches².

* * * * *