

US008560860B2

(12) **United States Patent**
Nickell et al.

(10) **Patent No.:** **US 8,560,860 B2**
(45) **Date of Patent:** **Oct. 15, 2013**

(54) **STRONG PASSWORD ENTRY**

(75) Inventors: **Seth Nickell**, Cambridge, MA (US);
Bryan William Clark, Cambridge, MA (US)

(73) Assignee: **Red Hat, Inc.**, Raleigh, NC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1984 days.

(21) Appl. No.: **11/171,452**

(22) Filed: **Jul. 1, 2005**

(65) **Prior Publication Data**

US 2007/0006301 A1 Jan. 4, 2007

(51) **Int. Cl.**

G06F 21/00 (2013.01)
G06F 17/00 (2006.01)
G06F 3/00 (2006.01)
H04L 29/06 (2006.01)

(52) **U.S. Cl.**

USPC **713/183**; 713/182; 726/1; 715/705

(58) **Field of Classification Search**

USPC 713/183; 726/22, 1; 715/780
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,026,491 A * 2/2000 Hiles 726/18
6,643,784 B1 * 11/2003 McCulligh 726/18
2003/0097357 A1 * 5/2003 Ferrari et al. 707/3
2004/0073815 A1 * 4/2004 Sanai et al. 713/202
2004/0250139 A1 * 12/2004 Hurley 713/202
2004/0250141 A1 * 12/2004 Casco-Arias et al. 713/202
2005/0010785 A1 * 1/2005 Abe et al. 713/182

* cited by examiner

Primary Examiner — Stephen Alvesteffer

(74) *Attorney, Agent, or Firm* — Lowenstein Sandler LLP

(57) **ABSTRACT**

Methods and systems are provided to assist users with the entry of strong passwords. The password may be considered strong if it satisfies one or more requirements. A set of these requirements may be selected and then presented to the user. The requirements may be randomly selected one by one or as a group. The requirements may also be presented to the user one by one in a random order or in the form of a list with a random order. As characters for the password are entered, the user may then be notified when one or more the requirements have been satisfied.

15 Claims, 5 Drawing Sheets


Use at least one number

Use at least one capital letter

Do not use a word

Password: *****

Re-Enter:



100

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

1**STRONG PASSWORD ENTRY**

FIELD OF THE INVENTION

The present invention relates generally to the creation of passwords. More particularly, embodiments of the present invention relate to assisting in the creation of strong passwords.

BACKGROUND OF THE INVENTION

In modern computer systems, authentication techniques, such as passwords, have become very important. However, password guessing and cracking tools have also become more capable. If someone is able to guess or hack a user's password, then they may be able to gain access to sensitive information, such as personal identity information or financial information. Therefore, it is generally recommended to use strong (or complex) passwords.

A strong password typically is a certain length and may contain characters of various types. There are many types of requirements for creating strong passwords. For example, a password may be required to be at least seven characters long, contain letters, contain numerals, and contain one or more symbols. In addition, a password may be required to be significantly different from previous passwords, not contain a name, and not be a common word or name. Known systems can provide a dialog window or list of rules through a graphical user interface to indicate the minimum requirements for entering a password.

Unfortunately, users are reluctant to create strong passwords because they can be difficult to remember or create. Instead, users tend to create passwords that are based primarily on a common word, or name. Even when users attempt to create a strong password, they often structure the password so that it is easily memorable. For example, if a user is required to create a password that is seven characters long and includes at least one number. Many users will merely create a password that contains six letters and one number, such as "password1." Although stronger than a plain password, such passwords are still easily guessed.

In addition, known methods and systems often require a user to make multiple attempts at entering a password before they are able to satisfy all the applicable rules. This can be a tedious and frustrating experience for the users.

Accordingly, it may be desirable to provide methods and systems that assist users in the entry of strong passwords.

SUMMARY OF THE INVENTION

In accordance with one feature of the invention, a method is provided for determining a password that is subject to a set of requirements. A first requirement is randomly selected from the set of requirements and provided. Characters for the password are received and it is determined whether the characters satisfy the first requirement. Information is then provided to indicate whether the characters satisfy the first requirement.

In accordance with another feature of the invention, a method of determining a password that is subject to a plurality of requirements is provided. A set of the plurality of requirements is determined and provided in a random sequence. Characters for each of the set of requirements are received and, as the characters are received, it is determined whether the characters respectively satisfy the set of requirements. Information is then provided to indicate whether the characters satisfy the set of requirements.

2

In accordance with another feature of the invention, a method of entering a password that is subject to a plurality of requirements is provided. A set of the requirements are provided in a random sequence. During entry of characters, it is determined whether the characters satisfy the set of requirements. Information is then provided to indicate when each of the set of requirements has been satisfied.

Additional features of the invention will be set forth in part in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the invention, as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description, serve to explain the principles of the invention. In the figures:

FIG. 1 illustrates a system that is consistent with the principles of the present invention;

FIG. 2 illustrates a server that is consistent with the present invention;

FIG. 3 illustrates an exemplary architecture for a server that is consistent with the present invention;

FIG. 4 illustrates an exemplary process flow that is consistent with the present invention; and

FIG. 5 shows an exemplary display screen that is consistent with the present invention.

DESCRIPTION OF THE EMBODIMENTS

Embodiments of the present invention assist users with the entry of strong passwords. The password may be considered strong if it satisfies one or more requirements, such as a minimum character length. A set of these requirements may be selected and then presented to the user. The requirements may be randomly selected individually or as a group. The requirements may also be presented to the user one by one in a random order or in the form of a list with a random order. As characters for the password are entered, the user may then be notified when one or more the requirements have been satisfied.

Reference will now be made in detail to exemplary embodiments of the invention, which are illustrated in the accompanying drawings. FIGS. 1-3 illustrate various systems and components that may be used to implement embodiments of the present invention. FIGS. 4-5 illustrate a process flow and display screen that is consistent with the principles of the present invention. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

FIG. 1 illustrates a system **100** that is consistent with the principles of the present invention. For purposes of illustration, system **100** is shown as a typical system implemented in a network environment, such as the Internet. One skilled in the art will recognize that there many applications on the Internet that may use authentication techniques, such as a password.

As shown, system **100** may comprise a client **102** and a server **104**. These components may be coupled together via network **106**. Network **106** may comprise one or more networks, such as a local area network, or wide area network. In addition, network **106** may support a wide variety of known

protocols, such as the transport control protocol and Internet protocol (“TCP/IP”) and hypertext transport protocol (“HTTP”).

The components of system **100** may be implemented on separate devices or may be implemented on one or more of the same devices or systems. For example, system **100** may have one or more of its components implemented on multiple machines that run different operating systems. Some of the specific components of system **100** will now be described.

Client **102** provides a user interface for system **100**. Client **102** may be implemented using a variety of devices and software. For example client **102** may be implemented on a personal computer, workstation, or terminal. In addition, client **102** may run under an operating system, such as the LINUX operating system, the Microsoft™ Windows operating system, and the like. Client **102** may also operate through an Internet browser application, such as Firefox by Mozilla, Internet Explorer by Microsoft Corporation, or Netscape Navigator by Netscape Communications Corporation. One skilled in the art will also recognize that client **102** may be implemented with various peripheral devices, such as a display, one or more speakers, and other suitable devices that are capable of providing feedback information to a user. Client **102** may also be implemented with various peripherals for accepting input from a user, such as a keyboard, a mouse, and the like. Although FIG. **1** shows a single client, system **100** may include any number of clients.

Server **104** stores, manages, and provides access control to items requested by client **102**. For example, server **104** may process requests to retrieve an object, document, image file, web page, and the like. Server **104** may be implemented using a variety of devices and software. For example, server **104** may be a computer that runs one or more application programs and stored procedures under an operating system, such as LINUX, Windows, or Solaris.

FIG. **2** illustrates a server that is consistent with the present invention. As shown, server **104** may include a central processor **200**, a cache **202**, a main memory **204**, a local storage device **206**, and an input/output controller **208**. These components may be implemented based on hardware and software that is well known to those skilled in the art.

Processor **200** may include cache **202** for storing frequently accessed information. Cache **202** may be an “on-chip” cache or external cache. Server **104** may also be provided with additional peripheral devices, such as a keyboard, mouse, or printer (not shown). In the embodiment shown, the various components of server **104** communicate through a system bus **210** or similar architecture.

Although FIG. **2** illustrates one example of the structure of server **104**, the principles of the present invention are applicable to other types of processors and systems. For example, server **104** may comprise multiple processors, such as those provided by the Intel Corporation, or may comprise multiple computers that are linked together.

FIG. **3** illustrates an exemplary functional architecture for server **104** that is consistent with the present invention. As shown, server **104** may include an operating system (“OS”) **300**, a user interface **302**, a password manager **304**, and a password database **306**. These components may be implemented as software, firmware, or some combination of both, which may be loaded into memory **204** of server **104**. The software components may be written in a variety of programming languages, such as C, C++, Java, etc.

OS **300** is an integrated collection of routines that service the sequencing and processing of programs and applications by server **104**. OS **300** may provide many services, such as resource allocation, scheduling, input/output control, and

data management. OS **300** may be predominantly software, but may also comprise partial or complete hardware implementations and firmware. Well known examples of operating systems that are consistent with the principles of the present invention include Mac OS by Apple Computer, Open VMS, GNU/LINUX, AIX by IBM, Java and Sun Solaris by Sun Microsystems, and the Windows family of operating systems by Microsoft Corporation.

Interface **302** provides a communications interface between server **104** and client **102**. For example, interface **302** may be configured to provide information that indicates the status of a proposed password that is being entered at client **106**. Such communications may be based on well known protocols and programming languages, such as TCP/IP and Java. Interfaces like interface **302** may be implemented using well known Internet technologies, such as web pages, which are well known to those skilled in the art.

Password manager **304** provides the logic for analyzing and managing the passwords proposed at client **106**. For example, password manager **304** may be configured to randomly retrieve one or more rules for a password, provide information that indicates these rules, and determine the status of a proposed password. As noted, password manager **304** may be written in a variety of programming languages, such as C, C++, Java, etc. and executed by server **104**. In other embodiments, one or more of the functions of password manager **304** may be implemented as program code running on client **102**.

Password database **306** provides storage and retrieval for the password data and the various rules that govern passwords. Password database **306** may be implemented using well known database technology, such as relational databases, or object oriented databases.

One skilled in the art will recognize that FIGS. **1-3** merely illustrate some embodiments of the present invention. For example, embodiments of the present invention may be implemented as software that is installed on a single computer. In other embodiments, server **104** may be configured as a central password authority to ensure that all clients, such as client **102**, adhere to the same password rules.

Reference will now be made to FIGS. **4-5** to illustrate an exemplary process and display that are consistent with the present invention. As noted, the process and display illustrated in FIGS. **4-5** may be implemented using client **102**, a programmed computer or other processing device. The program code may be stored on a storage medium, such as a compact disk, diskette, or any other suitable storage medium.

FIG. **4** illustrates a process flow for entering a strong password. In stage **400**, one or more requirements for the password are randomly selected and provided. Password manager **304** may be triggered to begin its operations based on a number of events. For example, password manager **304** may be triggered in response to a request from client **102**. Alternatively, password manager **304** may be triggered based on a time interval. For example, password manager **304** may be configured to require a new password at least once a month or once a year.

Password manager **304** may select one or more rules from password database **306** in various ways. For example, password database **306** may contain a large number of available rules for governing passwords and each rule may be assigned a unique identifier. Password manager **304** may then retrieve one or more of these rules from password database **306** by selecting the appropriate unique identifiers. In some embodiments, password manager **304** may select a rule randomly one at a time. That is, password manager **304** may select each rule independently of each other. Alternatively, password man-

ager 304 may randomly select a group of rules. For example, password manager 304 may be configured to support multiple types or classes of users such that some users may require higher levels of security. Accordingly, password manager 304 may retrieve and randomly select different groups of password rules for different classes of users.

Generally, password manager 304 may assist users in creating strong passwords by guiding the users in entering "random" characters for the password. In order to accomplish this, password manager 304 may be configured to provide its rules for a password in a random sequence either individually or in a group. For example, if a particular password is required to contain at least one capital letter and at least one numerical character, password manager 304 may provide these rules to the user in a random order. Otherwise, the user may be tempted to simply enter a password with a capital letter followed by a number as part of the password. However, if the user is randomly prompted first to enter a number and then a capital letter, the user is likely to respond in kind and enter the characters in a fashion that mimics the random order, which may eventually lead to a stronger password.

In addition, password manager 304 may also be configured to provide various rules for when users are changing from a previous password. For example, password manager 304 may randomly select one or more rules that specify the extent to which a new password must differ from a previous password.

Once it has selected the applicable rules, password manager 304 may provide the rules to client 102, for example, via interface 302. Password manager 304 may provide the applicable rules in the form of text or other type of information, such as extensible markup language data. Subsequently, client 102 may then provide the applicable password rules to the user. For example, client 102 may provide the password rules using a dialog window or other suitable graphical user interface. In order to assist the user, client 102 may display the rules one at a time or in the form of a list.

In stage 402, characters for the password are received and it is determined whether the characters satisfy the requirements. In particular, a user at client 102 may commence entering characters for a proposed password. Client 102 may then analyze these characters to determine if they satisfy the rules received from password manager 302. Client 102 may be configured to continuously analyze the entered characters one at a time or in sets. For example, client 102 may be configured to buffer a number of characters and then analyze whether this group of characters assists in satisfying one or more rules. The number of characters buffered may be configured by client 102 or may be directed by password manager 302.

In some embodiments, client 102 continuously evaluates the characters as they are entered by the user against the applicable password rules. Client 102 may perform this analysis alone or in conjunction with server 104. For example, when a user enters a character, client 102 may determine if a selected rule has been satisfied in real time.

In stage 404, as the user enters characters for the password, client 102 may provide feedback to the user regarding the status of satisfying the password rules. For example, client 102 may highlight a rule or display a visual indicator, such as a check mark or "X", to indicate that the recently entered character was sufficient to satisfy one or more rules. Conversely, client 102 may provide feedback when the characters entered fail to satisfy one or more rules. Client 102 may also provide other forms of feedback, such as an audible tone, to the user as characters are entered for a password.

Accordingly, client 102 may be configured to provide effective feedback to the user as to the status of their proposed

password. Client 102 may continuously provide the feedback visually or audibly, for example, after each character has been entered.

In some embodiments, the user may then confirm that their proposed password satisfies all of the rules provided. For example, client 102 may provide a dialog window with a button that the user selects to confirm they have completed entering a proposed password. Client 102 may then perform a final analysis of the entered password. This analysis may be performed by client 102 alone or in conjunction with server 104.

FIG. 5 shows an exemplary display screen that is consistent with the present invention. As shown, check marks are displayed next to various rules as the user has entered characters for a password. In the example shown, the rules have been selected and displayed in a random order (from top to bottom) to assist the user. Of course, one skilled in the art will recognize that other types of displays and windows may be used in embodiments of the present invention.

Other embodiments of the invention will be apparent to those skilled in the art from consideration of the specification and practice of the invention disclosed herein. It is intended that the specification and examples be considered as exemplary only.

What is claimed is:

1. A method comprising:

randomly selecting, by a computer executing a password manager, a first requirement for creating a password from a set of requirements;

providing the first requirement for creating the password; receiving characters for the password; determining whether the characters satisfy the first requirement;

providing information that indicates whether the characters satisfy the first requirement; and

randomly selecting, by the computer, a second requirement for creating the password from the set of requirements in response to the characters satisfying the first requirement, wherein the second requirement is selected independently of the first requirement.

2. The method of claim 1, wherein determining whether the characters satisfy the first requirement comprises determining whether the characters satisfy the first requirement as each of the characters are received.

3. The method of claim 1, wherein determining whether the characters satisfy the first requirement comprises:

buffering a set of received characters; and

determining whether the set of received characters satisfy the first requirement.

4. The method of claim 1, wherein providing information that indicates whether the characters satisfy the first requirement comprises providing information that indicates the characters fail to satisfy the first requirement.

5. The method of claim 1, wherein providing information that indicates whether the characters satisfy the first requirement comprises providing information that indicates the first requirement when the characters fail to satisfy the first requirement.

6. A non-transitory computer readable medium containing instructions that, when executed by a computer, cause the computer to perform a method comprising:

randomly selecting a first requirement for creating a password from a set of requirements;

providing the first requirement for creating the password; receiving characters for the password;

determining whether the characters satisfy the first requirement;

7

providing information that indicates whether the characters satisfy the first requirement; and
 randomly selecting a second requirement for creating the password from the set of requirements in response to the characters satisfying the first requirement, wherein the second requirement is selected independently of the first requirement.

7. The non-transitory computer readable medium of claim 6, wherein determining whether the characters satisfy the first requirement comprises determining whether the characters satisfy the first requirement as each of the characters are received.

8. The non-transitory computer readable medium of claim 6, wherein determining whether the characters satisfy the first requirement comprises:

buffering a set of received characters; and
 determining whether the set of received characters satisfy the first requirement.

9. The non-transitory computer readable medium of claim 6, wherein providing information that indicates whether the characters satisfy the first requirement comprises providing information that indicates the characters fail to satisfy the first requirement.

10. The non-transitory computer readable medium of claim 6, wherein providing information that indicates whether the characters satisfy the first requirement comprises providing information that indicates the first requirement when the characters fail to satisfy the first requirement.

11. A computer comprising:

a memory to store instructions for a password manager;
 and
 a processor, coupled to the memory, to execute the instructions, wherein the processor is configured to:

8

randomly select a first requirement for creating a password from a set of requirements;
 provide the first requirement for creating the password;
 receive characters for the password;
 determine whether the characters satisfy the first requirement;
 provide information that indicates whether the characters satisfy the first requirement; and
 randomly select a second requirement for creating the password from the set of requirements in response to the characters satisfying the first requirement, wherein the second requirement is selected independently of the first requirement.

12. The computer of claim 11, wherein determining whether the characters satisfy the first requirement comprises determining whether the characters satisfy the first requirement as each of the characters are received.

13. The computer of claim 11, wherein determining whether the characters satisfy the first requirement comprises:

buffering a set of received characters; and
 determining whether the set of received characters satisfy the first requirement.

14. The computer of claim 11, wherein providing information that indicates whether the characters satisfy the first requirement comprises providing information that indicates the characters fail to satisfy the first requirement.

15. The computer of claim 11, wherein providing information that indicates whether the characters satisfy the first requirement comprises providing information that indicates the first requirement when the characters fail to satisfy the first requirement.

* * * * *