

US008565999B2

(12) **United States Patent**
Bunce et al.

(10) **Patent No.:** **US 8,565,999 B2**
(45) **Date of Patent:** **Oct. 22, 2013**

(54) **GAS TURBINE ENGINE CONTROL USING ACOUSTIC PYROMETRY**

(75) Inventors: **Richard H. Bunce**, Altamonte Springs, FL (US); **Upul P. Desilva**, Oviedo, FL (US)

(73) Assignee: **Siemens Energy, Inc.**, Orlando, FL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 470 days.

(21) Appl. No.: **12/967,148**

(22) Filed: **Dec. 14, 2010**

(65) **Prior Publication Data**

US 2012/0150413 A1 Jun. 14, 2012

(51) **Int. Cl.**
G06F 19/00 (2011.01)
G06G 7/70 (2006.01)

(52) **U.S. Cl.**
USPC **701/100**; 701/1; 701/3; 701/99; 73/1.48;
73/29.03

(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,848,924 A 7/1989 Nuspl et al.
5,275,553 A 1/1994 Frish et al.
6,142,665 A 11/2000 Haffner et al.
6,768,938 B2 7/2004 McBrien et al.

7,013,210 B2 3/2006 McBrien et al.
7,383,165 B2 6/2008 Aragones
7,761,216 B2 7/2010 Norris et al.
2007/0027607 A1 2/2007 Norris et al.
2007/0151363 A1 7/2007 Ramsesh
2010/0076698 A1 3/2010 He et al.

OTHER PUBLICATIONS

Roberto Roubicek; Gas Temperature Measurement in the Fireside of Process Heaters-Using Acoustic Pyrometry; 2003 NPRA Maintenance Conference; 2003; Salt Lake City, Utah.

J.A. Kleppe et al.; The Application of Acoustic Pyrometry to Gas Turbines and Jet Engines; AIAA 98-3611; 1998.

Gustave C. Fralick et al.; Passive Acoustic Tomography Tested for Measuring Gas Temperatures; Research and Technology 2003; May 2004; NASA Glenn Research Center, Cleveland, OH.



Gustave C. Fralick; Acoustic Pyrometry Applied to Gas Turbines and Jet Engines; www.grc.nas.gov/WWW/RT/RT1998/5000/5510; 1998.

Primary Examiner — Bhavesh V Amin

(57) **ABSTRACT**

A method and apparatus for operating a gas turbine engine including determining a temperature of a working gas at a predetermined axial location within the engine. Acoustic signals are transmitted from a plurality of acoustic transmitters and are received at a plurality of acoustic receivers. Each acoustic signal defines a distinct line-of-sound path from one of the acoustic transmitters to an acoustic receiver corresponding to the line-of-sound path. A time-of-flight is determined for each of the signals traveling along the line-of-sound paths, and the time-of-flight for each of the signals is processed to determine a temperature in a region of the predetermined axial location.

20 Claims, 8 Drawing Sheets






FIG. 1




FIG. 2





FIG. 3






FIG. 5




FIG. 6




FIG. 7




FIG. 8

1

GAS TURBINE ENGINE CONTROL USING ACOUSTIC PYROMETRY

FIELD OF THE INVENTION

The present invention relates to temperature measurement in turbine engines and, more particularly, to determination of temperature using acoustic measurements to control a gas turbine engine.

BACKGROUND OF THE INVENTION

Combustion turbines, such as gas turbine engines, generally comprise a compressor section, a combustor section, a turbine section and an exhaust section. In operation, the compressor section can induct and compress ambient air. The combustor section generally may include a plurality of combustors for receiving the compressed air and mixing it with fuel to form a fuel/air mixture. The fuel/air mixture is combusted by each of the combustors to form a hot working gas that may be routed to the turbine section where it is expanded through alternating rows of stationary airfoils and rotating airfoils and used to generate power that can drive a rotor. The expanding gas exiting the turbine section can be exhausted from the engine via the exhaust section.

The fuel/air mixture at the individual combustors is controlled during operation of the engine to maintain one or more operating characteristics within a predetermined range, such as, for example, to maintain a desired efficiency and/or power output, control pollutant levels, prevent pressure oscillations and prevent flameouts. In a known type of control arrangement, a bulk turbine exhaust temperature may also be monitored as a parameter indicative of a condition in the combustor section. For example, a controller may monitor a measured turbine exhaust temperature relative to a reference temperature value, and a measured change in temperature may result in the controller changing the fuel/air ratio at the combustor section.

In a known temperature monitoring system for controlling combustion operations, temperature monitors, such as thermocouples, are located directly in the exhaust flow of the turbine. Such monitoring systems generally require locating thermocouples at different fixed axial locations along the exhaust flow, which may introduce uncertainties in relation to temperature calculations for controlling the engine as conditions affecting operation of the engine change, such as a varying load condition on the engine.

SUMMARY OF THE INVENTION

In accordance with an aspect of the invention, a method of operating a gas turbine engine may be provided including determining a temperature of a working gas passing through a flow path within the gas turbine engine. The method comprises transmitting acoustic signals from a plurality of acoustic transmitters located at a predetermined axial location adjacent to and downstream from a last stage of a turbine section of the gas turbine engine, and receiving the acoustic signals from the acoustic transmitters at a plurality of acoustic receivers located at the predetermined axial location. Each acoustic signal may comprise a distinct line-of-sound path from one of the acoustic transmitters to an acoustic receiver corresponding to the line-of-sound path. The method additionally includes determining a time-of-flight for the signals traveling along each of the line-of-sound paths, and processing the

2

time-of-flight for the signals traveling along the line-of-sound paths to determine a temperature in a region of the predetermined axial location.

In accordance with another aspect of the invention, a gas turbine engine may be provided including an apparatus for controlling operation of the gas turbine engine. The apparatus for controlling the gas turbine engine may comprise a plurality of acoustic transmitters located circumferentially on a boundary structure defining a flow path for a working gas passing through the gas turbine engine. The plurality of acoustic transmitters may be located at a predetermined axial location adjacent to and downstream from a turbine section of the gas turbine engine. A plurality of acoustic receivers may be located circumferentially around the boundary structure defining the flow path at the predetermined axial location. A plurality of line-of-sound paths may be defined by acoustic signals, each acoustic signal being transmitted from an acoustic transmitter and received by an acoustic receiver for a respective line-of-sound path. A controller may be configured to determine a time-of-flight for the acoustic signals traveling along each of the line-of-sound paths, and the controller may be configured to process a measured time-of-flight for the signals traveling along the line-of-sound paths to determine a local temperature in each of a plurality of locations located circumferentially around the flow path at the predetermined axial location.

BRIEF DESCRIPTION OF THE DRAWINGS

While the specification concludes with claims particularly pointing out and distinctly claiming the present invention, it is believed that the present invention will be better understood from the following description in conjunction with the accompanying Drawing Figures, in which like reference numerals identify like elements, and wherein:

FIG. 1 is a perspective cross-sectional view of a gas turbine engine illustrating implementation of an acoustic pyrometer system of the present invention;

FIG. 2 is a diagrammatic view of an embodiment of the acoustic pyrometer system of present invention;

FIG. 3 is an enlarged view of a portion of FIG. 2 illustrating exemplary line-of-sound paths;

FIG. 4 is a diagrammatic view illustrating exemplary isotherms that may define a temperature map determined by the acoustic pyrometer system of the present invention;

FIG. 5 is a diagrammatic view illustrating exemplary temperature regions that may be determined in accordance with a method of the present invention;

FIG. 6 is a diagrammatic view of an alternative embodiment of the acoustic pyrometer system of present invention;

FIG. 7 is an enlarged view of a portion of FIG. 6 illustrating exemplary line-of-sound paths; and

FIG. 8 is a flow diagram illustrating operation of the acoustic pyrometer system to control a gas turbine engine.

DETAILED DESCRIPTION OF THE INVENTION

In the following detailed description of the preferred embodiment, reference is made to the accompanying drawings that form a part hereof, and in which is shown by way of illustration, and not by way of limitation, a specific preferred embodiment in which the invention may be practiced. It is to be understood that other embodiments may be utilized and that changes may be made without departing from the spirit and scope of the present invention.

Referring to FIG. 1, embodiments of the invention are directed to an acoustic pyrometer system 10 that may be

incorporated in a gas turbine engine 12 and to methods of using the acoustic pyrometer system 10 to determine temperatures at predetermined locations in the engine 12 and to control an operation of the engine 12. Aspects of the invention will be explained in connection with various possible configurations, but the detailed description is intended only as exemplary.

As illustrated in FIG. 1, the turbine engine 12 generally includes a compressor section 14, a combustor section 16, a turbine section 18 and an exhaust section 20. The combustor section 16 may comprise a plurality of combustor baskets or combustors 22 and associated transition ducts 24 for conveying hot working gas to the turbine section 18. The exhaust section 20 may be configured as a diffuser 28, which can be a divergent duct formed between an outer shell 30, defining an outer boundary, and a hub structure 32, defining an inner boundary. The hot working gas is exhausted from the turbine section 18 through the exhaust section 20, i.e., between the outer shell 30 and the hub structure 32, to increase the pressure difference of the exhaust gas expanding across the last stage 34 of the turbine section 16.

The acoustic pyrometer system 10 may be located in an area of the exhaust section 20, adjacent to a rotating row of blades 36 of the last stage 34 of the turbine section 18. Specifically, the acoustic pyrometer system 10 may be located in a measurement plane extending generally perpendicular to a longitudinal axis 38 of the engine 12, i.e., perpendicular to a flow path 39 of the hot working gas, and positioned at a predetermined axial location defined by the line 2-2 in FIG. 1. In a preferred configuration, the acoustic pyrometer system 10 may be located relatively close to the last row of blades 36, and may be located, for example, approximately 3 inches downstream from the last row of blades 36. However, it should be understood that the particular axial location of the acoustic pyrometer system 10 may vary and may be selected depending on the particular design requirements of the engine 12.

A diagrammatic view of the acoustic pyrometer system 10 is illustrated in FIG. 2, taken at a cross-section of the engine 12 along line 2-2. The system 10 comprises a plurality of transmitters and receivers, illustrated herein as a plurality of transducers 40 (only one transducer 40 shown in FIG. 1), supported on the outer shell 30. In FIG. 2, eight transducers are shown and are designated as transducers 40A-H for the present description. However, it should be understood that, within the spirit and scope of the present invention, a greater number or fewer transducers 40 may be provided to perform a temperature sensing operation. For example, it may be desirable to provide a greater number of transducers to provide greater accuracy in mapping of temperatures within the flow path 39, as is described in greater detail below. Each of the transducers 40 includes a portion that may extend through the outer shell 30 to emit acoustic signals and to receive acoustic signals. The transducers 40 are connected to a control unit or controller 46 including a data acquisition and processing unit 48 that is configured to control the transducers 40 to produce predetermined output signals and to receive time-of-flight signals corresponding to the output signals (see FIG. 8). The data acquisition and processing unit 48 is further configured to store and process data corresponding to the received signals to calculate temperatures and to produce outputs in accordance with the calculated temperatures associated with the received signals. The controller 46 additionally comprises a combustion control unit 50 receiving signals from the data acquisition and processing unit 48 to output control signals for controlling operations affecting combus-

tion, including signals to the individual combustors 22, providing control of, for example, the fuel/air ratio at the combustors 22.

During a data acquisition operation, at least one of the transducers 40 may comprise a transmitting transducer 40 producing a signal that traverses the hot gas flow path 39 in the plane of the system 10, and at least one of the transducers 40 may comprise a receiving transducer 40, which may be a different transducer 40 or the same transducer 40 as the transmitting transducer 40. The time-of-flight of a signal traveling between the transmitting and the receiving transducers 40 may be used to determine an average temperature of the gas through which the signal has traveled. Specifically, the present invention uses the principle that the speed of sound in a gas changes as a function of temperature. For a determined or known composition of the gas, it is possible to determine the temperature of the gas based on the measured time for an acoustic or sound signal to travel the distance between the transmitting and receiving transducers 40, i.e., based on the speed of the sound signal traveling through the gas. The temperature, T ($^{\circ}$ C.), of the gas may be calculated using the equation:

$$T = \left(\frac{d}{B * t} \right)^2 - 273.16$$

where:

$$B = \text{acoustic constant} = \sqrt{\frac{\gamma * R}{M}}, \text{ (m/s)}$$

γ = ratio of specific heats of the gas

R = universal gas constant, 8.314 J/mole $^{\circ}$ K.

M = molecular weight of the gas (Kg/mole)

d = distance traveled by sound signal (m)

t = time-of-flight of the sound signal (s)

Referring to FIG. 3, exemplary line-of-sound paths for the transducers 40A-H will be described with reference to the transducers 40A, 40B and 40H. When the transducer 40A produces an acoustic signal, a plurality of line-of-sound paths 42 are defined within the flow path 39 defined between the outer shell 30 and the hub structure 32. A first line-of-sound path 42-1 extends radially inwardly toward the hub structure 32 and reflects off the hub structure 32 perpendicular to a first reflection point 44-1 on the surface of the hub structure 32. The first line-of-sound path 42-1 comprises a first path segment 42-1_a extending from the transducer 40A to the reflection point 44-1, and a second path segment 42-1_b extending from the reflection point 44-1 to the transducer 40A. A second line-of-sound path 42-2 extends at an angle toward the hub structure 32 in the direction of the transducer 40B, and reflects off the hub structure 32 at a second reflection point 44-2 in a direction toward the transducer 40B. The second line-of-sound path 42-2 comprises a first path segment 42-2_a extending from the transducer 40A to the reflection point 44-2, and a second path segment 42-2_b extending from the reflection point 44-2 to the transducer 40B. A third line-of-sound path 42-3 extends at an angle toward the hub structure 32 in the direction of the transducer 40H, and reflects off the hub structure 32 at a third reflection point 44-3 in a direction toward the transducer 40H. The third line-of-sound path 42-3 comprises a first path segment 42-3_a extending from the transducer 40A to the reflection point 44-3, and a second path segment 42-3_b extending from the reflection point 44-3 to the

5

transducer 40H. In addition, fourth and fifth line-of-sound paths 42-4 and 42-5, respectively, extend from the transducer 40A to the respective transducers 40C and 40G. The fourth and fifth line-of-sound paths 42-4 and 42-5 extend along a direct line-of-flight between the transducer 40A and the transducers 40C and 40G.

It should be understood that a plurality of line-of-sound paths 42 similar to those described for the transducer 40A may be associated with the other transducers 40B-H in the acoustic pyrometer system 10. Each of the plurality of line-of-sound paths 42 provides an average temperature measurement of the gas along the particular line-of-sound path 42. Hence, a plurality of average temperature measurements may be provided traversing across the annular space forming the flow path 39 at the exit to the turbine section 18.

Further, a plurality of intersections 42_i of the line-of-sound paths are defined by intersections of the reflected line-of-sound paths 42-1 through 42-3 with the direct line-of-flight line-of-sound paths 42-4 and 42-5, as well as intersections with the direct line-of-flight line-of-sound paths of adjacent transducers 40, e.g., intersections of the line-of-sound paths 42-1, 42-2 and 42-3 with a direct line-of-sound path 42-6 between transducers 40B and 40H. The data associated with each pair of intersecting line-of-sound paths 42 may be compared to each other to validate the temperature data corresponding to the pair of line-of-sound paths 42. In particular, the average temperature of each intersecting pair of line-of-sound paths 42 should be substantially the same, i.e., have a substantially similar temperature at the intersection 42_i, and a substantial variation in temperature between an intersecting pair of line-of-sound paths 42 may provide an indication that the data provided by at least one of the pair of intersecting line-of-sound paths 42 may be invalid.

Time-of-flight data corresponding to each of the plurality of line-of-sound paths 42 may be transmitted to the data acquisition and processing unit 48 to map the temperatures in the measurement plane of the acoustic pyrometer system 10, i.e., in the plane of line 2-2 in FIG. 1, wherein temperatures may be determined at a plurality of points within the radial and circumferential extent of the annular space at the exit of the turbine section 18. For example, a plurality of isotherms for temperatures in the flow path 39 may be mapped, as is illustrated by two exemplary isotherms 49A and 49B superposed on an outline of the flow path 39 in FIG. 4.

The time-of-flight data may be acquired from the transducers 40 sequentially in time. That is, the transducers 40 may each be activated at a different time to produce an output acoustic signal in order to enable identification of the signal source, i.e., the transmitting transducer 40, relative to the receiving transducers 40 that receive and provide time-of-flight data signals to the data acquisition and processing unit 48. Alternatively, two or more output signals may be transmitted from two or more of the transducers 40 simultaneously, such that there is little or no time difference between measurements provided by the different output signals at a plurality of locations in the flow path 39 to provide simultaneous temperature data from a plurality of the transducers 40. In particular, each of the transducers 40 may transmit an output signal at a different frequency than any other transducer 40. Hence, the source of each transmitted signal may have a distinctive frequency that may be identified by the data acquisition and processing unit 48 when the signals are received at the receiving transducers 40, such that each of the two or more output signals transmitted simultaneously may be uniquely identified by their frequency.

The acoustic pyrometer system 10 preferably may operate in a frequency range of from about 0.5 kHz to about 4 kHz.

6

The energy of acoustic signals is generally greater at lower frequencies, enabling the signals to travel a longer distance. Hence, it may be desirable to provide output signals having a lower frequency. Further, in a configuration in which the transducers 40 produce output signals at different frequencies, it may be preferable that the variation between output signal frequencies be small in order that all of the output signals may have a similar energy, for example, by providing an output signal frequency for each of the signals near the lower end of the frequency range.

As discussed above, each line-of-sound path, comprises a known distance between transmitting and receiving transducers 40. Hence, for a given data collection event comprising the collection of data from the receiving transducers 40 at a predetermined time, or within a predetermined time frame for sequential data produced by sequential output signals from the transducers 40, a plurality of temperature measurements may be provided traversing across different sections of the measurement plane. The data acquisition and processing unit 48 may process the plurality of temperature measurements by a cross-correlation technique to determine the temperature of the gas flow at different locations radially and circumferentially across the measurement plane.

In accordance with an aspect of the invention, the temperatures determined at the measurement plane of the acoustic pyrometer system 10 may be used to determine both a bulk exhaust temperature and to determine individual operating temperatures for each of the combustors 22 (FIG. 8). With regard to the bulk temperature measurement, the acoustic pyrometer system 10 determines average temperatures across multiple paths 42 that may be used to provide a true bulk average temperature at the measurement plane defined by the acoustic pyrometer system 10. In particular, the data acquisition and processing unit 48 may determine a bulk or global exhaust temperature across the flow path 39 that may be used by the controller 46 to control overall combustion operations, such as controlling a firing temperature in the combustion section 16.

The data acquisition and processing unit 48 may also determine temperatures at each of the combustors 22 to ensure proper operation of the individual combustors 22. For example, referring to FIG. 5, outer and inner temperature regions 52, 54, specifically identified as outer regions 52A-L and inner regions 54A-L, may be defined for use in identifying the temperature at circumferential and radial locations of regions in the measurement plane defined by the acoustic pyrometer system 10. The temperature for each region of the outer region 52A-L and inner region 54A-L may be an average temperature for the area covered by the particular region. The number of regions for each of the outer and inner regions 52A-L, 54A-L may correspond to the number of combustors 22, i.e., corresponding to twelve combustors 22 in the exemplary embodiment. Although the measurement plane of the acoustic pyrometer system 10 is displaced axially downstream of the individual combustors 22 and the turbine section 18, it is possible to infer the temperature at each individual combustor 22 based on the measurements at the measurement plane. That is, the temperature at each of the regions 52A-L and/or 54A-L may be used to determine the temperature at a combustor 22 wherein the regions 52A-L and/or 54A-L corresponding to a combustor 22 will typically be displaced circumferentially relative to the associated combustor 22 due to the rotational flow of the exhaust gases through the turbine section 18. The temperature of the combustors 22, as determined by the data acquisition and processing unit 48, may be used to determine an output of the combustion control unit 50 to control the fuel and/or air flow to

each of the respective combustors **22** to avoid flame-out of individual combustors **22**, as well as to provide combustor-to-combustor flame temperature variation information for feed back control for optimized, energy-efficient combustion. Hence, the temperature measurements provided by the transducers **40** may provide both a global temperature measurement and individual temperature measurements of the combustors **22** at a common axial location defined by the plane of the acoustic pyrometer system **10**.

As noted above, the particular location of the measurement plane may be selected based on the particular configuration and operation of the engine, and is preferably adjacent a last stage **34** of the turbine section **18**. In particular, the location of the measurement plane is preferably at an axial location in the exhaust section **20** where the working gas exiting the turbine section **18** has not substantially mixed within the exhaust section **20**. For example, the measurement plane may preferably be located at an upstream region of the exhaust section **20** prior to substantial expansion of the gases through the diffuser **28** of the exhaust section **20**, such that individual temperature measurements corresponding to the individual combustors **22** may be obtained. It may also be noted that obtaining the average temperature measurements corresponding to different portions of the flow path **39** traversed by the line-of-sound paths **42** further permits the location of the measurement plane to be used for determining a bulk temperature of the working gas as it exits the turbine section **18** and passes through the exhaust section **20**.

It should be understood that the spacial resolution of the temperature map provided by the transducers **40** may be increased by increasing the number of the transducers **40** around the circumference of the outer shell **30** at the measurement plane of the acoustic pyrometer system **10**. Further, it should be understood that although particular outer and inner regions **52**, **54** are described for designating temperatures within the measurement plane of the acoustic pyrometer system **10**, a different number of regions may be selected for identifying temperatures in both the radial and circumferential directions. Also, it should be understood that the regions, as used by the data acquisition and processing unit **48** for determining combustor temperatures, may comprise temperatures at point locations within the measurement plane, such as may be determined from the temperature map, as generally depicted by the isotherm map of FIG. 4. The locations of the temperature regions **52**, **54** or point locations may each correspond to a "hot spot" in the exhaust flow corresponding to the outlet temperature of exhaust from a predetermined one of the combustors **22**.

During operation of the engine **12**, the load on the engine **12** may change, such as in changing from a base load operation, i.e., a design operating point, of the engine **12** to a partial load operation of the engine **12**. As a result of a change in load on the engine **12**, the condition of the gas flow may vary, and the locations of the hot spots corresponding to each of the combustors **22** may change radially and/or circumferentially. In the past, temperature sensors, such as thermocouples have been mounted at fixed locations on thermocouple rakes in the exhaust section **20** of the turbine engine **12**, wherein the locations of the thermocouples were optimized for steady state base load operation of the engine. In accordance with an aspect of the present invention, the temperature measurement locations, i.e., the regions **52** and **54**, designated for providing temperatures corresponding to each of the combustors **22**, may be changed in real time to provide an optimum temperature measurement location for each load condition of the engine **12**, or for varying load conditions of the engine **12**. For example, as the load on the turbine engine **12** changes from a

base load to a partial load condition, the temperature monitoring locations may be adjusted or changed in the radial and/or circumferential directions within the annulus between the outer shell **30** and the hub structure **32** in the plane of the acoustic pyrometer system **10**. That is, a first set of temperature monitoring locations may be selected, corresponding to each of the combustors **22**, for a base load operation of the engine **12**, and a second, different set of temperature monitoring locations may be selected, corresponding to each of the combustors **22**, for a partial load operation of the engine **12**. Hence, the acoustic pyrometer system **10** may provide an increased accuracy of the temperature measurements used for controlling operation of the engine **12** throughout a range of varying operating conditions.

It should be noted that the distance along the line-of-sound paths **42** may vary slightly due thermal expansion and/or distortion of the outer shell **30**. In accordance with an aspect of the invention, a non-intrusive distance measuring device may be included in the acoustic pyrometer system **10** to provide distance-of-flight measurements (FIG. 8). For example, a laser triangulation, time-of-flight measurement may be provided by laser emitting devices and detectors built into the transducers **40**, as is depicted diagrammatically by an exemplary laser emitter **53** and receiver **55** in FIG. 2, and providing a measurement between each pair of transmitting and receiving transducers **40**. That is, a plurality of laser emitter and receivers, similar to the illustrated laser emitter **53** and receiver **55**, may be provided associated with a plurality of transducers **40**. The measurements from the distance measuring devices may be used to determine the thermal expansion and/or distortion of the outer shell **30**, and may be used by the data acquisition and processing unit **48** to correct for variations in distance of the line-of-sound paths **42**.

In accordance with a further aspect of the invention, one or more temperature sensors may be provided on the outer shell **30**, such as is illustrated by a thermocouple **56** associated with the transducer **40A** (FIG. 2). For example thermocouples **56** may be provided as part of or associated with each of the transducers **40** to provide a temperature measurement at the inner surface of the outer shell **30** at or adjacent to the measurement plane. The temperature measurement at the outer shell **30** may be provided to the controller **46** to adjust or correct the temperature measurements provided by the transducers **40** for a boundary layer temperature gradient at the wall of the outer shell **30** (FIG. 8).

In accordance with a further aspect of the invention, background noise at the measurement plane of the acoustic pyrometer system **10** may be detected by the transducers **40**. The background noise received by the transducers **40** may be input to the controller **46** (FIG. 8) and provided to the data acquisition and processing unit **48** and processed as a background noise level used to adjust a noise level attenuation for signals received by the transducers **40**. In particular, the noise level within the engine **12** will change, depending on the load condition of the engine **12**. The data acquisition unit **48** may monitor the noise level and adjust an attenuation threshold to filter the output signals from the transceivers **40** for the noise level, such as by increasing the threshold for attenuation as the noise level increases. Hence, the present acoustic pyrometer system **10** may provide an adjustable acoustic measurement that varies the sensing sensitivity with varying noise, so that the detection of the signals may be optimized to the extent possible with respect to the ambient sound, i.e., noise, in the combustion system.

Referring to FIG. 6, an alternative embodiment of the acoustic pyrometer system **10** is illustrated and identified as acoustic pyrometer system **110**. Elements of the acoustic

pyrometer system **110** corresponding to the acoustic pyrometer system **10** are identified with the same reference numeral increased by 100.

The acoustic pyrometer system **110** may be provided at the same location within the exhaust section **20** of a turbine engine **12** as is described for the acoustic pyrometer system **10** above. The acoustic pyrometer system **110** includes a plurality of transmitters and receivers, illustrated herein as a plurality of acoustic or sound emitting transmitters **162**, identified as transmitters **162A-H**, located on the outer shell **130**, and a plurality of receiving microphones **164**, identified as microphones **164A-P**, located on the hub structure **132**. It should be understood that the locations of the transmitters **162** and microphones **164** may be reversed, or transceivers may be provided in place of the transmitters **162** and microphones **164**.

The transmitters **162** and microphones **164** are connected to a control unit or controller **146** including a data acquisition and processing unit **148** that is configured to control the transmitters **162** to produce predetermined output signals and to receive time-of-flight signals from the microphones **164** corresponding to the output signals. The data acquisition and processing unit **148** further stores and processes data corresponding to the received signals to produce outputs in accordance with calculated temperatures associated with the received signals. The controller **146** additionally comprises a combustion control unit **150** receiving signals from the data acquisition and processing unit **148** to output control signals for controlling operations affecting combustion in a manner similar to that described above for the data acquisition and processing system **10**.

Referring to FIG. 7, exemplary line-of-sound paths for the output signals provided by the transmitter **162A** will be described. When the transmitter **162A** produces an acoustic signal, a plurality of line-of-sound paths **142** are defined within a flow path **139** defined between the outer shell **130** and the hub structure **132**. A first line-of-sound path **142-1** extends radially inwardly toward the microphone **164A**. A second line-of-sound path **142-2** extends radially inwardly toward the microphone **164B**. A third line-of-sound path **142-3** extends radially inwardly toward the microphone **164C**. A fourth line-of-sound path **142-4** extends radially inwardly toward the microphone **164P**. A fifth line-of-sound path **142-5** extends radially inwardly toward the microphone **164N**.

It should be understood that a plurality of line-of-sound paths **142** similar to those described for the transmitter **162A** may be associated with the other transmitters **162B-P**. Further, the line-of-sound paths **142** of each transmitter **162** intersect line-of-sound paths **142** of the adjacent transmitters **162**, such that verification of the data associated with pairs of intersecting line-of-sound paths **142** may be performed, as described above for the acoustic pyrometer system **10**. The microphones **164** receiving acoustic signals from the transmitters **162** provide output signals to the data acquisition and processing unit **148** which determines time-of-flight data for each line-of-sound path **142**, to provide an average temperature measurement of the gas along each line-of-sound path **142**. Hence, the time-of-flight data of the transmitters **162** and microphones **164** may be used to determine a temperature map of the plane defined by the acoustic pyrometer system **110** to control operation of the turbine engine in a manner similar to that described for the acoustic pyrometer system **10**. The plural direct line-of-sound paths **140** provided by the acoustic pyrometer system **110** may provide a reduction in an uncertainty of the data provided to the data acquisition and processing unit **148** in that the acoustic signals providing the

data of the system **110** do not reflect off structure within the exhaust section **20**. That is, the acoustic pyrometer system **110** may provide additional accuracy to the data by providing shorter path lengths with each line-of-sound path **142** providing a direct line-of-flight between the signal transmitter **162** and microphone (receiver) **164**.

The acoustic pyrometer system **10**, **110** of the present invention provides a combined temperature measurement function that permits elimination of a sensor location typically provided for sensing an exhaust temperature in a turbine engine. In particular, the present invention provides temperature measurements comprising individual combustor temperature measurements and a bulk or global exhaust temperature measurement in a common measurement plane downstream from the turbine section **18**. The present system may be used to replace existing exhaust temperature measurement systems, such as both blade path thermocouple rakes at the exit to the turbine section and bulk exhaust temperature thermocouple rakes located downstream in the exhaust section that may be provided in a typical turbine exhaust temperature sensing system.

Further, the acoustic pyrometer system **10**, **110** provides a configuration in which the temperature measurement elements, e.g., the transceivers **40** or the transmitters **162** and receivers **164**, are located out the path **39**, **139** of the hot gas flow. In addition, mounting of the transceivers **40** or transmitters **162** to the outer shell **32**, **132** may permit replacement of these components without stopping operation of the turbine engine **12**, reducing inefficiencies associated with maintenance of the temperature sensor system for the engine **12**.

While particular embodiments of the present invention have been illustrated and described, it would be obvious to those skilled in the art that various other changes and modifications can be made without departing from the spirit and scope of the invention. It is therefore intended to cover in the appended claims all such changes and modifications that are within the scope of this invention.

What is claimed is:

1. A method operating a gas turbine engine, including determining a temperature of a working gas passing through a flow path within the gas turbine engine, the method comprising the steps of:

transmitting acoustic signals from a plurality of acoustic transmitters located at a predetermined axial location adjacent to and downstream from a last stage of a turbine section of the gas turbine engine;

receiving the acoustic signals from the acoustic transmitters at a plurality of acoustic receivers located at the predetermined axial location;

each acoustic signal comprising a distinct line-of-sound path from one of the acoustic transmitters to an acoustic receiver corresponding to the line-of-sound path;

determining, using a processor, a time-of-flight for the signals traveling along each of the line-of-sound paths; and

processing, via a processor, the time-of-flight for the signals traveling along the line-of-sound paths to determine a temperature in a region of the predetermined axial location.

2. The method of claim 1, including transmitting acoustic signals for determining the time-of-flight along the line-of-sound paths at a predetermined time interval between a time of transmission of each of the acoustic signals.

3. The method of claim 1, including at least one of the acoustic transmitters transmitting at least one of the acoustic signals at a frequency that is different from the frequencies of the other acoustic signals, and wherein the at least one acous-

11

tic signal is transmitted simultaneously with at least one other acoustic signal of a different frequency transmitted from another acoustic transmitter.

4. The method of claim 1, wherein the plurality of acoustic transmitters are distributed around an outer boundary of the flow path, and including processing the time-of-flight for each of the acoustic signals to determine a plurality of local temperatures for the working gas in a corresponding plurality of regions distributed in a plane extending across the flow path at the predetermined axial location.

5. The method of claim 4, wherein the plurality of regions are distributed circumferentially around an axis of the gas turbine engine extending parallel to the flow path.

6. The method of claim 5, wherein the plurality of regions are further distributed radially between the outer boundary of the flow path and the axis of the gas turbine engine.

7. The method of claim 5, including the steps of:
 matching each of the regions circumferentially with a corresponding one of a plurality of combustors of the turbine engine; and
 controlling a fuel/air mixture of each of the combustors with reference to the local temperature at a corresponding region.

8. The method of claim 4, wherein the plurality of regions distributed in the plane extending across the flow path comprise a first set of point temperature measurements within the flow path, and including a second set of point temperature measurements located at different locations within the flow path than locations of the first set of point temperature measurements, and including the steps of:

monitoring the temperatures in the flow path at the first set of point temperature measurements and controlling an operating parameter of the gas turbine engine based on the temperatures at the first set of point temperature measurements during a first operating condition of the gas turbine engine; and

monitoring the temperatures in the flow path at the second set of point temperature measurements and controlling the operating parameter of the gas turbine engine based on the temperatures at the second set of point temperature measurements during a second operating condition of the gas turbine engine different from the first operating condition.

9. The method of claim 8, wherein the first operating condition of the gas turbine engine comprises a base load operation of the gas turbine engine, and the second operation condition of the gas turbine engine comprises a partial load operation of the gas turbine engine.

10. The method of claim 4, further including processing the time-of-flight for each of the acoustic signals to determine a bulk temperature comprising an average temperature for the working gas at the plane extending across the flow path at the predetermined axial location.

11. The method of claim 4, wherein each acoustic transmitter and acoustic receiver defines a transceiver, and the transceivers are circumferentially spaced around the outer boundary of the flow path, and including an inner boundary located radially inwardly from an outer boundary, and at least some of the line-of-sound paths comprise first and second path segments, the first path segment extending from a transmitting transceiver to the inner boundary and the second path segment extending from the inner boundary to a receiving transceiver.

12. The method of claim 1, including providing a distance measuring device and determining a distance measurement from at least one of the acoustic transmitters to at least one of the acoustic receivers, and correcting the determination of the

12

temperature in the region of the predetermined axial location where the at least two line-of-sound paths intersect with reference to the distance measurement.

13. The method of claim 1, including measuring a background noise level at the predetermined axial location and adjusting an attenuation level for filtering the acoustic signals received by the acoustic receivers with reference to the background noise level during processing of the time-of-flight signals to determine the temperature in the region of the predetermined axial location where the at least two line-of-sound paths intersect.

14. The method of claim 1, including obtaining a wall temperature measurement at the predetermined axial location, and inputting the wall temperature measurement to provide a boundary layer temperature gradient during processing of the time-of-flight signals to determine the temperature in the region of the predetermined axial location where the at least two line-of-sound paths intersect.

15. The method of claim 1, wherein at least two of the line-of-sound paths intersect within the flow path, and comparing the temperatures determined for each of the at least two line-of-sound paths to verify an accuracy of the temperature provided by each of the at least two line-of-sound paths.

16. A gas turbine engine including an apparatus for controlling operation of the gas turbine engine comprising:

a plurality of acoustic transmitters located circumferentially on a boundary structure defining a flow path for a working gas passing through the gas turbine engine, the plurality of acoustic transmitters located at a predetermined axial location adjacent to and downstream from a turbine section of the gas turbine engine;

a plurality of acoustic receivers located circumferentially around the boundary structure defining the flow path at the predetermined axial location;

a plurality of line-of-sound paths defined by acoustic signals, each acoustic signal transmitted from an acoustic transmitter and received by an acoustic receiver for a respective line-of-sound path; and

a controller configured to determine a time-of-flight for the acoustic signals traveling along each of the line-of-sound paths, and the controller being configured to process a measured time-of-flight for the signals traveling along the line-of-sound paths to determine a local temperature in each of a plurality of locations located circumferentially around the flow path at the predetermined axial location.

17. The gas turbine engine of claim 16, wherein the gas turbine engine comprises a combustion section, and the controller being configured to calculate a bulk exhaust gas temperature of the working gas at the predetermined axial location, the bulk temperature comprising an average of the temperatures at the plurality of locations, and the controller being configured to control a firing temperature in the combustion section with reference to the bulk temperature.

18. The gas turbine engine of claim 16, wherein each acoustic transmitter and acoustic receiver defines a transceiver, and the transceivers are circumferentially spaced around a circumferentially outer boundary of the boundary structure.

19. The gas turbine engine of claim 18, wherein the boundary structure comprises an inner boundary and at least some of the line-of-sound paths comprise first and second path segments, the first path segment extending from a transmitting transceiver to the inner boundary and the second path segment extending from the diffuser to a receiving transceiver.

20. The gas turbine engine of claim 16, wherein the boundary structure comprises an inner boundary located radially inwardly from an outer boundary of the boundary structure, and one of the acoustic transmitters and the acoustic receivers being located on one of the inner boundary and the outer boundary, and the other of the acoustic transmitters and the acoustic receivers being located on the other of the inner boundary and the outer boundary. 5

* * * * *