



US008575639B2

(12) **United States Patent**
Hussell

(10) **Patent No.:** **US 8,575,639 B2**
(45) **Date of Patent:** **Nov. 5, 2013**

(54) **LIGHT EMITTING DEVICES FOR LIGHT EMITTING DIODES (LEDS)**

(75) Inventor: **Christopher P. Hussell**, Cary, NC (US)

(73) Assignee: **Cree, Inc.**, Durham, NC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/435,912**

(22) Filed: **Mar. 30, 2012**

(65) **Prior Publication Data**

US 2012/0299022 A1 Nov. 29, 2012

Related U.S. Application Data

(63) Continuation-in-part of application No. 13/028,972, filed on Feb. 16, 2011, and a continuation-in-part of application No. 13/104,558, filed on May 10, 2011.

(51) **Int. Cl.**
H01L 33/00 (2010.01)

(52) **U.S. Cl.**
USPC **257/98**; 257/89; 257/99; 257/100;
257/E21.592

(58) **Field of Classification Search**
USPC 257/12-13, 98-99, 103, 431-433,
257/E21.592, E31.117; 438/22, 27-28,
438/48-52

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,946,547 A 8/1990 Palmour
5,200,022 A 4/1993 Kong
RE34,861 E 2/1995 Davis et al.

6,548,832 B1 4/2003 Sakamoto et al.
7,224,000 B2 5/2007 Aanegola et al.
D570,797 S 6/2008 Song
7,391,046 B2* 6/2008 Tsutsumi et al. 257/13
D573,553 S 7/2008 Uemoto et al.
D576,576 S 9/2008 Shida et al.
7,482,636 B2 1/2009 Murayama et al.
D589,470 S 3/2009 Chen
D591,248 S 4/2009 Imai et al.
D593,043 S 5/2009 Song
D602,451 S 10/2009 Gielen
D603,813 S 11/2009 Nishimura et al.
D607,420 S 1/2010 Imai et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN ZL 2011-30139847.5 8/2012
CN ZL 2011-30166527.9 8/2012

(Continued)

OTHER PUBLICATIONS

Taiwanese Search Report for Application No. 101302309 dated Jan. 14, 2013.

(Continued)



Primary Examiner — **Dung A. Le**

(74) *Attorney, Agent, or Firm* — **Jenkins, Wilson, Taylor & Hunt, P.A.**

(57) **ABSTRACT**

Light emitting devices for light emitting diodes (LEDs) are disclosed. In one embodiment a light emitting device can include a submount and a light emission area disposed over the submount. The light emission area can include one or more light emitting diodes (LEDs), a fillet at least partially disposed about the one or more the LEDs, and filling material. The filling material can be disposed over a portion of the one or more LEDs and a portion of the fillet.

52 Claims, 19 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

7,649,209 B2 1/2010 Hussell et al.
 D615,052 S 5/2010 Imai et al.
 D618,635 S 6/2010 Imai et al.
 7,825,578 B2 11/2010 Takashima et al.
 7,872,418 B2 1/2011 Hata et al.
 D637,564 S 5/2011 Tseng et al.
 7,994,518 B2 8/2011 Wang et al.
 D645,417 S 9/2011 Imai et al.
 8,044,418 B2 10/2011 Loh et al.
 8,058,088 B2 11/2011 Cannon
 D650,760 S 12/2011 Hussell et al.
 D667,803 S 9/2012 Hussell et al.
 D676,000 S 2/2013 Hussell et al.
 D676,395 S 2/2013 Hussell et al.
 2006/0147746 A1* 7/2006 Wakako et al. 428/627
 2006/0186418 A1 8/2006 Edmond
 2007/0018295 A1 1/2007 Kim et al.
 2007/0029569 A1 2/2007 Andrews
 2007/0158668 A1 7/2007 Tarsa
 2008/0054279 A1 3/2008 Hussell et al.
 2008/0054284 A1 3/2008 Hussell et al.
 2008/0054286 A1 3/2008 Loh et al.
 2008/0089072 A1 4/2008 Kim et al.
 2008/0173884 A1 7/2008 Chitnis
 2008/0179611 A1 7/2008 Chitnis
 2008/0224166 A1 9/2008 Glovatsky et al.
 2008/0258130 A1 10/2008 Bergmann
 2009/0261374 A1 10/2009 Hayashi
 2009/0289169 A1 11/2009 Yang et al.
 2009/0315061 A1 12/2009 Andrews
 2010/0078664 A1 4/2010 Helbing
 2010/0141182 A1 6/2010 Shi
 2010/0155763 A1 6/2010 Donofrio
 2010/0193822 A1* 8/2010 Inobe et al. 257/98
 2010/0253248 A1 10/2010 Shi
 2010/0270567 A1 10/2010 Emerson et al.
 2010/0320483 A1 12/2010 Kadotani et al.
 2011/0068674 A1 3/2011 Takenaka et al.
 2011/0128730 A1 6/2011 Chiu
 2011/0291151 A1 12/2011 Matsuda et al.
 2012/0126255 A1 5/2012 Hussell et al.
 2012/0126257 A1 5/2012 Reiherzer et al.
 2012/0193651 A1 8/2012 Edmond
 2012/0205689 A1 8/2012 Welch
 2012/0299022 A1 11/2012 Hussell
 2012/0313135 A1* 12/2012 Kashitani et al. 257/99

FOREIGN PATENT DOCUMENTS

CN ZL201230099913.5 11/2012
 CN ZL20123009998.1 12/2012
 CN ZL201230099954.4 12/2012
 CN ZL 201230472866.4 5/2013
 EP 2327930 6/2011
 JP 07-038940 9/1995
 JP 10-311937 11/1998
 JP 2001-294083 10/2001
 JP 2005-266117 9/2005
 JP 2006-294898 10/2006
 JP 2007-227680 9/2007
 JP 2007-266357 10/2007
 JP 2007-323857 12/2007
 JP 2007-335371 12/2007
 JP 2009-044055 2/2009
 JP 2009-289918 12/2009
 JP 2010-009972 1/2010
 KR 10-0793338 1/2008
 KR 10-2008-0092239 10/2008
 KR 10-2009-0011121 3/2009
 KR 10-2011-0004632 1/2011
 TW 113260 10/2006
 TW 124444 8/2008
 TW 128526 5/2009
 WO WO 2012/071136 5/2012

WO WO 2012/071138 5/2012
 WO WO 2012/071139 5/2012
 WO WO 2013/032737 3/2013
 WO WO 2013/070696 5/2013
 WO WO 2013/096431 6/2013

OTHER PUBLICATIONS

Taiwanese Office Action for Application No. 101302309 dated Jan. 23, 2013.
 Chinese Decision to Grant for Application No. 201230472866.4 dated Jan. 24, 2013.
 Notice of Allowance for U.S. Appl. No. 13/336,540 dated Jan. 31, 2013.
 Restriction Requirement for U.S. Appl. No. 13/671,089 dated Feb. 7, 2013.
 Restriction Requirement for U.S. Appl. No. 29/404,913 dated Feb. 15, 2013.
 Japanese Office Action for Application No. 2012-023963 dated Feb. 26, 2013.
 Japanese Office Action for Application No. 2012-026117 dated Feb. 26, 2013.
 Chinese Office Action for Application No. CN 2012/30130915.6 dated Feb. 27, 2013.
 Notice of Allowance for U.S. Appl. No. 13/028,972 dated Feb. 28, 2013.
 International Search Report and Written Opinion for Application No. PCT/US2012/051344 dated Feb. 28, 2013.
 International Search Report and Written Opinion for Application No. PCT/US2012/063861 dated Mar. 18, 2013.
 Non-Final Office Action for U.S. Appl. No. 13/671,089 dated Mar. 29, 2013.
 International Search Report and Written Opinion for Application No. PCT/US2012/070589 dated Apr. 22, 2013.
 Bridgelux Product Data Sheet—1 page.
 Citizen Co. Product Data Sheet—4 pages http://ce.citizen.co.jp/lighting_led/en/products/index.html.
 U.S. Appl. No. 29/379,636 for “Light Emitting Device Package” filed Nov. 22, 2010.
 Design U.S. Appl. No. 29/380,387 for “Light Emitting Device Package” filed Dec. 3, 2010.
 U.S. Appl. No. 13/028,972 for “Light Emitting Devices and Methods” filed Feb. 16, 2011.
 U.S. Appl. No. 13/104,558 for “Light Emitting Devices and Methods” filed May 10, 2011.
 Notice of Allowance for U.S. Appl. No. 29/379,636 dated Aug. 4, 2011.
 Design U.S. Appl. No. 29/404,913 for “Light Emitting Device Component” filed Oct. 26, 2011.
 U.S. Appl. No. 13/224,850 for “Light Emitting Device Component” filed Sep. 2, 2011.
 Design U.S. Appl. No. 29/379,636 for “Light Emitting Device Package” filed Nov. 22, 2011.
 Design U.S. Appl. No. 29/408,955 for “Light Emitting Device Package” filed Dec. 19, 2011.
 U.S. Appl. No. 13/336,540 dated Dec. 23, 2011.
 Notification of Granting Patent Right for Design for Application Serial No. CN 2011/30166527.9 dated Apr. 6, 2012.
 Non-Final Office Action for U.S. Appl. No. 29/380,387 dated Apr. 25, 2012.
 Notification of Granting Patent Right for Design for Application Serial No. CN 2011/30139847.5 dated Apr. 26, 2012.
 Notice of Allowance for U.S. Appl. No. 29/408,955 dated May 7, 2012.
 Notice of Allowance for U.S. Appl. No. 29/407,084 dated May 18, 2012.
 International Search Report and Written Opinion for Application Serial No. PCT/US2011/058603 dated May 23, 2012.
 International Search Report and Written Opinion for Application Serial No. PCT/US2011/058601 dated May 24, 2012.
 International Search Report and Written Opinion for Application Serial No. PCT/US2011/058596 dated Jun. 18, 2012.

(56)

References Cited

OTHER PUBLICATIONS

Chinese Office Action for Application Serial No. CN 2012/30130915.6 dated Jul. 12, 2012.
Office Action/Restriction Requirement for U.S. Appl. No. 13/028,972 dated Jul. 25, 2012.
Notification of Grant for Chinese Patent Application No. 2012/30099913.5 dated Aug. 7, 2012.
Notification of Grant for Chinese Patent Application No. 2012/30099981.1 dated Aug. 17, 2012.
Notification of Grant for Chinese Patent Application No. 2012/30099954.4 dated Aug. 17, 2012.
Notice of Allowance for U.S. Appl. No. 29/407,084 dated Aug. 21, 2012.
Notice of Allowance for U.S. Appl. No. 29/380,387 dated Sep. 18, 2012.
Notice of Allowance for U.S. Appl. No. 29/408,955 dated Oct. 4, 2012.
Non-Final Office Action for U.S. Appl. No. 13/028,972 dated Oct. 10, 2012.
Chinese Office Action for Application No. CN 2012/30130915.6 dated Oct. 24, 2012.

Chinese Office Action for Application No. 201230472866.4 dated Nov. 14, 2012.
Non-Final Office Action for U.S. Appl. No. 13/104,558 dated Jan. 3, 2013.
International Search Report and Written Opinion for Application No. PCT/US2013/025307 dated May 15, 2013.
Japanese Office Action for Application No. 2012-031549 dated Jun. 4, 2013.
Japanese Decision of Registration for Application No. 2012-023963 dated Jun. 4, 2013.
Japanese Decision of Registration for Application No. 2012-026117 dated Jun. 4, 2013.
Taiwanese Notice of Allowance for Application No. 101302309 dated Jun. 5, 2013.
Chinese Notice of Grant for Application No. 201230652790.3 dated Jun. 26, 2013.
Chinese Notice of Grant for Application No. 201230130915.6 dated Jul. 3, 2013.
Chinese Decision to Grant for Application No. 201230652789 dated Jul. 17, 2013.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13A




FIG. 13B




FIG. 14A




FIG. 14B




FIG. 15A







FIG. 15B






FIG. 19

1

LIGHT EMITTING DEVICES FOR LIGHT EMITTING DIODES (LEDS)

CROSS REFERENCE TO RELATED APPLICATIONS

This application relates and is a continuation-in-part of and claims priority to each of U.S. patent application Ser. No. 13/028,972, filed Feb. 16, 2011; and U.S. patent application Ser. No. 13/104,558, filed May 10, 2011. The disclosures of each of the related applications referenced herein are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

The subject matter disclosed herein relates generally to light emitting devices and methods. More particularly, the subject matter disclosed herein relates to light emitting devices and methods having increased brightness via increased reflectivity and more uniform encapsulant.

BACKGROUND

Light emitting diode (LED) chips, or LEDs, may be utilized in packages for providing white light (e.g., perceived as being white or near-white), and are developing as replacements for incandescent, fluorescent, and metal halide high-intensity discharge (HID) light products. A representative example of an LED device comprises a device having at least one LED chip, a portion of which can be coated with a phosphor such as, for example, yttrium aluminum garnet (YAG). The phosphor coating can convert light emitted from one or more LED chips into white light. For example, LED chips can emit light having desired wavelengths, and phosphor can in turn emit yellow fluorescence with a peak wavelength of about 550 nm. A viewer perceives the mixture of light emissions as white light. As an alternative to phosphor converted white light, light emitting devices of red, green, and blue (RGB) wavelengths can be combined in one device or package to produce light that is perceived as white.

Despite availability of various light emitting devices and methods in the marketplace, a need remains for brighter devices. In one aspect, brighter devices can be achieved by reducing the occurrence of defects during encapsulation of the devices. Light emitting devices and methods described herein can advantageously enhance light output performance while promoting ease of manufacture.

SUMMARY

In accordance with this disclosure, novel light emitting devices and methods are provided that are well suited for a variety of applications, including industrial and commercial lighting products. It is, therefore, an object of the present disclosure herein to provide improved and brighter light emitting devices, in part by increasing reflectivity within the device. Another object of the present disclosure is to reduce the occurrence of light affecting defects within the device, and to provide more uniform encapsulant.

These and other objects of the present disclosure as can become apparent from the disclosure herein are achieved, at least in whole or in part, by the subject matter disclosed herein.

BRIEF DESCRIPTION OF THE DRAWINGS

A full and enabling disclosure of the present subject matter including the best mode thereof to one of ordinary skill in the

2

art is set forth more particularly in the remainder of the specification, including reference to the accompanying figures, in which:

FIG. 1 is a top perspective view of an embodiment of a light emitting device according to the disclosure herein;

FIG. 2 is a side view of an embodiment of a light emitting device according to the disclosure herein;

FIGS. 3A and 3B are top views of an embodiment of a light emitting device having one or more patterns of light emitting diodes (LEDs) according to the disclosure herein;

FIG. 4 is a top perspective view of an embodiment of a light emitting device having one or more patterns of LEDs according to the disclosure herein;

FIG. 5 is a top view of an embodiment of a light emitting device according to the disclosure herein;

FIG. 6 is a first cross-sectional view of a light emission area of a light emitting device according to the disclosure herein;

FIG. 7 is a second cross-sectional view of a light emission area of a light emitting device according to the disclosure herein;

FIG. 8 is a top view of a light emitting device according to the disclosure herein;

FIG. 9 is a cross-sectional view of a gap area of a light emitting device according to the disclosure herein;

FIG. 10 is a top view of a light emitting device according to the disclosure herein;

FIGS. 11 to 14B are top views of embodiments of a light emitting device having one or more patterns of LEDs according to the disclosure herein;

FIGS. 15A and 15B are views of die attach techniques used for LED devices according to the disclosure herein;

FIGS. 16 to 18 are cross-sectional views of light emitting devices according to the disclosure herein; and

FIG. 19 is a top view of a light emitting device according to the disclosure herein.

DETAILED DESCRIPTION

Reference will now be made in detail to possible aspects or embodiments of the subject matter herein, one or more examples of which are shown in the figures. Each example is provided to explain the subject matter and not as a limitation. In fact, features illustrated or described as part of one embodiment can be used in another embodiment to yield still a further embodiment. It is intended that the subject matter disclosed and envisioned herein covers such modifications and variations.

As illustrated in the various figures, some sizes of structures or portions are exaggerated relative to other structures or portions for illustrative purposes and, thus, are provided to illustrate the general structures of the present subject matter. Furthermore, various aspects of the present subject matter are described with reference to a structure or a portion being formed on other structures, portions, or both. As will be appreciated by those of skill in the art, references to a structure being formed “on” or “above” another structure or portion contemplates that additional structure, portion, or both may intervene. References to a structure or a portion being formed “on” another structure or portion without an intervening structure or portion are described herein as being formed “directly on” the structure or portion. Similarly, it will be understood that when an element is referred to as being “connected”, “attached”, or “coupled” to another element, it can be directly connected, attached, or coupled to the other element, or intervening elements may be present. In contrast, when an element is referred to as being “directly connected”,

“directly attached”, or “directly coupled” to another element, no intervening elements are present.

Furthermore, relative terms such as “on”, “above”, “upper”, “top”, “lower”, or “bottom” are used herein to describe one structure’s or portion’s relationship to another structure or portion as illustrated in the figures. It will be understood that relative terms such as “on”, “above”, “upper”, “top”, “lower” or “bottom” are intended to encompass different orientations of the device in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, structure or portion described as “above” other structures or portions would now be oriented “below” the other structures or portions. Likewise, if devices in the figures are rotated along an axis, structure or portion described as “above”, other structures or portions would now be oriented “next to” or “left of” the other structures or portions. Like numbers refer to like elements throughout.

Light emitting devices according to embodiments described herein can comprise group III-V nitride (e.g., gallium nitride) based light emitting diodes (LEDs) or lasers fabricated on a growth substrate, for example, a silicon carbide substrate, such as those devices manufactured and sold by Cree, Inc. of Durham, N.C. For example, Silicon carbide (SiC) substrates/layers discussed herein can be 4H polytype silicon carbide substrates/layers. Other silicon carbide candidate polytypes, such as 3C, 6H, and 15R polytypes, however, can be used. Appropriate SiC substrates are available from Cree, Inc., of Durham, N.C., the assignee of the present subject matter, and the methods for producing such substrates are set forth in the scientific literature as well as in a number of commonly assigned U.S. patents, including but not limited to U.S. Pat. No. Re. 34,861; U.S. Pat. No. 4,946,547; and U.S. Pat. No. 5,200,022, the disclosures of which are incorporated by reference herein in their entireties. Any other suitable growth substrates are contemplated herein. For example, sapphire and gallium arsenide can be utilized as growth substrates for fabricating LEDs or lasers as described herein.

As used herein, the term “Group III nitride” refers to those semiconducting compounds formed between nitrogen and one or more elements in Group III of the periodic table, usually aluminum (Al), gallium (Ga), and indium (In). The term also refers to binary, ternary, and quaternary compounds such as GaN, AlGa_N and AlInGa_N. The Group III elements can combine with nitrogen to form binary (e.g., GaN), ternary (e.g., AlGa_N), and quaternary (e.g., AlInGa_N) compounds. These compounds may have empirical formulas in which one mole of nitrogen is combined with a total of one mole of the Group III elements. Accordingly, formulas such as Al_xGa_{1-x}N where 1>x>0 are often used to describe these compounds. Techniques for epitaxial growth of Group III nitrides have become reasonably well developed and reported in the appropriate scientific literature.

Although various embodiments of LEDs disclosed herein comprise a growth substrate, it will be understood by those skilled in the art that the crystalline epitaxial growth substrate on which the epitaxial layers comprising an LED are grown can be removed, and the freestanding epitaxial layers can be mounted on a substitute carrier substrate or substrate which can have different thermal, electrical, structural and/or optical characteristics than the original substrate. The subject matter described herein is not limited to structures having crystalline epitaxial growth substrates and can be used in connection with structures in which the epitaxial layers have been removed from their original growth substrates and bonded to substitute carrier substrates.

Group III nitride based LEDs according to some embodiments of the present subject matter, for example, can be

fabricated on growth substrates (such as a silicon carbide substrates) to provide horizontal devices (with both electrical contacts on a same side of the LED) or vertical devices (with electrical contacts on opposite sides of the LED). Moreover, the growth substrate can be maintained on the LED after fabrication or removed (e.g., by etching, grinding, polishing, etc.). The growth substrate can be removed, for example, to reduce a thickness of the resulting LED and/or to reduce a forward voltage through a vertical LED. A horizontal device (with or without the growth substrate), for example, can be flip chip bonded (e.g., using solder) to a carrier substrate or printed circuit board (PCB), or wire bonded. A vertical device (with or without the growth substrate) can have a first terminal solder bonded to a carrier substrate, mounting pad, or PCB and a second terminal wire bonded to the carrier substrate, electrical element, or PCB. Examples of vertical and horizontal LED chip structures are discussed by way of example in U.S. Publication No. 2008/0258130 to Bergmann et al. and in U.S. Publication No. 2006/0186418 to Edmond et al., the disclosures of which are hereby incorporated by reference herein in their entireties.

As described further, one or more LEDs can be coated, at least partially, with one or more phosphors with the phosphors absorbing at least a portion of the LED light and emitting a different wavelength of light such that the LED emits a combination of light from the LED and the phosphor. In one embodiment, the LED emits a white light which is a combination of light emission from the LED chip and phosphor. One or more LEDs can be coated and fabricated using many different methods, with one suitable method being described in U.S. patent application Ser. Nos. 11/656,759 and 11/899,790, both entitled “Wafer Level Phosphor Coating Method and Devices Fabricated Utilizing Method”, and both of which are incorporated herein by reference in their entireties. Other suitable methods for coating one or more LEDs are described in U.S. patent application Ser. No. 12/014,404 entitled “Phosphor Coating Systems and Methods for Light Emitting Structures and Packaged Light Emitting Diodes Including Phosphor Coating” and the continuation-in-part application U.S. patent application Ser. No. 12/717,048 entitled “Systems and Methods for Application of Optical Materials to Optical Elements”, the disclosures of which are hereby incorporated by reference herein in their entireties. LEDs can also be coated using other methods such electrophoretic deposition (EPD), with a suitable EPD method described in U.S. patent application Ser. No. 11/473,089 entitled “Close Loop Electrophoretic Deposition of Semiconductor Devices”, which is also incorporated herein by reference in its entirety. It is understood that LED devices, systems, and methods according to the present subject matter can also have multiple LEDs of different colors, one or more of which can be white emitting.

Referring now to FIGS. 1 to 15B, FIG. 1 illustrates a top view of a light emitting or LED device, generally designated 10. LED device 10 can comprise a submount 12 for supporting one or more LEDs. In one aspect, an emission area, generally designated 16, can be disposed over submount 12. In one aspect, emission area 16 can be disposed substantially centrally with respect to LED device 10. In the alternative, emission area 16 can be disposed in any location over LED device 10, for example, in a corner or adjacent an edge. In one aspect, emission area 16 can comprise a substantially circular shape. In other aspects, emission area 16 can comprise any other suitable shape, for example, a substantially square, oval, or rectangle shape. LED device 10 can comprise a single emission area 16 or more than one emission area 16. Notably, LED device 10 can comprise a uniform optical source in the

5

form of emission area which can simplify the manufacturing process for manufacturers of light products requiring a single component. LED device **10** can further comprise a retention material **14** disposed at least partially about emission area **16** where retention material **14** can be referred to as a dam. Retention material **14** can also be disposed over at least one electrostatic discharge (ESD) protection device, such as a Zener diode **44** (FIG. **9**). In some aspects, retention material can be disposed over two Zener diodes **44** connected in series between two electrical elements (FIG. **8**).

Submount **12** can comprise any suitable mounting submount or substrate, for example, a printed circuit board (PCB), a metal core printed circuit board (MCPCB), an external circuit, or any other suitable submount or substrate over which lighting devices such as LEDs can mount and/or attach. Emission area **16** can be in electrical and/or thermal communication with submount **12**. One or more intervening layers can be disposed between emission area **16** and submount **12** such that emission area **16** is indirectly disposed over submount **12** thereby indirectly electrically and/or thermally communicating with submount **12**. In the alternative, emission area **16** can directly mount over submount **12** thereby directly electrically and/or thermally communicating, or connecting, with submount **12**. In one aspect and for example only without limitation, submount **12** can comprise a compact dimension of 22 millimeter (mm)×22-mm square footprint. In other aspects, submount **12** can comprise any suitable dimension and/or shape, for example, a circular or rectangular shape.

Emission area **16** can comprise a plurality of LED chips, or LEDs **25** disposed within and/or below a filling material **40** such as illustrated in FIG. **7**. LEDs **25** can comprise any suitable size and/or shape. For example, LEDs **25** can have a rectangle, square, or any other suitable shape. In one aspect, filling material **40** can comprise an encapsulant having a predetermined, or selective, amount of phosphors and/or lumiphors in an amount suitable for any desired light emission, for example, suitable for white light conversion. Filling material **40** can interact with light emitted from the plurality of LEDs **25** such that a perceived white light, or any suitable and/or desirable wavelength of light, can be observed. Any suitable combination of encapsulant and/or phosphors can be used, and combinations of different phosphors for resulting in desired light emission can be used. In other aspects, filling material **40** can comprise a molded lens material. Filling material **40** can be substantially opaque such that emission area **16** can be substantially opaque (as illustrated in FIG. **1**), transparent, or semi-transparent depending upon, for example, the amount and type of phosphor used. Retention material **14** can be adapted for dispensing, or placing, about at least a portion of emission area **16**. After placement of retention material **14**, filling material **40** can be selectively filled to any suitable level within the space disposed between one or more inner walls of retention material **14**. For example, filling material **40** can be filled to a level equal to the height of retention material **14** or to any level above or below retention material. The level of filling material **40** can be planar or curved in any suitable manner, such as concave or convex.

Still referring to FIG. **1**, LED device **10** can also comprise at least one opening or hole, generally designated **20**, that can be disposed through or at least partially through submount **12** for facilitating attachment of LED device **10** to an external substrate or surface. For example, one or more screws can be inserted through the at least one hole **20** for securing device **10** to another member, structure, or substrate. LED device **10** can also comprise one or more electrical attachment surfaces **18**. In one aspect, attachment surfaces **18** comprise electrical

6

contacts such as solder contacts. Attachment surfaces **18** can be any suitable configuration, size, shape and/or location and can comprise positive and negative electrode terminals through which an electrical current or signal can pass when connected to an external power source. One or more electrically conductive wires (not shown) can be attached and electrically connected to attachment surfaces **18** when welded, soldered, or any other suitable attachment method known. Electrical current or signal can pass into LED device **10** from the external wires electrically connected to the attachment surfaces **18** and into the emission area **16** to facilitate light output. Attachment surfaces **18** can electrically communicate with emission area **16** which comprises one or more LEDs **25**. Attachment surfaces **18** can electrically communicate with first and second conductive traces **33** and **34** (see FIG. **8**) and therefore LEDs **25** which may be electrically connected using electrical connectors. Electrical connectors can comprise wirebonds or other suitable members for electrically connecting LEDs **25** to first and second conductive traces **34** and **33**.

LED device **10** can further comprise an indicator sign or symbol for denoting the electrical polarity for a given a side of LED device **10**. For example, a first symbol **22** can comprise a "+" sign denoting the side of LED device **10** comprising the positive electrode terminal. A second symbol **23** can comprise a "-" sign denoting the side of LED device **10** comprising the negative electrode terminal. One or more test points **15** can be located adjacent either a positive or negative side of the device for testing the electrical and/or thermal properties of the LED device **10**. In one aspect, test point **15** can be disposed adjacent the negative side, or terminal of LED device **10**.

FIG. **2** illustrates a side view of LED device **10**. As illustrated by FIGS. **1** and **2**, retention material **14** can comprise a substantially circular dam disposed about at least a portion of emission area **16** and disposed over submount **12**. Retention material **14** can be dispensed, positioned or otherwise placed over submount **12** and can comprise any suitable size and/or shape. Retention material **14** can comprise any suitable reflective material and can comprise a clear or opaque white material such as, for example, a silicone or epoxy material. Filler particles such as titanium dioxide (TiO₂), for example, can be used and added to retention material **14** for providing an opaque material. Retention material **14** can be dispensed or deposited in place using an automated dispensing machine where any suitable size and/or shape of dam can be formed. In one aspect, a circular shape as shown can be dispensed, although any other configuration could also be provided such as, for example, a rectangular configuration, a curved configuration and/or any combination of desired configurations and cross-sectional shapes. As FIG. **2** illustrates in a side view of LED device **10**, retention material **14** can comprise a rounded outer wall **24** such that the upper surface of retention material **14** opposite submount **12** is rounded. Rounding or curving outer wall **24** of retention material **14** may further improve the amount of light reflected by LED device **10**.

Retention material **14** can comprise any material known in the art, for example, a silicone material comprising 7% fumed silica+3% TiO₂+methyl silicone. In one aspect, retention material **14** is adapted to reflect light, and can comprise and/or be coated with a reflective material. As illustrated in FIGS. **3A** and **3B**, retention material **14** can be dispensed after wirebonding of the one or more LEDs **25** such that retention material **14** is disposed over and at least partially covers wirebonds **26** to contain at least a portion, such as one end of each of wirebonds **26** within retention material **14**. In FIGS. **3A** and **3B**, wirebonds **26** for the electrical ends of the strings of LEDs **25** can be disposed within retention material **14**. For example,

the electrical ends of the strings can comprise first and last, or outermost edge LEDs **25A** for a given set of LEDs such as LEDs **25** are disposed within retention material **14**. In one aspect, retention material **14** can be “planed” during dispersion at room temperature for accurate volume and/or height control. The addition of TiO₂ can increase reflection about the emission area **16** to further to optimize light emission of LED device **10**. Fumed silica can be added as a thixotropic agent. Dispersing retention material **14** can allow increased board space and the ability to withstand higher voltages. In some aspects, LED device **10** can be operable at 42 volts (V) or higher.

FIGS. **3A**, **3B** and **4** illustrate emission area **16** without a layer of filling material **40**. FIGS. **3A** and **3B** illustrate LED device **10** and emission area **16** comprising at least one pattern, or arrangement, of LEDs. LEDs **25** can be arranged, disposed, or mounted over a conductive pad **30**. LEDs **25** can be arranged or disposed in sets of LEDs, that can comprise one or more strings or LEDs, and a given set of LEDs can for example be one or more strings of LEDs electrically connected in series or any other suitable configuration. More than one set of LEDs can be provided, and each set of LEDs can be arranged in parallel to one or more other sets of LEDs. As described further herein, the LEDs in any given set or string of LEDs can be arranged in any suitable pattern or configuration, and even LEDs within a given set or string of LEDs can be arranged or disposed in one or more different patterns or configurations. For example, FIG. **3A** illustrates at least three sets of LEDs arranged in three patterns, for example, a first pattern **P1**, a second pattern **P2**, and a third pattern **P3**. Each of patterns **P1**, **P2**, and **P3** can comprise a consistent pattern design across emission area **16**. More than one of patterns **P1**, **P2**, and/or **P3** can be used. Each of patterns **P1**, **P2**, and/or **P3** can alternate or be arranged in any suitable configuration. For illustration purposes, only three patterns are illustrated. Any number of patterns or arrangements is contemplated, and patterns can comprise any suitable design, for example, a checkerboard design or a grid design or arrangement wherein the LEDs can be at least substantially aligned in at least two directions. FIG. **3B** illustrates at least three sets of LEDs arranged in patterns, for example, a first pattern **P1A**, second pattern **P2**, and a third pattern **P3A** which combine one or more of patterns **P1**, **P2**, and **P3** illustrated in FIG. **3A**. For example, patterns **P1A** and **P3A** can comprise a combination of more than one pattern. In one aspect, pattern **P1A** can comprise a grid arrangement or pattern and a straight line arrangement or pattern. In one aspect, pattern **P3A** can comprise the checkerboard and straight line pattern designs. Each of patterns **P1A** and **P3A** can comprise 14 LEDs **25**, seven LEDs of each pattern design. For illustration purposes, only two combinations are illustrated. However, please note that each set of LEDs can comprise a combination of having more than two patterns.

Still referring to FIGS. **3A** and **3B**, conductive pad **30** can be electrically and/or thermally conductive and can comprise any suitable electrically and/or thermally conductive material. In one aspect, conductive pad **30** can comprise a conductive metal. In one aspect shown in FIG. **3A**, emission area **16** can comprise one or more LEDs **25** arranged in a single pattern over conductive surface, or pad **30**. In an alternative, LEDs can be provided that are a combination of more than one pattern of LEDs, such as LEDs **25**, arranged over conductive pad **30** as FIG. **3B** illustrates. As noted above, emission area **16** can comprise a combination of different arrangements or patterns, for example, a combination of first pattern **P1**, second pattern **P2** and/or third pattern **P3** for optimizing light emission and device brightness. Each set, or string of

LEDs **25** disposed over conductive pad **30** can comprise outermost LEDs **25A** with one or more LEDs **25** disposed therebetween. Each string of LEDs **25** can comprise the same or a different pattern, for example, patterns **P1**, **P2**, and/or **P3**. Strings of LEDs **25** can comprise diodes of the same and/or different colors, or wavelength bins, and different colors of phosphors can be used in the filling material **40** (FIG. **7**) disposed over LEDs **25** that are the same or different colors in order to achieve emitted light of a desired wavelength. The one or more patterns of LEDs **25** can comprise an array of LEDs within emission area **16**.

FIGS. **3A**, **3B**, and **4** illustrate emission area **16** comprising, for example, 10 lines, or strings, of LEDs **25**. Each string of LEDs **25** can comprise any suitable number of LEDs electrically connected between electrical ends, such as outermost LEDs **25A** which can connect to respective electrical elements. In one aspect, each string of LEDs **25** can comprise at least 14 LEDs. In one aspect, LED device can comprise at least 140 LEDs arranged in an array. The arrangements, patterns, and/or combination of multiple patterns herein can comprise an array for optimizing color uniformity and brightness of light emitted from LED device **10**. The LEDs can be electrically connected in series using one or more wirebonds **26** for attaching bond pads of adjacent LEDs **25**. In one aspect as shown in FIG. **3A**, first pattern **P1** can comprise the first and tenth strings of 14 LEDs **25**. First pattern **P1** can comprise two opposing lines of LEDs **25** disposed between electrical ends such as the first and last, or outermost LEDs **25A** of the series. In one aspect, first pattern **P1** comprises what is referred to herein as a grid arrangement, pattern or design, where at least two LEDs are at least substantially aligned in at least two directions and can include single, unaligned LEDs at opposing ends of a set or string of LEDs. Each of the LEDs **25** comprising first pattern **P1** can be electrically connected in series. In one aspect, second arrangement or second pattern **P2** can be disposed adjacent first pattern **P1**, for example, located at the second and ninth strings of LEDs **25**. In one aspect, second pattern **P2** can comprise 14 total LEDs **25** wherein each of the 14 LEDs **25** can be arranged adjacent each other along a horizontal line in a straight line design, or arrangement, and each of the 14 LEDs **25** can be electrically connected in series. Any suitable number of LEDs **25** can be connected in any suitable configuration or arrangement such as in series to form a string having a suitable pattern. Care must be taken when connecting LEDs **25** in series such that the positive or negative electrode of a preceding LED electrically connects to an electrode of opposite electrical polarity for a subsequent LED for allowing electrical current to flow properly through the string of LEDs **25**.

Third pattern **P3** shown in FIG. **3A** can comprise a checkerboard pattern having a checkerboard design, or arrangement of LEDs **25** electrically connected in series. In one aspect, at least 14 LEDs **25** can comprise the checkerboard pattern, and third pattern **P3** can be disposed between and/or alternate with strings of LEDs having second pattern **P2**. The checkerboard pattern or third pattern **P3** can comprise a set of LEDs **25** alternating both above and below a horizontal line. Patterns **P1**, **P2**, and **P3** are not limited in the shape of pattern or to at least 14 LEDs, but rather, patterns can comprise any suitable arrangement and any suitable number of LEDs **25**. For illustration purposes, only three patterns are shown although any suitable number of patterns could be utilized. The alternating LEDs **25** of third pattern **P3** can optimize light output by ensuring uniform coverage and spatial alignment over conductive pad **30** such that light emission is uniform and improved. Third pattern **P3** can repeat from the third through the eighth string of LEDs **25**. First and last LEDs **25A**

in a given string of LEDs **25** for each of patterns P1, P2, and/or P3 can electrically connect to first and second conductive traces **33** and **34** (see FIGS. 7, 8) for receiving and transmitting electrical current or signal through and illuminating a given string of LEDs **25**.

The LEDs even in a single set or string in emission area **16** can comprise LEDs in more than one pattern or configuration. For example, FIG. 3B illustrates one aspect of a possible arrangement of LEDs in emission area **16** where there are at least two sets, shown here as strings without limitation, of LEDs **25** and where LEDs **25** for some sets or strings are arranged in different patterns or configurations with respect to another set or string of LEDs and even within one single set or string of LEDs. Any two given separate sets or strings of LEDs **25** can be electrically connected in a pattern such that some or all of the LEDs within each of the two sets or strings of LEDs can be arranged in different patterns, in identical patterns, or in any combination of patterns. In other words, the LEDs in any given set or string can be disposed in different or identical patterns with respect not only to the LEDs in that set or string but can also be disposed in any pattern with respect to another set or string of LEDs and the two sets or strings can in one aspect be parallel to one another. For example, LEDs **25** in FIG. 3B can be disposed in one aspect such that emission area **16** comprises a combination of different arrangements or patterns, for example, a first pattern P1A, a second pattern P2A and/or a third pattern P3A for optimizing light emission and device brightness.

As noted earlier, patterns P1A and P3A illustrate a combination of two different patterns, for example at least two of the checkerboard, straight line and/or grid arrangement, however, combinations of more than two patterns is hereby contemplated. Only three pattern arrangements have been disclosed (i.e., checkerboard, grid, straight line), but any suitable arrangement or pattern design can be used. Each string of LEDs **25** disposed over conductive pad **30** can comprise electrical ends. In one aspect, the electrical ends of the strings can comprise outermost LEDs **25A** with one or more LEDs **25** disposed therebetween. Each set or string of LEDs **25** can comprise the same or a different pattern, for example, patterns P1A, P2A, and/or P3A. Sets or strings of LEDs **25** can comprise diodes of the same and/or different colors, or wavelength bins, and different colors of phosphors can be used in the filling material **40** (FIG. 7) disposed over LEDs **25** that are the same or different colors in order to achieve emitted light of a desired wavelength. The one or more patterns of LEDs **25** can comprise an array of LEDs within emission area **16**. As FIG. 3B illustrates, for example, in pattern P3A, sets of LEDs **25** can comprise rectangular LEDs arranged where the major (i.e., long) axis of a first LED is disposed in a different orientation than the major axis of at least a second LED. That is, a given set of LEDs **25** can comprise LEDs **25** in different orientations. In other aspects, as illustrated in FIG. 3A for example, pattern P2 and pattern P3 can comprise sets of rectangular LEDs **25** where the major axis is the same is the same for the given set but different from the orientation of other sets.

The various LED arrangements and device designs as described herein are advantageous for providing a light emitting device with excellent performance and output while still being a small light emitting device where pressure exists to provide small devices while maintaining quality performance and light output.

FIG. 5 illustrates a second embodiment of an LED device, generally designated **50** which is similar in form and function to LED device **10**. LED device **50** can comprise submount **12** and emission area **16** disposed over submount **12**. Emission

area **16** can comprise any suitable size, shape, number and/or be disposed at any suitable location over submount **12**. Retention material **14** can be disposed over submount **12** and at least partially about emission area **16**. LED device **50** can comprise one or more openings or holes **20**, disposed through submount **12** for facilitating attachment of LED device **10** to an external substrate or surface. LED device **50** can comprise first and second symbols **22** and **23** for denoting the electrical polarity of LED device **50**. LED device **50** illustrates test point **15** disposed adjacent the positive or side of the device for testing the electrical and/or thermal properties of the LED device **50**. LED device **50** further can comprise at least one electrical attachment surface **18** that can electrically connect to one or more external wires (not shown) for facilitating the flow of electric current into emission area **16** of LED device **50**. In one aspect, attachment surface **18** can comprise a shape having curved corners. Rounding the corners, or edges of attachment surfaces **18** may better contain the flow of solder over the device than sharp corners when attaching one or more external conductive wires (not shown) to LED device **50**.

FIG. 6 illustrates a portion of a cross-section along an edge of conductive pad **30** of FIGS. 3A and 3B wherein the emission area **16** has not been filled with filling material **40** such as encapsulant and/or phosphors. FIG. 6 illustrates LEDs **25** comprising an outermost LED **25A** and adjacent LED for a given string of LEDs within emission area **16**. FIG. 7 illustrates a portion of a cross-section of FIG. 1 wherein filling material **40** is disposed over emission area **16**. For illustration purposes, four LEDs **25** are illustrated and electrically connected in series in FIG. 7. However, as noted earlier, each string, or pattern of LEDs **25** can comprise any suitable number of LEDs **25**. In one aspect, each string of LEDs can comprise 14 LEDs **25**. FIGS. 6 and 7 illustrate one or more LEDs **25** connected in series by one or more wirebonds **26**. LEDs **25** can be arranged over conductive pad **30** and can thermally communicate directly with conductive pad **30** or indirectly through one or more intervening layers. LEDs **25** can attach to conductive pad **30** or intervening layers using any attachment means known in art. In one aspect, LEDs **25** can attach using solder pastes, epoxies, or flux. Conductive pad **30** can be formed integral as one piece of submount **12** or can comprise a separate layer disposed over submount **12**. Conductive pad **30** can dissipate heat generated by the one or more LEDs **25**.

As FIGS. 6 and 7 further illustrate, the electrical ends of each string, such as the outermost LEDs **25A** for a series, string, or pattern of LEDs **25** can electrically communicate or connect to one or more electrical elements. Electrical elements can comprise first and second conductive traces **33** and **34** configured to flow, or supply electrical signal or current to the respective strings of LEDs **25**. One of first and second conductive traces **33** and **34** can comprise an anode and the other a cathode. The electrical polarity can be denoted by first and second symbols **22** and **23** (FIG. 1) as discussed earlier. Conductive pad **30** and conductive traces **33** and **34** can comprise any suitable electrical and thermally conductive materials and can comprise either the same or different materials. In one aspect, conductive pad **30** and conductive traces can comprise a layer of copper (Cu) deposited over a portion of submount (e.g., dielectric layer **36** of FIG. 7) using any suitable technique. An electrically insulating solder mask **32** can be disposed at least partially between conductive pad **30** and respective conductive traces **33** and **34** such that when solder is used to attach one or more LEDs **25** over conductive pad **30**, the solder cannot electrically connect with the con-

11

ductive traces **33** and **34** thereby causing one or more strings of LEDs **25** to become electrically shorted.

FIG. **6** illustrates various placement areas, positions, or locations of retention material **14** about emission area **16**. In one aspect, retention material **14** can be dispensed about at least a portion, or entirely about emission area **16**. Conventional devices can comprise a molded as opposed to dispensed dam placed at a location such as prior art location PA shown in broken lines in FIG. **6** and disposed along an edge of where solder mask **32** contacts first conductive trace **34**. The present subject matter envisions retention material **14** disposed in areas, positions, or locations R1, R2, and/or any location therebetween. When retention material **14** is disposed in locations R1 or R2, it can be disposed over and cover at least a portion of one or more wirebonds **26** connecting outermost LEDs **25A** to electrical elements, such as conductive trace **34**. When in location R1, retention material **14** can be disposed at least partially over each of solder mask **32** and wirebond **26** connected to outermost LED **25A** for a respective string of LEDs **25**. In one aspect, retention material **14** can be disposed entirely over the portion of solder mask **32** disposed between conductive pad **30** and conductive trace **34** and/or entirely over wirebond **26** when in location R1. In another aspect, retention material **14** can be disposed over and at least partially or entirely cover each of the wirebonds **26** of each of the outermost LEDs **25A** for each string of LEDs **25** disposed in emission area **16**. The retention material can be dispensed in a predetermined location on the submount **12** for providing a suitable distance between the retention material **14** and the one or more LEDs **25**. Notably, when in location R1, retention material **14** can eliminate the need for solder mask **32** as retention material would be disposed between conductive pad **30** and first and/or second conductive traces **33**, **34**. Location R2 illustrates retention material **14** disposed at least partially over solder mask **32** and at least partially over wirebond **26** of outermost LED **25A**. As illustrated, retention material **14** according to the subject matter herein can comprise a substantially rounded or hemispheric shaped cross-section. Rounding retention material **14** can increase the surface area from which light may be emitted and/or reflected.

FIG. **7** illustrates a string of one or more LEDs **25**, for illustration purposes four LEDs **25** are shown but strings of LEDs **25** can comprise any suitable number of LEDs, for example, 14 LEDs **25** arranged in series. FIG. **7** illustrates a cross-section of submount **12** over which LEDs **25** can be mounted or otherwise arranged. Submount **12** can comprise, for example, conductive pad **30**, first and second conductive traces **33** and **34**, and solder mask **32** at least partially disposed between conductive pad **30** and each of conductive traces **33** and/or **34**. As noted earlier, if retention material is positioned adjacent electrical ends of each string (e.g., such as adjacent outermost LEDs **25A**), for example in location R1, solder mask **32** between conductive pad **30** and first and second conductive traces **33** and **34** can be eliminated as it would no longer be necessary. Solder mask **32** can be disposed between conductive traces **33** and **34** and attachment surfaces **18** (FIG. **8**), the proximal edges of which can be seen in FIG. **7** adjacent retention material **14**, adjacent the outer wall **24** of retention material **14**. Submount **12** can further comprise a dielectric layer **36**, and a core layer **38**. For illustration purposes, submount **12** can comprise a MCPCB, for example, those available and manufactured by The Bergquist Company of Chanhassan, Minn. Any suitable submount **12** can be used, however. Core layer **38** can comprise a conductive metal layer, for example Cu or aluminum (Al). Dielectric layer **36** can comprise an electrically insulating but thermally conductive material to assist with heat dissipation through

12

submount **12**. FIG. **7** illustrates retention material **14** arranged, for example, in position R2 at least partially over each of solder mask **32** and the wirebond **26** connecting to conductive traces **33** and **34**. FIG. **7** illustrates filling material **40** disposed over the one or more LEDs **25**. Filling material **40** can be selectively filled to any suitable level higher, lower, or equal to the height of retention material **14**. Wirebonds **26** of the outermost LEDs **25A** as shown can be at least partially disposed within retention material **14**.

FIG. **7** further illustrates examples of first and second heights H1 and H2 of filling material **40** which can be selectively filled within LED device **10**. First height H1 can comprise a height at which filling material **40** is disposed over the LEDs **25**. The height may vary due to process variability, so an average height above the string of LEDs **25** can be used and controlled for optimal brightness. Second height H2 can comprise a height at which filling material **40** is selectively disposed over a top surface of conductive pad **30**. Second height H2 can be controlled, for example, by controlling the location of retention material **14** and whether it assumes location R1, R2 or any position therebetween. Second height H2 can also be controlled by controlling the amount of filling material **40** dispensed into the cavity defined by retention material **14**.

Controlling the volume of filling material **40** within the cavity, or dam defined by retention material **14** can affect first and second heights H1 and/or H2 and can notably allow for fine-tuning or micro-tuning the color, or wavelength, of light emitted from LED device **10**. Micro-tuning the color of LED devices **10** can therefore ideally increase product yields to 100%. For example, the amount of color affecting components, including but not limited to phosphors, contained in filling material **40** can be selectively added and the first and/or second heights H1, H2 can be selectively controlled by under or over filling the filling material **40** within emission area **16** depending on the wavelength of LEDs **25** used within device **10**. Location of retention material **14**, for example, locating retention material at R1, R2, or any position or distance therebetween can also affect first and/or second heights H1 and H2. Micro-tuning color can be achieved over multiple devices or on a per device, or package, basis by changing, for example the ratio of volume of phosphor to overall dispense capability volume of filling material **40**. The ratio of volume of phosphor to overall dispense capability volume of filling material **40** can be adjusted based on the wavelength bin of LEDs **25** selected for use in a given device to attain the desired overall wavelength output of LED device **10**. By manipulating, for example, the diameter of the dam provided by retention material **14** and/or the height of retention material **14**, each of which can affect heights H1 and/or H2 and therefore the volume of fill material, the color of individual devices **10** can be micro-tuned thereby attaining higher process yields. Notably, selectively controlling a volume of the fill material such that color-affecting components of the fill material can be fine-tuned allows for light produced by the one or more LEDs to fall within a predetermined and precise color range.

FIG. **8** illustrates LED device **10** comprising submount **12** prior to arranging, dispensing, or otherwise placing retention material **14** about at least a portion of emission area **16**. For illustration purposes, only a first string of LEDs **25** is illustrated, however, as noted earlier, emission area can comprise more than one strings of LEDs **25** electrically connected in series. In one aspect, LED device **10** comprises 10 strings of LEDs **25** connected in series. As illustrated, prior to placing retention material **14**, submount **12** can comprise first and second conductive traces **33** and **34** arranged in a substantially circular arrangement about conductive pad **30** such that LEDs arranged over conductive pad **30** can electrically com-

13

communicate to each trace by wirebonding and wirebonds **26** or by any other suitable attachment method. As illustrated, electrical ends of each string can electrically connect to conductive traces. For example, in one aspect electrical ends of each string can comprise outermost LEDs **25A** for a respective string of LEDs **25** can electrically connect to conductive traces.

At least one gap **42** can exist between conductive traces **33** and **34**. LED device **10** and devices disclosed herein can further comprise elements to protect against damage from ESD positioned, or disposed in the gap **42**. In one aspect, different elements can be used such as various vertical silicon (Si) Zener diodes, different LEDs arranged reverse biased to LEDs **25**, surface mount varistors and lateral Si diodes. In one aspect, at least one Zener diode **44** can be disposed between ends of first and second conductive traces **33** and **34** and reversed biased with respect to the strings of LEDs **25**. In one aspect, two Zener diodes **44** can be electrically connected in series using one or more wirebonds **46** between first and second conductive traces **33** and **34** for higher voltage applications. As Zener diodes **44** are typically black and absorb light, placing the at least one Zener diode **44** in gap **42** between conductive traces **33** and **34** and also beneath retention material **14** can further improve light output intensity.

FIG. **8** also illustrates one possible location for conductive pad **30**. That is, conductive pad **30** can comprise a substantially centrally located circular pad disposed between conductive traces **33** and **34**. Conductive pad **30** however, can be located at any suitable location over submount and any location other than substantially center the device. Solder mask **32** can be disposed at least partially between respective conductive traces and conductive pad **30**, such that the solder mask **32** comprises a substantially circular arrangement about conductive pad **30**. Solder mask **32** can also be disposed in areas outside of the conductive traces, for example, between the respective conductive traces and one or more attachment surfaces **18**. Broken lines **52** illustrate one possible aspect of the size and/or shape of the electrically and/or thermally conductive material comprising the conductive traces **33** and **34**. The lines are broken to illustrate how the material can be disposed under solder mask **32**. Thus, attachment surfaces **18** electrically and/or thermally communicate with respective conductive traces, and can comprise the same layer of material. External, conductive wires (not shown) can electrically connect to attachment surfaces **18**, and electrical current or signal can flow from the attachment surfaces **18** to the respective conductive traces. The electrical current can flow along the conductive material designated by dotted lines **52** disposed below the layer of solder mask **32**. The electrical current can flow into and/or out of the conductive traces and therefore into and out of respective strings of LEDs **25** mounted over conductive pad **30**.

As noted earlier, Zener diodes **44** are typically black and absorb light. FIG. **9** illustrates Zener diode **44** upon placement of the retention material. In one aspect, retention material **14** can be disposed at least partially over the at least one Zener diode **44**. In another aspect, retention material **14** can be disposed entirely over the at least one Zener diode **44** such that the diode is completely covered for further improving light output intensity. Zener diode **44** can be disposed over an electrically and/or thermally conductive surface or area **54** such that current can flow through the diode **44**, into the wirebonds **46**, and to respective conductive traces **33** and **34**.

LED devices disclosed herein can advantageously consume less energy while delivering equal or greater illumination. In one aspect, when used in traditional downlight applications, luminaires based on LED devices **10** and/or **50** can

14

deliver 38% more illumination than a 26-watt CFL or a 100-watt incandescent bulb, while consuming only 14 watts. In one aspect, LED device **10** can enable a 60-watt A-lamp equivalent while consuming only 11 watts. LED device **10** can comprise a light output of 1050 lumens at 11 watts, or 2000 lumens at 27 watts, with a 3000-K warm-white color temperature.

FIG. **10** illustrates another embodiment of an LED device, generally designated **55**. LED device **55** illustrates submount **12** prior to arranging, dispensing, or otherwise placing retention material **14** (FIG. **11**) about at least a portion of emission area **16**. For illustration purposes, only a first string of LEDs **25** is illustrated, however, emission area can comprise more than one string of LEDs **25** electrically connected in series. Each string of LEDs **25** can comprise the same or a different pattern. Prior to placing retention material **14**, submount **12** can comprise first and second conductive traces **33** and **34** arranged in a substantially circular arrangement about conductive pad **30** such that LEDs arranged over conductive pad **30** can electrically communicate to each trace by wirebonding via wirebonds **26** or any other suitable attachment method. As illustrated, outermost LEDs **25A** for a respective string of LEDs **25** can electrically connect to the conductive traces. In fact, for LED devices described herein, emission area **16** can comprise a single, undivided mounting area at least partially defined by outermost LEDs **25A**, with the outermost LEDs **25A** being wirebonded via wirebonds **26** to contact areas, such as conductive traces **33** and **34**. LEDs **25** that are not the outermost LEDs **25A** are wirebonded via wirebonds **26** in strings having one or more patterns or arrays.

At least one gap **42** can exist between conductive traces **33** and **34**. In this embodiment, one or more ESD protection device or Zener diode **44** can be disposed in gap **42** and can be electrically connected, or mounted to conductive area **54**. In this embodiment, conductive area **54** can comprise an area larger than a footprint of Zener diode **44**. Zener diode **44** can be positioned over conductive area **54** between ends of first and second conductive traces **33** and **34**. Zener diode **44** can be reversed biased with respect to the one or more strings of LEDs **25**. For example, when one Zener diode **44** is used, one or more wirebonds **46** can connect conductive area **54** to one of first and second conductive traces **33** and **34** such that Zener diode **44** can be reverse biased with respect to the strings of LEDs **25**. As Zener diodes **44** are typically black and absorb light, placing the at least one Zener diode **44** in gap **42** between conductive traces **33** and **34** and also beneath retention material **14** (FIG. **9**) can further improve light output intensity.

FIG. **10** also illustrates one possible location for test point **15**. Test point **15** can be disposed within the area marked by broken lines **52** which correspond to conductive material disposed under solder mask. Broken lines **52** illustrate one possible aspect of the size and/or shape of the conductive material which can be deposited on or in submount **12** for electrically coupling conductive traces **33** and **34** and attachment surfaces **18**. The electrical coupling allows electrical current to be communicated from attachment surfaces **18** to the one or more strings of LEDs **25** electrically connected to traces **33** and **34**. The lines are broken to illustrate how the material can be disposed under solder mask **32**. Thus, test point **15** and attachment surfaces **18** electrically and/or thermally communicate with respective conductive traces, and can comprise the same layer of material. Solder mask **32** can be deposited or disposed at least partially between respective conductive traces and conductive pad **30**, such that the solder mask **32** comprises a substantially circular arrangement about conductive pad **30**. Conductive pad **30** can comprise one or

15

more marks or notches **62** for orientation purposes and for proper alignment of retention material **14**.

Solder mask **32** can also be deposited in areas outside of the conductive traces, for example, between the respective conductive traces and one or more attachment surfaces **18** and/or test point **15**. External, conductive wires (not shown) can electrically connect to attachment surfaces **18**, and electrical current or signal can flow from the attachment surfaces **18** to the respective conductive traces. The electrical current can flow along the conductive material designated by dotted lines **52** disposed below the layer of solder mask **32**. The electrical current can flow into and/or out of the conductive traces and therefore into and out of respective strings of LEDs **25** mounted over conductive pad **30**. In one aspect, test point **15** can allow thermal properties of the device to be tested when probed with any suitable temperature sensor (not shown). The arrangement illustrated by FIG. **10**, i.e., the location of conductive traces **33** and **34**, conductive area **54**, Zener diode **44**, and test point **15** prior to placing retention material **14** can correspond to any one of the previously described LED devices e.g., **10** and **50** or any of the devices described in FIGS. **11-14**. For example, LED devices described in FIGS. **11-14** can comprise at least one opening or hole, generally designated **20**, that can be disposed through or at least partially through submount **12** for facilitating attachment of the LED devices to an external substrate or surface. In addition first symbol **22** and second symbols can be used to denote the portions of the LED devices comprising positive and negative electrode terminals. One or more test points **15** can be located adjacent either a positive or negative side of the device for testing the electrical and/or thermal properties of the LED devices.

FIGS. **11** to **14** illustrate top views of different embodiments of LED devices. Such devices can be similar in many aspects to previously described LED devices **10** and **50**, but can also be useful for a range of low and/or high voltage applications in addition to attaining different light output by pattern variation. For example, FIG. **11** illustrates one embodiment of an LED device, generally designated **60** which can be used in lower voltage applications. In one aspect and for example only without limitation, LED device **60** can be operable at approximately 16 V. In one aspect, LED device **60** can be operable at less than approximately 16 V, for example, 14 to 16 V. In one aspect, LED device **60** can be operable at more than approximately 16 V, for example, 16 to 18 V. In one aspect, using more than 140 LEDs **25**, e.g., more than LED device **10** and changing the pattern of LEDs **25** can allow LED device **60** to be operable at lower voltage applications. In one aspect, the pattern can be changed by electrically connecting less than 14 LEDs **25** together in a series or string.

FIG. **11** illustrates at least two sets of LEDs arranged in two patterns forming a reticulated array of LEDs **25** within emission area **16**. For example, a first set of LEDs can comprise second pattern **P2**, previously described. A second set of LEDs can comprise a fourth pattern **P4**. Each pattern can comprise, for example, 30 strings of five LEDs **25** electrically connected in series. That is, fewer than 14 (FIGS. **3A**, **3B**) LEDs **25** can be electrically connected in series in a given string. The first and last strings of LEDs **25** can comprise five LEDs **25** electrically connected in series according to previously described second pattern **P2**. The second to twenty-ninth strings can comprise another pattern different from the first and thirtieth strings. For example, FIG. **11** illustrates five LEDs **25** electrically connected in series according to pattern **P2**, the strings can be disposed on conductive pad **30** proximate one or more rounded outer edges of emission area **16**.

16

LEDs **25** arranged in the first and thirtieth strings can, for example and without limitation, be spaced equidistant from each other and uniformly across emission area **16** according to pattern **P2**. LEDs **25** arranged in pattern **P2** can comprise a straight line arrangement in which longer axes of LEDs **25** are substantially parallel. The shorter axes of LEDs **25** in pattern **P2** can also be at least substantially parallel. Longer axes of LEDs **25** arranged in pattern **P2** can be aligned perpendicular to wirebonds **26**. In addition, longer axes of LEDs **25** arranged in pattern **P2** can be perpendicular to longer axes of LEDs **25** arranged in adjacent patterns, e.g., pattern **P4**.

In one aspect, pattern **P4** can comprise five LEDs **25** electrically connected in series across conductive pad **30**. Pattern **P4** can comprise a straight line of LEDs, and each of the five LEDs **25** can be positioned such that longer axes of LEDs **25** are substantially aligned along a straight line. In one aspect, longer axes of each LED **25** can be aligned in a same direction as the direction of wirebonds **26** connecting the LEDs **25** to conductive traces **33** and **34** disposed below retention material **14**. Adjacent strings, e.g., adjacent strings in the second through twenty-ninth strings of LEDs **25** connected in pattern **P4** can alternate above and below a straight line such that the LEDs **25** form a substantially checkerboard type arrangement. That is, a first string of LEDs **25** arranged in pattern **P4** (i.e., the second overall string of LEDs **25** disposed below the first string comprising pattern **P2**) can comprise five LEDs **25** spaced equidistant apart, leaving a space in between adjacent LEDs **25**. In the alternative, LEDs **25** in pattern **P4** could be wirebonded in a checkerboard arrangement, but that could increase the voltage at which device **60** is operable. Below the first string of LEDs **25** arranged in pattern **P4**, a subsequent string of LEDs **25** arranged in pattern **P4** can be positioned or placed such that the LEDs **25** are substantially within and/or slightly below the space between adjacent LEDs **25** of the preceding string. That is, LEDs **25** arranged in pattern **P4** can comprise a first string aligned such that a bottom edge of each LED **25** in the string is aligned along a same first straight line. LEDs **25** in a neighboring subsequent string of pattern **P4** can be aligned such that a top edge of each LED **25** is also aligned along the same first straight line as the bottom edge of LEDs **25** in the preceding string. Thus, LEDs **25** of preceding and subsequent strings alternate above and/or below spaces between adjacent LEDs **25** in a given string, and the top and bottom edges of LEDs **25** in adjacent strings can be aligned along a same line. This arrangement comprises a substantially checkerboard shaped orientation which can advantageously allow LEDs **25** to uniformly emit light from LED device **60** without one or more adjacent LEDs blocking light.

Additional strings of LEDs **25** arranged in pattern **P4** can alternate according to the first two strings just described. Strings of LEDs **25** comprising pattern **P4** can comprise a same or similar width over emission area **16**. That is, each adjacent LED **25** of a given string can be spaced apart at equidistant lengths, but the overall string length may not be uniformly across emission area **16**. Rather, LEDs **25** can be spaced such that the second to twenty-ninth strings or rows can form a substantially reticulated array over emission area **16**. In one aspect, LEDs **25** form a rectangular array over emission area **16** which utilizes a substantially uniform portion of horizontal segments, or chords of conductive pad **30**. In one aspect, LED device **60** can comprise at least one group of LEDs **25** arranged in more than one string of LEDs, where the overall configuration can be in a predetermined geometrical shape, such as for example and without limitation, a rectangle. Any suitable number of LEDs **25** can be connected in series. Fewer number of LEDs **25**, for example five LEDs **25** connected in series as illustrated in FIG. **11** can allow LED

device 60 to be suitable for lower voltage applications, for example 16V applications. For illustration purposes, 30 strings of five LEDs 25 arranged in one or more patterns are illustrated for operation at lower voltages, however, any suitable number of strings and/or LEDs 25 electrically connected in series is contemplated.

LED device 60 can comprise outermost LEDs 25A electrically connected via electrical connectors such as wirebonds 26 to conductive traces 33, 34 (FIG. 10). Retention material 14 can then be dispensed at least partially about conductive pad 30 and at least partially over wirebonds 26. Retention material 14 can be dispensed about emission area 16 which can comprise a plurality of LED chips, or LEDs 25 disposed within and/or below filling material 40 such as illustrated in FIG. 7. Filling material 40 can be at least partially contained by retention material 14, and retention material can be used to control or adjust various heights of filling material as may be desirable. Notably, LED device 60 can comprise a uniform optical source in the form of single, cohesive, and undivided emission area which can simplify the manufacturing process for manufacturers of light products requiring a single component. LEDs 25 can be spaced a suitable distance apart such that device 60 can advantageously emit uniform light without having any light blocked by one or more adjacent LEDs 25. The patterns and pattern spacing (i.e., spacing between adjacent LEDs 25 and spacing between adjacent strings of LEDs 25) disclosed for example in LED devices 10 and 60 allow for optimization of light extraction by reducing the amount of light blocked by adjacent LEDs 25 and adjacent strings of LEDs 25. The pattern spacing disclosed for example in LED devices 10 and 60 can further be configured and expanded, for example, by increasing the spacing between adjacent LEDs 25 (e.g., to pattern spacing illustrated in FIGS. 12-14B) to maximum spacing within a given string and between one or more strings to further maximize and attain a higher efficiency and light extraction within a given LED device.

FIGS. 12 to 14B illustrate top views of LED devices which can be operable at higher voltages such as, for example only and not limited to approximately 42 V. In one aspect, LED devices illustrated by FIGS. 12 to 14B can comprise more than five LEDs 25 per string such that the device is configured to operate at greater than approximately 16 V. FIG. 12 illustrates an LED device generally designated 70 having, for example, five strings of 14 LEDs 25. LED device 70 can comprise strings of LEDs 25 arranged in one or more different patterns. For example, the first and last strings proximate rounded edges of conductive pad 30 can comprise 14 LEDs 25 arranged in previously described pattern P2. The longitudinal axes of adjacent LEDs 25 in pattern P2 can be aligned such that they are at least substantially parallel. The longitudinal axes of adjacent LEDs 25 in pattern P2 can be at least substantially perpendicular to the direction of wirebonds 26 connecting adjacent LEDs 25. For each LED device described, any shape, orientation, or structure of LEDs is contemplated. In one aspect, LED device 70 can comprise 70 total LEDs 25.

Still referring to FIG. 12, strings of LEDs 25 disposed between outermost strings of second pattern P2 can comprise a different pattern, for example, third pattern P3 previously described in FIGS. 3A and 3B. Third pattern P3 can comprise a substantially checkerboard pattern or arrangement of LEDs 25 electrically connected in series. In one aspect, pattern P3 can be disposed between and/or alternate with strings of LEDs having second pattern P2. The checkerboard pattern or third pattern P3 can comprise a set of LEDs 25 alternating both above and below a horizontal line. LED device 70 can be disposed uniformly across emission area 16 and/or conduc-

five pad 30, for example. In general, adjacent LEDs 25 in each of the strings of LED device 70 can be spaced at equidistant intervals to utilize a substantial portion of horizontal segments of conductive pad 30. That is, LEDs 25 in device 70 can occupy a greater amount of surface area and length of horizontal segments of conductive pad 30 than previously described LED device 60. For illustration purposes, five strings of 14 LEDs 25 arranged in two different patterns are illustrated, however, any suitable number of strings and/or LEDs 25 electrically connected in series is contemplated.

FIGS. 13A and 13B illustrate further embodiments of LED devices. In one aspect, LED devices in FIGS. 13A and 13B comprise six strings of 14 LEDs 25, for a total of 84 LEDs 25. Referring to FIG. 13A, LED device, generally designated 80 can comprise one or more strings of LEDs 25 arranged for example in a single pattern across conductive pad 30. The one or more strings of device 80 can have the same and/or different patterns. For illustration purposes, previously described pattern P3 is illustrated. LEDs 25 can be arranged in a checkerboard pattern alternating above and below a horizontal line. Adjacent LEDs 25 can be spaced a substantially uniform distance from each other across a large portion of the surface area of conductive pad 30. Checkerboard arrangements, e.g., pattern P3 can advantageously allow the LEDs 25 to uniformly emit light from LED device 80 without one or more adjacent LEDs 25 blocking light.

FIG. 13B illustrates another embodiment of a six string LED device, generally designated 85. Like LED device 80, LED device 85 can comprise six strings of 14 LEDs 25. Spacing between adjacent LEDs 25 within the same string and adjacent LEDs 25 within different strings has been maximized to minimize the amount of light absorbed by adjacent LEDs. In one aspect, LED device 85 comprises previously illustrated first pattern P1 (FIG. 3A) as the first and last strings. Notably, LEDs 25 of patterns P1 and P3 extend at least substantially the full length and width of conductive pad 30. The second through fifth strings of LEDs 25 within LED device 85 comprise pattern P3. When comparing the six string arrangement of FIG. 13A to the six string arrangement of FIG. 13B, it is apparent that the strings of FIG. 13B are more spread out, i.e., vertically and horizontally spaced further apart on conductive pad 30 to utilize more of the mounting area. Maximizing the space between strings of LEDs 25 can minimize the amount of light absorbed or blocked by neighboring LEDs 25.

In one aspect, inter-string spacing, that is, spacing between adjacent LEDs 25 of the same string has been increased by at least approximately 31%, or by 125 μm , or greater in the vertical direction for pattern P3 from LED device 80 to LED device 85. Similarly, inter-string spacing of LEDs 25 in pattern P1 has been increased and/or optimized in both the horizontal and vertical directions. For example, spacing has been increased approximately 41%, or by 225 μm , or greater, in the horizontal direction and by at least approximately 27%, or by 210 μm , or greater in the vertical direction from P1 in LED device 10 to P1 in LED device 85. Intra-string spacing i.e., spacing between LEDs 25 of adjacent strings can be increased by at least approximately 68%, or by 750 μm , or greater in LED device 85. Notably, although LED device 85 can comprise the same number of LEDs 25 as LED device 80, e.g., 84 LEDs, LED device 85 can comprise at least approximately a 1% to 3%, or greater, increase in efficiency and brightness when compared to LED device 80. In one aspect, increasing the spacing between adjacent LEDs 25 as described can increase the efficiency by at least approximately 2.5% or greater from one six string arrangement to another, e.g., LED device 85 can comprise a 2.5% or greater

19

increase in efficiency over LED device **80**. For example, LED device **85** can have a light output of at least approximately 2.5% or higher than the light output of LED device **80** described above, which can comprise approximately 1050 lumens or more at 11 watts, or approximately 2000 lumens or more at 27 watts.

FIGS. **14A** and **14B** illustrate further embodiments of LED devices. In one aspect, the LED devices in FIGS. **14A** and **14B** comprise eight strings of 14 LEDs **25**. Referring to FIG. **14A**, an LED device generally designated **90** is illustrated, and can be operable at higher voltages, not limited to greater than or equal to approximately 42 V. LED device **90** can comprise one or more strings of LEDs **25** arranged in one or more patterns across emission area **16** and/or conductive pad **30**. In one aspect, LED device **90** can comprise eight strings of LEDs **25** arranged in more than one pattern. Each string of LEDs **25** can comprise 14 LEDs **25**, or **112** total LEDs. In one aspect, the first and last strings can comprise previously described pattern **P2**. The second through seventh strings of LEDs **25** can comprise previously described pattern **P3**. Notably, LED devices illustrated by FIGS. **11** to **14B** can comprise a uniform optical source in the form of single, cohesive, and undivided emission area which can simplify the manufacturing process for manufacturers of light products requiring a single component.

FIG. **14B** illustrates another embodiment of an eight string LED device, generally designated **95**. Like LED device **90**, LED device **95** can comprise eight strings of 14 LEDs **25**. Spacing between adjacent LEDs **25** within the same string and adjacent LEDs **25** within different strings has been maximized to minimize the amount of light absorbed by adjacent LEDs. In one aspect, LED device **95** can comprise previously illustrated first pattern **P1** (FIG. **3A**) as the first and last strings. The second and seventh strings can comprise pattern **P2**, and the third through sixth strings can comprise pattern **P3**. Notably, LEDs **25** of patterns **P1**, **P2**, and **P3** extend at least substantially the full length and width of conductive pad **30**. LEDs **25** of **P1**, **P2**, and **P3** can be spaced further apart horizontally and/or vertically such that an amount of light blocked by adjacent LEDs **25** can be decreased. In one aspect, pattern **P1** spacing has been increased at least approximately 41%, or by 225 μm , or greater in the horizontal direction and by at least approximately 27%, or by 210 μm , or greater in the vertical direction from **P1** in LED device **10** to **P1** in LED device **95**. Similarly, horizontal and/or vertical spacing between LEDs **25** in pattern **P2** can be increased at least approximately 4% or greater over **P2** in LED device **90**. Intra-string spacing i.e., spacing between LEDs **25** of adjacent strings can be increased by at least approximately 68%, or by 750 μm , or greater in LED device **95**. Notably, although LED device **95** can comprise the same number of LEDs **25** as LED device **90**, e.g., 112 LEDs, LED device **95** can have at least an approximate 1% to 2%, or greater, increase in efficiency and brightness when compared to LED device **90**.

In one aspect, LED devices **10**, **60**, **70**, **80**, and **90** disclosed by FIGS. **3A**, **3B**, and **11** to **14B** can comprise a large quantity of LEDs **25** arranged in one or more patterns over conductive pad **30**. In one aspect, LED devices disclosed herein comprise a quantity of more than 64 LEDs **25**. For example, in one aspect and without limitation, LED device **10** can comprise 140 total LEDs, or **10** strings of LEDs **25** electrically connected in series. LED device **60** can comprise 150 total LEDs, or **30** strings of five LEDs **25** electrically connected in series. LED device **70** can comprise 70 total LEDs, or five strings of 14 LEDs **25**. LED device **80** can comprise 84 total LEDs, or six strings of 14 LEDs **25**. LED device **90** can comprise 112 total LEDs, or eight strings of 14 LEDs **25**. LEDs **25** used in

20

LED devices described herein can comprise a small footprint, or surface area when compared to conductive pad **30**. For example and without limitation, LEDs **25** can comprise chips of the following dimensions in Table 1 below:

TABLE 1

	Length (μm)	Width (μm)
LED chip size	350	470
	230	660
	500	500
	520	700

In one aspect and without limitation, conductive pad **30** can comprise a radius of approximately 6.568 mm and an area of approximately 135.5 mm^2 . Thus, the ratio of the area of a single LED chip **25** and the area of conductive pad **30** can comprise approximately 0.0027 or less. In one aspect, the ratio of the area of a single LED chip **25** and the area of conductive pad **30** can comprise approximately 0.0018 or less. In other aspects, the ratio can comprise approximately 0.0012 or less. Table 2 below lists various LED **25** chip sizes and the area of conductive pad **30**. LEDs **25** can comprise chips that are small compared to the area of conductive pad, that is, approximately 0.0027 of the area of the conductive pad or less. Any chip size can be used however.

TABLE 2

Chip Size (μm)	Conductive Pad Area (mm^2)	Ratio of Chip Area to Conductive Pad Area
350 \times 470	135.5	0.0012
230 \times 660	135.5	0.0011
500 \times 500	135.5	0.0018
520 \times 700	135.5	0.0027

Using a large quantity of LEDs **25** comprising a smaller footprint over a single emission area can advantageously allow for more uniform light output in addition to desirable optical properties such as high brightness as the LEDs **25** can be arranged into one or more uniform patterns over a portion of emission area **16**. The concentrated patterns of LEDs **25** can allow for concentrated light emission. In one aspect, the density or spacing of LEDs **25** in the one or more patterns described herein can be adjusted such that light will not be absorbed or blocked by adjacent LEDs **25**. That is, patterns and arrangements of LEDs **25** disclosed herein may improve light extraction by minimizing the amount of light absorbed by adjacent or neighboring LEDs **25**. The number of LEDs **25** per string can allow LED devices to be operable at low to high voltages. For illustration purposes, four patterns have been illustrated. However, any suitable pattern of LEDs **25** is contemplated. Each string of LEDs **25** can comprise a single pattern or a combination of more than one pattern.

FIGS. **15A** and **15B** illustrate methods of die attach that can, for example and without limitation, be used for LED devices according to the disclosure herein. LED **25** can comprise a backside metal pad or bonding layer **100** for mounting over conductive pad **30**. Bonding layer **100** can comprise a length of the entire bottom surface LED **25** or a portion thereof. For illustration purposes, bonding layer **100** is illustrated as having a same length as the entire bottom surface of LED **25**, however, any configuration is contemplated. LED **25** can comprise lateral sides **104** which can extend between an upper surface and the bottom surface of LED **25**. FIGS. **15A**

and 15B illustrate inclined lateral sides 104, however, lateral sides 104 can be substantially vertical or straight where a straight-cut LED is selected. FIGS. 15A and 15B illustrate LEDs 25 having an upper surface of a greater surface area than an area of bottom surface comprising bonding layer 100. However, upper surface can be of a smaller surface area than the surface area of bonding surface. LEDs 25 can comprise a square, rectangle, or any suitable shape in addition to having any suitable lateral side configuration.

Any suitable die attach method can be used to mount LED 25 over conductive pad 30 in any of the LED devices previously described. In one aspect, any suitable optimized die attach method and/or materials can be used. For example, optimized die attach methods can comprise metal-to-metal die attach methods for facilitating attachment of one or more metals on and/or between LED 25 and conductive pad 30. FIG. 15A illustrates an example of a metal-to-metal die attach method which can be eutectic or non-eutectic. This metal-to-metal die attach method can comprise using an assist material 106 to facilitate the metal-to-metal die attach. In one aspect, a flux-assisted eutectic metal-to-metal die attach method can be used and in other aspects a metal-assisted non-eutectic metal-to-metal die attach method can be used. In a flux-assisted eutectic, or flux eutectic, die attach method, bonding layer 100 can comprise a metal alloy having a eutectic temperature, for example, but not limited to, an alloy of gold (Au) and tin (Sn). For example, bonding layer 100 can comprise an 80/20 Au/Sn alloy having a eutectic temperature of approximately 280° C. In the flux eutectic technique, assist material 106 can comprise a flux material. In the non-eutectic technique, assist material 106 can comprise a metallic material as well as an adhesive such as silicone or epoxy. The assist material 106 can comprise a conduit for facilitating the metal-to-metal die attach between the bonding layer 100 and conductive pad 30 when the bonding layer 100 is heated above the eutectic temperature. The metal of bonding layer 100 can flow into and attach to the metal of conductive pad 30. The metal of bonding layer 100 or can atomically diffuse and bond with atoms of the underlying mounting conductive pad 30. In one aspect, flux used in a flux-assisted eutectic method can comprise a composition, for example, 55-65% rosin and 25-35% polyglycol ether in addition to small amounts of other components. Any suitable flux material can be used however.

Flux-assisted eutectic die attach methods can be tedious, and it is unexpected to use such methods when attaching a large quantity of LEDs 25 in predetermined arrangements and/or an array. Flux eutectic die attach according to the present subject matter can comprise dispensing flux assist material 106, that can be liquid at room temperature, in an amount to be precisely the right volume to avoid either floating of the LEDs 25 or poor die attach if too much or too little flux is used. Flux-assisted eutectic die attach according to the present subject matter can also require the right composition for each of the flux assist material 106 and bonding metal 100 of the emitter chips. Flux-assisted eutectic die attach according to the present subject matter can optimally utilize a very clean and flat surface and substrates or submounts that do not move or bend during heating and cooling such to stress the solder joint. Flux-assisted eutectic according to the present subject matter can utilize a fine surface roughness that is small enough not to encumber the Au/Sn bonding surface of the emitter chips while being rough enough to allow flux to escape during heating. The heating profile can be matched perfectly to the bonding metal 100, such as Au or AuSn, to ensure a good weld between the bonding metal 100 and underlying conductive pad 30. Using flux-assisted eutectic

for die attach according to the present subject matter also can utilize an inert atmosphere, such as a nitrogen atmosphere, to reduce oxygen gas (O₂) levels and also allow gravity to apply a downward force on LEDs 25. This can reduce the amount of oxidation at the metal-to-metal bond between bonding layer 100 and underlying conductive pad 30.

Still referring to FIG. 15A, a non-eutectic metal-to-metal die attach method can be used which can also comprise an assist material 106, wherein the assist material 106 can comprise a metallic material. In this aspect, bonding layer 100 can comprise a single metal or a metal alloy. For example, bonding layer 100 can comprise Au, Sn, or AuSn. In non-eutectic methods, the bonding layer does not need to reach or exceed a temperature, for example, a eutectic temperature. In this aspect, assist material 106 can comprise a metallic, silicone, or epoxy material to facilitate the metal-to-metal bonding. For example, assist material 106 can comprise AuSn paste, silicone adhesive, or Ag epoxy. Any suitable adhesive or assist material 106 can be used. The metal of bonding layer 100 can attach to the adhesive or metal of the assist material 106, where the assist material is metal. The metal of the assist material 106 can also attach to the metal of conductive pad 30. In one aspect, a metal “sandwich” forms between bonding layer 100, assist material 106, and conductive pad 30 in non-eutectic metal-to-metal attach techniques where a metallic assist material 106 is used. Metal-assisted, non-eutectic die attach can be tedious, just as flux-assisted methods, and it is also unexpected to use such methods when attaching LEDs 25 within one or more patterns for LED devices described herein. Metal-to-metal attachment using an assist material 106 can be hard to control and tedious when attaching multiple small footprint LEDs within a device.

FIG. 15B illustrates a metal-to-metal die attach technique which does not require an assist material 106. One such method can comprise a thermal compression die attach method wherein the metal of bonding layer 100 will directly attach to the metal of conductive pad 30. The thermal compression method can be eutectic or non-eutectic. In one aspect, thermal compression can be used when bonding layer 100 comprises an alloy having a eutectic temperature. In other aspects, bonding layer 100 can comprise a metal not having a eutectic temperature. Conductive pad 30 can comprise any suitable metal, not limited to a Cu, Al, Ag, or Pt layer within a metal core printed circuit board (MCPCB). Bonding layer 100 comprises any suitable metal. In one aspect, bonding layer 100 can comprise a layer of Sn having any suitable thickness. In one aspect, bonding layer 100 can comprise a thickness greater than approximately 0 μm. In one aspect, bonding layer 100 can comprise a bonding layer equal to or greater than at least approximately 0.5 μm. In one aspect, bonding layer 100 can comprise a layer of Sn having a thickness of at least equal to or greater than approximately 2.0 μm. Unlike the flux-assisted eutectic or metal-assisted non-eutectic methods just described, thermal compression metal-to-metal die attach techniques can utilize an external downward force F as illustrated in FIG. 15B.

Force F can comprise a compression delivered in a heated environment, thus deemed a thermal compression, as opposed to dispensing a flux or metallic assist material 106. The thermal compression technique is an alternative die attach method developed to reduce metal squeeze out along the conductive pad 30 which can form Shottky or shunt defects and allow subsequent leakage of current and other various and related problems. In one aspect, the bonding temperature in thermal compression techniques can be approximately 255-265° C. after optionally subjecting conductive pad 30 to a pre-heat treatment or process. Conductive

pad **30** can be heated to a mounting temperature of at least 20° C. above the melting temperature of the bonding layer **100**. The bonding time can be approximately 300 msec and the bonding force can be approximately 50+/-10 grams (g). Pre-determined settings can be important for this method, including adequate preheat, bonding temperature, bonding time, and bonding force. The equipment and predetermined settings for use with thermal compression methods can be difficult to use and/or maintain, and it is unexpected to use such methods when attaching a large quantity of LEDs **25** in an array and/or one or more patterns. Metal-to-metal methods for attaching an array of LEDs in LED devices is not known and is unexpected to use flux-assisted eutectic, metal-assisted non-eutectic, or thermal compression die attach techniques for attaching one or more strings of LEDs **25** in an array or pattern arrangement.

FIG. **16** is a cross-sectional view of a portion of a light emitting device, or LED device, generally designated **110**. LED device **110** can be similar in form and function to any of the devices previously described herein (e.g., 10, 50, 55, 60, 70, 80, 85, 90, and 95). In one aspect, LED device **110** comprises a submount **12** over which a retention material **14** and a light emission area **16** can each be disposed. In one aspect, retention material **14** can be dispensed about light emission area to dam, enclose, or support filling material **40** disposed within emission area **16**. For example, emission area **16** can comprise one or more LEDs **25** disposed under filling material **40**. The LEDs **25** can electrically and/or thermally communicate with one or more layers of submount **12**. In one aspect, a plurality of LEDs **25** can be disposed over submount **12**. The plurality of LEDs **25** can be electrically connected in series, parallel, combinations thereof, and can also be arranged in one or more patterns or arrays as previously described. Emission area **16** can further comprise a fillet member or fillet **112** at least partially disposed about the LEDs **25** and along one or more edges of emission area **16**. The term "fillet" can be broadly defined as a strip or band of material which can be any size (e.g., any width and/or thickness) and can comprise any straight, concave, and/or convex surfaces for placement between one or more portions of device **110**. In one aspect, the fillet **112** can comprise a narrow or thin band of material placed between one or more portions of device **110** thereby bridging the one or more portions of device **110**.

One or more portions of fillet **112** can be at least partially covered by filling material **40**. Fillet **112** can, for example and without limitation, be arranged along an edge of emission area **16** that is disposed inboard and spaced apart from retention material **14** (FIG. **16**) or inboard and directly adjacent retention material **14** (FIG. **17**). That is, fillet **112** can be disposed between a portion of one or more LEDs **25** and portions of retention material **14** and between a portion of the one or more LEDs **25** and the outermost edge of device **110**. Fillet **112** can be disposed directly adjacent one or more portions of one or more layers of submount **12** (e.g., solder mask **32** layer, dielectric layer **36**, or core layer **38** as shown in FIG. **16**). In other aspects, retention material **14** can be formed such that it forms and comprises an integral outer edge portion **115** that can be an extension of retention material **14** and shaped like a fillet (FIG. **18**). Fillet **112** can also be disposed between outermost LEDs **25** and portions of conductive trace **33**, portions of solder mask **32**, and/or portions of dielectric layer **36**. Notably, fillet **112** can comprise a clear or reflective material for increasing the reflectivity of light, thereby increasing brightness of LED device **110**. Fillet **112** can also advantageously reduce and/or eliminate defects that occur during introduction of filling material **40**. In one aspect,

defects such as bubbles can occur during application (e.g., dispensing) of filling material **40**. Such defects can block and/or interfere with light emitted from the LEDs **25**. Fillet **112**, therefore, advantageously reduces and/or eliminates defects occurring during encapsulation thereby improving the performance of device **110**. In one aspect, fillet **112** can advantageously allow for a more uniform encapsulant or filling material **40** as a result of fewer defects.

As previously described, filling material **40** can comprise an encapsulant having a predetermined, or selective, amount of phosphors and/or lumiphors in an amount suitable for any desired light emission, for example, suitable for white light conversion. Filling material **40** can interact with light emitted from the plurality of LEDs **25** such that a perceived white light, or any suitable and/or desirable wavelength of light, can be observed. Any suitable combination of encapsulant and/or phosphors can be used, and combinations of different phosphors for resulting in desired light emission or color points can be used. Filling material **40** can be filled to any level within emission area **16**, for example, a level that is substantially flush with a top surface of retention material **14** (as illustrated) or to any level above and/or below the top surface of retention material **14**.

In one embodiment, bubbles, or other defects, can occur during encapsulation (e.g., application of filling material **40**) at sharp, cornered edges of devices due to improper filling. For example, bubbles can occur along one or more sharp edges of substrate **12** or other mounting surfaces (e.g., conductive pad **30**, FIG. **7**) within emission area **16** as the substantially viscous encapsulant or filling material **40** can improperly fill such areas. Bubbles or other light affecting defects can form and float up as filling material **40** disperses or moves into areas with sharp corners. Bubble defects can block and/or improperly deflect light thereby hindering brightness and other optical properties of such LED devices. Notably, introduction of fillet **112** can effectively seal and/or substantially reduce the height of sharp corners or edges within emission area **16** thereby improving flow of filling material **40** to such areas. This can eliminate and/or substantially reduce the occurrence of bubbles. As such, fillet **112** can advantageously increase brightness and/or performance of device **110** by reducing defects occurring during encapsulation.

Fillet **112** can also increase brightness and/or performance of device **110** by adding another surface from which light can be reflected. In one aspect, fillet **112** can comprise a substantially curved or concave upper surface **114** for improving flow of filling material **40** during encapsulation. Fillet **112** can also in one aspect comprise a substantially triangular shaped cross-section with orthogonal sides formed adjacent curved upper surface **114** such that at least a portion of the cross-section forms a right-angle for effectively filling, or sealing, sharp corners within emission area **16**, as shown for example in FIG. **16**. In one aspect, any bubbles that may occur in fillet **112** can pop or burst because the volume of fillet **112** is small. The fillet **112** can be cured, or partially cured, before encapsulation (e.g., before dispensing filling material **40**). As such, bubbles cannot form in the encapsulant **40** with the fillet **112** in place. In one aspect, fillet **112** can comprise the same material as filling material **40** and/or retention material **14**. In some aspects, fillet **112** can be dispensed simultaneously at the same time and at the same processing step at which retention material **14** can be dispensed or formed.

Still referring to FIG. **16**, LED device **110** or devices and methods in accordance with the disclosure herein can comprise providing submount **12** and providing LEDs **25** over submount **12** and electrically connected in series or parallel

25

via wirebonds 26. Wirebonds 26 can supply electrical current from electrically conductive traces 33 and 34. Providing LED device 110 can comprise dispensing retention material 14 at least partially about the one or more LEDs 25 and over the submount 12 and in any desired shape (e.g., such that emission area 16 and retention material 14 comprise any regular, irregular, or asymmetrical shape). Retention material 14 can be dispensed over, and thereby cover at least a portion of one or more wirebonds 26. After dispensing retention material 14 and prior to filling emission area 16 with filling material 40, the clear or reflective fillet 112 can be dispensed and optionally cured to prevent bubbles from forming during encapsulation. In one aspect, fillet 112 can comprise a clear silicone material. In other aspects, fillet 112 can comprise the same encapsulant material used for filling material 40 and/or retention material 14. In further aspects, fillet 112 can comprise a clear silicone material having a reflective material added thereto.

For example and without limitation, fillet 112 can comprise silicone and any additional reflective material or reflective particulate material such as titanium dioxide (TiO₂) particles or aluminum oxide (Al₂O₃) particles. Fillet 112 can comprise the same material as retention material 14 and can optionally be simultaneously formed (e.g., dispensed) with retention material 14 in a same processing step. LED device 110 can be encapsulated with a silicone encapsulant (e.g., filling material 40) typically containing phosphor after dispensing and optionally curing fillet 112. Fillet 112 can further improve wetting to dissimilar or otherwise incompatible materials and can improve adhesion within the portions of submount 12. For example, where submount 12 comprises an FR-4 dielectric material, an adhesive material can be used to laminate portions of dielectric layer 36 to core layer 38. As known in the art, such adhesive materials can contain an epoxy which may have residual amine groups which can poison some Pt-cured silicone materials typically used for encapsulation. Notably, fillet 112 can therefore provide a barrier as well as an intermediate layer which is compatible to both epoxy and silicone materials which can improve adhesion within the submount 12 and which can prevent poisoning of Pt-cured silicone materials used for encapsulation (e.g., a Pt-cured silicone filling material 40).

As noted above, submount 12 can, for example and without limitation, comprise an FR-4 dielectric laminate panel which can differ slightly from that of previously described devices (e.g., FIG. 7), as the dielectric material can be less than fully disposed over the base layer, and as the dielectric material can comprise a FR-4 laminate panel which can be different from layers of the previously described MCPCB. For example, submount 12 can comprise a base or core layer 38, a dielectric layer 36, at least one conductive trace 33, and one or more layers of solder mask 32. Submount 12 can also comprise a bonding layer (not shown) such as epoxy which can be disposed between portions of dielectric layer 36 and core layer 38 and/or portions of core layer 38 and one or more reflection layers 116. A second conductive trace (e.g., 34) can be disposed on the opposite side of LED device 110, and is not shown (e.g., see location of 34 in FIG. 7). Core layer 38 can comprise a base metal material, for example and not limited to, an Al or Al-alloy material. In one aspect, core layer 38 can comprise Al or Al-alloy that can be approximately 0.5 millimeters (mm) to 1.6 mm thick. Any sub-range of thickness between 0.5 mm and 1.6 mm is contemplated, for example, approximately 0.5-0.8 mm; 0.8-1.2 mm; or 1.2-1.6 mm of Al or Al-alloy can be used. Thicknesses less than approximately 0.5 mm and greater than approximately 1.6 mm can also be used and are also contemplated. A mounting surface, such as

26

one or more thin, reflection enhancement layers 116 can be applied to the top surface of core layer 38 to improve light output.

One or more reflection enhancement layer(s) 116 can be formed integral as one piece of submount 12 or can comprise one or more separate layer(s) disposed over portions of core layer 38 of submount 12. In one aspect, the reflection enhancement layer(s) 116 can be at least partially disposed below one or more portions of dielectric layer 36. LEDs 25 can attach to and/or be mounted to reflection enhancement layer(s) 116 using any attachment material or method known in art as previously described herein. In one aspect, LEDs 25 can attach to enhancement layer(s) 116 using adhesive, solder paste, epoxy, flux, and combinations thereof. In one aspect, reflection enhancement layer(s) 116 can be optimized for the silicone interface (e.g., the interface between layers 116 and fillet 112 and layer(s) 116 and filling material 40). In other aspects, reflection enhancement layer(s) 116 can comprise one or more transparent or reflective dielectric layers disposed below LEDs 25 for improving reflectivity, thereby improving brightness. In one aspect, reflection enhancement layer(s) 116 can comprise more than one layer, for example, one or more metal layers adhered to and/or between one or more dielectric enhancement layers via binding materials as known in the art. In one aspect, reflection enhancement layer(s) 116 can have a total thickness of approximately 30 nanometers (nm), however, sub-ranges of thicknesses comprising approximately 1-10 nm; 10-20 nm; 20-30 nm; 30-40 nm; 40-50 nm; and greater than approximately 50 nm are also contemplated herein.

Dielectric layer 36 can comprise a layer of FR-4 dielectric laminate material, portions of which can be attached or applied to core layer 38 and/or reflection enhancement layer(s) 116 via adhesive (e.g., epoxy). In one aspect, dielectric layer 36 comprises an FR-4 laminate that is approximately 100 μ m thick. Other ranges or sub-ranges of thicknesses can be used however, such as 0-50 μ m; 50-100 μ m; 100-150 μ m; or greater than approximately 150 μ m. Any thickness of dielectric layer 36 (e.g., laminate panel) is hereby contemplated. Notably, dielectric layer 36 does not extend over entire core layer 38 as illustrated in FIG. 7, but rather, adheres to areas outside of the outermost LEDs 25A.

Substrate 12 can further comprise one or more electrical elements such as conductive trace 33 (and even an opposing conductive trace). Conductive trace 33 can comprise a layer of Cu or Cu-alloy and can be attached or disposed over dielectric layer 36 via using an adhesive, plating, or any other suitable attachment technique known in the art for connecting Cu trace 33 to dielectric layer 36. For example, FR-4 laminates typically comprise a layer of Cu foil that can be etched according to standard PCB processes. In one aspect, the thickness of conductive trace 33 can be approximately 35 μ m (e.g., approximately 1 ounce (oz.)). However, conductive trace 33 can be thicker and/or thinner than approximately 35 μ m, for example, and can be any sub-range of thicknesses such as approximately 0-35 μ m; 35-55 μ m; 55-75 μ m; or any thickness greater than approximately 75 μ m. Any thickness of Cu components such as conductive traces 33, 34 is hereby contemplated.

In one aspect, conductive trace 33 can be plated with a wirebondable metal or wirebondable metals such as electroless nickel and immersion gold metals (i.e., ENIG) or electroless nickel, electroless palladium, immersion gold metals (i.e., ENEPIG) to improve the bonding or adhesion between wirebonds 26 and trace 33. In other aspects, conductive trace 33 can be used alone without any further plating or coating. In further aspects, conductive trace 33 can be plated or coated

with any other metal or material for improving wirebondability, or adhesion between wirebonds **26** and trace **33**. Substrate **12** can further comprise one or more layers of solder mask **32** disposed over conductive trace **33** such that portions of solder mask **32** adhere directly to portions of conductive trace **33** (i.e., plated or non-plated) and/or directly to portions of dielectric layer **36**. At least one portion of conductive trace **33** can be left uncoated by solder mask **32** such that it is open and exposed for bonding or electrically connecting to one or more wirebonds **26**. Uncovered portions of conductive trace **33** can later become at least partially covered with a portion of retention material **14** as shown. Solder mask **32** can comprise any suitable electrically insulating material. In one aspect, a white solder mask **32** may be preferred for improving the reflectivity of the device.

FIGS. **17** and **18** are cross-sectional views of a portion of a light emitting device, or LED device, generally designated **120**. LED device **120** is also similar in form and function to any of the previously described devices, for example, device **120** can be similar to device **110** with the exception of the placement and/or shape of retention material **14**. For example, FIGS. **17** and **18** illustrate a device **120** wherein retention material **14** can be moved and/or expanded such that it at least partially covers reflection enhancement layer(s) **116**. In further aspects, retention material **14** can comprise an outer edge portion **115** having a curved or concave upper surface which is shaped similar to fillet **112** described herein (FIG. **18**).

Referring to FIGS. **17** and **18**, LED device **120** can comprise an emission area **16** having one or more LEDs **25** disposed over a FR-4 dielectric laminate panel substrate **12** as shown and described in FIG. **16**. The LEDs **25** can be at least partially covered by filling material **40** and surrounded by retention material **14**. As FIGS. **17** and **18** illustrate, retention material **14** can be moved during dispensing and/or comprise an expanded width such that retention material **14** moves closer to outermost LEDs **25A** and is disposed over at least a portion of reflection enhancement layer(s) **116**. For example, in one aspect retention material **14** can be dispensed entirely over the portion of solder mask **32** that is adjacent emission area **16**. Moving retention material **14** at least partially into emission area **16** (e.g., at least partially over mounting surface, layer(s) **116**) of emission area **16** and can advantageously reduce and/or minimize light affecting defects by reducing formation of such defects and/or by providing a surface to which such defects (e.g., bubbles) can adhere to, thereby decreasing the amount of light that becomes deflected or blocked.

Fillet **112** can be used with the moved or widened retention material **14** as illustrated in FIG. **17**, or the moved/widened retention material **14** could be used alone without need for a fillet **112** as illustrated in FIG. **18**. For example, as FIG. **17** illustrates, fillet **112** can be provided directly adjacent retention material **14** via dispensing or otherwise positioning fillet **112** within emission area **16**. As described earlier, fillet **112** can comprise a substantially curved or concave upper surface **114** for improving flow of filling material **40** during encapsulation. As such, fillet **112** can advantageously increase brightness of device **110** by reducing defects occurring during encapsulation. Fillet **112** can also increase brightness of device **110** by adding another surface from which light can be

reflected. As FIG. **18** illustrates, retention material **14** can comprise an outer edge portion **115** shaped substantially similar to fillet **112**. That is, outer edge portion **115** can comprise a substantially triangular shaped cross-section with orthogonal sides formed adjacent a curved upper surface such that at least a portion of the cross-section of portion **115** forms a right-angle for effectively filling, or sealing, sharp corners within emission area **16**. Thus, retention material **14** can advantageously increase brightness of device **120** by reducing defects occurring during encapsulation and can also increase brightness of device **110** by adding another surface or portion **115** from which light can be reflected.

FIG. **19** illustrates a top view of LED device **110** prior to application of filling material **40**. FIG. **19** illustrates fillet **112** disposed inboard of retention material **14** and disposed all the way around or about the perimeter of emission area **16** and LEDs **25**. Fillet **112** can also be disposed and extend only partially around or about the perimeter of emission area **16** and LEDs **25**, and fillet **112** can be disposed in a continuous manner or can comprise a plurality of discontinuous sections. Emission area **16** can comprise a single, uniform area with a plurality of LEDs **25** wirebonded in series over reflection enhancement layer(s) **116**. In one aspect, LED device **110** can comprise a single string of LEDs **25** electrically connected in series over substrate **12**, where the string can comprise more than one row of LEDs **25** and can extend across a larger portion of substrate **12** than previously illustrated devices having strings extending across the emission area **16** in a single row. Notably, the string of LEDs **25** can connect to smaller openings or exposed portions **118** of conductive traces **33** and **34**. Exposed portions **118** are illustrated in broken lines as such portions can be disposed below retention material **14**. Exposed portions can be created by opening up (e.g., via etching or otherwise) and/or patterning (e.g., via depositing a photoresist layer or otherwise) isolated areas of solder mask **32** such that it will not cover one or more predefined areas of conductive trace(s). Creating one or more isolated areas of exposed portions **118** of conductive traces, such as conductive traces **33** and **34**, as opposed to multiple or large openings (e.g., FIGS. **8**, **10**) can advantageously create a brighter LED device by reducing light interaction with the FR-4 like dielectric laminate material.

Embodiments of the present disclosure shown in the drawings and described above are exemplary of numerous embodiments that can be made within the scope of the appended claims. It is contemplated that the configurations of LED devices and methods of making the same can comprise numerous configurations other than those specifically disclosed.

What is claimed is:

1. A light emitting device, comprising:
 - a submount comprising a planar surface;
 - a light emission area disposed over the submount, wherein the light emission area comprises at least one light emitting diode (LED); and
 - a fillet at least partially disposed about the light emission area, wherein the fillet and the at least one LED are each disposed along the planar surface of the submount.
2. The light emitting device of claim 1, wherein the fillet is clear or reflective.
3. The light emitting device of claim 2, wherein the fillet comprises silicone.
4. The light emitting device of claim 3, wherein the silicone fillet further comprises reflective particulate material such as titanium dioxide (TiO₂) or aluminum oxide (Al₂O₃).

29

5. The light emitting device of claim 1, further comprising filling material, wherein the filling material is disposed over a portion of the light emission area and a portion of the fillet.

6. The light emitting device of claim 5, wherein the filling material comprises a silicone encapsulant containing phosphor.

7. The light emitting device of claim 1, wherein the light emission area comprises at least one string of light emitting diodes (LEDs).

8. The light emitting device of claim 1, wherein the light emission area comprises an array of light emitting diodes (LEDs).

9. The light emitting device of claim 8, wherein the light emission area comprises a plurality of LEDs electrically connected in series.

10. The light emitting device of claim 9, comprising a plurality of strings of LEDs electrically connected in series.

11. The light emitting device of claim 10, wherein electrical ends of the plurality of strings of LEDs are electrically connected to areas of electrically conductive traces.

12. The light emitting device of claim 1, wherein the submount comprises a base material and a dielectric laminate disposed over a portion of the base material.

13. The light emitting device of claim 12, wherein the base material comprises aluminum (Al) or an Al-alloy.

14. The light emitting device of claim 13, wherein the Al or Al-alloy has a thickness of approximately 0.5 millimeters (mm) to 1.6 mm.

15. The light emitting device of claim 12, wherein the submount further comprises a copper (Cu) trace disposed over the dielectric laminate.

16. The light emitting device of claim 15, wherein the submount further comprises a layer of solder mask at least partially disposed over the Cu trace.

17. The light emitting device of claim 12, wherein the submount further comprises at least one reflection enhancement layer disposed between portions of the base material and portions of the light emission area.

18. The light emitting device of claim 17, further comprising a retention material at least partially disposed around the light emission area.

19. The light emitting device of claim 18, wherein the retention material is disposed over a portion of the reflection enhancement layer.

20. The light emitting device of claim 17, wherein the reflection enhancement layer comprises one or more transparent or reflective dielectric layers.

21. The light emitting device of claim 1, wherein the fillet comprises a curved upper surface for reducing defects during encapsulation.

22. The light emitting device of claim 1, further comprising a retention material at least partially disposed around the light emission area.

23. The light emitting device of claim 22, wherein the fillet is disposed in an area between the light emission area and a portion of the retention material.

24. The light emitting device of claim 1, wherein the fillet is disposed in an area between the light emission area and a portion of a conductive trace.

25. A light emitting device, comprising:
a submount comprising a planar mounting surface;
one or more light emitting diodes (LEDs) disposed over the submount;
a fillet disposed over a portion of the submount; and
a filling material disposed over a portion of the one or more LEDs and a portion of the fillet

30

wherein a portion of the fillet is disposed adjacent a portion of the LED along the planar mounting surface of the submount.

26. The light emitting device of claim 25, further comprising a retention material at least partially disposed about the one or more LEDs.

27. The light emitting device of claim 26, wherein the fillet is at least partially disposed between a portion of the retention material and the one or more LEDs.

28. The light emitting device of claim 26, wherein the fillet and retention material are comprised of the same material.

29. The light emitting device of claim 25, wherein the fillet and the filling material are comprised of the same material.

30. The light emitting device of claim 29, wherein the material comprises silicone.

31. The light emitting device of claim 25, wherein the fillet comprises a curved upper surface for reducing defects during encapsulation.

32. The light emitting device of claim 25, wherein the fillet is clear or reflective.

33. The light emitting device of claim 25, wherein the submount comprises a dielectric laminate disposed over a portion of a base material.

34. The light emitting device of claim 33, wherein the base material comprises aluminum (Al) or an Al-alloy.

35. The light emitting device of claim 34, wherein the Al or Al-alloy has a thickness of approximately 0.5 millimeters (mm) to 1.6 mm.

36. The light emitting device of claim 25, wherein the one or more LEDs comprise a plurality of LEDs electrically connected in series.

37. The light emitting device of claim 36, further comprising a plurality of strings of LEDs electrically connected in series.

38. The light emitting device of claim 37, wherein electrical ends of the plurality of strings of LEDs are electrically connected to areas of electrically conductive traces.

39. A light emitting device, comprising:
a submount;
a light emission area disposed over the submount; and
a retention material at least partially disposed around the light emission area;
wherein the retention material comprises an outer edge portion comprising an integrally formed fillet at least partially disposed in the light emission area.

40. The light emitting device of claim 39, wherein the outer edge portion comprises a concave upper surface.

41. The light emitting device of claim 39, wherein the submount comprises a base material and at least one reflection enhancement layer, wherein the reflection enhancement layer is at least partially disposed between portions of the light emission area and portions of the base material.

42. The light emitting device of claim 41, wherein the outer edge portion is disposed over a portion of the reflection enhancement layer.

43. A light emitting device, comprising:
a submount;
a light emission area comprising at least one light emitting diode (LED) disposed over the submount; and
a fillet at least partially disposed about the light emission area;
wherein the fillet is directly adjacent to a portion of the submount; and
wherein a portion of the fillet and a portion of the at least one LED are coplanar along a portion of the submount.

44. The light emitting device of claim **43**, further comprising a retention material disposed about the light emission area.

45. The light emitting device of claim **43**, wherein the fillet is an integral portion of the retention material. 5

46. The light emitting device of claim **43**, wherein the submount comprises a base material and at least one reflection enhancement layer disposed over the base material, at least partially between the base material and the light emission area. 10

47. The light emitting device of claim **46**, wherein the fillet is adjacent to a portion of the reflection enhancement layer.

48. The light emitting device of claim **46**, wherein the submount further comprises a dielectric laminate at least partially disposed over the base material in an area outside of the light emission area. 15

49. The light emitting device of claim **48**, wherein the fillet is directly adjacent to a portion of the reflection enhancement layer and a portion of the dielectric laminate.

50. The light emitting device of claim **43**, wherein the light emission area comprises a plurality of LEDs and a filling material. 20

51. The light emitting device of claim **50**, wherein the filling material comprises an encapsulant having a selective amount of phosphor disposed therein. 25

52. The light emitting device of claim **51**, wherein the fillet comprises a concave upper surface.

* * * * *