



US008622454B2

(12) **United States Patent**
Andretich

(10) **Patent No.:** **US 8,622,454 B2**
(45) **Date of Patent:** **Jan. 7, 2014**

(54) **MOBILE STRUCTURE HAVING SUFFICIENT INTERNAL STRUCTURAL RIGIDITY TO ELIMINATE NEED FOR LOAD-BEARING PERIMETER SUPPORT STRUCTURES**

3,532,299 A	10/1970	Williamson et al.
3,584,911 A	6/1971	Coletto, Jr.
3,596,416 A	8/1971	Hojka
3,633,963 A *	1/1972	Haynes 296/24.31
3,690,080 A	9/1972	Dillard
3,731,644 A	5/1973	Bradt
3,792,557 A	2/1974	Pitts
3,840,267 A	10/1974	Honigman

(76) Inventor: **Micah F. Andretich**, Santa Rosa, CA (US)

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **12/845,062**

CN	2717093 Y	8/2005
CN	2914060 Y	6/2007

(Continued)

(22) Filed: **Jul. 28, 2010**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2011/0025101 A1 Feb. 3, 2011

Website: <http://tinyhouseblog.com/stick-built/first-wind-powered-tiny-house/comment-page-1/#comment-91851> Downloaded Dec. 5, 2009 First Wind Powered Tiny House?

(Continued)

Related U.S. Application Data

(60) Provisional application No. 61/271,925, filed on Jul. 28, 2009.

Primary Examiner — Kiran B Patel

(51) **Int. Cl.**
B60P 3/00 (2006.01)

(74) *Attorney, Agent, or Firm* — Russ Weinzimmer & Associates, P.C.

(52) **U.S. Cl.**
USPC **296/24.3**

(58) **Field of Classification Search**
USPC 296/24.3, 168, 210, 187.12; 180/291, 180/311, 89.1; 52/653.1; 248/237, 48.1, 248/422
See application file for complete search history.

(57) **ABSTRACT**


A mobile structure includes first and second rigid frames and first and second horizontal roof supports supported by the rigid frame. Each of the rigid frames includes a first vertical support, a second vertical support substantially parallel to the first vertical support, and a lateral rigid frame support extending perpendicularly at least from the first vertical support to the second vertical support. The mobile structure further includes a floor under the first and second horizontal roof supports, a wheel-axle assembly under the floor, and leveling assemblies that are extendable away from the floor. Each leveling assembly is in weight-bearing and in-line relationship with respect to one of the vertical supports of the first rigid frame.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,233,181 A *	2/1941	Quartullo	296/25
2,270,161 A	1/1942	Briggs		
2,678,442 A *	5/1954	Ensor	296/173
2,896,996 A *	7/1959	Atwater et al.	296/3
3,503,170 A	3/1970	Shelley		
3,508,305 A	4/1970	Koonce et al.		

15 Claims, 3 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,908,577 A 9/1975 Struyk
 3,961,716 A 6/1976 Renaud
 3,999,775 A * 12/1976 Brongo 280/79.2
 4,023,368 A 5/1977 Kelly
 4,041,974 A 8/1977 Keiser
 4,055,206 A * 10/1977 Griffin 144/285
 4,059,931 A 11/1977 Mongan
 4,149,748 A * 4/1979 Tanner 296/168
 4,151,872 A 5/1979 Slysh et al.
 4,214,555 A * 7/1980 Sawby 119/723
 4,404,465 A 9/1983 Miller
 4,421,943 A 12/1983 Withjack
 4,488,752 A 12/1984 Broussard
 4,526,548 A * 7/1985 Livingston 434/226
 4,555,585 A 11/1985 Behrens et al.
 4,564,002 A 1/1986 Taylor
 4,603,518 A 8/1986 Fennes
 4,627,202 A 12/1986 Esposito
 4,662,146 A 5/1987 Parry
 4,689,926 A 9/1987 McDonald
 4,747,566 A 5/1988 Kiendl
 4,805,355 A 2/1989 Plant
 4,832,002 A 5/1989 Medina
 4,836,395 A * 6/1989 Goutille 220/1.5
 4,856,228 A 8/1989 Robinson, Sr.
 4,883,340 A 11/1989 Dominguez
 4,988,060 A 1/1991 Janson et al.
 5,011,544 A 4/1991 Gaddy et al.
 5,173,052 A * 12/1992 Duncan, Jr. 434/226
 5,174,622 A * 12/1992 Gutta 296/77.1
 5,203,601 A * 4/1993 Guillot 296/77.1
 5,297,844 A * 3/1994 Haustein 296/190.04
 5,379,753 A 1/1995 Noennich
 5,448,861 A 9/1995 Lawson
 5,467,570 A 11/1995 Leek
 5,489,002 A 2/1996 Streiff
 5,658,037 A * 8/1997 Evans et al. 296/98
 5,706,615 A 1/1998 Bridges et al.
 5,706,846 A 1/1998 Sutton
 5,785,280 A 7/1998 Baghdasarian
 5,833,294 A * 11/1998 Williams et al. 296/24.32
 5,833,295 A * 11/1998 Farlow, Jr. 296/22
 5,836,730 A 11/1998 Boydston, IV et al.
 5,890,453 A * 4/1999 Waring-Brown 119/400
 5,906,339 A 5/1999 Basuthakur et al.
 5,918,924 A * 7/1999 Cowan 296/21
 5,938,261 A 8/1999 Faba
 5,969,501 A 10/1999 Glidden et al.
 6,058,869 A 5/2000 Thon
 6,104,910 A 8/2000 Koths
 6,161,339 A 12/2000 Cornett, Sr. et al.
 6,185,878 B1 2/2001 Bullard, III et al.
 6,243,992 B1 6/2001 Gyllenhammar
 6,257,638 B1 7/2001 Graber
 6,302,475 B1 * 10/2001 Anderson 296/175
 6,434,895 B1 * 8/2002 Hosterman et al. 52/143
 6,439,825 B1 * 8/2002 Bonsall 414/537
 6,502,523 B1 1/2003 Robb
 6,583,522 B1 6/2003 McNulty et al.
 6,712,414 B2 3/2004 Morrow
 6,722,357 B2 4/2004 Shingleton
 6,729,678 B1 * 5/2004 Atcravi 296/168
 6,843,027 B2 1/2005 Gaddie et al.
 6,848,442 B2 2/2005 Haber
 6,909,042 B2 6/2005 Geyer et al.
 7,013,829 B1 3/2006 Alexander
 7,017,975 B2 3/2006 Parmer
 7,134,444 B2 * 11/2006 Mintie et al. 135/131
 7,144,020 B2 * 12/2006 Huguet 280/47.34
 7,191,567 B2 * 3/2007 Brandt et al. 52/143
 7,194,842 B2 3/2007 Baird
 7,195,076 B2 * 3/2007 De Vor 168/48.1
 7,249,568 B1 7/2007 Cultrara
 7,273,019 B2 * 9/2007 Towley et al. 114/344
 7,296,808 B2 * 11/2007 Huguet 280/47.34

7,357,440 B1 4/2008 Calandruccio
 7,360,784 B2 4/2008 Stewart et al.
 7,445,275 B2 11/2008 Woodhouse et al.
 7,455,026 B2 * 11/2008 Towley et al. 114/344
 7,487,734 B2 2/2009 Davis
 7,513,250 B2 4/2009 Head et al.
 7,540,546 B2 6/2009 Kern et al.
 D600,200 S 9/2009 Dimov et al.
 7,591,497 B2 * 9/2009 Johns 296/3
 7,677,242 B2 3/2010 Carcangiu et al.
 7,695,049 B2 4/2010 Colborne
 7,712,813 B2 * 5/2010 Di Franco 296/26.14
 7,789,452 B2 * 9/2010 Dempsey et al. 296/173
 7,795,837 B1 * 9/2010 Haun et al. 320/101
 7,810,866 B2 * 10/2010 Dempsey et al. 296/173
 2004/0119853 A1 6/2004 Kokubun et al.
 2006/0277836 A1 12/2006 Chazyn
 2007/0090629 A1 4/2007 Ohnstad et al.
 2007/0125417 A1 6/2007 Johanson et al.
 2008/0040990 A1 2/2008 Vendig et al.
 2008/0142059 A1 6/2008 Bonebrake
 2008/0251115 A1 10/2008 Thompson et al.
 2009/0014054 A1 1/2009 Cano Messeguer et al.
 2009/0277699 A1 11/2009 Wan
 2009/0288698 A1 11/2009 Chen
 2009/0288891 A1 11/2009 Budge
 2010/0018570 A1 1/2010 Cashion et al.
 2010/0043781 A1 2/2010 Jones et al.
 2010/0051086 A1 3/2010 Keshner et al.
 2010/0126554 A1 5/2010 Morgan et al.
 2011/0016803 A1 * 1/2011 Ray 52/90.2

FOREIGN PATENT DOCUMENTS

CN 2923860 Y 7/2007
 CN 201035923 Y 3/2008
 CN 201077365 Y 6/2008
 CN 201118482 Y 9/2008
 CN 201231704 Y 5/2009
 CN 201240399 Y 5/2009
 CN 101451398 A 6/2009
 CN 101487349 A 7/2009
 CN 201319566 Y 9/2009
 EP 1035591 A1 9/2000
 EP 1754845 A1 2/2007
 EP 1995535 A2 11/2008
 EP 2083451 A1 7/2009
 EP 2123993 A1 11/2009
 GB 2240517 A 8/1991
 JP 61266814 A2 11/1986
 JP 03010988 A2 1/1991
 JP 06144131 A2 5/1994
 NL 1026606 C2 1/2006
 WO 8302594 A1 8/1983
 WO 8400803 A1 3/1984
 WO 9108708 A1 6/1991
 WO 2008047146 A1 4/2008
 WO 2008054377 A3 9/2008
 WO 2008129589 A2 10/2008
 WO 2007038760 A3 4/2009
 WO 2009099571 A2 8/2009
 WO 2010010513 A2 1/2010
 WO 2010054496 A2 5/2010

OTHER PUBLICATIONS

Website: <http://www.trafcon.com/pep.html> Downloaded Jun. 18, 2010 Portable Equipment Platform, Solar Powered.
 Website: http://www.rio02.com/proceedings/pdf/151_Koehler.pdf Downloaded Jun. 18, 2010 Photovoltaic-Panels on Greened Roofs.
 Website: <http://en.wikipedia.org/wiki/File:Gemini-house-2001.jpg> Downloaded Jun. 18, 2010 Gemini House rotates in its entirety and the solar panels rotate independently, allowing control of the natural heating from the sun.
 Website: <http://www.youtube.com/watch?v=fv4jifkXR9s> Downloaded Jun. 18, 2010 Freely rotating solar array.
 Website: <http://www.ecofriend.org/entry/e-bike-just-solar-energy-is-enough/> Downloaded Jun. 22, 2010 E-Bike In such E-bikes, pinion

(56)

References Cited

OTHER PUBLICATIONS

seat has been replaced by Solar Panel Array and the two panels fold down once the carrier comes into motion.

Website: <http://www.backwoodshome.com/articles2/yago108.html>
Downloaded Jun. 22, 2010 Solar Power Trailer.

Website: <http://www.answers.com/topic/ferris-wheel> Downloaded Jun. 25, 2010 Transportable Wheels Larger transportable wheels are designed to be repeatedly dismantled and rebuilt, some using water

ballast instead of the permanent foundations of their fixed counterparts.

Website: <http://www.inhabitat.com/2009/04/01/mobile-rolling-stone-eco-capsule-home/> Downloaded Dec. 5, 2009 Rolling Stone Eco-Capsule Home.

Website: <http://www.dezeen.com/2009/10/29/opera-by-axel-enthoven/> Downloaded Dec. 5, 2009 Mobile Holiday Home.

Website: <http://www.emergencyresponsestudio.org/> Downloaded Dec. 5, 2009 Emergency Response Studio.

* cited by examiner




Fig. 1




Fig. 2




Fig. 3

1

**MOBILE STRUCTURE HAVING SUFFICIENT
INTERNAL STRUCTURAL RIGIDITY TO
ELIMINATE NEED FOR LOAD-BEARING
PERIMETER SUPPORT STRUCTURES**

CROSS-REFERENCE TO RELATED
APPLICATIONS

The present application claims the benefit of and priority to U.S. Provisional Patent Application No. 61/271,925, entitled "SUSTAINABLE, MOBILE, EXPANDABLE STRUCTURE," filed Jul. 28, 2009, which application is fully incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

The present invention generally relates to mobile structures, and more particularly to towable mobile structures having substantial living, working, and/or storage space.

BACKGROUND

As used in this application, the term "mobile structure" is intended to encompass any structure, including a living, working, or storage area, that is mobile, i.e., capable of being pulled or towed (e.g., with a hitch). Thus, a "mobile structure," as the term is used herein, includes trailers, campers, recreational vehicles, mobile laboratories, and mobile medical units, among other things.

Mobile structures are typically inferior to more permanent structures. For example, mobile structures typically have less structural stability, fewer floor plan options, and smaller interior space.

To increase the usable interior space, some mobile structures expand when they arrive at their destination. For example, some mobile structures include pop-out rooms or slide-out rooms. However, the size, stability, and accessibility of such pop-out rooms and slide-out rooms is limited.

SUMMARY

In mobile structure embodiments of the present invention a unique configuration of structural framing elements, including rigid frames and leveling assemblies provide, among other things, flexibility in floor plan options, ease of use, and structural stability while minimizing an amount of material used and accommodating expansions areas.

A first general aspect of the invention is a mobile structure with ample interior space unobstructed by structural members. The mobile structure includes: first and second rigid frames, each of the first and second rigid frames including: a first vertical support; a second vertical support substantially parallel to the first vertical support; and a lateral support extending perpendicularly at least from the first vertical support to the second vertical support; first and second horizontal roof supports, the first and second horizontal roof supports being supported by the first and second rigid frames, and being mutually parallel; a floor under the first and second horizontal roof supports; a wheel-axle assembly under the floor; and a first set of leveling assemblies that are extendable down from the floor, each leveling assembly being in weight-bearing and in-line relationship with respect to one of the vertical supports of the first rigid frame.

In a preferred embodiment, the leveling assemblies are extendable to support the mobile structure on a surface when the mobile structure is in a stationary mode, and are retract-

2

able from their extended configuration when the mobile structure is in a transport mode.

In another preferred embodiment, the first rigid frame further includes a lateral floor joist that is substantially parallel to the lateral support, and that extends at least from the first vertical support to the second vertical support.

In another preferred embodiment, the mobile structure further includes a hitch in towing relationship with the floor.

In a further preferred embodiment, the mobile structure further includes a hitch leveling assembly extendable down from the hitch.

In yet another preferred embodiment, the mobile structure further includes at least one vertical roof support extending up from the floor to support one of the horizontal roof supports.

In another preferred embodiment, the mobile structure further includes a second set of leveling assemblies that are extendable down from the floor, each leveling assembly of the second set of leveling assemblies being in weight-bearing and in-line relationship with respect to one of the vertical supports of the second rigid frame.

In another preferred embodiment, the mobile structure includes a first stabilizing frame disposed outside of a space between the first and second rigid frames, the first stabilizing frame supporting and longitudinally stabilizing the first and second horizontal roof supports, the first stabilizing frame having a first vertical roof support and a second vertical roof support substantially parallel to the first vertical roof support, and the first and second vertical roof supports being supported by the floor.

In a further preferred embodiment, the mobile structure includes a second stabilizing frame disposed outside of a space between the first and second rigid frames, and disposed in symmetric relationship with respect to the first stabilizing frame, the second stabilizing frame supporting and longitudinally stabilizing the first and second horizontal roof supports, the second stabilizing frame having a first vertical roof support and a second vertical roof support substantially parallel to the first vertical roof support, and the first and second vertical roof supports of the second stabilizing frame being supported by the floor.

In yet another preferred embodiment, the mobile structure further includes: an eave support assembly supported by the first and second horizontal roof supports, the eave support assembly including: a first longitudinal eave support; a second longitudinal eave support substantially parallel to the first longitudinal eave support; and a plurality of lateral eave supports each extending perpendicularly at least from the first longitudinal eave support to the second longitudinal eave support, the first and second longitudinal eave supports being separated from one another by a distance greater than a distance separating the first and second vertical supports of at least one of the first and second rigid frames.

In a further preferred embodiment, each of the first and second horizontal roof supports includes a truss, the truss including a bottom chord joined to the first and second rigid frames; a top chord disposed above and in parallel with the bottom chord, the top chord being joined to the eave support assembly; and truss members disposed in triangular patterns between the top and bottom truss chords.

In yet another preferred embodiment, an extension distance of at least one of the leveling assemblies of the first set of leveling assemblies is manually adjustable.

In yet another preferred embodiment, an extension distance of at least one of the leveling assemblies of the first set of leveling assemblies is automatically adjustable.

In another preferred embodiment, at least one of the leveling assemblies of the first set of leveling assemblies includes

3

a base plate so as to distribute a load of the mobile structure over an area under the base plate.

In another preferred embodiment, each of the vertical supports of the first rigid frame extends through the floor and is joined in a weight-bearing and in-line relationship to a corresponding one of the leveling assemblies of the first set of leveling assemblies.

A second general aspect of the invention is a mobile structure with ample interior space unobstructed by structural members. The mobile structure includes: first and second rigid frames each including: a first vertical support; a second vertical support substantially parallel to the first vertical support; and a lateral rigid frame support extending at least from the first vertical support to the second vertical support. The mobile structure further includes: first and second horizontal roof supports, the first and second horizontal roof supports being supported by the first and second rigid frames, and being mutually parallel; a floor under the first and second horizontal roof supports, each of the vertical supports of the rigid frames extending through the floor; a wheel-axle assembly disposed under the floor; leveling assemblies that are extendable down from the floor, each leveling assembly being in weight-bearing and in-line relationship with respect to one of the vertical supports of the first and second rigid frames; a hitch in towing relationship with the floor; and an eave support assembly disposed above and supported by the first and second horizontal roof supports. The eave support assembly includes: a first longitudinal eave support; a second longitudinal eave support substantially parallel to the first longitudinal eave support; and a plurality of lateral eave supports each extending perpendicularly at least from the first longitudinal eave support to the second longitudinal eave support, the first and second longitudinal eave supports being separated from one another by a distance greater than a distance separating the first and second vertical supports of at least one of the first and second rigid frames.

In a preferred embodiment, the mobile structure includes: a first stabilizing frame disposed outside of a space between the first and second rigid frames, the first stabilizing frame supporting and longitudinally stabilizing the first and second horizontal roof supports, the first stabilizing frame having a first vertical roof support and a second vertical roof support substantially parallel to the first vertical roof support, and the first and second vertical roof supports being supported by the floor.

In another preferred embodiment, the mobile structure further includes: a second stabilizing frame disposed outside of a space between the first and second rigid frames, and disposed in symmetric relationship with respect to the first stabilizing frame, the second stabilizing frame supporting and longitudinally stabilizing the first and second horizontal roof supports, the second stabilizing frame having a first vertical roof support and a second vertical roof support substantially parallel to the first vertical roof support, and the first and second vertical roof supports of the second stabilizing frame being supported by the floor.

In another preferred embodiment, each of the first and second horizontal roof supports including a truss, the truss comprising: a bottom chord joined to the first and second rigid frames; a top chord disposed above and in parallel with the bottom chord, the top chord being joined to the eave support assembly; and truss members disposed in triangular patterns between the top and bottom truss chords.

In a further preferred embodiment, at least one of the first and second rigid frames further includes a lateral floor joist

4

that is substantially parallel to the lateral support, and that extends at least from the first vertical support to the second vertical support.

Additional features of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by the practice of the invention. The features of the invention may be realized and obtained by means of the instruments and combinations particularly pointed out in the appended claims. These and other features of the present invention will become more fully apparent from the following description and appended claims, or may be learned by the practice of the invention as set forth hereinafter.

BRIEF DESCRIPTION OF THE DRAWINGS

To further clarify the above and other features of the present invention, a more particular description of the invention will be rendered by reference to specific embodiments thereof which are illustrated in the appended drawings. It is appreciated that these drawings depict only typical embodiments of the invention and are therefore not to be considered limiting of its scope. The invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

FIG. 1 is a perspective view of structural framing elements in an example embodiment of a mobile structure;

FIG. 2 is a perspective view of the mobile structure of FIG. 1 and shows additional structural framing elements; and

FIG. 3 is a cross-section perspective view of the mobile structure of FIG. 2.

DETAILED DESCRIPTION

Reference will now be made to the figures wherein like structures will be provided with like reference designations. It is understood that the figures are diagrammatic and schematic representations of presently preferred embodiments of the invention, and are not limiting of the present invention, nor are they necessarily drawn to scale.

Embodiments of mobile structures described herein may provide, among other things, structural elements that provide rigidity and stability under heavy loads while enabling reconfiguration of the mobile structure into different modes of operation and permitting flexible floor plan options. Among the various structural elements is a plurality of rigid frames that use a minimal amount of material and preserve an open interior space while enhancing structural stability by effectively transferring lateral forces to leveling assemblies located directly under and in-line with vertical supports of the rigid frames. An eave support assembly also enhances structural stability by transferring internal and external loads to the rigid frames.

FIGS. 1 and 2 show a perspective view of structural framing elements of an example embodiment **100** of a mobile structure. As depicted in FIG. 1, mobile structure **100** comprises various structural framing elements including, for example, a carriage assembly **102**, rigid frames **104**, stabilizing frames **106**, primary leveling assemblies **112**, and a secondary or hitch leveling assembly **114**. FIG. 2 additionally shows horizontal roof supports **108** and an eave support assembly **110**. Each of the foregoing elements and their relationship to one another are described below.

Mobile structure **100** is a lightweight structure capable of being conveniently airlifted, towed, and/or hauled to any desired location. Carriage assembly **102** provides means for mobile structure **100** to be conveniently towed with the aid of

a motive force, such as a truck, and provides a base on which a working/living space of mobile structure **100** rests. Carriage assembly **102** includes a floor diaphragm (also referred to as “floor”) **102a** mounted to a plurality of transverse joists **102c** (hidden from view by floor diaphragm **102a**), which are in turn mounted to and disposed perpendicular to peripheral carriage longitudinal channels or beams **102b**.

Carriage assembly **102** further includes a hitch **102d**, angled neck beams **102e** joined to carriage longitudinal beams **102b** and meeting at hitch **102d**, a wheel-axle assembly **102f** mounted on an underside of floor diaphragm **102a**, and a fender **102g** mounted over wheels of wheel-axle assembly **102f**. Wheel-axle assembly **102f** may be mounted to longitudinal beams (depicted in FIG. 3 as carriage longitudinal beams **102j** under floor diaphragm **102a**) via a leaf spring suspension **102h**. Floor diaphragm **102a** may include or be joined to a tongue **102i** coextensive therewith and extending outwardly toward hitch **102d**.

Moreover, although wheel-axle assembly **102f** is depicted as having two axles and four wheels, one of ordinary skill will appreciate that a different number of wheels and/or a different number of axles (e.g., one axle and a corresponding pair of two wheels) may be used as different wheel-axle assemblies’ weight limits will permit. Moreover, although carriage assembly **102** is described as including various pieces or parts, a group of some or all of the parts may be formed as one integral piece. Conversely, one or more of the carriage assembly parts may be comprised of various sub-parts. Materials used to make the various parts of carriage assembly **102** may include any suitable materials including, for example, wood, metal (e.g., aluminum, steel), plastic, etc. and joints between parts may be of a type that is suitable for the material used including, for example, mortise and tenon joints or welded joints, etc. Fasteners for the joints may include bolts, nails, screws, rivets, adhesives, etc., as appropriate for the joint type.

Rigid frames **104** and stabilizing frames **106** are joined to and extend upward from carriage assembly **102** to support eave support assembly **110**. Rigid frames **104** also bear lateral loads from wind or other external forces, transferring such forces to the ground via primary leveling assemblies **112**. Although two rigid frames **104** are depicted, additional rigid frames may be included for increased support, particularly for embodiments of mobile structure **100** having relatively larger dimensions.

Rigid frames **104** include a rear rigid frame **104-1** proximate a rear end of mobile structure **100** and a front rigid frame **104-2** proximate a front end of mobile structure **100**. Each of rigid frames **104** includes a lateral floor joist **104a** (visible in FIG. 3), a pair of vertical supports **104b** that run parallel to each other, and a lateral support **104c**. All connections between components of rigid frames **104** are rigid connections, such as welded or bolted connections. By way of example and not limitation, vertical supports **104b** may be separated from each other by a distance of about three to about five feet. Lateral support **104c** and lateral floor beam **104a** of each rigid frame extends at least from one vertical support **104b** of the rigid frame to the other vertical support **104b** of the rigid frame and, optionally, beyond the vertical supports.

Stabilizing frames **106** include a rear stabilizing frame **106-1** proximate a rear end of mobile structure **100** and a front stabilizing frame **106-2** proximate a front end of mobile structure **100**. Each of stabilizing frames **106** supports and longitudinally stabilizes the first and second horizontal roof supports **108**, among other things. Each of stabilizing frames **106** also includes a lateral floor joist **106a** (not shown, but similar

in position to later floor joists **104a** depicted in FIG. 3 of rigid frames **104**) and a pair of vertical roof supports **106b** that run parallel to each other. Moreover, each of stabilizing frames **106** includes lateral supports **106c** and **106d** extending at least from one vertical roof support to the other vertical roof support of the stabilizing frame. All connections between components of stabilizing frames **106** are rigid connections, such as welded or bolted connections.

Rigid frames **104** are disposed centrally over carriage assembly **102** with respect to the more outwardly disposed stabilizing frames **106**. Moreover, stabilizing frames **106** are disposed outside of a space between the first and second rigid frames, and in symmetric relationship with respect to each other. Thus, front stabilizing frame **106-2** and rear rigid frame **104-1** are disposed on opposite sides of and longitudinally in line with front rigid frame **104-2**. Similarly, rear stabilizing frame **106-1** and front rigid frame **104-2** are disposed on opposite sides of and longitudinally in line with rear rigid frame **104-1**. By way of example and not limitation, front and rear rigid frames **104** are spaced apart by a distance of about eight to about sixteen feet, to allow for flexible floor plan options and convenient passage to lateral extension areas that may be deployed in a stationary mode of mobile structure **100**. A distance between rear stabilizing frame **106-1** and rear rigid frame **104-1**, on the other hand, may be smaller, e.g., between about three and about eight feet but not limited to this range of dimensions. A distance between front stabilizing frame **106-2** and front rigid frame **104-2** may also be of the same or a similar distance (i.e., between about three and about eight feet but not limited to this range of dimensions).

Rigid frames **104** may include or may be joined directly to primary leveling assemblies **112**. For example, in one embodiment, vertical supports **104b** of each rigid frame extend through floor diaphragm **102a** of carriage assembly **102** and integrally include primary leveling assemblies **112**. Alternatively, each vertical support **104b** may be sleeved within an upper component of a corresponding primary leveling assembly **112** to a depth of about four to eight inches (but not limited to this range). Vertical supports **104b** may be welded and or bolted to primary leveling assemblies **112** in the sleeved configuration.

In another embodiment, primary leveling assemblies **112** are not joined directly to or integrally part of vertical supports **104b** but each is instead mounted to a beam or support on an underside of floor diaphragm **102a** in weight-bearing and in-line relationship with a corresponding one of vertical supports **104b**. In either embodiment, however, a load transferring effect is similar—loads bearing on vertical supports **104b** of each rigid frame are transferred to the ground via primary leveling assemblies **112** without introducing extraneous torsion on any beams or supports of carriage assembly **102**.

Primary leveling assemblies **112** are extendable away from the underside of floor diaphragm **102a** when configuring mobile structure **100** in its stationary mode. Primary leveling assemblies **112** may be extended long enough to raise the wheels of mobile structure **100** off the ground or so the wheels just touch the ground or in some instances the wheels may add substantial support to the structure. An amount of extension is continuously or discretely variable to accommodate grade elevation variations of a surface on which mobile structure **100** is deployed. Moreover, primary leveling assemblies **112** may include jacks that are manually or automatically extendable and base plates or pads at distal ends thereof to distribute a load of the mobile structure over an area under the base plate. Secondary leveling assembly **114**, located proximate hitch **102d**, is similar in function to primary leveling assemblies **112**, but will typically not need to bear as much weight

and may therefore have a lower weight limit rating than primary leveling assemblies 112.

As depicted in FIG. 2, horizontal roof supports 108 are disposed above floor diaphragm 102a and are joined to rigid frames 104 in a perpendicular relationship with respect to vertical supports 104b and lateral supports/beams 104a/104c of each rigid frame. Horizontal roof supports 108 may include web tension and compression members 108a (also called truss members) and top and bottom chords 108b. As depicted, web tension and compression members 108a are disposed in triangular patterns. Horizontal roof supports 108 are joined (e.g., by bolting or welding) to rigid frames 104 at the intersection of vertical supports 104b and lateral supports 104c.

Horizontal roof supports 108 stabilize the position of each rigid frame 104 with respect to each another and transfer uplift or compression forces generated by lateral loads into vertical supports 104b. Thus, horizontal roof supports 108 provide rigidity to the overall frame of mobile structure 100. For example, without horizontal roof supports 108 rigid frames 104, when subjected to sufficiently strong forces, could buckle or fold. Moreover, distal ends of horizontal roof supports 108 are restrained by vertical roof supports 106b of stabilizing frames 106 to resist external lateral forces in addition to gravity loads. Furthermore, by locating horizontal roof supports 108 in an overhead assembly instead of in walls of mobile structure 100 or some other area that limits floor plan flexibility, open passages are preserved on the sides of mobile structure 100 for use with lateral extension areas.

As further depicted in FIG. 2, eave support assembly 110 positioned and supported above horizontal roof supports 108 includes lateral eave supports 110a, longitudinal stiffeners 110b, longitudinal eave supports 110c, and a roof diaphragm 110f. Eave support assembly 110 provides a base roof structure that is used to transfer roof diaphragm loads to horizontal roof supports 108 and to rigid frames 104 and 106 whether or not additional roof framing, such as sloped rafters, are utilized.

Lateral eave supports 110a are arranged in a parallel relationship and are rigidly joined to horizontal roof supports 108. Longitudinal stiffeners 110b are also arranged in a parallel relationship with respect to each other, but perpendicular to lateral eave supports 110a to provide overturning stability to lateral eave supports 110a.

An on center spacing of lateral eave supports 110a may be, but is not limited to, a dimension of about two feet to about six feet. Moreover, if sloped rafters (or other framing systems) are used they may be supported by eave support assembly 110 and roof diaphragm 110f may be fastened to such sloped rafters (or the like) instead of directly to eave support assembly 110 members 110a, 110b, and 110c, as depicted.

Longitudinal eave supports 110c are arranged in a parallel relationship with respect to each other and with respect to longitudinal stiffeners 110b. Longitudinal eave supports 110c provide a means to transfer shear forces from roof diaphragm 110f and are supported in a cantilevered method by the distal ends of lateral eave supports 110a providing structural flexibility. Longitudinal eave supports 110c are also joined to and support eaves of a roof (not shown) for mobile structure 100. A distance between longitudinal eave supports 110c may be between about six and about ten feet but not limited to this range of dimensions. For example, this distance may vary in accordance with an expected load placed on eave support assembly 110 and/or to accommodate a peaked roof having a desired slope.

Because rigid frames 104 can, in certain embodiments of mobile structure 100, fully support a roof, stabilizing frames 106 or portions thereof may optionally be omitted in those

embodiments. Moreover, rigid frames 104 may be positioned in locations other than those depicted. For example, in one alternative embodiment stabilizing frames 106 may be omitted and rigid frames 104 may be moved, along with primary leveling assemblies 112, to the spaces occupied by stabilizing frames 106. In this alternative embodiment, vertical supports 104b of rigid frames 104 (relocated to outer positions) extend at least partially past lateral supports 104c to restrain movement of horizontal roof supports 108 in a longitudinal direction.

In another alternative embodiment, rear rigid frame 104-1 and its corresponding set of primary leveling assemblies 112 are omitted. In this embodiment, front rigid frame 104-1 and its corresponding set of primary leveling assemblies 112 may be moved toward the front or the rear, as appropriate, to compensate for the omission of rear rigid frame 104-1. Moreover, in a deployed configuration, this alternative embodiment of mobile structure 100 may be configured to rest on wheels of wheel-axle assembly 102f in addition to primary and secondary leveling assemblies 112 and 114.

In a further modification of the immediately foregoing alternative embodiment, front rigid frame 104-1 has a structure similar to stabilizing frames 106. More specifically, vertical supports 104b of front rigid frame 104-1 may extend past bottom chords 108b of horizontal roof supports 108 and an additional lateral support may be included above lateral support 104c. Accordingly, horizontal roof supports 108 in this embodiment are segmented and face-mounted on either side of the modified front rigid frame 104-1, thus forming a pair of trusses on each side of front rigid frame 104-1 (i.e., a total of four trusses).

In another alternative embodiment, a single beam, such as an I-beam or a rectangular or square cross-section beam, is used on each lateral side of mobile structure 100 as horizontal roof supports 108. A beam is typically heavier and stronger, all else being equal, than an open-web truss and, therefore, use of beams for horizontal roof supports 108 may be appropriate in (but not limited to) circumstances in which weight restrictions are more liberal and/or in which larger external forces are expected.

FIG. 3 depicts a cross-section perspective view of one of rigid frames 104 of mobile structure 100 and its surrounding structural elements. Peripheral carriage longitudinal channels 102b are supported by cantilever from transverse joists 102c (hidden from view by floor diaphragm 102a) over interior carriage longitudinal beams 102j. Longitudinal stiffeners 102k provide stability from overturning of transverse joists 102c. Interior carriage longitudinal beams 102j support wheel-axle assembly 102f, and are joined (e.g., via a rigid connection) under floor diaphragm 102a to outer sides of vertical supports 104b of rigid frames 104. Floor diaphragm 102a, transverse joists 102c, peripheral carriage longitudinal beams 102b, and longitudinal stiffeners 102k work in conjunction to transfer floor loads back to rigid frames 104, which in turn transfer the floor loads to a ground surface via primary leveling assemblies 112. Floor loads are transferred to rigid frames 104 at least partially through fasteners (e.g., nails, bolts, or screws) that join floor diaphragm 102a to a top side of lateral floor joists 104a of rigid frames 104. Similar fasteners may also join floor diaphragm 102a to lateral floor joists 106a of stabilizing frames 106 and to transverse joists 102c of carriage assembly 102.

Horizontal roof supports 108, including tension and compression members 108a and top and bottom chords 108b, are also visible in FIG. 3. Although tension and compression members 108a appear to be floating and disconnected from any adjoining structure, this appearance is an artifact due to

the limitations of a cross-section view. As shown in FIG. 2, tension and compression members **108a** are actually formed in triangular patterns and span from one end of horizontal roof supports **108** to the other.

As described above with respect to carriage assembly **102**, any suitable materials may be used to make the various parts of rigid frames **104**, stabilizing frames **106**, horizontal roof supports **108**, eave support assembly **110**, and primary and secondary leveling assemblies **112** and **114**. In addition, various shapes and configurations of materials may be used for the structural framing elements. For example, I-beams, L-beams, C-beams, hollow rectangular or square cross-section beams, solid rectangular or square cross-section beams, or any combination thereof may be used for horizontally, vertically, and/or diagonally oriented supports, beams, or joists. Moreover, parts may be joined by any joint type appropriate for the materials being joined including, e.g., welded joints or mortise and tenon joints, and any suitable joint fasteners may be used, such as bolts, nails, screws, rivets, adhesives, etc.

U.S. Provisional Patent Application No. 61/271,925, entitled "SUSTAINABLE, MOBILE, EXPANDABLE STRUCTURE," filed Jul. 28, 2009, describes and depicts a finished mobile structure that uses the structural elements of mobile structure **100** described above. The description in the foregoing provisional application also describes in detail foldable wall panel assemblies that are joined to peripheral carriage longitudinal channels **102b** and foldable roof panel assemblies that are joined to fixed roof panels, which are in turn joined to eave support assembly **110**. The foldable wall panel assemblies and foldable roof panel assemblies may be joined via hinged joints to structural elements or to other elements mounted on the structural elements depicted in FIG. 2. In an expanded mode of mobile structure **100** the foldable wall panel assemblies and foldable roof panel assemblies are unfolded or extended to create expansion sections on lateral sides of mobile structure **100**. However, embodiments of the present invention are not limited to expandable mobile structures of the type described in the above-referenced provisional application. For example, mobile structures built in accordance with the principles described above may have permanently fixed wall and roof panels that do not expand or retract from a central body.

The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. Therefore, the described embodiments are to be considered in all respects only as illustrative and not restrictive. Moreover, the scope of the invention is indicated by the appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

What is claimed is:

1. A mobile structure having sufficient internal structural rigidity to eliminate the need for load-bearing perimeter support structure, the mobile structure comprising:

first and second rigid frames, each of the first and second rigid frames including:

at least two mutually parallel vertical supports; and

mutually parallel lateral roof and floor joist supports each extending perpendicularly between the at least two vertical supports;

a carriage assembly, the carriage assembly supporting a floor diaphragm coupled thereto, the carriage assembly being rigidly coupled to the lateral floor joist supports of each of the first and second frames;

at least two mutually parallel horizontal roof supports supporting a roof diaphragm, the horizontal roof supports

being substantially perpendicular with, and rigidly coupled to, the lateral roof supports of the first and second rigid frames;

a wheel-axle assembly coupled to the carriage assembly under the floor diaphragm; and

at least one set of leveling assemblies configured to support said mobile structure when in a stationary mode, each of the at least one set of leveling assemblies configured to be in weight-bearing and in-line relationship with respect to one of the vertical supports of one of the first and second rigid frames,

whereby whenever the leveling assemblies are extended to and rigidly coupled to the ground, substantially all lateral forces imposed on said mobile structure are transferred to the ground through the one of the first and second rigid frames.

2. The mobile structure of claim **1**, wherein the leveling assemblies are retractable from their extended configuration when the mobile structure is in a transport mode.

3. The mobile structure of claim **1**, further comprising an eave support assembly coupled between the roof diaphragm and the horizontal roof supports, the eave support assembly being in a cantilevered relationship with the horizontal roof supports.

4. The mobile structure of claim **1**, further comprising a hitch coupled to a towing end of the carriage assembly.

5. The mobile structure of claim **1**, wherein the horizontal roof supports are in a cantilevered relationship with the first and second rigid frames.

6. The mobile structure of claim **3**, wherein:

said mobile structure has two sides and two ends, the distance between the sides being its width and the distance between the ends being its length; and

the first and second rigid frames being symmetrically oriented so that the first and second lateral supports of the rigid frames are substantially perpendicular to the sides, and substantially parallel to the ends of said mobile structure, and disposed in a space that is located inside of the length of said mobile structure.

7. The mobile structure of claim **6**, wherein at least the roof lateral supports of the first and second rigid frames do not extend the entire width of said mobile structure, thereby providing room, at least along the sides of said mobile structure for, lateral extension structures supported by at least one of: the eave assembly and the carriage assembly.

8. The mobile structure of claim **6**, further comprising:

at least one stabilizing frame including:

at least two mutually parallel vertical stabilizing supports; and

first and second mutually parallel lateral roof supports; and

a lateral floor joist support,

wherein the first and second lateral roof supports and the lateral floor joist support extend perpendicularly between the at least two vertical stabilizing supports; and

wherein:

the first lateral roof support is rigidly coupled to the horizontal roof supports,

the second lateral roof support is rigidly coupled to the eave support assembly, and

the lateral floor joist support is rigidly coupled to the carriage assembly.

9. The mobile structure of claim **8**, wherein:

the at least one stabilizing frame is disposed outside of a space between the first and second rigid frames, and

11

disposed in substantially symmetric relationship with respect to the first and second rigid frames.

- 10.** The mobile structure of claim **6**, wherein:
the eave support assembly is supported by the first and second horizontal roof supports, the eave support assembly including:
5 a first longitudinal eave support;
a second longitudinal eave support substantially parallel to the first longitudinal eave support; and
a plurality of lateral eave supports each extending perpendicularly at least from the first longitudinal eave support to the second longitudinal eave support,
10 the first and second longitudinal eave supports being separated from one another by a distance greater than a distance separating the first and second vertical supports of at least one of the first and second rigid frames.
- 11.** The mobile structure of claim **10**, wherein each of the horizontal roof supports includes a truss, the truss comprising:
15 a bottom chord rigidly coupled to the lateral roof supports of the first and second rigid frames;

12

a top chord disposed above and in parallel with the bottom chord, the top chord being rigidly coupled to the eave support assembly; and

truss members disposed in triangular patterns between the top and bottom chords.

12. The mobile structure of claim **1**, wherein the horizontal roof supports are solid members.

13. The mobile structure of claim **1**, wherein an extension distance of at least one of the leveling assemblies of the first set of leveling assemblies is automatically adjustable.

14. The mobile structure of claim **1**, wherein at least one of the leveling assemblies of the first set of leveling assemblies includes a base plate so as to distribute a load of the mobile structure over an area under the base plate.

15. The mobile structure of claim **1**, wherein each of the vertical supports of the first rigid frame extends through the floor diaphragm and is directly coupled to a corresponding one of the leveling assemblies of the first set of leveling assemblies.

* * * * *