

US008644206B2

(12) **United States Patent**  
**Krishnaswamy et al.**

(10) **Patent No.:** **US 8,644,206 B2**  
(45) **Date of Patent:** **Feb. 4, 2014**

(54) **AD HOC SERVICE PROVIDER CONFIGURATION FOR BROADCASTING SERVICE INFORMATION**

(75) Inventors: **Dilip Krishnaswamy**, Del Mar, CA (US); **Atul Suri**, San Diego, CA (US)

(73) Assignee: **QUALCOMM Incorporated**, San Diego, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 811 days.

(21) Appl. No.: **11/861,280**

(22) Filed: **Sep. 26, 2007**

(65) **Prior Publication Data**

US 2009/0046676 A1 Feb. 19, 2009

**Related U.S. Application Data**

(60) Provisional application No. 60/956,658, filed on Aug. 17, 2007.

(51) **Int. Cl.**  
**H04H 20/71** (2008.01)

(52) **U.S. Cl.**  
USPC ..... **370/312; 370/338; 370/400; 370/401**

(58) **Field of Classification Search**  
USPC ..... **370/310, 328, 338, 312, 315, 343, 345, 370/351, 389, 400, 401**  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,263,121 A 11/1993 Melsa et al.  
5,301,359 A 4/1994 Van Den Heuvel et al.

5,999,813 A 12/1999 Lu et al.  
6,125,185 A 9/2000 Boesch  
6,295,453 B1 9/2001 Desgagne et al.  
6,650,900 B1 11/2003 Chavez, Jr. et al.  
6,735,417 B2 5/2004 Fonseca et al.  
6,871,071 B2 3/2005 Takao et al.  
6,961,575 B2 11/2005 Stanforth  
6,970,422 B1 11/2005 Ho et al.  
7,003,117 B2 2/2006 Kacker et al.  
7,046,647 B2 5/2006 Oba et al.  
7,110,372 B2 9/2006 Kovacs et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

CN 1342377 A 3/2002  
CN 1360795 A 7/2002

(Continued)

**OTHER PUBLICATIONS**

Sethom et al: "Secure and seamless mobility support in heterogeneous wireless networks" Global Telecommunications Conference 2005, Globecom '05. IEEE St. Louis, MO, USA, Nov. 28-Dec. 2, 2005, Piscataway, NJ, USA, IEEE. vol. 6, Nov. 28, 2005, pp. 34.


(Continued)

*Primary Examiner* — Chi Pham  
*Assistant Examiner* — Weibin Huang  
(74) *Attorney, Agent, or Firm* — Howard Seo

(57) **ABSTRACT**

An ad hoc service provider includes a processing system configured to enable access by one or more mobile clients to a first wireless network via a second wireless network. The processing system is further configured to assemble service information for broadcasting to one or more mobile clients. The service information includes attributes of access to the first wireless network, the access being offered by the ad hoc service provider to one or more mobile clients.

**25 Claims, 5 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

7,123,908 B2 10/2006 Chandler  
 7,161,914 B2 1/2007 Shoaib et al.  
 7,170,878 B2 1/2007 Fukuda  
 7,254,119 B2 8/2007 Jiang et al.  
 7,266,374 B2 9/2007 Kim  
 7,266,383 B2 9/2007 Anderson  
 7,295,532 B2\* 11/2007 Haller et al. .... 370/328  
 7,313,363 B2 12/2007 Davis et al.  
 7,339,915 B2 3/2008 Jakkahalli  
 7,346,167 B2 3/2008 Billhartz et al.  
 7,362,731 B2 4/2008 Vinayakray-Jani  
 7,363,050 B2 4/2008 Nakano  
 7,394,826 B2 7/2008 Cain et al.  
 7,408,929 B2 8/2008 Adachi et al.  
 7,420,952 B2 9/2008 Da Costa et al.  
 7,444,152 B2 10/2008 Wu et al.  
 7,486,651 B2 2/2009 Hagiwara et al.  
 7,496,363 B2 2/2009 Salkintzis  
 7,519,071 B2 4/2009 Thubert et al.  
 7,551,576 B2\* 6/2009 Ahmavaara ..... 370/328  
 7,552,234 B2 6/2009 Thubert et al.  
 7,573,904 B2 8/2009 Pichna et al.  
 7,624,267 B2 11/2009 Huang et al.  
 7,649,872 B2 1/2010 Naghian et al.  
 7,664,049 B1 2/2010 Arrakoski et al.  
 7,680,079 B2\* 3/2010 Jeong et al. .... 370/331  
 7,881,474 B2 2/2011 Sun  
 7,903,817 B2 3/2011 Cam-Winget et al.  
 7,929,460 B2 4/2011 Chen et al.  
 7,933,247 B2 4/2011 Gidwani  
 8,014,368 B2 9/2011 Kim et al.  
 2001/0012757 A1\* 8/2001 Boyle ..... 455/11.1  
 2001/0024443 A1 9/2001 Alriksson et al.  
 2002/0039367 A1\* 4/2002 Seppala et al. .... 370/401  
 2002/0080738 A1 6/2002 Kim et al.  
 2002/0138635 A1 9/2002 Redlich et al.  
 2002/0181447 A1 12/2002 Hashizume et al.  
 2002/0198019 A1 12/2002 Naim et al.  
 2003/0054796 A1 3/2003 Tamaki et al.  
 2003/0101263 A1 5/2003 Bouillet et al.  
 2003/0103521 A1 6/2003 Raphaeli et al.  
 2003/0157951 A1 8/2003 Hasty, Jr.  
 2003/0169697 A1 9/2003 Suzuki et al.  
 2003/0198346 A1 10/2003 Meifu et al.  
 2003/0202476 A1 10/2003 Billhartz et al.  
 2003/0203741 A1 10/2003 Matsuo et al.  
 2003/0212802 A1\* 11/2003 Rector et al. .... 709/228  
 2003/0235174 A1 12/2003 Pichna et al.  
 2004/0001442 A1 1/2004 Rayment et al.  
 2004/0008663 A1 1/2004 Srikrishna et al.  
 2004/0068571 A1 4/2004 Ahmavaara  
 2004/0087268 A1 5/2004 Hatano  
 2004/0171386 A1\* 9/2004 Mitjana ..... 455/452.2  
 2004/0174822 A1 9/2004 Bui  
 2004/0235452 A1 11/2004 Fischer  
 2004/0235481 A1 11/2004 Shimizu  
 2004/0266439 A1 12/2004 Lynch, Jr. et al.  
 2005/0053005 A1 3/2005 Cain et al.  
 2005/0088980 A1 4/2005 Olkkonen et al.  
 2005/0094588 A1 5/2005 Wentink  
 2005/0136834 A1 6/2005 Bonta et al.  
 2005/0138671 A1 6/2005 Love et al.  
 2005/0163078 A1 7/2005 Oba et al.  
 2005/0197098 A1 9/2005 Trossen  
 2005/0228853 A1 10/2005 Yamamura et al.  
 2005/0243719 A1 11/2005 Haverinen et al.  
 2005/0254472 A1 11/2005 Roh et al.  
 2005/0286476 A1 12/2005 Crosswy et al.  
 2006/0005008 A1 1/2006 Kao  
 2006/0007863 A1 1/2006 Naghian  
 2006/0009248 A1 1/2006 Sakamoto et al.  
 2006/0056368 A1 3/2006 Ratiu et al.  
 2006/0064589 A1 3/2006 Taniguchi et al.  
 2006/0092939 A1 5/2006 Duggi et al.  
 2006/0098598 A1 5/2006 Gallagher

2006/0101400 A1 5/2006 Capek et al.  
 2006/0114825 A1 6/2006 McAuley et al.  
 2006/0143026 A1 6/2006 Jagannathan et al.  
 2006/0176852 A1 8/2006 Wu et al.  
 2006/0178149 A1 8/2006 Kamat et al.  
 2006/0215576 A1 9/2006 Yu et al.  
 2006/0217062 A1 9/2006 Saffre et al.  
 2006/0229080 A1 10/2006 Khan et al.  
 2006/0236105 A1 10/2006 Brok et al.  
 2006/0240828 A1 10/2006 Jain et al.  
 2006/0258391 A1 11/2006 Lee  
 2007/0008902 A1 1/2007 Yaramada et al.  
 2007/0042769 A1 2/2007 Thommana et al.  
 2007/0097906 A1 5/2007 Kato  
 2007/0110009 A1 5/2007 Bachmann et al.  
 2007/0111705 A1 5/2007 Zhang et al.  
 2007/0149139 A1 6/2007 Gauvreau  
 2007/0172040 A1 7/2007 Cesarini et al.  
 2007/0206527 A1 9/2007 Lo et al.  
 2007/0220219 A1 9/2007 Bansal et al.  
 2007/0223408 A1 9/2007 Thielke et al.  
 2007/0234061 A1 10/2007 Teo  
 2007/0253376 A1\* 11/2007 Bonta et al. .... 370/338  
 2007/0254614 A1\* 11/2007 Muralidharan et al. .... 455/307  
 2007/0291722 A1 12/2007 Lee  
 2008/0040481 A1 2/2008 Joshi et al.  
 2008/0046542 A1 2/2008 Sano  
 2008/0049689 A1 2/2008 Nakfour et al.  
 2008/0069105 A1 3/2008 Costa et al.  
 2008/0080387 A1\* 4/2008 Wang et al. .... 370/252  
 2008/0081606 A1 4/2008 Cole  
 2008/0089288 A1 4/2008 Anschutz et al.  
 2008/0095134 A1 4/2008 Chen et al.  
 2008/0112355 A1 5/2008 Krishnakumar et al.  
 2008/0112362 A1 5/2008 Korus  
 2008/0165735 A1 7/2008 Chen et al.  
 2008/0192666 A1 8/2008 Koskan et al.  
 2009/0046591 A1 2/2009 Krishnaswamy et al.  
 2009/0046598 A1 2/2009 Krishnaswamy et al.  
 2009/0046644 A1 2/2009 Krishnaswamy et al.  
 2009/0046658 A1 2/2009 Krishnaswamy  
 2009/0046861 A1 2/2009 Krishnaswamy  
 2009/0047930 A1 2/2009 Krishnaswamy et al.  
 2009/0047964 A1 2/2009 Krishnaswamy  
 2009/0047966 A1 2/2009 Krishnaswamy et al.  
 2009/0049158 A1 2/2009 Krishnaswamy et al.  
 2009/0073943 A1 3/2009 Krishnaswamy et al.  
 2009/0125429 A1 5/2009 Takayama  
 2009/0172391 A1 7/2009 Kasapidis  
 2010/0034131 A1 2/2010 Kasapi et al.  
 2010/0173631 A1 7/2010 Kim et al.  
 2011/0019627 A1 1/2011 Krishnaswamy et al.  
 2011/0026477 A1 2/2011 Sinivaara et al.  
 2012/0027001 A1 2/2012 Krishnaswamy et al.

FOREIGN PATENT DOCUMENTS

CN 1435027 A 8/2003  
 CN 1602109 A 3/2005  
 CN 1736041 A 2/2006  
 CN 1741485 A 3/2006  
 CN 1747449 A 3/2006  
 CN 1921418 A 2/2007  
 CN 1929384 A 3/2007  
 CN 1961531 A 5/2007  
 DE 10208689 9/2003  
 DE 1005021315 12/2005  
 EP 1289200 3/2003  
 EP 1445893 A2 8/2004  
 EP 1458151 9/2004  
 EP 1178644 B1 7/2006  
 EP 1677462 A1 7/2006  
 EP 1701486 9/2006  
 EP 1761082 A1 3/2007  
 EP 1775972 A1 4/2007  
 GB 2398462 8/2001  
 GB 2388276 11/2003  
 GB 2408173 5/2005  
 JP 2000115171 A 4/2000

(56)

## References Cited

| FOREIGN PATENT DOCUMENTS |               |            |
|--------------------------|---------------|------------|
| JP                       | 2001275145    | A 10/2001  |
| JP                       | 2002544727    | A 12/2002  |
| JP                       | 2003070068    | A 3/2003   |
| JP                       | 2003101553    | A 4/2003   |
| JP                       | 2003143644    | A 5/2003   |
| JP                       | 2004153529    | A 5/2004   |
| JP                       | 2004519911    | A 7/2004   |
| JP                       | 2004253885    | A 9/2004   |
| JP                       | 2004264976    | A 9/2004   |
| JP                       | 2005500766    | A 1/2005   |
| JP                       | 2005502273    | A 1/2005   |
| JP                       | 2005033808    | A 2/2005   |
| JP                       | 2005176021    | A 6/2005   |
| JP                       | 2005204213    | A 7/2005   |
| JP                       | 2005523666    | A 8/2005   |
| JP                       | 2005295310    | A 10/2005  |
| JP                       | 2005531958    | A 10/2005  |
| JP                       | 2005536131    | A 11/2005  |
| JP                       | 2005348397    | A 12/2005  |
| JP                       | 2005536913    | A 12/2005  |
| JP                       | 2006013811    | A 1/2006   |
| JP                       | 2006502670    | A 1/2006   |
| JP                       | 2006041633    | A 2/2006   |
| JP                       | 2006050224    | A 2/2006   |
| JP                       | 2006505987    | A 2/2006   |
| JP                       | 2006074621    | A 3/2006   |
| JP                       | 2006163793    | A 6/2006   |
| JP                       | 2006197462    | A 7/2006   |
| JP                       | 2006304005    | A 11/2006  |
| JP                       | 2007036828    | A 2/2007   |
| JP                       | 2007074382    | A 3/2007   |
| JP                       | 2007505553    | A 3/2007   |
| JP                       | 2007508781    | A 4/2007   |
| JP                       | 2007116710    | A 5/2007   |
| JP                       | 2007129380    | A 5/2007   |
| JP                       | 2007143066    | A 6/2007   |
| JP                       | 2007522725    | A 8/2007   |
| JP                       | 2007528162    | A 10/2007  |
| JP                       | 2009500958    | A 1/2009   |
| JP                       | 2009500984    | A 1/2009   |
| JP                       | 2009526418    | A 7/2009   |
| JP                       | 4504934       | 7/2010     |
| JP                       | 2010537575    | 12/2010    |
| KR                       | 1020070034060 | 3/2007     |
| RU                       | 2192049       | C1 10/2002 |
| RU                       | 2206177       | C1 6/2003  |
| RU                       | 2273050       | C2 3/2006  |
| RU                       | 2301444       | 6/2007     |
| TW                       | I242937       | B 11/2005  |
| TW                       | I243620       | 11/2005    |
| TW                       | I246005       | B 12/2005  |
| TW                       | I246344       | B 12/2005  |
| WO                       | 9013211       | 11/1990    |
| WO                       | 0069186       | 11/2000    |
| WO                       | WO0199053     | A2 12/2001 |
| WO                       | 02063900      | 8/2002     |
| WO                       | WO0263990     | A1 8/2002  |
| WO                       | WO0271084     | A1 9/2002  |
| WO                       | WO02096132    | A1 11/2002 |
| WO                       | WO03017705    | A1 2/2003  |
| WO                       | WO03090847    | A2 11/2003 |
| WO                       | 2004002208    | A2 1/2004  |
| WO                       | WO2004004226  | A2 1/2004  |
| WO                       | WO2004017549  | A2 2/2004  |
| WO                       | WO2004017568  | A1 2/2004  |
| WO                       | WO2004034219  | A2 4/2004  |
| WO                       | 2004043008    | A1 5/2004  |
| WO                       | WO2004107656  | A1 12/2004 |
| WO                       | WO2005036348  | A2 4/2005  |
| WO                       | WO2005072183  | A2 8/2005  |
| WO                       | 2005086468    | A1 9/2005  |
| WO                       | WO2005088874  | A1 9/2005  |
| WO                       | WO2005109693  | A1 11/2005 |
| WO                       | WO2005116841  | A1 12/2005 |
| WO                       | WO2006000239  | A1 1/2006  |

|    |              |            |
|----|--------------|------------|
| WO | WO2006024343 | A1 3/2006  |
| WO | 2006043902   | 4/2006     |
| WO | WO2006043901 | 4/2006     |
| WO | 2006068878   | A1 6/2006  |
| WO | WO2006061682 | A1 6/2006  |
| WO | WO2006117738 | A1 11/2006 |
| WO | 2007004051   | 1/2007     |
| WO | 2007008751   | A1 1/2007  |
| WO | WO2007008574 | 1/2007     |
| WO | WO2007024932 | 3/2007     |
| WO | WO2007047118 | A2 4/2007  |
| WO | 2007052249   | 5/2007     |
| WO | 2007064249   | 6/2007     |
| WO | WO2007090176 | 8/2007     |
| WO | WO2007091699 | 8/2007     |
| WO | 2008063728   | 5/2008     |
| WO | WO2009026192 | 2/2009     |
| WO | WO2010000870 | A1 1/2010  |

## OTHER PUBLICATIONS

Dimitriadis et al.: "Seamless continuity of real-time video across umts and wlan networks: challenges and performance evaluation" IEEE Personal Communications, IEEE Communications Society, US, vol. 12, No. 3, Jun. 1, 2005, pp. 8-18, XP011134871.

Ashutosh et al.: "Seamless proactive handover across heterogeneous access networks" Wireless Personal Communications, Kluwer Academic Publishers, DO, vol. 43, No. 3, Jun. 28, 2007, pp. 837-855, XP019557974.

Ming et al.: "Ad hoc assisted handoff for real-time voice in IEEE 802.11 infrastructure WLANs" Wireless Communications and Networks Conference, 2004. WCNC. 2004 IEEE Atlanta, GA, USA Mar. 21-25, 2004, Piscaraway, NJ, USA, IEEE, vol. 1, Mar. 21, 2004, pp. 202-206.

Bharat et al.: "Integrating Heterogeneous Wireless Technologies: A Cellular Aided Mobile Ad Hoc Network (CAMA)" Mobile Networks and Applications, Kluwer Academic Publishers, BO, vol. 9, No. 4, Aug. 1, 2004, pp. 393-408, XP019213788.

European Search Report—EP08006429, European Search Authority—The Hague—Nov. 26, 2008.

International Search Report—PCT/US08/072863, International Search Authority—European Patent Office—Dec. 4, 2008.

Written Opinion—PCT/US08/072863, International Search Authority—European Patent Office—Dec. 4, 2008.

Cradlepoint Technology, "CTR350 Mobile Broadband Travel Router: Ethernet, USB Modem Support", Dec. 2008.

Cradlepoint Technology, "CTR500 Mobile Broadband Router: Ethernet, USB, and ExpressCard Modem Support" Dec. 2008.

Fon Wiki Beta, "Alien, Linus and Bill", [http://wiki.fon.com/wiki/alien2%20linus\\_and\\_Bill](http://wiki.fon.com/wiki/alien2%20linus_and_Bill), Feb. 27, 2009.

Fon Wiki Beta, "FON Spot", [http://wiki.fon.com/wiki/FON\\_Spot](http://wiki.fon.com/wiki/FON_Spot).

Kyocera, "KR1 Mobile Router: Technical Specifications" 2006 Kyocera Wireless Corp.

Dilip Krishnaswamy: "AWiMA: an Architecture for Adhoc Wireless Mobile Internet Access" Global Telecommunications Conference, 2008. IEEE Globecom 2008., Nov. 30, 2008, pp. 1-5, XP031370766 IEEE, Piscataway, NJ, USA ISBN: 978-1-4244-2324-8 abstract; figure 1 p. 2, col. 1, paragraph 3—p. 3, col. 2, paragraph 3.3.2; figure 2.

Sengupta S, et al., "Dynamic pricing for service provisioning and network selection in heterogeneous networks" Physical Communication, vol. 2, No. 1-2, 39-43 Mar. 1, 2009, pp. 138-150, XP026110196 ISSN: 1874-4907 [retrieved on Mar. 9, 2009] abstract.

Ying Qiu, Peter Marbach: "Bandwidth Allocation in Ad Hoc Networks: a Price-Based Approach" IEEE Infocom 2003, [Online] Jul. 3, 2003, pp. 1-11, XP002603370 infocom 2003 Retrieved from the Internet: URL:[http://www.ietf.org/infocom/2003/papers/20\\_01.pdf](http://www.ietf.org/infocom/2003/papers/20_01.pdf) [retrieved on Oct. 4, 2010] p. 1, col. 1, line 9, paragraph 1—p. 4, col. 1, line 20, paragraph II. E p. 9, col. 2, line 5, paragraph VIII—p. 11, col. 1, line 18, paragraph IX.

Taiwan Search Report—TW097131335—TIPO—Dec. 12, 2011.

Park, Mirang et al., "A Study of a Seamless User Authentication Protocol on Wireless LAN Systems," Journal of the Information

(56)

**References Cited**

OTHER PUBLICATIONS

Processing Society of Japan, The Information Processing Society of Japan, Jul. 15, 2006, 47(7), pp. 2058-2070.

\* cited by examiner




FIG. 1




FIG. 2





FIG. 3



**FIG. 4**






FIG. 5

1

## AD HOC SERVICE PROVIDER CONFIGURATION FOR BROADCASTING SERVICE INFORMATION

CLAIM OF PRIORITY UNDER 35 U.S.C. §119

The present Application for Patent claims priority to Provisional Application No. 60/956,658 entitled, "METHOD FOR A HETEROGENEOUS WIRELESS AD HOC MOBILE SERVICE PROVIDER" filed Aug. 17, 2007, and assigned to the assignee hereof and hereby expressly incorporated by reference herein.

### FIELD

The present disclosure relates generally to telecommunications, and more specifically to an ad hoc service provider configuration for broadcasting service information.

### BACKGROUND

Wireless telecommunication systems are widely deployed to provide various services to consumers, such as telephony, data, video, audio, messaging, broadcasts, etc. These systems continue to evolve as market forces drive wireless telecommunications to new heights. Today, wireless networks are providing broadband Internet access to mobile subscribers over a regional, a nationwide, or even a global region. Such networks are sometimes referred as Wireless Wide Area Networks (WWANs). WWAN operators generally offer wireless access plans to their subscribers such as subscription plans at a monthly fixed rate.

Accessing WWANs from all mobile devices may not be possible. Some mobile devices may not have a WWAN radio. Other mobile devices with a WWAN radio may not have a subscription plan enabled. Ad hoc networking allows mobile devices to dynamically connect over wireless interfaces using protocols such as WLAN, Bluetooth, UWB or other protocols. There is a need in the art for a methodology to allow a user of a mobile device without WWAN access to dynamically subscribe to wireless access service provided by a user with a WWAN-capable mobile device using wireless ad hoc networking between the mobile devices belong to the two users.

### SUMMARY

In one aspect of the disclosure, an ad hoc service provider includes a processing system configured to enable access by one or more mobile clients to a first wireless network via a second wireless network. The processing system is further configured to assemble service information for broadcasting to one or more mobile clients. The service information includes attributes of access to the first wireless network, the access being offered by the ad hoc service provider to one or more mobile clients.

In another aspect of the disclosure, an ad hoc service provider includes means for enabling access by one or more mobile clients to a first wireless network via a second wireless network. The ad hoc service provider further includes means for assembling service information for broadcasting to one or more mobile clients. The service information includes attributes of access to the first wireless network, the access being offered by the ad hoc service provider to the one or more mobile clients.

In a further aspect of the disclosure, a method of providing service information from an ad hoc service provider config-

2

ured to enable access by one or more mobile clients to a first wireless network via a second wireless network includes assembling service information for broadcasting to one or more mobile clients. The service information includes attributes of access to the first wireless network, the access being offered by the ad hoc service provider to one or more mobile clients.

In yet a further aspect of the disclosure, a machine-readable medium including instructions executable by a processing system in an ad hoc service provider includes code for enabling access by one or more mobile clients to a first wireless network via a second wireless network. The instructions further include code for assembling service information for broadcasting to one or more mobile clients. The service information includes attributes of access to the first wireless network, the access being offered by the ad hoc service provider to one or more mobile clients.

It is understood that other embodiments of the present invention will become readily apparent to those skilled in the art from the following detailed description, wherein various embodiments of the invention are shown and described by way of illustration. As will be realized, the invention is capable of other and different embodiments and its several details are capable of modification in various other respects, all without departing from the spirit and scope of the present invention. Accordingly, the drawings and detailed description are to be regarded as illustrative in nature and not as restrictive.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a conceptual block diagram illustrating an example of a telecommunications system.

FIG. 2 is a conceptual block diagram illustrating an example of the functionality of an ad hoc service provider.

FIG. 3 is a conceptual block diagram illustrating an example of a hardware configuration for an ad hoc service provider.

FIG. 4 is a flowchart illustrating an example of a method for providing service information from an ad hoc service provider.

FIG. 5 is a conceptual block diagram of an exemplary configuration of an ad hoc service provider.

### DETAILED DESCRIPTION

The detailed description set forth below in connection with the appended drawings is intended as a description of various configurations of the present invention and is not intended to represent the only configurations in which the present invention may be practiced. The detailed description includes specific details for the purpose of providing a thorough understanding of the present invention. However, it will be apparent to those skilled in the art that the present invention may be practiced without these specific details. In some instances, well-known structures and components are shown in block diagram form in order to avoid obscuring the concepts of the present invention.

FIG. 1 is a conceptual block diagram illustrating an example of a telecommunications system. The telecommunications system **100** is shown with multiple WWANs **104** that provide broadband access to a network **102** for mobile subscribers. The network **102** may be a packet-based network such as the Internet or some other suitable network. For clarity of presentation, two WWANs **104** are shown with a backhaul connection to the network **102**. However, the number of WWANs providing broadband access to network **102** is

not limited to two WWANs. Each WWAN **104** may be implemented with multiple fixed-site base stations (not shown) dispersed throughout a geographic region. The geographic region may be generally subdivided into smaller regions known as cells. Each base station may be configured to serve all mobile subscribers within its respective cell. A base station controller (not shown) may be used to manage and coordinate the base stations in the WWAN **104** and support the backhaul connection to the network **102**.

Each WWAN **104** may use one of many different wireless access protocols to support radio communications with mobile subscribers. By way of example, one WWAN **104** may support Evolution-Data Optimized (EV-DO), while the other WWAN **104** may support Ultra Mobile Broadband (UMB). EV-DO and UMB are air interface standards promulgated by the 3rd Generation Partnership Project 2 (3GPP2) as part of the CDMA2000 family of standards and employ multiple access techniques such as Code Division Multiple Access (CDMA) to provide broadband Internet access to mobile subscribers. Alternatively, one of the WWANs **104** may support Long Term Evolution (LTE), which is a project within the 3GPP2 to improve the Universal Mobile Telecommunications System (UMTS) mobile phone standard based primarily on a Wideband CDMA (W-CDMA) air interface. One of the WWANs **104** may also support the WiMAX standard being developed by the WiMAX forum. The actual wireless access protocol employed by a WWAN for any particular telecommunications system will depend on the specific application and the overall design constraints imposed on the system. The various techniques presented throughout this disclosure are equally applicable to any combination of heterogeneous or homogeneous WWANs regardless of the wireless access protocols utilized.

Each WWAN **104** has a number of mobile subscribers. Each subscriber may have a mobile node capable of accessing the network **102** directly through the WWAN **104**. The mobile nodes access the WWAN **104** shown in the telecommunications system in FIG. 1 using an EV-DO, UMB or LTE wireless access protocol; however, in actual implementations, these mobile nodes may be configured to support any wireless access protocol.

One or more of the mobile nodes may be configured to create in its vicinity an ad hoc network based on the same or a different wireless access protocol used to access the WWAN **104**. By way of example, a mobile node may support a UMB wireless access protocol with a WWAN, while providing an IEEE 802.11 access point for other mobile nodes that cannot directly access a WWAN. IEEE 802.11 denotes a set of Wireless Local Access Network (WLAN) standards developed by the IEEE 802.11 committee for short-range communications (e.g., tens of meters to a few hundred meters). Although IEEE 802.11 is a common WLAN wireless access protocol, other suitable protocols may be used.

A mobile node that may be used to provide an access point for another mobile node will be referred to herein as a “ad hoc service provider” and is represented in FIG. 1 as a service provider **106**. A mobile node that may use an access point of an ad hoc service provider **106** will be referred to herein as a “mobile client” and is represented in FIG. 1 as a client **108**. A mobile node, whether an ad hoc service provider **106** or a client **108**, may be a laptop computer, a mobile telephone, a personal digital assistant (PDA), a mobile digital audio player, a mobile game console, a digital camera, a digital camcorder, a mobile audio device, a mobile video device, a mobile multimedia device, or any other device capable of supporting at least one wireless access protocol.

The ad hoc service provider **106** may extend its wireless broadband network access service to mobile clients **108** that would otherwise not have access to the network **102**. A server **110** may be used as an “exchange” to enable mobile clients **108** to purchase unused bandwidth from ad hoc service providers **106** to access, for example, the network **102** across WWANs **104**.

An ad hoc service provider **106**, a server **110**, and one or more mobile clients **108** may establish a network that is an ad hoc heterogeneous wireless network. By way of example, a heterogeneous wireless network may include at least two types of wireless networks (e.g., a WWAN and a WLAN). By way of example, an ad hoc network may be a network whose specific configuration may change from time to time or from the formation of one network to the next. The network configuration is not pre-planned prior to establishing the network. Examples of configurations for an ad hoc network may include a configuration as to which members are to be in the network (e.g., which ad hoc service provider, which server, and/or which mobile client(s) are to be included in a network), a configuration as to the geographic locations of an ad hoc service provider and mobile client(s), and a configuration as to when and how long a network is to be established.

For illustrative purposes only, exemplary scenarios of ad hoc networks are described below. Scenario 1: While a mobile subscriber is at an airport on Tuesday 8 am, he may turn on his mobile node (e.g., a laptop computer or a mobile telephone), use it as an ad hoc service provider while he is waiting for his flight, and establish an ad hoc network for thirty minutes. The ad hoc network may include one or more mobile clients (e.g., other laptop computers or mobile telephones) in the vicinity. Scenario 2: On Wednesday 5 pm, while the mobile subscriber is at a hotel, he may use the same mobile node as an ad hoc service provider to form another ad hoc network for four hours, providing its service to the same mobile clients, different mobile clients, or a combination of both. Scenario 3: On Wednesday 5 pm, a different ad hoc service provider may form an ad hoc network at the airport where the first ad hoc service provider was the day before. Because the service providers and clients are mobile, an ad hoc network can be a “mobile” network.

The server **110** may be a centralized server or a distributed server. The centralized server may be a dedicated server or integrated into another entity such as a desktop or laptop computer, or a mainframe. The distributed server may be distributed across multiple servers and/or one or more other entities such as laptop or desktop computers, or mainframes. In at least one configuration, the server **110** may be integrated, either in whole or in part, into one or more ad hoc service providers.

In one configuration of a telecommunications system **100**, the server **110** charges the mobile clients **108** based on usage. For the occasional user of mobile Internet services, this may be an attractive alternative to the monthly fixed rate wireless access plans. The revenue generated from the usage charges may be allocated to the various entities in the telecommunications system **100** in a way that tends to perpetuate the vitality of the exchange. By way of example, a portion of the revenue may be distributed to the ad hoc service providers, thus providing a financial incentive for mobile subscribers to become ad hoc service providers. Another portion of the revenue may be distributed to the WWAN operators to compensate them for the bandwidth that would otherwise go unutilized. Another portion of the revenue may be distributed to the manufacturers of the mobile nodes. The remainder of the revenue could be kept by the server operator that provides the exchange. The server **110**, which may be a centralized

server as shown or a distributed server including multiple servers, may be used to determine how to allocate revenue generated from the mobile clients **108** to the various entities in the telecommunications system **100**.

The server **110** may be implemented as a trusted server. It can therefore be authenticated, for example, using a Public Key Infrastructure (PKI) certificate in a Transport Layer Security (TLS) session between the server **110** and an ad hoc service provider **106**, or between the server **110** and a mobile client **108**. Alternatively, the server **110** may be authenticated using self-signed certificates or by some other suitable means.

Regardless of the manner in which the server **110** is authenticated, a secure session channel may be established between the server **110** and an ad hoc service provider **106**, or between the server **110** and a mobile client **108**, during registration. In one configuration of a telecommunications system **100**, a mobile client **108** may register with the server **110** to set up a user name and password with payment information. An ad hoc service provider **106** may register with the server **110** to notify its desire to provide a wireless access point to the network **102** (e.g., an Internet access point) to mobile clients **108**.

The server **110** may also be used to provide admission control. Admission control is the process whereby the server **110** determines whether to allow an ad hoc service provider **106** to provide service within a geographic location. The server **110** may limit the number of ad hoc service providers **106** at a given location if it determines that additional ad hoc service providers **106** will adversely affect performance in the WWAN. Additional constraints may be imposed by the WWAN operators that may not want its mobile subscribers to provide service in a given geographic location depending on various network constraints.

The server **110** may also be used to manage dynamic sessions that are established between the ad hoc service providers **106** and the mobile clients **108**. In one configuration of the telecommunications system **100**, Extensible Authentication Protocol-Tunneled Transport Layer Security (EAP-TTLS) may be used for Authentication, Authorization and Accounting (AAA) and secure session establishment for a connection initiated by an ad hoc service provider **106** with the server **110** when the ad hoc service provider **106** is mobile and desires to provide service. EAP-TTLS may also be used for a session initiation request by a mobile client **108**. In the latter case, the mobile client **108** is the supplicant, the ad hoc service provider **106** is the authenticator, and the server **110** is the authentication server. The ad hoc service provider **106** sends the mobile client's credentials to the server **110** for EAP-AAA authentication. The EAP-TTLS authentication response from the server **110** is then used to generate a Master shared key. Subsequently, a link encryption key may be established between the ad hoc service provider **106** and the mobile client **108**.

Additional security may be achieved with a Secure Sockets Layer Virtual Private Network (SSL VPN) tunnel between a mobile client **108** and the server **110**. The SSL VPN tunnel is used to encrypt traffic routed through an ad hoc service provider **106** to provide increased privacy for a mobile client **108**. Alternatively, the tunnel may be an IPsec tunnel or may be implemented using some other suitable tunneling protocol.

Once the tunnel is established between the server **110** and the mobile client **108**, various services may be provided. By way of example, the server **110** may support audio or video services to the mobile client **108**. The server **110** may also support advertising services to the mobile client **108**. Other functions of the server **110** include providing routing to and

from the network for mobile client **108** content as well as providing network address translation to and from the network for mobile client **108**.

The server **110** may also provide support for a handoff of a mobile client **108** from one ad hoc service provider **106** to another based on any number of factors. These factors may include, by way of example, the quality of service (QoS) required by each mobile client **108**, the duration of the session required by each mobile client **108**, and the loading, link conditions, and energy level (e.g., battery life) at the ad hoc service provider **106**.

The server **110** also may be used to store a goodness metric for each ad hoc service provider **106**. The goodness metric reflects the level of service an ad hoc service provider **106** has provided during previous access sessions with mobile clients **108**. The server **110** may monitor each session between an ad hoc service provider **106** and a mobile client **108** and update the goodness metric associated with the ad hoc service provider **106** based on one or more factors. The factors may include, but are not limited to, the duration of the access session and the average bandwidth of access to the WWAN **104** provided to the mobile client **108**. Monitored factors may be assigned a value from a range of values for each session. The goodness metric for the session may be the sum or average of these values. As an ad hoc service provider **106** provides more access sessions to mobile clients **108**, the goodness metric associated with the ad hoc service provider may be continually updated by averaging the goodness metrics from prior access sessions. This average may be a straight average or it may be weighted to favor more recent access sessions.

FIG. 2 is a conceptual block diagram illustrating an example of the functionality of an ad hoc service provider **106**. The ad hoc service provider **106** has the ability to bridge wireless links over homogeneous or heterogeneous wireless access protocols. This may be achieved with a WWAN network interface **202** that supports a wireless access protocol for a WWAN to the network **102**, and a WLAN network interface **204** that provides a wireless access point for mobile clients **108**. By way of example, the WWAN network interface **202** may include a transceiver function that supports EV-DO for Internet access through a WWAN **104**, and the WLAN network interface **204** may include a transceiver function that provides an 802.11 access point for mobile clients **108**. Each network interface **202**, **204** may be configured to implement the physical layer by demodulating wireless signals and performing other radio frequency (RF) front end processing. Each network interface **202**, **204** may also be configured to implement the data link layer by managing the transfer of data across the physical layer.

The ad hoc service provider **106** is shown with a filtered interconnection and session monitoring module **206**. The module **206** provides filtered processing of content from mobile clients **108** so that the interconnection between the ad hoc wireless link and the WWAN network interface **202** is provided only to mobile clients **108** authenticated by the server. The module **206** is also responsible for monitoring the sessions between the server and the authenticated mobile clients **108**. The module **206** also maintains tunneled connectivity between the server and the authenticated mobile clients **108**.

The ad hoc service provider **106** also includes a service provider application **208** that (1) enables the module **206** to provide ad hoc services to mobile clients **108**, and (2) supports WWAN or Internet access to a mobile subscriber or user of the ad hoc service provider **106**. The latter function is supported by a user interface **212** that communicates with the

WWAN network interface **202** through the module **206** under control of the service provider application **208**. The user interface **212** may include a keypad, display, speaker, microphone, joystick, and/or any other combination user interface devices that enable a mobile subscriber or user to access the WWAN **104** or the network **102** (see FIG. 1).

As discussed above, the service provider application **208** also enables the module **206** to provide ad hoc services to mobile clients **108**. The service provider application **208** maintains a session with the server **110** to exchange custom messages with the server. In addition, the service provider application **208** also maintains a separate session with each mobile client **108** for exchanging custom messages between the service provider application **208** and the mobile client **108**. The service provider application **208** provides information on authenticated and permitted clients to the filtered interconnection and session monitoring module **206**.

The filtered interconnection and session monitoring module **206** allows content flow for only authenticated and permitted mobile clients **108**. The filtered interconnection and session monitoring module **206** also optionally monitors information regarding content flow related to mobile clients **108** such as the amount of content outbound from the mobile clients and inbound to the mobile clients, and regarding WWAN and WLAN network resource utilization and available bandwidths on the wireless channels. The filtered interconnection and session monitoring module **206** can additionally and optionally provide such information to the service provider application **208**. The service provider application **208** can optionally act on such information and take appropriate actions such as determining whether to continue maintaining connectivity with the mobile clients **108** and with the server, or whether to continue to provide service. It should be noted that the functions described in connection with module **206** and service provider application **208** can be implemented in any given platform in one or multiple sets of modules that coordinate to provide such functionality at the ad hoc service provider **106**.

When the ad hoc service provider **106** decides to provide the ad hoc services, the service provider application **208** sends a request to the server **110** for approval. The service provider application **208** requests authentication by the server **110** and approval from the server **110** to provide service to one or more mobile clients **108**. The server **110** may authenticate the ad hoc service provider **106** and then determine whether it will grant the ad hoc service provider's request. As discussed earlier, the request may be denied if the number of ad hoc service providers in the same geographic location is too great or if the WWAN operator has imposed certain constraints on the ad hoc service provider **106**.

Once the ad hoc service provider **106** is authenticated, the service provider application **208** may advertise service information for the ad hoc service provider. The service provider application **208** may also prompt changes to the advertised service information as conditions change. Interested mobile clients **108** may associate with an Service Set Identifier (SSID) to access the ad hoc service provider **106**. The service provider application **208** may then route authentication messages between the mobile clients **108** with the server **110** and configure the filtered interconnection and session monitoring module **206** to connect the mobile clients **108** to the server once authenticated. During the authentication of a mobile client **108**, the service provider application **208** may use an unsecured wireless link.

The service provider application **208** may manage the mobile client **108** generally, and the session specifically, through the user interface **212**. Alternatively, the service pro-

vider application **208** may support a seamless operation mode with processing resources being dedicated to servicing mobile clients **108**. In this way, the mobile client **108** is managed in a way that is transparent to the mobile subscriber. The seamless operation mode may be desired where the mobile subscriber does not want to be managing mobile clients **108**, but would like to continue generating revenue by sharing bandwidth with mobile clients **108**.

Although not shown, the ad hoc service provider **106** may also include a server application. The server application may be used to enable the ad hoc service provider **106** to function as a server to authenticate mobile clients **108**.

FIG. 3 is a conceptual block diagram illustrating an example of a hardware configuration for an ad hoc service provider. The ad hoc service provider **106** is shown with a WLAN transceiver **302**, a WWAN transceiver **304**, and a processing system **306**. By way of example, the WLAN transceiver **302** may be used to implement the analog portion of the physical layer for the WLAN network interface **202** (see FIG. 2), and the WWAN transceiver **304** may be used to implement the analog portion of the physical layer for the WWAN network interface **204** (see FIG. 2).

The processing system **306** may be used to implement the digital processing portion of the physical layer, as well as the link layer, for both the WLAN and the WWAN network adaptors **202** and **204** (see FIG. 2). The processing system **306** may also be used to implement the filtered interconnection and session monitoring module **206** and the service provider application **208** (see FIG. 2).

The processing system **306** may be implemented using software, hardware, or a combination of both. By way of example, the processing system **306** may be implemented with one or more processors. A processor may be a general-purpose microprocessor, a microcontroller, a Digital Signal Processor (DSP), an Application Specific Integrated Circuit (ASIC), a Field Programmable Gate Array (FPGA), a Programmable Logic Device (PLD), a controller, a state machine, gated logic, discrete hardware components, or any other suitable entity that can perform calculations or other manipulations of information. The processing system **306** may also include one or more machine-readable media for storing software. Software shall be construed broadly to mean instructions, data, or any combination thereof, whether referred to as software, firmware, middleware, microcode, hardware description language, or otherwise. Instructions may include code (e.g., in source code format, binary code format, executable code format, or any other suitable format of code).

Machine-readable media may include storage integrated into a processor, such as might be the case with an ASIC. Machine-readable media may also include storage external to a processor, such as a Random Access Memory (RAM), a flash memory, a Read Only Memory (ROM), a Programmable Read-Only Memory (PROM), an Erasable PROM (EPROM), registers, a hard disk, a removable disk, a CD-ROM, a DVD, or any other suitable storage device. In addition, machine-readable media may include a transmission line or a carrier wave that encodes a data signal. Those skilled in the art will recognize how best to implement the described functionality for the processing system **306**.

The functionality of the processing system **306** for one configuration of an ad hoc service provider **106** will now be presented with reference to FIG. 1. Those skilled in the art will readily appreciate that other configurations of the ad hoc service provider **106** may include a processing system **306** that has the same or different functionality.

Turning to FIG. 1, the processing system in the ad hoc service provider 106 provides a means for enabling access by one or more mobile clients 108 to a first wireless network, represented by a WWAN 104, via a second wireless network, represented by a WLAN comprising the one or more mobile clients 108 and the ad hoc service provider functioning as a wireless access point to the WLAN. The processing system may enable this access by implementing the filtered interconnection and session monitoring module 206 and the service provider application 208, as represented in FIG. 2 to bridge the wireless links associated with the WWAN 104 and the WLAN having different wireless access protocols (e.g., EV-DO and 802.11).

The processing system in the ad hoc service provider 106 may function to establish the wireless access point when authorized by the server 110. When the processing system decides to establish a wireless access point for one or more mobile clients 108, it sends a request to the server 110 for approval. The processing system requests authentication by the server 110 and approval from the server 110 to provide service to one or more mobile clients 108. The server 110 may authenticate the ad hoc service provider 106 and then determine whether it will grant the ad hoc service provider's request. As discussed earlier, the request may be denied if the number of ad hoc service providers in the same geographic location is too great or if the WWAN operator has imposed certain constraints on the ad hoc service provider 106.

Once the ad hoc service provider 106 is authenticated and approved to provide service to one or more mobile clients 108, the ad hoc service provider 106 may advertise its availability to provide access to the WWAN 104 by assembling and broadcasting service information to mobile clients 108 within range of its WLAN transceiver 302. The service information may include parameters for accessing the WLAN established with the ad hoc service provider 106 as a wireless access point as well as attributes of the access to the WWAN 104 offered by the ad hoc service provider 106. The parameters of access to the WLAN may include an ad hoc Service Set Identifier (SSID), supported data rates, data security mechanisms, as well as other parameters used by the mobile client 108 to associate and establish a wireless link with the ad hoc service provider. The SSID may be set to include characters identifying the ad hoc service provider 106 as a mobile node offering access to a WWAN 104.

The attributes of access to the WWAN 104 offered by the ad hoc service provider 106 may include information to enable a mobile client 108 to determine whether the ad hoc service provider 106 is providing sufficient access to the WWAN 104 to meet the needs of the mobile client 108 and to select the ad hoc service provider 106 if acceptable to the mobile client 108. The attributes of access may include the previously discussed goodness metric associated with the ad hoc service provider 106, fee rates of access to the WWAN 104, and/or one or more quality of service parameters. The quality of service parameters include, but are not limited to, an expected data rate of access to the WWAN 104, an expected duration of access to the WWAN 104, a latency of access to the WWAN 104, a frequency of access to the WWAN 104, and an amount of transferred data with respect to the WWAN 104.

The expected duration of access to the WWAN 104 is a user-specified period of time reflecting an amount of time a mobile subscriber anticipates making an ad hoc service provider 106 available at a particular geographic location such as an airport terminal, hotel lobby, sports venue, etc. The expected duration of access may be communicated to the

server 110 when the ad hoc service provider 106 is authenticated and approved by the server 110 to provide access to the WWAN 104.

The expected data rate of access to the WWAN 104 via the wireless link between the ad hoc service provider 106 and the WWAN 104 may vary depending on the wireless access protocol used within the WWAN 104, the signal strength of the wireless link between the ad hoc service provider 106 and the WWAN 104, and the amount of concurrent data traffic within the WWAN 104. The ad hoc service provider 106 may be configured to monitor the average data rate of access to the WWAN 104 available to the ad hoc service provider 106. Based on this average data rate, an expected average data rate of access to the WWAN 104 available to a mobile client 108 through the ad hoc service provider 106 is determined.

The expected average data rate of access to the WWAN 104 may be set as a percentage of the total available data rate available to the ad hoc service provider 106 or it may be set to a user-specified amount by the mobile subscriber offering access through the ad hoc service provider 106. In an alternative configuration, the server 110 may set the expected average data rate when the ad hoc service provider 106 is authenticated and approved to provide service. The server 110 may set the expected average data rate using information received from the ad hoc service provider 106 when approval was requested and based on an agreement reached with the mobile subscriber regarding the level of service to be provided.

Both the expected duration of access and the expected data rate of access to the WWAN 104 are dynamic attributes. For example, the expected duration of access to the WWAN 104 may be set when the ad hoc service provider 106 is authenticated and approved to provide service with the server 110. The expected duration will decrease to reflect the amount of time the ad hoc service provider 106 has been available to provide access to a mobile client 108 since the ad hoc service provider 106 was authenticated and approved by the server 110. Optionally, the mobile subscriber may update the amount of time the mobile service subscriber 106 will be available to provide access. The mobile service subscriber 106 may be required to re-authenticate and request approval from the server 110 to continue providing service once the initially set period to time expires.

The expected data rate of access to the WWAN 104 also may change while the ad hoc service provider 106 is available to provide access. For example, the overall data rate available to the ad hoc service provider 106 may vary due to changes in traffic on the WWAN 104. Similarly, the expected data rate of access may be partially utilized by a first mobile client 108 when subsequent mobile clients 108 seek access to the WWAN 104. The expected data rate of access to the WWAN 104 may be modified to take these changes into account.

The latency and frequency of access to the WWAN 104 refer to operating details of the access offered by the ad hoc service provider to the mobile client. For example, the latency and frequency of access may refer to the latency of packet access, the frequency of packet transmission, the duration of packet transmission, the packet length, etc. available to the mobile client during a given session. Varying these parameters varies the priority associated with associated access sessions available to mobile clients. Accordingly, a mobile client may select access offered by an ad hoc service provider that provides access priority to the WWAN 104 suitable for the applications being used by the mobile client.

The amount of transferred data refers to an amount of data transmitted and/or received by a mobile client when accessing the WWAN 104 during an access session. The amount of

transferred data may indicate the maximum amount of data that a mobile client is permitted to receive and/or transmit via WWAN 104 in a single access session. The amount of transferred data may refer to bytes per session or bytes per a specified period of time.

The fee rate of access to the WWAN 104 is the cost per unit time incurred by a mobile client 108 when accessing the WWAN 104 via a WLAN established by the ad hoc service provider 106. The fee rate may include a range of fee rates covering different periods of time. The fee rate also may include a range of fees associated with different combinations of quality of service parameters discussed above. The fee rate for access to the WWAN 104 may be provided by the server 110 to the ad hoc service provider 106 at the time of authentication and approval for providing access to the WWAN 104. Alternatively, the mobile subscriber may set or adjust the fee rate independent of the server 110.

The processing system 306 may be used to provide means for receiving one or more of the foregoing attributes of access to the WWAN 104 from the server 110. The processing system 306 may execute code to request and/or receive attributes from the server 110. These attributes may include the goodness metric associated with the ad hoc service provider 106 and a fee rate of access to the WWAN 104. The code may be implemented in a standalone application or it may be part of a larger application incorporating other functionality. For example, the code may be executed within the processing system when an ad hoc service provider 106 is authenticated and approved by the server 110 to provide access to the WWAN 104.

The processing system 306 may be used to provide means for dynamically updating one or more attributes of access to the WWAN 104 offered by the ad hoc service provider 106 based on the status of the ad hoc service provider 106. The processing system 306 may execute code to monitor factors affecting one or more attributes and to adjust the attributes based on monitored changes in the factors. As discussed above, such attributes may include the expected duration of access and the expected data rate of access to the WWAN 104. The code may be implemented in a standalone application or it may be part of a larger application incorporating other functionality. For example, the code may be executed within the processing system 306 continuously while the ad hoc service provider 106 is made available to offer access to the WWAN 104.

The processing system 306 in the ad hoc service provider 106 may be configured to provide a means for assembling the service information discussed above for broadcasting to one or more mobile clients 108. The parameters and attributes mentioned above may be stored within the processing system 306. The processing system 306 may execute code to retrieve each of the parameters and attributes and assemble them into a format suitable for broadcasting to one or more mobile clients 108 using the WLAN transceiver 302. For example, a driver for the WLAN network interface 204 may be modified to assemble the parameters and attributes into a beacon frame that is subsequently transmitted using WLAN transceiver 302.

Beacon frames are a common feature in wireless access protocols to notify mobile nodes within a specified range of the availability of a wireless network access point. A beacon frame may include fields whose contents are dictated by the wireless access protocol as well as fields that are vendor-specific or user-specific to allow for custom applications. The parameters of access to the WLAN may be automatically incorporated into fields of the beacon frame specified by the wireless access protocol used within the WLAN. The pro-

cessing system 306 may be configured to incorporate one or more of the attributes of access to the WWAN 104 into the user-specified fields.

The processing system 306 also may be configured to incorporate one or more attributes of access to the WWAN 104 into a parameter of access to the WLAN. For example, the SSID of the WLAN may not use all of the available bytes of the beacon frame. The processing system 306 may be configured to incorporate one or more attributes of access to the WWAN 104 into the SSID of the WLAN. The number of attributes that may be incorporated into the SSID will vary depending on the data size of the SSID and the data size of the attributes.

Once construction of the beacon frame is complete, WLAN transceiver 302 broadcasts the beacon frame to mobile clients 108 within range of the transceiver.

FIG. 4 is a flowchart illustrating an example of a method for providing service information from an ad hoc service provider 106 to enable access to a WWAN 104. For implementations in which attributes are received from server 110, the processing system 306 of the ad hoc service provider 106 receives such attributes in step 400. For implementations in which attributes are updated dynamically based on the status of the ad hoc service provider 106, the processing system 306 of the ad hoc service provider 106 updates the attributes in step 401. In step 402, the processing system 306 assembles the service information, which includes both parameters of access to the WLAN and attributes of access to the WWAN 104, into a format suitable for broadcasting to one or more mobile clients 108. In step 403, the assembled service information is broadcast to the mobile clients 108 using the WLAN transceiver 302.

Upon receiving the service information broadcast by the ad hoc service provider 106, the mobile clients 108 may be configured to parse the assembled service information to identify the various parameters of access to the WLAN and the attributes of access to the WWAN 104. The parameters and attributes may be displayed within a graphical user interface on the mobile client 108 to allow a mobile user to view the attributes of access to the WWAN 104 being offered by the ad hoc service provider. Based on the broadcast attributes, a mobile user can determine whether or not the offered access to the WWAN 104 is sufficient for the mobile user's desired applications. For example, the mobile user may require access for a minimum period of time or intend on using a data-intensive application requiring a high data rate. Furthermore, the mobile user can gain information on the reliability of the particular ad hoc service provider 106 based on the associated goodness metric. Additionally, if multiple ad hoc service providers 106 are within range of the mobile client 108, the mobile client may be configured to display the attributes of all available ad hoc service providers 106 thereby allowing the mobile user to compare the different ad hoc service providers and select one that best suits their needs.

Mobile clients 108 interested in the access offered by an ad hoc service provider 106 may associate with the broadcast SSID to access the ad hoc service provider 106. The processing system in the ad hoc service provider 106 may then authenticate the mobile clients 108 with the server 110 and then set up an interconnection bridge from the WLAN link to the mobile clients 108 over to the WWAN link. During the authentication of a mobile client 108, the processing system in the ad hoc service provider 106 may use an unsecured wireless link.

The processing system in the ad hoc service provider 106 may optionally choose to move a mobile client 108 to a new SSID with a secure link once the mobile client 108 is authen-

ticated. In such situations, the ad hoc service provider **106** may distribute the time it spends in each SSID depending on the load that it has to support for existing sessions with mobile clients **108**.

The processing system may also determine whether the ad hoc service provider **106** can support a mobile client **108** before allowing the mobile client **108** to access a network. Resource intelligence in the processing system that estimates the drain on the battery power and other processing resources that would occur by accepting a mobile client **108** may assist in determining whether the processing system should consider supporting a new mobile client **108** or accepting a handoff of that mobile client **108** from another ad hoc service provider **106**.

The processing system in the ad hoc service provider **106** may admit mobile clients **108** and provides them with a certain QoS guarantee, such as an expected average bandwidth during a session. Average throughputs provided to each mobile client **108** over a time window may be monitored. The ad hoc service provider **106** may monitor the throughputs for all flows going through it to ensure that resource utilization by the mobile clients **108** is below a certain threshold, and that it is meeting the QoS requirement that it has agreed to provide to the mobile clients **108** during the establishment of the session.

The processing system in the ad hoc service provider **106** may also provide a certain level of security to the wireless access point by routing data between the mobile client **108** and the server without being able to decipher the data. Similarly, the processing system may be configured to ensure data routed between the user interface and the WWAN cannot be deciphered by mobile clients. The processing system may use any suitable encryption technology to implement this functionality.

The processing system in the ad hoc service provider **106** may also maintain a time period for a mobile client **108** to access a network. The time period may be agreed upon between the ad hoc service provider **106** and the mobile client **108** during the initiation of the session. If the processing system determines that it is unable to provide the mobile client **108** with access to the network for the agreed upon time period, then it may notify both the server **110** and the mobile client **108** regarding its unavailability. This may occur due to energy constraints (e.g., a low battery), or other unforeseen events. The server **110** may then consider a handoff of the mobile client to another ad hoc service provider **106**, if there is such an ad hoc service provider **106** in the vicinity of the mobile client **108**. The processing system in the ad hoc service provider **106** may support the handoff of the mobile client **108**.

Turning now to the mobile client **108**, a TLS session may be used by the mobile client **108** to register with the server **110**. Once registered, the mobile client **108** may search for available ad hoc service providers **106**. When the mobile client **108** detects the presence of one or more ad hoc service providers **106**, it may initiate a session using EAP-TTLS with an ad hoc service provider **106** based on attributes and parameters such as the available bandwidth that the ad hoc service provider **106** can support, the goodness metric of the ad hoc service provider **106**, and the cost of the service advertised. As described earlier, a link encryption key may be established between the mobile client **108** and the ad hoc service provider **106** during the establishment of the session. An SSL VPN session may be established between the mobile client **108** and the server **110** so that all traffic between the two is encrypted. The transport layer ports may be kept in the open and not

encrypted to provide visibility for the network address translation functionality at the ad hoc service provider **106**.

A handoff of a mobile client **108** from one ad hoc service provider to another may occur due to any of a number of factors. The handoff of the mobile client **108** may be performed in a variety of ways. In one configuration, the mobile client **108** may maintain a limited session with multiple ad hoc service providers **106**, while using one ad hoc service provider **106** to access the Internet. As described earlier, this approach may facilitate the handoff process. In an alternative configuration, the mobile client **108** may consider a handoff only when necessary. In this configuration, the mobile client **108** may maintain an active list of ad hoc service providers **106** in its vicinity for handoff. The mobile client **108** may select an ad hoc service provider **106** for handoff from the active list when the current ad hoc service provider **106** needs to discontinue its service. When handoff is not possible, a mobile client **108** may need to reconnect through a different ad hoc service provider **106** to access the Internet.

If the bandwidth needs of a mobile client **108** are greater than the capabilities of the available ad hoc service providers **106**, then the mobile client **108** may access multiple ad hoc service providers **106** simultaneously. A mobile client **108** with multiple transceivers could potentially access multiple ad hoc service providers **106** simultaneously using a different transceiver for each ad hoc service provider **106**. If the same wireless access protocol can be used to access multiple ad hoc service providers **106**, then different channels may be used. If the mobile client **108** has only one transceiver available, then it may distribute the time that it spends accessing each ad hoc service provider **106**.

FIG. 5 is a conceptual block diagram of an exemplary configuration of an ad hoc service provider. This block diagram illustrates an example of the functionality of a processing system **306** in an ad hoc service provider **106**. The ad hoc service provider **106** may be used to enable access by a mobile client to a first wireless network such as a WWAN **104** via a second wireless network, such as a WLAN supported by the ad hoc service provider. The ad hoc service provider may include a module **500** for enabling access to the first wireless network via the second wireless network. The processing system **306** also may include a module **501** for assembling service information for broadcasting to one or more mobile clients. The processing system **306** may include module **502** for receiving attributes of access to the first wireless network from a server and module **503** for updating attributes of access to the first wireless network based on the status of the ad hoc service provider **106**.

Those of skill in the art would appreciate that the various illustrative blocks, modules, elements, components, methods, and algorithms described herein may be implemented as electronic hardware, computer software, or combinations of both. To illustrate this interchangeability of hardware and software, various illustrative blocks, modules, elements, components, methods, and algorithms have been described above generally in information of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. Skilled artisans may implement the described functionality in varying ways for each particular application.

It is understood that the specific order or hierarchy of steps in the processes disclosed is an illustration of exemplary approaches. Based upon design preferences, it is understood that the specific order or hierarchy of steps in the processes may be rearranged. The accompanying method claims



present elements of the various steps in a sample order, and are not meant to be limited to the specific order or hierarchy presented.

The previous description is provided to enable any person skilled in the art to practice the various aspects described herein. Various modifications to these aspects will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other aspects. Thus, the claims are not intended to be limited to the aspects shown herein, but is to be accorded the full scope consistent with the language claims, wherein reference to an element in the singular is not intended to mean "one and only one" unless specifically so stated, but rather "one or more." Unless specifically stated otherwise, the term "some" refers to one or more. Pronouns in the masculine (e.g., his) include the feminine and neuter gender (e.g., her and its) and vice versa. All structural and functional equivalents to the elements of the various aspects described throughout this disclosure that are known or later come to be known to those of ordinary skill in the art are expressly incorporated herein by reference and are intended to be encompassed by the claims. Moreover, nothing disclosed herein is intended to be dedicated to the public regardless of whether such disclosure is explicitly recited in the claims. No claim element is to be construed under the provisions of 35 U.S.C. §112, sixth paragraph, unless the element is expressly recited using the phrase "means for" or, in the case of a method claim, the element is recited using the phrase "step for."

What is claimed is:

1. An ad hoc service provider, comprising:
  - a processing system configured to enable access by one or more mobile clients to a first wireless network via a second wireless network, the processing system further configured to receive over the first wireless network and assemble service information for broadcasting to one or more mobile clients,
  - wherein the service information comprises attributes of access to the first wireless network relating to an ad hoc service provider advertised expectation of service, the access being offered by the ad hoc service provider to one or more mobile clients, wherein the ad hoc service provider is a mobile device.
2. The ad hoc service provider of claim 1, wherein the processing system is further configured to receive at least one attribute of access to the first wireless network from a server.
3. The ad hoc service provider of claim 1, wherein the processing system is further configured to dynamically update at least one attribute of access to the first wireless network based on a status of the ad hoc service provider.
4. The ad hoc service provider of claim 1, wherein the attributes of access to the first wireless network comprise at least one of a quality of service parameter and a fee rate of access to the first wireless network, and
  - wherein the quality of service parameter comprises at least one of an expected data rate of access to the first wireless network, an expected duration of access to the first wireless network, a latency of access to the first wireless network, a frequency of access to the first wireless network, and an amount of transferred data.
5. The ad hoc service provider of claim 1, wherein the attributes of access to the first wireless network comprise a service provider goodness metric based on prior access to the first wireless network provided by the ad hoc service provider to one or more mobile clients.
6. The ad hoc service provider of claim 1, wherein the processing system is further configured to construct a beacon

frame suitable for broadcasting to one or more mobile clients, the beacon frame comprising the service information.

7. The ad hoc service provider of claim 1, wherein the service information further comprises parameters of access to the second wireless network comprising a service set identifier,

wherein the processing system is further configured to incorporate at least one attribute of access to the first wireless network into the service set identifier.

8. The ad hoc service provider of claim 1, further comprising a transceiver for broadcasting the assembled service information to one or more mobile clients.

9. An ad hoc service provider, comprising:

means for enabling access by one or more mobile clients to a first wireless network via a second wireless network; and

means for receiving over the first wireless network and assembling service information for broadcasting to one or more mobile clients,

wherein the service information comprises attributes of access to the first wireless network relating to an ad hoc service provider advertised expectation of service, the access being offered by the ad hoc service provider to the one or more mobile clients, wherein the ad hoc service provider is a mobile device.

10. The ad hoc service provider of claim 9, wherein the ad hoc service provider further comprises means for receiving at least one attribute of access to the first wireless network from a server.

11. The ad hoc service provider of claim 9, wherein the ad hoc service provider further comprises means for dynamically updating at least one attribute of access to the first wireless network based on a status of the ad hoc service provider.

12. The ad hoc service provider of claim 9, wherein the attributes of access to the first wireless network comprise at least one of a quality of service parameter and a fee rate of access to the first wireless network, and

wherein the quality of service parameter comprises at least one of an expected data rate of access to the first wireless network, an expected duration of access to the first wireless network, a latency of access to the first wireless network, a frequency of access to the first wireless network, and an amount of transferred data.

13. The ad hoc service provider of claim 9, wherein the attributes of access to the first wireless network comprise a service provider goodness metric based on prior access to the first wireless network provided by the ad hoc service provider to one or more mobile clients.

14. The ad hoc service provider of claim 9, wherein the means for assembling service information further constructs a beacon frame suitable for broadcasting to one or more mobile clients, the beacon frame comprising the service information.

15. The ad hoc service provider of claim 9, wherein the service information further comprises parameters of access to the second wireless network comprising a service set identifier,

wherein the means for assembling service information further incorporates at least one attribute of access to the first wireless network into the service set identifier.

16. The ad hoc service provider of claim 9, further comprising means for broadcasting the assembled service information to one or more mobile clients.

17. A method of providing service information from an ad hoc service provider configured to enable access by one or

**17**

more mobile clients to a first wireless network via a second wireless network, the method comprising:

receiving over the first wireless network and assembling service information for

broadcasting to one or more mobile clients,

wherein the service information comprises attributes of access to the first wireless network relating to an ad hoc service provider advertised expectation of service, the access being offered by the ad hoc service provider to one or more mobile clients, wherein the ad hoc service provider is a mobile device.

**18.** The method of claim **17**, further comprising receiving at least one attribute of access to the first wireless network from a server.

**19.** The method of claim **17**, further comprising dynamically updating at least one attribute of access to the first wireless network based on a status of the ad hoc service provider.

**20.** The method of claim **17**, wherein the attributes of access to the first wireless network comprise at least one of a quality of service parameter and a fee rate of access to the first wireless network, and

wherein the quality of service parameter comprises at least one of an expected data rate of access to the first wireless network, an expected duration of access to the first wireless network, a latency of access to the first wireless network, a frequency of access to the first wireless network, and an amount of transferred data.

**21.** The method of claim **17**, wherein the attributes of access to the first wireless network comprise a service pro-

**18**

vider goodness metric based on prior access to the first wireless network provided by the ad hoc service provider to one or more mobile clients.

**22.** The method of claim **17**, wherein the assembling step further comprises constructing a beacon frame suitable for broadcasting to one or more mobile clients, the beacon frame comprising the service information.

**23.** The method of claim **17**, wherein the service information further comprises parameters of access to the second wireless network comprising a service set identifier,

wherein the assembling step further comprises incorporating at least one attribute of access to the first wireless network into the service set identifier.

**24.** The method of claim **17**, further comprising broadcasting the assembled service information to one or more mobile clients.

**25.** A non-transitory computer readable medium comprising instructions executable by a processing system in an ad hoc service provider, the instructions comprising code for:

enabling access by one or more mobile clients to a first wireless network via a second wireless network; and receiving over the first wireless network and assembling service information for

broadcasting to one or more mobile clients,

wherein the service information comprises attributes of access to the first wireless network relating to an ad hoc service provider advertised expectation of service, the access being offered by the ad hoc service provider to one or more mobile clients, wherein the ad hoc service provider is a mobile device.

\* \* \* \* \*