



US008656747B2

(12) **United States Patent**
Armstrong et al.

(10) **Patent No.:** **US 8,656,747 B2**
(45) **Date of Patent:** ***Feb. 25, 2014**

(54) **KEYING SYSTEM AND METHOD**

(75) Inventors: **Steven Armstrong**, San Juan Capistrano, CA (US); **Gerald B. Chong**, Rowland Heights, CA (US)

(73) Assignee: **Kwikset Corporation**, Foothill Ranch, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1131 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **12/174,025**

(22) Filed: **Jul. 16, 2008**

(65) **Prior Publication Data**

US 2008/0271505 A1 Nov. 6, 2008

Related U.S. Application Data

(60) Continuation of application No. 11/923,058, filed on Oct. 24, 2007, now Pat. No. 7,434,431, which is a continuation of application No. 11/465,921, filed on Aug. 21, 2006, now Pat. No. 7,322,219, which is a division of application No. 11/011,530, filed on Dec. 13, 2004, now Pat. No. 7,114,357, which is a continuation-in-part of application No. 10/256,066, filed on Sep. 26, 2002, now Pat. No. 6,860,131.

(51) **Int. Cl.**

E05B 27/04 (2006.01)

E05B 29/04 (2006.01)

E05B 35/10 (2006.01)

(52) **U.S. Cl.**

USPC **70/492; 70/340; 70/341; 70/383; 70/384; 70/493; 70/495**

(58) **Field of Classification Search**

USPC **70/337-343, 382-385, 368, 492, 493, 70/495, 496**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,565,556 A	12/1925	Fremon
1,610,224 A	12/1926	Dalboni et al.
1,845,867 A	2/1932	Ellingson
1,965,889 A	7/1934	Gerald
2,139,842 A	12/1938	Miller
2,194,469 A	3/1940	Fremon
2,232,017 A	2/1941	Wilder
2,370,862 A	3/1945	Johnstone
2,391,832 A	12/1945	Johnstone
2,895,323 A	7/1959	Ernest
2,977,786 A	4/1961	Marron
3,149,486 A	9/1964	Russell
3,183,692 A	5/1965	Check

(Continued)

FOREIGN PATENT DOCUMENTS

DE	19544840 A1	6/1997
EP	0157967	10/1985

(Continued)


Primary Examiner — Lloyd Gall

(74) *Attorney, Agent, or Firm* — Barnes & Thornburg LLP

(57) **ABSTRACT**

A kit for a master keying system includes a plurality of replacement master racks. A rack removal key is provided for insertion into a keyway. The rack removal key has a first cut defining a first lift amount. A rack removal tool is provided for insertion into the keyway. The rack removal tool has a second cut defining a second lift amount, wherein the second lift amount is greater than the first lift amount.

6 Claims, 47 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,190,093 A 6/1965 Schlage
 3,261,189 A 7/1966 Best
 3,320,781 A 5/1967 Hill
 3,431,757 A 3/1969 Hori
 3,589,153 A 6/1971 Hill
 3,667,262 A 6/1972 Hill
 3,693,384 A 9/1972 Genakis
 3,726,116 A 4/1973 Dimotta
 3,728,880 A 4/1973 Falk
 3,735,612 A 5/1973 Popovici
 3,754,422 A 8/1973 Stackhouse
 3,910,083 A 10/1975 Burlingame
 3,974,671 A 8/1976 Rossetti
 3,990,282 A 11/1976 Sorum
 3,999,413 A 12/1976 Raymond et al.
 4,015,458 A 4/1977 Mercurio
 4,069,694 A 1/1978 Raymond et al.
 4,094,175 A 6/1978 Pechner
 4,142,391 A 3/1979 Paig
 4,320,639 A 3/1982 Kleefeldt et al.
 4,372,139 A 2/1983 Laake
 4,376,382 A 3/1983 Raymond et al.
 4,377,940 A 3/1983 Hucknall
 4,393,673 A * 7/1983 Widen 70/358
 4,404,824 A 9/1983 Hennessy
 4,412,437 A 11/1983 Smith
 4,440,009 A 4/1984 Smith
 4,689,978 A 9/1987 Drummond
 4,712,399 A 12/1987 Mattosovich
 4,712,401 A 12/1987 Monahan
 4,712,402 A 12/1987 Monahan
 4,723,427 A 2/1988 Oliver
 4,729,231 A 3/1988 Wu
 4,732,023 A 3/1988 Shen
 4,741,188 A 5/1988 Smith
 4,747,281 A 5/1988 Monahan
 4,765,163 A 8/1988 Trull et al.
 4,794,772 A 1/1989 Falk et al.
 4,836,002 A 6/1989 Monahan
 4,850,210 A 7/1989 Adler et al.
 4,899,563 A 2/1990 Martin
 4,909,053 A 3/1990 Zipf, III et al.
 4,912,953 A 4/1990 Wobig
 4,920,774 A 5/1990 Martin
 4,942,749 A 7/1990 Rabinow
 4,966,021 A 10/1990 Boag
 4,996,856 A 3/1991 Lin et al.
 5,000,019 A 3/1991 Foster
 5,010,753 A 4/1991 Boris, Jr.
 5,024,071 A 6/1991 Shafirkin
 5,038,589 A 8/1991 Martin
 5,044,180 A 9/1991 Lebrecht
 5,044,185 A 9/1991 Green
 5,076,081 A 12/1991 Boris, Jr.
 5,088,305 A 2/1992 Myers
 5,121,619 A 6/1992 Martin
 5,174,136 A 12/1992 Thwing
 5,209,088 A 5/1993 Vaks

5,211,044 A 5/1993 Kim
 5,233,850 A 8/1993 Schroeder
 5,325,690 A 7/1994 Adler et al.
 5,428,978 A 7/1995 Tsukano
 5,431,034 A 7/1995 Fann et al.
 5,540,071 A 7/1996 Reikher
 5,640,865 A 6/1997 Widen
 5,704,234 A 1/1998 Resch
 5,718,136 A 2/1998 Aldieri et al.
 5,752,400 A 5/1998 Kim
 5,765,417 A 6/1998 Bolton
 5,791,181 A 8/1998 Sperber et al.
 5,884,512 A 3/1999 Wayne
 5,921,122 A 7/1999 Lin
 5,921,123 A 7/1999 Schwarzkopf et al.
 5,970,760 A 10/1999 Shen
 5,979,200 A 11/1999 Cliff
 6,029,484 A 2/2000 Jetton
 6,047,577 A 4/2000 Klimas
 6,076,386 A 6/2000 Etchells et al.
 6,079,240 A 6/2000 Shvarts
 6,119,495 A 9/2000 Loreti
 6,134,928 A 10/2000 Kang
 6,142,717 A 11/2000 Staiger
 6,295,850 B1 10/2001 Anderson
 6,425,274 B1 7/2002 Laitala et al.
 6,516,643 B1 2/2003 Olshausen
 6,523,378 B2 2/2003 Kuo
 6,532,782 B2 3/2003 Chiu
 6,564,601 B2 5/2003 Hyatt Jr.
 6,776,017 B2 8/2004 Herdman
 6,860,131 B2 3/2005 Armstrong et al.
 6,862,909 B2 3/2005 Armstrong et al.
 6,871,520 B2 3/2005 Armstrong et al.
 6,959,569 B2 11/2005 Strader et al.
 7,007,528 B2 3/2006 Chong et al.
 7,114,357 B2 10/2006 Armstrong et al.
 7,117,701 B2 10/2006 Armstrong et al.
 7,213,429 B2 5/2007 Armstrong et al.
 7,234,331 B2 6/2007 Armstrong et al.
 7,308,811 B2 12/2007 Armstrong et al.
 7,322,219 B2 * 1/2008 Armstrong et al. 70/492
 7,434,431 B2 * 10/2008 Armstrong et al. 70/492
 2003/0037582 A1 2/2003 Edwards, Jr. et al.
 2003/0084692 A1 5/2003 Herdman
 2003/0089149 A1 5/2003 Suzuki et al.
 2003/0154753 A1 8/2003 Dimig et al.
 2004/0069030 A1 4/2004 Takadama
 2006/0117822 A1 6/2006 Boesel et al.

FOREIGN PATENT DOCUMENTS

EP 0210037 1/1987
 EP 0872615 10/1998
 GB 990987 5/1965
 GB 1554877 10/1979
 JP 7197705 A 8/1995
 JP 2001234648 A 8/2001
 WO 9314290 7/1993
 WO 9736072 10/1997

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15C






FIG. 15E

FIG. 15B

FIG. 15A

FIG. 15D






FIG. 16D




FIG. 16E

FIG. 16F




FIG. 17A




FIG. 17B




FIG. 17C




FIG. 17D




FIG. 17E




FIG. 17F




FIG. 18A

FIG. 18B




FIG. 19A

FIG. 19B




FIG. 20A




FIG. 20B






FIG. 21A

FIG. 21B






FIG. 22C




FIG. 22D




FIG. 23




FIG. 24A

FIG. 24B




FIG. 24C




FIG. 24D




FIG. 24E




FIG. 25




FIG. 26A




FIG. 26B




FIG. 27A




FIG. 27B




FIG. 27C




FIG. 27D




FIG. 27E




FIG. 28A

FIG. 28B




FIG. 29A

FIG. 29B




FIG. 30A




FIG. 30B




FIG. 31




FIG. 32




FIG. 33




FIG. 34

FIG. 35




FIG. 36A




FIG. 36B




FIG. 36C




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 52

KEYING SYSTEM AND METHOD

This is a continuation of U.S. patent application Ser. No. 11/923,058, filed Oct. 24, 2007, now U.S. Pat. No. 7,434,431, which is a continuation of U.S. patent application Ser. No. 11/465,921, filed Aug. 21, 2006, now U.S. Pat. No. 7,322,219, which is a division of U.S. patent application Ser. No. 11/011,530 filed Dec. 13, 2004, now U.S. Pat. No. 7,114,357, which is a continuation-in-part of U.S. patent application Ser. No. 10/256,066 filed Sep. 26, 2002, now U.S. Pat. No. 6,860,131.

The present invention relates generally to lock cylinders and particularly to lock cylinders that can be rekeyed. More particularly, the invention relates to a keying system and method.

BACKGROUND OF THE INVENTION

When rekeying a cylinder using a traditional cylinder design, the user is required to remove the cylinder plug from the cylinder body and replace the appropriate pins so that a new key can be used to unlock the cylinder. This typically requires the user to remove the cylinder mechanism from the lockset and then disassemble the cylinder to some degree to remove the plug and replace the pins. This requires a working knowledge of the lockset and cylinder mechanism and is usually only performed by locksmiths or trained professionals. Additionally, the process usually employs special tools and requires the user to have access to pinning kits to interchange pins and replace components that can get lost or damaged in the rekeying process. Finally, professionals using appropriate tools can easily pick traditional cylinders.

In addition, in one form of a master keying system, such as a pin and tumbler design, master shims are positioned in between the pins of the lock cylinder to establish a shear line for the master key and user keys. In such a previous design, for example, the consumer replaces the pins and adds shims to convert the lock cylinder to a master keyed cylinder. This may be a complicated process for some consumers.

The present invention overcomes these and other disadvantages of conventional lock cylinders and master keying systems.

SUMMARY OF THE INVENTION

The present invention, in one form thereof, is directed to a keying method. The method includes providing a cylinder body and a plug assembly disposed in the cylinder body, the plug assembly having a keyway, a plug body and a carrier sub-assembly disposed adjacent the plug body, the carrier sub-assembly being moveable parallel to the longitudinal axis of the cylinder body between a first position and a retracted position, the plug assembly including a plurality of pins and a plurality of racks for respectively engaging the plurality of pins, each rack of the plurality of racks having a locking bar-receiving groove.

The method further includes moving the carrier sub-assembly that carries the plurality of racks to the retracted position to decouple the plurality of racks from the plurality of pins; inserting a rack removal key in the keyway, the rack removal key having a cut that lifts the plurality of pins by a first amount; releasing the carrier sub-assembly from the retracted position to reengage the plurality of racks with the plurality of pins; disengaging a locking bar from the locking bar-receiving groove of each rack of the plurality of racks to decouple the racks; removing the rack removal key from the keyway; inserting a rack removal tool into the keyway, the

rack removal tool having a cut that lifts the plurality of pins by a second amount greater than the first amount; moving the carrier sub-assembly to the retracted position to decouple the plurality of racks from the plurality of pins; removing each rack to be replaced from a corresponding access hole on the cylinder body; inserting a corresponding replacement rack through a respective access hole for each of the racks to be replaced, each replacement rack having the locking bar-receiving groove; releasing the carrier sub-assembly from the retracted position to engage each of the racks installed in the carrier sub-assembly with a corresponding pin of the plurality of pins; removing the rack removal tool from the keyway; reinserting the rack removal key in the keyway; without removing the rack removal key, engaging the locking bar with the locking bar-receiving groove of each rack to couple together the racks installed in the carrier sub-assembly; moving the carrier sub-assembly to the retracted position to decouple each of the racks installed in the carrier sub-assembly from the corresponding pin of the plurality of pins; and removing the rack removal key from the keyway.

The present invention, in another form thereof, is directed to a master keying method. The method includes providing a lock cylinder having a cylinder body with a longitudinal axis, and a plug assembly disposed in the cylinder body, the plug assembly having a keyway, a plug body having a plurality of protrusion features, and a carrier sub-assembly disposed adjacent the plug body, the carrier sub-assembly being moveable parallel to the longitudinal axis of the cylinder body between a first position and a retracted position, the plug assembly including a plurality of pins and a plurality of racks for engaging the pins, each rack of the plurality of racks having a locking bar-receiving groove and a protrusion receiving groove.

The method further includes inserting a valid master key into the keyway; rotating the valid master key to rotate the plug assembly from an original position to a first position in a first rotational direction; moving the carrier sub-assembly to a retracted position to decouple the plurality of racks from the plurality of pins and position the protrusion receiving groove of each rack over a corresponding protrusion feature on the plug body; removing the valid master key from the keyway; inserting a rack removal key in the keyway, the rack removal key having a cut that lifts the plurality of pins by a first amount; rotating the plug assembly to a second position in the first rotational direction to release the carrier sub-assembly from the retracted position to reengage the plurality of racks with the plurality of pins; removing a side plug from the cylinder body to disengage a locking bar from the locking bar-receiving groove of each rack, thereby decoupling all of the plurality of racks from each other rack; removing the rack removal key from the keyway; inserting a rack removal tool into the keyway, the rack removal tool having a cut that lifts the plurality of pins by a second amount greater than the first amount; moving the carrier sub-assembly to the retracted position to decouple the plurality of racks from the plurality of pins and position each rack above the corresponding protrusion feature on the plug body; removing the racks from access holes in the cylinder body; inserting each of a plurality of master racks through a respective access hole, each master rack of the plurality of master racks having a master locking bar-receiving groove and a master protrusion receiving groove; releasing the carrier sub-assembly from the retracted position to engage the plurality of master racks with the plurality of pins; remove the rack removal tool from the keyway; reinsert the rack removal key in the keyway; without removing the rack removal key, reinstalling the side plug back on to the cylinder body so that the locking bar engages with

3

the master locking bar-receiving groove of each master rack of the plurality of master racks, thereby coupling all of the plurality of master racks together; rotating the plug assembly to the first position in a second rotational direction opposite to the first rotational direction; moving the carrier sub-assembly to a retracted position to decouple the plurality of master racks from the plurality of pins and position the master protrusion receiving groove of each master rack over a corresponding protrusion feature on the plug body; removing the rack removal key from the keyway; inserting a new master key in the keyway; and rotating the plug body back in the second rotational direction back to the original position to release the carrier sub-assembly from the retracted position to reengage the plurality of master racks with the plurality of pins.

The present invention, in another form thereof, is directed to a keying system. The system includes a cylinder body having a longitudinal axis. A plug assembly is disposed in the cylinder body. The plug assembly has a keyway. The plug assembly includes a plug body and a carrier sub-assembly disposed adjacent the plug body. The carrier sub-assembly is moveable parallel to the longitudinal axis of the cylinder body between a first position and a second position. The plug assembly includes a plurality of pins and a plurality of racks for selectively engaging the plurality of pins. Each rack of the plurality of racks has a first locking bar-receiving groove along a neutral axis and at least a second locking bar-receiving groove spaced from the neutral axis. A spacing of the second locking bar-receiving groove from the neutral axis of a first rack of the plurality of racks is different from a spacing of the second locking bar-receiving groove from the neutral axis of at least one other of the plurality of racks.

The present invention, in still another form thereof, is directed to a kit for a master keying system. The kit includes a plurality of replacement master racks, a rack removal key for insertion into a keyway, and a rack removal tool for insertion into the keyway. The rack removal key has a first cut defining a first lift amount. The rack removal tool has a second cut defining a second lift amount. The second lift amount is greater than the first lift amount.

The present invention, in still another form thereof, is directed to a keying method, including providing a plurality of replacement master racks to be installed in a movable carrier assembly of a lock cylinder; and manipulating the movable carrier assembly with a rack removal key and a rack removal tool, each of the rack removal key and the rack removal tool being configured for insertion into a keyway of the lock cylinder, the rack removal key having a first cut defining a first lift amount, and the rack removal tool having a second cut defining a second lift amount, the second lift amount being greater than the first lift amount.

Other features and advantages will become apparent from the following description when viewed in accordance with the accompanying drawings and appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a lock cylinder according to the present invention.

FIG. 2 is an exploded view of the lock cylinder of FIG. 1.

FIG. 3 is a perspective view of a plug assembly illustrating a carrier sub-assembly with a locking bar disposed in a locking position to lock the plug assembly in a lock cylinder body.

FIG. 4 is a top plan view of the plug assembly of FIG. 3.

FIG. 5 is a partially broken away side view of the plug assembly of FIG. 3.

4

FIG. 6 is a partially exploded view of the plug assembly of FIG. 3.

FIG. 7 is a section view through the plug assembly of FIG. 3 and a cylinder body, the section being taken transversely at one of the pins and illustrating the positioning of the pin, a rack, and the locking bar relative to each other and the cylinder body in a locked configuration.

FIG. 8 is a perspective view of the plug assembly of FIG. 3 with a valid key inserted therein and illustrating the locking bar disposed in an unlocking position to allow the plug assembly to rotate in the lock cylinder body.

FIG. 9 is a top plan view of the plug assembly of FIG. 8.

FIG. 10 is a partially broken away side view of the plug assembly of FIG. 8.

FIG. 11 is a partially exploded view of the plug assembly of FIG. 8.

FIG. 12 is a section view through the plug assembly of FIG. 8 and a cylinder body, the section being taken transversely at one of the pins and illustrating the positioning of the pin, the rack, and the locking bar relative to each other and the cylinder body in an unlocked configuration.

FIG. 13 is a perspective view similar to FIG. 8 but with the carrier assembly moved axially to a rekeying position.

FIG. 14 is a top plan view of the plug assembly of FIG. 13.

FIGS. 15a-15e are various views of a cylinder body for use in the present invention.

FIGS. 16a-16f are various views of the cylinder plug body for use in the present invention.

FIGS. 17a-17f are various view of the carrier for use in the present invention.

FIGS. 18a-18b are views of a rack for use in the present invention.

FIGS. 19a-19b are views of a spring catch for use in the present invention.

FIGS. 20a-20b are views of a pin for use in the present invention.

FIGS. 21a-21b are views of a locking bar for use in the present invention.

FIGS. 22a-22d are views of a spring retaining cap for use in the present invention.

FIG. 23 is an exploded perspective view of an alternative embodiment of the invention.

FIGS. 24a-24e are views of an alternative embodiment of the lock cylinder housing.

FIG. 25 is a transverse section view taken through an alternative embodiment of the present invention.

FIGS. 26a-26b are views of an alternative embodiment of the spring catch.

FIGS. 27a-27e are views of an alternative embodiment of the carrier.

FIGS. 28a-28b are views of an alternative embodiment of the pin.

FIGS. 29a-29b are views of an alternative embodiment of the rack.

FIGS. 30a-30b are views of an alternative embodiment of the locking bar.

FIG. 31 shows a rack removal key in accordance with the present invention.

FIG. 32 shows a rack removal tool in accordance with the present invention.

FIG. 33 shows a lock cylinder having a plug assembly and keyway.

FIG. 34 shows a plurality of master racks in accordance with the present invention.

FIG. 35 shows the position of the plurality of master racks when a tenant key is inserted into the keyway.

FIGS. 36A-36C show a detailed flowchart of one embodiment of a method for rekeying a lock cylinder of the master keying system in accordance with the present invention.

FIG. 37 shows the position of the carrier sub-assembly as it is pushed to the retracted position.

FIG. 38 shows the placement of the master racks after the carrier sub-assembly is pushed to the retracted position.

FIG. 39 shows the placement of the master racks with the master key removed from the keyway.

FIG. 40 shows the rack removal key inserted in the keyway of the plug assembly.

FIG. 41 shows the removable side panel removed from the cylinder body, exposing the locking bar.

FIG. 42 shows the position of the plurality of master racks with the rack removal key inserted in the keyway.

FIG. 43 shows the plurality of master racks positioned above the corresponding protrusion feature of the plug body.

FIG. 44 shows the rack access holes in the cylinder body.

FIG. 45 shows a plurality of replacement master racks.

FIG. 46 shows the carrier sub-assembly released from the retracted position to engage the plurality of replacement master racks with the plurality of pins.

FIG. 47 shows the plurality of replacement master racks with the corresponding protrusion grooves lined up with the corresponding protrusion features on the plug body.

FIG. 48 shows the master locking bar-receiving grooves of the master racks positioned to receive the locking bar.

FIG. 49 shows the removable side panel reinstalled on the cylinder body.

FIG. 50 shows the plug assembly in the learn mode position.

FIG. 51 shows the individual positions of each of the plurality of replacement master racks when the carrier sub-assembly is moved to the retracted position.

FIG. 52 shows the plug body rotated by a new master key in the second rotational direction back to the original position so as to reengage the plurality of replacement master racks with the plurality of pins.

DETAILED DESCRIPTION OF THE DRAWINGS

A lock cylinder 10 according to the present invention is illustrated in FIG. 1-2. The lock cylinder 10 includes a longitudinal axis 11, a lock cylinder body 12, a plug assembly 14 and a retainer 16. In FIG. 1, the plug assembly 14 is in the home position relative to the cylinder body 12.

The lock cylinder body 12, as seen in FIGS. 15a-15e, includes a generally cylindrical body 20 having a front end 22, a back end 24 and a cylinder wall 26 defining an interior surface 28. The cylinder wall 26 includes an interior, locking bar-engaging groove 29 and a pair of detent recesses 30, 32. The generally V-shaped locking bar-engaging groove 29 extends longitudinally along a portion of the cylinder body 12 from the front end 22. The first detent recess 30 is disposed at the back end 24 and extends to a first depth. The second detent recess 32 is disposed adjacent the first detent recess 30 and extends to a lesser depth. A detent bore 34 extends radially through the cylinder wall 26 for receiving a detent ball 36 (FIG. 2).

The plug assembly 14 includes a plug body 40, a carrier sub-assembly 42 and a plurality of spring-loaded pins 38 (FIGS. 2 and 20a-20b). The plug body 40, illustrated in FIGS. 16a-16f, includes a plug face 44, an intermediate portion 46 and a drive portion 50. The plug face 44 defines a keyway opening 52, a rekeying tool opening 54 and a pair of channels 56 extending radially outwardly for receiving anti-drilling ball bearings 60 (FIG. 2). The drive portion 50 includes an

annular wall 62 with a pair of opposed projections 64 extending radially inwardly to drive a spindle or torque blade (neither shown). The drive portion 50 further includes a pair of slots 66 formed in its perimeter for receiving the retainer 16 to retain the plug body 40 in the cylinder body 12.

The intermediate portion 46 includes a main portion 70 formed as a cylinder section and having a first longitudinal planar surface 72 and a plurality of channels 74 for receiving the spring-loaded pins 38. The channels 74 extend transversely to the longitudinal axis of the plug body 40 and parallel to the planar surface 72. A second planar surface 76 extends perpendicular to the first planar surface 72 and defines a recess 80 for receiving a retaining cap 82 (FIGS. 2 and 22a-22d). The channels 74 extend from the second planar surface 76 partially through the plug body 40, with the side-walls of the channels open to the first planar surface 72. The first planar surface 72 further includes a plurality of bullet-shaped, rack-engaging features 78. A bore 86 for receiving a spring-loaded detent ball 36 (FIG. 2) extends radially inwardly from opposite the first planar surface 72.

The carrier sub-assembly 42 (FIGS. 2, 6 and 10) includes a carrier 90 (FIGS. 17a-17e), a plurality of racks 92 (FIGS. 18a-18b), a spring catch 96 (FIGS. 19a-19b), a spring-loaded locking bar 94 (FIGS. 21a-21b), and a return spring 98 (FIG. 2). The carrier 90 includes a body 100 in the form of a cylinder section that is complementary to the main portion 70 of the plug body 40, such that the carrier 90 and the main portion 70 combine to form a cylinder that fits inside the lock cylinder body 12. The carrier 90 includes a curved surface 102 and a flat surface 104. The curved surface 102 includes a locking bar recess 106 and a spring catch recess 108. The locking bar recess 106 further includes a pair of return spring-receiving bores 109 (FIG. 17c) for receiving the locking bar return springs. The flat surface 104 includes a plurality of parallel rack-receiving slots 103 extending perpendicular to the longitudinal axis of the carrier. A semi-circular groove 111 extends along the flat surface 104 parallel to the longitudinal axis of the carrier 90. The back end of the carrier 90 includes a recess 112 for receiving the return spring 98.

Each spring-loaded pin 38 includes a pin 113 and a biasing spring 115. The pins 113, illustrated in FIGS. 20a-20b, are generally cylindrical with annular gear teeth 114 and a central longitudinal bore 116 for receiving biasing springs 115 (FIG. 2). The racks 92, illustrated in FIGS. 18a-18b, include a pin-engaging surface 118 having a plurality of gear teeth 122 configured to engage the annular gear teeth 114 on the pins 113, as illustrated in FIGS. 7 and 12, and a semi-circular recess 124 for engaging the bullet-shaped, rack-engaging features 78 on the planar surface 72, as illustrated in FIG. 12. The racks 92 further include a second surface 126 that includes a plurality of anti-pick grooves 128 and a pair of locking bar-engaging grooves 132.

The spring-loaded locking bar 94, illustrated in FIGS. 21a-22b, is sized and configured to fit in the locking bar recess 106 in the carrier 90 and includes a triangular edge 134 configured to fit in the V-shaped locking bar-engaging groove 29. Opposite the triangular edge 134, the locking bar 94 includes a pair of longitudinally extending gear teeth 136 configured to engage the locking bar-engaging grooves 132 formed in the racks 92, as illustrated in FIG. 12.

The spring-retaining cap 82, illustrated in FIGS. 22a-22d, includes a curvilinear portion 140 having an upper surface 142 and a lower surface 144. The thickness of the curvilinear portion 140 is set to allow the curvilinear portion 140 to fit in the recess 80 with the upper surface 142 flush with the intermediate portion 46 of the plug body 40, as illustrated in FIGS. 7 and 12. A plurality of spring alignment tips 146 extend from

the lower surface **144** to engage the springs **115**. In addition, a pair of cap retaining tips **152** extend from the lower surface **144** to engage alignment openings **154** formed in the plug body **40** (FIGS. **16e-16f**).

To assemble the lock cylinder **10**, the pins **113** and spring **115** are disposed in the channels **74** of the plug body **40**. The spring-retaining cap **82** is placed in the recess **80**, with the cap retaining tips **152** disposed in the alignment openings **154** and the spring alignment tips **146** engaged with the springs **115**. The carrier sub-assembly **42** is assembled by placing the racks **92** into the slots **103** and the spring-loaded locking bar **94** into the locking bar recess **106**, with the gear teeth **136** engaging the locking bar-engaging grooves **132** formed in the racks **92**. The spring catch **96** is disposed in the spring catch recess **108** of the carrier **90**. A valid key **160** is inserted into the keyway **52**, the return spring **98** is compressed into the return spring recess **112**, and the carrier sub-assembly is placed adjacent the plug body **40**, as illustrated in FIG. **3**. The plug assembly **14** is placed in the lock cylinder body **12** and the retainer **16** is disposed in the slots **66** formed in the plug body **40** to retain the plug assembly **14** in the cylinder body **12**. The lock cylinder **10** is now keyed to the valid key **160**.

The properly keyed lock cylinder **10**, without the key **160** inserted, is illustrated in FIGS. **4-7**. The pins **113** are biased to the bottom of the channels **74** and, based on the cut of the key **160**, the racks **92** are disposed at various positions in the slots **103** of the carrier **90**. In this configuration, the locking bar **94** extends from the carrier **90** to engage the groove **29** in the cylinder body **12** to prevent the plug assembly **14** from rotating in the cylinder body **12** and the racks **92** engage the pins **113**, as illustrated in FIG. **4**. In addition, the bullet-shaped features **78** are misaligned with the groove **111** in the racks **92** and therefore interfere with movement of the racks **92** parallel to the longitudinal axis of the lock cylinder **10**, preventing the lock cylinder **10** from being rekeyed.

The internal configuration of a lock cylinder **10** with the valid key **160** inserted therein at the home position is illustrated in FIGS. **8-12**. In this configuration, the locking bar **94** is free to cam out of the groove **29** in the cylinder body **12**, as depicted in FIGS. **8, 9** and **12**. The bits of the key **160** lift the pins **113** in the channels **74** and thereby re-position the racks **92** in the slots **103**. When repositioned, the racks **92** are disposed to align the locking bar-engaging grooves **132** with the extended gear teeth **136** on the locking bar **94**. The locking bar **94** is free to cam out of the groove **29** as the key **160** is rotated. At the same time, the bullet-shaped features **78** are aligned with the groove **111** in the racks **92**, as illustrated in FIG. **12**, allowing the racks **92**, and the carrier **90**, to move parallel to the longitudinal axis of the lock cylinder **10**.

To rekey the lock cylinder **10**, the valid key **160** is inserted into the keyway **52**, as illustrated in FIGS. **13-14** and rotated approximately 45° counterclockwise from the home position until the spring catch **96** moves into the second detent recess **32** formed in the cylinder body **12**. A paperclip or other pointed device **162** is inserted into the tool opening **54** and pushed against the carrier **90** to move the carrier **90** parallel to the longitudinal axis of the lock cylinder **10** until the spring catch **96** moves into the first detent recess **30**, and the pointed device **162** is removed. With the spring catch **96** disposed in the first detent recess **30**, the racks **92** are disengaged from the pins **113**, as illustrated in FIG. **14**. The valid key **160** is removed and a second valid key is inserted and rotated clockwise to release the spring catch **96**. As the spring catch **96** leaves the first detent recess **30**, the carrier **90** is biased toward the plug face **44** by the return spring **98**, causing the racks **92** to re-engage the pins **113**. At this point, the lock cylinder **10** is keyed to the second valid key and the first valid key **160** no

longer operates the lock cylinder **10**. The lock cylinder **10** can be rekeyed to fit a third valid key by replacing the first and second valid keys in the above procedures with the second and third valid keys, respectively.

An alternative embodiment **210** of the invention is illustrated in FIGS. **23-29**. The alternative embodiment includes the same components, as illustrated in FIG. **23**, but several of the components have been modified. Functionally, both embodiments are the same.

The modified housing **212**, illustrated in FIGS. **23** and **24**, includes a plurality of apertures **214** running longitudinally along the bottom thereof and a pair of vertical grooves **216**, **218** formed in the housing sidewall. In addition, the sidewall includes a removable side panel **220**. The rectangular holes **214** are positioned to allow the use of a manual override tool. The center groove **216** includes an aperture **222** extending through the housing sidewall. The aperture **222** allows a user to move the locking bar during a manual override operation. The side panel **220** provides access for performing certain operations while changing the master key of the lock cylinder.

The modified pin biasing springs **226**, illustrated in FIGS. **23** and **25**, include a non-constant diameter, with the last few coils at each end of the springs **226** having a reduced diameter. The tapering allows for a greater spring force in a smaller physical height.

The modified spring catch **228**, illustrated in FIGS. **23** and **26**, includes a central U-shaped portion **230** and a pair of arms **232** extending from the U-shaped portion **230**.

The modified carrier **236**, illustrated in FIGS. **23** and **27**, includes means for retaining the spring catch **228** in the spring catch recess **238**. In the illustrated embodiment, this includes a guide **240** projecting outwardly in the center of the spring catch recess **238** and a pair of anchors **242** radially offset from the guide **240**. The guide **240** prevents the spring catch **228** from moving transversely in the recess **238** while permitting it to move radially outwardly to engage the housing **12**, **212** as described above. The anchors **242** engage the arms **232** of the spring catch **228** and prevent the arms **232** from splaying outwardly, thereby directing the compressive force of the spring catch **228** to extend the U-shaped portion **230** outwardly to engage the housing **12**, **212**.

The modified pins **244**, illustrated in FIGS. **23** and **28**, include a single gear tooth **246** instead of the plurality of gear teeth of the pins **113** described above. The single gear tooth **246**, which preferably includes beveled sides **248**, provides for a smoother engagement with the racks during the rekeying process.

The modified racks **250**, illustrated in FIGS. **23** and **29**, include beveled gear teeth to improve the engagement with the pins during the rekeying process. In addition, the pair of locking bar-engaging grooves **132** in the racks **92** are replaced with a single locking bar-engaging groove **251**.

The modified locking bar **252**, illustrated in FIGS. **23** and **30**, is thinner than locking bar **94** and replaces the pair of gear teeth **136** with a single gear tooth **256** and rounds out the triangular edge **134**. The thinner design reduces any rocking of the locking bar **252** in the locking bar recess **106**.

A kit may be provided that facilitates the rekeying of a lock cylinder with respect to a master keying system. The kit may include, for example, a rack carrier moving tool **162**, such as an elongate pin, e.g., a straightened portion of a paper clip, for moving a rack carrier, such as for example carrier **236**, in a longitudinal direction of the lock cylinder, such as that of the lock cylinder **210** of the alternative embodiment. Alternatively, the rack carrier moving tool **162** may be provided by the user.

The kit includes a rack removal key **310** (shown in FIG. **31**) and a rack removal tool **312** (shown in FIG. **32**). The rack removal key **310** is configured for insertion into a keyway, such as the keyway **314** of the plug assembly **316** shown in FIG. **33**. The rack removal key **310** has a first cut **318** defining a surface **320** having a first lift amount **322** for lifting the pins, e.g., pins **244**, and in turn, the racks, e.g., racks **250**, which may be installed in the lock cylinder **210**, and more precisely, installed in the plug assembly **316**. The rack removal tool **312** is also configured for insertion into the keyway **314**. The rack removal tool **312** has a second cut **326** defining a surface **328** having a second lift amount **330** for lifting the pins, e.g., pins **244**, and in turn, the racks, e.g., racks **250**, which may be installed in the lock cylinder **210**, and more precisely, installed in the plug assembly **316**. The second lift amount **330** of the rack removal tool **312** is greater than the first lift amount **322** of the rack removal key **310**.

Referring to FIG. **34**, the kit further includes a plurality of master racks **332**, which may be replacement master racks, including, for example, individual master racks **332A-332E**. In the embodiments shown, each master rack of the plurality of master racks **332** has a first locking bar-receiving groove **334**. The first locking bar-receiving groove **334** is located along a neutral axis **336**. At least a second locking bar-receiving groove **338A, 338B, 338C, 338D, 338E**, respectively, may be variously spaced from the neutral axis **336**. Also, each master rack of the plurality of replacement master racks has a protrusion groove **335** for receiving the protrusion features, e.g., rack engaging features, **344**, on the plug body **340** of the plug assembly **316** (see FIG. **23**), and which are spaced a common distance from neutral axis **336**. The configuration of the plurality of master racks **332**, and the various spacing of the second locking bar-receiving grooves, e.g., **338A, 338B, 338C, 338D, 338E**, respectively, from the neutral axis **336** for each master rack **332A-332E** may be correlated to a particular master key. The second locking bar-receiving groove **338A-338E** may be anywhere above or below the first locking bar-receiving groove **334**. The purpose of the second locking bar-receiving groove **338A-338E** is for the master keying capability of the lock cylinder **210**.

FIG. **35** shows the position of the plurality of master racks **332** when a tenant key has been inserted in the keyway **314** of the plug assembly **316**. The plug assembly **316** is still able to rotate in the cylinder body **212**, with the locking bar **364** engaging individual grooves of the plurality of master racks **332**. However, with the plurality of master racks **332** not having lined up along the neutral axis **336**, the lock cylinder **210** cannot be rekeyed.

FIGS. **36A-36C** show a detailed flowchart of one embodiment of a method for rekeying the lock cylinder **210** of the master keying system, which may utilize components of the kit described above in relation to FIGS. **31-35**. This method will be described with further reference to FIGS. **37-52**.

At step **S100**, and with reference to FIGS. **23** and **33**, a lock cylinder **210** is provided for rekeying. The lock cylinder **210** includes a cylinder body **212** with a longitudinal axis **342**, and with the plug assembly **316** disposed in the cylinder body **212**. The plug assembly **316** includes the keyway **314**, the plug body **340** having the plurality of protrusion features **344**, and a carrier sub-assembly **346** disposed adjacent the plug body **340**. The carrier sub-assembly **346** is moveable parallel to the longitudinal axis **342** of the cylinder body **212** between a first position, e.g., an initial position, and a second position, e.g., a retracted position. The plug assembly **316** includes the plurality of pins **244** and the plurality of racks **348**, as shown in FIG. **23**, or alternatively the plurality of master racks **332**, as shown in FIG. **34**, for engaging the pins **244**. Each rack of

the plurality of racks **348** has a locking bar-receiving groove **350** and a protrusion groove **352**.

At step **S102**, a valid master key **354** is inserted into the keyway **314**.

At step **S104**, as depicted in FIG. **33**, the valid master key **354** is rotated to rotate the plug assembly **316** from an original position along the x-axis by approximately 90 degrees in a first rotational direction, e.g., counterclockwise, respective to the X-axis.

At step **S106**, with reference to FIGS. **37** and **38**, the carrier sub-assembly **346**, which includes master racks **332** in the configuration of FIG. **38**, is moved in a direction **356** to a retracted position to decouple the plurality of master racks **332**, as shown, from the plurality of pins **244** and position the protrusion groove **335** of each rack **332A-332E** over a corresponding protrusion feature **344** (see also FIG. **34**) on the plug body **340**. The movement of carrier sub-assembly **346** may be effected by rack carrier moving tool **162** by inserting tool **162** into the rekeying tool opening **358** in the plug face **360** of the plug assembly **316**. FIG. **37** shows the position of the carrier sub-assembly **346**, which includes the plurality of master racks **332**, as it is pushed backwards by tool **162** to the retracted position. FIG. **38** shows the placement of the plurality of master racks **332** after carrier sub-assembly **346** is pushed back to the retracted position. As shown, the protrusion engaging groove of each of the master racks **332** rides up over the corresponding protrusion feature **344** on the plug body **340**.

At step **S108**, the valid master key **354** is removed from the keyway **314**. Referring to FIG. **39**, once the master key **354** is removed, the protrusion groove **335** of each of the plurality of master racks **332** will remain over the corresponding protrusion feature **344** on the plug body **340**, and the pins **244** will ride up against a ledge of the plug body **340**.

At step **S110**, the rack removal key **310** is inserted in the keyway **314**, as shown in FIG. **40**. As described above, the rack removal key **310** has a cut **318** that lifts the plurality of pins **244** by a first amount, and in turn lifts the plurality of master racks **332**. The relatively low cut **318** of rack removal key **310**, in comparison to the cut **326** of the rack removal tool **312**, is selected to locate all the racks at the neutral axis **336**.

At step **S112**, the plug assembly **316** is rotated by an additional 90 degrees in the first rotational direction, e.g., counterclockwise, by a corresponding rotation of the rack removal key **310**, so as to release the carrier sub-assembly **346** from the retracted position to reengage the plurality of master racks **332** with the plurality of pins **244**. For example, as shown in FIG. **23**, the plug catch **228** disengages from the slot (not shown) on the cylinder body **212** allowing the carrier spring **362** to push the carrier **236** of the carrier sub-assembly **346** forward to the first position, e.g., the initial position. As a result, in the present embodiment, the plurality of master racks **332** are reengaged with the tooth, or teeth, of the respective plurality of pins **244**.

At step **S114**, a removable side panel **220** is removed (see FIG. **23**) from the cylinder body **212** to disengage the locking bar **364** (see FIG. **41**) from the locking bar-receiving groove of each rack **332A-332E**, thereby decoupling all of the plurality of master racks **332** from each other rack. The position of the plurality of master racks **332** is as shown in FIG. **42**.

At step **S116**, the rack removal key **310** is removed from the keyway **314**.

At step **S118**, the rack removal tool **312** is inserted into the keyway **314**. As described above, the rack removal tool **312** has a cut **326** that lifts the plurality of pins **244** by a second amount greater than the first amount associated with the cut **318** of the rack removal key **310**. The rack removal tool **312**

11

lifts the plurality of master racks **332** to a position such that the entirety of the plurality of master racks **332**, including the protrusion grooves **335**, will be above the protrusion features **344** on the plug body **340**.

At step **S120**, the carrier sub-assembly **346** is subsequently moved to the retracted position to decouple the plurality of master racks **332** from the plurality of pins **244** and position each rack **332A-332E** above the corresponding protrusion feature **344** on the plug body **340**, as shown in FIG. **43**. The movement of carrier sub-assembly may be effected by rack carrier moving tool **162**, by inserting tool **162** into the rekeying tool opening **358** in the plug face **360** of the plug assembly **316**.

At step **S122**, one or more of the current plurality of master racks **332A-332E** may now be removed from access holes **366** in the cylinder body **212** (see FIG. **44**). In some cases, as in this example, each of the plurality of master racks **332** will be replaced by a corresponding plurality of replacement master racks **368** shown in FIG. **45**, individually identified as **368A-368E**.

At step **S124**, each of the plurality of replacement master racks **368** is inserted through a respective access hole **366** in cylinder body **212**. The position of the plurality of replacement master racks **368** after the master racks **368** are inserted through the access holes **366** will be substantially like that of the plurality of master racks **332** shown in FIG. **43**, wherein the plurality of replacement master racks **368** will be above, e.g., sitting on top of, the protrusion features **344** of the plug body **340**.

At step **S126**, the carrier sub-assembly **346** is released from the retracted position to engage the plurality of replacement master racks **368** with the plurality of pins **244**, as shown in FIG. **46**. Since no detent is provided in this example to hold the carrier sub-assembly **346** in the retracted position when the plug body **340** has been rotated by approximately 180 degrees, the carrier sub-assembly **346** is manually held in the retracted position, and manually released from the retracted position to move the plurality of replacement master racks **368** forward to clear the protrusion features **344** on plug body **340**.

At step **S128**, the rack removal tool **312** is removed from the keyway **314**.

At step **S130**, the rack removal key **310** is reinserted in the keyway **314**. This sets the position of the plurality of pins **244** and in turn lines up the master locking bar-receiving grooves **370** (see FIG. **45**) along the neutral axis **336** of each of the plurality of replacement master racks **368**, and in turn lines up the corresponding protrusion grooves **372** with the corresponding protrusion feature **344** on the plug body **340**, as shown in FIG. **47**. The master locking bar-receiving grooves of the master racks are now positioned to receive the locking bar **364**, as shown in FIG. **48**.

At step **S132**, without removing the rack removal key **310**, the removable side panel **220** is reinstalled as shown in FIG. **49** on to the cylinder body **212** so that the locking bar **364** engages with the master locking bar-receiving groove **370** of each replacement master rack **368A-368E** of the plurality of replacement master racks **368**, thereby coupling all of the plurality of replacement master racks **368** together.

At step **S134**, the plug assembly **316** is rotated by approximately 90 degrees in a second rotational direction, e.g., clockwise, opposite to the first rotational direction, by a corresponding rotation of rack removal key **310**. This places the plug assembly in the learn mode position, as shown in FIG. **50**.

At step **S136**, the carrier sub-assembly **346** is subsequently moved to the retracted position to decouple the plurality of

12

replacement master racks **368** from the plurality of pins **244** and position the protrusion grooves **372** of each replacement master rack **368A-368E** over a corresponding protrusion feature **344** on the plug body **340**. The movement of carrier sub-assembly may be effected by the rack carrier moving tool **162**, by inserting the tool **162** into the rekeying tool opening **358** in the plug face **360** of the plug assembly **316**. The individual positions of each of the plurality of replacement master racks **368** is shown in FIG. **51**.

At step **S138**, the rack removal key **310** is removed from the keyway **314**.

At step **S140**, a new master key **374** is inserted into the keyway **314**, as shown in FIG. **52**.

At step **S142**, the plug body **340** is rotated in the second rotational direction back to the original position, as shown in FIG. **52**, by a corresponding rotation of the new master key **374**, to release the carrier sub-assembly **346** from the retracted position to reengage the plurality of replacement master racks **368** with the plurality of pins **244**, to thereby learn the cut of the new master key **374**, thereby completing the rekeying of lock cylinder **210** to the new master key **374**.

The above-described embodiments, of course, are not to be construed as limiting the breadth of the present invention. Modifications and other alternative constructions will be apparent that are within the spirit and scope of the invention as defined in the appended claims.

The invention claimed is:

1. A kit for a master keying system, comprising:

a plurality of replacement master racks;
a rack removal key for insertion into a keyway, the rack removal key having a first cut defining a first lift amount;
a rack removal tool for insertion into the keyway, the rack removal tool having a second cut defining a second lift amount, the second lift amount being greater than the first lift amount and

wherein a lock cylinder to be keyed has a rack carrier configured to selectively carry one of a first plurality of racks and the plurality of replacement master racks, the kit further comprising a rack carrier moving tool configured to move the rack carrier in a longitudinal direction.

2. A kit for a master keying system, comprising:

a plurality of replacement master racks;
a rack removal key for insertion into a keyway, the rack removal key having a first cut defining a first lift amount;
a rack removal tool for insertion into the keyway, the rack removal tool having a second cut defining a second lift amount, the second lift amount being greater than the first lift amount;

wherein a lock cylinder to be keyed has a rack carrier configured to selectively carry one of a first plurality of racks and the plurality of replacement master racks, the kit further comprising a rack carrier moving tool configured to move the rack carrier in a longitudinal direction; and

wherein each rack of the plurality of replacement master racks has a first locking bar-receiving groove along a neutral axis and at least a second locking bar-receiving groove spaced from the neutral axis.

3. A kit for a master keying system, comprising:

a plurality of replacement master racks;
a rack removal key for insertion into a keyway, the rack removal key having a first cut defining a first lift amount;
a rack removal tool for insertion into the keyway, the rack removal tool having a second cut defining a second lift amount, the second lift amount being greater than the first lift amount;

a master key; and

wherein a lock cylinder to be keyed has a rack carrier configured to selectively carry one of a first plurality of racks and the plurality of replacement master racks, the kit further comprising a rack carrier moving tool configured to move the rack carrier in a longitudinal direction. 5

4. The kit of claim 1, wherein each of the rack removal key and rack removal tool is configured to facilitate removal of a first plurality of racks, carried by a rack carrier of a lock cylinder to be keyed, for replacement by the plurality of replacement master racks. 10

5. The kit of claim 4, further comprising a master key.

6. The kit of claim 1, wherein the first lift amount of the first cut is constant along a length of the rack removal key, and the second lift amount of the second cut is constant along a length of the rack removal tool. 15

* * * * *