



US008675177B2

(12) **United States Patent**  
**Kudo et al.**

(10) **Patent No.:** **US 8,675,177 B2**  
(45) **Date of Patent:** **Mar. 18, 2014**

(54) **EXPOSURE METHOD AND APPARATUS, AND METHOD FOR FABRICATING DEVICE WITH LIGHT AMOUNT DISTRIBUTION HAVING LIGHT LARGER IN FIRST AND SECOND PAIRS OF AREAS**

(75) Inventors: **Takehito Kudo**, Kumagaya (JP);  
**Shigeru Hirukawa**, Tokyo (JP)

(73) Assignee: **Nikon Corporation**, Tokyo (JP)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/902,277**

(22) Filed: **Sep. 20, 2007**

(65) **Prior Publication Data**

US 2008/0024747 A1 Jan. 31, 2008

**Related U.S. Application Data**

(60) Division of application No. 11/246,642, filed on Oct. 11, 2005, now Pat. No. 7,446,858, which is a continuation of application No. PCT/JP2004/004522, filed on Mar. 30, 2004.

(30) **Foreign Application Priority Data**

Apr. 9, 2003 (JP) ..... 2003-105920  
Aug. 25, 2003 (JP) ..... 2003-299628  
Aug. 29, 2003 (JP) ..... 2003-307806  
Sep. 19, 2003 (JP) ..... 2003-329194  
Sep. 22, 2003 (JP) ..... 2003-329309

(51) **Int. Cl.**  
**G03B 27/72** (2006.01)

(52) **U.S. Cl.**  
USPC ..... 355/71

(58) **Field of Classification Search**  
USPC ..... 355/71, 67, 53  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,146,294 A 8/1964 Koester et al.  
3,180,216 A 4/1965 Osterberg  
3,758,201 A 9/1973 MacNeille  
3,892,469 A 7/1975 Lotspeich  
3,892,470 A 7/1975 Lotspeich  
4,103,260 A 7/1978 Buchman  
4,175,830 A 11/1979 Marié  
4,198,123 A 4/1980 Kremen  
4,211,471 A 7/1980 Marie  
4,286,843 A 9/1981 Reytblatt

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1453645 A 5/2003  
CN 1501175 A 6/2004

(Continued)

OTHER PUBLICATIONS

Translation of JP-A-2002-324743, filed Nov. 8, 2002.

(Continued)


*Primary Examiner* — Chia-how Michael Liu

(74) *Attorney, Agent, or Firm* — Oliff PLC

(57) **ABSTRACT**

An exposure method and apparatus simultaneously transfer patterns with various pitches with high resolution. On the pupil surface of an illumination system, at least first and second pairs of areas are set. The distribution of intensity of light over the pupil surface is set so that the intensities of light of the second pair of areas is smaller than that of the first pair of areas.

**19 Claims, 20 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

4,346,164 A	8/1982	Tabarelli et al.	6,674,514 B2	1/2004	Shinoda
4,370,026 A	1/1983	Dubroeuq et al.	6,680,798 B2	1/2004	Kreuzer
4,744,615 A	5/1988	Fan et al.	6,698,891 B2	3/2004	Kato
4,755,027 A	7/1988	Schafer	6,710,855 B2	3/2004	Shiraishi
4,952,815 A	8/1990	Nishi	6,762,824 B2	7/2004	Mori
5,072,126 A	12/1991	Progler	6,769,273 B1	8/2004	Nakagawa et al.
5,216,541 A	6/1993	Takesue et al.	6,771,350 B2	8/2004	Nishinaga
5,251,222 A	10/1993	Hester et al.	6,774,984 B2	8/2004	Gerhard
5,253,110 A	10/1993	Ichihara et al.	6,831,731 B2	12/2004	Omura et al.
5,272,501 A	12/1993	Nishi et al.	6,836,380 B2	12/2004	Kreuzer
5,312,513 A	5/1994	Florence et al.	6,842,223 B2	1/2005	Tyminski
5,345,292 A	9/1994	Shiozawa et al.	6,844,982 B2	1/2005	Omura
5,365,371 A	11/1994	Kamon	6,856,379 B2	2/2005	Schuster
5,382,999 A	1/1995	Kamon	6,864,961 B2	3/2005	Omura
5,436,761 A	7/1995	Kamon	6,870,668 B2	3/2005	Ozawa
5,448,336 A	9/1995	Shiraishi	6,885,493 B2	4/2005	Ljungblad et al.
5,459,000 A	10/1995	Unno	6,891,655 B2	5/2005	Grebinski et al.
5,467,166 A	11/1995	Shiraishi	6,900,915 B2	5/2005	Nanjyo et al.
5,473,465 A	12/1995	Ye	6,913,373 B2	7/2005	Tanaka et al.
5,541,026 A	7/1996	Matsumoto	6,958,806 B2	10/2005	Mulder et al.
5,559,583 A	9/1996	Tanabe	6,965,484 B2	11/2005	Shaver
5,610,684 A	3/1997	Shiraishi	6,970,233 B2	11/2005	Blatchford
5,621,498 A *	4/1997	Inoue et al. .... 355/67	6,977,718 B1	12/2005	LaFontaine
5,627,626 A	5/1997	Inoue et al.	6,999,157 B2 *	2/2006	Kohno ..... 355/53
5,631,721 A	5/1997	Stanton et al.	7,009,686 B2 *	3/2006	Kawashima et al. .... 355/67
5,663,785 A	9/1997	Kirk et al.	7,031,077 B2	4/2006	Kreuzer
5,673,103 A	9/1997	Inoue et al.	7,038,763 B2	5/2006	Mulder et al.
5,677,755 A	10/1997	Oshida et al.	7,061,583 B2	6/2006	Mulkens et al.
5,677,757 A	10/1997	Taniguchi et al.	7,095,546 B2	8/2006	Mala et al.
5,684,567 A	11/1997	Shiozawa	7,098,992 B2	8/2006	Ohtsuki et al.
5,691,803 A	11/1997	Song et al.	7,145,720 B2	12/2006	Krahmer et al.
5,707,501 A	1/1998	Inoue et al.	7,217,503 B2	5/2007	Saitoh et al.
5,739,898 A	4/1998	Ozawa et al.	7,239,446 B2	7/2007	Kreuzer
5,841,500 A	11/1998	Patel	7,245,353 B2	7/2007	Mulkens et al.
5,933,219 A	8/1999	Unno	7,245,355 B2	7/2007	Mulkens et al.
5,969,441 A	10/1999	Loopstra et al.	7,295,286 B2	11/2007	Matsuura
6,031,658 A	2/2000	Riza	7,345,740 B2	3/2008	Wagner et al.
6,191,829 B1	2/2001	Hashimoto	7,408,616 B2	8/2008	Gruner et al.
6,191,880 B1	2/2001	Schuster	7,433,046 B2	10/2008	Everett et al.
6,208,407 B1	3/2001	Loopstra	7,446,858 B2	11/2008	Kudo et al.
6,211,944 B1	4/2001	Shiraishi	7,847,921 B2	12/2010	Gruner et al.
6,229,647 B1	5/2001	Takahashi et al.	8,259,393 B2	9/2012	Fiolka et al.
6,233,041 B1	5/2001	Shiraishi	8,270,077 B2	9/2012	Fiolka et al.
6,238,063 B1	5/2001	Tanitsu et al.	8,279,524 B2	10/2012	Fiolka et al.
6,252,647 B1	6/2001	Shiraishi	8,289,623 B2	10/2012	Fiolka et al.
6,252,712 B1	6/2001	Fürter et al.	8,320,043 B2	11/2012	Fiolka et al.
6,259,512 B1	7/2001	Mizouchi	2001/0012154 A1	8/2001	Schuster
6,304,317 B1	10/2001	Taniguchi et al.	2001/0019404 A1	9/2001	Schuster et al.
6,333,776 B1	12/2001	Taniguchi	2001/0035942 A1	11/2001	Hara et al.
6,341,007 B1	1/2002	Nishi et al.	2001/0052968 A1	12/2001	Shiozawa
6,361,909 B1	3/2002	Gau et al.	2002/0001134 A1	1/2002	Shinoda
6,366,404 B1	4/2002	Hiraiwa et al.	2002/0008863 A1	1/2002	Taniguchi et al.
6,373,614 B1	4/2002	Miller	2002/0024008 A1	2/2002	Iizuka
6,392,800 B2	5/2002	Schuster	2002/0027719 A1	3/2002	Kreuzer
6,400,441 B1	6/2002	Nishi et al.	2002/0080338 A1	6/2002	Taniguchi
6,404,482 B1 *	6/2002	Shiraishi ..... 355/53	2002/0085176 A1	7/2002	Hiraiwa et al.
6,406,148 B1	6/2002	Marshall et al.	2002/0085276 A1	7/2002	Tanitsu et al.
6,452,662 B2	9/2002	Mulkens et al.	2002/0101572 A1	8/2002	Shiraishi
6,466,303 B1	10/2002	Omura et al.	2002/0126380 A1	9/2002	Schuster
6,483,573 B1	11/2002	Schuster	2002/0152452 A1	10/2002	Socha
6,498,869 B1	12/2002	Yao	2002/0167653 A1	11/2002	Mulkens et al.
6,522,483 B2	2/2003	Kreuzer	2002/0176166 A1 *	11/2002	Schuster ..... 359/494
6,535,273 B1	3/2003	Maul	2002/0177048 A1	11/2002	Saitoh et al.
6,538,247 B2	3/2003	Iizuka	2002/0177054 A1 *	11/2002	Saitoh et al. .... 430/22
6,549,269 B1	4/2003	Nishi et al.	2002/0186462 A1	12/2002	Gerhard
6,577,379 B1	6/2003	Boettiger et al.	2002/0191288 A1	12/2002	Gruner et al.
6,583,931 B2	6/2003	Hiraiwa et al.	2002/0196416 A1	12/2002	Shiraishi
6,590,634 B1	7/2003	Nishi et al.	2003/0007158 A1	1/2003	Hill
6,597,430 B1	7/2003	Nishi et al.	2003/0025890 A1	2/2003	Nishinaga
6,606,144 B1	8/2003	Omura	2003/0038225 A1	2/2003	Mulder et al.
6,636,295 B2	10/2003	Shiozawa	2003/0038931 A1	2/2003	Toyoda et al.
6,646,690 B1	11/2003	Takezawa	2003/0043356 A1	3/2003	Shiraishi
6,661,499 B2	12/2003	Omura et al.	2003/0053036 A1	3/2003	Fujishima et al.
6,665,119 B1	12/2003	Kurtz et al.	2003/0086071 A1	5/2003	McGuire, Jr.
6,674,513 B2	1/2004	Omura	2003/0098959 A1	5/2003	Hagiwara et al.
			2003/0128349 A1	7/2003	Unno
			2003/0133099 A1	7/2003	Shiode
			2003/0160949 A1	8/2003	Komatsuda et al.
			2003/0174400 A1	9/2003	Patel et al.



(56)

References Cited

U.S. PATENT DOCUMENTS

2003/0206289 A1 11/2003 Matsuyama  
 2003/0214571 A1 11/2003 Ishikawa et al.  
 2004/0004771 A1 1/2004 Omura  
 2004/0012764 A1 1/2004 Mulder et al.  
 2004/0053148 A1 3/2004 Morohoshi  
 2004/0057034 A1 3/2004 Zinn et al.  
 2004/0057036 A1\* 3/2004 Kawashima et al. .... 355/77  
 2004/0100629 A1 5/2004 Stokowski et al.  
 2004/0104654 A1 6/2004 Lee et al.  
 2004/0119954 A1 6/2004 Kawashima et al.  
 2004/0120044 A1 6/2004 Kreuzer  
 2004/0160582 A1 8/2004 Lof et al.  
 2004/0169924 A1 9/2004 Flagello et al.  
 2004/0174512 A1 9/2004 Toyoda et al.  
 2004/0180278 A1 9/2004 Sato et al.  
 2004/0184019 A1 9/2004 Totzeck et al.  
 2004/0207386 A1 10/2004 Durr  
 2004/0227923 A1 11/2004 Flagello et al.  
 2004/0240073 A1 12/2004 Gerhard  
 2005/0024612 A1 2/2005 Hirukawa et al.  
 2005/0094268 A1 5/2005 Fiolka et al.  
 2005/0095749 A1 5/2005 Krellmann et al.  
 2005/0122499 A1 6/2005 Omura et al.  
 2005/0128458 A1 6/2005 Blatchford  
 2005/0134825 A1 6/2005 Schuster  
 2005/0146704 A1 7/2005 Gruner et al.  
 2005/0168790 A1 8/2005 Latypov et al.  
 2005/0237509 A1 10/2005 Blatchford  
 2005/0237527 A1 10/2005 Mori  
 2005/0264885 A1 12/2005 Albert  
 2005/0270608 A1 12/2005 Shiozawa et al.  
 2006/0012769 A1 1/2006 Suzuki  
 2006/0050261 A1 3/2006 Brotsack  
 2006/0055834 A1 3/2006 Tanitsu et al.  
 2006/0055909 A1 3/2006 Fiolka et al.  
 2006/0072095 A1 4/2006 Kudo et al.  
 2006/0077370 A1 4/2006 Mulkens et al.  
 2006/0092398 A1 5/2006 McCarthy  
 2006/0132748 A1 6/2006 Fukuhara  
 2006/0139611 A1 6/2006 Wagner et al.  
 2006/0146384 A1 7/2006 Schultz et al.  
 2006/0158624 A1 7/2006 Toyoda  
 2006/0164711 A1 7/2006 Govil et al.  
 2006/0170901 A1 8/2006 Tanitsu et al.  
 2006/0171138 A1 8/2006 Muramatsu et al.  
 2006/0203214 A1 9/2006 Shiraishi  
 2006/0203341 A1 9/2006 Schuster  
 2006/0232841 A1 10/2006 Toishi et al.  
 2006/0291057 A1 12/2006 Fiolka et al.  
 2007/0008511 A1 1/2007 De Boeij et al.  
 2007/0019179 A1 1/2007 Fiolka et al.  
 2007/0058151 A1 3/2007 Eurlings et al.  
 2007/0081114 A1 4/2007 Fiolka et al.  
 2007/0146676 A1 6/2007 Tanitsu et al.  
 2007/0183017 A1 8/2007 Hembd  
 2007/0201338 A1 8/2007 Yaoita et al.  
 2007/0263199 A1 11/2007 Fiolka et al.  
 2007/0296936 A1 12/2007 Kato et al.  
 2007/0296941 A1 12/2007 Omura  
 2008/0021948 A1 1/2008 Wilson et al.  
 2008/0030706 A1 2/2008 Yamamoto  
 2008/0030707 A1 2/2008 Tanaka et al.  
 2008/0068572 A1 3/2008 Kudo et al.  
 2008/0316459 A1 12/2008 Fiolka et al.  
 2008/0316598 A1 12/2008 Fiolka et al.  
 2009/0002675 A1 1/2009 Fiolka et al.  
 2009/0073411 A1 3/2009 Tanitsu  
 2009/0073414 A1 3/2009 Tanitsu et al.  
 2009/0073441 A1 3/2009 Tanitsu et al.  
 2009/0091730 A1 4/2009 Tanaka  
 2009/0097007 A1 4/2009 Tanaka  
 2009/0109417 A1 4/2009 Tanitsu  
 2009/0116093 A1 5/2009 Tanitsu  
 2009/0122292 A1 5/2009 Shiraishi  
 2009/0128886 A1 5/2009 Hirota

2009/0147233 A1 6/2009 Toyoda  
 2009/0147234 A1 6/2009 Toyoda  
 2009/0147235 A1 6/2009 Toyoda  
 2009/0185154 A1 7/2009 Tanitsu  
 2009/0185156 A1 7/2009 Kudo et al.  
 2009/0284729 A1 11/2009 Shiraishi  
 2009/0316132 A1 12/2009 Tanitsu et al.  
 2009/0323041 A1 12/2009 Toyoda  
 2010/0141921 A1 6/2010 Omura  
 2010/0141926 A1 6/2010 Omura  
 2010/0142051 A1 6/2010 Omura  
 2011/0037962 A1 2/2011 Tanitsu  
 2011/0069296 A1 3/2011 Gruner et al.  
 2011/0188019 A1 8/2011 Fiolka et al.  
 2011/0205519 A1 8/2011 Kanayamaya et al.  
 2011/0273692 A1 11/2011 Toyoda  
 2011/0273693 A1 11/2011 Toyoda  
 2011/0273697 A1 11/2011 Tanitsu et al.  
 2011/0273698 A1 11/2011 Toyoda  
 2011/0299055 A1 12/2011 Toyoda

FOREIGN PATENT DOCUMENTS

CN 1573571 A 2/2005  
 DE 206 607 2/1984  
 DE 221 563 A1 4/1985  
 DE 224 448 A1 7/1985  
 DE 242 880 A1 2/1987  
 DE 100 29 938 A1 7/2001  
 DE 102 06 061 A1 9/2003  
 DE 103 43 333 A1 4/2005  
 DE 10 2006 015 213 A1 10/2007  
 EP 0 023 231 A1 2/1981  
 EP 0 208 552 A2 1/1987  
 EP 0 230 931 A2 8/1987  
 EP 0 564 264 A1 10/1993  
 EP 0 656 555 A1 6/1995  
 EP 0 744 664 A2 11/1996  
 EP 0 779 530 A1 6/1997  
 EP 0 937 999 A1 8/1999  
 EP 1 014 196 A2 6/2000  
 EP 1 071 292 A2 1/2001  
 EP 1 139 521 A1 10/2001  
 EP 1 211 561 A2 6/2002  
 EP 1 260 849 A1 11/2002  
 EP 1 280 007 A2 1/2003  
 EP 1 489 462 A2 12/2004  
 EP 1 577 709 A2 9/2005  
 EP 1 662 553 A1 5/2006  
 EP 1 674 935 A2 6/2006  
 EP 1 681 710 A1 7/2006  
 EP 1 693 885 A1 8/2006  
 EP 1 798 758 A1 6/2007  
 EP 1 840 945 A1 10/2007  
 EP 1 953 805 A1 8/2008  
 FR 2 474 708 7/1981  
 GB 856621 A 12/1960  
 JP A-44-4993 2/1969  
 JP A-56-6666 1/1981  
 JP A-57-117238 7/1982  
 JP A-57-152129 9/1982  
 JP A-57-153433 9/1982  
 JP A-58-49932 3/1983  
 JP U-58-45502 3/1983  
 JP A-58-115945 7/1983  
 JP A-58-202448 11/1983  
 JP A-59-19912 2/1984  
 JP A-59-155843 9/1984  
 JP A-59-226317 12/1984  
 JP A-61-44429 3/1986  
 JP A-61-45923 3/1986  
 JP A-61-91662 5/1986  
 JP A-61-091662 5/1986  
 JP U-61-94342 6/1986  
 JP A-61-156736 7/1986  
 JP A-61-196532 8/1986  
 JP A-61-217434 9/1986  
 JP A-61-251025 11/1986  
 JP A-61-270049 11/1986

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	A-62-2539	1/1987	JP	A-4-152512	5/1992
JP	A-62-2540	1/1987	JP	A-4-179115	6/1992
JP	A-62-17705	1/1987	JP	A-4-186244	7/1992
JP	A-62-65326	3/1987	JP	U-4-80052	7/1992
JP	A-62-100161	5/1987	JP	A-4-211110	8/1992
JP	A-62-120026	6/1987	JP	A-4-225357	8/1992
JP	A-62-121417	6/1987	JP	A-04-225357	8/1992
JP	A-62-122215	6/1987	JP	A-4-235558	8/1992
JP	A-62-153710	7/1987	JP	A-4-265805	9/1992
JP	A-62-183522	8/1987	JP	A-4-273245	9/1992
JP	A-62-188316	8/1987	JP	A-4-273427	9/1992
JP	A-62-203526	9/1987	JP	A-4-280619	10/1992
JP	A-62-265722	11/1987	JP	A-4-282539	10/1992
JP	A-63-12134	1/1988	JP	A-4-296092	10/1992
JP	A-63-36526	2/1988	JP	A-4-297030	10/1992
JP	A-63-73628	4/1988	JP	A-4-305915	10/1992
JP	A-63-128713	6/1988	JP	A-4-305917	10/1992
JP	A-63-131008	6/1988	JP	U-4-117212	10/1992
JP	A-63-141313	6/1988	JP	A-4-330961	11/1992
JP	A-63-157419	6/1988	JP	A-4-343307	11/1992
JP	A-63-160192	7/1988	JP	A-4-350925	12/1992
JP	A-63-231217	9/1988	JP	A-5-21314	1/1993
JP	A-63-275912	11/1988	JP	A-5-45886	2/1993
JP	A-63-292005	11/1988	JP	A-5-62877	3/1993
JP	A-64-18002	1/1989	JP	A-05-090128	4/1993
JP	A-64-26704	2/1989	JP	A-5-90128	4/1993
JP	A-64-68926	3/1989	JP	A-5-109601	4/1993
JP	A-1-91419	4/1989	JP	A-05-109601	4/1993
JP	A-1-115033	5/1989	JP	A-5-127086	5/1993
JP	A-1-147516	6/1989	JP	A-5-129184	5/1993
JP	A-1-202833	8/1989	JP	A-5-134230	5/1993
JP	A-1-214042	8/1989	JP	A-05-160002	6/1993
JP	U-1-127379	8/1989	JP	A-5-160002	6/1993
JP	A-1-255404	10/1989	JP	A-5-175098	7/1993
JP	A-1-258550	10/1989	JP	A-5-199680	8/1993
JP	A-1-276043	11/1989	JP	A-5-217837	8/1993
JP	A-1-278240	11/1989	JP	A-5-217840	8/1993
JP	A-1-286478	11/1989	JP	A-05-217840	8/1993
JP	A-1-292343	11/1989	JP	A-5-226225	9/1993
JP	A-1-314247	12/1989	JP	A-5-241324	9/1993
JP	A-1-319964	12/1989	JP	A-5-243364	9/1993
JP	A-2-42382	2/1990	JP	A-5-259069	10/1993
JP	A-2-65149	3/1990	JP	A-5-283317	10/1993
JP	A-2-65222	3/1990	JP	A-05-283317	10/1993
JP	A-2-97239	4/1990	JP	A-5-304072	11/1993
JP	A-2-106917	4/1990	JP	A-5-319774	12/1993
JP	A-2-116115	4/1990	JP	A-5-323583	12/1993
JP	A-2-139146	5/1990	JP	A-5-326370	12/1993
JP	A-2-166717	6/1990	JP	A-5-326370	12/1993
JP	A-2-261073	10/1990	JP	06-053120	* 2/1994
JP	A-2-264901	10/1990	JP	A-6-29204	2/1994
JP	A-02-285320	11/1990	JP	A-6-42918	2/1994
JP	A-2-285320	11/1990	JP	A-6-53120	2/1994
JP	A-2-287308	11/1990	JP	A-6-53120	2/1994
JP	A-2-298431	12/1990	JP	A-6-97269	4/1994
JP	A-2-311237	12/1990	JP	A-6-104167	4/1994
JP	A-3-41399	2/1991	JP	A-6-118623	4/1994
JP	A-3-64811	3/1991	JP	A-6-120110	4/1994
JP	A-3-72298	3/1991	JP	B2-6-29102	4/1994
JP	A-3-94445	4/1991	JP	A-6-36054	5/1994
JP	A-3-132663	6/1991	JP	A-6-124126	5/1994
JP	A-3-134341	6/1991	JP	A-6-124872	5/1994
JP	A-3-167419	7/1991	JP	A-06-124872	5/1994
JP	A-3-168640	7/1991	JP	A-06-124873	5/1994
JP	A-3-211812	9/1991	JP	A-6-124873	5/1994
JP	A-3-263810	11/1991	JP	A-6-140306	5/1994
JP	A-4-11613	1/1992	JP	A-6-148399	5/1994
JP	A-4-32154	2/1992	JP	A-06-163350	6/1994
JP	A-4-065603	3/1992	JP	A-6-163350	6/1994
JP	A-4-96315	3/1992	JP	A-6-168866	6/1994
JP	A-04-101148	4/1992	JP	A-6-177007	6/1994
JP	A-4-101148	4/1992	JP	A-6-181157	6/1994
JP	A-4-130710	5/1992	JP	A-6-186025	7/1994
JP	A-4-132909	5/1992	JP	A-6-188169	7/1994
JP	A-4-133414	5/1992	JP	A-6-196388	7/1994
			JP	A-6-196388	7/1994
			JP	A-6-196388	7/1994
			JP	A-6-204113	7/1994
			JP	A-06-204121	7/1994
			JP	A-6-204121	7/1994

\* ..... H01L 21/027



(56)

## References Cited

FOREIGN PATENT DOCUMENTS			JP	A-8-330224	12/1996
JP	A-6-229741	8/1994	JP	A-8-334695	12/1996
JP	A-6-241720	9/1994	JP	A-8-335552	12/1996
JP	A-6-244082	9/1994	JP	A-08-335552	12/1996
JP	A-06-244082	9/1994	JP	A-9-7933	1/1997
JP	A-6-267825	9/1994	JP	A-9-15834	1/1997
JP	A-06-267825	9/1994	JP	A-9-22121	1/1997
JP	A-06-281869	10/1994	JP	A-9-61686	3/1997
JP	A-6-283403	10/1994	JP	A-9-82626	3/1997
JP	A-06-291023	10/1994	JP	A-9-83877	3/1997
JP	A-6-310399	11/1994	JP	A-9-92593	4/1997
JP	A-6-325894	11/1994	JP	A-9-108551	4/1997
JP	A-6-326174	11/1994	JP	A-9-115794	5/1997
JP	A-6-349701	12/1994	JP	A-9-134870	5/1997
JP	A-7-57933	3/1995	JP	A-9-148406	6/1997
JP	A-7-57992	3/1995	JP	A-9-151658	6/1997
JP	A-7-69621	3/1995	JP	A-9-160004	6/1997
JP	A-7-92424	4/1995	JP	A-09-160219	6/1997
JP	A-7-122469	5/1995	JP	A-9-160219	6/1997
JP	A-7-132262	5/1995	JP	A-9-162106	6/1997
JP	A-7-134955	5/1995	JP	A-9-178415	7/1997
JP	A-7-135158	5/1995	JP	A-9-184787	7/1997
JP	A-7-135165	5/1995	JP	A-09-184918	7/1997
JP	H7-122469	5/1995	JP	A-9-184918	7/1997
JP	A-7-147223	6/1995	JP	A-9-186082	7/1997
JP	A-07-147223	6/1995	JP	A-9-190969	7/1997
JP	A-7-161622	6/1995	JP	A-9-213129	8/1997
JP	A-7-167998	7/1995	JP	A-9-219358	8/1997
JP	A-7-168286	7/1995	JP	A-9-219358	8/1997
JP	A-7-174974	7/1995	JP	A-9-227294	9/1997
JP	A-7-176468	7/1995	JP	A-9-232213	9/1997
JP	A-7-183201	7/1995	JP	A-9-243892	9/1997
JP	A-07-183201	7/1995	JP	A-9-246672	9/1997
JP	A-7-183214	7/1995	JP	A-9-251208	9/1997
JP	A-7-190741	7/1995	JP	A-9-281077	10/1997
JP	A-7-201723	8/1995	JP	A-9-325255	12/1997
JP	A-07-201723	8/1995	JP	A-9-326338	12/1997
JP	A-7-220989	8/1995	JP	A-10-002865	1/1998
JP	A-7-220990	8/1995	JP	A-10-3039	1/1998
JP	A-7-220995	8/1995	JP	A-10-20195	1/1998
JP	A-07-220995	8/1995	JP	A-10-32160	2/1998
JP	A-7-221010	8/1995	JP	A-10-38517	2/1998
JP	A-7-230945	8/1995	JP	A-10-38812	2/1998
JP	A-7-239212	9/1995	JP	A-10-55713	2/1998
JP	A-7-243814	9/1995	JP	A-10-62305	3/1998
JP	A-7-245258	9/1995	JP	A-10-64790	3/1998
JP	A-7-263315	10/1995	JP	A-10-79337	3/1998
JP	A-07-263315	10/1995	JP	A-10-82611	3/1998
JP	A-07-283119	10/1995	JP	A-10-503300	3/1998
JP	A-7-283119	10/1995	JP	A-10-92735	4/1998
JP	A-7-297272	11/1995	JP	A-10-97969	4/1998
JP	A-7-307268	11/1995	JP	A-10-104427	4/1998
JP	A 07 307268	11/1995	JP	A-10-116760	5/1998
JP	A-7-318847	12/1995	JP	A-10-116778	5/1998
JP	A-7-335748	12/1995	JP	A-10-135099	5/1998
JP	A-8-10971	1/1996	JP	A-H10-116779	5/1998
JP	A-8-17709	1/1996	JP	A-H10-125572	5/1998
JP	A-8-22948	1/1996	JP	A-H10-134028	5/1998
JP	A-8-37149	2/1996	JP	A-10-163099	6/1998
JP	A-8-37227	2/1996	JP	A-10-163302	6/1998
JP	A-8-46751	2/1996	JP	A-10-169249	6/1998
JP	A-8-63231	3/1996	JP	A-10-189427	7/1998
JP	A-8-115868	5/1996	JP	A-10-189700	7/1998
JP	A-8-136475	5/1996	JP	A-10-206714	8/1998
JP	A-8-151220	6/1996	JP	A-10-208993	8/1998
JP	A-8-162397	6/1996	JP	A-10-209018	8/1998
JP	A-8-166475	6/1996	JP	A-10-214783	8/1998
JP	A-8-171054	7/1996	JP	A-10-228661	8/1998
JP	A-8-195375	7/1996	JP	A-10-255319	9/1998
JP	0 764 858	8/1996	JP	A-10-294268	11/1998
JP	A-8-203803	8/1996	JP	A-10-303114	11/1998
JP	A-8-279549	10/1996	JP	A-10-340846	12/1998
JP	A-8-288213	11/1996	JP	A-11-3849	1/1999
JP	A-8-297699	11/1996	JP	A-11-3856	1/1999
JP	A-8-316125	11/1996	JP	A-11-8194	1/1999
JP	A-8-316133	11/1996	JP	A-11-14876	1/1999
			JP	A-11-16816	1/1999
			JP	A-11-40657	2/1999
			JP	A 11-54426	2/1999

(56)

## References Cited

FOREIGN PATENT DOCUMENTS			JP	A-2001-167996	6/2001
JP	A-11-54426	2/1999	JP	A-2001-176766	6/2001
JP	A-11-74185	3/1999	JP	A-2001-203140	7/2001
JP	A-11-87237	3/1999	JP	A-2001-218497	8/2001
JP	A-11-111601	4/1999	JP	A-2001-228401	8/2001
JP	A-11-111818	4/1999	JP	A-2001-228404	8/2001
JP	A-11-111819	4/1999	JP	A-2001-230323	8/2001
JP	A-11-121328	4/1999	JP	A-2001-242269	9/2001
JP	A-11-135400	5/1999	JP	A-2001-265581	9/2001
JP	A-11-142556	5/1999	JP	A-2001-267227	9/2001
JP	A-11-150062	6/1999	JP	A-2001-272764	10/2001
JP	A-11-159571	6/1999	JP	A-2001-274083	10/2001
JP	A-11-162831	6/1999	JP	A-2001-282526	10/2001
JP	A-11-163103	6/1999	JP	A-2001-284228	10/2001
JP	A-11-164543	6/1999	JP	A-2001-296105	10/2001
JP	A-11-166990	6/1999	JP	A-2001-297976	10/2001
JP	A-11-98	7/1999	JP	A-2001-304332	10/2001
JP	A-11-176727	7/1999	JP	A-2001-307982	11/2001
JP	A-11-176744	7/1999	JP	A-2001-307983	11/2001
JP	A-11-195602	7/1999	JP	A-2001-313250	11/2001
JP	A-11-204390	7/1999	JP	A-2001-338868	12/2001
JP	A-11-204432	7/1999	JP	A-2001-345262	12/2001
JP	A-11-218466	8/1999	JP	A-2002-14005	1/2002
JP	A-11-219882	8/1999	JP	A-2002-15978	1/2002
JP	A-11-233434	8/1999	JP	A-2002-16124	1/2002
JP	A-11-238680	8/1999	JP	B2-3246615	1/2002
JP	A-11-239758	9/1999	JP	A-2002-43213	2/2002
JP	A-11-260686	9/1999	JP	A-2002-57097	2/2002
JP	A-11-260791	9/1999	JP	A-2002-66428	3/2002
JP	A-11-264756	9/1999	JP	A-2002-71513	3/2002
JP	A-11-283903	10/1999	JP	A-2002-75816	3/2002
JP	A-11-288879	10/1999	JP	A-2002-75816	3/2002
JP	A-11-307610	11/1999	JP	A-2002-075816	3/2002
JP	A-11-312631	11/1999	JP	A-2002-075835	3/2002
JP	A-11-354624	12/1999	JP	A-2002-91922	3/2002
JP	A-2000-3874	1/2000	JP	A-2002-93686	3/2002
JP	A-2000-12453	1/2000	JP	A-2002-93690	3/2002
JP	A-2000-21742	1/2000	JP	A-2002-100561	4/2002
JP	A-2000-21748	1/2000	JP	A-2002-118058	4/2002
JP	A-2000-29202	1/2000	JP	A-2002-141270	5/2002
JP	A-2000-32403	1/2000	JP	A-2002-158157	5/2002
JP	A-2000-36449	2/2000	JP	A-2002-162655	6/2002
JP	A-2000-58436	2/2000	JP	A-2002-170495	6/2002
JP	A-2000-58441	2/2000	JP	A-2002-190438	7/2002
JP	A-2000-81320	3/2000	JP	A-2002-195912	7/2002
JP	A-2000-92815	3/2000	JP	A-2002-198284	7/2002
JP	A-2000-97616	4/2000	JP	A-2002-202221	7/2002
JP	A-2000-106340	4/2000	JP	A-2002-203763	7/2002
JP	A-2000-114157	4/2000	JP	A-2002-208562	7/2002
JP	A-2000-121491	4/2000	JP	A-2002-520810	7/2002
JP	A-2000-147346	5/2000	JP	A-2002-222754	8/2002
JP	A-2000-154251	6/2000	JP	A-2002-227924	8/2002
JP	A-2000-180371	6/2000	JP	A 2002-231619	8/2002
JP	A-2000-206279	7/2000	JP	A-2002-231619	8/2002
JP	A-2000-208407	7/2000	JP	A-2002-258487	9/2002
JP	A-2000-240717	9/2000	JP	A-2002-261004	9/2002
JP	A-2000-243684	9/2000	JP	A-2002-263553	9/2002
JP	A-2000-252201	9/2000	JP	A-2002-277742	9/2002
JP	A-2000-283889	10/2000	JP	A-2002-289505	10/2002
JP	A-2000-286176	10/2000	JP	A-2002-289505	10/2002
JP	A-2000-311853	11/2000	JP	A-2002-305140	10/2002
JP	A-2000-323403	11/2000	JP	A-2002-305140	10/2002
JP	A-2001-7015	1/2001	JP	A-2002-323658	11/2002
JP	A-2001-20951	1/2001	JP	A-2002-324743	11/2002
JP	A-2001-23996	1/2001	JP	A 2002-324743	11/2002
JP	A-2001-37201	2/2001	JP	A-2002-329651	11/2002
JP	A-2001-44097	2/2001	JP	A 2002-334836	11/2002
JP	A-2001-74240	3/2001	JP	A-2002-334836	11/2002
JP	A-2001-83472	3/2001	JP	A-2002-353105	12/2002
JP	A-2001-85307	3/2001	JP	A-2002-357715	12/2002
JP	A-2001-97734	4/2001	JP	A-2002-359174	12/2002
JP	A-2001-100311	4/2001	JP	A-2002-362737	12/2002
JP	A-2001-110707	4/2001	JP	A-2002-365783	12/2002
JP	A-2001-118773	4/2001	JP	A-2002-367523	12/2002
JP	A-2001-135560	5/2001	JP	A-2002-367886	12/2002
JP	A-2001-144004	5/2001	JP	A-2002-373849	12/2002
			JP	A-2003-15040	1/2003
			JP	A-2003-015314	1/2003
			JP	A-2003-17003	1/2003
			JP	A-2003-17404	1/2003
			JP	A-2003-28673	1/2003
			JP	A-2003-035822	2/2003



(56)

## References Cited

FOREIGN PATENT DOCUMENTS			JP	A-2004-152705	5/2004
JP	A-2003-35822	2/2003	JP	A-2004-153064	5/2004
JP	A-2003-43223	2/2003	JP	A-2004-153096	5/2004
JP	A-2003-45219	2/2003	JP	A-2004-163555	6/2004
JP	A-2003-45712	2/2003	JP	A-2004-165249	6/2004
JP	A-2003-59799	2/2003	JP	A-2004-165416	6/2004
JP	A-2003-59803	2/2003	JP	A-2004-172471	6/2004
JP	A-2003-059821	2/2003	JP	A-2004-177468	6/2004
JP	A-2003-59821	2/2003	JP	A-2004-179172	6/2004
JP	A-2003-59826	2/2003	JP	A-2004-187401	7/2004
JP	A-2003-68600	3/2003	JP	A-2004-193252	7/2004
JP	A-2003-068600	3/2003	JP	A-2004-193425	7/2004
JP	A-2003-068604	3/2003	JP	A-2004-198748	7/2004
JP	A-2003-75703	3/2003	JP	A-2004-205698	7/2004
JP	A-2003-81654	3/2003	JP	A-2004-207696	7/2004
JP	A-2003-84445	3/2003	JP	A-2004-207711	7/2004
JP	A-2003-90978	3/2003	JP	A-2004-260115	7/2004
JP	A-2003-98651	4/2003	JP	A-2004-520618	7/2004
JP	A-2003-100597	4/2003	JP	A-2004-221253	8/2004
JP	A-2003-114387	4/2003	JP	A-2004-224421	8/2004
JP	A-2003-124095	4/2003	JP	A-2004-228497	8/2004
JP	A-2003-130132	5/2003	JP	A-2004-241666	8/2004
JP	A-2003-149363	5/2003	JP	A-2004-247527	9/2004
JP	A-2003-151880	5/2003	JP	A-2004-258670	9/2004
JP	A-2003-161882	6/2003	JP	A-2004-258670	9/2004
JP	A-2003-163158	6/2003	JP	A-2004-259828	9/2004
JP	A-2003-166856	6/2003	JP	A-2004-259966	9/2004
JP	A-2003-173957	6/2003	JP	A-2004-259985	9/2004
JP	A-2003-188087	7/2003	JP	A-2004-260043	9/2004
JP	A-2003-224961	8/2003	JP	A-2004-260081	9/2004
JP	A-2003-229347	8/2003	JP	A-2004-294202	10/2004
JP	A-2003-233001	8/2003	JP	A-2004-301825	10/2004
JP	A-2003-234285	8/2003	JP	A-2004-302043	10/2004
JP	A-2003-238577	8/2003	JP	A-2004-303808	10/2004
JP	A-2003-240906	8/2003	JP	A-2004-304135	10/2004
JP	A-2003-249443	9/2003	JP	A-2004-307264	11/2004
JP	A-2003-258071	9/2003	JP	A-2004-307265	11/2004
JP	A-2003-262501	9/2003	JP	A-2004-307266	11/2004
JP	A-2003-263119	9/2003	JP	A-2004-307267	11/2004
JP	A-2003-272837	9/2003	JP	A-2004-319724	11/2004
JP	A-2003-273338	9/2003	JP	A-2004-320017	11/2004
JP	A-2003-282423	10/2003	JP	A-2004-327660	11/2004
JP	A-2003-297727	10/2003	JP	A-2004-335808	11/2004
JP	A-2003-532281	10/2003	JP	A-2004-335864	11/2004
JP	A-2003-532282	10/2003	JP	A-2004-336922	11/2004
JP	A-2003-311923	11/2003	JP	A-2004-342987	12/2004
JP	A-2004-7417	1/2004	JP	A-2004-349645	12/2004
JP	A-2004-14642	1/2004	JP	A-2004-356410	12/2004
JP	A-2004-14876	1/2004	JP	A-2005-5295	1/2005
JP	A-2004-15187	1/2004	JP	A-2005-5395	1/2005
JP	A-2004-22708	1/2004	JP	A-2005-5521	1/2005
JP	A-2004-38247	2/2004	JP	A-2005-005521	1/2005
JP	A-2004-39952	2/2004	JP	A-2005-11990	1/2005
JP	A-2004-40039	2/2004	JP	A-2005-012190	1/2005
JP	A-2004-45063	2/2004	JP	A-2005-12228	1/2005
JP	A-2004-051717	2/2004	JP	A-2005-19628	1/2005
JP	A-2004-63847	2/2004	JP	A-2005-19864	1/2005
JP	A-2004-71851	3/2004	JP	A-2005-26634	1/2005
JP	A-2004-078136	3/2004	JP	A-2005-51147	2/2005
JP	A-2004-85612	3/2004	JP	A-2005-55811	3/2005
JP	A-2004-87987	3/2004	JP	A-2005-64210	3/2005
JP	A-2004-087987	3/2004	JP	A-2005-64391	3/2005
JP	A-2004-95653	3/2004	JP	A-2005-79222	3/2005
JP	U-3102327	3/2004	JP	A-2005-79584	3/2005
JP	A-2004-98012	4/2004	JP	A-2005-79587	3/2005
JP	A-2004-101362	4/2004	JP	A-2005-86148	3/2005
JP	A-2004-103674	4/2004	JP	A-2005-91023	4/2005
JP	A-2004-104654	4/2004	JP	A-2005-93324	4/2005
JP	A-2004-111569	4/2004	JP	A-2005-093522	4/2005
JP	A-2004-119497	4/2004	JP	A-2005-93948	4/2005
JP	A-2004-119717	4/2004	JP	A-2005-97057	4/2005
JP	A-2004-128307	4/2004	JP	A-2005-108925	4/2005
JP	A-2004-134682	4/2004	JP	A-2005-108934	4/2005
JP	A-2004-140145	5/2004	JP	A-2005-114882	4/2005
JP	A-2004-145269	5/2004	JP	A-2005-116570	4/2005
JP	A-2004-146702	5/2004	JP	A-2005-116571	4/2005
			JP	A-2005-116831	4/2005
			JP	A-2005-116831	4/2005
			JP	A-2005-123586	5/2005
			JP	A-2005-127460	5/2005
			JP	A-2005-136404	5/2005

(56)

## References Cited

FOREIGN PATENT DOCUMENTS					
JP	A1-2005-050718	6/2005	JP	A-2007-103153	4/2007
JP	A-2005-140999	6/2005	JP	A-2007-113939	5/2007
JP	A-2005-150759	6/2005	JP	A-2007-119851	5/2007
JP	A-2005-156592	6/2005	JP	A-2007-120333	5/2007
JP	A-2005-166871	6/2005	JP	A-2007-120334	5/2007
JP	A-2005-167254	6/2005	JP	A-2007-142313	6/2007
JP	A-2005-175176	6/2005	JP	A-2007-144864	6/2007
JP	A-2005-175177	6/2005	JP	A-2007-515768	6/2007
JP	A-2005-191344	7/2005	JP	A-2007-170938	7/2007
JP	A-2005-203483	7/2005	JP	A-2007-187649	7/2007
JP	A-2005-209705	8/2005	JP	A-2007-207821	8/2007
JP	A-2005-209706	8/2005	JP	A-2007-207821	8/2007
JP	A-2005-524112	8/2005	JP	2007-527549	9/2007
JP	A-2005-233979	9/2005	JP	A-2007-227637	9/2007
JP	A-2005-234359	9/2005	JP	A-2007-235041	9/2007
JP	A-2005-236088	9/2005	JP	A-2007-274881	10/2007
JP	A-2005-243770	9/2005	JP	A-2007-280623	10/2007
JP	A-2005-243904	9/2005	JP	A-2007-295702	11/2007
JP	A-2005-251549	9/2005	JP	A-2008-3740	1/2008
JP	A-2005-257740	9/2005	JP	A-2008-58580	3/2008
JP	A-2005-259789	9/2005	JP	A-2008-64924	3/2008
JP	A-2005-259830	9/2005	JP	A-2008-103737	5/2008
JP	A-2005-268700	9/2005	JP	A-2008-180492	8/2008
JP	A-2005-268741	9/2005	JP	A-2009-17540	1/2009
JP	A-2005-268742	9/2005	JP	A-2009-60339	3/2009
JP	A-2005-276932	10/2005	JP	A-2010-514716	5/2010
JP	A-2005-302826	10/2005	JP	A-2010-226117	10/2010
JP	A-2005-303167	10/2005	JP	B2-4582096	11/2010
JP	A-2005-311020	11/2005	JP	B2-4747844	8/2011
JP	A-2005-315918	11/2005	JP	A-2011-233911	11/2011
JP	A-2005-340605	12/2005	JP	B2-4976015	7/2012
JP	A-2005-366813	12/2005	JP	B2-4976094	7/2012
JP	A-2006-1821	1/2006	KR	10-0474578 B1	1/1997
JP	A-2006-5197	1/2006	KR	10-2011-0036050	4/1997
JP	A-2006-17895	1/2006	KR	A-10-1997-0016641	4/1997
JP	A-2006-019702	1/2006	KR	2000-0048227	7/2000
JP	A-2006-19702	1/2006	KR	2000-0076783 A	12/2000
JP	A-2006-24706	1/2006	KR	2001-0051438 A	6/2001
JP	A-2006-24819	1/2006	KR	2001-53240 A	6/2001
JP	A-2006-32750	2/2006	KR	2002-0042462 A	6/2002
JP	A-2006-41302	2/2006	KR	10 2003 0036105 A	5/2003
JP	A-2006-41302	2/2006	KR	10-2006-0132598	12/2006
JP	A-2006-54364	2/2006	KR	10-0839686 B1	6/2008
JP	A-2006-73584	3/2006	KR	10-0869390 B1	11/2008
JP	A-2006-73951	3/2006	KR	10-2010-0061551	6/2010
JP	A-2006-80281	3/2006	KR	10-1020378 B1	3/2011
JP	A-2006-86141	3/2006	KR	10-1020455 B1	3/2011
JP	A-2006-86442	3/2006	TW	516097	1/2003
JP	A-2006-100363	4/2006	TW	518662	1/2003
JP	A-2006-100686	4/2006	TW	094100817 A	8/2005
JP	A-2006-113437	4/2006	WO	WO 97/11411 A1	3/1997
JP	A-2006-513442	4/2006	WO	WO 98/15952 A1	4/1998
JP	A-2006-120985	5/2006	WO	WO 98/24115 A1	6/1998
JP	A-2006-128192	5/2006	WO	WO 98/59364 A1	12/1998
JP	A-2006-135165	5/2006	WO	WO 99/23692 A1	5/1999
JP	A-2006-140366	6/2006	WO	WO 99/27568 A1	6/1999
JP	A-2006-170811	6/2006	WO	WO 99/31716 A1	6/1999
JP	A-2006-170899	6/2006	WO	WO 99/34255 A1	7/1999
JP	A-2006-177865	7/2006	WO	WO 99/49366 A1	9/1999
JP	A-2006-184414	7/2006	WO	WO 99/49504 A1	9/1999
JP	A-2006-194665	7/2006	WO	WO 99/50712 A1	10/1999
JP	A-2006-250587	9/2006	WO	WO 99/66370 A1	12/1999
JP	A-2006-253572	9/2006	WO	WO 00/02092	1/2000
JP	A-2006-269762	10/2006	WO	WO 00/11706	3/2000
JP	A-2006-278820	10/2006	WO	WO 00/67303 A1	11/2000
JP	A-2006-289684	10/2006	WO	WO 01/03170 A1	1/2001
JP	A-2006-524349	10/2006	WO	WO 01/10137 A1	2/2001
JP	A-2006-332355	12/2006	WO	WO 01/20733 A1	3/2001
JP	A-2006-349946	12/2006	WO	WO 01/22480 A1	3/2001
JP	A-2006-351586	12/2006	WO	WO 01/23935	4/2001
JP	A-2007-5830	1/2007	WO	WO 01/27978 A1	4/2001
JP	A-2007-43980	2/2007	WO	WO 01/35451 A1	5/2001
JP	A-2007-48819	2/2007	WO	WO 01/59502 A1	8/2001
JP	A-2007-51300	3/2007	WO	WO 01/65296 A1	9/2001
JP	A-2007-87306	4/2007	WO	WO 01/81977 A2	11/2001
JP	A-2007-93546	4/2007	WO	WO 02/16993 A1	2/2002
			WO	WO 02/063664 A1	8/2002
			WO	WO 02/069049 A2	9/2002
			WO	WO 02/080185 A1	10/2002
			WO	WO 02/084720 A2	10/2002



(56)

## References Cited

## FOREIGN PATENT DOCUMENTS

WO WO 02/084850 A1 10/2002  
 WO WO 02/093209 A2 11/2002  
 WO WO 02/101804 A1 12/2002  
 WO WO 03/003429 1/2003  
 WO WO 03/023832 A1 3/2003  
 WO WO 03/063212 A1 7/2003  
 WO WO 03/077036 A1 9/2003  
 WO WO 03/085708 A1 10/2003  
 WO WO 2004/051717 A1 6/2004  
 WO WO 2004/053596 A2 6/2004  
 WO WO 2004/053950 A1 6/2004  
 WO WO 2004/053951 A1 6/2004  
 WO WO 2004/053952 A1 6/2004  
 WO WO 2004/053953 A1 6/2004  
 WO WO 2004/053954 A1 6/2004  
 WO WO 2004/053955 A1 6/2004  
 WO WO 2004/053956 A1 6/2004  
 WO WO 2004/053957 A1 6/2004  
 WO WO 2004/053958 A1 6/2004  
 WO WO 2004/053959 A1 6/2004  
 WO WO 2004/071070 A2 8/2004  
 WO WO 2004/086468 A1 10/2004  
 WO WO 2004/086470 A1 10/2004  
 WO WO 2004/090956 A1 10/2004  
 WO WO 2004/091079 A1 10/2004  
 WO WO 2004/094940 A1 11/2004  
 WO WO 2004/104654 A1 12/2004  
 WO WO 2004/105106 A1 12/2004  
 WO WO 2004/105107 A1 12/2004  
 WO WO 2004/107048 A2 12/2004  
 WO WO 2004/107417 A1 12/2004  
 WO WO 2004/109780 A1 12/2004  
 WO WO 2004/114380 A1 12/2004  
 WO WO 2005/006415 A1 1/2005  
 WO WO 2005/006418 A1 1/2005  
 WO WO 2005/008754 A1 1/2005  
 WO WO 2005/022615 A1 3/2005  
 WO WO 2005/026843 A2 3/2005  
 WO WO 2005/027207 A1 3/2005  
 WO WO 2005/029559 A1 3/2005  
 WO WO 2005/031467 A2 4/2005  
 WO WO 2005/036619 A1 4/2005  
 WO WO 2005/036620 A1 4/2005  
 WO WO 2005/036622 A1 4/2005  
 WO WO 2005/036623 A1 4/2005  
 WO WO 2005/041276 A1 5/2005  
 WO WO 2005/041277 A1 5/2005  
 WO WO 2005/048325 A1 5/2005  
 WO WO 2005/048326 A1 5/2005  
 WO WO 2005/050718 A1 6/2005  
 WO WO 2005/057636 A1 6/2005  
 WO WO 2005/067013 A1 7/2005  
 WO WO 2005/069081 A2 7/2005  
 WO WO 2005/071671 A2 8/2005  
 WO WO 2005/071717 A1 8/2005  
 WO WO 2005/076045 A1 8/2005  
 WO WO 2005/076321 A1 8/2005  
 WO WO 2005/076323 A1 8/2005  
 WO WO 2005/081291 A1 9/2005  
 WO WO 2005/081292 A1 9/2005  
 WO WO 2005/104195 A1 11/2005  
 WO WO 2006/006730 A1 1/2006  
 WO WO 2006/016551 A1 2/2006  
 WO WO 2006/019124 A1 2/2006  
 WO WO 2006/025341 A1 3/2006  
 WO WO 2006/028188 A1 3/2006  
 WO WO 2006/030727 A1 3/2006  
 WO WO 2006/030910 A1 3/2006  
 WO WO 2006-035775 A1 4/2006  
 WO WO 2006/049134 A1 5/2006  
 WO WO 2006/051909 A1 5/2006  
 WO WO 2006/064851 A1 6/2006  
 WO WO 2006/068233 A1 6/2006  
 WO WO 2006/077958 A1 7/2006  
 WO WO 2006/080285 A1 8/2006

WO WO 2006/085524 A1 8/2006  
 WO WO 2006/100889 A1 9/2006  
 WO WO 2006/118108 A1 11/2006  
 WO WO 2007/003563 A1 1/2007  
 WO WO 2007/018127 A1 2/2007  
 WO WO 2007/055120 A1 5/2007  
 WO WO 2007/055237 A1 5/2007  
 WO WO 2007/055373 A1 5/2007  
 WO WO 2007/066692 A1 6/2007  
 WO WO 2007/066758 A1 6/2007  
 WO WO 2007/097198 A1 8/2007  
 WO WO 2007/132862 A1 11/2007  
 WO WO 2007/141997 A1 12/2007  
 WO WO 2008/041575 A1 4/2008  
 WO WO 2008/059748 A1 5/2008  
 WO WO 2008/061681 A2 5/2008  
 WO WO 2008/065977 A1 6/2008  
 WO WO 2008/074673 A2 6/2008  
 WO WO 2008/075613 A1 6/2008  
 WO WO 2008/075742 A1 6/2008  
 WO WO 2008/078688 A1 7/2008  
 WO WO 2008/090975 A1 7/2008  
 WO WO 2008/139848 A1 11/2008  
 WO WO 2009/153925 A1 12/2009  
 WO WO 2009/157154 A1 12/2009  
 WO WO 2010/001537 A1 1/2010

## OTHER PUBLICATIONS

Translation of JP-A-5-326370, filed Dec. 10, 1993.  
 Translation of JP-A-2002-334836, filed Nov. 22, 2002.  
 Jan. 25, 2010 European Search Report for European Patent Application No. 09015058.2-1226.  
 English Translation of Korean Office Action for Patent Application No. 10-2008-7019082, issued May 31, 2010.  
 English Translation of Korean Office Action for Patent Application No. 10-2008-7019081, issued May 31, 2010.  
 Mar. 26, 2010 Office Action issued in related U.S. Appl. No. 11/902,282.  
 Final Rejection of Japanese Patent Application No. 2005-515570, issued Aug. 3, 2010 with English-language Translation.  
 Final Rejection of Japanese Patent Application No. 2006-262580, issued Aug. 3, 2010 with English-language Translation.  
 Aug. 23, 2010 Office Action issued in Chinese Patent Application No. 200810211496.1 (with translation).  
 Sep. 20, 2010 Notice of Allowance issued in U.S. Appl. No. 11/410,952.  
 Sep. 29, 2010 European Search Report issued in European Patent Application No. 10174843.2.  
 Oct. 4, 2010 Supplementary European Search Report issued in European Patent Application No. 05703646.9.  
 Jul. 20, 2010 Office Action issued in Korean Patent Application No. 10-2010-7008438 (with translation).  
 Jul. 20, 2010 Office Action issued in Korean Patent Application No. 10-2010-7008441 (with translation).  
 Jul. 20, 2010 Office Action issued in Korean Patent Application No. 10-2010-7008444 (with translation).  
 Jul. 20, 2010 Notice of Allowance issued in U.S. Appl. No. 12/289,515.  
 Aug. 3, 2010 Notice of Allowance issued in Japanese Patent Application No. 2006-553907.  
 Oct. 8, 2010 Office Action issued in Chinese Patent Application No. 200810126659.6 (with translation).  
 Oct. 26, 2010 Office Action issued in Japanese Patent Application No. 2005-517637 (with translation).  
 Oct. 26, 2010 Office Action issued in Japanese Patent Application No. 2006-262588 (with translation).  
 Oct. 26, 2010 Office Action issued in Japanese Patent Application No. 2006-262590 (with translation).  
 Dec. 7, 2010 Search Report issued in European Patent Application No. 10012876.8.  
 Nov. 12, 2010 Office Action issued in Chinese Patent Application No. 200710110948.2 with English translation.  
 Nov. 3, 2010 Office Action issued in European Patent Application No. 09015058.2.



(56)

**References Cited**

## OTHER PUBLICATIONS

- Oct. 18, 2010 Office Action issued in U.S. Appl. No. 12/382,277.  
 Jan. 6, 2011 Office Action issued in U.S. Appl. No. 11/902,282.  
 Nov. 30, 2010 Korean Notice of Allowance issued in Korean Application No. 10-2008-7019081.  
 Nov. 30, 2010 Notice of Allowance issued in Korean Application No. 10-2008-7019082.  
 Jan. 14, 2011 Office Action issued in U.S. Appl. No. 12/320,480.  
 Jan. 14, 2011 Office Action issued in U.S. Appl. No. 12/320,468.  
 Feb. 1, 2011 Notice of Reasons for Rejection issued in Japanese Application No. P2006-262588 with English translation.  
 Feb. 1, 2011 Notice of Reasons for Rejection issued in Japanese Application No. P2006-262590 with English translation.  
 Feb. 1, 2011 Notice of Reasons for Rejection issued in Japanese Application No. P2005-517637 with English translation.  
 Jan. 25, 2011 Office Action issued in Korean Patent Application No. 2009-7010159 (with English Translation).  
 Feb. 1, 2011 Office Action issued in Chinese Patent Application No. 200810126659.6 (with English Translation).  
 Feb. 8, 2011 Office Action issued in U.S. Appl. No. 12/320,465.  
 Jan. 24, 2011 Office Action issued in Korean Patent Application No. 2009-7010158 (with English Translation).  
 Jan. 24, 2011 Office Action issued in Korean Patent Application No. 2005-7018973 (with English Translation).  
 Feb. 26, 2009 Office Action issued in U.S. Appl. No. 11/347,421.  
 Oct. 29, 2009 Office Action issued in U.S. Appl. No. 12/289,515.  
 Nov. 25, 2009 Office Action issued in U.S. Appl. No. 11/410,952.  
 Jan. 7, 2010 Office Action issued in U.S. Appl. No. 12/289,518.  
 Feb. 23, 2010 Office Action issued in Japanese Patent Application No. P2006-262589 (with English Translations).  
 Feb. 23, 2010 Office Action issued in Japanese Patent Application No. P2005-515570 (with English Translations).  
 Nov. 12, 2010 Office Action issued in Chinese Patent Application No. 200910126047.1 (with English Translation).  
 Jan. 26, 2011 Office Action issued in Chinese Patent Application No. 200910173715.6 (with English Translation).  
 Jan. 14, 2011 Office Action issued in U.S. Appl. No. 12/461,852.  
 Feb. 15, 2011 Office Action issued in European Patent Application No. 05703646.9.  
 Jan. 8, 2009 Office Action issued in U.S. Appl. No. 11/410,952.  
 Jun. 16, 2010 Office Action issued in U.S. Appl. No. 11/410,952.  
 Mar. 29, 2011 Office Action issued in Japanese Patent Application No. P2007-251263 (with English Translation).  
 U.S. Appl. No. 12/835,860, filed Jul. 14, 2010 by Kanayamaya et al. Tsuruta, T. "Applied Optics II," Baifukan Co., Ltd. pp. 166-167, Jul. 1990 (with translation).  
 Nov. 6, 2009 Office Action issued in Chinese Application No. 2008102114957 (with translation).  
 Sep. 11, 2009 Office Action issued in Chinese Application No. 2008102114976 (with translation).  
 "High NA Lithographic Imagery at Brewster's Angle" Brunner, Timothy A., et al. SPIE (U.S.A.), vol. 4691, pp. 1-24, 2002.  
 Mar. 21, 2008 Office Action issued in Chinese Application No. 2004800341246 (with translation).  
 Apr. 21, 2010 Office Action issued in U.S. Appl. No. 12/289,518.  
 Apr. 24, 2009 Office Action issued in Chinese Application No. 2006800006868 (with translation).  
 Jan. 28, 2010 Search Report issued in European Application No. 06711853.9.  
 Apr. 22, 2010 Office Action issued in Japanese Application No. 2006-553907 (with translation).  
 Jul. 3, 2008 Office Action issued in U.S. Appl. No. 11/319,057.  
 Feb. 26, 2009 Office Action issued in U.S. Appl. No. 11/319,057.  
 Oct. 4, 2010 International Search Report issued in International Application No. PCT/JP2010/061300.  
 Oct. 4, 2010 Written Opinion of the International Searching Authority issued in International Application No. PCT/JP2010/061300.  
 Jan. 11, 2011 Office Action issued in U.S. Appl. No. 12/461,801.  
 Aug. 3, 2010 Office Action issued in Japanese Application No. 2006-262589 (with translation).  
 Jul. 12, 2010 Office Action issued in U.S. Appl. No. 12/461,801.  
 Sep. 15, 2008 Office Action issued in U.S. Appl. No. 11/644,966.  
 Jun. 25, 2009 Office Action issued in U.S. Appl. No. 11/644,966.  
 Apr. 15, 2010 Office Action issued in U.S. Appl. No. 10/587,254.  
 Sep. 27, 2010 Office Action issued in U.S. Appl. No. 10/587,254.  
 Levinson, Harry J., "Principles of Lithography," Bellingham, WA: SPIE Press, 2001, pp. 205-206.  
 May 14, 2008 International Preliminary Report on Patentability issued in International Application No. PCT/JP2006/321607.  
 May 14, 2008 Written Opinion issued in International Application No. PCT/JP2006/321607 (with translation).  
 Feb. 25, 2010 Extended Search Report issued in European Application No. 06822564.8.  
 Feb. 24, 2011 Office Action issued in Chinese Patent Application No. 200910173717.5 (with English Translation).  
 Feb. 28, 2011 Office Action issued in Korean Patent Application No. 10-2010-7008441 (with English Translation).  
 Mar. 8, 2011 Office Action issued in Chinese Patent Application No. 200910173716.0 (with English Translation).  
 Mar. 29, 2011 Notice of Allowance issued in Japanese Patent Application No. P2005-505207 (with English Translation).  
 Apr. 5, 2011 Office Action issued in Japanese Patent Application No. P2009-149426 (with English Translation).  
 Apr. 26, 2011 Office Action issued in U.S. Appl. No. 11/902,282.  
 Feb. 24, 2011 Office Action issued in Chinese Patent Application No. 201010128876.6 (with English Translation).  
 Mar. 23, 2011 Office Action issued in Chinese Patent Application No. 200910173718.X (with English Translation).  
 Apr. 15, 2011 Office Action issued in European Patent Application No. 04 817 303.3.  
 Jun. 23, 2011 Office Action issued in Chinese Patent Application No. 200910173714.1 (with English Translation).  
 Jul. 8, 2011 Office Action issued in U.S. Appl. No. 12/318,216.  
 Jul. 20, 2011 Office Action issued in Taiwanese Patent Application No. 094100817 (with English Translation).  
 Apr. 25, 2011 Office Action issued in Korean Patent Application No. 10-2011-7001502 (with English Translation).  
 Apr. 26, 2011 Office Action issued in Chinese Patent Application No. 200710110951.4 (with English Translation).  
 Jun. 10, 2011 Office Action issued in U.S. Appl. No. 12/289,515.  
 Apr. 20, 2011 Office Action issued in Chinese Patent Application No. 200710110949.7 (with English Translation).  
 Apr. 26, 2011 Office Action issued in Chinese Patent Application No. 200710110950.X (with English Translation).  
 Apr. 28, 2011 Office Action issued in Korean Patent Application No. 10-2010-7001898 (with English Translation).  
 Apr. 28, 2011 Office Action issued in Korean Patent Application No. 10-2006-7012265 (with English Translation).  
 Apr. 25, 2011 Office Action issued in Korean Patent Application No. 10-2010-7008438 (with English Translation).  
 Apr. 28, 2011 Office Action issued in Korean Patent Application No. 10-2009-7023904 (with English Translation).  
 Apr. 28, 2011 Office Action issued in Korean Patent Application No. 10-2010-7001907 (with English Translation).  
 May 3, 2011 International Search Report issued in PCT/JP2011/053595.  
 May 11, 2011 Office Action issued in European Patent Application No. 04724369.6.  
 May 18, 2011 International Search Report issued in PCT/JP2011/053588.  
 Jun. 14, 2011 Office Action issued in Korean Patent Application No. 2011-7006842 (with English Translation).  
 Jun. 15, 2011 Notice of Allowance issued in U.S. Appl. No. 12/289,518.  
 Mar. 31, 2011 Notice of Allowance issued in U.S. Appl. No. 11/410,952.  
 Apr. 6, 2011 Office Action issued in Taiwanese Patent Application No. 093131323 (with English Translation).  
 May 24, 2011 Office Action issued in U.S. Appl. No. 12/382,277.  
 Apr. 8, 2011 Office Action issued in Chinese Patent Application No. 200810211496.1 (with English Translation).



(56)

**References Cited**

## OTHER PUBLICATIONS

Third Party Submission Information Statement issued in Korean Patent Application No. 10-869390; dated Feb. 8, 2011 (with translation).

Feb. 7, 2011 Patent Register of Korean Patent Application No. 869390.

Carl Zeiss SMT GmbH—Microsoft Internet Explorer, “Semiconductor Technologies”, <http://www.zeiss.com>.

Wave Plate, Wikipedia, the free encyclopedia, [http://en.wikipedia.org/wiki/Wave\\_plate](http://en.wikipedia.org/wiki/Wave_plate), Feb. 7, 2011, pp. 16-1-16-16.

Marc D. Himel et al., “Design and fabrication of customized illumination patterns for low k1 lithography : a diffractive approach”, Proceedings of SPIE, vol. 4346, pp. 11-1-11-7.

Feb. 8, 2011 Third Party Submission Information Statement in Korean Patent Application No. 10-0839686 (with English translation).

Jun. 12, 2008 Patent Register of Korean Patent Application No. 10-0839686.

Mar. 9, 2011 Third Party Submission Information Statement in Korean Patent Application No. 10-1020378 (with English translation).

Feb. 28, 2011 Patent Register of Korean Patent Application No. 10-1020378.

Mar. 9, 2011 Third Party Submission Information Statement in Korean Patent Application No. 10-1020455 (with English translation).

Feb. 28, 2011 Patent Register of Korean Patent Application No. 10-1020455.

Oct. 18, 2011 Office Action in Japanese Patent Application No. 2006-262589 (with English translation).

Oct. 18, 2011 Office Action in Japanese Patent Application No. 2005-515570 (with English translation).

Oct. 10, 2011 Office Action in Chinese Patent Application No. 200710110952.9 (with English translation).

Aug. 11, 2011 Office Action in Korean Patent Application No. 10-2010-7000897 (with English translation).

Aug. 11, 2011 Office Action in Korean Patent Application No. 10-2010-7000893 (with English translation).

Jul. 26, 2011 Office Action in Korean Patent Application No. 10-2006-7018069 (with English translation).

Jul. 5, 2011 Office Action in Chinese Patent Application No. 201010128136.2 (with English translation).

Sep. 13, 2011 Office Action in European Patent Application No. 04 799 453.8.

Aug. 4, 2011 Office Action in Taiwanese Patent Application No. 093131767 (with English translation).

Sep. 6, 2011 Notice of Allowance in U.S. Appl. No. 11/644,966.

Notice of Allowance dated Jul. 13, 2011 from U.S. Appl. No. 11/410,952.

Sep. 30, 2011 Office Action in Korean Application No. 10-2005-7018973 (with English translation).

Dec. 16, 2011 Office Action issued in U.S. Appl. No. 13/067,958.

Dec. 15, 2011 Office Action issued in U.S. Appl. No. 12/382,277.

Nov. 17, 2011 Office Action issued in Taiwanese Patent Application No. 096119463 (with English translation).

Nov. 22, 2011 Office Action issued in Chinese Patent Application No. 200910173718.X (with English translation).

*Korean Language Dictionary*, 5<sup>th</sup> Edition, Jan. 10, 2002, MinJungseorim, Seoul, Korea (with English translation).

“Polarizer,” Wikipedia, <http://en.wikipedia.org/wiki/Polarizer>, Oct. 18, 2011 (11 pp.).

Nov. 29, 2011 Written Rebuttal against the Written Answer filed by the Respondent in Korean Patent Application No. 10-2006-7008368 (with English translation).

Nov. 29, 2011 Written Rebuttal against the Written Answer filed by the Respondent in Korean Patent Application No. 10-2007-7022489 (with English translation).

Nov. 29, 2011 Written Rebuttal against the Written Answer filed by the Respondent in Korean Patent Application No. 10-2008-7019081 (with English translation).

Nov. 29, 2011 Written Rebuttal against the Written Answer filed by the Respondent in Korean Patent Application No. 10-2008-7019082 (with English translation).

Nov. 30, 2011 Office Action issued in U.S. Appl. No. 11/902,282.

Dec. 12, 2011 Office Action issued in European Patent Application No. 10 174 843.2.

Nov. 25, 2011 Office Action issued in European Patent Application No. 06 711 853.9.

Feb. 10, 2012 Office Action issued in European Patent Application No. 10 012 876.8.

Jan. 18, 2012 Office Action issued in European Patent Application No. 10 174 843.2.

Feb. 13, 2012 Office Action issued in Taiwanese Patent Application No. 094100817 (with English translation).

Mar. 6, 2012 Notice of Allowance issued in U.S. Appl. No. 12/289,515.

Nov. 15, 2011 Office Action issued in European Patent Application No. 09 167 707.0.

Nov. 10, 2011 Office Action issued in European Patent Application No. 07 017 146.7.

Nov. 15, 2011 Office Action issued in Korean Patent Application No. 10-2009-7010159 (with English translation).

Nov. 15, 2011 Office Action issued in Korean Patent Application No. 10-2009-7010158 (with English translation).

Jan. 19, 2012 Office Action issued in U.S. Appl. No. 12/458,635.

Dec. 5, 2012 Office Action issued in Taiwan Patent Application No. 096138500 (with translation).

Nov. 9, 2012 Written Opinion against the Written Answer issued in Korean Patent Application No. 10-839686, Appeal No. 2011Dang301 (with translation).

Nov. 6, 2012 Written Opinion against the Written Answer issued in Korean Patent Application No. 10-869390, Appeal No. 2011Dang302 (with translation).

Nov. 26, 2012 Written Opinion against the Written Answer issued in Korean Patent Application No. 10-1020455, Appeal No. 2011Dang510 (with translation).

Nov. 26, 2012 Written Opinion against the Written Answer issued in Korean Patent Application No. 10-1020378, Appeal No. 2011Dang511 (with translation).

Dec. 12, 2012 Notice of Allowance issued in U.S. Appl. No. 12/289,515.

Dec. 18, 2012 Office Action issued in Japanese Patent Application No. 2009-149426 (with Translation).

Dec. 26, 2012 Office Action issued in Taiwanese Patent Application No. 097151805 (with Translation).

Dec. 26, 2012 Office Action issued in Taiwanese Patent Application No. 097151814 (with Translation).

Dec. 27, 2012 Office Action issued in Taiwanese Patent Application No. 095100035 (with Translation).

Dec. 27, 2012 Office Action issued in Taiwanese Patent Application No. 097151801 (with Translation).

Jan. 2, 2013 Office Action issued in Korean Patent Application No. 10-2007-7005320 (with translation).

Jan. 15, 2013 Notice of Allowance issued in U.S. Appl. No. 13/067,958.

Jan. 17, 2012 Japanese Office Action issued in Japanese Patent Application No. 2006-262589 (with translation).

Jan. 17, 2012 Japanese Office Action issued in Japanese Patent Application No. 2005-515570 (with translation).

Apr. 5, 2012 Notice of Allowance issued in U.S. Appl. No. 11/644,966.

Apr. 26, 2012 Chinese Office Action issued in Chinese Patent Application No. 200910126047.1 (with translation).

Apr. 30, 2012 Korean Office Action issued in Korean Patent Application No. 10-2006-7012265 (with translation).

Apr. 30, 2012 Korean Office Action issued in Korean Patent Application No. 10-2010-7001898 (with translation).

Apr. 30, 2012 Korean Office Action issued in Korean Patent Application No. 10-2010-7001907 (with translation).

May 4, 2012 Taiwanese Office Action issued in Taiwanese Patent Application No. 096138500 (with translation).

May 9, 2012 Chinese Office Action issued in Chinese Patent Application No. 200810211496.1 (with translation).



(56)

**References Cited**

## OTHER PUBLICATIONS

- May 21, 2012 Chinese Office Action issued in Chinese Patent Application No. 201010128876.6 (with translation).
- Jun. 1, 2012 European Office Action issued in European Patent Application No. 09 015 058.2.
- Jun. 8, 2012 Korean Office Action issued in Korean Patent Application No. 10-2007-7005320 (with translation).
- Jun. 11, 2012 Korean Office Action issued in Korean Patent Application No. 10-2012-7003793 (with translation).
- Jun. 28, 2012 Korean Office Action issued in Korean Patent Application No. 10-2012-7008342 (with translation).
- Mar. 8, 2012 Taiwan Office Action issued in Taiwanese Patent Application No. 093131767 (with translation).
- Nov. 28, 2011 Notice of Allowance issued in U.S. Appl. No. 12/801,043.
- Jan. 25, 2012 U.S. Office Action issued in U.S. Appl. No. 12/801,043.
- Feb. 22, 2012 Chinese Office Action issued in Chinese Patent Application No. 200910173715.6 (with translation).
- Mar. 30, 2012 U.S. Office Action issued in U.S. Appl. No. 12/318,216.
- Jul. 19, 2012 U.S. Office Action issued in U.S. Appl. No. 11/902,282.
- Jun. 4, 2012 Office Action issued in Chinese Patent Application No. 200710110950.X (with translation).
- Jun. 27, 2012 Office Action issued in Korean Patent Application No. 10-2009-7010158 (with translation).
- Jun. 29, 2012 Office Action issued in Chinese Patent Application No. 200910173714.1 (with translation).
- Jul. 17, 2012 Office Action issued in U.S. Appl. No. 12/382,277.
- Jul. 19, 2012 Office Action issued in U.S. Appl. No. 11/902,282.
- Aug. 3, 2012 Office Action issued in U.S. Appl. No. 13/137,342.
- Aug. 6, 2012 Office Action issued in U.S. Appl. No. 13/137,004.
- Aug. 7, 2012 Office Action issued in U.S. Appl. No. 13/137,003.
- Aug. 10, 2012 Office Action issued in U.S. Appl. No. 13/137,002.
- Oct. 30, 2012 Office Action issued in Korean Patent Application No. 10-2012-7023534 (with translation).
- Nov. 21, 2012 Office Action issued in European Patent Application No. 05 703 646.9.
- Aug. 20, 2012 Response to Written Answer submitted in Korean Patent Application No. 10-1020455 (with translation).
- Aug. 20, 2012 Response to Written Answer submitted in Korean Patent Application No. 10-1020378 (with translation).
- Oct. 12, 2012 Office Action issued in U.S. Appl. No. 12/458,635.
- Aug. 20, 2012 Office Action issued in Taiwanese Patent Application No. 097117881 (with translation).
- Aug. 20, 2012 Response to Written Answer submitted in Korean Patent Application No. 10-0869390 (with translation).
- Aug. 20, 2012 Response to Written Answer submitted in Korean Patent Application No. 10-0839686 (with translation).
- Oct. 18, 2007 European Search Report issued in European Patent Application No. 07017146.7.
- Apr. 2, 2007 European Search Report issued in European Patent Application No. 04724369.6.
- Oct. 1, 2008 Supplemental European Search Report issued in European Patent Application No. 04817303.3.
- Apr. 24, 2008 Supplemental European Search Report issued in European Patent Application No. 08002882.2.
- Jun. 25, 2010 European Search Report issued in European Patent Application No. 09167707.0.
- Oct. 13, 2009 European Search Report issued in European Patent Application No. 09167707.0.
- Feb. 23, 2009 Office Action issued in European Patent Application No. 08002882.2.
- Mar. 31, 2009 Office Action issued in European Patent Application No. 04 799 453.8.
- May 26, 2010 Office Action issued in European Patent Application No. 07 017 146.7.
- May 12, 2009 Office Action issued in European Patent Application No. 04 724 369.6.
- Jul. 12, 2010 Office Action issued in European Patent Application No. 06 711 853.9.
- Oct. 8, 2010 Office Action issued in European Patent Application No. 06822564.8.
- Oct. 7, 2009 Office Action issued in European Patent Application No. 04 799 453.8.
- Sep. 25, 2007 Office Action issued in European Patent Application No. 04 799 453.8.
- Jan. 18, 2010 Office Action issued in Korean Patent Application No. 10-2008-7019081 (with translation).
- Nov. 15, 2007 Office Action issued in Korean Patent Application No. 10-2007-7022489 (with translation).
- Apr. 3, 2008 Office Action issued in Korean Patent Application No. 10-2006-7008368 (with translation).
- Jan. 4, 2008 Office Action issued in Korean Patent Application No. 10-2006-7008368 (with translation).
- Feb. 2, 2007 Office Action issued in Korean Patent Application No. 10-2006-7008368 (with translation).
- Jan. 18, 2010 Office Action issued in Korean Patent Application No. 10-2008-7019082 (with translation).
- Dec. 3, 2010 Office Action issued in Korean Patent Application No. 10-2008-7029536 (with translation).
- Nov. 19, 2010 Office Action issued in Korean Patent Application No. 10-2008-7029535 (with translation).
- Oct. 27, 2010 Office Action issued in Korean Patent Application No. 10-2005-7009937 (with translation).
- Mar. 27, 2009 Office Action issued in Chinese Patent Application No. 2007101956440 (with translation).
- Dec. 14, 2010 Office Action issued in Chinese Patent Application No. 200380104450.5 (with translation).
- Jun. 13, 2008 Office Action issued in Chinese Patent Application No. 2003801044505 (with translation).
- Jan. 18, 2008 Office Action issued in Chinese Patent Application No. 2003801044505 (with translation).
- Jun. 29, 2007 Office Action issued in Chinese Patent Application No. 2003801044505 (with translation).
- Oct. 24, 2008 Office Action issued in Chinese Patent Application No. 2007101109529 (with translation).
- Nov. 13, 2009 Office Action issued in Chinese Patent Application No. 200810211496.1 (with translation).
- Jul. 25, 2008 Office Action issued in Chinese Patent Application No. 200710110949.7 (with translation).
- Aug. 21, 2009 Office Action issued in Chinese Patent Application No. 200810126659.6 (with translation).
- May 5, 2010 Office Action issued in Chinese Patent Application No. 200810126659.6 (with translation).
- Dec. 4, 2009 Office Action issued in Chinese Patent Application No. 2007101109529 (with translation).
- Apr. 13, 2010 Office Action issued in Chinese Patent Application No. 2007101109529 (with translation).
- Jun. 5, 2009 Office Action issued in Chinese Patent Application No. 2007101109497 (with translation).
- Jun. 5, 2009 Office Action issued in Chinese Patent Application No. 2007101109482 (with translation).
- Jul. 25, 2008 Office Action issued in Chinese Patent Application No. 2007101109482 (with translation).
- Jun. 5, 2009 Office Action issued in Chinese Patent Application No. 2007101109529 (with translation).
- Jun. 5, 2009 Office Action issued in Chinese Patent Application No. 2007101109514 (with translation).
- Jul. 25, 2008 Office Action issued in Chinese Patent Application No. 2007101109514 (with translation).
- Jun. 5, 2009 Office Action issued in Chinese Patent Application No. 200710110950X (with translation).
- Jul. 25, 2008 Office Action issued in Chinese Patent Application No. 200710110950X (with translation).
- Jun. 5, 2009 Office Action issued in Chinese Patent Application No. 2007101956421 (with translation).
- Apr. 28, 2010 Office Action issued in Chinese Patent Application No. 200710195642.1 (with translation).
- Dec. 18, 2009 Office Action issued in Chinese Patent Application No. 2007101956421 (with translation).
- Dec. 18, 2009 Office Action issued in Chinese Patent Application No. 2007101956417 (with translation).



(56)

**References Cited**

## OTHER PUBLICATIONS

- Jun. 5, 2009 Office Action issued in Chinese Patent Application No. 2007101956417 (with translation).
- Dec. 18, 2009 Office Action issued in Chinese Patent Application No. 2007101956440 (with translation).
- Aug. 7, 2009 Office Action issued in Chinese Patent Application No. 2007101956440 (with translation).
- Jan. 8, 2010 Office Action issued in Chinese Patent Application No. 2003801044505 (with translation).
- Oct. 26, 2004 Office Action issued in Chinese Patent Application No. 200480031414.5 (with translation).
- Jun. 10, 2010 Office Action issued in Chinese Patent Application No. 200810211497.6 (with translation).
- Feb. 6, 1996 Office Action issued in Taiwanese Patent Application No. 093109836 (with translation).
- Jul. 27, 2009 Office Action issued in Taiwanese Patent Application No. 092133642 (with translation).
- Mar. 17, 2008 Office Action issued in Taiwanese Patent Application No. 092133642 (with translation).
- Jul. 13, 2006 Office Action issued in Taiwanese Patent Application No. 092133642 (with translation).
- May 4, 2005 Office Action issued in Taiwanese Patent Application No. 092133642 (with translation).
- Dec. 3, 2004 Office Action issued in Taiwanese Patent Application No. 092133642 (with translation).
- Mar. 8, 2012 Office Action issued in Taiwanese Patent Application No. 093131767 (with translation).
- Jan. 28, 2010 Office Action issued in Japanese Patent Application No. 2008-077129 (with translation).
- Jun. 14, 2010 Office Action issued in Japanese Patent Application No. 2010-006125 (with translation).
- Apr. 15, 2010 Office Action issued in Japanese Patent Application No. 2007-251263 (with translation).
- Jan. 28, 2010 Office Action issued in Japanese Patent Application No. 2005-515005 (with translation).
- Feb. 20, 2009 Office Action issued in Japanese Patent Application No. 2005-505207 (with translation).
- Mar. 8, 2010 Office Action issued in Japanese Patent Application No. 2005-505207 (with translation).
- Aug. 5, 2009 Office Action issued in Japanese Patent Application No. 2004-570728 (with translation).
- Nov. 9, 2009 Office Action issued in Japanese Patent Application No. 2003-402584 (with translation).
- Nov. 10, 2009 Office Action issued in Japanese Patent Application No. 2003-390672 (with translation).
- Apr. 24, 2012 Office Action issued in Japanese Patent Application No. 2009-149426 (with translation).
- Sep. 27, 2011 Office Action issued in Japanese Patent Application No. 2010-003941 (with translation).
- Feb. 14, 2012 Office Action issued in Japanese Patent Application No. 2010-003941 (with translation).
- Sep. 27, 2011 Office Action issued in Japanese Patent Application No. 2010-003938 (with translation).
- Feb. 14, 2012 Office Action issued in Japanese Patent Application No. 2010-003938 (with translation).
- Mar. 6, 2012 Office Action issued in Japanese Patent Application No. 2007-544099 (with translation).
- Sep. 20, 2011 Office Action issued in Japanese Patent Application No. 2009-225810 (with translation).
- May 31, 2011 Office Action issued in Japanese Patent Application No. 2009-225810 (with translation).
- Jan. 17, 2012 Office Action issued in Japanese Appeal No. 2010-20697, Patent Application No. 2005-515570 (with translation).
- Jan. 17, 2012 Office Action issued in Japanese Appeal No. 2010-20696, Patent Application No. 2006-262589 (with translation).
- Jul. 14, 2008 Notice of Allowance issued in U.S. Appl. No. 11/246,642.
- Feb. 20, 2007 Office Action issued in U.S. Appl. No. 11/246,642.
- May 17, 2007 Office Action issued in U.S. Appl. No. 11/246,642.
- Dec. 4, 2007 Office Action issued in U.S. Appl. No. 11/246,642.
- Jun. 25, 2008 Office Action issued in U.S. Appl. No. 11/902,282.
- Feb. 9, 2009 Office Action issued in U.S. Appl. No. 11/902,282.
- Dec. 14, 2009 Office Action issued in U.S. Appl. No. 11/902,282.
- Jun. 20, 2008 Corrected Notice of Allowance issued in U.S. Appl. No. 11/140,103.
- Apr. 25, 2007 Office Action issued in U.S. Appl. No. 11/140,103.
- Jul. 12, 2007 Office Action issued in U.S. Appl. No. 11/140,103.
- Feb. 14, 2008 Office Action issued in U.S. Appl. No. 11/140,103.
- Nov. 6, 2008 Office Action issued in U.S. Appl. No. 12/155,301.
- Apr. 16, 2009 Office Action issued in U.S. Appl. No. 12/155,301.
- Sep. 14, 2009 Office Action issued in U.S. Appl. No. 12/155,301.
- Apr. 22, 2010 Office Action issued in U.S. Appl. No. 12/155,301.
- Aug. 31, 2011 Office Action issued in U.S. Appl. No. 12/093,303.
- Jan. 4, 2010 Notice of Allowance issued in U.S. Appl. No. 11/644,966.
- Apr. 14, 2010 Notice of Allowance issued in U.S. Appl. No. 11/644,966.
- Aug. 2, 2010 Notice of Allowance issued in U.S. Appl. No. 11/644,966.
- Feb. 8, 2011 Notice of Allowance issued in U.S. Appl. No. 11/644,966.
- Apr. 22, 2008 Office Action issued in U.S. Appl. No. 11/644,966.
- Nov. 12, 2008 Office Action issued in U.S. Appl. No. 11/410,952.
- Nov. 30, 2010 Notice of Allowance issued in U.S. Appl. No. 12/289,518.
- Nov. 18, 2010 Notice of Allowance issued in U.S. Appl. No. 12/289,515.
- Mar. 23, 2011 Notice of Allowance issued in U.S. Appl. No. 12/289,515.
- Nov. 28, 2011 Office Action issued in U.S. Appl. No. 12/801,043.
- Jan. 25, 2012 Office Action issued U.S. Appl. No. 12/801,043.
- Sep. 11, 2012 Preliminary Notice of First Office Action issued in Taiwanese Patent Application No. 097117896 (with Translation).
- Sep. 18, 2012 Office Action issued in Chinese Patent Application No. 200910173718.X (with Translation).
- Oct. 8, 2012 Office Action issued in Chinese Patent Application No. 200910173716.0 (with translation).
- Sep. 18, 2012 Notice of Reasons for Rejection issued in Japanese Patent Application No. 2010-094216 (with translation).
- Sep. 18, 2012 Notice of Reasons for Rejection issued in Japanese Patent Application No. 2011-144669 (with translation).
- Oct. 26, 2012 Office Action issued in Taiwanese Patent Application No. 097117893 (with translation).
- Oct. 17, 2012 Notice of Allowance issued in Korean Patent Application No. 10-2010-7001907 (with translation).
- Oct. 10, 2012 Office Action issued in Chinese Patent Application No. 200910173717.5 (with translation).
- Nov. 9, 2012 Office Action issued in U.S. Appl. No. 11/644,966.
- Jul. 30, 2012 Office Action issued in Korean Patent Application No. 10-2006-7018069 (with translation).
- Sep. 4, 2012 Notice of Reasons for Rejection in Japanese Patent Application No. 2010-087010 (with translation).
- Sep. 20, 2012 Office Action issued in European Patent Application No. 04 817 303.3.
- Jan. 7, 2013 Office Action issued in Chinese Patent Application No. 200910173715.6 (with translation).
- Jan. 14, 2013 Office Action issued in Chinese Patent Application No. 201010128876.6 (with translation).
- Jan. 9, 2013 Technical Presentation Document submitted in Korean Patent No. 839686 Appeal No. 2011Dang301 (with translation).
- Jan. 16, 2013 Office Action issued in Chinese Patent Application No. 200910173714.1 (with translation).
- Jan. 9, 2013 Technical Presentation Document submitted in Korean Patent No. 869390 Appeal No. 2011Dang302 (with translation).
- Jan. 14, 2013 Office Action issued in Chinese Patent Application No. 200910126047.1 (with translation).
- Jan. 18, 2013 Office Action issued in Chinese Patent Application No. 200810211496.1 (with translation).
- Feb. 6, 2013 Written Opinion issued in Korean Patent Application No. 10-2006-7008368 (with translation).
- Halliday et al., "Fundamentals of Physics: Extended, 4/e", John Wiley & Sons, Inc., Jul. 25, 1995.



(56)

**References Cited**

## OTHER PUBLICATIONS

- Feb. 6, 2013 Written Opinion issued in Korean Patent Application No. 10-2007-7022489 (with translation).
- Feb. 6, 2013 Written Opinion issued in Korean Patent Application No. 10-2008-7019081 (with translation).
- Feb. 6, 2013 Written Opinion issued in Korean Patent Application No. 10-2008-7019082 (with translation).
- Feb. 25, 2013 Office Action issued in U.S. Appl. No. 12/382,277.
- Feb. 22, 2013 Petitioner Statement issued in Korean Patent Application No. 10-2006-7008368 (with translation).
- Feb. 22, 2013 Petitioner Statement issued in Korean Patent Application No. 10-2007-7022489 (with translation).
- Feb. 22, 2013 Petitioner Statement issued in Korean Patent Application No. 10-2008-7019081 (with translation).
- Feb. 22, 2013 Petitioner Statement issued in Korean Patent Application No. 10-2008-7019082 (with translation).
- Jan. 29, 2013 Written Opinion submitted in Korean Patent No. 10-0869390 Appeal No. 2011Dang302 (with translation).
- Hecht, "Optics Fourth Edition", Addison Wesley, 2002.
- Hecht, "Optics Second Edition", Addison-Wesley, 1998.
- Bass, "Handbook of Optics", McGraw-Hill, 1995.
- Herzig, "Micro-optics", Taylor & Francis, 1997.
- Jan. 29, 2013 Written Opinion submitted in Korean Patent No. 10-0839686 Appeal No. 2011Dang301 (with translation).
- Jan. 30, 2013 Technical Presentation Documents submitted in Korean Patent No. 10-1020455 Appeal No. 2011Dang510 (with translation).
- Jan. 30, 2013 Technical Presentation Documents submitted in Korean Patent No. 10-1020378 Appeal No. 2011Dang511 (with translation).
- Feb. 24, 2013 Office Action issued in Korean Patent Application No. 10-2012-7034127 (with translation).
- Feb. 19, 2013 Office Action issued in Japanese Patent Application No. P2010-087010 (with translation).
- Feb. 19, 2013 Office Action issued in Japanese Patent Application No. P2011-138703 (with translation).
- Feb. 27, 2013 Office Action issued in Korean Patent Application No. 10-2012-7034128 (with translation).
- Mar. 19, 2013 Office Action issued in Japanese Patent Application No. P2010-145155 (with translation).
- Feb. 28, 2013 Trial Decision Rendered by Division VIII of Korean Patent Trial Board (KR Patent No. 10-0839686 Appeal No. 2011Dang301 (with translation)).
- Feb. 28, 2013 Trial Decision Rendered by Division VIII of Korean Patent Trial Board (KR Patent No. 10-0869390 Appeal No. 2011Dang302 (with translation)).
- Feb. 28, 2013 Trial Decision Rendered by Division VIII of Korean Patent Trial Board (KR Patent No. 10-1020455 Appeal No. 2011Dang510 (with translation)).
- Feb. 28, 2013 Trial Decision Rendered by Division VIII of Korean Patent Trial Board (KR Patent No. 10-1020378 Appeal No. 2011Dang511 (with translation)).
- Mar. 5, 2013 Office Action issued in Chinese Patent Application No. 200710110949.7 (with translation).
- Mar. 5, 2013 Office Action issued in Chinese Patent Application No. 200710110951.4 (with translation).
- Mar. 20, 2013 Office Action issued in U.S. Appl. No. 11/902,282.
- Apr. 2, 2013 Office Action issued in Japanese Patent Application No. P2010-286303 (translation only).
- Apr. 2, 2013 Office Action issued in Japanese Patent Application No. P2010-290979 (with translation).
- Apr. 9, 2013 Office Action issued in Korean Patent Application No. 10-2012-7008342 (with translation).
- Apr. 3, 2013 Office Action issued in Chinese Patent Application No. 200910173716.0 (with translation).
- Apr. 3, 2013 Office Action issued in Chinese Patent Application No. 200910173717.5 (with translation).
- Apr. 17, 2013 Office Action issued in Korean Patent Application No. 10-2013-7002721 (with translation).
- Apr. 18, 2013 Office Action issued in Korean Patent Application No. 10-2012-7003793 (with translation).
- May 2, 2013 Office Action issued in Taiwanese Patent Application No. 101102214 (with translation).
- May 14, 2013 Office Action issued in Japanese Patent Application No. 2011-130545 (with translation).
- May 7, 2013 Office Action issued in European Patent Application No. 04 817 303.3.
- May 16, 2013 Office Action issued in Taiwanese Patent Application No. 098115513 (with translation).
- Jun. 13, 2013 Search Report issued in European Patent Application No. 13156325.6.
- May 29, 2013 Office Action issued in European Patent Application No. 04799453.8.
- Apr. 23, 2013 Office Action issued in Chinese Patent Application No. 201010128876.6 (with translation).
- Jun. 18, 2013 Search Report issued in European Patent Application No. 13156322.3.
- Jun. 21, 2013 Search Report issued in European Patent Application No. 13156324.9.
- May 28, 2013 Office Action issued in Japanese Patent Application No. P2011-144669 (with translation).
- May 28, 2013 Office Action issued in Japanese Patent Application No. P2010-094216 (with translation).
- Jun. 4, 2013 Office Action issued in Chinese Patent Application No. 2007101 10950.X (with translation).
- Jul. 23, 2013 Office Action issued in U.S. Appl. No. 12/458,635.
- Jul. 23, 2013 Office Action issued in U.S. Appl. No. 11/410,952.
- Jul. 15, 2013 Notice of Allowance issued in U.S. Appl. No. 13/067,958.
- Jul. 15, 2013 Office Action issued in Chinese Patent Application No. 200910173718.X (with translation).
- Jul. 22, 2013 Notice of Allowance issued in U.S. Appl. No. 12/289,515.
- Aug. 1, 2013 Office Action issued in U.S. Appl. No. 12/318,216.
- Aug. 6, 2013 Office Action issued in U.S. Appl. No. 13/889,798.
- Jul. 1, 2013 Preparatory Document (1), Patent Invalidation Action 2013HE03937 issued in Korean Patent Application No. 10-2006-7008368 (with translation).
- Jul. 1, 2013 Preparatory Document (1), Patent Invalidation Action 2013HE03920 issued in Korean Patent Application No. 10-2007-7022489 (with translation).
- Jul. 1, 2013 Preparatory Document (1), Patent Invalidation Action 2013HE03944 issued in Korean Patent Application No. 10-2008-7019081 (with translation).
- Jul. 1, 2013 Preparatory Document (1), Patent Invalidation Action 2013HE03951 issued in Korean Patent Application No. 10-2008-7019082 (with translation).
- Jul. 1, 2013 Definition of Technical Terms (with translation).
- Doosan Encyclopedia, Optic axis (with translation).
- Buhrer, "Four waveplate dual tuner for birefringent filters and multiplexers", Applied Optics vol. 26, No. 17, 1 Sep. 1987, pp. 3628-3632.
- Niziev et al., "Influence of Beam Polarization on Laser Cutting Efficiency", Journal of Physics D Applied Physics 32, 1999, pp. 1455-1461.
- Sep. 11, 2013 Office Action issued in U.S. Appl. No. 13/890,603.
- Aug. 23, 2013 Reply Brief, Patent Invalidation Action 2013HE03975 issued in Korean Patent Application No. 10-2007-7022489 (with translation).
- Aug. 23, 2013 Reply Brief, Patent Invalidation Action 2013HE03982 issued in Korean Patent Application No. 10-2008-7019081 (with translation).
- Bagini et al., "The Simon-Mukunda polarization gadget", Eur. J.Phys.17, 1996, pp. 279-284.
- Mcguire, Jr. et al., "Analysis of spatial pseudodepolarizers in imaging systems", Optical Engineering, vol. 29 No. 12, 1990, pp. 1478-1484.
- Oct. 17, 2013 Notice of Allowance issued in Korean Patent Application No. 10-2012-7008342 (with English translation).
- Oct. 18, 2013 Office Action issued in U.S. Appl. No. 11/902,282.
- Oct. 29, 2013 Office Action issued in U.S. Appl. No. 13/890,547.



(56)

**References Cited**

OTHER PUBLICATIONS

Oct. 21, 2013 Office Action issued in U.S. Appl. No. 13/137,002.  
Oct. 29, 2013 Office Action issued in U.S. Appl. No. 13/890,142.  
Nov. 5, 2013 Office Action issued in Japanese Patent Application No. P2012-080675 (with translation).  
Nov. 5, 2013 Office Action issued in Japanese Patent Application No. P2012-080678 (with translation).  
Oct. 10, 2013 Office Action issued in U.S. Appl. No. 13/890,547.  
Oct. 15, 2013 Office Action issued in U.S. Appl. No. 13/889,965.  
Oct. 15, 2013 Office Action issued in U.S. Appl. No. 13/137,342.  
Oct. 16, 2013 Office Action issued in U.S. Appl. No. 13/137,003.  
Nov. 7, 2013 Office Action issued in U.S. Appl. No. 12/289,518.  
Nov. 8, 2013 Office Action issued in U.S. Appl. No. 13/912,832.  
Nov. 12, 2013 Office Action issued in U.S. Appl. No. 13/889,860.  
Nov. 13, 2013 Office Action issued in U.S. Appl. No. 13/889,965.  
Dec. 13, 2013 Office Action issued in European Patent Application No. 09 015 058.2.

Nov. 20, 2013 Office Action issued in U.S. Appl. No. 12/289,515.  
Oh, "Notarial Certificate of affiant Professor H. G. Oh", Oct. 22, 2013 (with English translation).  
"Declaration of Dr. Michael Totzeck", Oct. 8, 2013 (with English translation).  
"Korean Patent Office Guidelines for Examination," 2010 (with partial translation).  
Oct. 25, 2013 Preparatory Document (2-1), Korean Patent Invalidation Action 2013HE003937 (with English translation).  
Oct. 25, 2013 Preparatory Document (2-2), Korean Patent Invalidation Action 2013HE003937 (with English translation).  
Dec. 4, 2013 Office Action issued in Chinese Patent Application No. 2007101 10950.X (with translation).  
Dec. 17, 2013 Office Action issued in Korean Patent Application No. 10-2013-7026632 (with translation).  
Dec. 18, 2013 Office Action issued in Korean Patent Application No. 10-2012-7034127 (with translation).

\* cited by examiner



Fig. 1A




Fig. 1B




Fig. 1C






Fig. 2




Fig. 3






Fig. 4




Fig. 5






Fig. 6A




Fig. 6B






Fig. 7A




Fig. 7B






Fig. 8




Fig. 9






Fig. 10




Fig. 11A




Fig. 11B






Fig. 12




Fig. 13A




Fig. 13B






Fig. 14




Fig. 15A




Fig. 15C




Fig. 15B






Fig. 16A




Fig. 16B




Fig. 17






Fig. 18




Fig. 19




Fig. 20






Fig. 21




Fig. 22A




Fig. 22B






Fig. 23





Fig. 24





**EXPOSURE METHOD AND APPARATUS, AND  
METHOD FOR FABRICATING DEVICE WITH  
LIGHT AMOUNT DISTRIBUTION HAVING  
LIGHT LARGER IN FIRST AND SECOND  
PAIRS OF AREAS**

This is a Divisional of U.S. application Ser. No. 11/246,642 filed Oct. 11, 2005, which is a Continuation of International Application No. PCT/JP2004/004522 filed Mar. 30, 2004. The entire disclosures of the prior applications are hereby incorporated by reference herein in their entirety.

TECHNICAL FIELD

The present invention relates to an exposure technology used to transfer mask-pattern on substrates such as wafers in a lithography process for fabricating various kinds of devices such as semiconductor elements, liquid crystal displays, thin-film magnetic heads and, more particularly to an exposure technology using an illuminating technology related to the so-called deformed illumination. Further, the present invention relates to a technology for fabricating the device using the exposure technology.

BACKGROUND ART

The apparatus for the projection exposure of the batch exposure system such as the step-and-repeat system or the scan exposure system such as the step-and-scan system have been used to transfer the pattern of the reticle (or photo-mask etc.) as the mask on the wafers (or vitreous plate etc.) as the substrates intended for exposure in the lithography process for fabricating semiconductor elements (or liquid crystal displays etc.). In the kind of apparatus for the projection exposure, it is desirable to transfer various kinds of pattern on the wafers with each high resolution.

The transferred pattern that requires very fine high resolution is the so-called contact hole. The contact hole includes the densely massed contact hole having a plurality of predetermined shaped aperture arranged with predetermined fine pitch and the isolated contact hole being substantially comprised of a single aperture. In order to transfer the pattern of the former densely massed contact hole on the wafer with high resolution, the so-called deformed illumination system (deformed light source system) which allows the amount of light of the illumination light to be enlarged in one or more areas (particularly four areas) being eccentric for optical axis at the pupil plane of the illumination system, is effective (refer to Japanese Patent Applications Laid-open No. Hei 5-67558 (corresponding with U.S. Pat. No. 6,094,305) and NO. 2001-176766 (corresponding to U.S. Pat. No. 6,563,567)).

On the other hand, in order to transfer the pattern of the later isolated contact hole on the wafer with high resolution, the illumination system, which allows the amount of light of the illumination light to be enlarged in a relatively small round area centering optical axis at the pupil plane of the illumination system, that is, the illumination system that allows the  $\sigma$  value, being a coherence factor of the illumination system to be relatively lessened (hereinafter, it will be called "small  $\sigma$  illumination system" for convenience of description), is known to be effective.

DISCLOSURE OF THE INVENTION

As described above, the pattern of the densely massed contact hole with fine pitch and the isolated contact hole can be transferred on the wafer with high resolution through the

deformed illumination system and the small  $\sigma$  illumination system respectively. Recently with regard to this, for example, in fabricating semiconductor elements, it is becoming a requirement that transferring one reticle pattern being formed, the pattern being of the contact hole, with various kinds of pitch, which include the patterns ranging from the contact hole arranged with great pitch, which can be substantially regarded as the isolated contact hole, to the densely massed contact hole with fine pitch, on the wafer at one time exposure.

For that reason, however, it is a disadvantage that when using the deformed illumination system, the resolution is not sufficient for the contact hole with large pitch; while when using the small  $\sigma$  illumination system, the resolution is not sufficient for the densely massed contact hole with fine pitch.

Further, recently, for example, when fabricating semiconductors, it has come to be demanded to transfer the pattern of the so-called contact hole densely massed in one direction, which is arranged in the one direction with fine pitch and can be substantially regarded as the isolated pattern in terms of the direction orthogonal to it, to wafer with high resolution.

However, it is a disadvantage that the resolution is not sufficient in the direction in which the pattern can be regarded as the isolated pattern, with using the traditional deformed illumination system for this purpose. Whereas, it is not sufficient in the direction in which the pattern is arranged with the fine pitch, with using the small  $\sigma$  illumination system.

Considering this problem, the first object of the present invention is to provide an exposure technology for simultaneously transferring the pattern having various kinds of pitches with high resolution respectively.

And the second object of the present invention is to provide an exposure technology for transferring the pattern, which is arranged in one direction periodically and is substantially isolated (pattern densely massed in one direction) in terms of the orthogonal direction, with high resolution.

And the third object of the present invention is to provide a manufacturing technology for fabricating the device including various kinds of patterns or including the pattern densely massed in one direction with high accuracy and yet high throughput.

The first exposure method according to the present invention, which is an exposure method for illuminating a mask with an optical beam from an illumination system to expose a substrate with the optical beam through the mask and a projection system, characterized in that a light amount distribution of the optical beam on a predetermined plane with respect to the illumination system is set such that an amount of light is set larger in nine areas than in an area other than the nine areas, the nine areas including a first area and eight areas, an outer contour of the first area including an optical axis of the illumination system, and the eight areas being arranged so as to encompass the first area and each of the eight areas being smaller than the first area.

According to the present invention, such a pattern that is great in pitch and can be substantially regarded as the isolated contact hole by means of the optical beam passing through the first area is transferred with high resolution, and the pattern which includes the patterns ranging from the pattern with around middle pitch to the pattern with fine pitch like the densely massed contact hole by means of the optical beam passing through the eight areas enclosing the first area, is transferred with high-resolution. Accordingly, it is able to simultaneously transfer the patterns having various kinds of pitches with high resolution respectively.

In this case, it is preferable that the first area to be located at the center is an annular zone area. With the annular illumi-



nation at the first area, the resolution and the depth of focus might be improved in some cases. Furthermore, the amount of light (intensity per unit area e.g.) at the first area to be located in the center may be made different from the amount of light at the surround areas enclosing it.

Furthermore, as an example, the predetermined plane is a pupil plane of the illumination system, and the nine areas in which the amount of light on the predetermined plane is greater than the amount of light at the area other than the nine areas, comprises the first area, four second areas which are arranged along a first circumference that encloses the first area and which are respectively smaller than the first area, and four third areas which are arranged along a second circumference that encloses the first circumference and which are respectively smaller than the first area.

With this composition, the pattern having the around middle pitch is transferred with high resolution by means of the optical beam passing through the second areas, and the pattern having the fine pitch is transferred with high resolution by means of the optical beam passing through the third areas.

Furthermore, it is preferable that the first area, two of the second areas, and two of the third areas are arranged along a first straight line passing through the optical axis of the illumination system, and the first area, the other two of the second areas, and the other two of the third areas are arranged along a second straight line which is orthogonal to the first straight line and which passes through the optical axis of the illumination system.

The conventional pattern intended to transfer is two-dimensionally arranged along two directions orthogonal to each other (one of them will be called "arranging direction of pattern"). Then, by making the direction of the first straight line (or the second straight line) intersect the arranging direction of the pattern (preferably making it intersect at 45 degree), the pattern having various kinds of the pitches two-dimensionally arranged can be transferred with high resolution respectively.

Further, the radius (r1) when the first area is made circular, and the radii (r2, r3) when the second and third areas are made circular are preferably set to the following bounds with the maximum  $\sigma$  value (this will be assumed a) of the illumination system assumed to be a reference. In addition, also if the first area, second areas, and third areas are set to other shape different from the circles such as the square, the regular hexagon or the shape having one quarter circle, the sizes of them preferable equal those of the circulars. In addition, if the first area is annular, the outer radius (r1) is preferably set to the bounds of an equation (1), as follows:

$$0.2\sigma \leq r1 \leq 0.4\sigma \quad (1)$$

$$0.075\sigma \leq r2 \leq 0.2\sigma \quad (2)$$

$$0.075\sigma \leq r3 \leq 0.2\sigma \quad (3)$$

If each area becomes smaller than the lower limit of the equation (1), equation (2), and equation (3), there is a possibility that the resolution deteriorates for some patterns from among the patterns having various kinds of the pitches. On the other hand, if each area becomes greater than the upper limit of the equation (1), equation (2), and equation (3), there is a possibility that the resolution deteriorates for the pattern having fine pitch because this system will be close to the conventional illumination system.

Next, the second exposure method according to the present invention, which is an exposure method for illuminating a mask with an optical beam from an illumination system to

expose a substrate with the optical beam through the mask and a projection system, has a step of setting a light amount distribution of the optical beam on a predetermined plane with respect to the illumination system is set such that an amount of light is set larger in five areas than in an area other than the five areas, the five areas including a first area of an annular zone shape in which an outer contour of the first area including an optical axis of the illumination system, and the four areas being arranged so as to encompass the first area and each of the four areas being smaller than the first area.

According to the present invention, such a pattern that is large in the pitch and can be substantially regarded as the isolated contact hole is transferred by means of the optical beam passing through the annular first area is transferred with high resolution, and the pattern having fine pitch like the densely massed contact hole by means of the optical beam passing through the four areas enclosing the first area is transferred with high resolution. Accordingly, it is able to simultaneously transfer the patterns having various kinds of the pitches with high resolution respectively.

Further, as an example, the predetermined plane is a pupil plane of the illumination system, and the five areas in which the amount of light on the predetermined plane is greater than the amount of light at the area other than the five areas, comprises the first area and four second areas which are arranged, at intervals of substantially 90 degree therebetween, along a circumference that encloses the first area and which are respectively smaller than the first area.

With this composition, the pattern having the fine pitch is transferred with high resolution by means of the optical beam passing through the second areas. The conventional pattern intended to transfer is two-dimensionally arranged along two directions orthogonal to each other (one of them will be called "arranging direction of pattern"). Then, by making the direction, in which the second areas are arranged intersect the arranging direction of the pattern (preferably making it intersect at 45 degree), the pattern having various kinds of the pitches two-dimensionally arranged can be transferred with high resolution respectively.

Further, it is preferable that the radius (r1) when the first area is made annular with its contour assumed to be circular and the radius (r2) when the second area is made circular is preferably set within the bounds of the equations (1) and (2) described above with the maximum  $\sigma$  value (this will be assumed  $\sigma$ ) of the illumination system assumed to be a reference. This enables the pattern having various kinds of the pitches to be transferred with high resolution.

In the present invention, an optical beam generated from each of the areas which have large amount of light which are arranged out of the optical axis of the illumination system on the predetermined plane is linear polarization. In this case, a direction of polarization of the optical beam on the predetermined plane is substantially coincident with a circumference direction (that is, the optical beam may be S polarization).

Next, the third method for exposure according to the present invention, which is an exposure method having a step for illuminating a mask with an optical beam from an illumination system to expose a substrate with the optical beam through the mask and a projection system, has a step of setting a light amount distribution of the optical beam on a predetermined plane with respect to the illumination system is set such that an amount of light is set larger in three areas than in the area other than these.

According to the present invention, if one direction dense patterns are formed at the mask, the patterns are transferred with high resolution the direction of which the patterns are isolate by means of optical beam passing through the center of



5

the three areas, and the patterns are transferred with high resolution the direction of which the patterns are periodically arranged by means of optical beam passing through the two areas which sandwich the center area.

In this case, the three areas having large amount of light include a first area near an optical axis of the illumination system, and a second area and a third area which are arranged along a straight line passing through the optical axis so as to sandwich the first area. Alternatively, the three areas having large amount of light include a first area near an optical axis of the illumination system, and a second area and a third area which are arranged with the approximately same distance from the optical axis.

With these compositions, by providing (paralleling) the direction of which the three areas are arranged to the direction of which the one direction dense pattern is periodically arranged, it is able to transfer the one directional high density pattern to the two directions of the isolated and periodical ones with high resolution.

In other words, if a pattern formed on the mask includes a one directionally high density pattern which is periodically arranged along a predetermined first axis and which is substantially isolated in a direction of a second axis orthogonal to the first axis, the three areas having large amount of light are preferably arranged with a distance therebetween in a parallel direction to the first axis. Whereby, it is able to transfer the one directional high density pattern with high resolution along the first axis and the second axis respectively. Further, the three areas having large amount of light are preferably arranged along a straight line which is parallel to the first axis and which passes through the optical axis of the illumination system.

Furthermore, a center area of the three areas having large amount of light is preferably set such that an amount of light of a center part thereof is smaller than an amount of light of a part other than the center part. Whereby, it is able to increase the resolution in the direction of which the pattern is isolated and to widen the depth of focus.

In this case, the center area is around an annular zone area as an example. Furthermore, the center area comprises a plurality of areas separated from each other. The plurality of areas separated from each other, which are the center area, are arranged along a predetermined straight line passing through the optical axis of the illumination system on the predetermined plane as an example. Furthermore, an arranging direction of the plurality of areas separated from each other, which are the center area, is determined according to a size of the center area as another example.

Further, the three areas have outlines which are the substantially same with each other as an example. Further, the sizes of the three areas having large amount of light respectively correspond to 0.1 times 0.2 times of a maximum  $\sigma$  value of the illumination system. Whereby, the deep depth of focus is obtained according to the simulation of the present invention.

Furthermore, the two areas of the three areas having large amount of light, which are arranged at both ends with respect to the direction parallel to the first axis, may respectively have longitudinal directions which are substantially coincident with a direction parallel to the second axis. Whereby, it is able to enhance the resolution corresponding to the one directional high density pattern and to avoid the reduction of the amount of light.

Further, the center area of the three areas having large amount of light may have a longitudinal direction which is substantially coincident with the direction parallel to the first axis.

6

Furthermore, an optical beam generated from a center area of the three areas having large amount of light may linear polarization, a directions of polarization is substantially coincident with a direction parallel to the first axis.

Furthermore, an optical beam generated from a center area of the three areas having large amount of light and optical beams generated from the other two areas may have different polarization states from each other. In this case, a polarization direction of the optical beam generated from the center area and a polarization direction of the optical beams generated from the other two areas are orthogonal to each other.

Further, a size of the center area of the three areas having great amount of light and sizes of the other two areas may be different from each other.

Further, the optical beams generated from the other two areas except for the center area of the three areas having large amount of light may be respectively linear polarization. In this case, for an example, the directions of polarization of optical beams distributed in the other two areas on the predetermined plane may be respectively substantially coincident with a circumference direction (that is, the optical beam may be S polarization).

Further, for an example, the predetermined plane is a pupil plane of the illumination system. Furthermore, as another example, a predetermined plane is the conjugate plane for the pupil plane of the illumination system or the pupil of the projection system (or its conjugate plane). In this case, it is obtained the highest resolution.

Next, the first exposure apparatus according to the present invention, in an exposure apparatus which an illumination system illuminates a mask with an optical beam; and a projection system which exposes a substrate with the optical beam from the mask, characterized by comprising an optical member which sets a light amount distribution of the optical beam on a predetermined plane with respect to the illumination system such that an amount of light is set larger in nine areas than in an area other than the nine areas, the nine areas including a first area and eight areas, an outer contour of the first area including an optical axis of the illumination system, and the eight areas being arranged so as to encompass the first area and each of the eight areas being smaller than the first area.

According to the present invention, with the optical members, it is able to simultaneously transfer patterns having various kinds of pitch with high resolution respectively.

In this case, in order to more improve the resolution and the depth of focus, it is preferable that the central first area is an annular zone area.

Furthermore, as an example, the predetermined plane is a pupil plane of the illumination system, and the nine areas in which the amount of light at the predetermined plane is greater than the amount of light at the area other than the nine areas, comprises the first area, four second areas which are arranged along a first circumference that encloses the first area and which are respectively smaller than the first area, and four third areas which are arranged along a second circumference that encloses the first circumference and which are respectively smaller than the first area.

Furthermore, it is preferable that the first area, the two second areas, and two of the third areas are arranged along a first straight line passing through the optical axis of the illumination system, and the first area, the other two of the second areas, and the other two of the third areas are arranged along a second straight line which is orthogonal to the first straight line and which passes through the optical axis of the illumination system.



Also in this case, the size of each area preferably satisfies the conditions of the equations (1) to (3).

Next, the second exposure apparatus according to the present invention, in an exposure apparatus which an illumination system which illuminates a mask with an optical beam; and a projection system which exposes a substrate with the optical beam from the mask, characterized by comprising an optical member which sets a light amount distribution of the optical beam on a predetermined plane with respect to the illumination system such that an amount of light is set larger in five areas than in an area other than the five areas, the five areas including a first area of an annular zone shape and four areas, an outer contour of the first area including an optical axis of the illumination system, and the four areas being arranged so as to encompass the first area and each of the four areas being smaller than the first area.

According to the present invention, with the optical members, it is able to simultaneously transfer patterns having various kinds of pitch with high resolution respectively.

Further, as an example, the predetermined plane is a pupil plane of the illumination system, and the five areas in which the amount of light on the predetermined plane is greater than the amount of light at the area other than the five areas, comprises the first area and four second areas which are arranged, at intervals of substantially 90 degree therebetween, along a circumference that encloses the first area and which are respectively smaller than the first area.

Also in this case, the size of each area preferably satisfies the conditions of the equations (1) to (3).

Furthermore, as an example, the illumination system includes an optical integrator which substantially uniformize illuminance within an illuminant area on the mask on which the optical beam is irradiated, and the optical member is arranged at an incident side of the optical integrator in the illumination system, and the optical member includes a diffractive optical element which diffracts the optical beam to a plurality of directions. In particular, with using a phase type diffractive optical element, it is able to obtain high use-efficiency.

Furthermore, as another example, the illumination system includes an optical integrator which substantially uniformize illuminance within an illuminant area on the mask on which the optical beam is irradiated, and the optical member is arranged on the predetermined plane or a conjugate plane thereof, and the optical member includes an aperture stop defining an area in which an amount of light is enhanced on the predetermined plane. The aperture stop has a simple structure and can easily set the preferable distribution of the amount of light.

Further, the optical member can preferably set different plural light amount distributions including a distribution which enhances the amount of light at the plurality of areas. Whereby, it is able to expose various kinds of pattern with optimum irradiating condition.

In the exposure apparatus according to the present invention also, an optical beam generated from each of the areas which have large amount of light and which are arranged out of the optical axis of the illumination system on the predetermined plane may be linear polarization. In this case, a direction of polarization of the optical beam on the predetermined plane may substantially coincident with a circumference direction (that is, the optical beam may be S polarization).

Further, as an example, the optical member may further include a deflection member which generates optical beams respectively distributed at different areas on the predetermined plane, and a polarization setting member which sets

polarization states of the optical beams generated from the deflection member in the illumination system.

An example of the deflection member is a diffractive optical element which generates diffracted light to a plurality of directions on an optical path of the illumination system.

Furthermore, the optical member includes movable members which are arranged at an exit side of the deflection member, and which can change a positional relation between each area outside the optical axis on the predetermined plane and the optical axis of the illumination system, and the polarization setting member may be arranged between the deflection member and the movable member.

Further, the movable members may include at least one movable prism which has an inclined plane through which an optical beam distributed in a predetermined area including a plurality of areas outside the optical axis except the first area on the predetermined plane passes, the at least one movable prism moves along the optical axis of the illumination system.

Further, the optical member includes at least one movable prism which can change positions of a plurality of areas which enclose the first area and which have greater amount of light than an area other than the plurality of areas. The movable prism, as an example, has an inclined plane through which an optical beam distributed in a predetermined area including a plurality of areas outside the optical axis except the first area on the predetermined plane passes, and the movable prism moves along the optical axis of the illumination system. Furthermore, the movable prism, as another example, has a flat plane through which an optical beam distributed in the first area passes and which is approximately orthogonal to the optical axis of the illumination system.

Next, the third exposure apparatus according to the present invention, in an exposure apparatus which an illumination system illuminates a mask with an optical beam; and a projection system which exposes a substrate with the optical beam from the mask, characterized by comprising an optical member which sets a light amount distribution of the optical beam on a predetermined plane with respect to the illumination system such that an amount of light is set larger in a first area and a plurality of areas than in an area other than the first area and the plurality of areas, the first area substantially including an optical axis of the illumination system, and the plurality of areas being arranged outside the first areas, wherein the optical member includes a deflection member which generates optical beams respectively distributed at different areas on the predetermined plane, and at least one movable prism having a flat plane through which an optical beam generated from the deflection member and distributed in the first area passes and which is approximately orthogonal to the optical axis of the illumination system and an inclined plane through which an optical beam distributed in a predetermined area including a plurality of areas outside the optical axis except the first area passes, to change a positional relation between each area outside the optical axis on the predetermined plane and the optical axis of the illumination system.

According to the present invention, with the deflection member, it is able to simultaneously transfer pattern having various kinds of pitch with high resolution respectively. Further, with the movable prism, it is able to adjust the characteristic of the image-forming according to the kind of the pattern to be transferred.

In the present invention, as an example, the illumination system includes an optical integrator which substantially uniformize illuminance within an illuminant area on the mask on which the optical beam is irradiated, and the movable prism is



arranged at an incident side of the optical integrator in the illumination system, and the movable prism moves along the optical axis.

Further, optical beams generated from the plurality of areas arranged outside the first area are respectively linear polarization (S polarization) in which the polarization direction thereof being substantially coincident with a circumference direction on the predetermined plane.

Further, the optical member can preferably set different plural light amount distributions including a distribution which enhances the amount of light at the plurality of areas including the first area.

Next, the forth exposure apparatus according to the present invention, in an exposure apparatus an illumination system illuminates a mask with an optical beam; and a projection system which exposes a substrate with the optical beam from the mask, characterized by comprising optical members which set a light amount distribution of the optical beam on a predetermined plane with respect to the illumination system such that an amount of light is set larger in three areas separated from each other than in an area other than the three areas.

According to the present invention, with using the optical member, it is able to transfer the one direction dense pattern to the two directions of the isolated and periodical ones with high resolution.

In this case, the three areas having large amount of light preferably include a first area near an optical axis of the illumination optical system, and a second area and a third area which are arranged along a straight line passing through the optical axis so as to sandwich the first area. Alternatively, the three areas having large amount of light may include a first area near an optical axis of the illumination optical system, and a second area and a third area which are arranged with the approximately same distance from the optical axis.

In these compositions, if a first axis direction in which a high density pattern formed on the mask is periodically arranged and a second axis direction in which the high density pattern is arranged substantially isolatedly, the second axis direction being orthogonal to the first axis direction, the three areas having large amount of light are arranged with a distance therebetween in a parallel direction to the first axis direction. Whereby, it is able to transfer the one direction dense pattern with high resolution along the first axis and the second axis respectively. Further, the three areas having large amount of light are arranged along a straight line which passes through the optical axis of the illumination system and which is parallel to the first axis.

Further, a center area of the three areas having large amount of light is set such that an amount of light of a center part thereof is smaller than an amount of light of a part other than the center part. Whereby, it is able to increase the resolution in the direction of which the pattern is isolated and to widen the depth of focus.

In this case, the center area is substantially an annular zone area as an example. Furthermore, the center area comprises a plurality of areas separated from each other as another example. The plurality of areas separated from each other, which are the center area, are arranged along a predetermined straight line passing through the optical axis of the illumination optical system on the predetermined plane as an example. Furthermore, an arranging direction of the plurality of areas separated from each other, which are the center area, is determined according to a size of the center area as another example.

Further, the sizes of the three areas having large amount of light respectively correspond to 0.1 times to 0.2 times of a

maximum  $\sigma$  value of the illumination system. Whereby, the deep depth of focus is obtained according to the present invention.

Further, in the present invention, two areas of the three areas having large amount of light, which are arranged at both ends with respect to the direction parallel to the first axis, respectively have longitudinal directions which are substantially coincident with a direction parallel to the second axis.

Further, a center area of the three areas having large amount of light has a longitudinal direction which is substantially coincident with the direction parallel to the first axis.

Further, an optical beam generated from a center area of the three areas having large amount of light is linear polarization, a directions of polarization is substantially coincident with a direction parallel to the first axis.

Further, an optical beam generated from a center area of the three areas having large amount of light and optical beams generated from the other two areas may have different polarization states from each other. In this case, as an example, a polarization direction of the optical beam generated from the center area and a polarization direction of the optical beams generated from the other two areas are orthogonal to each other.

Further, a size of the center area of the three areas having great amount of light and sizes of the other two areas may be different from each other.

Further, optical beams generated from the other two areas except for the center area of the three areas having large amount of light are respectively linear polarization. In this case, as an example, directions of polarization of optical beams distributed in the other two areas on the predetermined plane are respectively substantially coincident with a circumference direction (S polarization).

Further, as an example, the optical member includes a deflection member which generates optical beams respectively distributed at different areas on the predetermined plane, and the exposure apparatus further comprises a polarization setting member which sets polarization states of the optical beams generated from the deflection member in the illumination system. In this case, further, the optical member includes a movable member which is arranged at an exit side of the polarization member, deflection member, and which can change a positional relation between the other two areas except for the center area of the three areas having large amount of light and the optical axis of the illumination system, and the polarization setting member is arranged between the deflection member and the movable member.

Further, the movable member includes at least one movable prism which has an inclined plane through which an optical beam distributed in a predetermined area including the other two areas except for the center area on the predetermined plane passes, and the at least one movable prism moves along the optical axis of the illumination system.

Further, the optical member may include at least one movable prism which can change positions of the other two areas except for the center area of the three areas having large amount of light. In this case, the movable prism, as an example, has an inclined plane through which an optical beam distributed in a predetermined area including the other two areas except for the center area on the predetermined plane passes, and the movable prism moves along the optical axis of the illumination system.

Further, the movable prism, as another example, may have a flat plane through which an optical beam distributed in the center area on the predetermined plane passes and which is approximately orthogonal to the optical axis of the illumination system. Further, as an example, the illumination system



## 11

includes an optical integrator which substantially uniformize illuminance within an illuminant area on the mask on which the optical beam is irradiated, and the movable prism is arranged at an incident side of the optical integrator in the illumination system.

Further, a predetermined plane is, as an example, a pupil plane of the illumination system. In this case, the illumination system, as an example, includes an optical integrator which substantially uniformize illuminance within an illuminant area on the mask on which the optical beam is irradiated, and the optical members include a diffractive optical element which is arranged at an incident plane side of the optical integrator in the illumination system. With this constitution, it is able to obtain a high efficiency.

Further, as another constitution of a predetermined plane being the pupil plane, the illumination system includes an optical integrator which substantially uniformize illuminance within an illuminant area on the mask on which the optical beam is irradiated, and the optical member is arranged on the predetermined plane or a conjugate plane thereof, and the optical member includes an aperture stop defining the three areas. With this constitution, it is easily able to make the distribution of the amount of light at a predetermined plane desirable distribution.

Further, the optical members can preferably set different plural light amount distributions including a light amount distribution which enhances the amount of light in the three areas. Whereby, it is able to transfer various kinds of patterns with high resolution.

Next, method for fabricating device according to the present invention is method for fabricating device including lithography process in which patterns are transferred to the photosensitive material by using the exposure method or apparatus according to the present invention. With the exposure method or apparatus according to the present invention, the mass production of devices including various kinds of patterns or one direction pattern with high accuracy.

## EFFECTS OF THE PRESENT INVENTION

In the present invention, when setting the distribution of a predetermined plane relating to the illumination system so as to increase the amount of light at a predetermined nine or five areas, it is able to simultaneously transfer patterns having various kinds of pitches with high resolution respectively.

Further, by making the center first area annular, it is able to more improve the resolution and depth of focus. Furthermore, by controlling the state of polarization of the optical beam, it might be able to more improve the resolution and the like.

Furthermore, in the present invention, when setting the distribution of a predetermined plane relating to the illumination system so as to increase the amount of light at a predetermined three areas, it is able to transfer one direction patterns with high resolution.

Furthermore, if the pattern formed at the mask is periodically arranged along a predetermined first axis and includes the one direction dense pattern which is substantially isolated in the direction of the second axis orthogonal to the first axis, by arranging the three areas in which the amount of light is great with distance in the parallel direction to the first axis, it is able to transfer the one direction dense pattern with high resolution both directions of arranging the one direction dense pattern to periodical and isolatable ones. Further, in the present invention, with setting the state of polarization of the optical beam oriented from the three areas in which the

## 12

amount of light is great, it might be to improve the resolution and the like for a predetermined pattern.

## BRIEF DESCRIPTION OF THE FIGURES IN THE DRAWINGS

FIG. 1A shows a composition of a projection exposure apparatus of the first embodiment according to the present invention, FIG. 1B shows an enlarged perspective view of prism 71, 72 of FIG. 1A, FIG. 1C shows other example composition of prism 71, 72;

FIG. 2 is a plan view showing an example pattern of reticle R;

FIG. 3 shows the distribution of amount of light to be set by diffractive optical element 21 on the exit plane (pupil plane) of the fly' eye lens 5, which includes the amount of light in nine areas;

FIG. 4 shows the distribution of amount of light becoming large in five areas on the exit plane (pupil plane) of the fly' eye lens 5;

FIG. 5 shows an evaluating result through simulation of the transferred image when exposure is made with the distribution of amount of light of FIGS. 3 and 4;

FIG. 6A shows a modified example of assuming the center of the area to be annular, in the distribution of amount of light of FIG. 3, and FIG. 6B shows another modified example of the amount of light of FIG. 3;

FIG. 7A shows a distribution of amount of light in which the amount of light becomes large in five areas including the center of the annulus to be set by the diffractive optical element 22 on the exit plane (pupil plane) of the fly' eye lens 5, and FIG. 7B shows a modified example of the distribution of amount of light of FIG. 7A;

FIG. 8 shows an evaluating result through simulation of the transferred image when exposure is made with the distribution of amount of light of FIG. 7A;

FIG. 9 shows a modified example for the distribution of amount of light of FIG. 3;

FIG. 10 shows a modified example of perspective view of the prisms 71 and 72 of FIG. 1A;

FIG. 11A is a plan view of one example of the pattern of reticle R 1 that becomes an object of exposure in the second embodiment of the present invention, and FIG. 11B shows a modified example of the pattern of reticle R 1;

FIG. 12 shows a distribution of amount of light, which is set by the diffractive optical element 22 A of FIG. 1A on the exit plane (pupil plane) of the fly' eye lens 5 in the second embodiment of the present invention;

FIG. 13A shows optical beams diffracted in the Y direction by the pattern 52 of FIG. 11A, and FIG. 13B shows optical beams diffracted in the X direction by the pattern 52 of FIG. 11A;

FIG. 14 shows an evaluating result of depth of focus (DOF) through simulation of the transferred image when exposure is made with the distribution of amount of light of FIG. 12;

FIG. 15A, FIG. 15B, and FIG. 15C respectively show a modified example for the distribution of amount of light FIG. 12;

FIG. 16A shows the distribution of amount of light to be set by the diffractive optical element 22 B of FIG. 1A on the exit plane (pupil plane) of the fly' eye lens 5, and FIG. 16B shows a modified example of the distribution of amount of light of FIG. 16A;

FIG. 17 shows an evaluating result of depth of focus (DOF) through simulation of the transferred image when exposure is made with the distribution of amount of light of FIG. 16A;



## 13

FIG. 18 shows a composition of a projection exposure apparatus of the third embodiment according to the present invention;

FIG. 19 shows a pattern of the aperture stop 42 of FIG. 18;

FIG. 20 shows a pattern of the aperture stop corresponding to the distribution of amount of light of FIG. 6;

FIG. 21 shows a pattern of the aperture stop corresponding to the distribution of amount of light of FIG. 7A;

FIG. 22A and FIG. 22B respectively show a pattern of the aperture stop 42 A and 42 B of FIG. 18;

FIG. 23 shows a main part of the illumination system of the fifth embodiment according to the present invention; and

FIG. 24 shows an example of the process for fabricating the semiconductor device using the projection exposure apparatus of the embodiment according to the present invention.

### BEST MODE FOR CARRYING OUT OF THE INVENTION

#### The First Embodiment

A preferably first embodiment will be described accompanying FIGS. 1 to 9, as follows:

This embodiment applies the present invention when doing exposure with the projection exposure apparatus using an illumination system which has a fly' eye lens as an optical integrator (uniformizer or homogenizer).

FIG. 1A shows a composition of the projection exposure apparatus of this embodiment, in FIG. 1A, a KrF excimer laser light source (wave-length 248 nm) is used as an exposure light source 1. In addition, the laser light sources such as an ArF excimer laser light source (wave-length 193 nm), a F<sub>2</sub> laser light source (wave-length 157 nm), a Fr<sub>2</sub> laser light source (wave-length 146 nm), or an Ar<sub>2</sub> laser light source (wave-length 126 nm); or high frequency generating apparatus such as a high frequency generating light source of a YAGI laser or a solid laser (for example semiconductor laser etc.) can be used as an exposure light source 1.

An illumination light IL comprised of ultraviolet pulse light as an optical beam for exposure (exposure beam) emitted from exposure light source 1 goes into the first diffractive optical element 21 through an optical path folding miller 3, after changing the cross-sectional shape of the optical beam into the desirable shape with beam expander 2, and is changed the optical beam DL which diffracts to the plural directions in order to be obtained a predetermined distribution of amount of light at a predetermined plane (for example pupil plane of the illumination system) as described after. The diffractive optical element 21 as a part of the optical member for setting distribution of amount of light is mounted to a revolver 24, the second diffractive optical element 22 having other diffractive characteristic and further, diffractive optical element (not shown) having another diffractive characteristic are also mounted. In this embodiment, a main control system 17 controlling over the all operation of the apparatus controls the revolving angle of the revolver 24 through a driver 23, by setting one of the diffractive optical element 21 and 22 etc. on the optical path of the illumination light IL, can change the condition of illumination.

In FIG. 1A, the optical beam DL diffracted by the diffractive optical element 21 is gathered by a relay lens 4, is gathered on an incident plane of the fly' eye lens as an optical integrator, through a first prism 71 and a second prism 72 (movable prism). In this case, the diffractive optical element 21 is arranged at a position slightly deviated from a front focus of the relay lens 4 to the exposure light source 1 than, and the incident plane of fly' eye lens 5 is approximately

## 14

arranged at the position of the back focus of the relay lens 4. Furthermore, a plurality of optical beams diffracted to the different directions are respectively gathered at the different areas on the incident plane of the fly' eye lens 5, a plane light source (2-dimensional light source comprised of many light source images in this embodiment) of distribution approximately corresponding to the amount of light of the incident plane is formed. With a combined lens system comprised of the relay lens 4 and fly' eye lens 5, the exit plane of the diffractive optical element 21 and the exit plane Q1 of the fly' eye lens 5 have approximately be conjugate (imaging relation).

In this embodiment, the diffractive optical element 21, the first prism 71, and the second prism 72 are corresponding to an optical member for setting a predetermined distribution of amount of light. As shown in FIG. 1B, the first prism 71 is a member which forms a parallel flat plate 71 at circular area of which the center is an optical axis BX (discuss later) of a illumination system, and forms a concave cone 71 b around the circular area; the second prism 72 is a member which forms inverted concave and convex for the first prism 71, and forms a parallel flat plate as a whole by combining with the first prism 71. In addition, an optical beam passing the circular area of the center of the first prism 71 and the second prism 72 (that is the optical beam traveling in a straight line along the optical axis BX within the first prism 71 and the second prism 72) distributes to areas which are a center of a distribution of amount of light on the exit plane Q1 on the fly' eye lens 5 in which amount of light is enhanced; an optical beam passing the cone part (slope plane) around the first prism 71 and the second prism 72 distributes to a plurality of areas (or a predetermined area including the plurality of areas) in which amount of light is enhanced around the distribution of amount of light.

Further, at least one of the first prism 71 and the second prism 72, for example in this embodiment, the second prism 72 is only supported movably by a driving mechanism (not shown), thus by changing the distance between the first prism 71 and the second prism 72 by moving the second prism 72 along the optical axis BX, the position of a plurality of peripheral areas in which the amount of light is great can adjust to the radial direction, without changing the central distribution (position of areas 28, 33 etc. described below) of the distribution of amount of light at the exit plane Q1 on the fly' eye lens 5.

In addition, a prism having not a cone but a pyramid may be used instead of the first prism 71 and the second prism 72. Furthermore, it is allow moving this position along the optical axis BX by only using the first prism 71 instead of the first prism 71 and the second prism 72. Further, as shown in FIG. 1C, it is allow using a pair of prisms 71A, 71B shaped like a letter V which has diffractive power to one direction and has not diffractive power to orthogonal direction, as the movable prism. In addition, the prisms 71A, 71B are arranged so that each rectangle area (in this embodiment, the parallel flat plate) of its center is approximately orthogonal to the optical axis BX and two slope planes of the around area are approximately symmetric with respect to a plane being orthogonal to the paper of FIG. 1C including the optical axis BX.

With this composition, by changing the distance between the prisms 71A, 71B, positions (distance from the optical axis BX) of a peripheral area, in which amount of light is great, concerning the above and below direction of the paper in FIG. 1C (e.g., corresponding to a Y direction in FIG. 3 showing a distribution of amount of light of an illumination light at a pupil plane of an illumination system 12) changes. Therefore, in order to adjust positions (distance from the optical axis BX)



of a peripheral area, in which amount of light is great, concerning the orthogonal direction to that position (the orthogonal direction to the paper in FIG. 1C, corresponding to an X direction in FIG. 3), another pair of prisms 71C, 71D constructed by revolving the pair of prisms 71A, 71B by 90 degrees about the optical axis BX may be arranged. Whereby, it is able to independently adjust each position (distance from the optical axis BX) being orthogonal each other in which amount of light is great.

In addition, however the prism described above whose slope plane is the cone, pyramid, or shaped like a letter V the center flat plate is the parallel flat plate, it may be aperture part (hollow part) by cutting at least one part of the center part, or may be an integral solid by making a plurality of members independently. In particular, the latter may be an integral solid by only dividing the peripheral slope plate except the center flat plate part into a plurality of parts.

In FIG. 1A, however if it is not necessary to change the position of peripheral area in which the amount of light is great to the radial direction, the first prism 71 and the second prism 72 can be omitted.

In addition, the fly' eye lens 5 is, as an example, a bundle of many lens elements each of which has a rectangular cross-section whose vertical and horizontal width is about a few of millimeter, the shape cross-section of each lens element is approximately similar to a slim piece of illumination area on a reticle. However, a micro fly' eye lens constructed by binding many micro lenses whose shape cross-section is rectangular with about a few tens of micrometer or circular with diameter of about a few tens of micrometer can be used.

The illumination light IL comprises optical beam emitted from the fly' eye lens 5 is onetime gathered on the plane Q2 by a condenser lens system 6. A fixed field stop (fixed blind) 7 for limiting an illumination area on a reticle R as an illuminated target to a slim shape orthogonal to scan direction, i.e., not-scan direction is arranged at slight front side of the plane Q2, a movable field stop (movable blind) 8 on the plane Q2. The movable field stop is used to prevent from useless exposure by controlling the width of the scan direction of the illumination area at the front and back of the scan exposure, and to limit the width of the not-scan direction of the illumination area during the scan exposure. As an example, a reticle stage driving system 16 described below controls open/close operation of the movable field stop 8 through a driving section 13 in sync with operation of the reticle stage.

The illumination light IL passing through the field stop 7 and 8, via a imaging-lens system 9, optical path folding miller 10, and main condenser lens system 11, illuminates a slim illumination area on a circuit pattern area of a pattern plane (it will be called "reticle plane" hereinafter) of the reticle R as a mask with even intensity distribution. An illumination system 12 is composed of the exposure light source 1, a beam expander 2, the miller 3, the diffractive optical element 21 (or other diffractive optical element), the relay lens 4, fly' eye lens 5, the condenser lens system 6, field stop 7, 8, the imaging-lens system 9, the miller 10, and the main condenser lens system 11. An optical axis of the illumination system 12 is regarded as the optical axis BX. In this case, the exit plane Q1 of the fly' eye lens 5 is substantially coincident to an optical Fourier transform plane for the pupil plane of the illumination system 12, i.e., reticle: the plane Q2 in which the movable field stop 8 is arranged is a conjugate plane with the reticle plane. In addition, the fixed field stop 7, for example, may be arranged near the reticle plane.

Under the illumination light IL, the imaging-circuit patterns within illumination area of the reticle R, via a projection optical system PL of both side telecentrics as a projection

system, transfers a resist layer of one shot area among a plurality of shot areas on a wafer W as a substrate arranged on an image-forming plane of the projection optical system PL with a predetermined downsizing magnification  $\beta$  (for example,  $\beta$  is  $1/4$ ,  $1/5$  etc.). In addition, the reticle R and wafer W is respectively regarded as a first object and second object. Furthermore, the wafer W as substrate for exposure is a circular substrate such as semiconductor (silicon etc.) or SOI (silicon on insulator) whose diameter is 200 or 300 mm, for example.

An optical axis AX of the projection optical system PL is coincident to an optical axis BX of the illumination system on the reticle R. Furthermore, a pupil plane Q3 (optical Fourier transform plane for the reticle plane) on the projection optical system PL is conjugate with the exit plane Q1 (the pupil plane of the illumination system 12) of the fly' eye lens 5. As the projection optical system PL of this embodiment, other one except the diffractive system can be used, for example, a catadioptric projection optical system having a plurality of optical systems having optical cross-axes each other as disclosed in Japanese Patent Application: TOKUKAI 2000-47114 (corresponding to U.S. Pat. No. 6,496,306) or, for example, a catadioptric projection optical system and the like which has an optical system including an optical axis intends from a reticle to a wafer and a catadioptric optical system including an optical axis being approximately orthogonal to that optical axis, and which forms an intermediate image twice in its interior as disclosed in international publication (WO): 01/065296 brochure (corresponding to US publication 2003/0011755A1). It will be described the projection optical system PL, with considering that a Z axis is paralleled to the optical axis AX, a X axis is not-scan direction (the direction parallel to the paper in FIG. 1A, in this case) orthogonal to the scan direction, and a Y axis is the scan direction (the direction orthogonal to the paper in FIG. 1A, in this case), as follows:

First, the reticle R is adsorbed and held on the reticle stage 14; the reticle stage 14 is mounted so as to move with a constant velocity along the Y direction on a reticle base 15, and to slightly move along rotating directions about the X, Y, and Z axis. The position of the reticle stage 14 is measured by a laser interferometer in a reticle driving system 16. The reticle driving system 16 controls the position and velocity of the reticle stage 14 through driving mechanism not shown, based on the measured information and control information from a main control system 17.

On the other hand, the wafer W is adsorbed and held on a wafer stage 18 through wafer holder not shown; the wafer stage 18 is movably mounted in the X and Y directions on a wafer base 19. The position of the wafer stage 18 is measured by a laser interferometer in a wafer driving system 20. The wafer driving system 20 controls the position and velocity of the wafer stage 18 through driving mechanism not shown, based on the measured information and control information from the main control system 17. Furthermore, a focusing mechanism for fitting the surface of the wafer into the image-forming plane of the projection optical system PL is assembled in the wafer stage 18 during the scan exposure, based on measured information of an auto-focus sensor not shown.

During scan exposure, under controlling of the main control system 17, the reticle driving system 16, and the wafer driving system 20, operation of scanning one shot area on the wafer W to a corresponding direction (+Y or -Y direction) for the slim exposure area (the illumination area of the illumination light IL being conjugated with the illumination area concerning projection optical system PL) with velocity  $\beta \cdot VR$  ( $\beta$  is projection magnification) through the wafer stage 18,



and operation of step-moving the wafer W to the X, Y directions through the wafer stage 18 are repeated, in sync with scanning the reticle R to the Y direction for the illumination area illuminated illumination light with velocity VR through reticle stage 14.

Next, an illumination system and an illumination method will be described in detail.

FIG. 2 shows an example of a pattern (original pattern) for transferring formed on a reticle R; in FIG. 2, a 2-dimensional pattern with three kinds of contact holes arranging pattern 25A, 25B, and 25C of approximate squares with pitch P1, P2, and P3 at the X, Y directions in a pattern region PA of the reticle R. Each pattern 25A, 25B, and 25C may be a transmission pattern formed in a light shielded film, or may conversely be a light shielded pattern formed in a transmission part. Furthermore, the width of each pattern 25A, 25B, and 25C is around equal to 1/2 or smaller than corresponding pitch P1, P2, and P3 respectively, however, the width of pattern 25B, 25C with larger pitch can be around equal to pattern 25A with most fine pitch. In this case, the pitch P1, P2, and P3 are set to gradually become several-fold, as follows:

$$P1 < P2 < P3 \quad (4)$$

If the projection magnification  $\beta$  of the projection optical system PL in FIG. 1A is 1/4-fold, pitch P1, P2, and P3 on the reticle plane are respectively set, as an example, around 300 nm, 600 nm, and 900 nm. That is, the original patterns on the reticle plane include a first pattern for dense contact holes with fine pitch, a second pattern for dense contact holes with around middle pitch, and a third pattern for contact holes arranged with large pitch substantially regarding as the isolated contact holes. In order to transfer an image of these original patterns on wafer onetime with high accuracy, as shown FIG. 1A in this embodiment, with arranging the diffractive optical element 21 on the optical path of an illumination light IL, the distribution of amount of light (strength distribution) of the illumination light IL at the exit plane Q1 (pupil plane) of the fly' eye lens 5 as a predetermined plane.

FIG. 3 shows the distribution of amount of light of the illumination light IL at the exit plane Q1 (pupil plane of the illumination system) of the fly' eye lens 5. In this FIG. 3, the direction on the exit plane Q1 corresponding to the X direction and Y direction (i.e., the arranging direction of the pattern to transfer) on the reticle R is respectively defined the X direction and Y direction. Here, if the numerical aperture of the object side (reticle side) of the projection optical system PL in FIG. 1A is NA, the numerical aperture of the image side (wafer side) is  $NA_{PL}$ , a relation is obtained with using the projection magnification  $\beta$ , as follows:

$$NA = \beta \cdot NA_{PL} \quad (5)$$

Further, it is defined that the maximum value among the numerical apertures of the illumination light IL incident to the reticle R from the illumination system 12 is  $NA_{IL}$ , the value of ratio (coherence factor) of the maximum numerical aperture  $NA_{IL}$  to the numerical aperture NA of the projection optical system PL is called maximum  $\sigma$  value in this embodiment, and maximum  $\sigma$  value is  $\sigma$ . That is, the illumination light of maximum  $\sigma$  value is the light incident on the reticle R with the maximum angle among the illumination light IL. The maximum  $\sigma$  value ( $\sigma$ ) can be expressed, as follows:

$$\sigma = NA_{IL} / NA = NA_{IL} / (\beta \cdot NA_{PL}) \quad (6)$$

In a pupil plane of an illumination system shown in FIG. 3, a maximum outer circle 26 indicates an outer area passed through virtual optical beam having the same numerical aperture as the numerical aperture NA at the incident side of the

projection optical system PL, an inner circle 27 indicates a circle is tangent to areas passed through illumination light having numerical aperture of the maximum  $\sigma$  value ( $\sigma$ ); all illumination light pass through within the circle 27. The illumination light IL of this embodiment, in FIG. 3, approximately has a constant amount of light at nine areas with distance each other which include a circular area 28 with radius r1 centered an optical axis BX of the illumination system 12, four circular areas 29A, 29B, 29C, and 29D with radius r2 whose centers are arranged along a first circle 32A with radius R1 enclosing the area 28, and four circular areas 30A, 30B, 30C, and 30D with radius r3 whose centers are arranged along a second circle 32B with radius R2 enclosing the areas 29A to 29D, and has distribution of amount of light of lower amount of light (approximate 0 in this embodiment) at other areas than the constant amount of light. In addition, the amount of light, near the outline of the area 28, areas 29A to 29D, and areas 30A to 30D, may have distributions which gradually decrease toward the outside. The center area 28 corresponds to a first area; the four areas 29A to 29D enclosing the area 28 correspond to second areas; further the four areas 30A to 30D enclosing the areas 29A to 29D correspond to third areas. Hereinafter, the radii r1 to r3 and R1, R2 respectively indicates the length (distance between point passed through the optical beam of the maximum  $\sigma$  value and the optical axis BX) corresponding the maximum  $\sigma$  value ( $\sigma$ ) as unit.

First, the center area 28 is set larger than other eight areas 29A to 29D and 30A to 30D ( $r1 > r2 > r3$ ). Further, since the arranging directions of the 2-dimensional patterns as the targets to transfer are the X direction and Y direction, it is defined that a straight line crossed to the X direction by 45 degrees in clock winding is a straight line 31A; a straight line (the straight line crossed to the X direction by 45 degrees in counter clock winding) is a straight line 31B. Furthermore, the center of the center area 28, the middle two areas 29A and 29C, and other most outer two areas 30A and 30C is arranged on the first straight line 31A; the center of the center area 28, the middle other two areas 29B and 29D, and other most outer two areas 30B and 30D is arranged on the second straight line 31B. That is, the eight areas 29A to 29D and 30A to 30D enclosing the center area 28 are arranged along the two directions being orthogonal with revolving the two arranging directions by 45 degrees, which are orthogonal, in which patterns as the targets for transfer.

Further, as an example, the radius r1 of the area 28, the radii r2 of the areas 29A to 29D, and the radii r3 of the areas 30A to 30D are set 0.3-fold, 0.1-fold, and 0.1-fold of the maximum  $\sigma$  value ( $\sigma$ ) (the radius of circle 27, after being similar to this), as follows:

$$r1 = 0.3\sigma \quad (7)$$

$$r2 = r3 = 0.1\sigma \quad (8)$$

Further, the radius R1 of the first circle 32A and the radius R2 of the second circle 32B are set 0.55-fold and 0.9-fold of the maximum  $\sigma$  value ( $\sigma$ ), as follows:

$$R1 = 0.55\sigma \quad (9)$$

$$R2 = 0.9\sigma \quad (10)$$

In this case, the radial distance d1 between the outer of the area 28 and the first circle 32A, and the radial distance d2 between the first circle 32A and the second circle 32B are as follows:

$$d1 = 0.25\sigma, d2 = 0.35\sigma \quad (11)$$



In this case, the diffractive characteristic of the diffractive optical element **21** in FIG. 1A is set, so as to obtain the distribution of amount of light in which the amount of light approximately becomes constant at the area **28**, the areas **29A** to **29D**, and the areas **30A** to **30D** in FIG. 3 satisfying the condition of the equations (7) to (10): approximately becomes 0 at other areas. For the reason, the diffractive optical element **21**, as an example, can fabricate by forming a concave and convex grating having approximately systematically along in the direction of the straight line **31A**, and a concave and convex grating having approximately systematically along in the direction of the straight line **31B** of FIG. 3. Alternatively, the diffractive optical element **21** may be a combination of a plurality of phase type diffractive gratings. In these cases, since the diffractive optical element **21** is phase type, it is advantage of high efficiency for using light. In addition, it is able to use an optical element changing refractive index distribution corresponding to a diffractive grating distribution as an optical element **21**. In addition, a construction and a method for fabricating having a specific diffractive characteristic is closely disclosed, for example, in Japanese Patent Application: TOKUKAI 2001-176766 (corresponding to U.S. Pat. No. 6,563,576) by this applicant.

In addition, with setting the distribution of amount of light obtained by the diffractive optical element **21** to around constant amount of light at the areas including the area **28**, the areas **29A** to **29D**, and the areas **30A** to **30D** in FIG. 3, the aperture stop, whose aperture is formed at the part corresponding to the area **28**, the areas **29A** to **29D**, and the areas **30A** to **30D** in FIG. 3, may be arranged at the exit plane **Q1** (pupil plane) of the fly' eye lens **5** or its conjugate plane. Also in this case, it is advantage of high efficiency for using the illumination light **IL**.

For this embodiment, this inventor have evaluated the CD (critical dimension), through the simulation of the computer, which is obtained by transferring a downsizing image of pattern of contact holes with various kinds of pith arranged on the reticle plane to the wafer through the projection optical system **PL**, under the distribution of amount of light in which the amount of light becomes constant at the nine areas comprising the area **28**, the areas **29A** to **29D**, and the areas **30A** to **30D** in FIG. 3 satisfying the condition of the equations (7) to (10): becomes 0 at the other areas. The CD used is the line width of patterns transferred. In addition, as this simulation, the numerical aperture  $NA_{PL}$  of the image side (wafer side) of the projection optical system **PL** in FIG. 1A is 0.82, projection magnification  $\beta$  is 1/4-fold, and the maximum  $\sigma$  value ( $\sigma$ ) is 0.9, as follows:

$$NA=0.82, \beta=1/4, \sigma=0.9 \quad (12)$$

The curve **36** in FIG. 5 shows the simulation result of the CD value in case that the amount of light becomes constant at the nine areas on the pupil plane, the horizontal axis is the pitch (nm) of the pattern transferred on the reticle plane, vertical axis is the CD value (nm) in FIG. 5. The pitch 280 to 1120 nm is equivalent of 70 to 280 nm at the wafer side. As shown in the curve **36**, with using the distribution of amount of light in this embodiment, the preferable CD value having approximately constant across the wide range of pitch 280 to 1120 nm.

Accordingly, with using the distribution of amount of light on the pupil plane in FIG. 3 in this embodiment, the patterns of the reticle **R** including three kinds of pitch in FIG. 2 can onetime transfer on the wafer with high accuracy.

In addition, the distribution of amount of light on the pupil plane in FIG. 3 is not satisfied the condition of the equations

(7) to (10), the radius  $r1$  of the area **28**, the radii  $r2$  of the areas **29A** to **29D**, and the radii  $r3$  of the areas **30A** to **30D** may be the ranges, as follows:

$$0.2\sigma \leq r1 \leq 0.46 \quad (13)$$

$$0.075\sigma \leq r2 \leq 0.26 \quad (14)$$

$$0.075\sigma \leq r3 \leq 0.26 \quad (15)$$

Further, the radius **R1** of the first circle **32A** and the radius **R2** of the second circle **32B** may be changed up to around  $\pm 10\%$  of the equations (9) and (10). Furthermore, the numerical aperture  $NA_{PL}$  of the image side, the projection magnification  $\beta$ , and the maximum  $\sigma$  value ( $\sigma$ ) in the projection optical system **PL** can be taken any values though the values described above. For example, in order to control the maximum  $\sigma$  value ( $\sigma$ ), by changing the distance between prism **71** and **72** in FIG. 1A, the radial position of the areas **29A** to **29D**, and the areas **30A** to **30D** with peripheral area in which the amount of light is great among the distribution of amount of light in FIG. 3 (the distance from the optical axis **BX** relating to the X direction and Y direction) may only be changed. Alternatively, as shown in FIG. 1C, by using two pairs of prism **71A**, **71B** and **71C**, **71D**, the position of the areas **29A** to **29D**, and the areas **30A** to **30D** with peripheral area in which the amount of light is great among the distribution of amount of light in FIG. 3 (the distance from the optical axis **BX**) in the X direction and Y direction may independently controlled.

In addition, about the distribution of amount of light in FIG. 3, the amount of light of the center area **28** (e.g., intensity per unit size) and that of the areas **29A** to **29D**, and the areas **30A** to **30D** may be different. Furthermore, the amount of light of the four areas **29A** to **29D** along the peripheral first circle **32A** and that of the four areas **30A** to **30D** along the peripheral second circle **32B** may be different. The relative amount of these lights may be adjusted so that the optimum resolution is obtained for each pattern, for example.

Further, instead of the distribution of amount of light in FIG. 3, as shown FIG. 6B, a distribution of amount of light becoming great amount of light of the five areas including four slim areas **130A**, **130B**, **130C**, and **130D** which are substantially connected to the radial each two areas **29A**, **29B**, **29C**, **29D**, **30A**, **30B**, **30C**, and **30D** of the radial in FIG. 3 respectively and the center area **28** may be used. Also in this case, it is almost able to transfer patterns having various kinds of pitch with high resolution. In addition, in FIG. 6B, the amount of light of the connecting parts of two areas in the radial may around equal to that of the two areas, or may be different from that of the two areas, for example smaller.

In addition, in order to more improve the resolution and depth of focus than using the amount of light of FIG. 3, an area of annular may be used instead of the center area **28** as the first area.

FIG. 6(A) shows a distribution of amount of light of the illumination light **IL** on the exit plane **Q1** (pupil plane of the illumination system **12**) of fly' eye lens **5** in FIG. 1(A), when the first area is the area of annular. In FIG. 6(A) with marking the same notes to the parts corresponding to in FIG. 3, the amount of light of the area **28R** of annular consist of the outer radius  $r1$ , the inner radius  $r1R$ , and the center of the optical axis **BX** and that of the nine areas including the area **28**, the areas **29A** to **29D**, and the areas **30A** to **30D** are approximately constant; and amount of light of the illumination light at the other areas is approximately 0. Furthermore, the value of ratio of the outer radius  $r1$  and inner radius  $r1R$  ( $=r1R/r1$ ) of the annular zone area **28R** is any value between 0 and 1, as



## 21

an example,  $\frac{1}{3}$  annular ( $r1R/r1=\frac{1}{3}$ ),  $\frac{1}{2}$  annular ( $r1R/r1=\frac{1}{2}$ ),  $\frac{2}{3}$  annular ( $r1R/r1=\frac{2}{3}$ ) etc. can be used. The condition other than it is the same as that of the case where the amount of light in FIG. 3 is used.

When the amount of light in FIG. 6A is used, the more stable distribution of CD value can be obtained than the simulation result of the CD value represented in the curve 36 of FIG. 5. Further, the more stable CD value can be obtained with wider depth of focus.

Further, in this embodiment, the light distributed at the peripheral areas 29A to 29D, and the areas 30A to 30D in FIG. 6A may be linear polarization. In this case, as an example, as shown with an arrow mark AR, the light distributed at the peripheral areas may be S polarization (vertical direction for the incident plane) whose polarization direction is the tangent direction. Whereby, the resolution etc. for the specific pattern might be enhanced. It is the similar to the case of using the distribution of amount of light in FIG. 3 or 6B.

In addition, if the light distributed at the peripheral eight or four areas with area in which the amount of light is great described above is non-polarization or whose polarization direction is not coincidental to the circumference direction, for example, with arrangement polarization setting member such as  $\frac{1}{2}$  wave plate or  $\frac{1}{4}$  wave plate on the optical path passed through the lights distributed at each area between diffractive optical element 21 (deflection member) and the fly' eye lens 5, the optical beam is preferably changed into that of the linear polarization whose polarization direction is approximately coincident to the circumference direction. In this case, the polarization setting member is preferably arranged between one of the plurality of prisms (movable member) described above which is arranged at the most upstream side (light source side) and incident side, for example the lens 4, or the diffractive optical element 21 and the lens 4. In this case, it is not necessary to move the polarization setting member in accordance with change of the diffractive optical element or the traveling direction of the optical beam (optical path) depending on modification of the distance among the plurality of prisms; or not necessary to enlarge the polarization setting member in expectation of such change.

In addition, in the distribution of amount of light in FIG. 6B, the center circular area 28 may be the area of the annular similar to FIG. 6A.

Further, the diffractive optical element 21 in this embodiment, however, sets the distribution of amount of light on the pupil plane of the illumination system 12 as a predetermined plane to a predetermined state; the predetermined plane may be the pupil plane Q3 of the projection optical system PL. In this case, if the reticle R is not in existence due to the diffractive optical element 21, the distribution of amount of light is set which is approximately constant at the first area including the axis AX and the eight areas enclosing it, and which is lower at the other areas.

In addition, in the examples of FIG. 3 and FIG. 6A of this embodiment, the area 28 (or 28R), each of the areas 29A to 29D, and the areas 30A to 30D, in which amount of light is approximately constant on the pupil plane, is the circular (or annular) however, each circular (or annular) can be an area of ellipse (ellipse annular). Furthermore, as described bellow, the area of circular (or annular) can be an area of polygon (or frame shape of polygon), or can be combination of the area of circular (or annular) and the area of polygon.

FIG. 9 shows possible another distribution of amount of light on the pupil plane, as shown FIG. 9, the distribution of amount of light is approximately constant at the center square (right square or right hexagon etc. is possible) area 28A, four

## 22

square areas 30E to 30H enclosing it, and lower than it at the other areas. In this case, the positions and sizes of the areas may be respectively similar to those of the area 28, areas 29A to 29D, and the areas 30A to 30D. In addition, if corresponding to FIG. 6A, an area of frame type may be used instead of the center area 28A in FIG. 9.

Next, a second diffractive optical element 22 having different diffractive characteristic is provided to the revolver 24 in FIG. 1A. With setting the second diffractive optical element 22 on the optical path of the illumination light IL, distribution of amount of light which is approximate constant amount of light at the five areas of the exit plane Q1 (pupil plane) of the fly-eye lens 5, and the lower (approximate 0 in this embodiment) than it at the other area is obtained.

FIG. 7A shows a distribution of amount of light of the illumination light IL on the exit plane Q1 (pupil plane) of fly-eye lens 5 in FIG. 1A, when the second diffractive optical element 22 is used. In FIG. 7A with marking the same notes to the parts corresponding to in FIG. 3, the distribution of amount of light at five areas with distance each other including an area 33R (first area) of circular annular consist of the outer radius r1, the inner radius r1R, and the center of the optical axis BX of the illumination system 12, and four circular areas 34A, 34B, 35C, and 35D (second area) arranging along the a circle 35 having radius R3 with radius r5 and 90 degrees distance enclosing the area 33R is approximately constant; and is smaller (approximate 0 in this embodiment) than the constant amount of light. In this case also, the outer outline of the center area 33R is set larger than that of other four areas 34A to 34D ( $r4>r5$ ).

Further, the value of ratio of the outer radius r4 and inner radius r4R ( $=r4R/r4$ ) of the annular zone area 33R is any value between 0 and 1, as an example,  $\frac{1}{3}$  annular ( $r4R/r4=\frac{1}{3}$ ),  $\frac{1}{2}$  annular ( $r4R/r4=\frac{1}{2}$ ),  $\frac{2}{3}$  annular ( $r4R/r4=\frac{2}{3}$ ) etc. can be used. Further, the preferable range of the radius r4 is similar to that of the radius r1 of the equation (13), and the preferable range of the radius R3 and radius r5 are similar to that of the radius R2 of the equation (10) and radius r2 of the equation (14) respectively.

Further, in this example, since the arranging direction of the 2-dimensional pattern is the X direction and Y direction, the outer four areas 34A to 34D are respectively arranged along the straight lines pass through the optical axis BX and cross by 45 degrees in the X direction (or Y direction).

Further, as an example, the radius r4 of the area 33R, the radius r5 of the areas 34A to 34D, and the radius R3 of the circle 35 are respectively set 0.2-fold, 0.1-fold, and 0.9-fold of the maximum  $\sigma$  value ( $\sigma$ ), as follows:

$$r4=0.3\sigma, r5=0.1\sigma \quad (16)$$

$$R3=0.9\sigma \quad (17)$$

This inventor has evaluated the CD (critical dimension), through the simulation of the computer, which is obtained by transferring a downsizing image of pattern of contact holes with various kinds of pith arranged on the reticle plane to the wafer through the projection optical system PL, under the distribution of amount of light in which the amount of light becomes constant at the five areas comprising the area 33, and the areas 34A to 34D in FIG. 4 satisfying the condition of the equations (16) and (17); becomes 0 at the areas in addition thereto. In addition, as this simulation, the exposure wave length is ArF laser light, the numerical aperture  $NA_{PL}$  of the image side (wafer side) of the projection optical system PL in FIG. 1A is 0.78, projection magnification  $\beta$  is  $\frac{1}{4}$ -fold, and the maximum  $\sigma$  value ( $\sigma$ ) is 0.9.



The curves of line graph F1, F2 in FIG. 8 show the simulation result of the CD value in case that the amount of light becomes constant at the five areas on the pupil plane, the horizontal axis is the defocus amount of wafer ( $\mu\text{m}$ ), vertical axis is the line width ( $\mu\text{m}$ ) (line width on wafer) of the pattern well transferred as the CD value. Furthermore, approximate flat curve F1 indicates simulation result for the pattern of contact holes with line width 140 nm, pitch 220; mountain-shaped curve F2 indicates simulation result for the isolated pattern with line width 140 nm. As shown F1, F2, approximately constant CD value with range in which the defocus amount is around  $-0.2\ \mu\text{m}$  to  $0.2\ \mu\text{m}$  is obtained. Accordingly, various kinds of pattern from the isolated pattern to the pattern with fine contact holes with high accuracy and wide depth of focus.

In addition, when the distribution of amount of light in FIG. 7A is used, for example, in order to control the maximum  $\sigma$  value ( $\sigma$ ), by changing the distance between prisms 71 and 72 in FIG. 1A, the radial position (distance from the optical axis BX relating to the X direction and Y direction) of the areas 34A to 34D in which the amount of light is great in FIG. 7A may be changed. Alternatively, as shown in FIG. 1C, by using two pairs of prism 71A, 71B and 71C, 71D, the position (distance from the optical axis BX) of the areas 34A to 34D with peripheral area in which the amount of light is great among the distribution of amount of light in FIG. 7A in the X direction and Y direction may independently controlled.

Further, about the distribution of amount of light in FIG. 7A, it can be set the amount of light of the center area 33R (e.g., intensity per unit size) and that of the peripheral four areas 34A to 34D differ. The relative amount of these lights may be adjusted so as to be obtained the optimum resolution at each pattern for example.

Further, instead of the distribution of amount of light in FIG. 7A, as shown FIG. 7B, a distribution of amount of light becoming great amount of light of the area 134 which is a starfish shape having an aperture at the center or a star shape substantially connected the four areas 34A to 34D and the center annular zone area 33R in the radial direction may be used. The amount of light of the central part of the area 134 may be not 0 only smaller. Also in this case, it is almost able to transfer patterns having various kinds of pitch with high resolution.

In addition, when, in FIG. 7A, the peripheral areas 34A to 34D and the center area 33R are connected in FIG. 7B, the amount of light of the connected part getting longer to radial direction may be around equal to those of the peripheral and center areas, or may be different from those, for example smaller than those.

Further, in this example, the light distributed at the peripheral areas 34A to 34D in FIG. 7A may be linear polarization. In this case, as an example, as shown with an arrow mark AR, the light distributed at the peripheral areas may be S polarization (vertical direction for the incident plane) whose polarization direction is the tangent direction. Whereby, the resolution etc. for the specific pattern might be enhanced. It is similar to the case of using the distribution of amount of light in FIG. 7B. The light distributing the peripheral area getting longer to the radial direction, particularly its part corresponding to the peripheral areas 34A to 34D in FIG. 7A may be the linear polarization whose polarization becomes the tangent direction. In addition, if the light distributed at the peripheral areas is non-polarization or whose polarization direction is not coincidental to the circumference direction, as described above, for example, it is preferable to provide polarization setting member between the diffractive optical element 21 and the fly-eye lens 5.

In order to compare, the simulation result in which the amount of light is set constant at a circular area instead of the center annular zone area 33R in FIG. 7A is represented.

FIG. 4 shows the distribution of amount of light in which the amount of light is set constant at a circular area 33 instead of the center annular zone area 33R in FIG. 7A, and the amount of light is set constant at four areas 34A to 34D enclosing it as with FIG. 7A.

In FIG. 4, as an example, the radius  $r_4$  of the area 33, the radii  $r_5$  of the areas 34A to 34D, and the radius  $R_3$  of the circle 35 are respectively set 0.2-fold, 0.1-fold, and 0.9-fold of the maximum  $\sigma$  value ( $\sigma$ ), as follows:

$$r_4=0.2\sigma, r_5=0.1 \quad (18)$$

$$R_3=0.9\sigma \quad (19)$$

This inventor have evaluated the CD (critical dimension), through the simulation of the computer, which is obtained by transferring a downsizing image of pattern of contact holes with various kinds of pith arranged on the reticle plane to the wafer through the projection optical system PL, under the distribution of amount of light in which the amount of light becomes constant at the five areas comprising the area 33, and the areas 34A to 34D in FIG. 4 satisfying the condition of the equations (18) and (19): becomes 0 at the other areas. In addition, as this simulation, the values of the numerical aperture  $NA_{PL}$  of the image side (wafer side) of the projection optical system PL in FIG. 1A, projection magnification  $\beta$ , and the maximum  $\sigma$  value ( $\sigma$ ) are similar to the equation (12) in the FIG. 3.

The dotted line curve 37 in FIG. 5 shows the simulation result of CD value in which the amount of light becomes constant at the five areas of this pupil plane, as shown in the curve 37; the CD value is low around pitch 500 to 700 nm.

Accordingly, it is understand that the case using the distribution of amount of light in which the amount of light becomes approximately constant at the nine areas on the pupil plane in FIG. 3 can transfer the pattern across wider pitch range with high resolution than the case of using the distribution of amount of light in which the amount of light becomes approximately constant at the five areas in FIG. 4.

#### The Second Embodiment

Next, the second embodiment according to the present invention will be described accompanying FIG. 10 to FIG. 17. Also in this embodiment, the exposure is fundamentally performed by using the scan exposure type projection optical apparatus in FIG. 1A. In this embodiment, however, instead of the diffractive optical element 21 in FIG. 1A, a diffractive optical element 22A (described bellow in detail) having different characteristic is used. Accordingly, the diffractive optical element 22A, the first prism 71, and the second prism 72 are corresponding to an optical member for setting a predetermined distribution of amount of light. In this embodiment, as with the first embodiment, the prism 71, 72 (or the first prism 71 only) are used as movable prism.

Further, as shown FIG. 10, it is allow using a pair of prisms 71A, 71B shaped like a letter V which has diffractive power to one direction and has not diffractive power to orthogonal direction, as the movable prism. In addition, the prisms 71A, 71B are arranged so that each rectangle area (in this embodiment, the parallel flat plate) of its center is approximately orthogonal to the optical axis BX and two slope planes of the around area are approximately symmetric with respect to a plane being orthogonal to the paper of FIG. 1A including the optical axis BX.



With this constitution, by changing the distance between the prisms **71A**, **71B**, positions (distance from the optical axis BX) of a peripheral area in which the amount of light is great concerning above and below of within the paper in FIG. **10** (for example, corresponding to X direction in FIG. **12** described below in which a distribution of amount of light of an illumination light at a pupil plane of an illumination system **12**) changes.

Next, an illumination system and an illumination method will be described in detail. In this embodiment, a reticle RA is loaded on the reticle stage **14** instead of the reticle R in FIG. **1A**.

FIG. **11A** shows an example of a pattern (original pattern) for transferring formed on the reticle RA loaded on the reticle stage **14** in FIG. **1A**. In FIG. **11A**, a pattern **52** for the one directional high density pattern is formed, in which square aperture patterns **51** having width *a* in the X direction and width *b* in the Y direction, are periodically arranged in the X direction (non-scan direction in this embodiment) with pitch *P* at the pattern region PA. The pitch *P* is fine pitch (for example, around 150 nm length converted to projection image on wafer W) which is close to approximate limited resolution of the projection exposure apparatus in this embodiment, the width *a* of the X direction is around 1/2 of the pitch *P*, and the width *b* of the Y direction is around equal to the width *a* to 10-fold (around *a* to 10*a*). The pattern **52** is one directional high density pattern which can regard an isolated pattern about the Y direction (scan direction in this embodiment). In addition, though the pattern **52** is the periodical pattern arranging four aperture pattern **51** in X direction, the number of the aperture pattern **51** may be 2 or any than 2. Further, though the aperture pattern **51** is the transmission pattern formed in a light shielded film, a light shielded pattern provided in transmission part may be used instead of it.

Further, another pattern **53** for one directional high density pattern is also formed at a position distant from the pattern **52** in the Y direction, in which square aperture patterns **51** with pitch *Q* larger than the pitch *P*. The pattern **52** and **53** are actually small pattern whose length of X direction is a few μm or less, various kinds of other pattern (not shown) may be formed on the pattern region PA of the reticle RA. further, as shown in FIG. **11B**, when pattern **52A**, **52B**, and **52C**, in which aperture pattern **51** is arranged in the X direction with pitch *P* respectively, are formed with considerably larger pitch than pitch *P* in the Y direction, each of pattern **52A**, **52B**, and **52C** is regarded as one directional high density pattern, can be the target for transfer in this embodiment. In addition, the plurality of periodic pattern may only be arranged with the distance, so as to be isolated for orthogonal direction (Y direction) to the periodic direction, and their number may be arbitrary.

In order to transfer image of these original patterns on wafer with high accuracy, as shown FIG. **1A** in this embodiment, with arranging the diffractive optical element **22A** on the optical path of an illumination light IL, the distribution of amount of light (strength distribution) of the illumination light IL at the exit plane Q1 (pupil plane) of the fly-eye lens **5** as a predetermined plane.

FIG. **12** shows the distribution of amount of light of the illumination light IL at the exit plane Q1 (pupil plane of the illumination system **12**) of the fly-eye lens **5** in FIG. **1A** in this embodiment. In this FIG. **12**, the direction on the exit plane Q1 corresponding to the X direction (periodically arranging direction) and Y direction (regarding as isolated direction) on the reticle R is respectively defined the X direction and Y direction. Here, if the numerical aperture of the object side (reticle side) of the projection optical system PL in FIG. **1A** is

NA, the numerical aperture of the image side (wafer side) is  $NA_{PL}$ , a relation is obtained with using the projection magnification  $\beta$ , as follows:

$$NA = \beta \cdot NA_{PL} \quad (5) \text{ (as with the first embodiment)}$$

Further, it is defined that the maximum value among the numerical apertures of the illumination light IL incident to the reticle R from the illumination system **12** is  $NA_{IL}$ , the value of ratio (coherence factor) of the maximum numerical aperture  $NA_{IL}$  to the numerical aperture NA of the projection optical system PL is called maximum  $\sigma$  value in this embodiment, and maximum  $\sigma$  value is  $\sigma_{IL}$ . That is, the illumination light of maximum C value is the light incident on the reticle R with the maximum angle among the illumination light IL. The maximum  $\sigma$  value ( $\sigma_{IL}$ ) can be expressed, as follows:

$$\sigma_{IL} = NA_{IL} / NA = NA_{IL} / (\beta \cdot NA_{PL}) \quad (6A)$$

In a pupil plane of an illumination system shown in FIG. **12**, a maximum outer circle **26** indicates an outer area passed through virtual optical beam having the same numerical aperture as the numerical aperture NA at the incident side of the projection optical system PL, an inner circle **27** indicates a circle is tangent to areas passed through illumination light having numerical aperture of the maximum  $\sigma$  value ( $\sigma_{IL}$ ); all illumination light pass through within the circle **27**. The radius  $\sigma$  of the circle **27** is equal to  $\sigma_{IL} \cdot NA$ , as follows:

$$\sigma = NA_{IL} = \sigma_{IL} \cdot NA = \sigma_{IL} \cdot \beta \cdot NA_{PL} \quad (6B)$$

Further, in FIG. **12**, the origin point of the X axis and Y axis is on the optical axis BX. The illumination light IL, in FIG. **12**, has the distribution of amount of light with the approximate constant amount of light at the three areas (hatched areas) including the annular zone area **54** with the radius *r4* which centers on the optical axis BX of the illumination system **12** and the two circular areas **55A**, **55B** with the radius *r5* sandwiching the area **54** in the X direction; and with the smaller amount of light (approximate 0 in this embodiment) than the constant amount of light. That is, the centers of the three areas **54**, **55A**, and **55B** are arranged along the straight line which passes through the optical axis of the illumination system and parallels the X axis (periodically arranging direction of one directional high density pattern as target for transfer), the distance between the each center of the area **55A** and **55B** both ends and the optical axis BX is respectively *R3*.

Further, the annular zone area **54** has 1/2 annular in which the inner radius is 1/2 of the outer radius *r4*, 1/3 annular in which the inner radius is 1/3 of the outer radius *r4*, or 2/3 annular in which the inner radius is 2/3 of the outer radius *r4* and the like. In addition, as shown FIG. **15A**, the circular area **54A** with the radius *r4* can be used instead of the annular zone area **54**. Further, a plurality of areas substantially split can be used instead of the annular zone area **54**. Concretely, as shown in FIG. **15C**, the distribution of amount of light at the two half-circular (or circular etc.) areas **54A1**, **54A2** split in the Y direction (or X direction), in which the amount of light become great, may be used instead of the annular zone area **54**. In this case, the amount of light may become great at a four-way split area in the X direction and Y direction (or direction crossed these axes) instead of the annular zone area **54**. Furthermore, distribution in which the amount of light gradually decreases toward outer may be near the outline of the area **54**, **55A**, **55B**. The center area **54** is corresponding to the first area, and the two areas **54A** and **54B** sandwiching it is respectively corresponding to the second area and third area. Hereinafter, the radii *r4*, *r5* and *R3* respectively indicate the radius  $\sigma$  in the equation (6B) (distance between point



passed through the optical beam of the maximum  $\sigma$  value and the optical axis BX) corresponding to the maximum  $\sigma$  value ( $\sigma_{IL}$ ) as unit.

In this embodiment, the radii  $r4$ ,  $r5$  are preferably set within around  $0.1\sigma$  to  $0.2\sigma$  respectively, as follows:

$$0.1\sigma \leq r4 \leq 0.2\sigma \quad (21)$$

$$0.1\sigma \leq r5 \leq 0.2\sigma \quad (22)$$

If the values of the radii  $r4$ ,  $r5$  are smaller than the lower limit of the equation (21), equation (22), the depth of focus of the projection optical system PL becomes shallow for the optical beam in the isolated direction of one directional high density pattern; if the values of the radii  $r4$ ,  $r5$  are greater than the upper limit of the equation (21), equation (22), the depth of focus of the projection optical system PL becomes shallow for the optical beam in the periodic direction of one directional high density pattern (described below in detail). Furthermore, radius  $r4$  and radius  $r5$  are preferably equal, as follows:

$$r4 = r5 \quad (23)$$

Further, the areas **55A** and **55B** of each end in FIG. **12** are inscribed to the circle **27** of the maximum  $\sigma$  value. Accordingly, the equation holds, as follows:

$$R3 = \sigma - r5 \quad (24)$$

In this case, the diffractive characteristic of the diffractive optical element **21** in FIG. **1A** is set, so as to obtain the distribution of amount of light in which the amount of light approximately becomes constant at the area **54**, the areas **55A**, **55B** in FIG. **12** satisfying the condition of the equations (21) to (24); approximately becomes 0 at other areas. For the reason, the diffractive optical element **22A**, as an example, can fabricate by forming a concave and convex grating having approximately systematically along in the direction of the straight line **31A**, and a concave and convex grating having approximately systematically along the X axis of FIG. **12**. Alternatively, the diffractive optical element **22A** may be a combination of a plurality of phase type diffractive gratings. In these cases, since the diffractive optical element **22A** is phase type, it is advantage of high efficiency for using light. In addition, it is able to use an optical element changing refractive index distribution corresponding to a diffractive grating distribution as an optical element **22A**. In addition, a construction and a method for fabricating having a specific diffractive characteristic is closely disclosed, for example, in Japanese Patent Application Laid-open No. 2001-176766 (corresponding to U.S. Pat. No. 6,563,567) by this applicant.

In addition, it is allowed that the amount of light distribution obtained by diffraction optical device **22A** is set to be approximately the predetermined of light at a region including regions **54**, **55A** and **55B** in FIG. **12**. Furthermore then, an aperture stop where an aperture is formed at a portion corresponding to the regions **54**, **55A** and **55B** in FIG. **12** may be disposed on the emission plane **Q1** (pupil plane) of the fly eye lens **5** in FIG. **1A**. Also in this case, advantage in which utilization efficiency of the illumination light **IL** is high is obtained.

There will be explained, while referring to FIG. **13**, the focus light flux, when illuminating the pattern **52** of the one directional high density contact hole (one directional high density pattern) of reticle **RA** in FIG. **11A** with the amount of light distribution of the illumination light in FIG. **12**.

FIG. **13A** shows diffraction light (focus light flux) diffracted in the isolated Y direction from the pattern **52**. FIG. **13B** shows diffraction light (focus light flux) diffracted in the

periodic X direction from the pattern **52**. In FIGS. **13A** and **13B**, light beams **58**, **59** and **60** show the illumination light **IL** passed through the regions **54**, **55A** and **55B** on the pupil plane of the illumination system in FIG. **12** respectively. The diffraction light generated from the pattern **52** (aperture pattern **51**) due to the light beams **58**, **59** and **60** generates, in the Y direction, with distribution in which the diffraction light is generated most strongly at the center, and the larger the tilt angle, the lower the intensity decreases, as shown in FIG. **13A**.

On the other hand, as shown in FIG. **13B**, there are positive primary light **58P** and negative primary light **58M** in addition to zero-order light, in the diffraction light generated in the X direction from the pattern **52** by illumination of the light beam **58** from the region **54** with optical axis **BX** in FIG. **12** as center. At this point, the pattern **52** is resolution limit, therefore, the positive primary light **58P** and the negative primary light **58M** can not be passed through the projection optical system **PL** in FIG. **1**. Further, the zero-order light generated in the X direction from the pattern **52** by the illumination of the light beams **59** and **60** from the regions **55A** and **55B** of both ends in FIG. **12** is taken to as the zero-order lights **59** and **60** respectively, as shown in FIGS. **13A** and **13B**. The pattern **52** of this embodiment is approximately the resolution limit, therefore, the positive primary light **59P** from the pattern **52** due to one light beam **59** is made incident into the projection optical system **PL** in FIG. **1A** in parallel to the other zero-order light **60**, while, the negative primary light **60M** from the pattern **52** due to the other light beam **60** is made incident into the projection optical system **PL** in FIG. **1A** in parallel to one zero-order light **59**.

Further, wavelengths of incident light beams **58**, **59** and **60** are taken to as  $\lambda$ , exit angle in the X direction to the normal line of the pattern **52** of the zero-order light **59** is taken to as  $\theta$ , and exit angle in the X direction to the normal line of the pattern **52** of the zero-order light **60** is taken to as  $-\theta$ , and in FIG. **13B**, among the other light beams **59**, the light beam passed through the adjacent aperture pattern **51** with interval **P** of the X direction is taken to as the light beams **59A** and **59B**. In this case, differential value  $\Delta A$  of the optical path length between the positive primary light **59AP** of the light beam **59A** and the positive primary light **59BP** of the light beam **59B** equals to the wavelength  $\lambda$  as follows:

$$\Delta A = 2 \cdot P \cdot \sin \theta = \lambda \quad (25)$$

Furthermore, the interval **R3** in the X direction between the regions **55A** and **55B**, and the optical axis **BX** in FIG. **12** corresponds to  $\sin \theta$  of the exit angle  $\theta$  of the zero-order light of the light beams **59** and **60** in FIG. **13B** as follows:

$$R3 = \sigma - r5 = \sin \theta \quad (26)$$

In addition, equation (26) corresponds to the case in which focal distance **fQ1** at the side of the emission plane **Q1** of the partial optical system between the emission plane **Q1** (pupil plane) in the illumination system **12** in FIG. **1A** and the reticle plane is set to 1. Next relationship is approved from the equations (25) and (26). Since, there is no unit of the interval **R3** of the equation (26), unit of both sides of next equation becomes length.

$$P = \lambda / (2 \cdot R3) = \lambda / \{2(\sigma - r5)\} \quad (27A)$$

In other words, equation (27A) indicates resolution limit of X direction (cycle direction) in the object plane (reticle plane) of the projection exposure apparatus of this embodiment, in which the larger is the interval **R3** while making  $\sigma$  larger or while making radius **r5** smaller, the less it is possible to make the pitch **P** to be the resolution limit smaller. The pitch **P** is



converted into pitch  $\beta \cdot P$  as the following equation, which the pitch  $\beta \cdot P$  is length on the wafer. The pitch  $\beta \cdot P$  becomes the resolution limit in the X direction on the image plane (wafer plane) of the projection optical system PL.

$$\beta \cdot P = \beta \cdot \lambda \{2(\sigma - r5)\} \quad (27B)$$

In this embodiment, the wavelength  $\lambda$  is set to 193.306 nm. As one example, numerical aperture  $NA_{PL}$  at the wafer side of the projection optical system PL is taken to be 0.85, projection scale factor  $\beta$  of the projection optical system PL is taken to be  $1/4$ ,  $\sigma_{IL}$  to be  $\sigma$  value of illumination system 12 is taken to be 0.90, and radius  $r5$  of the regions 55A and 55B in FIG. 12 is taken to be  $0.14\sigma$ , that is called as “the first illumination condition”. The resolution limit  $\beta \cdot P$  at the image plane side under this condition becomes about 147 nm as shown in next equation from relationship of the equations (6B) and (27B).

$$\beta \cdot P = 146.7 \text{ (nm)} \quad (28)$$

FIG. 12 can be regarded as the drawing showing amount of light distribution in the X direction in the pupil plane Q3 of the projection optical system PL in FIG. 1A. In this case, the regions 54, 55A and 55B in FIG. 12 correspond to position through which the zero-order light of the illumination light IL is passed, and the positive primary light in the X direction of the illumination light IL according to the pattern 52 in FIG. 1A becomes distribution in which the amount of light distribution in the circumference 27 is moved in parallel toward the region in the circumference 57A with the spaced point 56A as the center, which the spaced point 56A is spaced from the optical axis BX (optical axis AX of the projection optical system PL) by only interval  $2 \cdot R3$  in the +X direction. Similarly, the negative primary light in the X direction of the illumination light IL according to the pattern 52 becomes distribution in which the amount of light distribution in the circumference 27 is moved in parallel toward the region in the circumference 57B with the spaced point 56A as the center, which the spaced point 56B is spaced from the optical axis BX (optical axis AX) by only interval  $2 \cdot R3$  in the -X-direction. In this case, the positive primary light (or the negative primary light) of the light beam passing through the region 55B (or 55A) passes through the region 55A (or 55B), therefore, the image of the pattern 52 is projected on the wafer with high resolution.

In addition, if a part of the positive primary light (negative primary light) of the light beam passing through the region 55B (55A) is passed through within the circumference 26, the image of the pattern 52 is imaged, therefore, actual resolution limit  $\beta \cdot P$  at the image plane side becomes smaller value than that of the equation (28).

Concerning this embodiment, the present inventor, in order to obtain the optimum balance between radius  $r4$  of central region 54 and radius  $r5$  of the regions 55A and 55B at both ends in FIG. 12, has calculated depth of focus (DOF) of the image according to the projection optical system PL with simulation of the computer while varying the radius  $r4$  gradually. The condition in addition to the  $r4$ , at this time, is the same as the above described first illumination condition, and the radius  $r5$  is  $0.14\sigma$ . Furthermore, the pitch  $P$  of the pattern 52, in FIG. 11A, is taken to be 145 nm to be approximate resolution limit, and the width  $a$  in the X direction of the aperture pattern 51 is taken to be 70 nm, and width  $b$  in the Y direction is taken to as 500 nm. It should be noted that the pitch  $P$ , and the widths  $a$  and  $b$  are lengths which are converted on the image plane of the projection optical system PL respectively.

The curved line 61 in FIG. 14 shows the simulation results, and the horizontal axis in FIG. 14 is the radius  $r4$  (unit is  $a$ ) of

the region 54 (center  $a$ ) of the center of FIG. 12, and the vertical axis is calculation results of the depth of focus (DOF) (nm) corresponding to the value of the radius  $r4$ . As known from the curved line 61, there is obtained the depth of focus more than approximate 100 nm within the range in which the radius  $r4$  is from  $0.1\sigma$  to  $0.2\sigma$ . In addition, when the radius  $r4$  is  $\sigma$  ( $=0.14\sigma$ ), that is, when the radius  $r4=r5$  is approximately approved, there is obtained the deepest depth of focus. In this case, even though some degree of unevenness exist on the wafer as a substrate, curvature and the like occur on the image plane within the above described exposure region by aberration of the projection optical system PL or the like, or certain degree of tracking error of the focus position remains at the time of exposure in the scanning exposure method, for instance, it is possible to transfer the one directional high density pattern with high resolution. It should be noted that when the radius  $r4$  becomes smaller than degree of  $0.1\sigma$ , the depth of focus of the focus light flux in the isolated direction of the pattern 52 in FIG. 11A becomes narrow. On the other hand, when the radius  $r4$  becomes larger than degree of  $0.2\sigma$ , the depth of focus of the focus light flux in the cyclic direction of the pattern 52 in FIG. 11A becomes narrow, by the flare effect of the light beam from the region 54 of the center of FIG. 12.

In addition, in the pattern 53 of the one directional high density contact hole existing in the position spaced from the pattern 52 of FIG. 11A, arrangement direction is the same as that of the pattern 52, and the pitch  $Q$  is larger than the pitch  $P$ , therefore, the pattern 53 is transferred on the wafer with high resolution under the above described illumination condition.

As described above, by employing the amount of light distribution on the pupil plane of this embodiment in FIG. 12, the pattern of the reticle RA including the pattern 52 of the one directional high density contact hole of FIG. 11A is capable of being transferred on the wafer  $W$  in the X direction and the Y direction with high resolution.

In addition, for instance, when one directional high density pattern with X direction as cyclic direction and one directional high density pattern with Y direction as cyclic direction are formed on the reticle RA of FIG. 11A, it is allowed that arrangement direction of three regions 54, 55A and 55B through which the illumination light of FIG. 12 is passed in parallel to the cyclic direction of the pattern which has the smallest pitch among them. At this time, three regions 54, 55A and 55B are allowed to be disposed on the straight line in parallel to the cyclic direction of one pattern which is passed through the optical axis BX on the pupil plane of the illumination system 12 and whose pitch is the smallest one. At least one of 2 regions 55A and 55B except for the central region 54 is allowed that distance of the optical axis BX concerning the direction in parallel to the cyclic direction of the other pattern is not zero, or the distance is allowed to be set in accordance with the pitch of the other pattern, for instance.

Furthermore, numerical aperture  $NA_{PL}$  at the image side of the projection optical system PL, the projection scale factor  $\beta$ , and the maximum  $\sigma$  value ( $\sigma_{IL}$ ) of the illumination system 12 are capable of taking arbitrary value without restricting the value to the above described values. For instance, position (distance of the optical axis BX concerning X direction to the region 55B) in the radius direction of the regions 55A and 55B where peripheral amount of light is large among amount of light distribution of FIG. 12 is allowed to be varied while varying interval between prisms 71 and 72 of FIG. 1A to control the maximum  $\sigma$  value ( $\sigma_{IL}$ ), or the interval  $R3$  of FIG. 12. It is possible to control the maximum  $\sigma$  value similarly,



also by employing the V-type prisms 71A and 72A of FIG. 10 instead of the prisms 71 and 72.

In addition, in the amount of light distribution of FIG. 12, it is allowed that the amount of light (for instance, intensity per unit area) of the center region 54 is made different from the amount of light of peripheral 2 regions 55A and 55B. Relative largeness of these light quantities is allowed to be adjusted so that the optimum resolution can be obtained every transferring pattern, for instance. Furthermore, in this embodiment, it is allowed that distributed light in peripheral regions 55A and 55B of FIG. 12 may be made linearly polarized light. At this occasion, it is allowed that, as one example, the light distributed on the peripheral regions 55A and 55B is made S polarization in which the polarizing direction is direction of the tangential line (vertical direction to incident plane). By this matter, in some cases, resolution and so forth to the specific pattern are improved.

In addition, when the lights which are respectively distributed at three regions having large peripheral amount of light described above while being generated from the light source 1 are non-polarized lights, or the polarizing direction thereof do not agree with the direction of the tangential line, it is preferable that the lights are converted into the light beam of the linear polarized light in which the polarizing direction approximately agrees with the direction of the tangential line upon disposing the polarization setting member such as a half-wave plate or a quarter-wave plate or so forth on the optical path through which the lights distributed at respective regions are passed between the diffraction optical element 21 (deflection member) and the fly eye lens 5, for instance. At this time, it is preferable that there is provided the polarization setting member at incident side of one prism (movable member), which is movable along the optical axis BX and disposed at the most upstream (light source side) between one pair of the prisms described above, for instance, between the movable member and the lens 4, or between the diffraction optical device described above and the lens 4. In this case, it is not necessary to move the polarization setting member in accordance with variation of direction of travel of the light beam (optical path) caused by exchange of the diffraction optical device or interval change of one pair of prisms or so forth, or it is not necessary to form the polarization setting member largely in anticipation of its variation.

In addition, the diffraction optical device 22A in this embodiment sets the amount of light distribution on the pupil plane of the illumination system 12 as the predetermined plane into predetermined condition, however, the predetermined plane is possible to be the pupil plane Q3 of the projection optical system PL of FIG. 1A. At this time, in the case that the reticle RA does not exist caused by its diffraction optical device 22A, the amount of light distribution, which becomes approximately constant in the first region including the optical axis AX and in two regions putting the first region therebetween, and becomes lower amount of light than it at the region in addition thereto, is set in the pupil plane Q3 of the projection optical system PL.

In addition, in this embodiment, the regions 54, 55A and 55B, which have approximately constant amount of light on the pupil plane, have circular form (or annular form), however, outward form of those regions are possible to be respective oval regions. Further, outward form of each region is possible to be rectangular region as described later, furthermore, outward form of each region is possible to be combined between the circular (or oval) region and the rectangular region.

FIG. 15B shows another possible amount of light distribution on its pupil plane, as shown in FIG. 15B, the amount of

light distribution becomes approximately the predetermined of light at the frame shaped region 54B of the center rectangular shape (regular hexagon or so forth is possible in addition to square), and at two rectangular regions 55C and 55D, which put the region 54B therebetween in the X direction, and the amount of light distribution becomes low at the region in addition thereto. In this case, position and area of the rectangular (or frame shape) region are allowed to be approximately the same as the position and area of the regions 54, 55A and 55B of FIG. 12.

Next, from the above described equations (27A) or (27B) in the amount of light distribution of the illumination light on the pupil plane of FIG. 12, it is seen that the larger is  $\sigma$  to be radius of the circumference 27 and the smaller is the radius  $r5$  of the regions 55A and 55B at both ends, the smaller it is possible to minimize the resolution limit P (or  $\beta P$ ). However, when the radius  $r5$  becomes smaller than degree of  $0.1\sigma$ , the depth of focus becomes shallow. Consequently, there will be explained the method capable of improving the resolution while minimizing the radius  $r5$  substantially and maintaining the depth of focus deep below. For that reason, there is provided the second diffraction optical device 22B having slightly different diffraction property in the revolver 24 of FIG. 1A. When the second diffraction optical device 22B is mounted on the optical path of the illumination light IL, there is obtained the amount of light distribution, which becomes approximately the predetermined of light at three regions 62, 63A and 63B of FIG. 16A, and becomes the amount of light lower than it (approximate zero in this embodiment) in the region in addition thereto, at the emission plane Q1 (pupil plane) of the fly eye lens 5.

FIG. 16A shows the amount of light distribution of the illumination light IL in the emission plane Q1 (the pupil plane of the illumination system 12) of the fly eye lens 5 in FIG. 1A in the case that the second diffraction optical device 22B is used. In FIG. 16A where the same sign is added to corresponding part to FIG. 12, there is set two oval regions 63A and 63B (the second region and the third region) having the shape in which slender in the Y direction is external form, width in the X direction is  $t$ , and length in the Y direction is  $h$  ( $h > t$ ), so as to put the circular region 62 (the first region) of the radius  $r6$  between these two oval regions 63A and 63B in the X direction, with the optical axis BX of the illumination system 12 in FIG. 1A as the center, so that the interval from the optical axis BX to each center becomes  $R4$ . Also in this example, the center region 62 is allowed to be the annular shape. Two slender oval regions 63A and 63B are the overlapped region in which the region in the circumference 27 having the radius  $\sigma$  is overlapped by the region in the circumferences 65A and 65B whose radii are  $NA$  (or  $\sigma$  is possible) by employing the positions 64A and 64B, which have the interval of  $R5$  from the optical axis BX, as the center. On this occasion, the interval  $R4$  is set longer than the interval  $R3$  from the optical axis BX in FIG. 12 to the center of the regions 55A and 55B, the intervals  $R4$  and  $R5$  are capable of being expressed with the following equations.

$$R4 = (\sigma - t/2) > R3 \quad (29A)$$

$$R5 = R4 + NA - t/2 \quad (29B)$$

In order to bring the relation of  $R4 > R3$  into existence, on the assumption that the equation (22) is already brought into existence,  $1/2$  of the width  $t$  in the X direction of oval regions 63A and 63B, as one example, is set approximately to next range. Similarly, the radius  $r6$  of the center circular region 62 is set within the range of approximately the degree of two times of  $t/2$ .



$$0.025\sigma \leq t/2 \leq 0.075\sigma \quad (30)$$

$$0.05\sigma \leq r6 \leq 0.16\sigma \quad (31)$$

More desirably,  $t/2$  is set to the degree of  $0.05\sigma$ . The resolution limit  $P$  in the  $X$  direction on the object plane of the corresponding projection optical system PL to the equation (27A) in these cases becomes smaller than the value of the equation (27A) as the following equation.

$$P = \lambda / (2 \cdot R4) < \lambda / (2 \cdot R3) \quad (32)$$

Also, concerning the illumination condition in FIG. 16A, the present inventor, in order to obtain the optimum balance between radius  $r6$  of central region 62 and half width ( $t/2$ ) of the oval regions 63A and 63B at both ends, has calculated depth of focus (DOF) of the image according to the projection optical system PL by simulation of the computer while varying the radius  $r6$  gradually. In the illumination condition (the second illumination condition) on this occasion, the wavelength  $\lambda$  is set to 193.306 nm. Numerical aperture  $NA_{PL}$  at the wafer side of the projection optical system PL is taken to be 0.85, projection scale factor  $\beta$  is taken to be  $1/4$ ,  $\sigma_{IL}$  to be  $\sigma$  value of illumination system 12 is taken to be 0.93, and the half width ( $t/2$ ) of the oval regions 63A and 63B is taken to be  $0.05\sigma$ . In addition, the pitch  $P$  of the pattern 52, in FIG. 11A of the object of transfer is taken to be 140 nm to be approximately resolution limit, and the width  $a$  in the  $X$  direction of the aperture pattern 51 is taken to be 70 nm. It should be noted that the pitch  $P$ , and the widths  $a$  and  $b$  are lengths which are converted on the image plane of the projection optical system PL respectively.

The curved line 66 in FIG. 17 shows the simulation results, and the horizontal axis in FIG. 17 is the radius  $r6$  (unit is  $\sigma$ ) of the region 62 (center  $\sigma$ ) of the center of FIG. 16A, and the vertical axis is calculation results of the depth of focus (DOF) (nm) corresponding to the value of the radius  $r6$ . As known from the curved line 66, there is obtained the depth of focus more than approximate 250 nm within the range in which the radius  $r6$  is from degree of  $0.05\sigma$  to  $0.16\sigma$ . In addition, when the radius  $r6$  is  $\sigma/2$  ( $=0.11\sigma$ ), that is, when the radius  $r6=t$  is approximately brought into existence, there is obtained the deepest depth of focus (about 350 nm). Accordingly, by employing the illumination condition in FIG. 16A, there is obtained higher resolution to the one directional high density pattern, and the deep depth of focus. In this embodiment, even though the width in the  $X$  direction (cycle direction) of the regions 63A and 63B of both ends in FIG. 16A becomes narrow, the areas of the regions 63A and 63B are approximately the same degree as the areas of the regions 55A and 55B in FIG. 12, therefore, the deep depth of focus can be obtained.

In addition, instead of the center circular region 62 in FIG. 16A, as shown in FIG. 16B, it is also allowed that there may be used the amount of light distribution where the amount of light becomes large at the oval region 62A with  $X$  direction as longitudinal direction, in which  $X$  direction is direction (that is, direction in parallel to arrangement direction of three regions) perpendicular to the longitudinal direction of the peripheral oval regions 63A and 63B. In the amount of light distribution in FIG. 16B, the amount of light of two oval regions 63A and 63B, which put the oval region 62A therebetween, becomes large. Thus, by making the central region 62 oval shape, in some cases, it is possible to improve resolution in the isolated direction with respect to the one directional high density pattern without reducing the amount of light.

In addition, in the amount of light distribution of FIGS. 16A and 16B, it is allowed that the amount of light (for

instance, intensity per unit area) of the center regions 62 and 62A is made different from the amount of light of peripheral regions 63A and 63B.

Furthermore, it is also allowed that distributed light in peripheral regions 63A and 63B in FIGS. 16A and 16B may be made linearly polarized light (for instance, longitudinal direction is the polarizing direction). In particular, in the amount of light distribution in FIG. 16B, as one example, it is preferable that the light distributed at the peripheral oval regions 63A and 63B is made the linear polarized light (S polarized light) in which the polarizing direction is the longitudinal direction thereof as shown by the arrows PC and PB (that is, the longitudinal direction is the direction corresponding to isolated direction of the pattern of the reticle in FIG. 11A). In this occasion, furthermore, it is preferable that the light distributed at the center oval region 62A is made the linear polarized light in which the polarizing direction is the longitudinal direction thereof (that is, the longitudinal direction is the direction corresponding to the cycle direction of pattern of the reticle in FIG. 11A) as shown in the arrow PA2. By this matter, in some cases, resolution and so forth to the specific pattern are improved.

In addition, when the lights distributed at the peripheral regions 63A and 63B are non-polarized lights, or the polarizing direction thereof do not agree with the longitudinal direction of the tangential line, in the amount of light distribution in FIGS. 16A and 16B, like the above, for instance, it is preferable that the polarization setting member is provided between the diffraction optical device and the fly eye lens 5. Similarly, in the amount of light distribution in FIG. 16B, when the lights distributed at the center region 62A are the non polarized lights, or the polarizing direction thereof does not agree with the longitudinal direction, it is preferable that its polarized condition is adjusted by the above polarization setting member.

### Third Embodiment

Next, there will be explained a third embodiment of the present invention referring to FIG. 18 to FIG. 21. The first embodiment uses member including the diffraction optical devices 21, 22 as the optical member for setting the predetermined amount of light distribution, on the contrary, this embodiment uses the aperture stop as the optical member thereof, and in FIG. 18, there is attached the same symbol to a portion corresponding to FIG. 1A to omit its detailed description.

FIG. 18 shows a configuration of the projection exposure apparatus of this embodiment, in this FIG. 18, the illumination light IL from the exposure light source 1, is made incident into the fly-eye lens 5 via the beam expander 2 and the mirror 3. There is disposed the aperture stop (a stop) 42 as the optical member for obtaining the predetermined amount of light distribution at the emission plane Q1 as the predetermined plane, in the emission plane Q1 (the pupil plane of the illumination system 12) of the fly-eye lens 5 of this embodiment. The aperture stop 42 is mounted on the revolver 41, and the revolver 41 is mounted with another aperture stop 44, and further, still another aperture stop (not shown in the drawings). The present embodiment is so constituted that the illumination condition is capable of being switched upon providing either of the aperture stops 42, 44 and so forth at the emission plane Q1 (pupil plane) while controlling the rotation angle of the revolver 41 via the driver 43 by the main control system 17.

The illumination light IL passed through the aperture stop 42 illuminates a slender illumination region of the pattern



plane (reticle plane) of the reticle R as the mask with uniform intensity distribution via the condenser lens system 6, the field stops 7, 8, the image-forming lens system 9, the mirror 10 and the main condenser lens system 11. The illumination system 12 of the present embodiment is constituted by the exposure light source 1, the beam expander 2, the mirror 3, the fly-eye lens 5, the aperture stop 42 (or another aperture stop), the condenser lens system 6, the field stops 7, 8, the image-forming lens system 9, the mirror 10 and the main condenser lens system 11. The constitution in addition to the above is the same as the embodiment in FIG. 1A.

In this embodiment, the pattern on the reticle R of the object of transfer is the pattern including the contact hole having three-kind of different pitches as shown in FIG. 2. The aperture stop 42 in FIG. 18, in accordance with this, forms nine apertures in the shading plate to obtain the same amount of light distribution as the amount of light distribution in FIG. 3.

FIG. 19 shows the shape of the aperture stop 42. In FIG. 19, in the aperture stop 42 comprised of the shading plate, the aperture stop 42 is formed with nine apertures each of which is spaced mutually, which include a circular shaped aperture 45 with the optical axis BX of the illumination system 12 as the center, four circular shaped apertures 46A, 46B, 46C and 46D in which respective centers are disposed along the first circumference surrounding the aperture 45, and four circular shaped apertures 47A, 47B, 47C and 47D in which the centers thereof are disposed along the second circumference surrounding the apertures 46A to 46D. In addition, positions and shapes of the aperture 45, apertures 46A to 46D, and apertures 47A to 47D are the same as that of the region 28, region 29A to 29D, and regions 30A to 30D in which amount of light is approximately constant on the respective amount of light distribution in FIG. 3.

Accordingly, by employing the aperture stop 42, the amount of light distribution on the emission plane Q1 (pupil plane) of the fly-eye lens 5 becomes approximately constant at nine regions shown in FIG. 3 like the first embodiment, and becomes low at the region in addition thereto, therefore, it is possible to transfer the reticle pattern image including the contact hole having various kind of pitch as FIG. 2 on the wafer at once with high resolution. In the case that the aperture stop 42 is used as this embodiment, the utilization efficiency of the illumination light 1L decreases, however, there is advantage that it is possible to set the amount of light distribution at the predetermined plane (the pupil plane or so forth of the illumination system 12) into the required condition accurately using simple constitution.

In addition, it is also allowed to use an aperture stop (also numbered 42) in which the center aperture is made the annular aperture 45R as shown in FIG. 20, instead of the aperture stop 42 in FIG. 19, or by combining it. In this case, the amount of light distribution, which is the same as FIG. 6A, is obtained accurately and easily, therefore, it is possible to further improve the resolution or the depth of focus. In addition, it is possible to form the amount of light distribution, which is the same as that of FIG. 6B, upon coupling two apertures respectively lined up in the radius direction at the aperture stop 42 in FIG. 20.

Further, the aperture stop 44 in FIG. 18, as shown in FIG. 21, is the stop in which the annular region 33R in FIG. 7A and corresponding parts to the regions 34A to 34D are made the bracelet shaped aperture 48R and the circular shaped apertures 49A to 49D respectively. Accordingly, by installing the aperture stop 44 on the emission plane Q1 (pupil plane) of the fly-eye lens 5, the amount of light distribution on the pupil plane, like FIG. 7A, becomes approximately constant at five

regions, and becomes approximately zero at the region in addition thereto, therefore, there is obtained the wide depth of focus and high resolution with respect to the patterns having various kind of pitches.

In addition, it is possible to form the amount of light distribution, which is the same as that in FIG. 7B, upon coupling the annular shaped aperture 48R to the circular apertures 49A to 49D in the aperture stop 44 in FIG. 21.

In addition, in the present embodiment, a part other than the aperture is taken to as the light shielding part in the aperture stops 42, 44, however, it is also allowed that a part other than the aperture is taken to as a light attenuating part (a part where the light transmittance is small). In this case, in the amount of light distribution on the pupil plane of the illumination system, like FIG. 3, FIG. 6A and FIG. 7A, the amount of light does not become zero in the region other than five regions or nine regions. Further, in the present embodiment, the aperture stop is disposed on the pupil plane or the conjugated plane thereof of the illumination system 12, however, it is allowed that the aperture stop is disposed on a part adjacent to the incident plane of the fly-eye lens 5, for instance.

#### Fourth Embodiment

Next, referring to FIG. 22, a fourth embodiment of the present invention will be explained. The second embodiment employs the member including the diffractive optical elements 22A and 22B as the optical member for setting a predetermined distribution of amount of light, whereas this embodiment employs the aperture stop as its optical member. For this, in this embodiment, similarly to the third embodiment, the scan exposure type of the projection exposure apparatus of FIG. 18 is employed for exposure. However, in this embodiment, aperture stops 42A and 42B to be later described are used instead of the aperture stops 42 and 44 of FIG. 18 respectively, and the reticle stage RA of FIG. 11A is loaded onto the reticle stage 14 instead of the reticle R.

Also in this embodiment, it is assumed that the pattern of the reticle RA, being an object of transfer, is a pattern 52 including the pattern of one directional high density contact hole that is arranged in a pitch P in the X direction shown in FIG. 11A. In response hereto, the aperture stop 42A of FIG. 18 is produced by forming three apertures in the shading plate in order to obtain the distribution of amount of light identical to that of FIG. 12.

FIG. 22A shows a shape of its aperture stop 42A and in FIG. 22A, the aperture stops 42A to be composed of the shading plate has the three apertures including an annular aperture 66 with the optical axis BX of the illumination system 12 of FIG. 18 centered, and two circular apertures arranged so as to hold its aperture 66 between them, each of which is spaced from each other. In addition, the position and shape of the apertures 66, 67A and 67B are identical to areas 54, 55A and 55B having approximately constant amount of light on the distribution of amount of light of FIG. 12 respectively.

Accordingly, by employing the aperture stop 42, the distribution of amount of light on the exit plane Q1 (pupil plane) of the fly-eye lens 5 becomes approximately constant in three areas shown in FIG. 12 similarly to the second embodiment, and it becomes low in the area other than it, whereby the image of the pattern of the reticle including the pattern 52 of the one directional high density contact hole can be transferred onto the wafer with a high-resolution in the X direction and the Y direction. In a case of employing the aperture stop 42A like the case of this embodiment, the utilization efficiency of the illumination light 1L is lowered; however there



exists an advantage that the simple configuration enables the distribution of amount of light on a predetermined plane (the pupil plane of the illumination system **12** or its conjugate plane) to be accurately set in a desired state.

In addition, the second aperture stop **42B** of FIG. **18**, as shown in FIG. **22B**, is an aperture stop having the aperture **68** and slender oval apertures **69A** and **69B** formed responding to the circular area **62** and the slender oval areas **63A** and **63B** of FIG. **16A** respectively. Accordingly, installing the aperture stop **42B** on the exit plane **Q1** (pupil plane) of the fly-eye lens **5** of FIG. **18** enables the pattern of the one directional high density contact hole to be transferred onto the wafer with a high resolution and yet at a deep depth of focus, similarly to the case of employing the illumination condition of FIG. **16A**. In addition, in this embodiment, not only the aperture stops **42A** and **42B** shown in FIG. **22A** and FIG. **22B**, but also, for example, the aperture stop forming the distribution of amount of light shown in FIG. **15A** to FIG. **15C** and FIG. **16B** can be used.

Additionally, in this embodiment, the aperture stop may be arranged not only on the pupil plane of the illumination system **12** or its conjugate plane, but also arranged closely to the incident plane of, for example, the fly-eye lens **5**. In addition, in this embodiment, the section other than each of the aperture stops **42A** and **42B** is assumed to be a shading section; however the section other than its aperture may be assumed to be a light-reducing section (the portion having less quantity of light). In this case, with the distribution of amount of light on the pupil plane of the illumination optical-system **12**, the amount of quantity does not become zero on the area other than three areas.

#### Fifth Embodiment

Next, referring to FIG. **23**, a fifth embodiment of the present invention will be explained. The above-mentioned first to fourth embodiments employ the fly-eye lens as an optical integrator (uniformizer or homogenizer), whereas this embodiment uses an inner-plane reflection type integrator, for example, a rod type integrator as the optical integrator.

FIG. **23** shows the main part of the illumination system of the projection exposure apparatus of this embodiment, and this optical system of FIG. **23** is arranged, for example, between the mirror **3** of the illumination system **12** and the fixed field stop **7** of FIG. **1A**. In FIG. **23**, the illumination light **1L** from the exposure light source, which is not shown in the figure, enters the diffractive optical element **21** having an identical configuration to that of the first embodiment or the diffractive optical element **22A** having an identical configuration to that of the second embodiment. The diffracted light from the diffractive optical element **21** (or **22A**) is gathered in nine (or three) areas on the plane **Q4** as a predetermined plane via a relay lens **152**. In addition, the illumination light that has passed through the plane **Q4** is gathered in the incident plane of a rod integrator **151** via a condenser lens **153**. In this case, the plane **Q4** is approximately positioned at the frontal focus plane of the condenser lens **153**, and the incident plane of the rod integrator **151** is approximately positioned at the rear focus of the condenser lens **153**.

In addition, the exit plane **Q5** of the rod integrator **151** is a conjugate plane with the reticle plane, the fixed field stop **154** is arranged in the vicinity of this exit plane **Q5**, and closely hereto a movable field stop (not show in the figure) is arranged. In addition hereto, the illumination light to be injected from the rod integrator **151** illuminates a pattern of the reticle, which is not shown in the figure, through the

optical system similar to the imaging lens system **9** and the main condenser lens system **11**.

Also, in this embodiment, the distribution of amount of light shown in FIG. **3** (or FIG. **12**) on the plane **Q4** is set by using the diffractive optical element **21** (or **22A**), thereby enabling the image of the pattern (or pattern including the one directional high density contact hole) including the variously pitched contact holes to be transferred onto the wafer at a time and with a high precision.

In addition, also in this embodiment, instead of employing the diffractive optical element **21**, the aperture stop provided with nine apertures similar to the aperture stop **42** of FIG. **19** and FIG. **20**, or the aperture stop **44** of FIG. **21** may be arranged on the plane **Q4**. Further, as described above, also in this embodiment, when it is necessary to adjust the polarization state of the luminous flux in at least one out of a plurality of the areas, for example, nine, five, or three areas, in which the amount of light is enhanced with the distribution of amount of light on the pupil plane of the illumination system, for example, the foregoing deflection polarization setting member may be installed on the plane **Q4**.

Further, in FIG. **23**, the diffractive optical element **22B** of FIG. **1A** for setting the distribution of amount of light of FIG. **16A** may be arranged instead of the diffractive optical element **22A**. In addition, as described above, when it is necessary to adjust the polarization state of the luminous flux in at least one out of three areas, in which the amount of light is enhanced with the distribution of amount of light on the pupil plane of the illumination system, for example, the foregoing polarization setting member may be installed on the plane **Q4**.

In addition, one pair of the interval-variable prisms **71** and **72** (movable prisms) of FIG. **1A** may arranged for example, between a lens **152** of FIG. **23** and the plane **Q4** to make the position in the radial direction of the area, in which the amount of light of the vicinity is large, variable.

Additionally, as the rod integrator **151** can be used the light-transmissive optical member that is of polygonal column shape, for example, of square column shape, of hexagonal column shape, etc. or the reflective member of such hollow metal etc. that is of polygonal column shape or of cylindrical column shape as mentioned above.

In addition, the focus point of the illumination light **1L** (diffracted light) **1L** by the condenser lens **153** should be deviated from the incident plane of the rod integrator **151**.

Further, in this embodiment, the plane **Q4** is assumed to be a predetermined plane (equivalent to the pupil plane of the optical system or its conjugate plane); however the predetermined plane is not limited hereto, and for example, it may be a plane between the rod integrator **151** and the reticle **R** (or the reticle **RA**). In addition, when, for example, any of the aperture stops **42** and **44** (or **42A** and **42B**) is employed instead of the diffractive optical element **21** (or **22A** etc.) or in combination thereof, its aperture stop may be arranged in the downstream side (reticle side) of the rod integrator **151**.

Additionally, in the above-mentioned first and fifth embodiments, in a case where both of the foregoing diffractive optical element and aperture stop are employed, thereby to set the distribution of amount of light of the illumination **1L** on the pupil plane of the illumination system, when the diffracted light to be generated from the diffractive optical element is distributed on the aperture stop as shown in FIG. **3** or FIG. **7A**, the utilization efficiency of the illumination light becomes highest (the loss of the amount of light of the illumination light is minimized); however its diffracted light does not need to be accurately distributed as shown in FIG. **3** or FIG. **7A**. That is, the utilization efficiency of the illumination light is lowered; however the diffractive optical element dif-



ferent from the foregoing diffractive optical elements (21 and 22) may be employed, thereby to distribute its diffracted light on a predetermined area including the area other than nine or five areas.

In addition, the aperture stop that is used in conjunction with the foregoing diffractive optical elements does not need always to have five or nine areas shown in FIG. 19 to FIG. 21, and the point is that it is enough to have the shading section or the light-reducing section for setting the distribution of amount of light of the diffracted light (illumination light 1L), which is generated from the diffractive optical element and is distributed on the pupil plane of the illumination system or its conjugate plane, to the distribution of amount of light shown in FIG. 3, FIG. 6A, and FIG. 7A. For example, the diffractive optical element, which is employed for setting the distribution of amount of light of FIG. 3 or FIG. 4, may be used in conjunction with the aperture stop for partially shadowing or light-reducing the center of the center areas 29 or 33 of its distribution of amount of light, thereby to set the distribution of amount of light of FIG. 6A or FIG. 7A, and no necessity exists for forming the aperture, which corresponds to its distribution of amount of light (of five or nine areas in which the amount of light is enhanced) that should be set, on this aperture stop.

In addition, in the above-mentioned first and fifth embodiments, at least one part of the optical system (4; 152 and 153) that is provided between the diffractive optical element to be arranged within the illumination system and the optical integrator (5; 151) is assumed to be a zoom lens (a focal system), thereby to make the size of the nine or five areas, in which the illumination light 1L on the pupil plane of the illumination system is distributed, variable. Further, at least one pair of the foregoing interval-variable prisms may be built in its optical system (4; 152 and 153). At this time, so as to distribute the illumination light 1L on the center area (28; 33), each of the vicinities of the apexes of one pair of the prisms is cut out, thereby to assume the part, through which the illumination light 1L to be distributed on the center area passes, to be an approximately vertical plane to the light axis BX of the illumination system.

Additionally, in the above-mentioned first and fifth embodiments, by means of the formation optical system (equivalent to the optical member), which is comprised of only a plurality of the diffractive optical elements that are arranged for replacement in the illumination system, or the formation optical system having its plurality of the diffractive optical elements and the optical system, in which at least one of the foregoing zoom lens and one pair of the prisms is built, combined, when the optical integrator is the fly eye lens 5, the intensity distribution of the illumination 1L on its incident plane is caused to change, and when the optical integrator is the inner-plane reflection type integrator 151, the range of the incident angle of the illumination light 1L that enters the its incident plane is changed, thereby allowing the distribution of amount of light (shape or size of the secondary light source) of the illumination light 1L on the pupil plane of the illumination system, i.e. the illumination condition of the reticle to be changed arbitrarily. At this time, a plurality of the diffractive optical element to be hold in the revolver 24 are not limited to only the foregoing diffractive optical elements 21 and 22, and may include at least one out of the four diffractive optical elements to be used, for example, for each of the illuminating having small  $\sigma$ , the annular illumination, the bipolar illumination, and the tetra-polar illumination. In addition, the foregoing aperture stop may be combined with its formation optical system. At this time, for example, one (including the foregoing diffractive optical element etc. except

the aperture stop) out of the formation optical system may be arranged in the upstream side of the optical integrator (between the light source 1 and the optical integrator), and its aperture stop may be arranged in the downstream side of the optical integrator.

In addition, in the above-mentioned first, and third, and fifth embodiments, the pitch in the X direction of three patterns 25A to 25C shown in FIG. 2 is identical to that in the Y direction thereof respectively, whereby as shown in FIG. 3, the straight lines 31A and 31B, in which nine areas in which the illumination 1L on the pupil plane of the illumination system is distributed are arranged, intersect each other in the optical axis of the illumination system; however when the pitch in the X direction of three patterns 25A to 25C differs from that in the Y direction thereof, the straight lines 31A and 31B do not intersect each other, that is, the distance in the X direction to the optical axis differs from the distance in the Y direction hereto in four middle areas 29A to 29D respectively, and yet the distance in the X direction to the optical axis differs from the distance in the Y direction hereto in four most peripheral areas 30A to 30D respectively. Additionally, the number (kind) of the pattern to be formed on the reticle is not limited to three, and it may be two or four, and the array directions of the pattern does not need always to coincide with the X direction and the Y direction respectively.

In addition, in the above-mentioned first, third, and fifth embodiments, by means of a plurality of the foregoing interval-variable prisms, each position of the four or eight areas except the center area, in which the light quantity on the pupil plane is enhanced, is made variable; however the number of its neighboring area is not limited to four or eight, and for example, two is acceptable.

Additionally, in the above-mentioned second, and fifth embodiments, in a case where both of the foregoing diffractive optical member and aperture stop are employed, thereby to set the distribution of amount of light of the illumination light 1L on the pupil plane of the illumination system, when the diffracted light that is generated from the diffractive optical system is distributed on the aperture stop as shown in FIG. 12 or FIG. 16A, the utilization efficiency becomes highest (the loss of amount of light of the illumination light is minimized); however its diffracted light does not need to be accurately distributed as shown in FIG. 12 or FIG. 16A. That is, the diffractive optical element different from the foregoing diffractive optical elements 22A and 22B may be employed, thereby to distribute its diffracted light on a predetermined area including the area other than three areas even though the utilization efficiency becomes low.

In addition, the aperture stop, which is used in conjunction with the foregoing diffractive optical element, does not need always to have the three apertures shown in FIG. 22, and the point is that it is enough to have the shading section or the light-reducing section for setting the distribution of amount of light of the diffracted light (the illumination light 1L), which is generated from the diffractive optical element and is distributed on the pupil plane of the illumination system or its conjugate plane, to, for example, the distribution of amount of light shown in FIG. 12, FIG. 15 and FIG. 16A. For example, the diffractive optical element, which is employed for setting the distribution of amount of light of FIG. 15A may be used in conjunction with the aperture stop for partially shading or light-reducing the center of the center area 54A of its distribution of amount of light, thereby to set the distribution of amount of light of FIG. 12, and no necessity exists for forming the aperture corresponding to its distribution of amount of light which should be set (three areas in which amount of light is enhanced), on this aperture stop.



In addition, in the above-mentioned second and fifth embodiments, at least one part of the optical system (4; 152 and 153) that is provided between the diffractive optical element to be arranged within the illumination system and the optical integrator (4; 152 and 153) may be assumed to be a zoom lens (a focal system), thereby making the size of three areas, in which the illumination light 1L on the pupil plane of the illumination system is distributed, variable. Further, one pair of the foregoing interval-variable prisms may be built in its optical system (4; 152 and 153).

Additionally, in the above-mentioned second and fifth embodiments, by means of the formation optical system (equivalent to the optical member), which is comprised of only a plurality of the diffractive optical elements that are arranged for replacement in the illumination system, or the formation optical system, which has its plurality of the diffractive optical elements and the optical system, in which at least one of the foregoing zoom lens and one pair of the prisms is built, combined, when the optical integrator is the fly eye lens 5, the intensity distribution of the illumination 1L on its incident plane is caused to change, and when the optical integrator is the inner-plane-reflection type integrator 151, the range of the incident angle of the illumination light 1L that enters its incident plane is caused to change, thereby allowing the distribution of amount of light (shape or size of the secondary light source) of the illumination light 1L on the pupil plane of the illumination system, i.e. the illumination condition of the reticle to be changed arbitrarily. At this time, a plurality of the diffractive optical element to be held in the revolver 24 are not limited only to the foregoing diffractive optical elements 21 and 22, and may include at least one out of the four diffractive optical elements to be used for, for example, each of the small  $\sigma$  illumination, the annular illumination, the bipolar illumination, and the tetra-polar illumination. In addition, its formation optical system and the foregoing aperture stop may be combined.

At this time, for example, one (including the foregoing diffractive optical element etc.) except the aperture stop out of the formation optical system may be arranged in the upstream side of the optical integrator (between the light source 1 and the optical integrator), and its aperture stop may be arranged in the downstream side of the optical integrator.

In addition, in the above-mentioned second, fourth, and fifth embodiments, the pattern being an object of transfer, is the pattern of the one directional high density contact hole (one directional high density contact hole); however the pattern, being an object of transfer, can be regarded as a pattern that is substantially isolated in one direction, and it is apparent that any pattern is acceptable so long as it is a pattern including the pattern to be periodically formed in the direction intersecting it (for example, orthogonal hereto).

Further, in the above-mentioned second, fourth, and fifth embodiments and its modified examples, three areas in which the amount of light is enhanced with the distribution of amount of light of the illumination light 1L on the pupil plane of the illumination light system 12, which is substantially conjugate with the pupil plane Q3 of the projection optical system PL, or its conjugate plane (or predetermined plane), are adapted to be arranged along a straight line, which is parallel to the periodical direction of the foregoing one directional high density pattern, on its predetermined plane, and passes through the optical axis of the illumination optical light system, however its three areas do not need always to be arranged on the identical straight line. For example, out of the three areas, at least one of the remaining two areas except the center area may be deviated from the above-mentioned straight line in the Y direction, and its two areas are caused to

differ from each other in the distances to the optical axis of the illumination system with regard to the Y direction light.

In addition, in the above-mentioned second, fourth, and fifth embodiments and its modified examples, the center area out of the foregoing three areas may be not only of circle shape but also of annular shape or of square frame shape; however its shape (distribution of amount of light) is not restricted hereto. That is, with its center area, similarly to the annulus etc. the amount of light of the center thereof may be set to be smaller than that of other part, and for example, it may be comprised of a plurality of the areas (its shape is arbitrary), each of which is separated from the other. At this time, its number or position of the plurality of the areas may be set so that the gravity center of amount of light of the center area approximately coincides with the optical axis of the illumination system, and for example, the number is preferably the total  $2n$  of  $n$  areas ( $n$  is a natural number) in which the center (gravity center) is out of the optical axis and the distances to the optical axis are approximately identical, and  $n$  areas which are symmetrically arranged to these  $n$  areas with regard to the optical axis. In addition, the plurality of the areas each of which is separated from the other in its center area may be arranged in a predetermined straight line that passes through the optical axis of the illumination system 12 on the foregoing predetermined plane, and, for example, may be arranged along the identical straight line, and for example, may be two areas to be arranged along the identical straight line. Further, with the plurality of the areas each of which is separated from the other in its center area, its array direction may be decided responding to the size of its center area (equivalent to the  $\sigma$  value), and it is preferable that its array direction is caused to approximately coincide with that (X direction) of the foregoing three areas, for example, when the size of the center area is relatively small, and conversely, it is preferable that its array direction is caused to be approximately orthogonal to that (X direction) of the foregoing three areas (that is, it is assumed to the Y direction).

Moreover, in the above-mentioned second, fourth, and fifth embodiments and its modified examples, while the positions of the remaining areas except the center area out of the foregoing three areas, i.e. the distances to the optical axis of the illumination system with regard to the direction (X direction) parallel to the periodical direction of the foregoing one directional high density pattern are kept approximately equal, they may be made variable responding to its pitch.

In addition, in each of the above-mentioned embodiments, the formation optical system to be employed for altering the illumination condition of the reticle is adapted to include a plurality of the diffractive optical elements; however instead of these diffractive optical elements, for example, a plurality of the lens elements having different aberrations may be employed for replacement. Further, in case of employing the first and second prisms 71 and 72 of which the periphery forms a cone, altering the interval of the prisms 71 and 72, i.e. the distance of each area, in which the intensity on the pupil plane of the illumination system 12 is enhanced, to the optical axis BX allows the shape of each area to be changed responding to its alteration. Thereupon, when its change quantity exceeds a predetermined allowable value, for example, the foregoing zoom lens, the foregoing cylindrical lens or the like may be employed, thereby to suppress (lessen) a change in its shape.

In addition, the projection exposure apparatus of FIG. 1 may employ a double integrator technique in which two optical integrators are arranged along the optical axis BX within the illumination system 12, and these two optical integrators differ from each other in its kind. Additionally, in the above-



mentioned embodiments, the distribution of amount of light of the illumination light on the pupil plane of the illumination system is enhanced in a plurality of the areas; however, for example, when the amount of light is reduced gradually, the so-called area in which the amount of light is enhanced points to the area in which the amount of light becomes equal to or more than a predetermined value.

Additionally, in each of the above-mentioned embodiments, in a case of employing vacuum ultra violent light having a frequency of, for example, less than 180 nm or something like it as the illumination 1L, the optical material of the refractive member such as the substrate of the diffractive optical elements 21, 22, 22A, and 22B, the glass substrate composing the reticles R and RA, and the lens composing the projection optical system PL is preferably formed of the material selected from a group of fluoride crystal such as quartzite ( $\text{CaF}_2$ ), magnesium fluoride, and lithium fluoride, quartz glass having fluorine and hydrogen doped, quartz glass of which the structure determining temperature is 1200 K or less, and yet of which the hydroxyl group concentration is 1000 ppm or more (for example, disclosed in Japanese Patent No. 2770224 publication by filed this applicant), quartz glass of which the structure determining temperature is 1200 K or less, and yet of which the hydrogen molecule concentration is  $1 \times 10^{17}$  molecules/cm<sup>3</sup> or more, quartz glass of which the structure determining temperature is 1200 K or less, and yet of which the base concentration is 500 ppm or less, and quartz glass of which the structure determining temperature is 1200 K or less, of which the hydrogen molecule concentration is  $1 \times 10^{17}$  molecules/cm<sup>3</sup> or more and yet of which the chlorine concentration is 50 ppm or less (For example, disclosed in Japanese Patent No. 2936138 publication by filed this applicant (corresponding to U.S. Pat. No. 5,908,482)). On the other hand, in case of employing the ArF excimer laser beam, the KrF excimer laser beam or the like, it is possible to employ the synthesized quarts in addition to each of the above-mentioned substances as its optical material.

Next, one example of the process for fabricating the semiconductor device using the projection exposure apparatus of the above-mentioned embodiments will be explained with a reference to FIG. 24.

FIG. 24 shows an example of the process of fabricating the semiconductor device, and in FIG. 24, at first, a wafer W is fabricated from a silicon semiconductor etc. Thereafter, a photo resist is coated on the wafer W (step S10), and in a next step S12, the reticle R1 is loaded onto the reticle stage of the projection exposure apparatus of the above-mentioned embodiments (FIG. 1A or FIG. 18) to transfer (expose) the pattern (denoted by a code A) of the reticle R1 (for example, the reticle R of FIG. 2) to the entire shot areas SE on the wafer WE with the scan exposure system. Additionally, the wafer W is for example, a wafer having a diameter of 300 mm (12-inch wafer), the shot area SE of which the width is 25 mm in the non-scan direction and 33 mm in the scan direction respectively, is of rectangular area. Next, in a step S14, by performing the developing, the etching, and the ion implantation, a predetermined pattern is formed in each shot area of the wafer W.

Next, in a step S16, the photo resist is coated on the wafer W (step S10), and thereafter, in a next step S18, the reticle R2 (for example, the reticle RA of FIG. 11A is loaded onto the reticle stage of the projection exposure apparatus of the above-mentioned embodiments (FIG. 1A or FIG. 18) to transfer (expose) the pattern (denoted by a code B) of the reticle R2 (for example, the reticle R of FIG. 2) to the entire shot areas SE on the wafer WE with the scan exposure system. In addition hereto, in a step S20, by performing the developing, the

etching, and the ion implantation, a predetermined pattern is formed in each shot area of the wafer W.

The exposure step to the pattern formation step described above (step S16 to step S20) are repeated by the number of times necessary for fabricating the desired semiconductor device. In addition hereto, through the dicing step of cutting each chip CP off the wafer W one by one (step S22), the bonding step, the packaging step (step S24) etc. the semiconductor device SP is fabricated as a product.

In addition, the illumination system to be composed of a plurality of lens and the projection optical system are built in the main frame of the exposure apparatus to make an optical adjustment, and the reticle stage and the wafer stage to be composed of a number of machine parts are mounted on the main frame of the exposure apparatus to connect the wiring cables and the pipes, and to further make a comprehensive adjustment (electric adjustment, operational confirmation, etc.), thereby enabling the projection exposure apparatus of the above-mentioned embodiments to be manufactured. Additionally, the projection exposure apparatus is desirably manufactured in a clean room in which the temperature and the cleanliness are controlled.

In addition, needless to say, the present invention can apply not only to the case of making an exposure with scan exposure type of the projection exposure apparatus, but also to the case of making an exposure with the batch exposure type of the projection exposure apparatus such as the stepper. The scale factor of the projection optical system in these cases may be a one-to-one factor, and may be an enlarged scale factor. Further, the present invention can apply, for example, to the case of making an exposure with the liquid-penetration type of the projection exposure apparatus disclosed in international Publication Number (WO) 99/49504 etc. The liquid-penetration type of the projection exposure apparatus may be of the scan exposure technique employing the reflective/refractive type of the projection optical system, or may be of the static exposure technique employing the projection optical system of which the projection scale factor is  $\frac{1}{8}$ . In the latter liquid-penetration type of the projection exposure apparatus, so as to form a large pattern on the substrate, the step and stitch technique explained in the above-mentioned embodiment is preferably employed.

Additionally, the application of the liquid-penetration type of the projection exposure apparatus of the above-mentioned embodiment is not limited to that of the exposure apparatus for fabricating the semiconductor element, and for example, it can be widely applied for the exposure apparatus for the display apparatus such as the liquid display element or the plasma display, which is formed on the angular glass plate, or the exposure apparatus for fabricating the various devices such as the imaging element (CCD etc.), the micro-machine, the thinly coated magnetic head, and the DNA chip. Further, the present invention can apply to the exposure step (exposure apparatus) in fabricating the reticle having the reticle pattern of the various devices using the photolithography step.

The aforementioned disclosures of all the United States patents etc. are incorporated herein by reference, as far as the national laws of the designated states designated in the present international application or the elected states elected in the present international application permit.

The present invention is not limited to the above-mentioned embodiments, and the invention may, as a matter of course, be embodied in various forms without departing from the gist of the present invention. Furthermore, the entire disclosure of Japanese Patent Applications 2003-105920 filed on Apr. 9, 2003, 2003-299628 filed on Aug. 25, 2003, 2003-307806 filed on Aug. 29, 2003, 2003-329194 filed on Sep. 19,



45

2003, 2003-329309 filed on Sep. 22, 2003 including description, claims, drawings and abstract are incorporated herein by reference in its entirety.

## INDUSTRIAL APPLICABILITY

In addition, in accordance with the method of fabricating the device, the device including the various patterns can be manufactured with a high precision and yet with a high throughput.

In addition, in the method of fabricating the device of the present invention, when the distribution of amount of light on a predetermined plane with regard to the illumination system is set so that the amount of light is enlarged in a predetermined three areas, the device including the one-direction mass pattern can be fabricated at a high precision.

The invention claimed is:

1. An exposure method for illuminating a pattern with an illumination system to expose a substrate through a projection system, the method comprising:

illuminating the pattern with illumination light having a light amount distribution which is set such that an amount of light is larger in each of two first areas than in a third area and an amount of light is larger in each of two second areas than in the third area, the third area being an area other than the two first areas and the two second areas on a pupil plane of the illumination system, the two first areas being in line so that a first straight line interconnecting the two first areas passes through an optical axis and the two first areas are located approximately at the same distance from the optical axis along the first straight line, the two second areas being in line so that a second straight line orthogonal to the first straight line at the optical axis interconnects the two second areas and passes through the optical axis and the two second areas are located approximately at the same distance from the optical axis along the second straight line; and

projecting an image of the illuminated pattern onto the substrate by the projection system,

wherein the light amount distribution is generated by a formation optical system which is provided on an incident side of the pupil plane in the illumination system, the third area includes the optical axis on the pupil plane, each of the two first areas is surrounded by the third area and each of the two second areas is surrounded by the third area,

distances from the two second areas to the optical axis are smaller than distances from the two first areas to the optical axis,

an amount of light is smaller in each of the two second areas than in each of the two first areas, and

the first straight line passes through only the two first areas and the third area without passing through any of the second areas.

2. The exposure method according to claim 1, wherein the two first areas are approximately symmetrically arranged with respect to the optical axis on the pupil plane.

3. The exposure method according to claim 2, wherein the two first areas are arranged on the first straight line passing through the optical axis and being parallel to a first direction on the pupil plane.

4. The exposure method according to claim 2, wherein the two second areas are approximately symmetrically arranged with respect to the optical axis on the pupil plane.

46

5. The exposure method according to claim 4, wherein a size of each of the two second areas is smaller than a size of each of the two first areas.

6. The exposure method according to claim 1, wherein the illumination light distributed in the two first areas is substantially linearly polarized light.

7. The exposure method according to claim 6, wherein a direction of the linearly polarized light approximately coincides with a tangent direction.

8. The exposure method according to claim 1, wherein the light amount distribution is used in an illumination for the pattern which is periodical in one of two directions orthogonal to each other and isolated in the other of the two directions, and the one of the two directions orthogonal to each other corresponds to a first direction.

9. A device manufacturing method, comprising: exposing the substrate by the exposure method as recited in claim 1;

developing the exposed substrate; and processing the developed substrate.

10. An exposure apparatus, comprising:

an illumination system which illuminates a pattern; a projection system which projects the pattern onto a substrate; and

a formation optical system which changes a light amount distribution of illumination light on a pupil plane of the illumination system and which generates a light amount distribution in which an amount of light is larger in each of two first areas than in a third area and an amount of light is larger in each of two second areas than in the third area, the third area being an area other than the two first areas and the two second areas on the pupil plane of the illumination system, the two first areas being in line so that a first straight line interconnecting the two first areas passes through an optical axis and the two first areas are located approximately at the same distance from the optical axis along the first straight line, the two second areas being in line so that a second straight line orthogonal to the first straight line at the optical axis interconnects the two second areas and passes through the optical axis and the two second areas are located approximately at the same distance from the optical axis along the second straight line,

wherein the formation optical system is provided on an incident side of the pupil plane in the illumination system,

the third area other than the two first areas and the two second areas includes the optical axis on the pupil plane, each of the two first areas is surrounded by the third area and each of the second areas is surrounded by the third area,

distances from the two second areas to the optical axis are smaller than distances from the two first areas to the optical axis, and an amount of light is smaller in each of the two second areas than in each of the two first areas, and

the first straight line passes through only the two first areas and the third area without passing through any of the second areas.

11. The exposure apparatus according to claim 10, wherein the two first areas are approximately symmetrically arranged with respect to the optical axis on the pupil plane.

12. The exposure apparatus according to claim 11, wherein the two first areas are arranged on the first straight line passing through the optical axis and are parallel to a first direction on the pupil plane.



13. The exposure apparatus according to claim 11, wherein the two second areas are approximately symmetrically arranged with respect to the optical axis on the pupil plane.
14. The exposure apparatus according to claim 13, wherein a size of each of the two second areas is smaller than a size of each of the two first areas. 5
15. The exposure apparatus according to claim 14, wherein the formation optical system can change the light amount distribution by at least one of movement of an optical element and exchange of optical elements. 10
16. The exposure apparatus according to claim 10, wherein the illumination light distributed in the first areas is substantially linearly polarized light.
17. The exposure apparatus according to claim 16, wherein a direction of the linearly polarized light approximately coincides with a tangent direction. 15
18. The exposure apparatus according to claim 10, wherein the light amount distribution in which the amount of light is made larger in the two first areas and the two second areas is used in an illumination for the pattern which is periodical in one of two directions orthogonal to each other and that is isolated in the other of the two directions, and the one of the two directions orthogonal to each other corresponds to a first direction. 20 25
19. A device manufacturing method, comprising:  
 exposing the substrate with the exposure apparatus as recited in claim 10;  
 developing the exposed substrate; and  
 processing the developed substrate. 30

\* \* \* \* \*