



US008700059B1

(12) **United States Patent**
Vivanco et al.

(10) **Patent No.:** **US 8,700,059 B1**
(45) **Date of Patent:** **Apr. 15, 2014**

(54) **SELECTING A CARRIER**

(56) **References Cited**

(75) Inventors: **Daniel Vivanco**, Sterling, VA (US);
Krishna Sitaram, Chantilly, VA (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **Sprint Spectrum L.P.**, Overland Park,
KS (US)

2006/0128392	A1*	6/2006	Turina et al.	455/452.1
2011/0105155	A1	5/2011	Bienas et al.	
2011/0269447	A1	11/2011	Bienas et al.	
2011/0306363	A1*	12/2011	Wang et al.	455/456.1
2012/0034922	A1*	2/2012	Jones et al.	455/438

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 38 days.

* cited by examiner

Primary Examiner — Kamran Afshar
Assistant Examiner — Farideh Madani

(21) Appl. No.: **13/456,696**

(57) **ABSTRACT**

(22) Filed: **Apr. 26, 2012**

In systems and methods of selecting a carrier, tracking area update messages for a wireless device communicating over a first carrier are monitored to determine that a number of tracking update messages meets a traffic threshold. A first tracking area configuration for the first carrier and a second tracking area configuration for a second carrier are determined, and a location and a mobility of the wireless device relative to the first tracking area configuration and the second tracking area configuration are ascertained. Based on the first tracking area configuration, the second tracking area configuration, the determined location, and the determined mobility a handover of the wireless device from the first carrier to the second carrier is performed.


(51) **Int. Cl.**
H04W 4/00 (2009.01)

(52) **U.S. Cl.**
USPC **455/456.1**; 455/453; 455/435.2

(58) **Field of Classification Search**
USPC 455/456.1, 453, 452.1, 435.2, 436–444;
370/331–332

See application file for complete search history.

14 Claims, 7 Drawing Sheets



↶ 100




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

1**SELECTING A CARRIER**

TECHNICAL BACKGROUND

A wireless device can enter into a lower power state, such as an idle mode or a sleep mode, in which the wireless device is not in continuous communication with an access node. A communication system maintains a record of a recent location of the wireless device in an idle state in order to route paging messages to the wireless device if data is sent to the wireless device. One method of maintaining a record of a recent location of a wireless device is by use of a tracking area. A tracking area comprises a group of access nodes which are associated with a tracking area code. When a message such as data arrives for a wireless device in an idle mode, a first paging message is sent to the access node most recently in communication with the wireless device. When the wireless device does not respond to the first paging message within a predetermined period of time, a second paging message is sent to all of the access nodes in the tracking area.

OVERVIEW

In an embodiment, tracking area update messages for a wireless device communicating over a first carrier are monitored to determine that a number of tracking update messages meets a traffic threshold. A first tracking area configuration for the first carrier and a second tracking area configuration for a second carrier are determined, and a location and a mobility of the wireless device relative to the first tracking area configuration and the second tracking area configuration are ascertained. Based on the first tracking area configuration, the second tracking area configuration, the determined location, and the determined mobility a handover of the wireless device from the first carrier to the second carrier is performed.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates an exemplary communication system to select a carrier.

FIG. 2 illustrates exemplary tracking area configurations.

FIG. 3 illustrates an exemplary method of selecting a carrier.

FIG. 4 illustrates another exemplary communication system to select a carrier.

FIG. 5 illustrates another exemplary method of selecting a carrier.

FIG. 6 illustrates additional exemplary tracking area configurations.

FIG. 7 illustrates an exemplary processing node.

DETAILED DESCRIPTION

In systems and method of selecting a carrier, tracking area update messages for a wireless device communicating over a first carrier are monitored to determine that a number of tracking update messages meets a traffic threshold. A first tracking area configuration for the first carrier and a second tracking area configuration for a second carrier are determined. A location and a mobility of the wireless device relative to the first tracking area configuration and the second tracking area configuration are ascertained. Based on the first tracking area configuration, the second tracking area configuration, the determined location, and the determined mobility a handover of the wireless device from the first carrier to the second carrier is performed. In an embodiment, based on a determination that the wireless device can communicate over

2

the first carrier and the second carrier, the first tracking area configuration is determined for the first carrier and the second tracking area configuration is determined for the second carrier.

FIG. 1 illustrates an exemplary communication system 100 to select a carrier comprising wireless device 102, access node 104, and communication network 106. Examples of wireless device 102 can include a cell phone, a smart phone, a computing platform such as a laptop, palmtop, or tablet, a personal digital assistant, or an internet access device, including combinations thereof. Wireless device 102 can communicate with access node 104 over communication links 108A and 108B.

Access node 104 is a network node capable of providing wireless communications to wireless device 102, and can be, for example, a base transceiver station, a radio base station, an eNodeB device, or an enhanced eNodeB device. Communication links 108A and 108B can be, for example, a first carrier and a second carrier, over which access node 104 and wireless device 102 can communicate. Access node 104 is also in communication with communication network 106 over communication link 110.

Communication network 106 can be a wired and/or wireless communication network, and can comprise processing nodes, routers, gateways, and physical and/or wireless data links for carrying data among various network elements, including combinations thereof, and can include a local area network, a wide area network, and an internetwork (including the Internet). Communication network 106 may also comprise base stations, wireless communication nodes, telephony switches, internet routers, network gateways, computer systems, communication links, or some other type of communication equipment, and combinations thereof. Wired network protocols that may be utilized by communication network 106 comprise Ethernet, Fast Ethernet, Gigabit Ethernet, Local Talk (such as Carrier Sense Multiple Access with Collision Avoidance), Token Ring, Fiber Distributed Data Interface (FDDI), and Asynchronous Transfer Mode (ATM). Wireless network protocols may comprise code division multiple access (CDMA) 1xRTT, Global System for Mobile communications (GSM), Universal Mobile Telecommunications System (UMTS), High-Speed Packet Access (HSPA), Evolution Data Optimized (EV-DO), EV-DO rev. A, Third Generation Partnership Project Long Term Evolution (3GPP LTE), and Worldwide Interoperability for Microwave Access (WiMAX).

Communication links 108A, 108B and 110 can be wired or wireless communication links. Wired communication links can be, for example, twisted pair cable, coaxial cable or fiber optic cable, or combinations thereof. Wireless communication links can be a radio frequency, microwave, infrared, or other similar signal, and can use a suitable communication protocol, for example, Global System for Mobile telecommunications (GSM), Code Division Multiple Access (CDMA), Worldwide Interoperability for Microwave Access (WiMAX), or Long Term Evolution (LTE), or combinations thereof. Other wireless protocols can also be used.

Other network elements may be present in the communication system 100 to facilitate wireless communication but are omitted for clarity, such as base stations, base station controllers, gateways, mobile switching centers, dispatch application processors, and location registers such as a home location register or visitor location register. Furthermore, other network elements may be present to facilitate communication between access node 104 and communication network 106 which are omitted for clarity, including additional

processing nodes, routers, gateways, and physical and/or wireless data links for carrying data among the various network elements.

In an embodiment, tracking area update messages for wireless device **102** communicating over a first carrier **108A** are monitored to determine that a number of tracking update messages meets a traffic threshold. A first tracking area configuration for the first carrier **108A** and a second tracking area configuration for a second carrier **108B** are determined, and a location and a mobility of wireless device **102** relative to the first tracking area configuration and the second tracking area configuration are ascertained. Based on the first tracking area configuration, the second tracking area configuration, the determined location, and the determined mobility a handover of wireless device **102** from first carrier **108A** to second carrier **108B** is performed

A wireless device such as wireless device **102** can enter into a lower power state, such as an idle mode or a sleep mode, in which wireless device **102** is not in continuous communication with access node **104**. Nevertheless, communication system **100** maintains a record of a recent location of wireless device **102** in order to route paging messages to wireless device **102**, for example, if data is sent to wireless device **102**. One method of maintaining a record of a recent location of wireless device **102** is by use of a tracking area. A tracking area consists of a group of access nodes which are associated with a tracking area code. In an embodiment, communication network **100** maintains a record of the access node that wireless device **102** communicated with most recently, as well as the associated tracking area code, and thus the associated tracking area, of that access node. Wireless device **102** can be considered to be within the tracking area associated with the most recent access node. When a message such as data arrives for wireless device **102**, a paging message is sent to the access node most recently in communication with wireless device **102**. When wireless device **102** does not respond to the paging message within a predetermined period of time, a paging message is sent to the access nodes in the tracking area.

Typically, when a wireless device moves from a first tracking area to a second tracking area, the wireless device sends a tracking area update (TAU) message to update communication system **100** of its new location. Referring to FIG. 2, when, for example, wireless device **102** moves from tracking area **204** to tracking area **208** (for example, if wireless device **102** is handed over from access node **104** associated with tracking area **204** to access node **202** associated with tracking area **208**), then wireless device **102** will send a TAU to communication system **100** through access node **202**. If wireless device **102** enters an idle mode subsequent to its handover to access node **202**, when a message arrives for wireless device **102** communication system **100** can use the tracking area code of tracking area **208** to route a paging message to wireless device **102**. (While two access nodes **104** and **202** are illustrated in FIG. 2 for simplicity, it will be understood that a tracking area typically comprises a plurality of access nodes. In addition, while tracking areas in FIG. 2 are illustrated as circular, it will be understood that this is merely an illustration for simplicity of explanation and that tracking areas and tracking area configurations may vary according to numerous factors, including variations in geography and network topology.)

In a communication system which uses a plurality of carriers, different tracking area configurations may be associated with different carriers. For example, tracking areas **204** and **208** may be associated with a first carrier, and tracking area **206** may be associated with a second carrier. Tracking area configuration can affect a volume of TAUs in communication

network **100**. For example, when wireless device **102** is mobile and using the first carrier, given the size of tracking areas **204** and **208**, wireless device **102** will send TAUs more frequently as it moves among tracking areas **204** and **208** associated with the first carrier. As another example, when wireless device **102** is relatively stationary in a border region (for example, at the edges) of two tracking areas **204** and **208**, it may be determined that wireless device **102** is moving repeatedly between the two tracking areas, and wireless device **102** will send a TAU each time it is determined to move to a new tracking area. As the number of wireless devices in communication with communication system **100** increase, TAU message volume can increase, especially if the wireless devices are highly mobile, or if they are in or near a border region of two or more tracking areas. As the volume of TAU increases, uplink congestion in both air interfaces and the communication network may result, as well as an increase in call controller processing. Additionally, the more TAUs a wireless device is required to send, the greater the drain on its battery. If wireless device **102** were to change from using the first carrier, associated with tracking areas **204** and **208**, to using the second carrier, associated with tracking area **206**, wireless device **102** would be required to send fewer TAUs.

FIG. 3 illustrates an exemplary method of selecting a carrier. In operation **302**, tracking area update messages are monitored to determine that a number of tracking area update messages meets a traffic threshold. For example, TAUs sent by wireless device **102** can be monitored, and it can be determined that the number of TAUs sent by wireless device **102** meet a traffic threshold. This can be, for example, because wireless device **102** is using a first carrier associated with tracking areas **204** and **208** and is highly mobile, or because wireless device **102** is located near the border area between tracking areas **204** and **208**.

In operation **304**, a first tracking area configuration for the first carrier and a second tracking area configuration for a second carrier are determined. For example, a configuration of tracking areas **204** and **208** can be determined as the first tracking area configuration, and further a tracking area configuration of tracking area **206** (and other tracking areas) associated with a second carrier can also be determined.

In operation **306**, a location and a mobility of the wireless device relative to the first tracking area configuration and the second tracking area configuration can be ascertained. For example, the location of wireless device **102** can be determined to be near the border region of tracking areas **204** and **208**, and a mobility of wireless device **102** can be determined to be relatively stationary near the border region. The location of wireless device **102** can also be determined to be within, and not near a border of, tracking area **206**. As another example, a mobility of wireless device **102** can also be determined to indicate that wireless device **102** is mobile. Such mobility can indicate, for example, that when wireless device **102** uses the first carrier, wireless device **102** will be required to send more TAUs than if wireless device were using the second carrier (associated with tracking area **206**). In operation **308**, based on the first tracking area configuration, the second tracking area configuration, the determined location, and the determined mobility, a handover is performed to hand over the wireless device from the first carrier to the second carrier. For example, wireless device **102** can be handed over from the first carrier associated with tracking areas **204** and **208** to the second carrier associated with tracking area **206**.

FIG. 4 illustrates another exemplary communication system **400** to select a carrier comprising wireless device **402**, access nodes **404**, **406** and **408**, carrier selection node **410**, and communication network **412**. Examples of wireless

5

device **402** can include a cell phone, a smart phone, a computing platform such as a laptop, palmtop, or tablet, a personal digital assistant, or an internet access device, including combinations thereof.

Access nodes **404**, **406** and **408** are network nodes capable of providing wireless communications to wireless device **402**, and can be, for example, a base transceiver station, a radio base station, an eNodeB device, or an enhanced eNodeB device. Communication links **414A**, **416A**, and **418A** can be, for example, a first carrier, and communication links **414B**, **416B**, and **418B** can be, for example, a second carrier. Wireless device **402** can communicate with access nodes **404**, **406** and **408** over communication links **414A** and **414B**, **426A** and **416B**, and **418A** and **418B**, respectively. Access nodes **404**, **406**, and **408** are also in communication with carrier selection node **410** over communication links **420**, **422** and **424**.

Carrier selection node **410** is a processing node configured to select a carrier over which wireless device **402** can communicate with access nodes **404**, **406**, and/or **408**. Carrier selection node **410** can comprise a processor and associated circuitry to execute or direct the execution of computer-readable instructions for managing content, and can retrieve and execute software from storage, which can include a disk drive, flash drive, memory circuitry, or some other memory device, and which can be local or remotely accessible. The software comprises computer programs, firmware, or some other form of machine-readable instructions, and may include an operating system, utilities, drivers, network interfaces, applications, or some other type of software, including combinations thereof. Carrier selection node **410** can communicate with communication network **412** over communication link **426**. Examples of carrier selection node can include, for example, a mobility management entity (MME), a serving gateway (S-GW), a mobile switching center (MSC), or other similar network node. The functionality of carrier selection node **410** can also be incorporated into a network node such as one of the aforementioned network nodes or another network node.

Communication network **412** can be a wired and/or wireless communication network, and can comprise processing nodes, routers, gateways, and physical and/or wireless data links for carrying data among various network elements, including combinations thereof, and can include a local area network, a wide area network, and an internetwork (including the Internet). Communication network **412** may also comprise base stations, wireless communication nodes, telephony switches, internet routers, network gateways, computer systems, communication links, or some other type of communication equipment, and combinations thereof. Communication network **412** can use wired and/or wireless network protocols analogous to communication network **106**.

Communication links **414A**, **414B**, **416A**, **416B**, **418A**, **418B**, **420**, **422**, **424** and **426** can be wired or wireless communication links. Wired communication links can be, for example, twisted pair cable, coaxial cable or fiber optic cable, or combinations thereof. Wireless communication links can be a radio frequency, microwave, infrared, or other similar signal, and can use a suitable communication protocol, for example, Global System for Mobile telecommunications (GSM), Code Division Multiple Access (CDMA), Worldwide Interoperability for Microwave Access (WiMAX), or Long Term Evolution (LTE), or combinations thereof. Other wireless protocols can also be used.

Other network elements may be present in the communication system **400** to facilitate wireless communication but are omitted for clarity, such as base stations, base station

6

controllers, gateways, mobile switching centers, dispatch application processors, and location registers such as a home location register or visitor location register. Furthermore, other network elements may be present to facilitate communication between access nodes **404**, **406** and **408**, carrier selection node **410**, and communication network **412** which are omitted for clarity, including additional processing nodes, routers, gateways, and physical and/or wireless data links for carrying data among the various network elements.

FIG. **5** illustrates another exemplary method of selecting a carrier. In operation **502**, tracking area update messages for a wireless device communicating over a first carrier are monitored to determine that a number of tracking update messages meets a traffic threshold. For example, wireless device **402** may move from a first tracking area associated with access node **404** to a second tracking area associated with access node **406**. Referring to FIG. **6**, as an example, when wireless device **302** moves from tracking area **602** to tracking area **604**, wireless device **302** sends a TAU to communication system **400**.

Returning to FIG. **5**, in operation **504**, a battery level of wireless device **402** and a node processor utilization level of a processing node are monitored. For example, a battery level of wireless device **402** can be monitored to determine whether it meets a battery threshold. Additionally, or alternatively, a processor of a processing node, such as an MME or other node in communication network **412**, or of carrier selection node **410**, can be monitored to determine if the processor utilization level meets a processor utilization threshold. The battery level of wireless device **402** and the node processor utilization level can provide an indication of a number of TAUs in communication system **400**. The battery level of wireless device **402**, for example, can be drained more rapidly when wireless device **402** sends frequent TAUs. Similarly, the processor utilization level of a processing node can increase as the number of TAUs in communication system **400** increases.

In operation **506**, it is determined whether a number of tracking area update messages meets a traffic threshold. The battery level of wireless device **402** and/or the node processor utilization level can also be used in the determination of whether a number of TAUs meets a traffic threshold. That is, in an embodiment the determined number of TAUs and the traffic threshold can also take into account not only a number of TAUs, but also the battery level of wireless device **402** and/or the node processor utilization level. In an embodiment, the number of TAUs and the battery levels of a plurality of wireless devices in communication with access node **404**, **406** and/or **408** are monitored.

When the number of TAUs does not meet the traffic threshold (operation **506-NO**) then monitoring of TAUs is continued. When the number of traffic area updates meets the traffic threshold (operation **506-YES**), the carrier capabilities of wireless device **402** are determined. For example, it can be determined that wireless device **402** can use a first carrier (used by communication links **414A**, **416A**, and **418A**, for example) and a second carrier (used, for example, by communication links **414B**, **416B**, and **418B**).

Based on the determined carrier capabilities of wireless device **402**, tracking area configurations of the carriers are determined (operation **510**). For example, when wireless device **402** can use a first carrier and a second carrier, tracking area configurations associated with the first carrier and the second carrier can be determined. For example, tracking areas **602**, **604** and **606** illustrated in FIG. **6** can be associated with the first carrier, and tracking areas **608** and **610** can be associated with the second carrier. Further, the configurations of

these tracking areas, illustrated in FIG. 6, can be determined based at least in part on the determined carrier capabilities of wireless device 402. While tracking areas in FIG. 6 are illustrated as circular, it will be understood that this is merely an illustration for simplicity of explanation and that tracking areas and tracking area configurations may vary according to numerous factors, including variations in geography and network topology.

Returning to FIG. 5, in operation 512 a location and a mobility of the wireless device can be ascertained. The location and the mobility of the wireless device can be determined, for example, based on GPS information obtained by wireless device 402, or it can be obtained by access node triangulation of the location and mobility of wireless device 402. The location and the mobility of the wireless device can be ascertained relative to the first tracking area configuration and the second tracking area configuration. For example, the location of wireless device 402 can be determined to be near the border region between tracking areas 602 and 604 (FIG. 6) which are associated with the first carrier, such as location 612. Similarly, the location of wireless device 402 can be determined to be near the border region between tracking areas 608 and 610 which are associated with the second carrier, such as location 614. Additionally, a mobility of wireless device 402 can be determined. For example, wireless device 402 can be determined to be relatively stationary in a border region at location 612, or at location 614. A mobility of wireless device 402 can also be determined to indicate that wireless device 402 is mobile. Such mobility can indicate, for example, that when wireless device 402 uses the first carrier, wireless device 402 will be required to send more TAUs than if wireless device were using the second carrier (associated with tracking areas 608 and 610). While location 612 is near a border region between tracking areas 602 and 604, location 612 is within, and not near an edge of, tracking area 608. In addition, while location 614 is near a border region between tracking areas 608 and 610, location 614 is within, and not near an edge of, tracking area 604.

In operation 514 (FIG. 5), a handover is performed of wireless device 402 from the first carrier to the second carrier based on the first tracking area configuration, the second tracking area configuration, the determined location, and the determined mobility. For example, when it is determined that wireless device 402 can use both the first carrier and the second carrier, that wireless device 402 is at location 612, and that wireless device 402 is relatively stationary at location 612, then a handover can be performed to hand over wireless device 402 from the first carrier to the second carrier.

Thereafter, the number of traffic area updates, the battery level of wireless device 402, and the node processor utilization can be further monitored (operation 516), and it may be determined that a number of TAUs meets a traffic threshold when wireless device 402 is using the second carrier (operation 518). For example, referring to FIG. 6, wireless device 402 may have moved to location 614, which is near a border region of traffic areas 608 and 610, which are associated with the second carrier. Location 614 is also within, and not near an edge of, tracking area 604.

Returning to FIG. 5, when the number of TAUs does not meet a traffic threshold (operation 518-NO), then monitoring of the number of traffic area updates, the battery level of wireless device 402, and the node processor utilization can continue. When the number of TAUs meets a traffic threshold (operation 518-YES), a location and mobility of wireless device 402 can be determined. The location and mobility of the wireless device can be determined relative to the first and second tracking area configurations. For example, the loca-

tion of wireless device 402 can be determined to be in the border region of traffic areas 608 and 610 (FIG. 6), and within tracking area 604.

In operation 522 (FIG. 5), based on the first tracking area configuration, the second tracking area configuration, the determined location, and the determined mobility, a handover is performed to hand over the wireless device from the second carrier to the first carrier. For example, wireless device 402 can be handed over from the second carrier associated with tracking areas 608 and 610 (FIG. 6) to the second carrier associated with tracking area 604.

FIG. 7 illustrates an exemplary processing node comprising communication interface 702, user interface 704, and processing system 706 in communication with communication interface 702 and user interface 704. Processing node 700 is capable of selecting a carrier. Processing system 706 includes storage 708, which can comprise a disk drive, flash drive, memory circuitry, or other memory device. Storage 708 can store software 710 which is used in the operation of the processing node 700. Storage 708 may include a disk drive, flash drive, data storage circuitry, or some other memory apparatus. Software 710 may include computer programs, firmware, or some other form of machine-readable instructions, including an operating system, utilities, drivers, network interfaces, applications, or some other type of software. Processing system 706 may include a microprocessor and other circuitry to retrieve and execute software 710 from storage 708. Processing node 700 may further include other components such as a power management unit, a control interface unit, etc., which are omitted for clarity. Communication interface 702 permits processing node 700 to communicate with other network elements. User interface 704 permits the configuration and control of the operation of processing node 700.

An example of processing node 700 includes carrier selection node 410. Processing node 700 can also be an adjunct or component of a network element, such as an element of access node 104, 404, 406 or 408. Processing node 700 can also be another network element in a communication system.

The exemplary systems and methods described herein can be performed under the control of a processing system executing computer-readable codes embodied on a computer-readable recording medium or communication signals transmitted through a transitory medium. The computer-readable recording medium is any data storage device that can store data readable by a processing system, and includes both volatile and nonvolatile media, removable and non-removable media, and contemplates media readable by a database, a computer, and various other network devices.

Examples of the computer-readable recording medium include, but are not limited to, read-only memory (ROM), random-access memory (RAM), erasable electrically programmable ROM (EEPROM), flash memory or other memory technology, holographic media or other optical disc storage, magnetic storage including magnetic tape and magnetic disk, and solid state storage devices. The computer-readable recording medium can also be distributed over network-coupled computer systems so that the computer-readable code is stored and executed in a distributed fashion. The communication signals transmitted through a transitory medium may include, for example, modulated signals transmitted through wired or wireless transmission paths.

The above description and associated figures teach the best mode of the invention. The following claims specify the scope of the invention. Note that some aspects of the best mode may not fall within the scope of the invention as specified by the claims. Those skilled in the art will appreciate that the fea-

tures described above can be combined in various ways to form multiple variations of the invention. As a result, the invention is not limited to the specific embodiments described above, but only by the following claims and their equivalents.

What is claimed is:

1. A method of selecting a carrier, comprising:
monitoring tracking area update messages for a wireless device communicating over a first carrier and a processor utilization of a carrier selection node; determining that a number of tracking area update messages meets a traffic threshold based on the number of tracking area update messages and the processor utilization of the carrier selection node; determining a first tracking area configuration for the first carrier and a second tracking area configuration for a second carrier; ascertaining a location and a mobility of the wireless device based on the first tracking area configuration and the second tracking area configuration; and performing a handover of the wireless device from the first carrier to the second carrier based on the first tracking area configuration, the second tracking area configuration, the ascertained location, and the ascertained mobility.

2. The method of claim **1**, wherein determining a first tracking area configuration further comprises: determining that the wireless device is configured to communicate over the first carrier and the second carrier; and determining a first tracking area configuration for the first carrier and a second tracking area configuration for the second carrier based on the determination that the wireless device is configured to communicate over the first carrier and the second carrier.

3. The method of claim **1**, further comprising: monitoring a battery level of the wireless device; and determining that the number of tracking area update messages meets the traffic threshold based on the number of tracking area update messages, the processor utilization of the carrier selection node, and the battery level of the wireless device.

4. The method of claim **1**, wherein the first and second tracking area configurations each comprise a geographic location of at least one access node using the first and second carriers, respectively.

5. The method of claim **1**, wherein the first and second tracking area configurations each comprise a coverage area indicated by a respective first and second tracking area identity.

6. The method of claim **1**, wherein the wireless device is in an idle mode when the wireless device is in communication with the first carrier and the second carrier.

7. The method of claim **1**, further comprising: determining that a second number of tracking area update messages meets the traffic threshold based on the second number of tracking area update messages and the processor utilization of the carrier selection node; re-ascertaining the location and the mobility of the wireless device based on the first tracking area configuration and the second tracking area configuration; and performing a handover of the wireless device from the second carrier to the first carrier based on the first tracking area configuration, the second tracking area configuration, the re-ascertained location, and the re-ascertained mobility.

8. A system for selecting a carrier, comprising: a carrier selection node configured to: monitor tracking area update messages for a wireless device communicating over a first carrier and a processor utilization of the carrier selection node; determine that a number of tracking area update messages meets a traffic threshold based on the number of tracking area update messages and the processor utilization of the carrier selection node; determine a first tracking area configuration for the first carrier and a second tracking area configuration for a second carrier; ascertain a location and a mobility of the wireless device based on the first tracking area configuration and the second tracking area configuration; and perform a handover of the wireless device from the first carrier to the second carrier based on the first tracking area configuration, the second tracking area configuration, the ascertained location, and the ascertained mobility.

9. The system of claim **8**, wherein the carrier selection node is further configured to: determine that the wireless device is configured to communicate over the first carrier and the second carrier; and determine the first tracking area configuration for the first carrier and the second tracking area configuration for the second carrier based on the determination that the wireless device is configured to communicate over the first carrier and the second carrier.

10. The system of claim **8**, wherein the carrier selection node is further configured to: monitor a battery level of the wireless device; and determine that the number of tracking area update messages meets the traffic threshold based on the number of tracking area update messages, the processor utilization of the carrier selection node, and the battery level of the wireless device.

11. The system of claim **8**, wherein the first and second tracking area configurations each comprise a geographic location of at least one access node using the first and second carriers, respectively.

12. The system of claim **8**, wherein the first and second tracking area configurations each comprise a coverage area indicated by a respective first and second tracking area identity.

13. The system of claim **8**, wherein the wireless device is in an idle mode when the wireless device is in communication with the first carrier and the second carrier.

14. The system of claim **8**, wherein the carrier selection node is further configured to: determine that a second number of tracking area update messages meets the traffic threshold based on the second number of tracking area update messages and the processor utilization of the carrier selection node; re-ascertain the location and the mobility of the wireless device based on the first tracking area configuration and the second tracking area configuration; and perform a handover of the wireless device from the second carrier to the first carrier based on the first tracking area configuration, the second tracking area configuration, the re-ascertained location, and the re-ascertained mobility.

* * * * *