

US008703321B2

(12) **United States Patent**
Kim et al.

(10) **Patent No.:** **US 8,703,321 B2**
(45) **Date of Patent:** **Apr. 22, 2014**

(54) **SECONDARY BATTERY PACK**

FOREIGN PATENT DOCUMENTS

(75) Inventors: **Jaerok Kim**, Yongin-si (KR);
Kyeongbeom Cheong, Yongin-si (KR);
Jongman Kim, Yongin-si (KR)

JP	5-12232	2/1993
JP	08-321329	12/1996
JP	11-126585	5/1999
JP	2006-147531 A	6/2006
JP	2009-054403	3/2009
JP	2009-170687	7/2009
KR	10-2008-0032748 A	4/2008
KR	10-2009-0110471 A	10/2009
WO	WO 2012/045175	* 4/2012

(73) Assignee: **Samsung SDI Co., Ltd.**, Yongin-si,
Gyeonggi-do (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 380 days.

OTHER PUBLICATIONS

(21) Appl. No.: **13/137,911**

Korean Notice of Allowance Dated Jan. 31, 2013.

(22) Filed: **Sep. 21, 2011**

* cited by examiner

(65) **Prior Publication Data**

US 2012/0214038 A1 Aug. 23, 2012

Primary Examiner — Jonathan Crepeau

(30) **Foreign Application Priority Data**

Feb. 21, 2011 (KR) 10-2011-0015001

(74) *Attorney, Agent, or Firm* — Lee & Morse, P.C.

(51) **Int. Cl.**
H01M 10/50 (2006.01)
H01M 2/10 (2006.01)

(57) **ABSTRACT**

(52) **U.S. Cl.**
USPC **429/120**

A secondary battery pack includes at least two secondary batteries, each secondary battery having a first long side surface, a second opposing long side surface opposite to the first long side surface, and a peripheral wall extending between and connecting the first and second long side surfaces, a spacer interposed between the at least two secondary batteries, the spacer including at least two elastomeric members, a centrally positioned thermal conductor between the at least two elastomeric members, and a support plate under the at least two elastomeric members and contacting the thermal conductor.

(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2009/0061299 A1 3/2009 Uchida et al.
2013/0244077 A1* 9/2013 Palanchon et al. 429/120

16 Claims, 10 Drawing Sheets




FIG.1




FIG.2




FIG.3




FIG. 4




FIG. 5




FIG.6

220




FIG.7

320




FIG. 8




FIG. 9A




FIG. 9B




FIG. 9C





FIG. 9D



1**SECONDARY BATTERY PACK**

BACKGROUND

1. Field

Embodiments relate to a secondary battery pack.

2. Description of the Related Art

A pouch type secondary battery includes an electrode assembly and a pouch case surrounding and sealing the electrode assembly. The electrode assembly is formed by sequentially stacking a positive electrode plate, a separator and a negative electrode plate. In addition, the electrode assembly further includes electrode tabs welded to the positive electrode plate and the negative electrode plate, respectively, and protruding to the outside of the pouch case. The pouch case includes a case body having a space in which the electrode assembly is accommodated, and a case cover extending from one end of the case body and covering the case body.

SUMMARY

Embodiments are directed to a second battery pack.

According to an embodiment, a secondary battery pack includes at least two secondary batteries, each secondary battery having a first long side surface, a second opposing long side surface opposite to the first long side surface and a peripheral wall extending between and connecting the first and second long side surfaces, and a spacer interposed between the at least two secondary batteries, wherein the spacer includes at least two elastomeric members, a centrally positioned thermal conductor between the at least two elastomeric members, and a support plate under the at least two elastomeric members and contacting the thermal conductor.

The spacer may be plate-shaped and may include a planar surface corresponding to the long side surface of the secondary battery. The planar surface may be horizontally aligned with the long side surface of the secondary battery. The spacer may include at least one plate having a rectangular shape.

The thermal conductor may include a plate having a planar surface. In addition, the thermal conductor may have a bottom surface contacting the support plate. Further, the thermal conductor may have a mesh-type configuration including transverse bars and longitudinal bars, the longitudinal bars and transverse bars intersecting each other. In addition, bottom ends of the longitudinal bars may contact the support plate.

The thermal conductor may include a material having higher thermal conductivity than the elastomeric members. The thermal conductor may include a metal, graphite or thermally conductive plastic. The elastomeric members may contact the first and second long side surfaces of the secondary battery.

In addition, the elastomeric members may be spaced apart from the long side surfaces of the secondary battery. The elastomeric members may include silicone or rubber.

The secondary battery pack may further include a heat dissipation plate under the secondary batteries and the spacer. The support plate may include a first connection part at a lower portion thereof, and a second connection part extending downwardly from the first connection part, and the heat dissipation plate may have a receiving part coupled with the second connection part.

In addition, the support plate may be made of a thermally conductive material.

2

BRIEF DESCRIPTION OF THE DRAWINGS

The embodiments will become more apparent to those of ordinary skill in the art by describing in detail exemplary embodiments with reference to the attached drawings, in which:

FIG. 1 illustrates an exploded perspective view of a secondary battery according to an embodiment;

FIG. 2 illustrates a perspective view of the secondary battery shown in FIG. 1;

FIG. 3 illustrates a cross-sectional view, taken along the line A-A' of FIG. 2;

FIG. 4 illustrates an exploded perspective view of a secondary battery pack according to an embodiment;

FIG. 5 illustrates an exploded perspective view of a spacer and a heat dissipation plate of the secondary battery pack of FIG. 4;

FIG. 6 illustrates a cross-sectional view, taken along the line B-B' of FIG. 5;

FIG. 7 illustrates a perspective view of a spacer according to another embodiment;

FIG. 8 illustrates a cross-sectional view, taken along the line C-C' of FIG. 7; and

FIGS. 9A to 9D illustrate thermal analysis results of a secondary battery pack according to an embodiment.

DETAILED DESCRIPTION

Korean Patent Application No. 10-2011-0015001, filed on Feb. 21, 2011, in the Korean Intellectual Property Office, and entitled: "Secondary Battery Pack," is incorporated by reference herein in its entirety.

Example embodiments will now be described more fully hereinafter with reference to the accompanying drawings; however, they may be embodied in different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art.

In the drawing figures, the dimensions of layers and regions may be exaggerated for clarity of illustration. It will also be understood that when a layer or element is referred to as being "on" another element or substrate, it can be directly on the other element or substrate, or intervening elements may also be present. Further, it will be understood that when an element is referred to as being "under" another element, it can be directly under, and one or more intervening elements may also be present. In addition, it will also be understood that when an element is referred to as being "between" two elements, it can be the only element between the two elements, or one or more intervening elements may also be present. Like reference numerals refer to like elements throughout.

FIG. 1 illustrates an exploded perspective view of a secondary battery according to an embodiment. FIG. 2 illustrates a perspective view of the secondary battery shown in FIG. 1. FIG. 3 illustrates a cross-sectional view, taken along the line A-A' of FIG. 2. FIG. 4 illustrates an exploded perspective view of a secondary battery pack according to an embodiment. FIG. 5 illustrates an exploded perspective view of a spacer and a heat dissipation plate of the secondary battery pack of FIG. 4. FIG. 6 illustrates a cross-sectional view, taken along the line B-B' of FIG. 5.

Referring to FIGS. 1 to 6, the secondary battery pack 10 according to an embodiment may include a secondary battery 110 and a spacer 220. The secondary battery pack 10 may further include a heat dissipation plate 300 and a case 400.

The secondary battery pack **10** may include a stack of at least two secondary batteries, e.g., a first secondary battery **110** and a second secondary battery **120**. In the following description, the secondary battery pack **10** will be described with regard to a stacked structure of two secondary batteries.

The first and second secondary batteries **110** and **120** may each be a pouch type secondary battery. Alternatively, the first and second secondary batteries **110** and **120** may each be a prismatic secondary battery. The first secondary battery **110** and the second secondary battery **120** may have the same configuration, and the following description will focus on the first secondary battery **110**.

The first secondary battery **110** may include a first electrode assembly **111**, a first pouch **112** accommodating or holding the first electrode assembly **111**, and a first protective circuit module **113** coupled with the first pouch **112**. The first pouch **112** may be sealed.

The first secondary battery **110** may have a pair of parallel and opposing long side surfaces **115**, and a peripheral wall **116** that extends between and connects the opposing long side surfaces **115**. The first secondary battery **110** may include the first protective circuit module **113** mounted at a terrace or upper ledge portion of the first pouch **112**. The first protective circuit module **113** may form a top surface of the first pouch **112**. The first electrode assembly **111** may be fabricated by winding (in a jelly roll configuration) a first positive electrode plate **111a**, a first negative electrode plate **111b**, and a first separator **111c** (interposed between the first positive and negative electrode plates **111a** and **111b**). Alternatively, the first electrode assembly **111** may also be fabricated by sequentially stacking a first positive electrode plate **111a**, a first separator **111c** and a first negative electrode plate **111b**.

The first positive electrode plate **111a** may include a positive electrode current collector (formed of a highly conductive metal foil, e.g., an aluminum (Al) foil) and a positive electrode active material layer coated or disposed on surfaces of the positive electrode current collector. The first positive electrode plate **111a** may include positive electrode uncoated portions (which are not coated with a positive electrode active material at opposite sides thereof) at opposite ends thereof. A first positive electrode tab **111d** made of, e.g., aluminum (Al) may be bonded to one of the positive electrode uncoated portions.

The first negative electrode plate **111b** may include a negative electrode current collector (formed of a highly conductive metal foil, e.g., a copper (Cu) foil) and a negative electrode active material layer coated or disposed on surfaces of the negative electrode current collector. The first negative electrode plate **111b** may include negative electrode uncoated portions (which are not coated with a negative electrode active material) at opposite ends thereof. A first negative electrode tab **111e** made of, e.g., nickel (Ni) may be bonded to one of the negative electrode uncoated portions.

The first separator **111c** may be positioned between the first positive electrode plate **111a** and the first negative electrode plate **111b**. The separator **111c** may be made of polyethylene (PE) or polypropylene (PP), and, in an implementation, may be formed of a porous layer using a composite film of PE and PP.

The first pouch **112** may include a first pouch body **112a** and a first pouch cover **112d**. The first pouch body **112a** may include a drawing portion **112b** (having a predetermined depth) to receive the first electrode assembly **111**, and a sealing portion **112c** extending from the drawing portion **112b**. The drawing portion **112b** may include a bottom of the first pouch body **112a**. The first pouch cover **112d** may be adhered to the sealing portion **112c** and may seal an upper

opening of the sealing portion **112c** while covering the drawing portion **112b**. The first positive electrode tab **111d** and the first negative electrode tab **111e** may extend from inside the drawing portion **112b** to outside the first secondary battery **110** through the sealing portion **112c** at one side of the first pouch **112**, as shown in FIG. 2.

The first pouch **112** may include one surface that has a denatured polypropylene attached thereto and another surface that has a vinyl compound attached thereto in view of an aluminum foil in the center. The materials that may be used to form the first pouch **112** are not limited to the materials specifically described herein.

The first protective circuit module **113** may include a protective circuit board **113a** (having a wire pattern formed thereon) a plurality of control elements **113b** (for controlling charging and discharging and mounted on the protective circuit board **113a**) and a resin **113c** (surrounding the protective circuit board **113a** and the control elements **113b**). In the first protective circuit module **113**, the protective circuit board **113a** may be electrically connected to the first positive electrode tab **111d** and the first negative electrode tab **111e** (that extends outside of the first pouch **112**). The first protective circuit module **113** may be positioned on a terrace portion or ledge portion of the first pouch **112**.

Although not shown in FIG. 2 or 3, a plurality of terminals may be formed on the protective circuit board **113a**; and the plurality of terminals may be exposed to the outside through the resin **113c**.

The secondary battery pack **10** may include one or more spacers. In an implementation, the secondary battery pack **10** may include a first spacer **210**, a second spacer **220** and a third spacer **230**, as shown in FIG. 4. The second spacer **220** may be positioned between stacked secondary batteries **110** and **120**. The first and third spacers **210** and **230** may be disposed on exposed or outer sides of the stacked secondary batteries **100**. For example, the first and third spacers **210** and **230** may be disposed on opposite sides of the secondary battery pack **10**. Accordingly, a number of the spacers may increase according to a number of stacked secondary batteries. For example, in a case where two secondary batteries are stacked, the spacer may include one spacer positioned between the stacked secondary batteries and two spacers respectively positioned on opposite sides of the secondary battery pack **10**.

Each of the spacers **210**, **220**, and **230** may include thermal conductors **211**, **221**, and **231**, respectively. Each of the spacers **210**, **220**, and **230**, may include elastomeric members **212**, **222**, and **232** respectively. Opposing sides of the thermal conductors **211**, **221**, and **231** may include the elastomeric portions **212**, **222**, and **232**, respectively. Support plates **213**, **223**, and **233** may be positioned at a bottom portion of the spacers **210**, **220**, and **230**, respectively. For example, the first spacer **210** may include a first thermal conductor **211**, first elastomeric members **212** on opposing sides of the first thermal conductor **211**, and a first support plate **213** extending across a bottom surface of the first thermal conductor **211**, the first elastomer **212**, and the first support plate **213**. The second spacer **220** may include a second thermal conductor **221**, second elastomeric members **222** on opposing sides of the second thermal conductor **221**, and a second support plate **223** extending across a bottom surface of the second thermal conductor **221**, the second elastomer **222**, and the second support plate **223**. The third spacer **230** may include a third thermal conductor **231**, third elastomeric members **232** on opposing sides of the third thermal conductor **231**, and a third support plate **233** extending across a bottom surface of the third thermal conductor **231**, the third elastomeric members **232**, and the third support plate **233**. In an implementation,

5

the first spacer **210** and the third spacer **230** may be disposed on outermost or exposed surfaces of the secondary batteries, and the second spacer **220** may be positioned between the secondary batteries.

The elastomeric members may support long side surfaces of the secondary battery **100**. Thus, the spacers may suppress or help to prevent swelling or expansion of the secondary battery **100** while at least partially accommodating a swollen portion of the secondary battery **100** or tolerating some expansion of the secondary battery in the event that the secondary battery **100** does swell. In addition, the spacer **200** may facilitate restoration of the secondary battery **100** to its original configuration by imparting a restoring force to the secondary battery **100** when the secondary battery **100** deviates from its original state. For example, the spacer **200** may facilitate contraction of the secondary battery **100** after expansion, and thereby return to its original configuration. The spacer **200** may also facilitate the thermal conductors **211**, **221**, and **231** to efficiently dissipate heat transferred from the secondary battery **100** through the support plates.

The first spacer **210**, the second spacer **220** and the third spacer **230** may have the same configuration, and the following description will focus on the second spacer **220**. Alternatively, the first spacer **210** and the third spacer **230** may or may not have elastomeric members at surfaces thereof facing the secondary battery **100**, in view of the thermal conductors.

The second spacer **220** may include a second thermal conductor **221**, second elastomeric members **222**, and a second support plate **223**.

The second spacer **220** may have a plate shape corresponding to a long side surface of the secondary battery **100**. The first secondary battery **110** and the second secondary battery **120** may be positioned on opposing sides of the second spacer **220**. The second spacer **220** may be positioned to be opposed to long side surfaces of the first secondary battery **110** and the second secondary battery **120**. The second spacer **220** may contact the long side surfaces of the first secondary battery **110** and the second secondary battery **120**. In addition, the second spacer **220** may be spaced apart from the long side surfaces of the first secondary battery **110** and the second secondary battery **120**. For example, the second spacer **220** may be disposed between the first secondary battery **110** and the second secondary battery **120** without directly contacting the first secondary battery **110** and the second secondary battery **120**. Here, the second spacer **220** may more efficiently accommodate a swollen portion of the secondary battery **100** in a case where the secondary battery **100** swells comparatively a lot.

The second thermal conductor **221** may include a plate made of a thermally conductive material. The second thermal conductor **221** may be made of a material having higher thermal conductivity than the second elastomeric members **222**. The second thermal conductor **221** may be made of a metal, graphite, or a thermally conductive plastic material. The second thermal conductor **221** may be a component of the second spacer **220**. In addition, the second thermal conductor **221** may be exposed to opposite side surfaces and a top surface of the case **400**. The second thermal conductor **221** may dissipate heat (generated during charging and discharging of the first secondary battery **110** and the second secondary battery **120**) to the outside. For example, the second thermal conductor **221** may transfer the heat from the first secondary battery **110** and the second secondary battery **120** to the second support plate **223**. In addition, the second thermal conductor **221** may dissipate heat to the air or to the case **400** when the second thermal conductor **221** is exposed to the opposite side surfaces and the top surface of the case **400**.

6

The second elastomeric members **222** may be made of a material having elasticity greater than that of the second thermal conductor **221**. The second elastomeric members **222** may be made of elastic silicone or rubber. The second elastomeric members **222** may be formed substantially as plate-like structures. In addition, the second elastomeric members **222** may contact opposing sides of the second thermal conductor **221**. For example, the second elastomeric members **222** may sandwich the second thermal conductor **221** therebetween. Portions of the second thermal conductor **221** may be exposed to opposite side surfaces of the second elastomeric members **222**. In addition, a bottom portion of the second thermal conductor **221** may be aligned with bottom portions of the second elastomeric members **222**, so that the second elastomeric members **222** and the second thermal conductor **221** contact the second support plate **223**.

The second elastomeric members **222** may contact long side surfaces of the first secondary battery **110** and the second secondary battery **120**. Therefore, the second elastomeric members **222** may suppress or help to prevent the first secondary battery **110** and the second secondary battery **120** from swelling or expanding. When the first secondary battery **110** and the second secondary battery **120** do swell or expand, the second elastomeric members **222** may apply or provide a restoring force to the first secondary battery **110** and the second secondary battery **120**, facilitating restoration of the first secondary battery **110** and the second secondary battery **120** to their original state. In addition, the second elastomeric members **222** may be spaced a predetermined distance apart from the long side surfaces or top and bottom surfaces of the first secondary battery **110** and the second secondary battery **120**.

The second support plate **223** may include a plate, for example a first connection part **223a**, that contacts or extends across bottom portions of the second elastomeric members **222** and the second thermal conductor **221**. The second support plate **223** may be made of a thermally conductive material, like the second thermal conductor **221**. In an implementation, the second support plate **223** may be integrally formed with the second thermal conductor **221**. The second support plate **223** may include a second plate, for example, a second connection part **223b**, as shown in FIG. 5, that extends from the first connection part **223a**.

The second support plate **223** may contact the second thermal conductor **221** to facilitate transfer of the heat from the second thermal conductor **221** to the heat dissipation plate **300**.

The second connection part **223b** may include a plate extending downwardly from the first connection part **223a**. The second connection part **223b** may have a width and a length similar to a width and length of the first connection part **223a**. The second connection part **223b** may be inserted into or coupled with a receiving part **310** of the heat dissipation plate **300**. Therefore, the second connection part **223b** may contact the heat dissipation plate **300** to efficiently transfer the heat from the second thermal conductor **221**.

The heat dissipation plate **300** may include a plate having a width corresponding to a width of the secondary battery **100**. In addition, the heat dissipation plate **300** may have a length corresponding to a length of a plurality of secondary batteries **100** and spacers **200** alternately stacked together. The heat dissipation plate **300** may be made of a thermally conductive material, e.g., a metal. In an implementation, the heat dissipation plate **300** may be coated with a metal having superb heat transfer efficiency, thereby increasing the heat dissipation efficiency and temperature uniformity.

The heat dissipation plate **300** may be positioned under the secondary battery **100** and the spacer **200** and may contact the bottom surface of the spacer **200**. Thus, the heat dissipation plate **300** may dissipate heat from the spacer **200** out of the secondary battery pack **10**. The heat dissipation plate **300** may connect to a separate dissipation member positioned outside the secondary battery pack **10** for the purpose of dissipating heat more effectively.

The heat dissipation plate **300** may further include the receiving part **310**. The receiving part **310** may be an open portion or opening defined in a top surface of the heat dissipation plate **300**. The receiving part **310** may be a groove having a predetermined width and length. For example, the receiving part **310** may have a width and length corresponding to the length and width of the second connection part **223b**. The receiving part **310** may engage with the second connection part **223b** and contact the second connection part **224**, thereby facilitating efficient emission of heat from the second connection part **223b**.

The case **400** may receive or retain the secondary battery **100**, the spacer **200** and the heat dissipation plate **300**. The case **400** may have various shapes suitable to receive or retain the secondary battery **100**, the spacer **200** and the heat dissipation plate **300**. In addition, the case **400** may be formed such that a portion of the heat dissipation plate **300** may be exposed to the outside or may be external to the secondary battery **100**.

Next, a secondary battery pack according to another embodiment will be described.

FIG. 7 illustrates a perspective view of a spacer according to another embodiment. FIG. 8 illustrates a cross-sectional view, taken along the line C-C' of FIG. 7.

The secondary battery pack according to the present embodiment may include a second spacer **520** (instead of the second spacer **220**, described previously). In all other regards, the second battery pack **100**, including the second spacer **520**, may be substantially the same as the secondary battery pack according to the previous embodiment shown in FIGS. 1 to 6. Therefore, the following description will focus on the second spacer **520**.

In the present embodiment, the second spacer **520** may include a plurality of second thermal conductors **521**, a second elastomer **522** and a second support plate **523**. The second spacer **520** may be substantially the same as the second spacer **220** according to the previous embodiment shown in FIGS. 1 to 6, except that the second spacer **520** may include second thermal conductors **521**. Therefore, the following description will focus on the second thermal conductors **521**, and other components of the second spacer **520** corresponding to components of the second spacer **220** shown in FIGS. 1 to 6 will only be briefly described.

The second thermal conductors **521** may be arranged in a mesh-type configuration. Thus, the second thermal conductors **521** may include transverse bars **521a** and longitudinal bars **521b**. The second thermal conductors **521** may be made of a thermally conductive material. According to an embodiment, the second thermal conductors **521** may be made of a material having higher thermal conductivity than the second elastomer **522**. For example, the second thermal conductors **521** may be made of a metal, graphite or thermally conductive plastic.

As described above, the transverse bars **521a** and longitudinal bars **521b** of the second thermal conductors **521** are components of the second spacer **520**. In addition, the transverse bars **521a** and the longitudinal bars **521b** may be formed such that ends thereof at least partially form exposed opposing side surfaces and a top surface of the second spacer **520**.

For example, opposing ends of the transverse bars **521a** may at least partially form an outer surface of opposing side surfaces of the second spacer **520**, and one end of the longitudinal bars **521b** may at least partially form an outer top surface of the second spacer **520**. Further, bottom ends of the longitudinal bars **521b** may contact the second support plate **523**.

The second thermal conductors **521** may emit or transfer heat generated during charging and discharging of the first secondary battery **110** and the second secondary battery **120** to the outside. For example, the second thermal conductors **521** may transfer heat from the first secondary battery **110** and the second secondary battery **120** to the second support plate **523**. In addition, the second thermal conductors **521** may emit heat to the air or to an outer casing when the transverse bars **521a** and the longitudinal bars **521b** are exposed to or flush with the opposing side surfaces and top surface of the outer casing of the second spacer **520**.

The second elastomer **522** may be made of a material having elasticity greater than that of the second thermal conductors **521**. The second elastomer **522** may be made of elastic silicone or rubber. The second elastomer **522** may have a substantially plate-like shape and may surround the second thermal conductors **521**. According to an embodiment, the second elastomer **522** may be box-shaped and may encase the second thermal conductors **521**. In addition, the second elastomer **522** may surround second thermal conductors **521** such that ends of the transverse bars **521a** and the longitudinal bars **521b** are exposed to or flush with the opposite side surfaces and top surface of the second elastomer **522**. In addition, the second elastomer **522** may expose bottom ends of the longitudinal bars **521b** to the bottom surface of the second elastomer **522**.

The second support plate **523** may be similar to the second support plate **223** of the second spacer **220** shown in FIGS. 1 to 6. Thus, a detailed description thereof will not be given. The second support plate **523** may include a first connection part **523a** and a second connection part **523b**.

Next, the operation of the secondary battery pack will be described in more detail through examples and comparative examples.

FIGS. 9A to 9D illustrate thermal analysis result of a secondary battery pack according to an embodiment, in which the circular dark grey and circular light grey portions correspond to secondary batteries, and the rectangular light grey portions indicate spacers or empty space. In FIGS. 9A to 9D, the central portions in dark grey are high temperature portions, and the left corner portions in dark grey are relatively low temperature portions.

EXAMPLE 1

In this exemplary example, a secondary battery pack including a spacer having elastomeric members and a thermal conductor according to an embodiment was used.

Referring to FIG. 9A, the highest temperature of the secondary battery pack was 72.0° C., and a temperature difference between stacked secondary batteries was 13.4° C.

EXAMPLE 2

In this exemplary example, a secondary battery pack including a spacer having elastomeric members and a thermal conductor and a heat dissipation plate according to an embodiment was used.

Referring to FIG. 9B, the highest temperature of the secondary battery pack was 71.7° C., and a temperature difference between stacked secondary batteries was 12.3° C.

COMPARATIVE EXAMPLE 1

In this comparative example, a secondary battery pack including stacked secondary batteries spaced apart from each other without a spacer was used.

Referring to FIG. 9C, the highest temperature of the secondary battery pack was 79.8° C., and a temperature difference between stacked secondary batteries was 23.5° C.

COMPARATIVE EXAMPLE 2

In this comparative example, a secondary battery pack including a spacer having only elastomer was used (without a thermal conductor).

Referring to FIG. 9D, the highest temperature of the secondary battery pack was 75.5° C., and a temperature difference between stacked secondary batteries was 17.8° C.

As described above, the evaluation results show that the secondary battery pack **10** according to an embodiment had a lower temperature than the secondary battery pack without a spacer or the secondary battery pack with a spacer having an elastomer only. In addition, the secondary battery pack **10** according to an embodiment had a smaller temperature difference between secondary batteries than the secondary battery pack without a spacer or the secondary battery pack with a spacer of an elastomer only. Therefore, according to an embodiment, the spacer may include a thermal conductor and an elastomer. Thus, the spacer facilitates the heat generated from the secondary batteries to be efficiently emitted, thereby lowering the highest temperature of the secondary battery and reducing a temperature difference between secondary batteries.

The secondary battery and the pouch case of the secondary battery, according to example embodiments, may be protected from deformation, e.g., expansion or contraction, in response to a charging or discharging operation. In particular, expansion of the electrode assembly may be suppressed and contraction of the electrode assembly after expansion may be facilitated. Therefore, the conventional pouch type secondary battery may be less vulnerable to deformation based on contraction and expansion due to prolonged use of the electrode assembly. Also, heat dissipating capacity may be increased. In addition, undesirable rise of the internal temperature of the secondary battery may be avoided. The secondary battery pack may be capable of improving the life span of a secondary battery.

As described above, in the secondary battery pack according to an embodiment, swelling of the secondary battery may be suppressed and a restoring force may be imparted to the secondary battery in an event of swelling, thereby preventing deformation of the secondary battery and extending a life span of the secondary battery. In addition, in the secondary battery pack according to an embodiment, heat dissipation efficiency of the secondary battery may be improved.

Example embodiments have been disclosed herein, and although specific terms are employed, they are used and are to be interpreted in a generic and descriptive sense only and not for purpose of limitation. In some instances, as would be apparent to one of ordinary skill in the art as of the filing of the present application, features, characteristics, and/or elements described in connection with a particular embodiment may be used singly or in combination with features, characteristics, and/or elements described in connection with other embodiments unless otherwise specifically indicated. Accordingly, it will be understood by those of skill in the art that various

changes in form and details may be made without departing from the spirit and scope of the present invention as set forth in the following claims.

5 What is claimed is:

1. A secondary battery pack, comprising:

at least two secondary batteries, each secondary battery having a first long side surface, a second opposing long side surface opposite to the first long side surface, and a peripheral wall extending between and connecting the first and second long side surfaces; and

a spacer interposed between the at least two secondary batteries,

15 wherein the spacer includes at least two elastomeric members, a centrally positioned thermal conductor between the at least two elastomeric members, and a support plate under the at least two elastomeric members and contacting the thermal conductor.

20 2. The secondary battery pack as claimed in claim 1, wherein the spacer is plate-shaped and includes a planar surface corresponding with the long side surface of the secondary battery.

3. The secondary battery pack as claimed in claim 2, wherein the planar surface is horizontally aligned with the long side surface of the secondary battery.

4. The secondary battery pack as claimed in claim 2, wherein the spacer includes at least one plate having a rectangular shape.

30 5. The secondary battery pack as claimed in claim 1, wherein the thermal conductor includes a plate having a planar surface.

6. The secondary battery pack as claimed in claim 1, wherein the thermal conductor has a bottom surface contacting the support plate.

7. The secondary battery pack as claimed in claim 1, wherein the thermal conductor has a mesh-type configuration including transverse bars and longitudinal bars, the longitudinal bars and the transverse bars intersecting each other.

8. The secondary battery pack as claimed in claim 7, wherein bottom ends of the longitudinal bars contact the support plate.

9. The secondary battery pack as claimed in claim 1, wherein the thermal conductor includes a material having higher thermal conductivity than the elastomeric members.

10. The secondary battery pack as claimed in claim 1, wherein the thermal conductor includes a metal, graphite, or a thermally conductive plastic.

50 11. The secondary battery pack as claimed in claim 1, wherein the elastomeric members contact the first and second long side surfaces of the secondary battery.

12. The secondary battery pack as claimed in claim 1, wherein the elastomeric members are spaced apart from the long side surfaces of the secondary battery.

13. The secondary battery pack as claimed in claim 1, wherein the elastomeric members include silicone or rubber.

14. The secondary battery pack as claimed in claim 1, further comprising a heat dissipation plate under the secondary batteries and the spacer.

15. The secondary battery pack as claimed in claim 14, wherein:

the support plate includes a first connection part at a lower portion thereof and a second connection part extending downwardly from the first connection part, and the heat dissipation plate has a receiving part coupled with the second connection part.

16. The secondary battery pack as claimed in claim 1, wherein the support plate is made of a thermally conductive material.

* * * * *