



US008744314B2

(12) **United States Patent**
Huck et al.

(10) **Patent No.:** **US 8,744,314 B2**
(45) **Date of Patent:** **Jun. 3, 2014**

(54) **SYSTEMS AND METHODS FOR
REMANUFACTURING IMAGING
COMPONENTS**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(75) Inventors: **Donald D. Huck**, Sanford, NC (US);
James H. Jones, Fayetteville, NC (US);
Matthew J. Morton, Holly Springs, NC
(US); **Anthony D. Causey**, Fuquay
Varina, NC (US)

(73) Assignee: **Static Control Components, Inc.**,
Sanford, NC (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 79 days.

(21) Appl. No.: **13/444,449**

(22) Filed: **Apr. 11, 2012**

(65) **Prior Publication Data**

US 2012/0195637 A1 Aug. 2, 2012

Related U.S. Application Data

(63) Continuation of application No. 13/283,684, filed on
Oct. 28, 2011, which is a continuation of application
No. 12/902,625, filed on Oct. 12, 2010, now Pat. No.
8,073,364, which is a continuation of application No.
11/825,262, filed on Jul. 5, 2007, now Pat. No.
7,813,676.

(51) **Int. Cl.**
G03G 15/00 (2006.01)

(52) **U.S. Cl.**
USPC **399/167**

(58) **Field of Classification Search**
USPC 399/111, 116, 117, 159, 167; 464/162,
464/179, 182

See application file for complete search history.

5,128,715 A	7/1992	Furuyama	
5,669,046 A	9/1997	Yoshida et al.	
5,903,803 A	5/1999	Kawai	
5,926,673 A	7/1999	Foster	
5,987,287 A	11/1999	Huang	
6,163,665 A	12/2000	Watanabe	
6,173,146 B1	1/2001	Wang	
6,175,706 B1	1/2001	Watanabe	
6,226,478 B1	5/2001	Watanabe	
6,240,266 B1	5/2001	Watanabe	
6,336,018 B1	1/2002	Kawai	
6,349,188 B1	2/2002	Kawai	
6,400,914 B1	6/2002	Noda	
6,501,926 B1	12/2002	Watanabe	
6,501,927 B1	12/2002	Watanabe	
6,885,838 B2	4/2005	Kawai	
6,999,696 B2	2/2006	Noda	
7,236,722 B2	6/2007	Portig	
7,433,631 B2 *	10/2008	Karz et al.	399/167
2010/0196047 A1	8/2010	Jin	

FOREIGN PATENT DOCUMENTS

EP 0735432 2/1996

* cited by examiner

Primary Examiner — Hoan Tran

(57) **ABSTRACT**

A drive gear for a generally cylindrical imaging component. The drive gear includes a body for engaging the generally cylindrical imaging component; a cylindrical shaft attached to the body, the cylindrical shaft having an end surface; and three prongs extending longitudinally outward from the end surface.

9 Claims, 10 Drawing Sheets




FIG. 1
(PRIOR ART)




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17





FIG. 18



1

SYSTEMS AND METHODS FOR REMANUFACTURING IMAGING COMPONENTS

This application is a continuation of U.S. application Ser. No. 13/283,684 filed on Oct. 28, 2011, which is a continuation of U.S. application Ser. No. 12/902,625 filed on Oct. 12, 2010, which issued as U.S. Pat. No. 8,073,364, which is a continuation of U.S. application Ser. No. 11/825,262 filed on Jul. 5, 2007, which issued as U.S. Pat. No. 7,813,676, all of which are incorporated by reference herein in its entirety.

BACKGROUND

The present invention generally relates to manufacturing, remanufacturing or repairing replaceable imaging components, and more particularly to apparatus and techniques for providing a drive gear for a drum or roller, such as an organic photo conductor (OPC) drum, for example, of a replaceable imaging cartridge adapted for holding marking material, such as toner.

In the imaging industry, there is a growing market for the remanufacture and refurbishing of various types of replaceable imaging cartridges such as toner cartridges, drum cartridges, inkjet cartridges, and the like. These imaging cartridges are used in imaging devices such as laser printers, xerographic copiers, inkjet printers, facsimile machines and the like, for example. Imaging cartridges, once spent, are unusable for their originally intended purpose. Without a refurbishing process these cartridges would simply be discarded, even though the cartridge itself may still have potential life. As a result, techniques have been developed specifically to address this issue. These processes may entail, for example, the disassembly of the various structures of the cartridge, replacing toner or ink, cleaning, adjusting or replacing any worn components and reassembling the imaging cartridge.

Laser printer toner cartridges are typically composed of two portions. One of these sections is the waste bin assembly which houses the OPC drum. The OPC may include a drive gear which engages with a printer drive member. During the remanufacturing of a laser printer toner cartridge, the OPC drum may need to be replaced due to the wear or damage of the OPC drum. The replacement OPC drum may include a replacement drive gear, or gear, attached to one end of the replacement OPC drum. The present invention provides for an improved replacement drive gear.

SUMMARY

In one aspect of the present invention, a drive gear for a generally cylindrical imaging component includes a body for engaging the generally cylindrical imaging component; a cylindrical shaft attached to the body, the cylindrical shaft having an end surface; and three prongs extending longitudinally outward from the end surface.

In another aspect of the present invention, an imaging apparatus assembly includes a drive mechanism including a helical recess; and a drive gear including a body for engaging a generally cylindrical imaging component; a cylindrical shaft attached to the body, the cylindrical shaft having an end surface; and three prongs extending longitudinally outward from the end surface and engaging the helical recess.

In another aspect of the present invention, an imaging apparatus assembly includes a generally cylindrical imaging component; and a drive gear including a body engaging a generally cylindrical imaging component; a cylindrical shaft

2

attached to the body, the cylindrical shaft having an end surface; and three prongs extending longitudinally outward from the end surface.

A more complete understanding of the present invention, as well as further features and advantages of the invention, will be apparent from the following detailed description and the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a perspective view of a prior art drive mechanism;

FIGS. 2-17 show perspective views of multiple embodiments of a drive gear in accordance with the present invention; and

FIG. 18 shows a drive gear and OPC drum in accordance with the present invention.

DETAILED DESCRIPTION

The following detailed description of preferred embodiments refers to the accompanying drawings which illustrate specific embodiments of the invention. In the discussion that follows, specific systems and techniques for providing a drive gear for a drum or roller, such as an organic photo conductor (OPC) drum, for example, of a replaceable imaging cartridge adapted for holding marking material, are disclosed. Other embodiments having different structures and operations for the repair, remanufacture and operation of other types of replaceable imaging components and for various types of imaging devices, such as laser printers, inkjet printers, copiers, facsimile machines and the like, do not depart from the scope of the present invention.

FIG. 1 shows a prior art drive mechanism **100**. The drive mechanism **100** may include a body **102** having a raised section **104**. A helical recess **106** may be formed in the raised section **104**. The raised section **104** may include an outer cylindrical surface **104a**. In operation, the drive mechanism **100** is part of a printer and engages a gear (not shown) having a shaped helical extrusion on an imaging cartridge, and causes the gear with the helical extrusion to rotate. Further details of such a prior art drive mechanism **100** and gear are disclosed in U.S. Pat. No. 6,400,914 which is incorporated by reference herein in its entirety.

FIG. 2 shows a drive gear **200** in accordance with the present invention. One end of the drive gear **200** is adapted to be attached to a hollow roller or generally cylindrical imaging component, such as an OPC drum. The other end of the drive gear **200** is adapted to engage the helical recess **106** of the drive mechanism **100** of a printer. The drive gear **200** includes a body **202** for engaging the generally cylindrical imaging component and a cylindrical shaft **204** attached to the body **202**. The cylindrical shaft **204** has an end surface **206**. Three prongs **208** extend longitudinally outward from the end surface **206** and are shaped to engage the helical recess **106** of the drive mechanism **100**. Each of the three prongs **208** may be generally triangular in shape with one vertex **208a** of each triangular shaped prong **208** being generally rounded.

When the user closes a door of the printer, the drive mechanism **100** slides onto the cartridge drive gear **200** so that the three drive gear prongs **208** are inserted into the helical recess **106**. As the printer drive mechanism **100** rotates, the three prongs **208** are engaged, and the entire cartridge drive gear **200** rotates, which in turn drives an OPC (not shown) attached to the drive gear **200**. In this embodiment, only the OPC is rotated by this drive interface, however this design is not limited only to this embodiment. The drive gear may include

3

one or more gears which drive the rest of the cartridge components in addition to the OPC.

FIG. 3 shows a drive gear 300 in accordance with the present invention. One end of the drive gear 300 is adapted to be attached to a hollow roller or generally cylindrical imaging component, such as an OPC drum. The other end of the drive gear 300 is adapted to engage the helical recess 106 of the drive mechanism 100 of a printer. The drive gear 300 includes a body 302 for engaging the generally cylindrical imaging component and a cylindrical shaft 304 attached to the body 302. The cylindrical shaft 304 has an end surface 306. Three prongs 308 extend longitudinally and radially outward from the end surface 306 and are shaped to engage the helical recess 106 of the drive mechanism 100. Each of the prongs 308 may be generally rectangular in cross section. Bracing members 308a may be disposed between the prongs 308. The drive gear 300 may include one or more gears 310 which drive the additional cartridge components.

FIG. 4 shows a drive gear 400 in accordance with the present invention. One end of the drive gear 400 is adapted to be attached to a hollow roller or generally cylindrical imaging component, such as an OPC drum. The other end of the drive gear 400 is adapted to engage the helical recess 106 of the drive mechanism 100 of a printer. The drive gear 400 includes a body 402 for engaging the generally cylindrical imaging component and a cylindrical shaft 404 attached to the body 402. The cylindrical shaft 404 has an end surface 406. Three prongs 408 extend longitudinally and radially outward from the end surface 406 and are shaped to engage the helical recess 106 of the drive mechanism 100. Each of the prongs 408 may be generally rectangular in cross section. The drive gear 400 may include one or more gears 410 which drive the additional cartridge components.

FIG. 5 shows a drive gear 500 in accordance with the present invention. One end of the drive gear 500 is adapted to be attached to a hollow roller or generally cylindrical imaging component, such as an OPC drum. The other end of the drive gear 500 is adapted to engage the helical recess 106 of the drive mechanism 100 of a printer. The drive gear 500 includes a body 502 for engaging the generally cylindrical imaging component and a cylindrical shaft 504 attached to the body 502. The cylindrical shaft 504 has an end surface 506. Three prongs 508 extend longitudinally outward from the end surface 506 and are shaped to engage the helical recess 106 of the drive mechanism 100. Each of the prongs 508 may be generally circular in cross section and may be inclined at a slight angle to the end surface 506 in a twisted fashion. The drive gear 500 may include one or more gears 510 which drive the additional cartridge components.

FIG. 6 shows a drive gear 600 in accordance with the present invention. One end of the drive gear 600 is adapted to be attached to a hollow roller or generally cylindrical imaging component, such as an OPC drum. The other end of the drive gear 600 is adapted to engage the helical recess 106 of the drive mechanism 100 of a printer. The drive gear 600 includes a body 602 for engaging the generally cylindrical imaging component and a cylindrical shaft 604 attached to the body 602. The cylindrical shaft 604 has an end surface 606. Three prongs 608 extend longitudinally and latitudinally outward from the end surface 606 and are shaped to engage the helical recess 106 of the drive mechanism 100. Each of the prongs 608 may include a longitudinal element 608a and a latitudinal element 608b. The drive gear 600 may include one or more gears 610 which drive the additional cartridge components.

FIG. 7 shows a drive gear 700 in accordance with the present invention. One end of the drive gear 700 is adapted to be attached to a hollow roller or generally cylindrical imaging

4

component, such as an OPC drum. The other end of the drive gear 700 is adapted to engage the helical recess 106 of the drive mechanism 100 of a printer. The drive gear 700 includes a body 702 for engaging the generally cylindrical imaging component and a cylindrical shaft 704 attached to the body 702. The cylindrical shaft 704 has an end surface 706. A triangular shaped element 708 extends outward from the end surface 706 and is shaped to engage the helical recess 106 of the drive mechanism 100. The drive gear 700 may include one or more gears 710 which drive the additional cartridge components.

FIG. 8 shows a drive gear 800 in accordance with the present invention. One end of the drive gear 800 is adapted to be attached to a hollow roller or generally cylindrical imaging component, such as an OPC drum. The other end of the drive gear 800 is adapted to engage the helical recess 106 of the drive mechanism 100 of a printer. The drive gear 800 includes a body 802 for engaging the generally cylindrical imaging component and a cylindrical shaft 804 attached to the body 802. The cylindrical shaft 804 has an end surface 806. A cam shaped element 808 extends outward from the end surface 806 and is shaped to engage the helical recess 106 of the drive mechanism 100. The drive gear 800 may include one or more gears 810 which drive the additional cartridge components.

FIG. 9 shows a drive gear 900 in accordance with the present invention. One end of the drive gear 900 is adapted to be attached to a hollow roller or generally cylindrical imaging component, such as an OPC drum. The other end of the drive gear 900 is adapted to engage the helical recess 106 of the drive mechanism 100 of a printer. The drive gear 900 includes a body 902 for engaging the generally cylindrical imaging component and a cylindrical shaft 904 attached to the body 902. The cylindrical shaft 904 has an end surface 906. A generally triangular shaped element 908 extends and flares outward from the end surface 906 and is shaped to engage the helical recess 106 of the drive mechanism 100. The drive gear 900 may include one or more gears 910 which drive the additional cartridge components.

FIG. 10 shows a drive gear 1000 in accordance with the present invention. One end of the drive gear 1000 is adapted to be attached to a hollow roller or generally cylindrical imaging component, such as an OPC drum. The other end of the drive gear 1000 is adapted to engage the helical recess 106 of the drive mechanism 100 of a printer. The drive gear 1000 includes a body 1002 for engaging the generally cylindrical imaging component and a cylindrical shaft 1004 attached to the body 1002. The cylindrical shaft 1004 has an end surface 1006. A six-pointed star shaped element 1008 extends outward from the end surface 1006 and is shaped to engage the helical recess 106 of the drive mechanism 100. The drive gear 1000 may include one or more gears 1010 which drive the additional cartridge components.

FIG. 11 shows a drive gear 1100 in accordance with the present invention. One end of the drive gear 1100 is adapted to be attached to a hollow roller or generally cylindrical imaging component, such as an OPC drum. The other end of the drive gear 1100 is adapted to engage the helical recess 106 of the drive mechanism 100 of a printer. The drive gear 1100 includes a body 1102 for engaging the generally cylindrical imaging component and a cylindrical shaft 1104 attached to the body 1102. The cylindrical shaft 1104 has an end surface 1106. An off-center element 1108 having two lobes 1108a extends outward from the end surface 1106 and is shaped to engage the helical recess 106 of the drive mechanism 100. The drive gear 1100 may include one or more gears 1110 which drive the additional cartridge components.

5

FIG. 12 shows a drive gear 1200 in accordance with the present invention. One end of the drive gear 1200 is adapted to be attached to a hollow roller or generally cylindrical imaging component, such as an OPC drum. The other end of the drive gear 1200 is adapted to engage the helical recess 106 of the drive mechanism 100 of a printer. The drive gear 1200 includes a body 1202 for engaging the generally cylindrical imaging component and a cylindrical shaft 1204 attached to the body 1202. The cylindrical shaft 1204 has an end surface 1206. A tri-lobe element 1208 flares outward from the end surface 1206 and is shaped to engage the helical recess 106 of the drive mechanism 100. The drive gear 1200 may include one or more gears 1210 which drive the additional cartridge components.

FIG. 13 shows a drive gear 1300 in accordance with the present invention. One end of the drive gear 1300 is adapted to be attached to a hollow roller or generally cylindrical imaging component, such as an OPC drum. The other end of the drive gear 1300 is adapted to engage the helical recess 106 of the drive mechanism 100 of a printer. The drive gear 1300 includes a body 1302 for engaging the generally cylindrical imaging component and a cylindrical shaft 1304 attached to the body 1302. The cylindrical shaft 1304 has an end surface 1306. A tri-lobe element 1308 flares outward from the end surface 1306 and is shaped to engage the helical recess 106 of the drive mechanism 100. The drive gear 1300 may include one or more gears 1310 which drive the additional cartridge components.

FIG. 14 shows a drive gear 1400 in accordance with the present invention. One end of the drive gear 1400 is adapted to be attached to a hollow roller or generally cylindrical imaging component, such as an OPC drum. The other end of the drive gear 1400 is adapted to engage the helical recess 106 of the drive mechanism 100 of a printer. The drive gear 1400 includes a body 1402 for engaging the generally cylindrical imaging component and a cylindrical shaft 1404 attached to the body 1402. The cylindrical shaft 1404 has an end surface 1406. A tri-lobe element 1408 extends outward from the end surface 1406 and is shaped to engage the helical recess 106 of the drive mechanism 100. The drive gear 1400 may include one or more gears 1410 which drive the additional cartridge components.

FIG. 15 shows a drive gear 1500 in accordance with the present invention. One end of the drive gear 1500 is adapted to be attached to a hollow roller or generally cylindrical imaging component, such as an OPC drum. The other end of the drive gear 1500 is adapted to engage the drive mechanism 100 of a printer. The drive gear 1500 includes a body 1502 for engaging the generally cylindrical imaging component and a cylindrical shaft 1504 attached to the body 1502. The cylindrical shaft 1504 has an end surface 1506. Three prongs 1508 extend longitudinally and radially outward from the end surface 1506 and are shaped to grip outer cylindrical surface 104a of the drive mechanism 100. The drive gear 1500 may include one or more gears 1510 which drive the additional cartridge components.

FIG. 16 shows a drive gear 1600 in accordance with the present invention. One end of the drive gear 1600 is adapted to be attached to a hollow roller or generally cylindrical imaging component, such as an OPC drum. The other end of the drive gear 1600 is adapted to engage the drive mechanism 100 of a printer. The drive gear 1600 includes a body 1602 for engaging the generally cylindrical imaging component and a cylindrical shaft 1604 attached to the body 1602. The cylindrical shaft 1604 has an end surface 1606. Three prongs 1608 extend longitudinally and radially outward from the end surface 1606 and are shaped to grip the outer cylindrical surface

6

104a of the drive mechanism 100. A cylindrical element 1612 extends outward to engage the helical recess 106 of the drive mechanism 100. The drive gear 1600 may include one or more gears 1610 which drive the additional cartridge components.

FIG. 17 shows a drive gear 1700 in accordance with the present invention. One end of the drive gear 1700 is adapted to be attached to a hollow roller or generally cylindrical imaging component, such as an OPC drum. The other end of the drive gear 1700 is adapted to engage the helical recess 106 of the drive mechanism 100 of a printer. The drive gear 1700 includes a body 1702 for engaging the generally cylindrical imaging component and a cylindrical shaft 1704 attached to the body 1702. The cylindrical shaft 1704 has an end surface 1706. A triangular shaped element 1708 extends longitudinally outward from the end surface 1706 and is shaped to engage the helical recess 106 of the drive mechanism 100. The element may generally triangular in shape but missing one vertex 1708a. A cylindrical shaped element 1712 is shaped to engage the outer cylindrical surface 104a of the drive mechanism 100. The drive gear 1700 may include one or more gears 1710 which drive the additional cartridge components.

FIG. 18 shows the drive gear 200 attached to an OPC drum 1800 in accordance with the present invention.

Although specific embodiments have been illustrated and described herein, those of ordinary skill in the art appreciate that any arrangement that is calculated to achieve the same purpose may be substituted for the specific embodiments shown and that the invention has other applications in other environments. This application is intended to cover any adaptations or variations of the present invention. The following claims are in no way intended to limit the scope of the invention to the specific embodiments described herein.

What is claimed is:

1. A drive gear for a generally cylindrical imaging component, the drive gear comprising:
 - a body for engaging the generally cylindrical imaging component;
 - a cylindrical shaft attached to the body, the cylindrical shaft having an end surface;
 - three prongs extending longitudinally outward from the end surface, wherein each of the three prongs is generally rectangular in cross section; and
 - a bracing member disposed between at least two of the prongs.
2. The drive gear of claim 1 wherein the bracing member connects one prong to the other two prongs.
3. A drive gear for a generally cylindrical imaging component, the drive gear comprising:
 - a body for engaging the generally cylindrical imaging component;
 - a cylindrical shaft attached to the body, the cylindrical shaft having an end surface; and
 - three prongs extending longitudinally outward from the end surface, wherein each of the three prongs is generally rectangular in cross section, wherein each of the three prongs extends longitudinally and radially outward from the end surface.
4. An imaging apparatus assembly comprising:
 - a drive mechanism including a helical recess;
 - a drive gear including a body for engaging a generally cylindrical imaging component; a cylindrical shaft attached to the body, the cylindrical shaft having an end surface; and three prongs extending longitudinally outward from the end surface and engaging the helical

7

recess, wherein each of the three prongs is generally rectangular in cross section; and
a bracing member disposed between at least two of the prongs.

5 5. The imaging apparatus of claim 4 wherein the bracing member connects one prong to the other two prongs.

6. An imaging apparatus assembly comprising:
a drive mechanism including a helical recess; and
a drive gear including a body for engaging a generally cylindrical imaging component; a cylindrical shaft
10 attached to the body, the cylindrical shaft having an end surface; and three prongs extending longitudinally outward from the end surface and engaging the helical recess, wherein each of the three prongs is generally rectangular in cross section,

15 wherein each of the three prongs extends longitudinally and radially outward from the end surface.

7. An imaging apparatus assembly comprising:
a generally cylindrical imaging component;
a drive gear including a body engaging a generally cylindrical imaging component; a cylindrical shaft attached

8

to the body, the cylindrical shaft having an end surface; and three prongs extending longitudinally outward from the end surface, wherein each of the three prongs is generally rectangular in cross section; and

a bracing member disposed between at least two of the prongs.

8. The imaging apparatus of claim 7 wherein the bracing member connects one prong to the other two prongs.

9. An imaging apparatus assembly comprising:

a generally cylindrical imaging component; and

a drive gear including a body engaging a generally cylindrical imaging component; a cylindrical shaft attached to the body, the cylindrical shaft having an end surface; and three prongs extending longitudinally outward from the end surface, wherein each of the three prongs is generally rectangular in cross section,

wherein each of the three prongs extends longitudinally and radially outward from the end surface.

* * * * *