



US008746225B2

(12) **United States Patent**
Christopher et al.

(10) **Patent No.:** **US 8,746,225 B2**
(45) **Date of Patent:** **Jun. 10, 2014**

(54) **PAINTBALL LOADER DRIVE SYSTEM**

(75) Inventors: **James T. Christopher**, Garland, TX (US); **Chris T. Goddard**, Lewisville, TX (US); **David M. Banks**, Dallas, TX (US)

(73) Assignee: **KEE Action Sports I LLC**, Swewll, NJ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/361,526**

(22) Filed: **Jan. 30, 2012**

(65) **Prior Publication Data**

US 2012/0272940 A1 Nov. 1, 2012

Related U.S. Application Data

(63) Continuation of application No. 12/264,012, filed on Nov. 3, 2008, now Pat. No. 8,104,462, which is a continuation of application No. 11/116,774, filed on Apr. 28, 2005, now Pat. No. 7,445,002, which is a continuation of application No. 10/414,134, filed on Apr. 14, 2003, now Pat. No. 6,889,680.

(60) Provisional application No. 60/372,273, filed on Apr. 12, 2002.

(51) **Int. Cl.**
F41B 11/02 (2006.01)

(52) **U.S. Cl.**
USPC **124/51.1**

(58) **Field of Classification Search**
USPC 124/48, 51.1, 52
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,404,689 A 1/1922 Fairweather
1,743,576 A 1/1930 Smith

1,867,513 A 7/1932 Lahti
1,954,093 A 4/1934 Nelson
2,357,951 A 9/1944 Hale
2,639,904 A 5/1953 McMaster et al.
3,248,008 A 4/1966 Meierjohan
3,610,223 A 10/1971 Green
3,630,118 A 12/1971 Stoner

(Continued)

FOREIGN PATENT DOCUMENTS

DE 876370 5/1953
DE 2035097 1/1972

(Continued)

OTHER PUBLICATIONS

WARPIG—World and Regional Paintball Information Guide, <http://www.warpig.com/paintball/technical/loaders/halo/index.shtml>, WARPIG.COM, Odyssey Readies Halo for Production, By Bill Mills, Jun. 2001, pp. 1 to 6.

(Continued)


Primary Examiner — John Ricci

(74) *Attorney, Agent, or Firm* — Volpe and Koenig, P.C.

(57) **ABSTRACT**

The present invention is directed to a ball feed mechanism and associated method for use in a paintball loader. The ball feed mechanism includes a feeder which conveys or impels balls toward a feed neck, and a drive member which is concentric with the feeder. The feeder is coupled to the drive member. An electric motor is used to rotate the drive member which in turn causes the feeder to rotate. The feed mechanism includes sensors which detect the motion of the feeder and the drive member. A controller determines the position of the feeder relative to the drive member and actuates a motor when necessary.

13 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,695,246 A 10/1972 Filippi et al.
 3,855,988 A 12/1974 Sweeton
 3,894,657 A 7/1975 Eckmayr
 4,027,646 A 6/1977 Sweeton
 4,044,290 A 8/1977 Gullo
 4,148,415 A 4/1979 Florida et al.
 4,207,857 A 6/1980 Balka, Jr.
 4,332,097 A 6/1982 Taylor, Jr.
 4,396,193 A 8/1983 Reinhardt et al.
 4,695,954 A 9/1987 Rose et al.
 4,748,600 A 5/1988 Urquhart
 4,759,435 A 7/1988 Cedrone
 4,965,951 A 10/1990 Miller et al.
 4,993,400 A 2/1991 Fitzwater
 5,042,685 A 8/1991 Moulding, Jr. et al.
 5,061,222 A 10/1991 Suris
 5,070,995 A 12/1991 Schaffer et al.
 5,097,816 A 3/1992 Miller
 5,097,985 A 3/1992 Jones
 5,282,454 A 2/1994 Bell et al.
 5,335,579 A 8/1994 David
 5,456,153 A 10/1995 Bentley et al.
 5,505,188 A 4/1996 Williams
 5,520,171 A 5/1996 David
 5,542,570 A 8/1996 Nottingham et al.
 5,561,258 A 10/1996 Bentley et al.
 5,600,083 A 2/1997 Bentley et al.
 5,673,812 A 10/1997 Nelson
 5,722,383 A 3/1998 Tippmann, Sr. et al.
 5,727,538 A 3/1998 Ellis
 5,736,720 A 4/1998 Bell et al.
 5,791,325 A 8/1998 Anderson
 5,794,606 A 8/1998 Deak
 5,809,983 A 9/1998 Stoneking
 5,816,232 A 10/1998 Bell
 5,836,583 A 11/1998 Towers
 5,839,422 A 11/1998 Ferris
 5,947,100 A 9/1999 Anderson
 5,954,042 A 9/1999 Harvey
 6,062,208 A 5/2000 Seefeldt et al.
 6,083,105 A 7/2000 Ronin et al.
 6,109,252 A 8/2000 Stevens
 6,206,562 B1 3/2001 Eyraud et al.
 6,213,110 B1 4/2001 Christopher et al.
 6,220,237 B1 4/2001 Johnson et al.
 6,305,367 B1 10/2001 Kotsiopoulos et al.
 6,311,682 B1 11/2001 Rice et al.
 6,327,953 B1 12/2001 Andresen
 6,415,781 B1 7/2002 Perrone
 6,418,919 B1 7/2002 Perrone
 6,467,473 B1 10/2002 Kostopoulos
 6,488,019 B2 12/2002 Kotsiopoulos
 6,502,567 B1 1/2003 Christopher et al.
 6,520,854 B1 2/2003 McNally
 6,526,955 B1 3/2003 Juan
 6,609,511 B2 8/2003 Kotsiopoulos et al.
 6,644,293 B2 11/2003 Jong
 6,701,907 B2 3/2004 Christopher et al.
 6,725,852 B1 4/2004 Yokota et al.
 6,739,323 B2 5/2004 Tippmann, Jr.
 6,792,933 B2 9/2004 Christopher et al.
 6,889,680 B2 5/2005 Christopher et al.
 6,899,328 B2 5/2005 Halliburton et al.
 6,915,792 B1 7/2005 Sheng
 6,978,776 B2 12/2005 Hamilton
 6,981,493 B1 1/2006 Poteracke
 7,017,569 B2 3/2006 Jong
 7,021,302 B2 4/2006 Neumaster et al.
 7,040,505 B2 5/2006 Hashimoto et al.
 7,222,617 B2 5/2007 Andresen
 7,234,456 B2 6/2007 Andresen
 7,270,121 B2 9/2007 Lubben
 7,343,909 B2 3/2008 Christopher et al.
 7,357,129 B2 4/2008 Neumaster et al.
 7,428,899 B2 9/2008 Andresen

7,445,002 B2 11/2008 Christopher et al.
 7,654,255 B2 2/2010 Spicer
 7,770,569 B2 8/2010 Andresen
 7,832,389 B2 11/2010 Christopher
 7,921,834 B2 4/2011 Hamilton
 2002/0092513 A1 7/2002 Christopher et al.
 2003/0047173 A1 3/2003 Juan
 2004/0074487 A1 4/2004 Christopher et al.
 2004/0211402 A1 10/2004 Christopher et al.
 2004/0245276 A1 12/2004 Hashimoto et al.
 2005/0274370 A1 12/2005 Lubben
 2006/0086347 A1 4/2006 Hedberg
 2006/0196489 A1 9/2006 Campo
 2006/0249131 A1 11/2006 Broersma
 2006/0254572 A1 11/2006 Hall
 2007/0012304 A1 1/2007 van Dorsser et al.
 2007/0017494 A1 1/2007 Andresen
 2007/0017495 A1 1/2007 Andresen
 2007/0056573 A1 3/2007 Campo
 2007/0062506 A1 3/2007 Bell
 2007/0101981 A1 5/2007 Chen
 2007/0113834 A1 5/2007 Spicer
 2007/0137631 A1 6/2007 Christopher
 2007/0215137 A1 9/2007 Jones et al.
 2007/0246479 A1 10/2007 Andresen
 2008/0047536 A1 2/2008 Chen
 2008/0141990 A1 6/2008 Andresen
 2008/0178859 A1 7/2008 Moore et al.
 2009/0000608 A1 1/2009 Christopher et al.
 2009/0025700 A1 1/2009 Andresen

FOREIGN PATENT DOCUMENTS

DE 3721527 1/1989
 DE 4343870 6/1994
 DE 4343871 6/1995
 DE 19922589 12/2000
 EP 0075970 4/1983
 EP 1054228 11/2000
 EP 1653189 5/2006
 FR 921527 5/1947
 GB 470201 8/1937
 GB 551077 2/1943
 GB 2322438 8/1998
 JP 1179898 7/1989
 JP 6-325233 11/1994
 TW M255391 1/2005
 WO 98/13660 4/1998
 WO 01/44745 6/2001
 WO 02/42708 5/2002
 WO 03/087698 10/2003
 WO 2007/033309 3/2007
 WO 2007/035601 3/2007
 WO 2007/044546 4/2007
 WO 2007/044822 4/2007
 WO 2007/098554 9/2007
 WO 2008/104061 4/2008
 WO 2009/009748 1/2009

OTHER PUBLICATIONS

WARPIG—World and Regional Paintball Information Guide, <http://www.warpig.com/paintball/technical/loaders/halo/review.shtml>,
 WARPIG.COM, Odyssey Halo By Bill Mills, Dec. 2001, pp. 1 to 7.
 Odyssey Halo B Paintball Hopper Review, [http://www.paintball-gun-review.com/hopper-reviews/odyssey-halo-b . . .](http://www.paintball-gun-review.com/hopper-reviews/odyssey-halo-b...), Paintball Gun Review, Odyssey Halo B Paintball Hopper Review, 2004 Paintball-Gun-Review.com, pp. 1 to 3.
www.ODYSSEYPAINBALL.com, [http://web.archive.org/web/20030205112543/http://www.odysseypain . . .](http://web.archive.org/web/20030205112543/http://www.odysseypain...), Odyssey Paintball Products, Understanding Halo B, pp. 1 to 3.
 WARPIG—World and Regional Paintball Information Guide, [http://www.warpig.com/paintball/technical/loaders/evlution/evlution . . .](http://www.warpig.com/paintball/technical/loaders/evlution/evlution...)
 eVLution 2 Sneak Preview, by Bill Mills, Aug. 2001, p. 1 to 4.
 WARPIG—World and Regional Paintball Information Guide, <http://www.warpig.com/paintball/technical/loaders/evlution/index.shtml>
 Brass Eagle's eVLution Loader, by Bill Mills, Aug. 2000, pp. 1 to 7.

(56)

References Cited

OTHER PUBLICATIONS

WARPIG—World and Regional Paintball Information Guide, <http://www.warpig.com/paintball/technical/labs/revytimes/index/shtml>

WARPIG Ballistic Labs Report: Revolution Response Times, by Bill Mills, copyright 1992-2010, pp. 1 to 4.

WARPIG—World and Regional Paintball Information Guide <http://www.warpig.com/paintball/technical/loaders/lineup> WARPIG Ballistic Labs Loader Speed Comparison, by Bill Mills, Sep. 2001, 8 pages.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 10




FIG. 7




FIG. 8




FIG. 9

PAINTBALL LOADER DRIVE SYSTEM**CROSS REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 12/264,012, filed Nov. 3, 2008, issuing as U.S. Pat. No. 8,104,462 on Jan. 31, 2012, which is a continuation of U.S. patent application Ser. No. 11/116,774, filed Apr. 28, 2005, which issued as U.S. Pat. No. 7,445,002 on Nov. 4, 2008, which is a continuation of U.S. patent application Ser. No. 10/414,134, filed Apr. 14, 2003, which issued as U.S. Pat. No. 6,889,680 on May 10, 2005, which claims priority to U.S. Provisional Patent Application No. 60/372,273, filed Apr. 12, 2002, which are all incorporated by reference as if fully set forth herein.

FIELD OF INVENTION

This invention relates to paintball loaders and, more particularly, to a detection system for controlling ball feed in a paintball loader.

BACKGROUND

Popularity and developments in the paintball industry have led to the demand for increased performance from paintball guns. Paintball gun users usually partake in paintball war games. A paintball war game is generally played between two teams of players that try to capture the opposing team's flag. Each flag is located at the team's home base. Such a game is played on a large field with opposing home bases at each end. The players are each armed with a paintball gun that shoots paintballs. Paintballs are gelatin-covered spherical capsules filled with paint.

During the game, the players of each team advance toward the opposing team's base in an attempt to steal the opposing team's flag. The players must do so without first being eliminated from the game by being hit by a paintball shot by an opponent's gun. When a player is hit by a paintball the gelatin capsule ruptures and the paint is splashed onto the player. As a result the player is "marked" and is out of the game.

These war games have increased in popularity and sophistication resulting in more elaborate equipment. One such improvement is the use of semi-automatic and automatic paintball guns which allow for rapid firing of paintballs. As a result of the increased firing speed, a need has developed for increased storage capacity of paintballs in the paintball loaders that are mounted to the gun. Also, users demand faster feed rates as the guns continue to develop.

Paintball loaders typically include a housing that sits on an upper portion of a paintball gun and which is designed to hold a large quantity of paintballs. There is an outlet tube at the bottom of the housing through which the paintballs drop by the force of gravity. The paintballs pass into an inlet tube located in the upper portion of the gun.

In use, paintballs fall sequentially through the outlet tube into the inlet of the gun. The inlet tube directs each paintball into the firing chamber of the gun where the paintball is propelled outwardly from the gun by compressed air. Because existing paintball loaders rely on the force of gravity to feed the paintballs to the gun, they function properly to supply paintballs only if the gun and the loader are held in a substantially upright position. If, during a game, a player is forced to hold the gun sideways or upside down, the loader will not function properly.

Furthermore, it is not uncommon that, while feeding paintballs to the gun, the paintballs jam in the gun. In order to correct the problem, the player may shake the gun or strike the loader in order to dislodge the jammed paintball. This obviously places the player at risk during the game since the player is distracted by the need to adjust the equipment.

Currently there are on the market paintball loaders that utilize an optical sensor mounted within the loaders to detect the absence of a paintball in the infeed tube of a paintball gun. When the sensor detects that there is no paintball in the infeed tube of the paintball gun, a motor is activated which causes a paddle to force a paintball into the paintball gun. Other conventional paintball loaders utilize agitators having sound sensors to sense a gun firing event. In response to the sound of the gun firing, an electrical signal is sent to activate an agitator which moves a paintball into the feed tube.

While recent feed systems are an improvement over the prior feeders, the current feed systems are complicated and costly to manufacture. Such systems may also lead to jamming.

There is, therefore, a need for a feed mechanism for a feed system that simply and reliably feeds paintballs to a paintball gun at a high rate, while at the same time prevents or reduces the likelihood of paintball jams. There is also a need for a paintball loader which controls the feed motor so as to prolong battery life and reduce undesirable noise.

SUMMARY

In one aspect, the present invention is a ball feed mechanism for use in a paintball loader. The ball feed mechanism includes a feeder for feeding paintballs. The feeder may be a drive cone, paddle wheel, or indexing belt, which has protrusions, recesses or paddles that convey or impel balls toward a feed neck. The feed mechanism also preferably includes a drive shaft which is concentric with the feeder. The feeder mounts on the drive shaft and is free to rotate about the drive shaft before engaging mechanical stops. The feeder is coupled to the drive shaft through a spring. The spring is configured to store potential energy which is used to rotate the feeder and, thus, drive the balls toward the feed neck. An electric motor is used to rotate the drive shaft to wind or compress the spring.

In operation the spring is normally compressed so that the spring energy is always available to impel balls toward the feed neck as required. The motor is energized as needed to restore the spring energy (e.g., through compression of the spring). Other resilient members, such as elastomers, may be used in place of the spring.

The feed mechanism includes an indexing mechanism which includes a sensor, for example, to determine the degree of tension or winding of the spring. In one embodiment, the indexing mechanism accomplishes this by using the sensors to detect rotational movement of the feeder and a drive mechanism (which includes the drive shaft). A controller is in communication with the sensors and determines the relative position of the feed mechanism to the drive mechanism for determining whether the spring requires winding. The relative position of the feeder and drive mechanism can be correlated with the degree of compression/tension of the spring. If the controller determines that the spring requires winding, a motor is activated, causing the drive mechanism to rotate. This, in turn, causes the spring to wind.

The feed mechanism may alternately include a tensionometer or a strain gauge in communication with a controller. These devices are used to determine the state of deflection of the spring. If the controller determines that additional deflec-

tion of the spring is required, the controller will actuate a motor which rotates the drive mechanism and the spindle. The rotation of the spindle, in turn, causes the spring to compress or tension.

The foregoing and other features of the invention and advantages of the present invention will become more apparent in light of the following detailed description of the preferred embodiments, as illustrated in the accompanying figures. As will be realized, the invention is capable of modifications in various respects, all without departing from the invention. Accordingly, the drawings and the description are to be regarded as illustrative in nature, and not as restrictive.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing summary, as well as the following detailed description of the invention, will be better understood when read in conjunction with the appended drawings. In the drawings:

FIG. 1 is a side elevation view of a rapid feed paintball loader constructed in accordance with the teachings of the present invention and operatively attached to a representative paintball gun illustrated in phantom;

FIG. 2 is an exploded upper isometric view of one embodiment of the loader according to the present invention;

FIG. 3 is an exploded lower isometric view of the embodiment of the loader shown in FIG. 2;

FIG. 4 is a lower isometric view of the embodiment of the loader shown in FIG. 3;

FIG. 5 is an exploded upper isometric view of a second embodiment of the loader according to the present invention;

FIG. 6 is a side view of the loader of FIG. 5;

FIG. 7 is a top view of an alternate feeder according to the present invention;

FIG. 8 is a top view of yet another feeder according to the present invention;

FIG. 9 is a schematic of a controller according to the present invention; and

FIG. 10 illustrates a pulley mechanism for driving the drive shaft in accordance with an alternate embodiment of the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the drawings wherein like numerals indicate like elements throughout, FIG. 1 is a side elevation view of paintball loader 40 in accordance with the present invention and operatively attached to a representative paintball gun 20, illustrated in phantom. The paintball gun 20, includes a main body 22, a compressed gas cylinder 24, a front handgrip 26, a barrel 28, and a rear handgrip 30. The paintball gun 20 also includes an inlet tube 32, leading to a firing chamber (not shown) in the interior of the main body and a trigger 34. The front handgrip 26 preferably extends downwardly from the barrel 28 and provides a grip. The compressed gas cylinder 24 is typically secured to a rear portion of the paintball gun 20. The compressed gas cylinder normally contains CO₂, NO₂ or air, although other gases may also be used.

In using the paintball gun 20, trigger 34 is squeezed, thereby actuating the compressed gas cylinder to release controlled bursts of compressed gas. The bursts of gas are used to eject paintballs outwardly through the barrel 28. The paintballs are continually fed by the paintball loader 40 through the

inlet tube of the firing chamber. The paintball gun depicted in FIG. 1 is an automatic paintball gun, however the gun may also be semi-automatic.

The paintball loader 40 comprises a paintball container 42 having a container wall 44 forming an interior area 46. The container has an upper portion 48 and a lower portion 50. An exit tube 52 leads from the lower portion of the container to an outlet opening 54. The exit tube is positioned on top of the inlet tube 32 of the paintball gun 20. A feed mechanism 100 (shown in FIG. 2) is used to drive or urge the paintballs toward the exit tube and into the inlet tube 32.

FIG. 2 is an exploded isometric view of one embodiment of the feed mechanism 100 according to the present invention. While a preferred feed mechanism 100 is shown, various other components may be substituted therefore for driving paintballs into the paintball gun 20. The feed mechanism 100 includes a feeder 102 which drives or otherwise conveys paintballs into the exit tube 52, and a drive mechanism 500.

A variety of feeders 102 can be used in the present invention, including an feeder, drive cone, paddle wheel, carrier or other device which can direct or otherwise urge paintballs from the loader into the exit tube 52. One preferred feeder 102 is shown in the figures and includes a housing 103 with a plurality of fins 104 which preferably extend in a radial direction from the housing 103. While the fins 104 are shown as being straight, other shapes can be used as will be discussed below. The feeder 102 also preferably includes flanges 105 that extend between adjacent fins 104. As should be apparent from the drawings, the housing, fins and flanges can be made as a single injection molded part. While fins are shown, the feeder may include recesses within which the paintballs sit as they are shuttled toward the exit tube.

A cylindrical opening 106 is formed in the center of the housing 103 for receiving a fastener 130. The fastener 130 is used to engage or mount the feeder 102 to a drive shaft or spindle 108 of the drive mechanism 500. More particularly, the fastener 130 extends through the opening 106 and threads into a hole formed in the top of the drive shaft 108.

Referring now to FIG. 3, the bottom of the feeder 102 is shown in more detail. The housing 103 includes a first flange 124 which is attached to and projects downward from the housing 103. In the illustrated embodiment, the first flange 124 is formed integral with the housing 103. The first flange 124 is designed to engage with a first end of a spring 116 as will be better understood hereafter.

As shown in FIGS. 2-4, the drive mechanism 500 includes a spring housing 112 which is disposed about the drive shaft 108 and is positioned so as to be below the feeder 102. The spring housing 112 includes an outer wall 113 and a bottom wall 115. An inner wall 117 is formed about a central opening 119. The drive shaft 108 is designed to pass through the central opening 119 and engage with the spring housing 112 such that rotation of the drive shaft 108 produces concomitant rotation of the spring housing 112. In the illustrated embodiment, a portion of the drive shaft 108 is shown non-cylindrical in shape and the opening 119 is formed with a mating non-cylindrical shape. A spring clip 132 or similar fastener is preferably used to restrain vertical movement of the spring housing 112 on the drive shaft 108. This is more clearly illustrated in FIG. 4 which shows the spring housing 112 mounted to the drive shaft 108.

A second flange 120 is attached to or, more preferably, formed integral with the spring housing 112. The second flange 120 is configured to engage with a second end of the spring 116.

The inner wall 117 and outer wall 113 define a spring chamber 114 within the spring housing 112. A spring or other

5

biasing member **116** is located within the spring chamber **114**. Although a spring is shown in the figures, it should be readily apparent that other biasing members, such as elastomers, could instead be used. The spring **116** is preferably a torsion spring. A first leg **150** on the first end of the spring **116** is adapted to engage with the first flange **124** on the feeder **102**. A second leg **152** on the second end of the spring is adapted to engage with the second flange **120** on the spring housing **112**. As such, the spring **116** is mounted so as to bias the feeder **102** against rotation relative to the spring housing **112**. In other words, rotation of the spring housing **112** relative to the feeder **102** produces deflection or winding of the spring **116**. When the spring is rotated in the direction which produces winding of the spring, the rotation creates a restoring force (potential energy) in the spring which attempts to counter-rotate the spring housing **112** relative to the feeder **102**. As should be readily apparent, if the feeder **102** is unrestrained, rotation of the spring housing will produce concomitant rotation of the feeder **102**. It is only when there is something which inhibits rotation of the feeder **102** (such as paint balls already in the exit tube) that the spring housing **112** will wind the spring **116**.

FIG. 4 illustrates the assembled feeder **102**, spring housing **112**, and the drive shaft **108**. The drive shaft **108** projects downward from the spring housing **112** and is adapted to engage with a drive member or gear that is part of the drive mechanism **500**.

Extending downward from the lower surface of the feeder **102** is at least one and, more preferably, a plurality of spaced apart upper indexing teeth **160**. The upper indexing teeth **160** are preferably spaced in a circular pattern about the bottom of the feeder **102**. As will be discussed below, the upper indexing teeth **160** are used in combination with a sensor to determine the rotational position of the feeder **102**. The indexing teeth **160** are preferably formed integral with or attached to the feeder **102**. While indexing teeth are shown in the illustrated embodiment, other indexing members, such as reflectors, markers, recesses, etc, may be used.

Referring back to FIGS. 2 and 3, one embodiment of the drive member **508** is shown. In this embodiment, the drive member **508** is a drive gear includes a plurality of spaced apart gear teeth **503** formed about the periphery of the drive gear **508**. The teeth **503** of the drive gear **508** are adapted to engage with mating teeth on a second gear connected to a motor **95**. While the drive member **508** in the illustrated embodiment is a gear, other types of conventional drive members can be used to produce controlled rotation, such as a pulley mechanism or stepper motor. A pulley mechanism is shown in FIG. 10. The pulley **508** is engaged to the motor through a belt **97**.

The drive member **508** also includes at least one and, more preferably, a plurality of lower indexing members **510** formed on the drive gear **508** and preferably on its lower surface. As with the upper indexing teeth **160**, the lower indexing members **510** are used to determine the position of the drive gear **508** and, thus, the spring housing **112**. While the indexing members are shown as protrusions in the illustrated embodiment, other indexing members, such as teeth, reflectors, markers, recesses, etc, may be used.

The feed mechanism **100** also includes a first indexing sensor positioned below and preferably adjacent to the lower surface of the feeder **102**. The first indexing sensor **504** is located so as to be able to detect or otherwise sense the upper indexing teeth **160**. More particularly, as the feeder **102** rotates around its central axis, the sensor **504** detects the upper indexing teeth **160** as they pass the sensor. The number of passing teeth **160** that is sensed (e.g., over a prescribed period) is used to determine the rotational motion of the

6

feeder **102**. As should be readily apparent, the more upper indexing teeth **160** that are formed on the feeder **102**, the more accurate the position of the feeder **102** can be determined. A signal is sent from the sensor indicative of the sensed number of passing teeth. Alternatively, the sensor **504** may be a ratcheting mechanism that supplies the controller with a signal after the ratchet has rotated a predetermined number of times or amount.

A second indexing sensor **506** is mounted adjacent to the drive gear **508** so as to be able to detect the passing of the lower indexing members **510**. The rotational motion of the drive gear **508** and, thus, the spring housing **112**, is determined by counting the number of passing lower indexing members **510**. A signal is sent from the sensor indicative of the sensed number of passing teeth. While the illustrated embodiment depicts the sensor and indexing members as being mounted to the drive gear, it should be readily understood that the sensor can be mounted so as to detect rotational motion of the drive shaft.

Referring to FIG. 9, the first indexing sensor **504** and second indexing sensor **506** are in communication with a controller **900**, such as a computer or microprocessor (not shown). The controller **900** determines the position of the feeder **102** relative to the drive gear **508** and evaluates whether the spring **116** requires tensioning (winding) or deflection. If the controller **900** determines that the spring **116** requires tensioning, the controller will actuate a motor **950** which is engaged with the drive gear **508** to rotate the drive gear **508** a desired amount. The engagement is preferably through a drive system **960**, such as a gear that meshes with the teeth **503** on the drive gear **508**. Rotation of the drive gear **508**, in turn, rotates the drive shaft **108** and, thus, the spring housing **112**. The rotation of the spring housing **112** relative to the feeder **102** causes the spring **116** to wind, preferably until the second flange **120** meets the first flange **124**.

During operation, as the feeder **102** advances the paint balls into the gun, the first sensor **504** counts the number of upper indexing teeth **160** that have passed and provides a signal to the controller. The second sensor **506**, likewise, counts the number of lower indexing members **510** that have passed and provides a signal indicative thereof to the controller. It is envisioned that, during firing, the drive gear **508** may not necessarily be moving. Instead, only after the controller **900** detects that the positional location of the feeder **102** relative to the drive gear **508** correlates to a spring that needs "rewinding" would the controller **900** send a signal to the motor **950** to rotate the drive gear **508**. For example, the system may be set such that only after half of the paintballs are dispensed that can be held by the feeder is the motor activated to rotate the drive gear **508**.

Alternately, the controller **900** can continuously monitor the movement of the feeder **102** and the drive gear **508**. Any movement of the feeder **102** relative to the drive gear **508** can result in the motor rotating the drive gear **508** to rewind the spring. Thus, the gun will always be set to feed the maximum number of balls possible using the feeder.

The controller **900** may also be programmed to rotate the drive gear **508** a prescribed distance to wind the spring, thus preventing overwinding. The lower indexing members **510** can be tracked through the second sensor **506** to stop the rotation of the drive gear **508** when desired. For example, the controller may be programmed to tension the spring a sufficient amount to feed 10 paintballs into the gun before needing to be rewound. Upon firing of the gun, tension of the spring will feed the 10 paintballs into the exit tube. The controller determines the number of balls to be fed from the data provided by the first indexing sensor **504**.

Alternatively, the present invention may utilize only one sensor to detect the movement of the feeder. A motor, such as a stepper motor, can be used to incrementally wind the spring for every detected movement of the feeder. For example, if the spring has a tension sufficient to feed 10 paintballs, for every ball that the sensor detects as being fed by the feeder, the motor will wind the spring by 1/10th of the complete rotation.

The controller may be used to detect whether there are any paintballs in the exit tube. If the controller 900 determines that there are no paintballs in the tube, that would indicate that the spring is in an unwound condition. Thus, the controller 900 would activate the motor 950 and rewind the spring.

An alternate embodiment of the sensor mechanism is shown in FIG. 5. In this embodiment, the first sensor includes a first emitter 602 and a first receiver 604. The first emitter 602 provides a beam that is reflected by reflectors placed around the periphery of the underside of feed cone 102. The reflected signal is detected by receiver 604. Although depicted separately for clarity, the emitter 602 and receiver 604 may be housed in the same unit. The beam may be an infrared (IR) beam. Likewise a second emitter 606 and a second receiver 608 are provided in lieu of second indexing sensor 506. The second emitter 606 provides a beam that is reflected by reflectors placed around the periphery of the top or underside of drive gear 508. The reflected beam is detected by second receiver 608. The emitter 606 and receiver 608 may be housed in the same unit, or mounted separate as shown. The first and second emitters/receivers are in communication with the controller 900. FIG. 6 illustrates the assembled unit of FIG. 5.

The sensing mechanism may instead include a tensionometer or strain gauge 93 (shown in phantom in FIG. 2) to determine the tension of the spring. The strain gauge would be in communication with the controller. If the tension in the spring falls below a preselected limit, the controller will actuate the motor which rotates the drive mechanism that in turn rotates the spindle, thereby tensioning the spring.

Referring to FIGS. 7 and 8, alternate feeder arrangements are shown. More particularly, FIG. 7 illustrates a feeder 200 which includes two fins 202. The fins are spaced 180 degrees apart, thus permitting a plurality of balls 206 to be located between adjacent fins 202. FIG. 8 illustrates a feeder with a plurality of curved fins 302, each one designed to cup an individual paintball 206. Those skilled in the art would be readily capable of substituting alternate design configurations for the feeder in order to effect sufficient feeding of the desired number of paint balls.

The present invention provides a novel system for feeding paintballs from a container. The use of a two sensors permits controlled feeding which is not possible with conventional feeders. The controller in the present invention can be adjusted to minimize use of the motor, thereby conserving battery power. The controller can also be used to accurately track the amount of balls dispensed.

Furthermore, the controller in the present invention can also be controlled so as to vary the tension and pressure applied to the ball supply. The feed mechanism can include a user input mechanism, such as a dial or pushbuttons, which permits the user to adjust when the drive mechanism re-winds the spring.

While the potential energy caused by the spring has been described as resulting from winding the spring, it should be readily apparent that a compression spring can be used, in which case the winding of the spring should be understood to refer to a compression of the spring to build up a restoring force or potential energy.

The present invention may be embodied in other specific forms without departing from the spirit thereof and, accord-

ingly, reference should be made to the appended claims, rather than to the foregoing specification, as indicating the scope of the invention.

Although preferred embodiments of the sensors have been described and shown in the drawings, those skilled in the art will understand how features from the two embodiments may be combined and interchanged.

What is claimed is:

1. A paintball loader comprising:

a container;
a feed mechanism comprising a motor;
a sensor configured to directly detect movement of at least a portion of the feed mechanism; and
a controller in communication with the motor and the sensor, the controller configured to operate the motor in response to a signal generated by the sensor.

2. The paintball loader of claim 1, wherein the controller comprises a microprocessor.

3. The paintball loader of claim 1, wherein the feed mechanism comprises at least one indexing member and the controller determines movement of the feeder based on a signal provided by the sensor, indicative of the movement of the indexing member.

4. The paintball loader of claim 3, wherein the sensor detects changes in the position of the indexing member, and the controller determines movement of the feeder based on the changes and operates the motor based on the changes.

5. The paintball loader of claim 3, further comprising a second sensor, in communication with the controller, which detects the indexing member and sends a second signal to the controller, the controller comparing the signals to determine movement of the feeder.

6. A method of controlling a paintball loader motor comprising:

directly detecting movement of at least a portion of a feed mechanism of the paintball loader;
sending a signal indicative of movement of at least a portion of the feed mechanism; and
operating the motor based on the signal.

7. The method of claim 6, wherein movement of the feeder is detected by a sensor.

8. The method of claim 6, wherein a controller receives the signal and operates the motor.

9. The method of claim 8, wherein the controller is a microprocessor.

10. A method of controlling projectile feeding in a paintball gun from a loader having a feed mechanism comprising a motor for feeding paintballs into the paintball gun, the feed mechanism comprising:

at least a portion adapted to move;
a sensor for detecting movement of at least a portion of the feed mechanism; and
a controller for controlling the motor, the method comprising the steps of:
detecting movement of at least a portion of the feed mechanism with the sensor;
receiving signals at the controller from the sensor;
determining movement of the feeder based on the signals received from the sensor; and
controlling the motor based on the signal.

11. A method of controlling a motor of a paintball loader having a feed mechanism comprising at least one moveable portion, the method comprising directly detecting movement of at least a portion of the feed mechanism and controlling the operation of the motor in response to the detection.

12. The method of claim 11, wherein the detection is by a sensor.

13. The method of claim 12, wherein the operation of the motor is controlled by a controller in communication with the sensor.

* * * * *