



US008749346B2

(12) **United States Patent**
Flick

(10) **Patent No.:** **US 8,749,346 B2**
(45) **Date of Patent:** ***Jun. 10, 2014**

(54) **VEHICLE SECURITY SYSTEM INCLUDING PRE-WARNING FEATURES FOR A VEHICLE HAVING A DATA COMMUNICATIONS BUS AND RELATED METHODS**

(71) Applicant: **Omega Patents, L.L.C.**, Douglasville, GA (US)

(72) Inventor: **Kenneth E. Flick**, Douglasville, GA (US)

(73) Assignee: **Omega Patents, L.L.C.**, Douglasville, GA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/854,585**

(22) Filed: **Apr. 1, 2013**

(65) **Prior Publication Data**

US 2013/0271262 A1 Oct. 17, 2013

Related U.S. Application Data

(60) Continuation of application No. 12/534,978, filed on Aug. 4, 2009, now Pat. No. 8,432,268, which is a
(Continued)

(51) **Int. Cl.**
B60R 25/00 (2013.01)

(52) **U.S. Cl.**
USPC **340/5.72**; 340/426.25; 340/426.15;
340/425.5; 340/539.1; 340/12.54; 701/32.7;
701/33.4

(58) **Field of Classification Search**
USPC 340/426.25, 426.15, 438, 425.5, 461,
340/539.1, 12.54; 701/32.7, 33.4
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,055,772 A 10/1977 Leung 307/10 R
4,236,594 A 12/1980 Ramsperger 180/167

(Continued)

FOREIGN PATENT DOCUMENTS

DE 19530721 2/1997 H02J 9/04
EP 0699562 7/1995 B60R 16/02

(Continued)

OTHER PUBLICATIONS

SAE International, Voss et al., In-Vehicle Data Bus Systems—The Key for New Concepts in Comfort and Convenience Electronics, Feb. 26-29, 1996, pp. 1-9.

(Continued)


Primary Examiner — Daryl Pope

(74) *Attorney, Agent, or Firm* — Allen, Dyer, Doppelt, Milbrath & Gilchrist, P.A.

(57) **ABSTRACT**

A remote control system is for a vehicle including a data communications bus extending therein, and a plurality of vehicle devices communicating over the data communications bus. The system may include a cellular transceiver within the vehicle, and a multi-vehicle controller within the vehicle and coupled to the data communications bus for communication with at least one of the plurality of vehicle devices to perform a remote vehicle function based upon a received remote control signal. The multi-vehicle controller may be enabled to communicate via the data communications bus using a desired set of signals for a corresponding desired vehicle from a plurality of sets of signals for different vehicles based upon learning from at least one of the plurality of vehicle devices on the data communications bus and downloading via the cellular transceiver.

20 Claims, 9 Drawing Sheets



Related U.S. Application Data

division of application No. 10/626,969, filed on Jul. 25, 2003, now Pat. No. 7,576,637, which is a continuation-in-part of application No. 10/264,917, filed on Oct. 4, 2002, now Pat. No. 6,696,927, which is a continuation-in-part of application No. 09/583,333, filed on May 31, 2000, now Pat. No. 6,812,829, which is a continuation-in-part of application No. 09/382,245, filed on Aug. 25, 1999, now Pat. No. 6,275,147, which is a continuation of application No. 09/023,838, filed on Feb. 13, 1998, now Pat. No. 6,011,460, which is a continuation-in-part of application No. 08/701,356, filed on Aug. 22, 1996, now Pat. No. 5,719,551.

(56)

References Cited**U.S. PATENT DOCUMENTS**

4,288,778	A	9/1981	Zucker	340/64
4,383,242	A	5/1983	Sassover et al.	340/64
4,446,460	A	5/1984	Tholl et al.	340/825.69
4,538,262	A	8/1985	Sinniger et al.	370/85
4,697,092	A	9/1987	Roggendorf et al.	307/10 R
4,754,255	A	6/1988	Saunders et al.	340/64
4,760,275	A	7/1988	Sato et al.	307/10 R
4,761,645	A	8/1988	Mochida	340/825.31
4,792,783	A	12/1988	Burgess et al.	340/22
4,794,368	A	12/1988	Grossheim et al.	340/63
4,841,159	A	6/1989	Evans et al.	307/38
4,897,630	A	1/1990	Nykerk	340/426
4,926,332	A	5/1990	Komuro et al.	364/424.05
4,933,668	A	6/1990	Oyer et al.	340/541
4,940,964	A	7/1990	Dao	340/438
5,006,843	A	4/1991	Hauer	340/825.31
5,024,186	A	6/1991	Long et al.	123/179
5,040,990	A	8/1991	Suman et al.	439/34
5,046,041	A	9/1991	Lecocq et al.	364/900
5,049,867	A	9/1991	Stouffer	340/426
5,054,569	A	10/1991	Scott et al.	180/167
5,063,371	A *	11/1991	Oyer et al.	340/541
5,081,667	A	1/1992	Drori et al.	379/59
5,084,697	A	1/1992	Hwang	340/541
5,142,278	A	8/1992	Moallemi et al.	240/825.06
5,146,215	A	9/1992	Drori	340/825.32
5,216,407	A	6/1993	Hwang	340/426.22
5,223,844	A *	6/1993	Mansell et al.	342/357.31
5,243,322	A	9/1993	Thompson et al.	340/429
5,252,966	A	10/1993	Lambropoulos et al.	340/825.69
5,315,285	A *	5/1994	Nykerk	340/426.23
5,334,974	A *	8/1994	Simms et al.	340/990
5,382,948	A	1/1995	Richmond	340/825.36
5,406,270	A	4/1995	Van Lente	340/825.34
5,469,298	A	11/1995	Suman et al.	359/630
5,473,540	A	12/1995	Schmitz	701/1
5,475,818	A	12/1995	Molyneaux et al.	395/200.05
5,481,253	A	1/1996	Phelan et al.	340/825.31
5,506,562	A	4/1996	Wiesner	340/425.5
5,521,588	A	5/1996	Kuhner et al.	340/825.22
5,523,948	A	6/1996	Adrain	364/999.999
5,525,977	A	6/1996	Suman	340/825.25
5,555,498	A	9/1996	Berra et al.	364/424.03

5,559,491	A	9/1996	Stadler	340/426
5,587,715	A *	12/1996	Lewis	342/357.24
5,606,306	A	2/1997	Mutoh et al.	340/426
5,612,578	A	3/1997	Drew	307/10.5
5,619,412	A	4/1997	Hapka	364/424.045
5,646,457	A	7/1997	Vakavtchiev	307/10.6
5,646,591	A	7/1997	Issa et al.	340/566
5,673,017	A	9/1997	Dery et al.	340/426
5,689,142	A	11/1997	Liu	307/10.5
5,719,551	A *	2/1998	Flick	340/426.25
5,721,550	A	2/1998	Lopez	341/176
5,739,748	A	4/1998	Flick	340/426
5,751,073	A	5/1998	Ross	307/10.5
5,757,086	A	5/1998	Nagashima	307/10.6
5,793,283	A	8/1998	Davis	340/426
5,811,886	A	9/1998	Majmudar	340/426
5,818,330	A	10/1998	Schweiger	340/426
5,832,397	A	11/1998	Yoshida et al.	701/29
5,838,255	A	11/1998	DiCroce	340/825.69
5,864,297	A	1/1999	Sollestre et al.	340/5.23
5,912,512	A	6/1999	Hayashi et al.	307/10.5
5,990,786	A *	11/1999	Issa et al.	340/429
6,005,478	A	12/1999	Boreham et al.	340/425.5
6,011,460	A *	1/2000	Flick	340/426.25
6,028,537	A	2/2000	Suman et al.	340/988
6,100,792	A	8/2000	Ogino et al.	340/426.25
6,243,004	B1 *	6/2001	Flick	340/426.25
6,249,216	B1 *	6/2001	Flick	340/426.14
6,275,147	B1 *	8/2001	Flick	340/426.25
6,297,731	B1 *	10/2001	Flick	340/426.16
6,392,534	B1 *	5/2002	Flick	340/426.17
7,489,233	B2	2/2009	Flick	340/426.1
7,501,937	B2	3/2009	Flick	340/426.1
8,432,268	B2 *	4/2013	Flick	340/426.1


FOREIGN PATENT DOCUMENTS

JP	HEI 111999-62793	5/1999	F02N 11/08
WO	9210387	6/1992	B60R 25/10
WO	9728988	8/1997	B60R 16/02

OTHER PUBLICATIONS

SAE International, Powers et al., The Consumerization of the Automotive Environment: The ITS Data Bus, Aug 6-8, 1997, pp. 1-7.
 SAE International, In-Vehicle Electronics for IVHS Workshop, Speaker Handouts, Nov. 30 & Dec. 1, 1995.
 SAE International, In-Vehicle Electronics for Intelligent Transportation Systems, Workshop II Results, Jul. 9-10, 1996.
 SAE Inc., Surface Vehicle Information Report, SAE J2058, Jun. 21, 1990.
 SAE Inc., Surface Vehicle Standard, SAE J1850 Jul. 1995.
 Mark Thompson, The Thick and Thin of Car Cabling, IEEE Spectrum, Feb. 1996, pp. 42-45.
 Leen et al., Expanding Automotive Electronic Systems, IEEE, Jan. 2002.
 SAE Inc., Surface Vehicle Recommended Practice, Universal Interface for OBD II Scan, SAE J2201, Jun. 30, 1993, pp. 1-45.
 SAE Inc., Surface Vehicle Recommended Practice, OBD II Scan Tool, SAE J1978, Jun. 1994, pp. 1-14.
 SAE Inc., Surface Vehicle Recommended Practice, E/E Diagnostic Test Modes, SAE J1979, Jun. 1994, pp. 1-32.

* cited by examiner

FIG. 1




FIG. 2




FIG. 3





FIG. 4






FIG. 6




FIG. 7




FIG. 8






FIG. 9

FIG. 10FIG. 11

1

VEHICLE SECURITY SYSTEM INCLUDING PRE-WARNING FEATURES FOR A VEHICLE HAVING A DATA COMMUNICATIONS BUS AND RELATED METHODS

FIELD OF THE INVENTION

The present invention relates to the field of security systems and, more particularly, to a security system and related methods for vehicles.

BACKGROUND OF THE INVENTION

Vehicle security systems are widely used to deter vehicle theft, prevent theft of valuables from a vehicle, deter vandalism, and to protect vehicle owners and occupants. A typical automobile security system, for example, includes a central processor or controller connected to a plurality of vehicle sensors. The sensors, for example, may detect opening of the trunk, hood, doors, windows, and also movement of the vehicle or within the vehicle. Ultrasonic and microwave motion detectors, vibration sensors, sound discriminators, differential pressure sensors, and switches may be used as sensors. In addition, radar sensors may be used to monitor the area proximate the vehicle.

The controller typically operates to give an alarm indication in the event of triggering of a vehicle sensor. The alarm indication may typically be a flashing of the lights and/or the sounding of the vehicle horn or a siren. In addition, the vehicle fuel supply and/or ignition power may be selectively disabled based upon an alarm condition.

A typical security system also includes a receiver associated with the controller that cooperates with one or more remote transmitters typically carried by the user as disclosed, for example, in U.S. Pat. No. 4,383,242 to Sassover et al. and U.S. Pat. No. 5,146,215 to Drori. The remote transmitter may be used to arm and disarm the vehicle security system or provide other remote control features from a predetermined range away from the vehicle. Also related to remote control of a vehicle function U.S. Pat. No. 5,252,966 to Lambropoulos et al. discloses a remote keyless entry system for a vehicle. The keyless entry system permits the user to remotely open the vehicle doors or open the vehicle trunk using a small handheld transmitter.

Unfortunately, the majority of vehicle security systems need to be directly connected by wires to individual vehicle devices, such as the vehicle horn or door switches of the vehicle. In other words, a conventional vehicle security system is hardwired to various vehicle components, typically by splicing into vehicle wiring harnesses or via interposing T-harnesses and connectors. The number of electrical devices in a vehicle has increased so that the size and complexity of wiring harnesses has also increased. For example, the steering wheel may include horn switches, an airbag, turn-signal and headlight switches, wiper controls, cruise control switches, ignition wiring, an emergency flasher switch, and/or radio controls. Likewise, a door of a vehicle, for example, may include window controls, locks, outside mirror switches, and/or door-panel light switches.

In response to the increased wiring complexity and costs, vehicle manufacturers have begun attempts to reduce the amount of wiring within vehicles to reduce weight, reduce wire routing problems, decrease costs, and reduce complications which may arise when troubleshooting the electrical system. For example, some manufacturers have adopted multiplexing schemes to reduce cables to three or four wires and to simplify the exchange of data among the various onboard

2

electronic systems as disclosed, for example, in "The Thick and Thin of Car Cabling" by Thompson appearing in the IEEE Spectrum, February 1996, pp. 42-45.

Implementing multiplexing concepts in vehicles in a cost-effective and reliable manner may not be easy. Successful implementation, for example, may require the development of low or error-free communications in what can be harsh vehicle environments. With multiplexing technology, the various electronic modules or devices may be linked by a single signal wire in a bus also containing a power wire, and one or more ground wires. Digital messages are communicated to all modules over the data communications bus. Each message may have one or more addresses associated with it so that the devices can recognize which messages to ignore and which messages to respond to or read.

The Thompson article describes a number of multiplexed networks for vehicles. In particular, the Grand Cherokee made by Chrysler is described as having five multiplex nodes or controllers: the engine controller, the temperature controller, the airbag controller, the theft alarm, and the overhead console. Other nodes for different vehicles may include a transmission controller, a trip computer, an instrument cluster controller, an antilock braking controller, an active suspension controller, and a body controller for devices in the passenger compartment.

A number of patent references are also directed to digital or multiplex communications networks or circuits, such as may be used in a vehicle. For example, U.S. Pat. No. 4,538,262 Sinniger et al. discloses a multiplex bus system including a master control unit and a plurality of receiver-transmitter units connected thereto. Similarly, U.S. Pat. No. 4,055,772 to Leung discloses a power bus in a vehicle controlled by a low current digitally coded communications system. Other references disclosing various vehicle multiplex control systems include, for example, U.S. Pat. No. 4,760,275 to Sato et al.; U.S. Pat. No. 4,697,092 to Roggendorf et al.; and U.S. Pat. No. 4,792,783 to Burgess et al.

Several standards have been proposed for vehicle multiplex networks including, for example, the Society of Automotive Engineers "Surface Vehicle Standard, Class B Data Communications Network Interface", SAE J1850, July 1995. Another report by the SAE is the "Surface Vehicle Information Report, Chrysler Sensor and Control (CSC) Bus Multiplexing Network for Class 'A' Applications", SAE J2058, July 1990. Many other networks are also being implemented or proposed for communications between vehicle devices and nodes or controllers.

Unfortunately, conventional vehicle security systems for hardwired connection to vehicle devices, such as aftermarket vehicle security systems, are not readily adaptable to a vehicle including a data communications bus. Moreover, a vehicle security system if adapted for a communications bus and devices for one particular model, model year, and manufacturer, may not be compatible with any other models, model years, or manufacturers. Other systems for remote control of vehicle functions may also suffer from such shortcomings.

SUMMARY OF THE INVENTION

In view of the foregoing background, it is therefore an object of the present invention to provide a vehicle remote control system and associated methods which provide the capability to operate with multiple vehicles.

These and other objects, features and advantages are provided by a remote control system for a vehicle comprising a data communications bus extending within the vehicle, and a plurality of vehicle devices communicating over the data

3

communications bus. The remote control system may comprise a cellular transceiver to be positioned within the vehicle, and a multi-vehicle controller to be positioned within the vehicle and coupled to the data communications bus for communication with at least one of the plurality of vehicle devices to perform a remote vehicle function based upon a received remote control signal. More particularly, the multi-vehicle controller may also be coupled to the cellular transceiver and be enabled to communicate via the data communications bus using a desired set of signals for a corresponding desired vehicle from a plurality of sets of signals for different vehicles based upon learning from at least one of the plurality of vehicle devices on the data communications bus and downloading via the cellular transceiver. Accordingly, the remote control system is compatible with multiple vehicles.

The remote control system may include a remote transmitter, and a receiver to be positioned within the vehicle and coupled to the multi-vehicle controller for receiving the remote control signal from the remote transmitter. For example, the remote transmitter may comprise a handheld transmitter.

In some embodiments, the plurality of vehicle devices may comprise a vehicle security sensor, and the multi-vehicle controller may comprise a multi-vehicle alarm controller. In other embodiments, the plurality of vehicle devices may comprise a plurality of vehicle door locks, and the multi-vehicle controller may comprise a multi-vehicle keyless entry controller. In yet other embodiments, the plurality of vehicle devices may comprise at least one device associated with starting an engine of the vehicle, and the multi-vehicle controller may comprise a multi-vehicle remote start controller. At least one of the plurality of vehicle devices may comprise at least one vehicle controller.

The remote control system may comprise a central station for communicating with the multi-vehicle controller via the cellular transceiver. In addition, the data communications bus may carry at least one of vehicle device data and address information thereover.

A method aspect is directed remote control method for a vehicle comprising a data communications bus extending within the vehicle, and a plurality of vehicle devices communicating over the data communications bus. The method may comprise enabling a multi-vehicle controller, positioned within the vehicle and coupled to the data communications bus, to communicate via the data communications bus using a desired set of signals for a corresponding desired vehicle from a plurality of sets of signals for different vehicles based upon learning from at least one of the plurality of vehicle devices on the data communications bus and downloading via a cellular transceiver within the vehicle and coupled to the multi-vehicle controller. The method may further include operating the multi-vehicle controller for communication with at least one of the plurality of vehicle devices to perform a remote vehicle function based upon a received remote control signal.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic block diagram of the vehicle security system in accordance with the invention.

FIG. 2 is a schematic diagram of a remote transmitter of the vehicle security system in accordance with the invention.

FIG. 3 is a schematic block diagram of a portion of a first embodiment of the vehicle security system in accordance with the present invention.

4

FIG. 4 is a schematic block diagram of a portion of a second embodiment of the vehicle security system in accordance with the present invention.

FIG. 5 is a schematic block diagram of a portion of a third embodiment of the vehicle security system in accordance with the present invention.

FIG. 6 is a schematic block diagram of a portion of a fourth embodiment of the vehicle security system in accordance with the present invention.

FIG. 7 is a schematic block diagram of the vehicle security system in accordance with the present invention.

FIG. 8 is a schematic block diagram of a remote keyless entry system in accordance with the present invention.

FIG. 9 is a schematic block diagram of a remote engine starting system in accordance with the present invention.

FIG. 10 is a schematic block diagram of the vehicle security system in accordance with the present invention illustrating a pre-warning feature thereof.

FIG. 11 is a schematic block diagram of an alternate embodiment of the vehicle security system of FIG. 10.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention will now be described more fully hereinafter with reference to the accompanying drawings in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the illustrated embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like numbers refer to like elements throughout. Prime and multiple prime notation are used in alternate embodiments to indicate similar elements.

Referring now to the schematic block diagram of FIG. 1, a vehicle security system 10 according to one aspect of the invention is first described. The security system includes a controller 11 which, in turn, in the illustrated embodiment includes a central processing unit (CPU) or microprocessor 12 operating under stored program control.

In the illustrated embodiment, a transmitter and receiver 13 are connected to the CPU 12 for receiving signals from a remote transmitter and for transmitting signals to a remote unit, as will be described in greater detail below. As would be readily understood by those skilled in the art, the transmitter portion of the controller 11 may not be needed in some embodiments of the invention. An antenna 13a is illustratively connected to the transmitter and receiver 13.

In the illustrated embodiment, the CPU 12 is also operatively connected to a memory (EEPROM) 14 and a data communications bus interface 15 which provides both input and output interfaces to various vehicle devices. As would be readily understood by those skilled in the art, the CPU 12 may alternately or additionally have its own on-board memory.

The data communications bus interface 15 is illustratively connected to various vehicle input devices including: an ignition switch 20; a key in the ignition sensor 21; two zone sensors 22a, 22b; conventional trunk hood and door pin sensors or switches 23, 24, and 25, respectively; and door lock switches 28. In addition, a pre-warn sensor 26 and valet switch 27 also provide inputs to the controller 11 in the illustrated embodiment. As would be readily understood by those skilled in the art, other inputs are also contemplated by the present invention and are generally described herein by the term sensor. In addition, an input signal may also be received from a remote transmitter 50 (FIG. 2).

5

The data communications bus interface **15** of the controller **11** may also preferably be connected to a plurality of output devices. The outputs may include auxiliary relay outputs **30**, such as for window control, remote starting, or a remote alarm indication, as would be readily understood by those skilled in the art. A siren and/or lights **31**, and green and red light emitting diodes (LEDs) **32**, **33** for dashboard mounting are also illustratively connected to the controller **11**. Other outputs may be directed to a valet LED **34**, a dome light **36**, a central lock relay or lock control unit **41**, a starter kill circuit **42**, and an armed relay output **43**. In addition, other outputs may be directed to one or more of an audible tone generator **37**, an alphanumeric display **44**, a speech message annunciator **45**, and a vibration transducer **46**, as will be readily appreciated by those skilled in the art. Other similar indicating devices are also contemplated by the present invention, as would be readily understood by those skilled in the art. Some of the illustrated devices may be hardwired to various control nodes as would be readily understood by those skilled in the art. The control nodes may be connected by the data communications bus as would also be known to those skilled in the art.

Referring now more particularly to FIG. 2, a remote transmitter **50** in accordance with the invention is described. The remote transmitter **50** illustratively includes a housing **51** and a plurality of first momentary contact switches **52a-52d** carried by the housing. A second momentary contact switch **53** and an indicating light, such as the illustrated LED **54** are also carried by or mounted on the housing **51**. As would be readily understood by those skilled in the art, the remote transmitter **50** is typically relatively small and includes an opening **55** for facilitating connection to a vehicle key ring, for example. In addition, the remote transmitter **50** includes a central processing unit or microprocessor **56** operatively connected to the plurality of first switches **52a-52d**, the second switch **53**, and the LED **54**. The microprocessor is also connected to a transmitter and/or receiver circuit **57** and its associated antenna **57a** for transmitting and/or receiving signals to and from the controller **11** of the vehicle security system **10**. Accordingly, the term "remote transmitter" is used broadly herein to describe the embodiment also including receiver means.

The remote transmitter **50** may also include a numeric or alphanumeric display **58**, and a speaker **59** coupled to an audible tone generator or a speech message generator, as may be provided by the microprocessor **56**. A vibration transducer, not shown, may also be incorporated into the remote transmitter **50** for communicating to the user as would be readily understood by those skilled in the art.

Turning now additionally to FIG. 3 a first embodiment of the desired signal enabling means **17** is described. The vehicle security system **10** preferably comprises a vehicle security sensor and associated sensor bus interface means **60** for interfacing the vehicle security sensor to the data communications bus **62**. The vehicle security system **10** also preferably includes an alarm indicator and associated alarm indicator bus interface means **64** for interfacing the alarm indicator to the data communications bus. Examples of vehicle security sensors and alarm indicators are described above in greater detail with reference to FIG. 1.

The security system **10** further preferably comprises desired signal enabling means **17** for enabling the alarm controller **10** to operate using a desired set of signals for a desired vehicle from among a plurality of possible sets of signals for different vehicles. As would be readily understood by those skilled in the art, the term different vehicles may include vehicles from different manufacturers, different models, or even different trim levels of the same make and model.

6

Accordingly, the desired signal enabling means **17** permits the alarm controller, that is, the security CPU and bus interface **65**, to communicate with the vehicle security sensor and the alarm indicator via the data communications bus **62** so that the CPU is capable of operating the alarm indicator responsive to the vehicle security sensor.

The data communications bus **62** may preferably be a multiplexed data bus as would be readily understood by those skilled in the art. Accordingly, the sensor bus interface means, the alarm bus interface means, and the alarm controller bus interface means may each comprise multiplexing means for interfacing with the multiplexed data bus of the vehicle. For example, any of the various multiplexing schemes as disclosed in "The Thick and Thin of Car Cabling" by Thompson appearing in the IEEE Spectrum, February 1996, pp. 42-45 may be used. Other data bus connection schemes are also contemplated by the present invention.

As illustrated in FIG. 3, one embodiment of the desired signal enabling means **17** may preferably include a memory **70** for storing a plurality of sets **72a**, **72b** and **72n** of signals for different vehicles, and selecting means for selecting the desired set of signals from the plurality of different sets of signals for different vehicles. By storing sets of signals is meant storing information or data necessary to generate the desired signals on the data bus **62** as would be readily understood by those skilled in the art. The memory **70** may include device address memory means for storing a plurality of different sets of signals representative of different device addresses for different vehicles. Alternatively, or in addition thereto, the memory means may comprise protocol memory means for storing a plurality of different protocols for different vehicles. One or more other control nodes and associated bus interfaces **66** may also be connected to the data communications bus **62** as would also be readily understood by those skilled in the art. For example, other control nodes may include an engine controller thereby permitting the alarm controller to disable the engine, or the body controller thereby permitting the alarm controller to control the vehicle door locks as would be readily understood by those skilled in the art.

In the illustrated embodiment of FIG. 3, the selecting means may comprise user selecting means **75** for permitting a user to select the desired set of signals. A keypad or other input means may be used to permit the user to select the desired signal set for his vehicle. The valet switch **27** (FIG. 1), for example, may also be operated by the user to select the desired signal set. The user may select the desired set of signals by entering a unique digital code similar to the selection of signals for a home electronics universal remote control. Other techniques for permitting the user to select the desired signal set from a plurality of stored sets are also contemplated by the invention as would be readily appreciated by those skilled in the art.

Referring now additionally to FIG. 4 another embodiment of the desired signal enabling means **17'** is described in accordance with the security system **10'** of the present invention. In this embodiment, the selecting means may comprise bus determining means **77** for determining the desired set of signals based upon signals on the data communications bus. For example, the bus determining means could determine the desired set of signals based upon sensed voltage levels or based upon the timing of signal pulses on the data communications bus **62**. The other components of this embodiment of the desired signal enabling means **17'** are similar to those described above with reference to FIG. 3 and need no further description.

Yet another embodiment of the security system 10" according to the invention is explained with reference to FIG. 5. In this illustrated embodiment, the desired signal enabling means 17" includes a desired signal set memory 81 operatively connected to the illustrated bus learning means 80. The bus learning means 80 may determine and store in the signal set memory 81 the protocol and/or device addresses for the vehicle devices. For example, the bus learning means 80 may permit the user to operate various vehicle devices and store a desired signal set based thereon as would be readily understood by those skilled in the art. The other components of the desired signal enabling means 17" are similar to those described above with reference to FIG. 3 and need no further description.

Still another embodiment of the desired signal enabling means 17"" is explained with reference to FIG. 6. The desired signal enabling means 17"" includes a signal set memory 81 operatively connected to the schematically illustrated download learning means 84. The download learning means 84 may include an interface connected to the illustrated vehicle cellular telephone 86 to permit learning or downloading of the desired signal set from a remote or central monitoring and control station 88, for example. As would be readily understood by those skilled in the art, the download learning means as well as the other desired signal enabling means may be implemented by software in the CPU 12 of the controller 11 or in a separate microprocessor or circuits.

One implementation of the security system 10 is shown in FIG. 7 and includes the vehicle security controller 11. The remote transmitter 50 can switch the controller 11 between the armed and disarmed modes. The controller 11 in the armed mode is capable of generating an alarm indication via the siren 31 (FIG. 1) and based upon the door switches 25 (FIG. 1), for example. The communications are via the data communications bus 62 and, are based upon the desired signal set from the desired signal enabling means 17.

The features and aspects described above may also be readily implemented into other vehicle related systems, such as for performing remote control functions. As shown in FIG. 8, the invention may be embodied in a remote keyless entry system 90 including a remote keyless entry controller 91 operated by a remote handheld transmitter 93. The controller 91 communicates with the door lock motors 94 and illustrated trunk release 96 via the data communications bus 62. The remote keyless entry system 90 also includes the desired signal enabling means 17 which permits the controller 91 to perform the desired door locking and trunk release remote control functions or operations as would also be readily understood by those skilled in the art. As would be readily appreciated by those skilled in the art, any of the desired signal enabling means described herein and equivalent thereto may be used for the remote keyless entry system 90 in accordance with the present invention.

Turning now to FIG. 9, yet another vehicle associated remote control function is illustrated and now explained. The remote engine starting system 100 includes a remote start controller 101 operable by a remote transmitter 103. The remote controller 101 may communicate via the data communications bus 62 to enable the ignition and fuel systems 106 and crank the engine starter 104. Various sensors may also be monitored as would be readily understood by those skilled in the art.

A method aspect of the invention is for operating a vehicle security system 10 for a vehicle of a type including a data communications bus 62 connecting a plurality of vehicle devices. The method preferably comprises the steps of interfacing an alarm controller 11 to the data communications bus

62, and enabling the alarm controller to operate using a desired set of digital signals for a desired vehicle from a plurality of possible sets of signals for different vehicles to thereby permit the alarm controller to communicate with at least one of a vehicle security sensor 60 and an alarm indicator 64 via the data communications bus 62 (FIG. 3). Accordingly, the alarm controller is capable of operating the alarm indicator responsive to the vehicle security sensor and via the data communications bus.

Another method of the invention is for remotely controlling a vehicle function for a vehicle of a type including a data communications bus 62 connecting a plurality of vehicle devices, and a vehicle function controller and associated bus interface means for interfacing the vehicle function controller to the data communications bus. The method may comprise enabling the vehicle function controller to operate using a desired set of signals for a desired vehicle from a plurality of sets of signals for different vehicles for permitting the vehicle function controller to communicate via the data communications bus with at least one of the vehicle devices. It may further comprise receiving a signal at the vehicle from a remote transmitter so that the vehicle function controller remotely controls a vehicle function responsive to the remote transmitter.

Referring now to FIGS. 10 and 11, a pre-warning feature of the vehicle security system 200 in accordance with the present invention is now described. As noted above, the vehicle security system 200 is for a vehicle of a type including a vehicle data communications bus 201 connected to a plurality of vehicle devices 202. By way of example, the vehicle devices may include the door lock motors 94, trunk release 96, and/or the engine starter 104 discussed above, as well as others.

In particular, the vehicle security system 200 illustratively includes at least one vehicle security sensor 203 and associated interface for interfacing the sensor with the vehicle data communications bus 201. The vehicle security sensor 203 is for generating a pre-warning signal or an alarm signal, depending upon a sensed threat level. To this end, the sensor 203 may be a multi-stage sensor, where the first stage provides the pre-warning signal and the second stage provides the alarm signal. Of course, separate sensors could also be used. That is, a pre-warn sensor having a lower sensitivity could be used for providing the pre-warning signal, and an alarm sensor having a higher sensitivity for providing the alarm signal, as illustrated by the inputs 26 and 22a, 22b in FIG. 1. Further, the two sensors could be different types of sensors. By way of example, the at least one security sensor 203 may include one or more motion sensors and/or shock sensors (e.g., a two-zone motion sensor), as noted above.

The vehicle security system 200 also illustratively includes an alarm indicator 204 and a vehicle security controller 205. By way of example, the alarm indicator 204 could be the siren 31, as well as a vehicle horn or light, etc. In the illustrated example, the alarm indicator 204 is hard-wire connected to the vehicle security controller 205 and does not receive commands therefrom via the vehicle data communications bus 201.

The vehicle security controller 205 interfaces with the vehicle data communications bus 201, as discussed previously above, for causing the alarm indicator to generate a pre-warning indication based upon the pre-warning signal, or for causing the alarm indicator to generate an alarm indication based upon the alarm signal. Generally speaking, it may be preferable that the alarm indication have a greater duration than the pre-warning indication. Thus, for a visual alarm indicator 204, such as a vehicle light, the light may continue

to flash longer for an alarm indication than for a pre-warning indication. Similarly, in the case of an audible alert generator (e.g., a siren or horn), the alarm indication sound may last longer than the pre-warning indication sound. The alarm indication may also have a greater volume than the pre-warning indication. Of course, other combinations of pre-warning and alarm indications may also be used, as will be appreciated by those skilled in the art.

In an alternate embodiment of the vehicle security system **200'** (FIG. 11), the vehicle security sensor(s) **203'** may be connected to the vehicle security controller **205'** and not interface with the bus **201'**. Conversely, the alarm indicator **204'** may have an associated bus interface, similar to the alarm indicator and bus interface **64** discussed above (FIG. 3). More particularly, the alarm indicator **204'** may be directly interfaced to the bus **201'**, or interfaced to the bus via an intervening device or module, for example, as will be appreciated by those skilled in the art. In such case, the vehicle security controller **205'** causes the alarm indicator **204'** to generate the pre-warning indication or the alarm indication via the data communications bus **201'**. Of course, as will be appreciated from FIGS. 10 and 11, in some embodiments both the vehicle security sensor **203** and the alarm indicator **204** could be connected to the vehicle data communications bus **201**.

Still another vehicle security method aspect of the invention is for a vehicle of a type including a vehicle data communications bus **201** and an alarm indicator **204**. The method may include interfacing at least one vehicle security sensor **203** with the vehicle data communications bus **201**. The at least one vehicle security sensor **203** may be for generating a pre-warning signal or an alarm signal depending upon a sensed threat level. The method may further include causing the alarm indicator **204** to generate a pre-warning indication based upon the pre-warning signal, or causing the alarm indicator to generate an alarm indication based upon the alarm signal, as discussed above.

Yet another advantageous vehicle security method aspect of the invention may include interfacing an alarm indicator **204'** with a vehicle data communications bus **201'**, and causing the alarm indicator to generate a pre-warning indication based upon a pre-warning signal on the vehicle data communications bus. The method may also include causing the alarm indicator **204'** to generate an alarm indication based upon an alarm signal on the vehicle data communications bus, as previously described above.

Those of skill in the art will readily recognize the benefits and advantages of the present invention for aftermarket security systems and other aftermarket systems for implementing remote control functions wherein compatibility with a potentially large number of different protocols and/or device addresses is desired. Of course, many modifications and other embodiments of the invention will come to the mind of one skilled in the art having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Accordingly, it is understood that the invention is not to be limited to the illustrated embodiments disclosed, and that the modifications and embodiments are intended to be included within the spirit and scope of the appended claims.

That which is claimed is:

1. A remote control system for a vehicle comprising a data communications bus extending within the vehicle, and a plurality of vehicle devices communicating over the data communications bus, the remote control system comprising:

- a cellular transceiver to be positioned within the vehicle; and
- a multi-vehicle controller to be positioned within the vehicle and coupled to the data communications bus for

communication with at least one of the plurality of vehicle devices to perform a remote vehicle function based upon a received remote control signal;

said multi-vehicle controller also being coupled to said cellular transceiver and being enabled to communicate via the data communications bus using a desired set of signals for a corresponding desired vehicle from a plurality of sets of signals for different vehicles based upon learning from at least one of the plurality of vehicle devices on the data communications bus and downloading via said cellular transceiver.

2. The remote control system of claim 1 further comprising:

- a remote transmitter; and
- a receiver to be positioned within the vehicle and coupled to said multi-vehicle controller for receiving the remote control signal from said remote transmitter.

3. The remote control system of claim 2 wherein said remote transmitter comprises a handheld transmitter.

4. The remote control system of claim 1 wherein the plurality of vehicle devices comprises a vehicle security sensor; and wherein said multi-vehicle controller comprises a multi-vehicle alarm controller.

5. The remote control system of claim 1 wherein the plurality of vehicle devices comprises a plurality of vehicle door locks; and wherein said multi-vehicle controller comprises a multi-vehicle keyless entry controller.

6. The remote control system of claim 1 wherein the plurality of vehicle devices comprises at least one device associated with starting an engine of the vehicle; and wherein said multi-vehicle controller comprises a multi-vehicle remote start controller.

7. The remote control system of claim 1 further comprising a central station for communicating with said multi-vehicle controller via said cellular transceiver.

8. The remote control system of claim 1 wherein at least one of the plurality of vehicle devices comprises at least one vehicle controller.

9. The remote control system of claim 1 wherein the data communications bus carries at least one of vehicle device data and address information thereover.

10. A remote control system for a vehicle comprising a data communications bus extending within the vehicle, and a plurality of vehicle devices communicating over the data communications bus, the remote control system comprising:

- a remote transmitter;
- a cellular transceiver to be positioned within the vehicle; and
- a multi-vehicle controller to be positioned within the vehicle and coupled to the data communications bus for communication with at least one of the plurality of vehicle devices to perform a remote vehicle function based upon a received remote control signal from said remote transmitter;

said multi-vehicle controller also being coupled to said cellular transceiver and being enabled to communicate via the data communications bus using a desired set of signals for a corresponding desired vehicle from a plurality of sets of signals for different vehicles based upon learning from at least one of the plurality of vehicle devices on the data communications bus and downloading via said cellular transceiver.

11. The remote control system of claim 10 wherein the plurality of vehicle devices comprises a vehicle security sensor; and wherein said multi-vehicle controller comprises a multi-vehicle alarm controller.

11

12. The remote control system of claim 10 wherein the plurality of vehicle devices comprises a plurality of vehicle door locks; and wherein said multi-vehicle controller comprises a multi-vehicle keyless entry controller.

13. The remote control system of claim 10 wherein the plurality of vehicle devices comprises at least one device associated with starting an engine of the vehicle; and

wherein said multi-vehicle controller comprises a multi-vehicle remote start controller.

14. The remote control system of claim 10 further comprising a central station for communicating with said multi-vehicle controller via said cellular transceiver.

15. The remote control system of claim 10 wherein at least one of the plurality of vehicle devices comprises at least one vehicle controller.

16. A remote control method for a vehicle comprising a data communications bus extending within the vehicle, and a plurality of vehicle devices communicating over the data communications bus, the method comprising:

enabling a multi-vehicle controller, positioned within the vehicle and coupled to the data communications bus, to communicate via the data communications bus using a desired set of signals for a corresponding desired vehicle from a plurality of sets of signals for different vehicles based upon learning from at least one of the plurality of

12

vehicle devices on the data communications bus and downloading via a cellular transceiver within the vehicle and coupled to the multi-vehicle controller; and

operating the multi-vehicle controller for communication with at least one of the plurality of vehicle devices to perform a remote vehicle function based upon a received remote control signal.

17. The method of claim 16 further comprising operating a receiver positioned within the vehicle and coupled to the multi-vehicle controller for receiving the remote control signal from a remote transmitter.

18. The method of claim 16 wherein the plurality of vehicle devices comprises a vehicle security sensor; and wherein the multi-vehicle controller comprises a multi-vehicle alarm controller.

19. The method of claim 16 wherein the plurality of vehicle devices comprises a plurality of vehicle door locks; and wherein the multi-vehicle controller comprises a multi-vehicle keyless entry controller.

20. The method of claim 16 wherein the plurality of vehicle devices comprises at least one device associated with starting an engine of the vehicle; and wherein the multi-vehicle controller comprises a multi-vehicle remote start controller.

* * * * *