

US008760303B2

(12) **United States Patent**
Hillger et al.

(10) **Patent No.:** **US 8,760,303 B2**
(45) **Date of Patent:** **Jun. 24, 2014**

(54) **SPRAY DRIFT SYSTEMS AND METHODS INCLUDING AN INPUT DEVICE**

(75) Inventors: **David E. Hillger**, Noblesville, IN (US);
Tammie J. Jones-Jefferson,
Indianapolis, IN (US); **Damon M. Palmer**, Pittsboro, IN (US)

(73) Assignee: **Dow AgroSciences, LLC.**, Indianapolis, IN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 155 days.

(21) Appl. No.: **13/330,194**

(22) Filed: **Dec. 19, 2011**

(65) **Prior Publication Data**

US 2012/0169504 A1 Jul. 5, 2012

Related U.S. Application Data

(60) Provisional application No. 61/428,195, filed on Dec. 29, 2010, provisional application No. 61/474,222, filed on Apr. 11, 2011.

(51) **Int. Cl.**
G08B 21/00 (2006.01)

(52) **U.S. Cl.**
USPC **340/603**; 340/540; 340/693.11

(58) **Field of Classification Search**
USPC 340/603, 611, 500, 540, 612-613, 619, 340/625, 641, 656, 666, 691.6, 693.11
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,343,744 A 9/1994 Ammann
5,475,614 A 12/1995 Tofte

5,574,657 A 11/1996 Tofte
6,013,108 A 1/2000 Kapadia
6,424,295 B1* 7/2002 Lange 342/357.52
6,726,120 B2 4/2004 Schaffter et al.
7,292,723 B2* 11/2007 Tedesco et al. 382/159
7,388,662 B2 6/2008 Cantin et al.
8,061,562 B2* 11/2011 Carpenter et al. 222/52
2001/0056516 A1 12/2001 Schollenberger
2003/0019152 A1* 1/2003 Raun et al. 47/58.1 SC

(Continued)

FOREIGN PATENT DOCUMENTS

DE 196 46 219 12/1997
DE 10 2006 012504 9/2007

(Continued)

OTHER PUBLICATIONS

International Searching Authority, International Search Report and Written Opinion for PCT/US2011/065860, May 2012 (14 pages).

(Continued)


Primary Examiner — Daniel Previl

(74) *Attorney, Agent, or Firm* — C. W. Arnett; Faegre Baker Daniels LLP

(57) **ABSTRACT**

Systems and methods for adjusting or providing instructions to spraying systems are provided. In an exemplary embodiment of the present disclosure, an apparatus to identify sensitive areas is provided. The apparatus comprising: a module to electronically receive sensitive area information, the sensitive area information related to one or more sensitive areas proximate to a first specified location; a module to electronically receive an identity of a first substance to be sprayed at the first specified location; and an alert mechanism to provide an indication of a first sensitive area proximate to the first specified location which is sensitive to the first substance.

32 Claims, 12 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2003/0111546	A1	6/2003	Schaffter	
2006/0196576	A1*	9/2006	Fleming et al.	141/198
2007/0076202	A1	4/2007	Cantin et al.	
2009/0050704	A1	2/2009	Harrison, Jr.	
2009/0242657	A1	10/2009	Peterson	
2010/0179734	A1	7/2010	Schumann et al.	
2012/0168528	A1	7/2012	Hillger et al.	
2013/0103211	A1	4/2013	Peterson et al.	
2013/0105591	A1	5/2013	Peterson	

FOREIGN PATENT DOCUMENTS

DE	102006012504	9/2007
EP	0 824 852	2/1998
JP	H10243707	9/1998
WO	WO 2005/034622	4/2005
WO	WO 2006/113688	10/2006
WO	WO 2012/091988	7/2012
WO	WO 2012/091990	7/2012
WO	WO 2013/063225	5/2013

OTHER PUBLICATIONS

International Searching Authority, International Search Report and Written Opinion for PCT/US2011/065857, May 2012, (13 pages).

Office of the Indiana State Chemist, "Driftwatch" brochure, as early as 2009 (2 pages).

"H2Ovis, Temik Monitor, Visual Information System," presentation slides, As early as 2010, (10 pages).

Case IH "Patriot Sprayers" brochure CIH6070601, as early as 2007 (16 pages).

Office Action Issued in U.S. Appl. No. 13/330,168, mailed Dec. 3, 2013, 11 pages.

Response to Office Action issued in U.S. Appl. No. 13/330,168, filed Feb. 18, 2014, 10 pages.

Communication Pursuant to Rules 161(1) and 162 EPC in European patent application 11809020.8, dated Aug. 6, 2013, 2 pages.

Response to Communication Pursuant to Rules 161(1) and 162 EPC in European patent application 11809020.8, dated Feb. 6, 2014, 8 pages.

Communication Pursuant to Rules 161(1) and 162 EPC in European patent application 11809019.0, dated Aug. 6, 2013, 2 pages.

Response to Communication Pursuant to Rules 161(1) and 162 EPC in European patent application 11809019.0, dated Feb. 6, 2014, 7 pages.

European Search Report in Application No. 11809020.8, dated Apr. 11, 2014, 6 pages.

European Search Report in Application No. 11809019.0, dated Apr. 11, 2014, 6 pages.

* cited by examiner




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7




Figure 8




Figure 9




Figure 10




Figure 11




Figure 12

SPRAY DRIFT SYSTEMS AND METHODS INCLUDING AN INPUT DEVICE

CROSS REFERENCE TO RELATED APPLICATIONS

This application claims priority to U.S. Provisional Patent Application 61/474,222, filed Apr. 11, 2011, and U.S. Provisional Patent Application 61/428,195, filed Dec. 29, 2010, the entire disclosures of which are incorporated by reference. The entire disclosures of U.S. Provisional Patent Application 61/474,217, filed Apr. 11, 2011, and U.S. Provisional Patent Application 61/428,201, filed Dec. 29, 2010, are also incorporated by reference.

FIELD OF THE DISCLOSURE

The present disclosure relates in part to the identification and avoidance of plants and/or animals based upon provided information and in particular to systems and methods for controlling spraying applications based at least on the presence of plants or animals that may be sensitive to a sprayed substance or that may be marketed with a certain property that is inconsistent with the sprayed substance.

BACKGROUND OF THE DISCLOSURE

Certain agricultural crops, animals, or insects may be more sensitive than others to the application of one or more applied substances, and may not be the target of the application. The applied substances may include pesticides, fertilizers, fungicides, other growth promoting or inhibiting compounds, or excessive amounts of water. For example, a colony of honeybees may be sensitive to a pesticide, so that a small amount of airborne pesticide, drifting from one field to another field, may damage or destroy the colony, even if it was released to support crops in an adjacent field. Similarly, a field of tomatoes may be sensitive to one or more pesticides, so that a small amount of the pesticide may damage the tomatoes and reduce the overall output of tomatoes in the field. Further, an at-risk habitat may include plants and animals that are sensitive to one or more applied substances, or an endangered species may be present in a particular area to be protected from further population decreases. In another example, a watershed or drainage basin may be identified, and the application of chemicals near the watershed may be prohibited or undesirable. Additionally, the presence or absence of workers in an area, the presence or absence of nearby population centers, or the presence of homes, businesses, or other industrial areas may also be considered when applying chemicals to fields.

In addition, some crops or animals are marketed having certain properties. An example property is that the crop is organically grown or that the animal is raised on organic food. For these crops, applied substances drifting from an adjacent field may make the crop or animal unsuitable for marketing as having the certain properties, such as organic.

Federal and/or state regulatory bodies maintain a list of requirements for the application of certain substances to fields, and creates "buffer zone" or proximity limit requirements for specific substances. For example, the proximity limit requirements define additional areas surrounding a field where certain substances should not be applied due to proximity to sensitive areas and/or species of animals or plants. Techniques for application of substances which tends to reduce or limit the exposure of people and/or animals to the substances, or additional precautions taken for the application of the substances, may be rewarded with "buffer credits"

or drift reduction technology credits as limit reductions. The limit reductions include, but are not limited to, rewards in the form of smaller required buffer zone distances for applications of the same substance, or other rewards for reducing exposure to substances.

Websites are known which permit members of the public to identify areas containing crops or animals that are either sensitive to applied substances or that are being raised for marketing with certain properties. A substance applicator, such as a farmer, a specialized applicator, or pilot, may refer to the website prior to applying a substance, such as a pesticide, to crops in a field. By referring to the website prior to spraying the field the applicator is able to determine the presence, if any, of areas containing crops or animals that are either sensitive to applied substances or that are being raised for marketing with certain properties and to plan the intended spraying accordingly.

SUMMARY

In an exemplary embodiment of the present disclosure, an apparatus to identify sensitive areas is provided. The apparatus comprising: a module to electronically receive sensitive area information, the sensitive area information related to one or more sensitive areas proximate to a first specified location; a module to electronically receive an identity of a first substance to be sprayed at the first specified location; and an alert mechanism to provide an indication of a first sensitive area proximate to the first specified location which is sensitive to the first substance. In an embodiment, the alert mechanism includes a display and a visual alert. In an embodiment, the apparatus also comprises a location identifier to determine the location of the apparatus. In an embodiment, the location identifier receives location information from a Global Positioning System (GPS). In an embodiment, the apparatus receives input regarding a potential application including at least a date and time of a potential application, and the one or more substances to be applied to the locations proximate to the one or more sensitive areas. In an embodiment, the apparatus receives input regarding a potential application including at least one or more spraying system parameters. In an embodiment, the one or more spraying system parameters includes droplet size, desired pressure, or drift reduction technology credits. In an embodiment, the apparatus further includes a module to determine instructions for the application of the one or more substances to the locations proximate to the one or more sensitive areas; and a module to operate a spraying system according to the instructions. In an embodiment, operating the spraying system may include one or more of changing the speed of the spraying system, changing the direction of the spraying system, altering the droplet size of the spraying system, or changing the boom height of the spraying system.

In an exemplary embodiment of the present disclosure, a method of identifying sensitive areas is provided. The method comprising: providing a handheld device having a first specified location; electronically receiving with the handheld device sensitive area information, the sensitive area information related to the one or more sensitive areas proximate to the first specified location; electronically receiving with the handheld device an identity of a first substance to be sprayed at the first specified location; and providing with a display of the handheld device a visual indication of a first sensitive area proximate to the first specified location which is sensitive to the first substance. In an embodiment, the handheld device creates a log file including information related to the first substance and the sensitive area. In an embodiment, the hand-

held device interfaces with a database to receive the sensitive area information. In an embodiment, the handheld device overlays the sensitive areas on a map. In an embodiment, the handheld device corresponds to a current location with the first specified location. In an embodiment, the current location is identified with a Global Positioning System (GPS). In an embodiment, the handheld device is spaced apart from the first specified location. In an embodiment, the handheld device also receives information from a spraying system. In an embodiment, the received sensitive information includes information regarding the first sensitive area and a second sensitive area. In an embodiment, the received sensitive information includes information regarding the first sensitive area and a second sensitive area and wherein a visual indication of the second sensitive area is not provided with the display of the handheld device because the second sensitive area is not sensitive to the first substance. In an embodiment, the received sensitive information includes information regarding the first sensitive area and a second sensitive area and wherein the visual indication of the first sensitive area has a first characteristic and a visual indication of the second sensitive area is provided with the display of the handheld device having a second characteristic, the second characteristic being different from the first characteristic. In an embodiment, the first specified location is one of a current location of the handheld device or a location input into the handheld device.

In an exemplary embodiment of the present disclosure, an apparatus to identify sensitive areas is provided. The apparatus comprising: a module to electronically receive sensitive area information, the sensitive area information related to the one or more sensitive areas proximate to a first specified location; a module to electronically receive an identity of a first substance to be sprayed at the first specified location; a location identifier operable to receive location information regarding the location of the apparatus; an alert mechanism to provide an indication of a first sensitive area proximate to the first specified location which is sensitive to the first substance; and a module to operate a spraying system according to at least the sensitive area information, the identity of the first substance, and the location information. In an embodiment, the location identifier receives location information from a Global Positioning System (GPS). In an embodiment, the apparatus receives input regarding a potential application including at least a date and time of the potential application, and the one or more substances to be applied to the locations proximate to the one or more sensitive areas. In an embodiment, the apparatus receives input regarding a potential application including at least one or more spraying system parameters. In an embodiment, the one or more spraying system parameters includes one or more of droplet size, desired pressure, or drift reduction technology credits. In an embodiment, operating the spraying system may include one or more of changing the speed of the spraying system, changing the direction of the spraying system, altering the droplet size of the spraying system, or changing the boom height of the spraying system. In an embodiment, the apparatus further comprises a log file to capture information related to the spraying system, wherein the log file captures one or more of a substance being applied, a date, a current time, the current location of the spraying system, a location of a projected route, an amount of deviation from an actual route to the projected route, actions of a user, information regarding current weather, the location of the one or more sensitive areas, a proximity of the spraying system to the one or more sensitive areas, and a warning. In an embodiment, the log file is electronically transmitted to a system.

BRIEF DESCRIPTION OF THE DRAWINGS

The detailed description of the drawings particularly refers to the accompanying figures in which:

FIG. 1 is a component view of an exemplary identification system according to an embodiment of the present disclosure;

FIG. 2 is a component view of the receiving system of FIG. 1 according to an embodiment of the present disclosure;

FIG. 3 is a component view of the sensitive area information transmitter of FIG. 1 according to an embodiment of the present disclosure;

FIG. 4 is a component view of the sensitive area information receiving device of FIG. 1 according to an embodiment of the present disclosure;

FIG. 5 is a flowchart showing a method of identifying sensitive areas according to an embodiment of the present disclosure;

FIG. 6 is a flowchart showing a method of locating sensitive areas according to an embodiment of the present disclosure;

FIG. 7 is an exemplary field showing sensitive areas according to an embodiment of the present disclosure;

FIG. 8 is an exemplary spraying system according to an embodiment of the present disclosure;

FIG. 9 is a flowchart showing a method of compiling a spray plan according to an embodiment of the present disclosure;

FIG. 10 is an exemplary view of a screen of a sensitive area information receiving device according to an embodiment of the present disclosure;

FIG. 11 is an exemplary view of a display screen of a sensitive area information receiving device according to an embodiment of the present disclosure;

FIG. 12 is an exemplary alert screen for a sensitive area information receiving device according to an embodiment of the present disclosure.

Corresponding reference characters indicate corresponding parts throughout the several views. The exemplifications set out herein illustrate exemplary embodiments of the disclosure and such exemplifications are not to be construed as limiting the scope of the disclosure in any manner.

DETAILED DESCRIPTION OF THE DRAWINGS

The embodiments of the disclosure described herein are not intended to be exhaustive or to limit the disclosure to the precise forms disclosed. Rather, the embodiments selected for description have been chosen to enable one skilled in the art to practice the subject matter of the disclosure. Although the disclosure describes specific configurations of an identification system, it should be understood that the concepts presented herein may be used in other various configurations consistent with this disclosure.

The present disclosure relates in part to the identification and avoidance of plants and/or animals based upon provided information and in particular to systems and methods for controlling spraying applications based at least on the presence of plants or animals that may be sensitive to a sprayed substance or that may be marketed with a certain property that is inconsistent with the sprayed substance.

The present disclosure provides systems and methods for controlling spraying applications based at least on the presence of plants or animals that may be sensitive to a sprayed substance or that may be marketed with a certain property that is inconsistent with the sprayed substance.

“Sensitive area” or “sensitive areas” may include areas where sensitive crops are planted, areas where sensitive crops

5

may be planted in the future, areas where animals that may be sensitive to substances are located or may be located, for example a migratory path or nesting area, watersheds or areas around watersheds, or other areas where any plant, animal, fungi, or bacteria reside or may reside that may be adverse to the application of one or more substances.

FIG. 1 shows a component view of an exemplary identification system 100 according to an embodiment of the present disclosure. In an exemplary embodiment, the identification system 100 includes one or more sensitive area identification devices 111, one or more networks 107, a receiving system 101, a sensitive area database 103, a sensitive area information transmitter 105, one or more sensitive area information receiving devices 113, and one or more distribution systems 117. In an embodiment, the identification system 100 is also operable to receive information from and/or transmit information to one or more third party systems 109.

The sensitive area identification device 111 is used to identify the location and/or type of sensitive or non-sensitive sensitive areas to be included in the sensitive area database 103, and transmit the identification information to the receiving system 101. In one embodiment, the sensitive area identification device 111 is, for example and without limitation, a smartphone or other electronic device equipped with a global positioning system (“GPS”) device used to identify the device’s location. Software and/or hardware may be installed on the smartphone to allow the smartphone to capture location information and/or sensitive area location, and transmit the location information and/or sensitive area information to a network 107. The smartphone or other device may be moved around the field containing the sensitive areas, so that GPS data points are recorded, and one or more fields with sensitive or non-sensitive sensitive areas is marked by moving around the boundaries of the field. In one embodiment, the device is operated by a user as a handheld remote device. In another embodiment, the device is installed on machinery such as, for example, a tractor, a sprayer, an all-terrain vehicle, or other suitable vehicles. In another embodiment, the sensitive area identification device 111 is a map available on a computer, and a user may, for example, draw one or more boxes on the map with an input device, or specify locations on the map in other ways. In the embodiment, the sensitive area identification device 111 translates the electronic markings into location information, and transmits the location information to the receiving system 101 via, for example and without limitation, a cellular network or other wireless network. In another embodiment, a user may identify locations on a physical map, and may photograph, scan, or fax the map to the receiving system 101. In another embodiment, a user may describe location information to an operator over a telephone or other device, and the operator may input the location information into the receiving system 101.

The network 107 may include one or more of: a local area network, a wide area network, a radio network such as a radio network using an IEEE 802.11x communications protocol, a cellular network, a satellite network, a cable network, a fiber network or other optical network, a token ring network, or any other kind of packet-switched or direct transmission network may be used. In one embodiment, the network 107 includes the Internet. In another embodiment, the network 107 includes any other type of public or private network. The use of the term “network” does not limit the network to a single style or type of network, or imply that one network is used. A combination of networks of any communications protocol or type may be used. For example, two or more packet-switched networks may be used, or a packet-switched network may be in communication with a radio network.

6

The receiving system 101 is described in more detail with reference to FIG. 2. The receiving system 101 receives information provided by the sensitive area identification device 111, and, in an embodiment, rearranges, adds to, or deletes from the data provided by the sensitive area identification device 111 so that the data is in a form to be included in the sensitive area database 103. In an embodiment, the receiving system 101 receives sensitive area information from one or more different types of sensitive area identification devices 111, or one or more other methods of gathering sensitive area information. In an embodiment, the one or more different types of sensitive area identification device 111 each transmit different data structures containing the sensitive area information, so that the receiving system 101 performs one or more different processes on the data received from the one or more sensitive area identification devices 111 so that the data transmitted to the sensitive area database 103 has a uniform data structure, regardless of the data structures transmitted to the receiving system 101 from the one or more sensitive area identification devices 111.

In an embodiment, the receiving system 101 is a separate physical system than the system controlling the sensitive area database 103. In another embodiment, the receiving system 101 and the sensitive area database 103 operate on the same system or systems. In an embodiment, the receiving system 101 may be implemented as one or more processes in software, operating on a hardware platform. In another embodiment, the receiving system 101 is implemented as hardware. As shown with respect to FIG. 2, the receiving system 101 receives an input, performs one or more operations on the input, and generates one or more outputs. In an embodiment, the output is transmitted to the sensitive area database 103. In another embodiment, the output is transmitted to other systems. In an embodiment, the receiving system 101 receives data regarding sensitive area locations from one or more sensitive area identification device 111 via a network 107.

The third party systems 109 may include additional receiving systems 101. For example, a number of receiving systems 101 may receive sensitive area location information from a number of different sensitive area identification devices 111, and transmit the sensitive area location information to the sensitive area database 103. In the embodiment, the different receiving systems 101 may be owned or controlled by different entities, or may be controlled by the same entity for different uses or locations. For example, one receiving system 101 may receive sensitive area location information for one geographical area, and another receiving system 101 may receive sensitive area location information for a different geographical area. In another example, the third party systems 109 includes systems owned or operated by different entities, such as the Environmental Protection Agency, the United States Department of Agriculture, one or more state Departments of Agriculture or similar entities, or other commercial or nonprofit entities. The third party systems 109 may also include information related to additional environmental factors. For example, a third party system 109 may include the real-time location of one or more workers, or the location of workers at specified future times. For example, the third party system 109 may include data regarding the future work schedule of other farmers, or workers for picking produce or performing field maintenance. A third party system 109 may also display aerial hazards, such as the location of wind turbines or areas with flight restrictions. A third party system 109 may also display additional information related to the soil or air characteristics. For example, a third party system 109 may display soil composition characteristics or weather information. In an embodiment, the receiving systems 101

also transmit information received from the sensitive area identification devices to the third party systems. For example, and without limitation, a user may mark a field as containing a sensitive crop, transmitting that information to the receiving system **101**. In the embodiment, the receiving system **101** transmits the information regarding the geographical location of the field, the type of crop, and/or time and date information to one or more of the third party systems **109**. This transmission may allow the receiving system **101** to share information with the third party systems **109** to enable each of the systems to have similar data.

In one embodiment, receiving system **101** receives sensitive area information from various identification devices **111** and sends that information along to third party systems **109** to update the databases of the third party systems **109**. The receiving system **101** may rearrange, add to, or delete from the sensitive area information provided by the identification device **111** to format the data for each respective third party system **109**. As such, the receiving system **101** provides a gateway for a user of an identification device **111** to update multiple databases controlled by different entities.

In an embodiment, the third party systems **109** are separate from the sensitive area database **103**, and the third party systems **109** and the sensitive area database **103** may communicate via one or more networks **107**. In another embodiment, the third party systems **109** operate with the sensitive area database **103**, the receiving system **101**, and/or the sensitive area information transmitter **105** on the same system or systems. The third party systems **109** may store and recall sensitive area information using a similar data structure as the sensitive area database **103**, or the third party systems **109** may store and recall sensitive area information differently than the sensitive area database **103**. If the third party systems **109** and the sensitive area database **103** use different data structures, the third party systems **109** may reformat the sensitive area information on the third party systems **109** to become compatible with the data structure of the sensitive area database **103**, or the sensitive area database **103** may receive sensitive area information from the third party systems **109**, and may reformat the data into the one or more data structures used by the sensitive area database **103** to store and recall sensitive area information. Additionally, in an embodiment, the sensitive area database **103** transmits sensitive area information to the third party systems **109**.

The sensitive area database **103** stores and recalls the data provided by the receiving system **101** and/or the third party systems **109**. In an embodiment, the sensitive area database **103** uses a relational database to store the data. In another embodiment, the sensitive area database **103** uses other structures to store the data. For example, the sensitive area database **103** may include data stored in a hierarchical data structure, a flat file data structure, or another type of data structure that may allow the storage and recall of data. In another embodiment, the sensitive area database **103** includes data stored on a map, or associated with a map, that is used to determine the location of sensitive areas. In an embodiment, the sensitive area database **103** may be a separate physical system as the receiving system **101** and/or the sensitive area information transmitter **105**. In another embodiment, the sensitive area database **103** and the receiving system **101** and/or the sensitive area information transmitter **105** operate on the same physical system or systems. If the sensitive area database **103** is separate from the receiving system **101** and/or the sensitive area information transmitter **105**, the sensitive area database **103** may be in communication with the receiving system **101** and/or the sensitive area information transmitter **105** via, for example, one or more networks **107**. The sensitive

area information transmitter **105** is described in more detail with reference to FIG. 3. The sensitive area information transmitter **105** receives requests for sensitive area information from one or more sensitive area information receiving device **113**, and interacts with the sensitive area database **103** to provide the requested information to the sensitive area information receiving device **113**. The sensitive area information transmitter **105** may rearrange, add to, or delete from the data provided by the sensitive area database **103** for transmission to the sensitive area information receiving device **113**. In an embodiment, the sensitive area information transmitter **105** is a separate physical system than the sensitive area database **103**. In another embodiment, the sensitive area information transmitter **105** and the sensitive area database **103** operate on the same system or systems. The sensitive area information transmitter **105** may be implemented as one or more processes in software, operating on a hardware platform, or may be implemented as hardware, or may be implemented as a combination of hardware and software. As shown with respect to FIG. 3, the sensitive area information transmitter **105** receives an input, performs one or more operations on the input, and generates one or more outputs. In an embodiment, the output is transmitted to the sensitive area information receiving device **113**. In another embodiment, the output is transmitted to other systems. In an embodiment, the sensitive area information transmitter **105** transmits data regarding sensitive area information to one or more sensitive area information receiving device **113** via a network **107**. One or more different types of sensitive area information receiving devices **113** may request data, and the data that each different type of sensitive area information receiving devices **113** requests may be different. For example, and without limitation, one sensitive area information receiving device **113** may request all of the data in a geographical area from the sensitive area database **103**. Another sensitive area information receiving device **113** may request sensitive area information only for a specific type of sensitive area in a specific geographical area. Yet another sensitive area information receiving device **113** may request other types of map data from the sensitive area database **103**. The sensitive area information transmitter **105**, in one embodiment, is able to correctly provide the requested data, when the requests are different.

The sensitive area information receiving device **113** transmits a request to the sensitive area information transmitter **105**, and receives sensitive area information from the sensitive area database **103** via the sensitive area information transmitter **105**. The sensitive area information receiving device **113** may be implemented as software or as hardware, and may, in one embodiment, be a smartphone. In another embodiment, the sensitive area information receiving device **113** is attached to or in communication with farm equipment such as, for example and without limitation, a tractor, a sprayer, an all-terrain vehicle, or other suitable vehicles. The communication may be over one or more wired or wireless communication protocols. In an alternate embodiment, the sensitive area information receiving device **113** is a computer that is in communication with the sensitive area information transmitter **105** via, for example and without limitation, one or more networks.

In an embodiment, the user interacts with the sensitive area information receiving device **113**, and inputs, for example, date and time or other temporal identification of a potential application, the particular substance or substances that are to be applied, the desired droplet size, the desired pressure, any drift reduction technology (“DRT”) credit, and state or federal limitations, and the geographical location of the field for application. In an embodiment, the sensitive area information

receiving device **113** may request and receive some inputs from the sensitive area database **103** and/or one or more third party systems **109**, such as, for example, DRT credits or state or federal limitations for a substance. The sensitive area information receiving device **113** interacts with the sensitive area information transmitter, and compiles a list of instructions for the user to follow. The instructions may include, but are not limited to, an approval or disapproval of the date and time of the potential application, one or more routes to take through the field, flow parameters for the distribution system **117**, including flow rate and/or speed, the location of sensitive crops or other areas around the application site, and/or additional weather information. The sensitive area information receiving device **113** may provide the information to the user via a printout, or may upload information to another device that the user may bring and refer to while completing the application, such as a smartphone, a tablet computer, a laptop computer, or a netbook. In another embodiment, the computer may provide information to a removable storage device, which may interface with a computer or system associated with the distribution system **117**. The computer or the sensitive area information transmitter **105** may send further updates to the user, via, for example and without limitation, e-mail, text message, phone call, or other mechanisms to alert a user to a change in the instructions. For example, the computer or the sensitive area information transmitter **105** may send updates to the user to account for changing wind patterns, temperature differences, or other variables not understood at the time the report was printed or transferred to another computer.

The sensitive area information receiving device **113** implements hardware and/or software to calculate or receive a location from a location identifier **115** such as, for example, a GPS receiver to receive location signals from a GPS system. In another embodiment, the sensitive area information receiving device **113** uses one or more internal devices to calculate its location. For example, the sensitive area information receiving device **113** may contain a compass or an inertial guidance system to determine location. In another example, the sensitive area information receiving device **113** includes a device or sensor to measure linear distance. In another example, the sensitive area information receiving device **113** includes one or more accelerometers and/or gyroscopes to determine location or movement from a location. In one embodiment, the sensitive area information receiving device **113** is in communication with one or more distribution systems **117**, and transmits sensitive area information to the distribution system **117**.

The sensitive area information receiving device **113** may be separate from the distribution systems **117**, or may be in the same location as the distribution systems **117**. In an embodiment, the sensitive area information receiving device **113** also notes the location of the distribution systems **117**, and/or notes the orientation of the sprayers in the distribution systems **117**. In one embodiment, the sensitive area information receiving device **113** includes one or more displays, to display the sensitive area location information to a user, or includes other visual, auditory, or tactile devices to convey sensitive area location information. In an embodiment, the sensitive area information receiving device **113** includes additional software and/or hardware that operate to display the received sensitive area information. For example, and without limitation, the sensitive area information receiving device **113** may include a pre-loaded map or satellite images, and the sensitive area information may include location information, which the sensitive area information receiving device

113 overlays on the pre-loaded map. In another embodiment, the map or satellite images are retrieved from a server across the network **107**.

In one embodiment, the sensitive area information receiving device **113** is portable or is attached to the distribution system **117**. In the embodiment, the sensitive area information receiving device **113** includes a touch-sensitive screen or other touch sensitive area associated with a screen. In another embodiment, the sensitive area information receiving device **113** includes a keyboard, mouse, or one or more additional input devices to input data, and one or more displays to visualize data. Additionally, the sensitive area information receiving device **113** may include one or more speakers or other devices for auditory or tactile outputs.

In one embodiment, the sensitive area information receiving device **113** receives location information and is capable of operating the distribution system **117**. The operation may include directly issuing commands to the distribution system **117** to control speed, direction, rate of flow, sprayer operations, or other operations of the distribution system **117**. The sensitive area information receiving device **113** may also receive information from the distribution system **117**, regarding data such as speed, direction, rate of flow, sprayer operations, or other operations. In one embodiment, the sensitive area information receiving device **113** communicates with the distribution system **117** over a cable or other communication device directly connecting the sensitive area information receiving device **113** and the distribution system **117**. In another embodiment, the sensitive area information receiving device **113** communicates with the distribution system **117** via one or more wireless communication protocols, such as, for example and without limitation, one or more IEEE 802.11x protocols, Bluetooth protocols, or a cellular or satellite connection. The sensitive area information receiving device **113** and the distribution system **117** may be in two-way communication, so that the sensitive area information receiving device **113** both communicates information to and receives information from the distribution system **117**, or the sensitive area information receiving device **113** may be in one-way communication, so that either the sensitive area information receiving device **113** issues commands to the distribution system **117**, but does not receive information from the distribution system **117**, or the sensitive area information receiving device **113** receives information from the distribution system **117**, but does not send information to the distribution system **117**.

The user may correct the sensitive area information receiving device **113** if an error is detected, or may take control of the distribution system **117** in the event of an emergency or to complete other tasks. In other embodiments, the sensitive area information receiving device **113** may present information to the user in the form of visual, auditory, or tactile stimulation, for example an alert, a flashing light or indicator on a screen, heads-up display, or two or three dimensional model or overlay, an audible tone or verbal warning, or a tactile vibration, to alert a user that the distribution system is inside or outside of the bounds of the instructions.

FIG. **10** shows an exemplary view of a screen **1000** of a sensitive area information receiving device according to an embodiment of the present disclosure. FIG. **10** is an example of an introductory screen, where the user may select information to be displayed. The user may touch one or more of the areas of the screen, if the sensitive area information receiving device **113** is equipped with a touch screen, or may select one or more of the areas with a mouse or a keyboard shortcut, if the sensitive area information receiving device **113** is so equipped. The user may select, for example, to display envi-

11

ronmental conditions in the “Environmental Conditions Display,” including humidity, temperature, a Doppler representation of the current weather, future weather forecasts, and/or other weather conditions. The user may select the “Equipment Settings Display” to display current or projected settings from the distribution system 117, for example, boom height, spray characteristics, product currently loaded, speed, direction, or other settings related to the operation of the distribution system 117. The user may select the “Field Map Display” to display characteristics of the field for application, to select a new field, or to select other field display options. The user may select the “Sensitive Area Location Display” to display certain sensitive areas, to display information related to one or more of the sensitive areas, or to display sensitive areas in one or more geographical areas. The user may select the “Audible and Visual Alert Module” to select one or more manners of alert, including visual, auditory, or tactile. The user may select the “Wind Direction Visual Display” to selectively display the wind speed and/or direction. The user may select the “Device Location Display” to show the location of the sensitive area information receiving device 113 and/or the distribution system 117 on the field. The user may select one or more display options, and the information related by the options may be overlaid upon one another. In an example, the user elects to display a satellite or aerial image view of the field, and elects to show the geographical boundaries of sensitive areas for crops. The information for the geographical boundaries is overlaid on the satellite view. The user may toggle additional information to be overlaid on the display, so that the user may, for example, toggle the display of soil conditions or the display of current weather conditions on the display. The user may toggle additional information to show as much, or as little, information as the user desires or is necessary or useful to complete a task.

FIG. 11 shows an exemplary view of a display screen 1101 of a sensitive area information receiving device 113 according to an embodiment of the present disclosure. In the example provided in FIG. 11, the distribution system 117 has traveled from a beginning point along a line 1111 to a current location, represented by an oval or other marker. In the embodiment, the sensitive area information receiving device 113 tracks the distribution system 117 and displays the historical locations as well as the current location. The sensitive area information receiving device 113 also displays information in box 1103 including boom height, speed, spray pressure, gallons per acre (“GPA”), a desired droplet size as calculated by the sensitive area information receiving device 113, and an actual droplet size that the user has selected or that the distribution system 117 is currently using. The sensitive area information receiving device 113 may also display a direction, indicated by direction marker 1107, and another box 1105 including current weather conditions. Box 1105 may include, but is not limited to, wind direction and speed, and current temperature. The sensitive area information receiving device 113 may also display one or more sensitive area zones 1113. In an embodiment, the sensitive area zones 1113 may expand or contract, or may change shape, depending on the current weather conditions and/or the current conditions of the distribution system 117 and/or other current conditions. For example, if the distribution system 117 changes from a coarse to a fine droplet size, the sensitive area zone 1113 may expand, as the potential drift of the droplets may be increased. The sensitive area information receiving device 113 may also recommend changes based on other environmental factors, such as wind speed, temperature, soil conditions, or other information received by a third party system 109 or sensors on the distribution system 117 or

12

sensors that convey information at or near the distribution system 117. In the embodiment, the sensitive area zones 1113 may not indicate the geographical location of sensitive areas, but instead may indicate areas where the user must alter spray patterns or other aspects of the distribution system 117 in order to avoid drift into the sensitive areas. The geographical boundaries of sensitive areas may be separately displayed, so that the geographical boundaries of the sensitive areas and the sensitive area zones 1113 may be overlaid on one another. In the embodiment, the user may select one of the sensitive areas or the sensitive area zones 1113 to display, or may display both. In another embodiment, the sensitive area zones 1113 may indicate the location of sensitive areas, and so may not change according to current weather conditions and/or the current conditions of the distribution system 117.

FIG. 12 shows an exemplary alert screen 1201 for a sensitive area information receiving device 113 according to an embodiment of the present disclosure. In the example screen shown in FIG. 12, the sensitive area information receiving device 113 indicates that the distribution system is approaching a sensitive area, and the user is advised to take remedial action to prevent the distribution system 117 from applying product to a sensitive area, or to allow the product to drift into the sensitive area. The screen 1201 shows the current location of the distribution system 117, and also shows the weather condition box 1105, the direction marker 1107, and the sensitive area 1113, but also includes an alert message 1209. The alert message 1209, in the embodiment, includes an indicator of the type of alert an analysis of the conditions that have generated the alert. In the example, the alert is that the distribution system 117 is approaching a sensitive area, and that the wind direction may present a drift hazard, such that the applied product may drift into the sensitive area. The box 1203, in the embodiment, includes a highlight of factors that the sensitive area information receiving device 113 calculates could be changed to fix or abate the alert. In another embodiment, the alert message 1209 may also include additional instructions to take one or more actions. The user may take corrective action to avoid the sensitive area.

The location identifier 115, in some embodiments, assists the sensitive area information receiving device 113 and/or the sensitive area identification device 111 in determining location. The location identifier 115 may be, for example and without limitation, a global positioning system device, one or more transmitters or receivers to determine an approximate location, such as by radio triangulation, astronomical location, or other methods to determine an approximate point of location. In an embodiment, the location identifier 115 also includes other global positioning satellite systems, or may use one or more global navigation satellite systems and/or other methods of location identification to refine or augment location information. In an embodiment, the location identifier 115 uses two or more of the exemplary devices listed above to determine location.

The distribution system 117, in an embodiment, is in communication with the sensitive area information receiving device 113, and receives sensitive area information from the sensitive area information receiving device 113. The distribution system 117 may apply substances, such as liquid chemicals, solid chemicals, and/or water, to a field or to portions of a field. In an embodiment, the distribution system 117 is moveable. In another embodiment, the distribution system 117 is fixed in the location of the field. In an embodiment, the distribution system 117 includes a sprayer or sprayers to apply liquids to a field. Shown with respect to FIG. 8, the sprayers may include one or more tanks to hold the liquid or liquids, a mixing device to mix liquids from different tanks

together before application, and one or more valves to control the mixing of the liquids and/or the flow of liquids to applicators. The applicators may include one or more nozzles. In another embodiment, the distribution system **117** includes one or more spreading devices to spread solids to a field. The solids may include, but are not limited to, fertilizers, pesticides, fungicides, or nutrients. The spreading devices may include one or more holding areas to contain one or more solids, a mixing device to mix the solids before application to a field, and one or more outlets to mix the one or more solids and spread the solids onto the field. While a distribution system **117** may be a spraying system **620** with a plurality of ground engaging members **632** as shown in exemplary FIG. **8**, other delivery devices may also be used. For example, and without limitation, the distribution system **117** may be associated with an aircraft, for example a crop dusting aircraft or a helicopter, or may be associated with a railroad, ballast sprayer, or boat.

The distribution system **117**, in an embodiment, includes the ability to selectively spray, alter spray patterns or direction, alter pressure or spray distance, alter the relative size of the droplets of the spray, start and stop the spray, or change the direction or speed of the distribution system **117**. If the distribution system **117** includes more than one sprayer, the distribution system **117** may include the ability to direct flow to one or more of the sprayers, or to alter the flow to one or more of the sprayers. In an embodiment, the distribution system **117** includes other instruments, such as wind sensors, temperature sensors, humidity sensors, pressure sensors, or other sensors, to monitor the local weather and/or field conditions. In an embodiment, the distribution system **117** also includes one or more sensors to indicate the position of the distribution system **117**. In another embodiment, the sensors or instruments are associated with the sensitive area information receiving device **113**.

In an embodiment, the distribution system **117** uses the sensitive area information, the location information provided by the location identifier **115** or sensitive area information receiving device **113**, and/or one or more sensors to determine a spray pattern so that the spray from the distribution system **117** does not drift into locations of sensitive areas that have been identified as sensitive. The distribution system **117** may alter flow, position, droplet size, or may selectively reduce or eliminate flow to one or more sprayer to minimize or eliminate spray drift into locations of sensitive areas that have been identified as sensitive.

Returning to FIG. **2**, a component view of the receiving system **101** of FIG. **1** according to an embodiment of the present disclosure is shown. The receiving system **101** in the illustrative embodiment includes an input module **203**, a database module **205**, and a sensitive area analysis module **207**. In one embodiment, the receiving system **101** is a single system. In another embodiment, the receiving system **101** is two or more systems in communication with each other. In the illustrative embodiment, the receiving system **101** includes one or more input devices, one or more output devices, one or more processors, and memory **209** associated with the one or more processors. The memory **209** associated with the one or more processors may include, but is not limited to, memory associated with the execution of the modules, and memory associated with the storage of data. The receiving system **101** may also be associated with one or more networks **107**, and may communicate with one or more additional systems via the one or more networks **107**. The modules may be implemented in hardware or software, or a combination of hardware and software. The receiving system **101** may also include additional hardware and/or software to allow the receiving system

101 to access the input devices, the output devices, the processors, the memory, and the modules. In an embodiment, the modules, or a combination of the modules, are associated with a different processor and/or memory, for example on distinct systems, and the systems are located separately from one another. In another embodiment, the modules are executed on the same system as one or more processes or services. The modules may be operable to communicate with one another and to share information. Although the modules are described as separate and distinct from one another, the functions of two or more modules may instead be executed in the same process, or in the same system.

The memory **209** includes computer readable media. Computer-readable media may be any available media that may be accessed by one or more processors of the receiving system **101** and includes both volatile and non-volatile media. Further, computer readable-media may be one or both of removable and non-removable media. By way of example, computer-readable media may include, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, Digital Versatile Disk (DVD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which may be used to store the desired information and which may be accessed by receiving system **101**. The receiving system **101** may be a single system, or may be two or more systems in communication with each other. In one embodiment, the receiving system **101** includes one or more input devices, one or more output devices, one or more processors, and memory **209** associated with the one or more processors.

In the illustrative embodiment, the input module **203** receives data from one or more sensitive area identification devices **111** through the use of one or more networks **107**. The input module **203** may also receive input over a network **107** from another system. For example, and without limitation, the input module **203** may receive one or more signals from third party systems **109** over one or more networks **107**. In an embodiment, the input module **203** receives data from the network **107**, and rearranges or reprocesses the data so that it may be transmitted to the sensitive area analysis module **207**.

In the illustrative embodiment, the sensitive area analysis module **207** receives an input from the input module **203**, and, in an embodiment, the sensitive area analysis module **207** reformats and/or analyzes the input and transmits the results to the database module **205**. For example, the sensitive area analysis module **207** may receive an input in the form of one or more location identifiers **115** for a sensitive area location, and queries the sensitive area database **103** to determine if sensitive areas have been registered within one or more of the location identifiers **115**. In another embodiment, the sensitive area analysis module **207** reformats the sensitive area identification information or sensitive area location information so that the information may be transmitted to the sensitive area database **103**.

In the illustrative embodiment, the database module **205** receives an input, and transmits the input to the sensitive area database **103**. In one embodiment, the database module **205** receives the input from the sensitive area analysis module **207** in the form of alphanumeric data, and transmits the data to the sensitive area database **103**. The database module **205** and the sensitive area database **103** may be in communication with one another. For example, and without limitation, the database module **205** and the sensitive area database **103** may be in communication via a network **107**, or may be in communication via a dedicated connection, such as a cable or radio link. In an embodiment, the database module **205** also refor-

mats the data received from the sensitive area analysis module 207 into a format usable by the sensitive area database 103. For example, the database module 205 may create one or more files that may be read by the sensitive area database 103. In one embodiment, the database module 205 reformats the data into one or more electronic files that may be imported into a relational database, or into one or more strings of data that may be imported into a relational database.

Returning to FIG. 3 a component view of the sensitive area information transmitter 105 of FIG. 1 according to an embodiment of the present disclosure is shown. In an illustrative embodiment, the sensitive area information transmitter 105 includes a database module 303 and an input/output module 305. In an embodiment, the sensitive area information transmitter 105 is a single system. In another embodiment, the sensitive area information transmitter 105 is two or more systems in communication with each other. The sensitive area information transmitter 105 may include one or more input devices, one or more output devices, one or more processors, and memory associated with the one or more processors. The memory associated with the one or more processors may include, but is not limited to, memory associated with the execution of the modules, and memory associated with the storage of data. The sensitive area information transmitter 105 may also be associated with one or more networks 107, and may communicate with one or more additional systems via the one or more networks 107. The modules may be implemented in hardware or software, or a combination of hardware and software. In an embodiment, the sensitive area information transmitter 105 also includes additional hardware and/or software to allow the sensitive area information transmitter 105 to access the input devices, the output devices, the processors, the memory, and/or the modules. In an embodiment, the modules, or a combination of the modules, are associated with a different processor and/or memory, for example on distinct systems, and the systems are located separately from one another. In an embodiment, the modules are executed on the same system as one or more processes or services. The modules may be operable to communicate with one another and to share information. Although the modules are described as separate and distinct from one another, the functions of two or more modules may instead be executed in the same process, or in the same system.

The memory 307 includes computer readable media. Computer-readable media may be any available media that may be accessed by one or more processors of the sensitive area information transmitter 105 and includes both volatile and non-volatile media. Further, computer readable-media may be one or both of removable and non-removable media. By way of example, computer-readable media may include, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, Digital Versatile Disk (DVD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which may be used to store the desired information and which may be accessed by sensitive area information transmitter 105. The sensitive area information transmitter 105 may be a single system, or may be two or more systems in communication with each other. In one embodiment, the sensitive area information transmitter 105 includes one or more input devices, one or more output devices, one or more processors, and memory 307 associated with the one or more processors.

In the illustrative embodiment, the database module 303 receives an input, and transmits the input to the sensitive area database 103. In one embodiment, the database module 303

transmits a query to the sensitive area database 103 in the form of alphanumeric data, and receives information from the sensitive area database 103 in response to the transmitted query. The database module 303 and the sensitive area database 103 may be in communication with one another. For example, and without limitation, the database module 303 and the sensitive area database 103 may be in communication via a network 107, or may be in communication via a dedicated connection, such as a cable or radio link. In an embodiment, the database module 303 reformats the data received from the sensitive area database 103 into a format usable by the sensitive area information receiving device 113.

In the illustrative embodiment, the input/output module 305 receives data from one or more sensitive area information receiving devices 113 through the use of one or more networks 107. In an embodiment, the data is in the form of a location of the sensitive area information receiving device 113, and a request for sensitive area information surrounding the sensitive area information receiving device 113. In an embodiment, the input/output module 305 receives data from the network 107, and rearranges or reprocesses the data for transmission to the database module 303. In the illustrative embodiment, the database module 303 receives the data from the input/output module 305, and transmits to and receives information from the sensitive area database 103. In the embodiment, the database module 303 transmits the sensitive area database 103 information to the input/output module, and the input/output module transmits the sensitive area database 103 information to the sensitive area information receiving device 113.

Returning to FIG. 4, a component view of the sensitive area information receiving device 113 of FIG. 1 according to an embodiment of the present disclosure is shown. The sensitive area information receiving device 113 in the illustrative embodiment includes a location information module 350, a substance information module 352, an environmental information module 354, a sprayer system information module 356, a spray analysis module 358, and a log file module 382. In one embodiment, sensitive area information receiving device 113 is a handheld device. In one embodiment, sensitive area information receiving device 113 is a smartphone. In the illustrative embodiment, sensitive area information receiving device 113 includes one or more input devices, one or more output devices, one or more processors, and a memory 360 associated with the one or more processors. Exemplary output devices include audio output devices, visual output devices, and tactile output devices. An exemplary audio output device is a speaker. An exemplary visual output device is a display. An exemplary tactile output device is a vibration module. Exemplary input devices includes keys, roller balls, dials, switches, touch pads, touch screens, and other suitable input devices.

The memory 360 associated with the one or more processors may include, but is not limited to, memory associated with the execution of the modules, and memory associated with the storage of data. The sensitive area information receiving device 113 may also be associated with one or more networks 107, and may communicate with one or more additional systems via the one or more networks 107. The modules may be implemented in hardware or software, or a combination of hardware and software. The sensitive area information receiving device 113 may also include additional hardware and/or software to allow the sensitive area information receiving device 113 to access the input devices, the output devices, the processors, the memory, and the modules. In an embodiment, the modules, or a combination of the modules, are associated with a different processor and/or

memory, for example on distinct systems, and the systems are located separately from one another. In another embodiment, the modules are executed on the same system as one or more processes or services. The modules may be operable to communicate with one another and to share information. Although the modules are described as separate and distinct from one another, the functions of two or more modules may instead be executed in the same process, or in the same system.

The memory **360** includes computer readable media. Computer-readable media may be any available media that may be accessed by one or more processors of the receiving system **101** and includes both volatile and non-volatile media. Further, computer readable-media may be one or both of removable and non-removable media. By way of example, computer-readable media may include, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, Digital Versatile Disk (DVD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which may be used to store the desired information and which may be accessed by sensitive area information receiving device **113**. The sensitive area information receiving device **113** may be a single system, or may be two or more systems in communication with each other.

In the illustrative embodiment, the location information module **350** determines a location of the sensitive area information receiving device **113** or provides an interface to receive a desired location through one of the input devices. The location may be a single location or may be an area. The substance information module provides an interface to receive a desired substance to be applied at the specified location. The environmental information module **354** determines the environmental characteristics for the specified location or provides an interface to receive default anticipated environmental characteristics. Exemplary environmental characteristics include wind speed and direction. In one embodiment, environmental information module **354** queries at least one third party system **109** for the environmental characteristics. The sprayer system information module **356** provides an interface to receive characteristics of a spraying system to be used or communicates with distribution system **117** to determine the characteristics of the spraying system.

The spray analysis module **358** based on the specified location determines sensitive areas within the region of the specified location. Based on the sprayer system characteristics and the environmental characteristics, the spray analysis module **358** determines the likelihood of spray drift impinging upon any sensitive areas in the region of the specified location.

In one embodiment, sensitive area information receiving device **113** also includes a substance database **370**. Substance database **370** includes a listing of a plurality of substances and identifies types of plants or animals that are sensitive to each substance. In one embodiment, the listing of substances is presented in the interface of substance information module **352** so that a user of sensitive area information receiving device **113** may select one of the listed substances. In one embodiment, the substance database **370** is updated by contacting one or more third party system **109**. In one example, a manufacturer of substances may provide a substance database for downloading from server. In this example, sensitive area information receiving device **113** would download a copy or an update to an existing copy for storage in memory **360**. Sensitive area information receiving device **113** may receive information on substances from, for example and without limitation, product manufacturers, one or more crop

data management systems ("CDMS"), or databases supplied or maintained by regulatory agencies, for example the Environmental Protection Agency or other state or federal agencies. The information may include, but is not limited to, applicable best management practices or label requirements of substances, such as buffer zone requirements or suggestions. Information may also include labels for substances, or data tables regarding substances.

In one embodiment, spray analysis module **358** provides an indication of all sensitive areas within the region of the specified location. In one embodiment, spray analysis module **358** provides an indication of only sensitive areas within the region of the specified location that are sensitive to proposed substance to be sprayed. In one embodiment, spray analysis module **358** provides a first indication of all sensitive areas within the region of the specified location and a second indication only sensitive areas within the region of the specified location that are sensitive to proposed substance to be sprayed. Certain types of sensitive areas may be sensitive to generally all substances, such as sensitive areas with plants or animals being marketed as organically grown or raised. Other types of sensitive areas may be sensitive to a first substance, but not a second substance. In one embodiment, spray analysis module **358** attempts to determine alternative substances to be sprayed that the identified sensitive areas may not be sensitive to as an alternative to the selected substance.

The log file module **382** captures information related to the application of a substance to an area. In one embodiment, the log file module **382** captures information when the sensitive area information receiving device **113** is activated. In another embodiment, the log file module **382** may be started or stopped, so that the log file module **382** captures or does not capture information. In one embodiment, the log file module **382** may be started or stopped by the user. In another embodiment, the log file module **382** may be started or stopped remotely, by a third party. The log file module **382** captures, for example and without limitation, the type of substance being applied, the date, the current time, the location of one or more of the sprayers, the location of the projected route, the amount of deviation from the actual to the projected routes, the actions of the user, information regarding the current weather, the location of one or more sensitive areas, the proximity of the sprayers to the sensitive areas, or the warnings generated by the sensitive area information receiving device **113**.

The log file module **382** may write to a log file **384**. In one embodiment, the log file **384** is stored as one or more files in the memory of the sensitive area information receiving device **113**. At periodic intervals, the information stored in the one or more files may be transmitted to one or more additional systems, for example the sensitive area information transmitter **105** or the sensitive area database **103**. When the information stored in the one or more files is transmitted, the information or the log files **384** may be deleted from the sensitive area information receiving device **113**, or may be archived with the sensitive area information receiving device **113**. In another embodiment, the information from the log file module **382** is transmitted to the sensitive area information transmitter **105** without being stored with the sensitive area information receiving device **113**, or the information from the log file module **382** is buffered in memory associated with the sensitive area information receiving device **113** before being transmitted. In one embodiment, the one or more log files **384** are stored in a relational database. In another embodiment, the one or more log files **384** are stored in a text file, or an encrypted file.

FIG. 5 shows a flowchart showing a method 400 of identifying sensitive areas according to an embodiment of the present disclosure. The method may begin as illustrated in box 401. The user may identify one or more sensitive areas, as illustrated in box 403. In an embodiment, the user marks the sensitive areas by using a sensitive area identification device 111 to note the location of a field containing sensitive areas. In another embodiment, the user marks the position of one or more sensitive areas on an electronic map, or marks the location of one or more sensitive areas on a paper map, and then scans or faxes the paper map to an operator, who inputs the location information from the paper map into the sensitive area database 103. In another embodiment, the user may communicate with an operator via, for example and without limitation, a telephone, a paging device, or other communication over a network 107 to note the location and type of one or more sensitive areas.

The user may use the sensitive area identification device 111 to note the type and location of the sensitive areas, as illustrated in box 405. The user may use the sensitive area identification device 111 to note the type of sensitive areas by using, for example and without limitation, a drop-down list of sensitive items including one or more crops, animals, sensitive locations, or other sensitive or endangered items; one or more codes to indicate specific types of crops, animals, sensitive locations, or other sensitive or endangered items; or other method of selecting information. In one embodiment, the user uses a camera or camera-enabled device, to take a picture of the crops or seeds planted, and the crop identification device 111 and/or the receiving system 101 use image recognition to determine the type of seed and thus the type of crops. In another embodiment, the user speaks or gestures the name of the crops, and the crop identification device 111 uses voice or pattern recognition to determine the specific type of crop.

The sensitive area identification device 111 may note the type of crop, and may note the location of the crop as well, as illustrated in box 407. In an embodiment, the sensitive area identification device 111 uses a global positioning system or other global positioning satellite system or other location identifier 115. The sensitive area identification device 111 transmits the sensitive area identification and the location information to the receiving system 101. The receiving system 101 may transmit an acknowledgement to indicate that the sensitive area identification information has been successfully transmitted to the receiving system 101.

The receiving system 101 may receive the sensitive area information, including the type and location information, and may transmit the sensitive area information to the sensitive area database 103, as illustrated in box 409. In an embodiment, the receiving system 101 adds information, deletes information, or alters information from the information received from the sensitive area identification device 111 before the information is transmitted and recorded in the sensitive area database 103. The method 400 may end as illustrated in box 411.

FIG. 6 shows a flowchart showing a method 500 of locating crops according to an embodiment of the present disclosure.

The method may begin as illustrated in box 501. In an embodiment, the sensitive area information receiving device 113 requests sensitive area information from the sensitive area information transmitter 105 as illustrated in box 503. The sensitive area information receiving device 113 transmits the request to the sensitive area information transmitter 105 through, for example, a network 107. The sensitive area information receiving device 113 may use a location identifier 115 to determine the location of the sensitive area information

receiving device 113, or the location of the sensitive area information receiving device 113 may be determined another way. For example, and without limitation, the user may input the location of the sensitive area information receiving device 113, or may provide other information to the sensitive area information transmitter 105 to allow the sensitive area information transmitter 105 to approximately or precisely locate the sensitive area information receiving device 113. In another embodiment, the sensitive area information receiving device 113 does not transmit location information to the sensitive area information transmitter 105, but the sensitive area information transmitter 105 sends all or part of the sensitive area information located in the sensitive area database 103 to the sensitive area information receiving device 113. In an embodiment, the sensitive area information receiving device 113 also requests sensitive area information for a predetermined or user defined area around the sensitive area information receiving devices' 113 current location, or other location. For example, and without limitation, the sensitive area information receiving device 113 may request sensitive area information for a three mile radius from the sensitive area information receiving devices' 113 current location. The sensitive area information receiving device 113 may also request sensitive area information based on other identifiers. For example, the sensitive area information receiving device 113 may request sensitive area information for one or more specific types of crops, including buffer zone information, or one or more types of crops that have an adverse interaction with a specific chemical, or request sensitive area information for crops within a zip code, city, county, state, or other geographical boundary identifier.

In an embodiment, the sensitive area information transmitter 105 receives the location data from the sensitive area information receiving device 113, accesses the sensitive area database 103, and requests sensitive area information from the sensitive area database 103 based at least in part on the location information received from the sensitive area information receiving device 113, as illustrated in box 505. The sensitive area information transmitter 105 may, for example and without limitation, request sensitive area information for a preset or user defined radius from the current location transmitted by the sensitive area information receiving device 113. The sensitive area information transmitter 105 may also request sensitive area information from the sensitive area database 103 according to the request transmitted from the sensitive area information receiving device 113. The sensitive area database 103 accesses the sensitive area information, and transmits the requested sensitive area information, if any is available, to the sensitive area information transmitter 105 via one or more networks 107. The sensitive area information transmitter 105 receives the sensitive area information, and, in an embodiment, performs one or more transformations on the sensitive area data, to present it to the sensitive area information receiving device 113. For example, and without limitation, the sensitive area information transmitter 105 may overlay the sensitive area information onto a map, and transmit the map and the sensitive area information to the sensitive area information receiving device 113. In another embodiment, the sensitive area information transmitter 105 adds or deletes information from the sensitive area information before transmitting it to the sensitive area information receiving device 113. For example, and without limitation, the sensitive area information transmitter 105 may remove sensitive area information for crops that are outside of the requested range of crops, or may remove sensitive area information that is outside of a radius or other geographical boundary transmitted by the sensitive area information receiving

device **113**. The sensitive area information transmitter **105** transmits the sensitive area information to the sensitive area information receiving device **113** via the network **107**. In an embodiment, the sensitive area information transmitter **105** does not modify the sensitive area information transmitted from the sensitive area database **103**, transmitting the unmodified sensitive area information received from the sensitive area database **103** to the sensitive area information receiving device **113**.

The sensitive area information receiving device **113** receives sensitive area information from the sensitive area information transmitter **105**, as illustrated in box **507**. The sensitive area information receiving device **113** may receive the sensitive area information from a network **107**, or through other communication methods. For example, and without limitation, the sensitive area information receiving device **113** may receive the sensitive area information from a cellular data network **107**, or other type of wireless network **107**.

In an embodiment, the sensitive area information receiving device **113** may interact with the location transmitter to receive information related to the location of the sensitive area information receiving device **113**, as illustrated in box **509**. In one embodiment, the sensitive area information receiving device **113** receives GPS signals from a GPS system, and uses the one or more GPS signals to calculate its position. In another embodiment, the sensitive area information receiving device **113** uses one or more signals from cellular networks **107** and/or cellular network **107** stations to triangulate or otherwise calculate its location. In another embodiment, the sensitive area information receiving device **113** uses one or more internal devices to calculate its location. For example, the sensitive area information receiving device **113** may contain a compass or an inertial guidance system, or may include a device or sensor to measure linear distance, or may include one or more accelerometers and/or gyroscopes. The sensitive area information receiving device **113** may determine its location using one or more location sensors, and may determine the location of one or more crops based at least in part on the sensitive area information transmitted from the sensitive area information transmitter **105**.

In an embodiment, the sensitive area information receiving device **113** sends one or more alerts and/or makes one or more adjustments to one or more distribution systems **117** based on the location of the sprayers, the location of crops or areas containing animals that may be harmed by the substance or substances that the distribution system **117** is delivering, and other information, such as weather conditions, that may be received by other sensors or instruments and transmitted to the sensitive area information receiving device **113** and/or the distribution system **117**, as illustrated in box **511**. The sensitive area information receiving device **113** may, for example and without limitation, provide a visual, auditory, or tactile alert to the user. The distribution system **117** may also include, for example, and without limitation, the ability to selectively spray, alter spray patterns or direction, alter pressure or spray distance, or alter the relative size of the droplets of the spray. If the distribution system **117** includes more than one sprayer, the distribution system **117** may include the ability to direct flow to one or more of the sprayers, or to alter the flow to one or more of the sprayers. The method may end, as illustrated in box **513**.

While the sensitive area information receiving device **113** is depicted in some embodiments as being portable, where a user inputs variables in real time during or before an application, in other embodiments, the sensitive area information receiving device **113** may be a desktop computer, a laptop computer, a notepad computer, or other type of computer, and

the user may interact with the computer and prepare a plan before applying substances to a field. In FIG. **9**, a flowchart showing a method **900** of compiling a spray plan according to an embodiment of the present disclosure is shown. The method begins at box **901**. In box **903**, the user interacts with the sensitive area information receiving device **113** to identify sensitive areas around the field or fields to which the user intends to apply chemicals. The user may input this information to the sensitive area information receiving device **113** by typing one or more locations into the sensitive area information receiving device **113**, or by highlighting one or more areas on a map. The sensitive area information receiving device **113** communicates the information to the sensitive area information transmitter **105**, which communicates the information to the sensitive area database **103**. The sensitive area database **103** uses the information and transmits the location of sensitive areas to the sensitive area information transmitter **105**, which then transmits the information to the sensitive area information receiving device **113**. The sensitive area information receiving device **113** uses the information from the sensitive area database **103**, and may also use additional information, such as weather or information from the third party systems **109**, to create one or more plans, shown in box **907**.

The plans include information for avoiding the sensitive areas, and may include, but are not limited to, information regarding times and dates of application, applicator speed, amounts or flow rates of the substances, or other information to minimize the risk of substances entering the sensitive areas. The sensitive area information receiving device **113** may present the plans in the form of a paper printout, or may transmit the plans electronically to another device. For example, the sensitive area information receiving device **113** may transmit the plans to a portable computer. The portable computer may interface with the distribution system **117**, or the portable computer may provide alerts or other signals to the user. In one embodiment, the sensitive area information receiving device **113** transmits the plans to a computer or other device located in or on the distribution system **117**.

In an alternate embodiment, the sensitive area information receiving device **113** may be used to perform predictive modeling of one or more future substance applications or other potential environmental impact models. The user may input variables into the sensitive area information receiving device **113** including, but not limited to, the area of proposed application, the type or amount of substance, application directions related to the type or amount of substance, the time of the future application, intended distribution system **117** parameters, the rate of release of the substance, the method used to release the substance, or other variables. In the embodiment, the sensitive area information receiving device **113** receives the variables, and retrieves the data from the sensitive area database **103** and/or one or more of the third party systems **109**, and generates a prediction based on the information received from the user and from the sensitive area database **103** and/or one or more of the third party systems **109**. The third party systems **109** may provide data related to past, current, or future environmental conditions such as weather or placement of sensitive areas, data regarding geologies of the site of proposed application or other areas, data regarding the topologies of the site of proposed application or other areas, or other data regarding the site of proposed application or other areas. Other data that may be considered include the release rate of the proposed application, environmental impact analyses for the substance or substances to be applied, or spray drift modeling data from a sprayer or distribution system.

In one embodiment, the prediction is an indicator to make the application based on the input variables, or an indicator to not make the application based on the input variables. In this embodiment, the user may change one or more of the input variables and re-execute to receive a different indication based on the updated input variables. In another embodiment, the prediction includes a time and/or date to make the application, based at least in part on the input variables and the data retrieved from the one or more third party systems 109. The time and/or date may be a time or date of an ideal time to make the application within a range of dates specified by the user, or may be an ideal time within a predetermined range of dates.

In one example of predictive modeling, the sensitive area information receiving device 113 may receive input from the user regarding the type and amount of substance to be applied to a specific field at a specific date. The sensitive area information receiving device 113 may, for example, query a third party system 109 to retrieve water table information or watershed information, and may recommend not spraying the substance at the particular time, as the information received from the third party system 109 may indicate, for example, that the water table may be too high to spray the substance. The sensitive area information receiving device 113 may recommend the application occur on another day, or that the distribution system 117 parameters be altered to achieve a more desirable outcome.

In another example of predictive modeling, the sensitive area information receiving device 113 may receive input from the user regarding the type and amount of substance to be applied to a specific field at a specific date. The sensitive area information receiving device 113 may, for example, query a third party system 109 to retrieve weather or other meteorological data, and may recommend spraying or not spraying the substance at the particular time. For example, the third party system 109 may indicate that rain or high winds are predicted during one or more times, and the rain may remove the applied substance too quickly, or more quickly than is recommended in the application instructions. In another example, the third party system 109 may indicate that high winds are predicted during one or more times, which may create drift concerns, or may reduce the effectiveness of the applied substance. The sensitive area information receiving device 113 may recommend the application occur on another day, or that the distribution system 117 parameters be altered to achieve a more desirable outcome.

In box 909, the user takes the printouts or the portable computer with the plans to the distribution system 117, and makes the application onto the field. If conditions change after the user has created the plans, in one embodiment, the sensitive area information receiving device 113 transmits updated information to the portable computer, or may attempt to transmit the updates to the user via other methods. For example, and without limitation, the sensitive area information receiving device 113 may transmit a text message, or an e-mail message, or other form of electronic communication, to the user to inform of updated plans. During the application, the user or other system may note any deviations from the plan, and may log the deviations in one or more data files, or log files. The log files may indicate the time and date of any deviations, and may also include information related to the deviation. For example, the location, the substance applied, the amount of deviation from the plan, and/or the user's actions may be recorded, or the user may record the information.

In box 911, the data from the application may be uploaded to a repository to track and maintain compliance information. The repository may be the sensitive area information trans-

mitter 105, or may be another system to store and access the compliance information. The user may upload the log files, or the user may input information into an interface regarding deviations from the plan. The method 900 may end at box 913.

FIG. 7 is an exemplary field showing crops and an exemplary spraying system 620 according to an embodiment of the present disclosure. While a spraying system 620 is used in the example, other substance distribution systems may also be used. For example, and without limitation, an airplane, a helicopter, a boat, a railroad, or a ballast sprayer may be used. A first field 601 and a second field 603 are adjacent to one another. The second field 603 includes a bed of sensitive crops 611 and two beds of insensitive crops 609.

The sensitive crops 611, in the exemplary embodiment, are sensitive to the substance or substance that the spraying system 620 in the first field 601 is planning on delivering. The insensitive crops 609, in the exemplary embodiment, are not sensitive to the substance or substance that the distribution system 117 in the first field 601 is planning on delivering. The sensitive crops 611 and the insensitive crops 609 are marked using one or more crop identification devices 111, which may note the location and the content of the beds. In another embodiment, only the sensitive crops 611 are identified and noted with the crop identification device 111.

Spraying system 620 is to follow a path 622 through field 601 while spraying the crops in field 601. Exemplary north is denoted in element 613. During spraying, the wind is blowing in a north-eastern direction 624 increasing the drift of a sprayed substance in direction 624.

Referring to FIG. 8, an exemplary embodiment of spraying system 620 is shown. Spraying system 620 is an example of a mobile spraying system. Other exemplary spraying systems may be fixed systems having moveable arms supporting spray nozzles, such as irrigation style systems.

Spraying system 620 includes a frame 630 supported by a plurality of ground engaging members 632. Ground engaging members 632 are rotatable relative to the frame 630. At least one of the ground engaging members 632 is operatively coupled to an engine 634 of spraying system 620 to provide power to propel spraying system 620 relative to the ground. Spraying system 620 further includes an operator area 636 having a plurality of controls whereby an operator is able to navigate spraying system 620, such as along path 622.

Spraying system 620 further includes a tank 640 containing the substance to be sprayed by spraying system 620. The interior of tank 640 is in fluid communication with a plurality of spray nozzles 642A-H through a plurality of fluid conduits 644A-J and a plurality of valves 646A-B. In one embodiment, a pump is provided to pump the fluid from tank 640 to the valves 646A-B under pressure. In the illustrated embodiment, spray solution is feed from tank 640 to valve 644A through fluid conduit 644I. Valve 644A, in turn, feeds the spray solution to the respective spray nozzles 642A-D through respective fluid conduits 644A-D. In one embodiment, valve 644A communicates a constant pressure of the spray fluid to every one of the spray nozzles 642A-D. In one embodiment, valve 644A is a manifold and provides individual control relative to each of spray nozzles 642A-D such that the pressure of spray fluid communicated to each spray nozzle is independently controllable. In the illustrated embodiment, spray solution is feed from tank 640 to valve 644B through fluid conduit 644J. Valve 644B, in turn, feeds the spray solution to the respective spray nozzles 642E-H through respective fluid conduits 644E-H. In one embodiment, valve 644B communicates a constant pressure of the spray fluid to every one of the spray nozzles 642E-H. In one embodiment, valve 644B is a mani-

fold and provides individual control relative to each of spray nozzles 642E-H such that the pressure of spray fluid communicated to each spray nozzle is independently controllable. In one embodiment, spray nozzles 642A-H are controllable to alter an amount of spray fluid exiting the respective nozzle. In this example, valves 644A-B are not needed.

Each of spray nozzles 642A-H are supported on a spray frame 650. Nozzles 642D-E are supported on a center spray frame member 652 supported by frame 630 of spraying system 620. Nozzles 642A-C are supported on a first boom arm 654 rotatably coupled to center spray frame member 652. Nozzles 642F-H are supported on a second boom arm 656 rotatably coupled to center spray frame member 652.

Spraying system 620 also includes a spraying system controller 658 which controls the communication of spraying fluid from tank 640 to spray nozzles 642. In one embodiment, spraying system controller is supported by frame 630. In one embodiment, spraying system controller 658 receives input from an environmental sensor 660, such as a wind sensor, to determine the environmental conditions surrounding spraying system 620. In one embodiment, spraying system controller 658 receives input from a location identifier unit 662, such as a GPS device, to determine a current location of spraying system 620. In one embodiment, one or both of environmental sensor 660 and location identifier unit 662 are monitored by sensitive area information receiving devices 113 which in turn reports to spraying system controller 658. In one embodiment, one or both of environmental sensor 660 and location identifier unit 662 are supported by frame 630.

Further, spraying system controller 658 is in communication with sensitive area information receiving devices 113 to determine the relationship of spraying system 620 relative to sensitive crops within the vicinity of spraying system 620 and to adjust one or more spraying characteristics of spraying system 620 accordingly. In one embodiment, the determination of spray characteristic adjustment is made by sensitive area information receiving devices 113. In one embodiment, the determination of spray characteristic adjustment is made by spraying system controller 658. In one embodiment, sensitive area information receiving devices 113 is integrated into spraying system controller 658.

As an example, when spraying system 620 is at the location shown in FIG. 7, based on the information derived from sensitive area database 103, environmental sensor 660, and location identifier unit 662, one of sensitive area information receiving devices 113 and spraying system controller 658 determines that a spray region 680 of spraying system 620 is not overlapping sensitive crops 611 or any other sensitive area. Therefore, spraying system 620 may operate normally. Spray region 680 is a representation of the anticipated area in which spray may fall to ground. As shown in FIG. 7, spray region 680 is elongated to the east of spraying system 620 and forward of spray frame 650 of spraying system 620 on the eastern side. This shape of spray region 680 is due to the direction and speed of the wind.

Of course as spraying system 620 moves through first field 601 and as the speed and direction of the wind change the shape and area of spray region 680 changes. For example, when spraying system 620 is positioned at location 672 in first field 601, the spray region may have the shape of region 680'. This spray region 680' also does not overlap any known sensitive areas so spraying system 620 may operate normally. When spraying system 620 is positioned at location 674 in first field 601, the spray region may have the shape of region 680". This anticipated spray region 680" does overlap sensitive crops 611 so spraying system 620 may not operate normally without risking damage to sensitive crops 611. As such,

one of sensitive area information receiving devices 113 and spraying system controller 658 causes an alteration of the operation of spraying system 620 to reduce the area or shape of spray region 680" to prevent overlap with sensitive crops 611. In one embodiment, an indicator is provided to an operator of spraying system 620 of the risk of overlap and the operator alters the operation of spraying system 620 based thereon. Exemplary indicators include audio indicators, visual indicators, tactile indicators, or combinations thereof.

In one embodiment, the indicator provides multiple levels of indication to an operator. In one embodiment, visual indicator, such as one or more lights or a visual icon on a display, provides multiple visual indications based on a distance to a sensitive area. For example, for a given distance, a green indicator is provided if the given distance is within a first safe range from a sensitive area, a yellow indicator is provided if the given distance is within a second caution range from a sensitive area, and a red indicator is provided if the given distance is within a third range from a sensitive area. The distances that correspond to the boundaries for each range may be user specified valves or pre-programmed values. In one embodiment, the distances are adjusted based on environmental conditions, such as wind. In one embodiment, the given distance is an anticipated boundary of the spray region 680.

In one embodiment, one of sensitive area information receiving devices 113 and spraying system controller 658 automatically alters the operation of spraying system 620 to prevent overlap. In one example, the operation of one or more of valves 644 and nozzles 642 is altered to change the spray pattern. In the case of location 674, nozzles 642A and 642B may be effectively turned off to shorten the extent of spray region 680" towards the east. As spraying system 620 progresses along path 622 the operation of spraying system 620 may return to normal, such as in location 676 whereat region 680" (for normal operation) does not overlap any sensitive area.

In one embodiment, the sensitive area information receiving device 113 (or spraying system controller 658) notes the location of spraying system 620 in the first field 601. The sensitive area information receiving device 113 requests crop information for crops located around spraying system 620. The crop information, in the exemplary embodiment, are stored in the sensitive information database 103, and are transmitted from the sensitive information database 103 to the sensitive area information transmitter 105, and then from the sensitive area information transmitter 105 to the sensitive area information receiving device 113 using a network 107. The sensitive area information receiving device 113 identifies the location of the insensitive crops 609 and the sensitive crops 611, or only the sensitive crops 611. Sensors in spraying system 620 and/or the sensitive area information receiving device 113 indicate that the wind is blowing from the west to the east at a high rate of speed. Sensitive area information receiving devices 113 identifies that spraying system 620, if allowed to spray normally, may create droplets that may drift into the sensitive crops 611. The sensitive area information receiving devices 113 alters the spray pattern of spraying system 620 by, for example, limiting the flow to the spray nozzles 642 or changing the droplet size so that the droplets are unlikely to drift into the sensitive crops 611. The size may be adjusted based on the pulse width of the sprayer and with variable orifice nozzles. In one embodiment, auto steer technology may be used to divert the sprayer of the spraying system. As the wind speed or wind direction changes or the location of spraying system 620 changes, sensitive area information receiving devices 113 changes flow, droplet size, and/

or other spray characteristics so that droplets are unlikely to drift into the sensitive crops **611**.

While this disclosure has been described as having exemplary designs, the present disclosure can be further modified within the spirit and scope of this disclosure. This application is therefore intended to cover any variations, uses or adaptations of the disclosure using its general principles. Further, this application is intended to cover such departures from the present disclosure as come within known or customary practice in the art to which this disclosure pertains.

We claim:

1. An apparatus to identify sensitive areas, comprising:
a module to electronically receive sensitive area information, the sensitive area information related to one or more sensitive areas proximate to a first specified location;

a module to electronically receive an identity of a first substance to be sprayed at the first specified location; and

an alert mechanism to provide an indication of a first sensitive area proximate to the first specified location which is sensitive to the first substance.

2. The apparatus of claim **1**, wherein the alert mechanism includes a display and a visual alert.

3. The apparatus of claim **1**, further comprising a location identifier to determine the location of the apparatus.

4. The apparatus of claim **3**, wherein the location identifier receives location information from a Global Positioning System (GPS).

5. The apparatus of claim **3**, wherein the apparatus receives input regarding a potential application including at least a date and time of a potential application, and the one or more substances to be applied to the locations proximate to the one or more sensitive areas.

6. The apparatus of claim **3**, wherein the apparatus receives input regarding a potential application including at least one or more spraying system parameters.

7. The apparatus of claim **6**, wherein the one or more spraying system parameters includes droplet size, desired pressure, or drift reduction technology credits.

8. The apparatus of claim **3**, wherein the apparatus further includes a module to determine instructions for the application of the one or more substances to the locations proximate to the one or more sensitive areas; and a module to operate a spraying system according to the instructions.

9. The apparatus of claim **8**, wherein operating the spraying system may include one or more of changing the speed of the spraying system, changing the direction of the spraying system, altering the droplet size of the spraying system, or changing the boom height of the spraying system.

10. The apparatus of claim **1**, further comprising a substance database, the substance database includes a plurality of substances and information regarding the sensitivity of at least one of plants and animals to the plurality of substances, the plurality of substances including the first substance.

11. The apparatus of claim **10**, further comprising an interface through which the first substance is selected from the plurality of substances.

12. The apparatus of claim **10**, wherein the substance database includes a buffer zone requirement.

13. A method of identifying sensitive areas, comprising:
providing a handheld device having a first specified location;

electronically receiving with the handheld device sensitive area information, the sensitive area information related to the one or more sensitive areas proximate to the first specified location;

electronically receiving with the handheld device an identity of a first substance to be sprayed at the first specified location; and

providing with a display of the handheld device a visual indication of a first sensitive area proximate to the first specified location which is sensitive to the first substance.

14. The method of claim **13**, wherein the handheld device creates a log file including information related to the first substance and the sensitive area.

15. The method of claim **13**, wherein the handheld device interfaces with a database to receive the sensitive area information.

16. The method of claim **13**, wherein the handheld device overlays the sensitive areas on a map.

17. The method of claim **13**, wherein the handheld device corresponds to a current location with the first specified location.

18. The method of claim **17**, wherein the current location is identified with a Global Positioning System (GPS).

19. The method of claim **13**, wherein the handheld device is spaced apart from the first specified location.

20. The method of claim **13**, wherein the handheld device also receives information from a spraying system.

21. The method of claim **13**, wherein the received sensitive information includes information regarding the first sensitive area and a second sensitive area.

22. The method of claim **13**, wherein the received sensitive information includes information regarding the first sensitive area and a second sensitive area and wherein a visual indication of the second sensitive area is not provided with the display of the handheld device because the second sensitive area is not sensitive to the first substance.

23. The method of claim **13**, wherein the received sensitive information includes information regarding the first sensitive area and a second sensitive area and wherein the visual indication of the first sensitive area has a first characteristic and a visual indication of the second sensitive area is provided with the display of the handheld device having a second characteristic, the second characteristic being different from the first characteristic.

24. The method of claim **13**, wherein the first specified location is one of a current location of the handheld device or a location input into the handheld device.

25. An apparatus to identify sensitive areas, comprising:
a module to electronically receive sensitive area information, the sensitive area information related to the one or more sensitive areas proximate to a first specified location;

a module to electronically receive an identity of a first substance to be sprayed at the first specified location;
a location identifier operable to receive location information regarding the location of the apparatus;

an alert mechanism to provide an indication of a first sensitive area proximate to the first specified location which is sensitive to the first substance; and

a module to operate a spraying system according to at least the sensitive area information, the identity of the first substance, and the location information.

26. The apparatus of claim **25**, wherein the location identifier receives location information from a Global Positioning System (GPS).

27. The apparatus of claim **25**, wherein the apparatus receives input regarding a potential application including at least a date and time of the potential application, and the one or more substances to be applied to the locations proximate to the one or more sensitive areas.

28. The apparatus of claim **25**, wherein the apparatus receives input regarding a potential application including at least one or more spraying system parameters.

29. The apparatus of claim **28**, wherein the one or more spraying system parameters includes one or more of droplet size, desired pressure, or drift reduction technology credits. 5

30. The apparatus of claim **25**, wherein operating the spraying system may include one or more of changing the speed of the spraying system, changing the direction of the spraying system, altering the droplet size of the spraying system, or changing the boom height of the spraying system. 10

31. The apparatus of claim **25**, further comprising a log file to capture information related to the spraying system, wherein the log file captures one or more of a substance being applied, a date, a current time, the current location of the spraying system, a location of a projected route, an amount of deviation from an actual route to the projected route, actions of a user, information regarding current weather, the location of the one or more sensitive areas, a proximity of the spraying system to the one or more sensitive areas, and a warning. 15 20

32. The apparatus of claim **31**, wherein the log file is electronically transmitted to a system.

* * * * *