



US008774825B2

(12) **United States Patent**  
**Forstall et al.**

(10) **Patent No.:** **US 8,774,825 B2**  
(45) **Date of Patent:** **Jul. 8, 2014**

(54) **INTEGRATION OF MAP SERVICES WITH USER APPLICATIONS IN A MOBILE DEVICE**

(75) Inventors: **Scott Forstall**, Mountain View, CA (US); **Gregory N. Christie**, San Jose, CA (US); **Robert E. Borchers**, Pleasanton, CA (US); **Kevin Tiene**, Cupertino, CA (US)

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 780 days.

(21) Appl. No.: **12/135,073**

(22) Filed: **Jun. 6, 2008**

(65) **Prior Publication Data**

US 2009/0005072 A1 Jan. 1, 2009

**Related U.S. Application Data**

(60) Provisional application No. 60/946,915, filed on Jun. 28, 2007.

(51) **Int. Cl.**  
**H04W 24/00** (2009.01)  
**G06F 3/14** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **455/456.1**; 455/456.2; 455/456.3;  
715/864

(58) **Field of Classification Search**  
USPC ..... 455/456.1–456.3; 715/864  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,644,351 A 2/1987 Zabarsky et al.  
4,903,212 A 2/1990 Yokouchi et al.  
4,907,159 A 3/1990 Mauge et al.

4,999,783 A 3/1991 Tenmoku et al.  
5,031,104 A 7/1991 Ikeda et al.  
5,046,011 A 9/1991 Kakihara et al.  
5,067,081 A 11/1991 Person  
5,126,941 A 6/1992 Gurmu et al.  
5,164,904 A 11/1992 Sumner  
5,170,165 A 12/1992 Iihoshi et al.  
5,173,691 A 12/1992 Sumner  
5,182,555 A 1/1993 Sumner  
5,187,810 A 2/1993 Toneyama et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

BR 9904979 12/2000  
CA 2163215 5/1994

(Continued)

**OTHER PUBLICATIONS**

Microsoft Outlook 2003 User's Guide. [http://opan.admin.ufl.edu/user\\_guides/outlook2003.htm](http://opan.admin.ufl.edu/user_guides/outlook2003.htm). Aug. 2004.\*

(Continued)


*Primary Examiner* — Nathan Mitchell

(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**

A method includes receiving an electronic message at a mobile device; displaying the electronic message in an electronic message user interface, the electronic message including sender information; determining a contact entry of an address book application associated with the sender information of the electronic message, the contact entry including physical address information; determining a geographic location of the mobile device; and displaying the contact entry on an address book application user interface, the displayed contact entry including proximity information indicating a distance from the device to the physical address of the contact entry.

**14 Claims, 12 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,195,031 A	3/1993	Ordish	5,870,686 A	2/1999	Monson
5,208,763 A	5/1993	Hong et al.	5,872,526 A	2/1999	Tognazzini
5,218,629 A	6/1993	Dumond, Jr. et al.	5,873,068 A	2/1999	Beaumont et al.
5,243,652 A	9/1993	Teare	5,883,580 A	3/1999	Briancon
5,274,560 A	12/1993	LaRue	5,887,269 A	3/1999	Brunts et al.
5,289,572 A	2/1994	Yano et al.	5,892,454 A	4/1999	Schipper et al.
5,295,064 A	3/1994	Malec et al.	5,893,898 A	4/1999	Tanimoto
5,307,278 A	4/1994	Hermans et al.	5,898,680 A	4/1999	Johnstone
5,317,311 A	5/1994	Martell et al.	5,899,954 A	5/1999	Sato
5,337,044 A	8/1994	Folger et al.	5,905,451 A	5/1999	Sakashita
5,339,391 A	8/1994	Wroblewski et al.	5,908,465 A	6/1999	Ito et al.
5,371,678 A	12/1994	Nomura	5,910,799 A	6/1999	Carpenter
5,374,933 A	12/1994	Kao	5,923,861 A	7/1999	Bertram et al.
5,379,057 A	1/1995	Clough et al.	5,933,094 A	8/1999	Goss et al.
5,390,125 A	2/1995	Sennott et al.	5,933,100 A	8/1999	Golding
5,406,490 A	4/1995	Braegas	5,936,572 A	8/1999	Loomis et al.
5,416,712 A	5/1995	Geier et al.	5,938,721 A	8/1999	Dussell et al.
5,416,890 A	5/1995	Beretta	5,941,930 A	8/1999	Morimoto et al.
5,463,725 A	10/1995	Henckel	5,941,934 A	8/1999	Sato
5,469,362 A	11/1995	Hunt et al.	5,946,618 A	8/1999	Agre et al.
5,479,600 A	12/1995	Wroblewski et al.	5,948,040 A	9/1999	DeLorme et al.
5,504,482 A	4/1996	Schreder	5,948,041 A	9/1999	Abo et al.
5,508,707 A	4/1996	LeBlanc et al.	5,948,061 A	9/1999	Merriman et al.
5,510,801 A	4/1996	Engelbrecht et al.	5,955,973 A	9/1999	Anderson
5,519,760 A	5/1996	Borkowski et al.	5,959,577 A	9/1999	Fan
5,523,950 A	6/1996	Peterson	5,959,580 A	9/1999	Maloney et al.
5,537,460 A	7/1996	Holliday, Jr. et al.	5,968,109 A	10/1999	Israni et al.
5,539,395 A	7/1996	Buss	5,969,678 A	10/1999	Stewart
5,539,647 A	7/1996	Shibata et al.	5,982,298 A	11/1999	Lappenbusch et al.
5,552,989 A	9/1996	Bertrand	5,982,324 A	11/1999	Watters et al.
5,559,520 A	9/1996	Barzegar et al.	5,987,381 A	11/1999	Oshizawa
5,570,412 A	10/1996	LeBlanc	5,991,692 A	11/1999	Spencer, II et al.
5,598,572 A	1/1997	Tanikoshi et al.	5,999,126 A	12/1999	Ito
5,627,547 A	5/1997	Ramaswamy et al.	6,002,932 A	12/1999	Kingdon et al.
5,627,549 A	5/1997	Park	6,002,936 A	12/1999	Roel-Ng et al.
5,628,050 A	5/1997	McGraw	6,005,928 A	12/1999	Johnson
5,630,206 A	5/1997	Urban et al.	6,014,090 A	1/2000	Rosen et al.
5,636,245 A	6/1997	Ernst	6,014,607 A	1/2000	Yagyuu et al.
5,642,303 A	6/1997	Small	6,023,653 A	2/2000	Ichimura et al.
5,646,853 A	7/1997	Takahashi et al.	6,026,375 A	2/2000	Hall et al.
5,654,908 A	8/1997	Yokoyama	6,028,550 A	2/2000	Froeberg et al.
5,663,732 A	9/1997	Stangeland et al.	6,029,069 A	2/2000	Takaki
5,675,362 A	10/1997	Clough et al.	6,031,490 A	2/2000	Forssen et al.
5,675,573 A	10/1997	Karol et al.	6,041,280 A	3/2000	Kohli et al.
5,677,837 A	10/1997	Reynolds	6,052,645 A	4/2000	Harada
5,684,859 A	11/1997	Chanroo et al.	6,058,350 A	5/2000	Ihara
5,689,252 A	11/1997	Ayanoglu et al.	6,064,335 A	5/2000	Eschenbach
5,689,270 A	11/1997	Kelley et al.	6,067,502 A	5/2000	Hayashida et al.
5,689,431 A	11/1997	Rudow et al.	6,069,570 A	5/2000	Herring
5,708,478 A	1/1998	Tognazzini	6,073,013 A	6/2000	Agre et al.
5,717,392 A	2/1998	Eldridge	6,073,062 A	6/2000	Hoshino et al.
5,732,074 A	3/1998	Spaur et al.	6,076,041 A	6/2000	Watanabe
5,742,666 A	4/1998	Alpert	6,078,818 A	6/2000	Kingdon et al.
5,745,865 A	4/1998	Rostoker et al.	6,081,206 A	6/2000	Kielland
5,748,109 A	5/1998	Kosaka et al.	6,085,090 A	7/2000	Yee et al.
5,752,186 A	5/1998	Malackowski et al.	6,085,148 A	7/2000	Jamison
5,754,430 A	5/1998	Sawada	6,087,965 A	7/2000	Murphy
5,758,049 A	5/1998	Johnson et al.	6,088,594 A	7/2000	Kingdon et al.
5,760,773 A	6/1998	Berman et al.	6,091,956 A	7/2000	Hollenberg
5,767,795 A	6/1998	Schaphorst	6,091,957 A	7/2000	Larkins
5,774,824 A	6/1998	Streit et al.	6,092,076 A	7/2000	McDonough et al.
5,774,829 A	6/1998	Cisneros et al.	6,094,607 A	7/2000	Diesel
5,793,630 A	8/1998	Theimer	6,101,443 A	8/2000	Kato
5,796,365 A	8/1998	Lewis	6,104,931 A	8/2000	Havinis et al.
5,796,613 A	8/1998	Kato et al.	6,108,555 A	8/2000	Maloney et al.
5,806,018 A	9/1998	Smith et al.	6,111,541 A	8/2000	Karmel
5,825,306 A	10/1998	Hiyokawa et al.	6,115,611 A	9/2000	Kimoto et al.
5,825,884 A	10/1998	Zdepski et al.	6,115,754 A	9/2000	Landgren
5,831,552 A	11/1998	Sogawa et al.	6,119,014 A	9/2000	Alperovich et al.
5,835,061 A	11/1998	Stewart	6,122,520 A	9/2000	Want et al.
5,839,086 A	11/1998	Hirano	6,125,279 A	9/2000	Hyziak et al.
5,845,227 A	12/1998	Peterson	6,127,945 A	10/2000	Mura-Smith
5,848,373 A	12/1998	DeLorme et al.	6,128,482 A	10/2000	Nixon et al.
5,862,244 A	1/1999	Kleiner et al.	6,128,571 A	10/2000	Ito et al.
5,867,110 A	2/1999	Naito et al.	6,134,548 A	10/2000	Gottzman et al.
			6,138,003 A	10/2000	Kingdon et al.
			6,138,142 A	10/2000	Linsk
			6,140,957 A	10/2000	Wilson et al.
			6,151,309 A	11/2000	Busuioc et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,151,498	A	11/2000	Roel-Ng et al.	6,401,027	B1	6/2002	Xu et al.
6,154,152	A	11/2000	Ito	6,401,032	B1	6/2002	Jamison
6,157,381	A	12/2000	Bates et al.	6,405,034	B1	6/2002	Tijerino
6,157,841	A	12/2000	Bolduc et al.	6,405,123	B1	6/2002	Rennard et al.
6,163,749	A	12/2000	McDonough et al.	6,411,899	B2	6/2002	Dussell et al.
6,166,627	A	12/2000	Reeley	6,414,635	B1	7/2002	Stewart et al.
6,167,266	A	12/2000	Havinis et al.	6,415,207	B1	7/2002	Jones
6,169,552	B1	1/2001	Endo et al.	6,415,220	B1	7/2002	Kovacs
6,175,740	B1	1/2001	Souissi et al.	6,415,227	B1	7/2002	Lin
6,177,905	B1	1/2001	Welch	6,427,115	B1	7/2002	Sekiyama
6,177,938	B1	1/2001	Gould	6,430,411	B1	8/2002	Lempio et al.
6,181,934	B1	1/2001	Havinis et al.	6,434,530	B1	8/2002	Sloane et al.
6,185,427	B1	2/2001	Krasner et al.	6,438,490	B2	8/2002	Ohta
6,188,959	B1	2/2001	Schupfner	6,449,485	B1	9/2002	Anzil
6,195,557	B1	2/2001	Havinis et al.	6,452,498	B2	9/2002	Stewart
6,195,609	B1	2/2001	Pilley et al.	6,456,234	B1	9/2002	Johnson
6,199,014	B1	3/2001	Walker	6,456,956	B1	9/2002	Xiong
6,199,045	B1	3/2001	Giniger et al.	6,459,782	B1*	10/2002	Bedrosian et al. .... 379/201.08
6,199,099	B1	3/2001	Gershman et al.	6,463,289	B1	10/2002	Havinis et al.
6,202,008	B1	3/2001	Beckert et al.	6,477,581	B1	11/2002	Carpenter
6,202,023	B1	3/2001	Hancock et al.	6,487,305	B2	11/2002	Kambe et al.
6,208,866	B1	3/2001	Rouhollahzadeh et al.	6,490,454	B1	12/2002	Kangas et al.
6,212,473	B1	4/2001	Stefan et al.	6,490,519	B1	12/2002	Lapidot et al.
6,216,086	B1	4/2001	Seymour et al.	6,501,421	B1	12/2002	Dutta et al.
6,222,483	B1	4/2001	Twitchell et al.	6,505,046	B1	1/2003	Baker
6,233,518	B1	5/2001	Lee	6,505,048	B1	1/2003	Moles et al.
6,236,365	B1	5/2001	LeBlanc et al.	6,505,123	B1	1/2003	Root et al.
6,236,933	B1	5/2001	Lang	6,507,802	B1	1/2003	Payton et al.
6,246,948	B1	6/2001	Thakker	6,516,197	B2	2/2003	Havinis et al.
6,249,252	B1	6/2001	Dupray	6,519,463	B2	2/2003	Tendler
6,252,543	B1	6/2001	Camp	6,526,335	B1	2/2003	Treyz et al.
6,252,544	B1	6/2001	Hoffberg	6,529,143	B2	3/2003	Mikkola et al.
6,256,498	B1	7/2001	Ludwig	6,535,140	B1	3/2003	Goss et al.
6,259,405	B1	7/2001	Stewart et al.	6,542,812	B1	4/2003	Obradovich et al.
6,266,612	B1	7/2001	Dussell et al.	6,542,819	B1	4/2003	Kovacs et al.
6,266,614	B1	7/2001	Alumbaugh	6,545,638	B2	4/2003	Sladen
6,266,615	B1	7/2001	Jin	6,546,336	B1	4/2003	Matsuoka et al.
6,272,342	B1	8/2001	Havinis et al.	6,546,360	B1	4/2003	Gilbert et al.
6,278,884	B1	8/2001	Kim	6,552,682	B1	4/2003	Fan
6,281,807	B1	8/2001	Kynast et al.	6,563,430	B1	5/2003	Kemink et al.
6,282,491	B1	8/2001	Bochmann et al.	6,564,143	B1	5/2003	Alewine et al.
6,282,496	B1	8/2001	Chowdhary	6,570,557	B1	5/2003	Westerman et al.
6,295,454	B1	9/2001	Havinis et al.	6,571,279	B1	5/2003	Herz et al.
6,298,306	B1	10/2001	Suarez et al.	6,574,484	B1	6/2003	Carley
6,304,758	B1	10/2001	Iierbig et al.	6,574,550	B2	6/2003	Hashida
6,313,761	B1	11/2001	Shinada	6,587,688	B1	7/2003	Chambers et al.
6,314,369	B1	11/2001	Ito et al.	6,587,782	B1	7/2003	Nocek et al.
6,314,406	B1	11/2001	O'Hagan et al.	6,587,835	B1	7/2003	Treyz et al.
6,317,684	B1	11/2001	Roeseler et al.	6,594,480	B1	7/2003	Montalvo et al.
6,321,158	B1	11/2001	DeLorme et al.	6,597,305	B2	7/2003	Szeto et al.
6,323,846	B1	11/2001	Westerman et al.	6,611,687	B1	8/2003	Clark et al.
6,324,692	B1	11/2001	Fiske	6,611,788	B1	8/2003	Hussa
6,326,918	B1	12/2001	Stewart	6,615,131	B1	9/2003	Rennard et al.
6,332,127	B1	12/2001	Bandera et al.	6,615,213	B1	9/2003	Johnson
6,339,437	B1	1/2002	Nielsen	6,643,587	B2	11/2003	Brodie et al.
6,339,746	B1	1/2002	Sugiyama et al.	6,647,257	B2	11/2003	Owensby
6,343,317	B1	1/2002	Glorikian	6,650,902	B1	11/2003	Richton
6,345,288	B1	2/2002	Reed et al.	6,650,997	B2	11/2003	Funk
6,351,235	B1	2/2002	Stilp	6,662,016	B1	12/2003	Buckham et al.
6,353,398	B1	3/2002	Amin et al.	6,667,963	B1	12/2003	Rantalainen et al.
6,353,743	B1	3/2002	Karmel	6,671,377	B1	12/2003	Havinis et al.
6,353,837	B1	3/2002	Blumenau	6,674,849	B1*	1/2004	Froeberg ..... 379/201.06
6,356,761	B1	3/2002	Huttunen	6,677,894	B2	1/2004	Sheynblat et al.
6,356,763	B1	3/2002	Kangas et al.	6,678,516	B2	1/2004	Nordman et al.
6,356,836	B1	3/2002	Adolph	6,679,932	B2	1/2004	Birler et al.
6,356,838	B1	3/2002	Paul	6,680,694	B1	1/2004	Knockeart et al.
6,370,629	B1	4/2002	Hastings et al.	6,681,120	B1	1/2004	Kim
6,377,886	B1	4/2002	Gotou	6,683,538	B1	1/2004	Wilkes, Jr.
6,381,465	B1	4/2002	Chern et al.	6,697,018	B2	2/2004	Stewart
6,381,539	B1	4/2002	Shimazu	6,697,734	B1	2/2004	Suomela
6,381,603	B1	4/2002	Chan et al.	6,711,408	B1	3/2004	Raith
6,385,458	B1	5/2002	Papadimitriou et al.	6,711,474	B1	3/2004	Treyz et al.
6,385,465	B1	5/2002	Yoshioka	6,714,791	B2	3/2004	Friedman
6,385,535	B2	5/2002	Ohishi et al.	6,718,344	B2	4/2004	Hirono
6,389,288	B1	5/2002	Kuwahara et al.	6,721,572	B1	4/2004	Smith et al.
				6,731,236	B1	5/2004	Hager et al.
				6,731,238	B2	5/2004	Johnson
				6,732,047	B1	5/2004	de Silva
				6,738,808	B1	5/2004	Zellner et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,741,188	B1	5/2004	Miller et al.	7,213,048	B1	5/2007	Parupudi et al.
6,741,926	B1	5/2004	Zhao et al.	7,215,967	B1	5/2007	Kransmo et al.
6,748,226	B1	6/2004	Wortham	7,236,883	B2	6/2007	Garin et al.
6,748,318	B1	6/2004	Jones	7,254,481	B2	8/2007	Yamada et al.
6,750,883	B1	6/2004	Parupudi et al.	7,256,711	B2	8/2007	Sheha et al.
6,759,960	B2	7/2004	Stewart	7,257,392	B2	8/2007	Tang et al.
6,762,772	B1	7/2004	Imamura et al.	7,260,378	B2	8/2007	Holland et al.
6,766,174	B1 *	7/2004	Kenyon ..... 455/457	7,266,376	B2	9/2007	Nakagawa
6,766,245	B2	7/2004	Padmanabhan	7,269,601	B2	9/2007	Kinno et al.
6,781,575	B1	8/2004	Hawkins et al.	7,271,765	B2	9/2007	Stilp et al.
6,782,278	B2	8/2004	Chen et al.	7,272,403	B2	9/2007	Creamer et al.
6,789,012	B1	9/2004	Childs et al.	7,272,404	B2	9/2007	Overy et al.
6,795,686	B2	9/2004	Master et al.	7,274,332	B1	9/2007	Dupray
6,801,855	B1	10/2004	Walters et al.	7,274,939	B2	9/2007	Ruutu et al.
6,810,323	B1	10/2004	Bullock et al.	7,280,822	B2	10/2007	Fraccaroli
6,813,501	B2	11/2004	Kinnunen et al.	7,286,933	B2	10/2007	Cho
6,813,503	B1	11/2004	Zillikens et al.	7,295,556	B2	11/2007	Roese et al.
6,813,582	B2	11/2004	Levi et al.	7,295,925	B2	11/2007	Breed et al.
6,816,782	B1	11/2004	Walters et al.	7,298,327	B2	11/2007	Dupray et al.
6,819,919	B1	11/2004	Tanaka	7,299,008	B2	11/2007	Gluck
6,823,188	B1	11/2004	Stern	7,310,516	B1	12/2007	Vacanti
6,834,195	B2	12/2004	Brandenberg et al.	7,313,467	B2	12/2007	Breed et al.
6,845,318	B1	1/2005	Moore et al.	7,319,412	B1	1/2008	Coppinger et al.
6,847,891	B2	1/2005	Pietras et al.	7,336,928	B2	2/2008	Paalasmaa et al.
6,847,969	B1	1/2005	Mathai et al.	7,336,949	B2	2/2008	Nasielski
6,853,911	B1	2/2005	Sakarya	7,339,496	B2	3/2008	Endo et al.
6,853,917	B2	2/2005	Miwa	7,343,564	B2	3/2008	Othmer
6,859,149	B1	2/2005	Ohta	7,349,706	B2	3/2008	Kim et al.
6,865,483	B1	3/2005	Cook, III et al.	7,353,034	B2	4/2008	Haney
6,868,074	B1	3/2005	Hanson	7,359,713	B1	4/2008	Tiwari
6,871,144	B1	3/2005	Lee	7,370,283	B2	5/2008	Othmer
6,882,313	B1	4/2005	Fan et al.	7,373,246	B2	5/2008	O'Clair
6,888,536	B2	5/2005	Westerman et al.	7,386,396	B2	6/2008	Johnson
6,909,902	B1	6/2005	Sawada et al.	7,389,179	B2	6/2008	Jin et al.
6,912,398	B1	6/2005	Domnitz	7,392,017	B2	6/2008	Chu et al.
6,914,626	B2	7/2005	Squibbs	7,395,031	B1	7/2008	Ritter
6,915,208	B2	7/2005	Garin et al.	7,418,402	B2	8/2008	McCrossin et al.
6,931,322	B2	8/2005	Jung et al.	7,421,422	B1	9/2008	Dempster et al.
6,933,841	B2	8/2005	Muramatsu et al.	7,421,486	B1	9/2008	Parupudi et al.
6,944,447	B2	9/2005	Portman et al.	7,426,437	B2	9/2008	Breed et al.
6,948,656	B2	9/2005	Williams	7,427,021	B2	9/2008	Kemper et al.
6,950,746	B2	9/2005	Yano et al.	7,433,694	B2	10/2008	Morgan et al.
6,952,181	B2	10/2005	Karr et al.	7,440,842	B1	10/2008	Vorona
6,954,646	B2	10/2005	Churt	7,441,203	B2	10/2008	Othmer et al.
6,954,735	B1	10/2005	Djupsjobacka et al.	7,466,235	B1	12/2008	Kolb et al.
6,957,072	B2	10/2005	Kangras et al.	7,483,944	B2	1/2009	Parupudi et al.
6,975,959	B2	12/2005	Dietrich et al.	7,486,201	B2	2/2009	Kelly et al.
6,980,909	B2	12/2005	Root et al.	7,500,607	B2	3/2009	Williams
6,990,495	B1 *	1/2006	Grason et al. .... 1/1	7,512,487	B1	3/2009	Golding et al.
6,999,779	B1	2/2006	Hashimoto	7,522,927	B2	4/2009	Fitch et al.
7,003,289	B1	2/2006	Kolls	7,525,484	B2	4/2009	Dupray et al.
7,009,556	B2	3/2006	Stewart	7,536,388	B2	5/2009	Jung et al.
7,031,725	B2	4/2006	Rorabaugh	7,545,281	B2	6/2009	Richards et al.
7,044,372	B2	5/2006	Okuda et al.	7,558,696	B2	7/2009	Vilppula et al.
7,058,594	B2	6/2006	Stewart	7,565,132	B2	7/2009	Ben Ayed
7,069,319	B2	6/2006	Zellner et al.	7,565,157	B1	7/2009	Ortega et al.
7,076,255	B2	7/2006	Parupudi et al.	7,574,222	B2	8/2009	Sawada et al.
7,082,365	B2	7/2006	Sheha et al.	7,577,448	B2	8/2009	Pande et al.
7,089,264	B1	8/2006	Guido et al.	7,587,345	B2	9/2009	Mann et al.
7,096,029	B1	8/2006	Parupudi et al.	7,593,740	B2	9/2009	Crowley et al.
7,096,030	B2	8/2006	Huomo	7,593,991	B2	9/2009	Friedman et al.
7,103,470	B2	9/2006	Mintz	7,596,450	B2	9/2009	Hong
7,117,015	B2	10/2006	Scheinert et al.	7,599,795	B1	10/2009	Blumberg et al.
7,120,469	B1	10/2006	Urakawa	7,603,233	B2	10/2009	Tashiro
7,123,189	B2	10/2006	Lalik et al.	7,606,580	B2	10/2009	Granito et al.
7,123,926	B2	10/2006	Himmelstein	7,617,044	B2	11/2009	Lee
7,146,298	B2	12/2006	Motamedi et al.	7,620,404	B2	11/2009	Chesnais et al.
7,149,503	B2	12/2006	Aarnio et al.	7,623,848	B2	11/2009	Rosenfelt et al.
7,151,921	B2	12/2006	Otsuka	7,624,358	B2	11/2009	Kim et al.
7,165,725	B2	1/2007	Casey	7,647,174	B2	1/2010	Kwon
7,171,190	B2	1/2007	Ye et al.	7,680,591	B2	3/2010	Nagaa et al.
7,181,189	B2	2/2007	Hotta et al.	7,689,916	B1 *	3/2010	Goel et al. .... 715/711
7,187,997	B2	3/2007	Johnson	7,710,290	B2	5/2010	Johnson
7,200,409	B1	4/2007	Ichikawa et al.	7,711,478	B2	5/2010	Gluck
7,200,566	B1	4/2007	Moore et al.	7,714,778	B2	5/2010	Dupray
				7,729,691	B2	6/2010	Newville
				7,739,040	B2	6/2010	Horvitz
				7,743,074	B1	6/2010	Parupudi et al.
				7,756,639	B2	7/2010	Colley et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,768,395 B2	8/2010	Gold	2004/0068439 A1	4/2004	Elgrably
7,783,421 B2	8/2010	Arai et al.	2004/0072557 A1	4/2004	Paila et al.
7,792,273 B2	9/2010	Fano et al.	2004/0072577 A1	4/2004	Myllymaki et al.
7,811,203 B2	10/2010	Unuma et al.	2004/0073361 A1	4/2004	Tzamaloukas et al.
7,822,547 B2	10/2010	Lindroos	2004/0082351 A1	4/2004	Westman
7,848,388 B2	12/2010	Tudosoiu	2004/0083050 A1*	4/2004	Biyani ..... 701/200
7,848,765 B2	12/2010	Phillips et al.	2004/0093155 A1	5/2004	Simonds
7,860,758 B2	12/2010	McCrossin et al.	2004/0093392 A1	5/2004	Nagamatsu et al.
7,890,123 B2	2/2011	Granito et al.	2004/0093566 A1*	5/2004	McElligott ..... 715/531
7,933,612 B2	4/2011	Counts et al.	2004/0098175 A1	5/2004	Said et al.
7,933,929 B1	4/2011	McClendon et al.	2004/0104842 A1	6/2004	Drury et al.
7,941,188 B2	5/2011	Jung et al.	2004/0110515 A1	6/2004	Blumberg et al.
7,970,418 B2	6/2011	Schmidt et al.	2004/0128067 A1	7/2004	Smith
7,991,432 B2	8/2011	Silverbrook et al.	2004/0151151 A1	8/2004	Kubler et al.
8,036,630 B2	10/2011	Park et al.	2004/0158401 A1	8/2004	Yoon
8,046,009 B2	10/2011	Bodmer et al.	2004/0158584 A1	8/2004	Necsoiu et al.
8,073,565 B2	12/2011	Johnson	2004/0172409 A1	9/2004	James
8,082,094 B2	12/2011	Gao	2004/0176907 A1	9/2004	Nesbitt
8,250,634 B2	8/2012	Agarwal et al.	2004/0180669 A1	9/2004	Kall
8,332,878 B2	12/2012	Harm	2004/0192299 A1*	9/2004	Wilson et al. .... 455/433
2001/0018349 A1	8/2001	Kinnunen et al.	2004/0198335 A1	10/2004	Campen
2001/0046884 A1	11/2001	Yoshioka	2004/0198379 A1	10/2004	Magee et al.
2002/0032035 A1	3/2002	Teshima	2004/0198397 A1	10/2004	Weiss
2002/0035493 A1	3/2002	Mozayeny et al.	2004/0203569 A1	10/2004	Jijina et al.
2002/0035609 A1	3/2002	Lessard et al.	2004/0203746 A1	10/2004	Knauerhase et al.
2002/0042266 A1	4/2002	Heyward et al.	2004/0203836 A1	10/2004	Gorday et al.
2002/0046069 A1	4/2002	Mozayeny et al.	2004/0203880 A1	10/2004	Riley
2002/0046077 A1	4/2002	Mozayeny et al.	2004/0203909 A1	10/2004	Koster
2002/0046084 A1	4/2002	Steele et al.	2004/0204842 A1	10/2004	Shinozaki
2002/0055373 A1	5/2002	King et al.	2004/0215707 A1	10/2004	Fujita et al.
2002/0067353 A1	6/2002	Kenyon et al.	2004/0225436 A1	11/2004	Yoshihashi
2002/0077144 A1	6/2002	Keller et al.	2004/0228330 A1	11/2004	Kubler et al.
2002/0087505 A1	7/2002	Smith et al.	2004/0236504 A1	11/2004	Bickford et al.
2002/0091991 A1	7/2002	Castro	2004/0242149 A1	12/2004	Luneau
2002/0095486 A1	7/2002	Bahl	2004/0246940 A1	12/2004	Kubler et al.
2002/0118112 A1	8/2002	Lang	2004/0248586 A1	12/2004	Patel et al.
2002/0126146 A1*	9/2002	Burns et al. .... 345/752	2004/0260939 A1	12/2004	Ichikawa et al.
2002/0128773 A1	9/2002	Chowanic et al.	2004/0263084 A1	12/2004	Mor et al.
2002/0132625 A1	9/2002	Ogino et al.	2004/0264442 A1	12/2004	Kubler et al.
2002/0140560 A1	10/2002	Altman et al.	2005/0002419 A1	1/2005	Doviak et al.
2002/0160815 A1	10/2002	Patel et al.	2005/0004838 A1	1/2005	Perkowski et al.
2002/0167442 A1	11/2002	Taylor	2005/0009511 A1	1/2005	Bostrom et al.
2002/0173905 A1	11/2002	Jin et al.	2005/0027442 A1	2/2005	Kelley et al.
2003/0014181 A1	1/2003	Myr	2005/0033509 A1	2/2005	Clapper
2003/0016804 A1*	1/2003	Sheha et al. .... 379/201.06	2005/0033515 A1	2/2005	Bozzone
2003/0032404 A1	2/2003	Wager et al.	2005/0037781 A1	2/2005	Ozugur et al.
2003/0055560 A1	3/2003	Phillips et al.	2005/0039140 A1	2/2005	Chen
2003/0060212 A1	3/2003	Thomas	2005/0046584 A1	3/2005	Breed
2003/0060215 A1	3/2003	Graham	2005/0071078 A1	3/2005	Yamada et al.
2003/0060973 A1	3/2003	Mathews et al.	2005/0071702 A1	3/2005	Morisawa
2003/0060976 A1	3/2003	Sato et al.	2005/0075116 A1	4/2005	Laird
2003/0065934 A1	4/2003	Angelo et al.	2005/0085272 A1	4/2005	Anderson et al.
2003/0069029 A1	4/2003	Dowling et al.	2005/0091408 A1	4/2005	Parupudi et al.
2003/0069683 A1	4/2003	Lapidot et al.	2005/0096840 A1	5/2005	Simske
2003/0078054 A1	4/2003	Okuda	2005/0114021 A1	5/2005	Krull et al.
2003/0078055 A1	4/2003	Smith et al.	2005/0130677 A1	6/2005	Meunier et al.
2003/0078057 A1	4/2003	Watanabe et al.	2005/0134440 A1	6/2005	Breed
2003/0093217 A1	5/2003	Petzold et al.	2005/0134578 A1	6/2005	Chambers et al.
2003/0096620 A1	5/2003	Ozturk et al.	2005/0149250 A1	7/2005	Isaac
2003/0100326 A1	5/2003	Grube et al.	2005/0153681 A1	7/2005	Hanson
2003/0100334 A1	5/2003	Mazzara, Jr.	2005/0176411 A1	8/2005	Taya
2003/0101225 A1	5/2003	Han et al.	2005/0186954 A1	8/2005	Kenney
2003/0105826 A1*	6/2003	Mayraz ..... 709/206	2005/0192025 A1	9/2005	Kaplan
2003/0120423 A1	6/2003	Cochlovius et al.	2005/0197767 A1	9/2005	Nortrup
2003/0134657 A1	7/2003	Norta et al.	2005/0203698 A1	9/2005	Lee
2003/0140136 A1	7/2003	Nakamura	2005/0221799 A1	10/2005	Tervo et al.
2003/0144793 A1	7/2003	Melaku et al.	2005/0221808 A1	10/2005	Karlsson et al.
2003/0148774 A1	8/2003	Naghian et al.	2005/0221843 A1	10/2005	Friedman et al.
2003/0158655 A1	8/2003	Obradovich et al.	2005/0222756 A1	10/2005	Davis et al.
2003/0191578 A1	10/2003	Paulauskas et al.	2005/0222763 A1	10/2005	Uyeki
2003/0236106 A1	12/2003	Master et al.	2005/0227709 A1	10/2005	Chang et al.
2004/0010358 A1	1/2004	Oesterling et al.	2005/0228860 A1	10/2005	Hamynen et al.
2004/0036649 A1	2/2004	Taylor	2005/0234637 A1	10/2005	Obradovich et al.
2004/0054428 A1	3/2004	Sheha et al.	2005/0239477 A1	10/2005	Kim et al.
2004/0059502 A1	3/2004	Levi et al.	2005/0250440 A1	11/2005	Zhou et al.
			2005/0256639 A1	11/2005	Aleksic et al.
			2005/0286421 A1	12/2005	Janacek
			2006/0009908 A1	1/2006	Tomita et al.
			2006/0015249 A1	1/2006	Gieseke

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2006/0022048	A1	2/2006	Johnson	2007/0127439	A1	5/2007	Yokoyama
2006/0025158	A1	2/2006	Leblanc et al.	2007/0127661	A1	6/2007	Didcock
2006/0029109	A1	2/2006	Moran	2007/0129888	A1	6/2007	Rosenberg
2006/0038719	A1	2/2006	Pande et al.	2007/0130153	A1	6/2007	Nachman et al.
2006/0041374	A1	2/2006	Inoue	2007/0135136	A1	6/2007	Ische
2006/0041377	A1	2/2006	Jung et al.	2007/0135990	A1	6/2007	Seymour et al.
2006/0041378	A1	2/2006	Cheng et al.	2007/0142026	A1	6/2007	Kuz et al.
2006/0056388	A1	3/2006	Livingood	2007/0149212	A1	6/2007	Gupta et al.
2006/0058955	A1	3/2006	Mehren	2007/0150192	A1	6/2007	Wakamatsu et al.
2006/0063539	A1	3/2006	Beyer, Jr.	2007/0150320	A1	6/2007	Huang
2006/0064239	A1	3/2006	Ishii	2007/0153983	A1	7/2007	Bloebaum et al.
2006/0068809	A1	3/2006	Wengler et al.	2007/0153984	A1	7/2007	Bloebaum et al.
2006/0069503	A1	3/2006	Suomela	2007/0153986	A1	7/2007	Bloebaum et al.
2006/0085392	A1	4/2006	Wang et al.	2007/0155360	A1	7/2007	An
2006/0094353	A1	5/2006	Nielsen et al.	2007/0155404	A1	7/2007	Yamane et al.
2006/0101005	A1	5/2006	Yang et al.	2007/0156326	A1	7/2007	Nesbitt
2006/0111122	A1	5/2006	Carlsan et al.	2007/0156337	A1	7/2007	Yanni
2006/0116137	A1	6/2006	Jung	2007/0162224	A1	7/2007	Luo
2006/0148463	A1	7/2006	Zhu et al.	2007/0179854	A1	8/2007	Ziv et al.
2006/0149461	A1	7/2006	Rowley	2007/0184855	A1	8/2007	Klassen
2006/0150119	A1	7/2006	Chesnais et al.	2007/0191029	A1	8/2007	Zarem et al.
2006/0166679	A1	7/2006	Karaoguz et al.	2007/0198304	A1	8/2007	Cohen et al.
2006/0168300	A1	7/2006	An et al.	2007/0200713	A1	8/2007	Weber et al.
2006/0172769	A1	8/2006	Oh	2007/0202887	A1	8/2007	Counts et al.
2006/0172778	A1	8/2006	Sundararajan et al.	2007/0204218	A1	8/2007	Weber et al.
2006/0179114	A1*	8/2006	Deeds ..... 709/206	2007/0206730	A1	9/2007	Polk
2006/0180649	A1	8/2006	Casey	2007/0208492	A1	9/2007	Downs et al.
2006/0184320	A1	8/2006	Hong	2007/0208497	A1	9/2007	Downs et al.
2006/0184978	A1	8/2006	Casey	2007/0208498	A1	9/2007	Barker et al.
2006/0195481	A1	8/2006	Arrouye et al.	2007/0208507	A1	9/2007	Gotoh
2006/0199567	A1	9/2006	Alston	2007/0219706	A1	9/2007	Sheynblat
2006/0199612	A1*	9/2006	Beyer et al. .... 455/556.2	2007/0229549	A1	10/2007	Dicke et al.
2006/0202819	A1	9/2006	Adamczyk et al.	2007/0232326	A1	10/2007	Johnson
2006/0211453	A1	9/2006	Schick	2007/0233387	A1	10/2007	Johnson
2006/0218209	A1	9/2006	Arrouye et al.	2007/0238491	A1	10/2007	He
2006/0227047	A1	10/2006	Rosenberg	2007/0243853	A1	10/2007	Bumiller et al.
2006/0229802	A1	10/2006	Vertelney et al.	2007/0247435	A1*	10/2007	Benko ..... 345/173
2006/0247855	A1	11/2006	de Silva et al.	2007/0254676	A1	11/2007	Pedigo et al.
2006/0251034	A1	11/2006	Park	2007/0259674	A1	11/2007	Neef et al.
2006/0270421	A1	11/2006	Phillips et al.	2007/0260751	A1	11/2007	Meesseman
2006/0271280	A1	11/2006	O'Clair	2007/0266116	A1*	11/2007	Rensin et al. .... 709/217
2006/0284767	A1	12/2006	Taylor	2007/0270159	A1*	11/2007	Lohtia et al. .... 455/456.1
2006/0287824	A1	12/2006	Lin	2007/0271328	A1	11/2007	Geelen et al.
2006/0291639	A1	12/2006	Radziewicz et al.	2007/0276586	A1	11/2007	Jeon et al.
2006/0293029	A1	12/2006	Jha et al.	2007/0276587	A1	11/2007	Johnson
2006/0293083	A1*	12/2006	Bowen ..... 455/558	2007/0276596	A1	11/2007	Solomon et al.
2007/0001875	A1	1/2007	Taylor	2007/0282521	A1	12/2007	Broughton
2007/0003040	A1	1/2007	Radziewicz et al.	2007/0282565	A1	12/2007	Bye et al.
2007/0005188	A1	1/2007	Johnson	2007/0290920	A1	12/2007	Shintai et al.
2007/0005233	A1	1/2007	Pinkus et al.	2007/0299601	A1	12/2007	Zhao et al.
2007/0006098	A1	1/2007	Krumm et al.	2008/0004789	A1	1/2008	Horvitz et al.
2007/0008515	A1	1/2007	Otani et al.	2008/0004791	A1	1/2008	Sera
2007/0010942	A1	1/2007	Bill	2008/0004802	A1	1/2008	Horvitz
2007/0016362	A1	1/2007	Nelson	2008/0005104	A1	1/2008	Flake et al.
2007/0027614	A1	2/2007	Reeser et al.	2008/0005301	A1	1/2008	Li et al.
2007/0027628	A1	2/2007	Geelen	2008/0015422	A1	1/2008	Wessel
2007/0038364	A1	2/2007	Lee et al.	2008/0021632	A1	1/2008	Amano
2007/0038369	A1	2/2007	Devries et al.	2008/0024360	A1	1/2008	Taylor
2007/0042790	A1	2/2007	Mohi et al.	2008/0024364	A1	1/2008	Taylor
2007/0055684	A1	3/2007	Stevens	2008/0027636	A1	1/2008	Tengler et al.
2007/0060328	A1	3/2007	Zrike et al.	2008/0030308	A1	2/2008	Johnson
2007/0061245	A1	3/2007	Ramer et al.	2008/0032703	A1	2/2008	Krumm et al.
2007/0061301	A1	3/2007	Ramer et al.	2008/0032721	A1	2/2008	MacDonald et al.
2007/0061363	A1	3/2007	Ramer et al.	2008/0045234	A1	2/2008	Reed
2007/0071114	A1	3/2007	Sanderford et al.	2008/0046176	A1	2/2008	Jurgens
2007/0073480	A1	3/2007	Singh	2008/0052407	A1	2/2008	Baudino et al.
2007/0073719	A1	3/2007	Ramer et al.	2008/0065311	A1	3/2008	Bauchot et al.
2007/0087726	A1	4/2007	McGary et al.	2008/0070593	A1	3/2008	Altman et al.
2007/0093258	A1	4/2007	Steenstra et al.	2008/0071466	A1	3/2008	Downs et al.
2007/0093955	A1	4/2007	Hughes	2008/0082254	A1	4/2008	Huhtala et al.
2007/0106465	A1	5/2007	Adam et al.	2008/0085727	A1	4/2008	Kratz
2007/0115868	A1	5/2007	Chen et al.	2008/0086240	A1	4/2008	Breed
2007/0124043	A1	5/2007	Ayoub et al.	2008/0088486	A1	4/2008	Rozum et al.
2007/0124058	A1	5/2007	Kitagawa et al.	2008/0091347	A1	4/2008	Tashiro
2007/0124066	A1	5/2007	Kikuchi	2008/0096518	A1	4/2008	Mock et al.
				2008/0097698	A1	4/2008	Arnold-Huyser et al.
				2008/0098090	A1	4/2008	Geraci et al.
				2008/0104634	A1	5/2008	Gajdos et al.
				2008/0109153	A1	5/2008	Guezic

(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0113672 A1 5/2008 Karr et al.  
 2008/0129528 A1 6/2008 Guthrie  
 2008/0132243 A1 6/2008 Spalink et al.  
 2008/0132251 A1 6/2008 Altman et al.  
 2008/0132252 A1 6/2008 Altman et al.  
 2008/0140308 A1 6/2008 Yamane et al.  
 2008/0140520 A1 6/2008 Hyder et al.  
 2008/0153512 A1 6/2008 Kale et al.  
 2008/0153513 A1 6/2008 Flake et al.  
 2008/0155453 A1 6/2008 Othmer  
 2008/0160956 A1 7/2008 Jackson et al.  
 2008/0161034 A1 7/2008 Akiyama  
 2008/0167083 A1 7/2008 Wyld et al.  
 2008/0167796 A1\* 7/2008 Narayanaswami ..... 701/200  
 2008/0167811 A1 7/2008 Geelen  
 2008/0172173 A1 7/2008 Chang et al.  
 2008/0172361 A1 7/2008 Wong et al.  
 2008/0172374 A1 7/2008 Wolosin et al.  
 2008/0176545 A1 7/2008 Dicke  
 2008/0177793 A1 7/2008 Epstein et al.  
 2008/0178116 A1 7/2008 Kim  
 2008/0186162 A1 8/2008 Rajan et al.  
 2008/0189033 A1 8/2008 Geelen et al.  
 2008/0194273 A1 8/2008 Kansal et al.  
 2008/0200142 A1 8/2008 Abdel-Kader et al.  
 2008/0207167 A1 8/2008 Bugenhagen  
 2008/0225779 A1 9/2008 Bragiel et al.  
 2008/0227473 A1 9/2008 Haney  
 2008/0242312 A1\* 10/2008 Paulson et al. .... 455/456.1  
 2008/0248815 A1 10/2008 Busch  
 2008/0249667 A1 10/2008 Horvitz et al.  
 2008/0268876 A1 10/2008 Gelfand et al.  
 2008/0271072 A1 10/2008 Rothschild et al.  
 2008/0280600 A1\* 11/2008 Zhou ..... 455/415  
 2008/0284642 A1 11/2008 Seacat et al.  
 2008/0287124 A1 11/2008 Karabinis  
 2008/0288166 A1 11/2008 Onishi et al.  
 2008/0293397 A1 11/2008 Gajdos et al.  
 2008/0310850 A1 12/2008 Pederson et al.  
 2008/0318550 A1 12/2008 DeAtley  
 2008/0319644 A1 12/2008 Zehler  
 2008/0319652 A1 12/2008 Moshfeghi  
 2009/0003659 A1 1/2009 Forstall et al.  
 2009/0005005 A1 1/2009 Forstall et al.  
 2009/0005018 A1 1/2009 Forstall et al.  
 2009/0005021 A1 1/2009 Forstall et al.  
 2009/0005068 A1 1/2009 Forstall et al.  
 2009/0005070 A1 1/2009 Forstall et al.  
 2009/0005071 A1 1/2009 Forstall et al.  
 2009/0005076 A1 1/2009 Forstall et al.  
 2009/0005080 A1 1/2009 Forstall et al.  
 2009/0005082 A1 1/2009 Forstall et al.  
 2009/0005964 A1 1/2009 Forstall et al.  
 2009/0005965 A1 1/2009 Forstall et al.  
 2009/0005975 A1 1/2009 Forstall et al.  
 2009/0005978 A1 1/2009 Forstall et al.  
 2009/0005981 A1 1/2009 Forstall et al.  
 2009/0006336 A1 1/2009 Forstall et al.  
 2009/0030605 A1 1/2009 Breed  
 2009/0031006 A1 1/2009 Johnson  
 2009/0033540 A1 2/2009 Breed et al.  
 2009/0042585 A1 2/2009 Matsuda  
 2009/0089706 A1 4/2009 Furches et al.  
 2009/0098857 A1 4/2009 DeAtley  
 2009/0177385 A1 7/2009 Matas et al.  
 2009/0197612 A1 8/2009 Kiiiskinen  
 2009/0228961 A1 9/2009 Wald et al.  
 2009/0234743 A1 9/2009 Wald et al.  
 2009/0259573 A1 10/2009 Cheng et al.  
 2009/0271271 A1 10/2009 Johnson  
 2009/0281724 A1 11/2009 Blumenberg et al.  
 2009/0286549 A1 11/2009 Sazegari et al.  
 2010/0076818 A1 3/2010 Peterson et al.  
 2010/0082820 A1 4/2010 Furukawa  
 2010/0106397 A1 4/2010 Van Essen

2010/0120450 A1 5/2010 Herz  
 2010/0128935 A1 5/2010 Filley et al.  
 2010/0131584 A1 5/2010 Johnson  
 2010/0173647 A1 7/2010 Sheynblat  
 2010/0207782 A1 8/2010 Johnson  
 2010/0285817 A1 11/2010 Zhao et al.  
 2011/0051658 A1 3/2011 Jin et al.  
 2011/0159887 A1\* 6/2011 Lohtia et al. .... 455/456.1

FOREIGN PATENT DOCUMENTS

CA 2287596 4/2000  
 CA 2432239 12/2004  
 CN 1 412 573 4/2003  
 DE 3 621 456 1/1988  
 DE 4437360 4/1996  
 DE 19506890 8/1996  
 DE 19914257 3/1999  
 DE 10 141 695 3/2003  
 EP 0 288 068 7/1992  
 EP 0 633 452 1/1995  
 EP 0 745 867 12/1996  
 EP 0 762 362 3/1997  
 EP 0 763 749 3/1997  
 EP 0 786 646 7/1997  
 EP 785535 7/1997  
 EP 0 809 117 11/1997  
 EP 0 813 072 12/1997  
 EP 0 699 330 4/1998  
 EP 0 908 835 4/1999  
 EP 0 997 808 5/2000  
 EP 1 083 764 3/2001  
 EP 1 251 362 10/2002  
 EP 1 300 652 4/2003  
 EP 1 457 928 9/2004  
 EP 1 469 287 10/2004  
 EP 1 496 338 1/2005  
 EP 1 770 956 9/2005  
 EP 1 465 041 2/2006  
 EP 1 659 817 5/2006  
 EP 1 672 474 6/2006  
 EP 1 790 947 5/2007  
 EP 1 860 904 11/2007  
 EP 1 944 701 7/2008  
 EP 1 933 249 8/2008  
 EP 1 975 567 10/2008  
 FR 2730083 8/1996  
 FR 2754093 4/1998  
 FR 2272911 6/1999  
 FR 2810183 12/2001  
 GB 2 278 196 11/1994  
 GB 2 322 248 8/1998  
 GB 2 359 888 5/2001  
 GB 2 407 230 4/2005  
 JP 62142215 6/1987  
 JP 05-071974 3/1993  
 JP 06-525189 5/1994  
 JP 2007-221433 5/1994  
 JP 08-069436 3/1996  
 JP 09-054895 2/1997  
 JP 09-098474 4/1997  
 JP 9-113288 5/1997  
 JP 09-153125 6/1997  
 JP 9-062993 7/1997  
 JP 09-200850 7/1997  
 JP 9-210710 8/1997  
 JP 9-319300 12/1997  
 JP 10-021259 1/1998  
 JP 11-234736 8/1999  
 JP 2000-163379 6/2000  
 JP 2001-008270 1/2001  
 JP 2001-160063 6/2001  
 JP 2002-310680 10/2002  
 JP 10-030933 2/2003  
 JP 2003-228532 8/2003  
 JP 2004-045054 2/2004  
 JP 2004-219146 8/2004  
 JP 2004-362271 12/2004  
 JP 2005-106741 4/2005

(56)

## References Cited

## FOREIGN PATENT DOCUMENTS

JP	2005-182146	7/2005
JP	2005-241519	9/2005
JP	2005/277764	10/2005
JP	2006-112338	4/2006
JP	2006-184007	7/2006
JP	2006-270889	10/2006
JP	2006-279838	10/2006
JP	2007-033220	2/2007
JP	2007-033331	2/2007
JP	2007-033368	2/2007
JP	2007-127439	5/2007
JP	2007-147439	6/2007
JP	2007-201699	8/2007
JP	2007-240400	9/2007
JP	2007-259291	10/2007
JP	2007-271299	10/2007
JP	2007-304009	11/2007
JP	2008-058917	3/2008
JP	2008-129774	6/2008
KR	2004-102440	12/2004
KR	2005-096746	10/2005
TW	200426387	12/2004
WO	WO 93/20546	10/1993
WO	WO 94/08250	4/1994
WO	WO 97/07467	2/1997
WO	WO 97/24577	7/1997
WO	WO 97/41654	11/1997
WO	WO 98/03951	1/1998
WO	WO 98/07112	2/1998
WO	WO 98/54682	12/1998
WO	WO 99/16036	4/1999
WO	WO 99/44183	9/1999
WO	WO 99/61934	12/1999
WO	WO 01/31966	5/2001
WO	WO 01/37597	5/2001
WO	WO 02/33533	4/2002
WO	WO 02/054813	7/2002
WO	WO 03/023593	3/2003
WO	WO 03/096055	11/2003
WO	WO 2004/008792	1/2004
WO	WO 2004/16032	2/2004
WO	WO 2004/021730	3/2004
WO	WO 2004/34194	4/2004
WO	WO 2004/061576	7/2004
WO	WO 2004/076977	9/2004
WO	WO 2005/006258	1/2005
WO	WO 2005/84052	9/2005
WO	WO 2006/065856	6/2006
WO	WO 2006/113125	10/2006
WO	WO 2007/27065	3/2007
WO	WO 2007/052285	5/2007
WO	WO 2008/051929	5/2008
WO	WO 2008/085740	7/2008
WO	WO 2009/02942	12/2008
WO	WO 2009/140031	11/2009

## OTHER PUBLICATIONS

"Error: could not find contact with this e-mail address". Outlookbanter.com. Dec. 2006.\*

Binzhao et al., "Mobile Phone GIS Based on Mobile SVG", IEEE 2005.

Nardi et al., "Integrating Communication and Information through Contact Map", Communications of the ACM, vol. 45, No. 4, Apr. 2002.

Balliet, "Transportation Information Distribution System", IBM Technical Disclosure Bulletin, [online] [Retrieved Nov. 7, 2008] Retrieved from the Internet, URL: <https://www.delphion.com/tlbs/tdb?order=86A+61395>; Jun. 1986; 2 pages.

Jain, R., Potential Networking Applications of Global Positioning Systems (GPS) [online] [retrieved on Nov. 18, 2008] [<http://arxiv.org/ftp/cs/papers/9809/9809079.pdf>] OSU Technical Report TR-24, Apr. 1996, pp. 1-40.

International Search Report and Written Opinion, dated Jun. 9, 2008, issued in International Application No. PCT/US2007/088880, filed Dec. 27, 2007.

Spohrer. "New Paradigms for Using Computers", 1997; retrieved from the Internet, URL: <http://almaden.ibm.com/npuc97/1997/spohrer.htm>.

Yang et al. "Global Snapshots for Distributed Debugging", IEEE, pp. 436-440, 1992.

"Cyberguide: a mobile context-aware tour guide", Wireless Networks Archive (Special Issue: Mobile computing and networking; selecting papers from MobiCom '96), 3(5):421-433, 1997.

"Frontiers in electronic media", Interactions Archive 4(4):32-64, 1997.

"Location-aware mobile applications based on directory services", International Conference on Mobile Computing and Networking Archive, Proceedings on the 3rd Annual ACM/IEEE International Conference on Mobile Computing and Networking, Budapest, Hungary, pp. 23-33, 1997.

Sharpe et al., U.S. Appl. No. 12/434,586, filed May 1, 2009.

Sharp et al., U.S. Appl. No. 12/434,582, filed May 1, 2009.

Van Os et al., U.S. Appl. No. 12/165,413, filed Jun. 30, 2008.

Blumenberg et al., U.S. Appl. No. 12/119,316, filed May 12, 2008.

Low et al., U.S. Appl. No. 12/233,358, filed Sep. 18, 2008.

Sazegari et al., U.S. Appl. No. 12/122,339, filed May 16, 2008.

Johnson, U.S. Appl. No. 12/044,363, filed Mar. 7, 2008.

Johnson, U.S. Appl. No. 11/827,065, filed Jul. 10, 2007.

Herz, U.S. Appl. No. 12/270,814, filed Nov. 13, 2008.

Drane et al., "The accurate location of mobile telephones", Third Annual World Congress on Intelligent Transport Systems, Orlando, Florida, Oct. 1996.

"Travel Time Data Collection Handbook—Chapter 5: Its Probe Vehicle Techniques", FHWA-PL-98-035 Report, Department of Transport, University of Texas, Mar. 1998; [online] [Retrieved from the Internet at <http://www.fhwa.dot.gov/ohim/handbook/chap5.pdf>.

Ygnace et al., "Travel Time Estimation on the San Francisco Bay Area Network Using Cellular Phones as Probes", Working Paper, Institute of Transportation Studies, University of California, Berkeley, 2000.

Wang et al., "A Unified Vehicle Supervising and Traffic Information System", IEEE, 1996, pp. 968-972.

U.S. Appl. No. 12135073, Johnson, filed Mar. 27, 2008.

"New program for mobile blogging for Pocket PC released: MY BLOG," [online] [Retrieved on Apr. 5, 2006]; Retrieved from the Internet URL: <http://msmobiles.com/news.php/4067.html>; 1 page.

"Numbering and Dialing Plan Within the United States," *Alliance for Telecommunications Industry Solutions*, 2005, 17 pages.

Dalrymple, "Google Maps adds locator, but not for iPhone," [online] [Retrieved Nov. 30, 2007]; Retrieved from the Internet URL: [http://news.yahoo.com/s/macworld/20071130/tc\\_macworld/googlemaps20071130\\_0&printer=1;\\_ylt=Auvf3s6LQK\\_p0aJlb954T\\_DQn6gB](http://news.yahoo.com/s/macworld/20071130/tc_macworld/googlemaps20071130_0&printer=1;_ylt=Auvf3s6LQK_p0aJlb954T_DQn6gB); 1 page.

Maxwell et al., "Alfred: The Robot Waiter Who Remembers You," *AAAI Technical Report WS-99-15*, 1999, 12 pages.

Shibata et al., "Development and Integration of Generic Components for a Teachable Vision-Based Mobile Robot," *IEEE/ASME Transactions on Mechatronics*, 1996, 1(3):230-236.

Wu et al., "A Multimedia System for Route Sharing and Video-Based Navigation," *IEEE*, 2006, pp. 73-76.

Yogesh C. Rathod, Third Party Submission in U.S. Appl. No. 12/233,358 mailed Mar. 30, 2010, 12 pages.

Feddema et al., "Cooperative Sentry Vehicles and Differential GPS Leapfrog," 2000, United States Department of Energy, pp. 1-12.

U.S. Appl. No. 11/464,671, Johnson, filed Aug. 15, 2006

U.S. Appl. No. 11/827,065, Johnson, filed Jul. 10, 2007.

U.S. Appl. No. 11/972,559, Alten, filed Jan. 10, 2008.

U.S. Appl. No. 12/044,363, Johnson, filed Mar. 7, 2008.

U.S. Appl. No. 11/114,714, Williamson et al., filed May 2, 2008

U.S. Appl. No. 12/119,316, Blumenberg et al., filed May 12, 2008.

U.S. Appl. No. 12/122,339, Sazegari et al., filed May 16, 2008.

U.S. Appl. No. 12/233,358, Low et al., filed Nov. 13, 2008.

U.S. Appl. No. 12/270,814, Herz, filed Nov. 13, 2008.



(56)

## References Cited

## OTHER PUBLICATIONS

- “27 Countries in your pocket”; [online] [Retrieved on Sep. 29, 2005] Retrieved from the Internet <URL <http://www.mio-tech.be/en/printview/press-releases-2005-09-29.htm>; 1 page.
- “Animated Transition”; [online] [Retrieved on Oct. 16, 2006] Retrieved from the Internet <URL: [http://designinterfaces.com/Animated\\_Transition](http://designinterfaces.com/Animated_Transition); 2 pages.
- “DaimlerCrysler Guide5 Usecases Overview Map”, 1 page (no reference date).
- “International Roaming Guide—Personal Experience(s) from Customer and Community Member”; [online] [Retrieved Jun. 26, 2006] Retrieved from the Internet <URL: <http://forums.cingular.com/cng/board/message?board.id=1185>; 6 pages.
- “Mio 269+ Users Manula”; 2005; 44 pages.
- Review Guide—Google Maps for mobile (beta); Google; 2006; 7 pages.
- “User-centered design of mobile solutions”, NAMAHN, 2006, 18 pages.
- “User’s Manual MioMap 2.0”; Aug. 2005; 60 pages.
- “Windows Live Search for Mobile Goes Final, Still Great”; [online] [Retrieved on Mar. 11, 2007]; Retrieved from the Internet, URL: <http://gizmodo.com/gadgets/software/windows-live-search-for-mobile-goes-final-still-great-236002.php>; 3 pages.
- “Windows Mobile 6 Professional Video Tour”; [online] [Retrieved on Mar. 11, 2007]; Retrieved from the Internet, URL: <http://gizmodo.com/gadgets/cellphones/windows-mobile-6-professional-video-tour-237039.php>; 4 pages.
- “Windows Mobile”; Microsoft; 2007, 2 pages.
- Anand et al., “Quantitative Analysis of Power Consumption for Location-Aware Applications on Smart Phones”, IEEE International Symposium on Industrial Electronics, 2007.
- Beard et al., “Estimating Positions and Paths of Moving Objects”, IEEE 2000, pp. 1-8.
- Bederson, B.B., Audio Augmented Reality: A Prototype Automated Tour Guide [online] [retrieved on Aug. 30, 2002] [<http://www.cs.umd.edu/~bederson/papers/chi-95-aar/>] pp. 1-4.
- Berman et al., “The Role of Dead Reckoning and Inertial Sensors in Future General Aviation Navigation”, IEEE, 1998, pp. 510-517.
- Bevly et al., “Cascaded Kalman Filters for Accurate Estimation of Multiple Biases, Dead-Reckoning Navigation, and Full State Feedback Control of Ground Vehicles”, IEEE Transactions on Control Systems in Technology, vol. 15, No. 2, Mar. 2007, pp. 199-208.
- Bokharouss et al., “A Location-Aware Mobile Call Handling Assistant”, International Conference on Advanced Information Networking and Applications Workshops, 2007.
- Boonsrimuang et al., “Mobile Internet Navigation System”, IEEE, 2002, pp. 325-328.
- Camp et al., “A computer-based method for predicting transit time systems”, Decision Sciences, vol. 5, pp. 339-346, 1974.
- Carew; “Phones that tell you where to drive, meet, eat”; [online] [Retrieved May 26, 2007]; Retrieved from the Internet <URL [http://news.yahoo.com/s/nm/20070525/wr\\_nm/column\\_pluggedin\\_dc\\_2&printer=1;\\_ylt=Ahqafn7x\\_m1S2rOFZFeu9G4ht.cA](http://news.yahoo.com/s/nm/20070525/wr_nm/column_pluggedin_dc_2&printer=1;_ylt=Ahqafn7x_m1S2rOFZFeu9G4ht.cA); 2 pages.
- Cho et al., A Traveler Information Service Structure in Hybrid T-DMB and Cellular Communication Network, Broadcast Systems Research Group, IEEE, 2006, pp. 747-750.
- Christie et al., “Development and Deployment of GPS wireless devices for E911 and Location based services”, IEEE 2002.
- Chua et al., “Intelligent Portal for Event-triggered SMS Alerts”, 2nd International Conference on Mobile Technology, Applications and Systems, 2005.
- Civilis et al., “Efficient Tracking of Moving Objects with Precision Guarantees”, IEEE, Proceedings of the First Annual International Conference on Mobile and Ubiquitous Systems: Networking and Services, 2004, 10 pages.
- Dibdin, Peter, “Where are mobile location based services?”, Dec. 14, 2001, pp. 1-8.
- Dunn et al., “Wireless Emergency Call System”, IBM TDB, Sep. 1994.
- Ebine, “Dual Frequency resonant base station antennas for PDC systems in Japan”, IEEE, pp. 564-567, 1999.
- Evans, “In-Vehicle Man-Machine Interaction the Socrates Approach”, Vehicle Navigation & Information System Conference Proceedings, 1994, Aug.,31,—Sep. 2, 1994, pp. 473-477.
- FM 3-25.26 Map Reading and Land Navigation Field Manual No. 3-25.26, Headquarters Department of the Army, Washington, DC [online] [retrieved on Apr. 9, 2004] [retrieved from <http://155.217.58.58/cgi-bin/atdl.d11/fm/3-25.26/toc.htm>] 20 Jul. 2001, pp. 1-7 and J-1 to J-3.
- GPS 12 *Personal Navigator Owner’s Manual & Reference*, Garmin Corporation, Jan. 1999, pp. 1-60.
- Guo et al., “An Intelligent Query System based on Chinese Short Message Service for Restaurant Recommendation”, IEEE 2007, 1 page.
- Hameed et al., “An Intelligent Agent-Based Medication and Emergency System”, IEEE 2006.
- Helal et al., “Drishti: An Integrated Navigation System for Visually Impaired and Disabled”, Fifth International Symposium on Wearable Computers (ISWC’01), IEEE, 2001, pp. 149-156.
- Hohman et al., “GPS Roadside Integrated Precision Positioning System”, Position Location and Navigation Symposium (IEEE 2000), pp. 221-230.
- International Numbering and SMS—Type of Numbering, TON, Numbering Plan Indicator, NPI, [online] [Retrieved Jan. 5, 2007] Retrieved from the Internet <URL: <http://www.activeexperts.com/support/activsms/tonnpi/>.
- Jirawimut et al., “A Method for Dead Reckoning Parameter Correction in Pedestrian Navigation System”, IEEE Transactions on Instrumentation and Measurement, vol. 52, No. 1, Feb. 2003, pp. 209-215.
- Ju et al., “RFID Data Collection and Integration based on Mobile Agent”, IEEE, 2006.
- Kbar et al., “Mobile Station Location based on Hybrid of Signal Strength and Time of Arrival”, IEEE, 2005.
- Koide et al., “3-D Human Navigation System with Consideration of Neighboring Space Information”, IEEE International Conference on Systems, Man and Cybernetics, 2006 (SMC ’06), vol. 2, (Oct. 8-11, 2006), pp. 1693-1698.
- Lloyd et al., “Cellular phone base stations installation violate the Electromagnetic Compatibility regulations”, IEEE, 2004.
- Manabe et al., “On the M-CubITS Pedestrian Navigation System”, IEEE, 2006, pp. 793-798.
- Meier et al., “Location-Aware Event-Base Middleware: A Paradigm for Collaborative Mobile Applications?”, Sep. 2003.
- Miller et al., “Synchronization of Mobile XML Databases by Utilizing Deferred Views”, IEEE 2004.
- Northard, “Docking Station Communication Link”, IBM TDB, Feb. 1994.
- Oh et al., “Spatial Applications Using 4S Technology for Mobile Environment”, IEEE 2002.
- Paksoy et al., “The Global Position System-Navigation Tool of the Future”, Journal of Electrical & Electronics, 2002, vol. 2, No. 1, pp. 467-476.
- Parikh, “Tele Locate”, IBM Technical Disclosure Bulletin, [online] [Retrieved Nov. 7, 2008] Retrieved from the Internet, URL: <https://www.delphion.com/tddb/tdb?order=92A+62775>; Sep. 1992; 1 page.
- Partial International Search Report, dated Jul. 29, 2008, issued in corresponding PCT/US2008/050295.
- Pfoser et al., “Dynamic Travel Time Maps—Enabling Efficient Navigation”, Proceedings of the 18th International Conference on Scientific and Statistical Database Management (SSDBM’06), IEEE, 10 pages.
- Portfolio 2007; [online] [Retrieved on Jun. 14, 2007]; Retrieved from the Internet, URL: <http://eric.wahlforss.com/folio>; 3 pages.
- RD 409052, Research Disclosure Alerting Abstract, “Location dependent information for satellite based vehicle communication—required application of Global Position System (GPS) to automatically extract relevant portions of data package as vehicle changes position,” May 10, 1998, 1 page.
- Rekimoto, J., *Augment-able Reality: Situated Communication through Physical and Digital Spaces*, iswc, pp. 68, Second International Symposium on Wearable computers (ISWC’98), 1998, pp. 1-8.

(56)

## References Cited

## OTHER PUBLICATIONS

- Rogers et al., "Adaptive User Interfaces for Automotive Environments", IEEE Intelligent Vehicles Symposium 2000, Oct. 3-5, 2000, pp. 662-667.
- Rozier, J., *Hear & There: An Augmented Reality System of Linked Audio*, Proceedings of the International Conference on Auditory Display, Atlanta, GA, Apr. 2000, pp. 1-6.
- Samadani et al., "PathMaker: Systems for Capturing Trips", IEEE (2004) International Conference on Multimedia and Expo., Publication Date: Jun. 27-30, 2004, vol. 3, pp. 2123-2126, 2004.
- Schreiner, "Where We At? Mobile Phones Bring GPS to the Masses", IEEE Computers Society, May/Jun. 2007, pp. 6-11.
- Sung et al., "Towards Reliable Peer-to-Peer Data Sharing over Mobile Ad hoc Networks", IEEE, 2005.
- Weib et al., "Zone services—an approach for location-based data collection", Proceedings of the 8th International Conference on E-commerce Technology and the 3rd IEEE International Conference on Enterprise Computing, E-Commerce and E-Services.
- Yang et al., "A Multimedia System for Route Sharing and Video-based Navigation", IEEE, 2006, pp. 73-76.
- Yanyan et al., "The model of optimum route selection in vehicle automatic navigation system based on unblocked reliability analyses", IEEE 2003.
- Weiss et al., "Zone services—an approach for location-based data collection", Proceedings of the 8th International Conference on E-commerce Technology and the 3rd IEEE International Conference on Enterprise Computing, E-Commerce and E-Services, 2006; 8 pages.
- Charny, "AT&T puts 411 to the text"; [online] [Retrieved Mar. 4, 2009]; Retrieved from the Internet <URL [http://news.cnet.com/ATT-puts-411-to-the-text/2100-1039\\_3-1000669.html](http://news.cnet.com/ATT-puts-411-to-the-text/2100-1039_3-1000669.html); May 8, 2003; 2 pages.
- Budka et al., "A Bayesian method to Improve Mobile Geolocation Accuracy", IEEE, 2002, pp. 1021-1025.
- Yamamoto et al., "Position Location Technologies Using Signal Strength in Cellular Systems", IEEE, 2001, pp. 2570-2575.
- International Search Report and Written Opinion, dated Oct. 1, 2009, issued in PCT/US2009/041298.
- Dey, "Context-Aware Computing: The CyberDesk Project," [online] Retrieved from the Internet: URL: <http://www.cc.gatech.edu/fce/cyberdesk/pubs/AAAI98/AAAI98.html>; AAAI '98 Spring Symposium, Stanford University, Mar. 23-25, 1998, downloaded from the Internet on Aug. 6, 2010, 8 pages.
- Challe, "CARMINAT-An Integrated information and guidance system," Vehicle Navigation and Information Systems Conference, Oct. 20-23, 1991, Renault—Direction de la Recherche, Rueil-Malmaison, France.
- Pungel, "Traffic control-beat the jam electronically," *Funkschau*, 1988, 18:43-45 (w/English translation).
- Rillings and Betsold, "Advanced driver information systems," *Vehicular Technology*, IEEE Vehicular Technology Society, 1991, 40:31-40.
- Tsuzawa and Okamoto, "Advanced Mobile Traffic Information and Communication System," First Vehicle Navigation and Information Systems Conference, Sep. 11-13, 1989, Toronto, Canada, Abstract only.
- Wong, "GPS: making roads safer and solving traffic tangles," *Asia Engineer*, 1995, 23(9):31-32.
- "Sprite Terminator User Guide," [online] Dec. 6, 2007 (Dec. 6, 2007), pp. 1-45, Retrieved from the Internet: URL: <http://www.spritesoftware.com/getmedia/4d2lad24-fd62-4c5e-a4fe-15ebc99aac9a/SpriteTerminator.aspx> [retrieved on Jul. 9, 2010].
- Ayatsuka et al., "UbiquitousLinks: Hypermedia Links Embedded in the Real World, Technical Report of Information Processing Society, 96-HI-67," Information Processing Society of Japan, Jul. 11, 1996, 96(62):23-30.
- Nagao et al., *Walk Navi: A Location-Aware Interactive Navigation/Guideline System and Software III*, First edition, pp. 9-48, published by Kindai-Kagaku-Sya Co. Ltd., Dec. 10, 1995.
- Benefon ESC! GSM+GPS Personal Navigation Phone, benefon.com, Copyright 2001, 4 pages.
- Freundschuh, "Does 'Anybody' Really Want (or Need) Vehicle Navigation Aids?" First Vehicle Navigation and Information System Conference, Sep. 11-13, 1989, Toronto, Canada, 5 pages.
- Gould, "The Provision of Usable Navigation Assistance: Considering Individual Cognitive Ability," First Vehicle Navigation and Information System Conference, Sep. 11-13, 1989, Toronto, Canada, 7 pages.
- Mark, "A Conceptual Model for Vehicle Navigation Systems," First Vehicle Navigation and Information System Conference, Sep. 11-13, 1989, Toronto, Canada, 11 pages.
- Wheeler et al., "Development of Human Factors Guidelines for Advanced Traveler Information Systems and Commercial Vehicle Operations: Task Analysis of ATIS/CVO Functions," US Dept. Transportation Federal Highway Administration Research and Development, Publication No. FHWA-RD-95-176, Nov. 1996, 124 pages.
- Miller et al., "Integrating Hierarchical Navigation and Querying: A User Customizable Solution," ACM Multimedia Workshop on Effective Abstractions in Multimedia Layout, Presentation, and Interaction, San Francisco, CA, Nov. 1995, 8 pages.
- Hoogenraad, "Location Dependent Services," 3rd AGILE Conference on Geographic Information Science, Helsinki/Espoo, Finland, May 25-27, 2000, pp. 74-77.
- Bonsignore, "A Comparative Evaluation of the Benefits of Advanced Traveler Information System (ATIS) Operational Tests," MIT Masters Thesis, Feb. 1994, 140 pages.
- Noonan and Shearer, "Intelligent Transportation Systems Field Operational Test Cross-Cutting Study Advance Traveler Information systems," Intelligent Transportation Systems Field Operational Test Cross-Cutting Study, Sep. 1998, 26 pages.
- Burnett, "Usable Vehicle Navigation Systems: Are We There Yet?" *Vehicle Electronic Systems* 2000, Jun. 29-30, 2000, 3.1.1-3.1.12.
- Khattak et al., "Bay Area ATIS Testbed Plan," Research Reports, California Partners for Advanced Transit and Highways (PATH), Institute of Transportation Studies, UC Berkeley, Jan. 1, 1992, 83 pages.
- Yim et al., "Travinfo Field Operational Test: Work Plan for the Target, Network, and Value Added Reseller (VAR) Customer Studies," Working Papers, California Partners for Advanced Transit and Highways (PATH), Institute of Transportation Studies, UC Berkeley, Apr. 1, 1997, 49 pages.
- Mahmassani et al., "Providing Advanced and Real-Time Travel/Traffic Information to Tourists," Center for Transportation Research, Bureau of Engineering Research, the University of Texas at Austin, Oct. 1998, 15 pages.
- "New Handsets Strut Their Stuff At Wireless '99," Internet: URL: [http://findarticles.com/p/articles/mi\\_m0BMD/is\\_1999\\_Feb\\_11/ai\\_n27547656/](http://findarticles.com/p/articles/mi_m0BMD/is_1999_Feb_11/ai_n27547656/) downloaded from Internet on Feb. 11, 1999, 3 pages.
- "School Buses to Carry Noticom's First Application," Internet: URL: [http://findarticles.com/p/articles/mi\\_m0BMD/is\\_1999\\_Feb\\_17/ai\\_n27547754/](http://findarticles.com/p/articles/mi_m0BMD/is_1999_Feb_17/ai_n27547754/) downloaded from the Internet on Feb. 17, 1999, 2 pages.
- Green et al., "Suggested Human Factors Design Guidelines for Driver Information Systems," Technical Report UMTRI-93-21, Nov. 1993, 119 pages.
- Tijerina et al., "Driver Workload Assessment of Route Guidance System Destination Entry While Driving: A Test Track Study," Proceedings of the 5th ITS World Congress, Oct. 12-16, 1998, Seoul, Korea, 9 pages.
- Muraskin, "Two-Minute Warnings for School Bus Riders," Internet: URL: <http://www.callcentermagazine.com/shared/printableArticle.jhtml;jsessionid=PQH1SZXW...> Jul. 1, 1999, 3 pages.
- Ni and Deakin, "On-Board Advanced Traveler Information Systems," Dec. 1, 2002, 10 pages.
- Serafin et al., "Functions and Features of Future Driver Information Systems," Technical Report UMTRI-91-16, May 1991, 104 pages.
- Shekhar and Liu, "Genesis and Advanced Traveler Information Systems (ATIS): Killer Applications for Mobile Computing?" NSF Mobidata Workshop on Mobile and Wireless Information Systems, Nov. 1994, 20 pages.

(56)

## References Cited

## OTHER PUBLICATIONS

- "LaBarge in joint venture on bus system," Internet: URL: <http://www.bizjournals.com/stlouis/stories/1998/08/10/focus2.html?t=printable>, Aug. 7, 1998, 1 page.
- Clarke et al., "Development of Human Factors Guidelines for Advanced Traveler Information Systems (ATIS) and Commercial Vehicle Operations (CVO): Comparable Systems Analysis," U.S. Department of Transportation Federal Highway Administration, Publication No. FHWA-RD-95-197, Dec. 1996, 212 pages.
- Zubac and Strahonja, "Theory and Development of an Online Navigation System," 18th International Conference on Information and Intelligent Systems, University of Zagreb, Sep. 12-14, 2007.
- Brown, "The stick-e document: a framework for creating context-aware applications," *Electronic Publishing*, 1995, 8:259-272.
- Brown, "Triggering Information by Context," *Personal Technologies*, 1998, 2:18-27.
- Dey et al., "CyberDesk: a framework for providing self-integrating context-aware services," *Knowledge-Based Systems*, 1998, 11:3-13.
- Hodes and Katz, "Composable ad hoc location-based services for heterogeneous mobile clients," *Wireless Networks*, 1999, 5:411-427.
- Kreller et al., "A Mobile-Aware City Guide Application," ACTS Mobile Communication Summit, 1998, Rhodes, Greece, 7 pages.
- Lusky et al., "Mapping the Present," *ColoradoBiz*, Nov. 1999, 26(11):16-17.
- McCarthy and Meidel, "ACTIVEMAP: A Visualization Tool for Location Awareness to Support Informal Interactions," HUC '99, LNCS 1707, 1999, pp. 158-170.
- O'Grady et al., "A Tourist-Centric Mechanism for Interacting with the Environment," *Proceedings of the First International Workshop on Managing Interactions in Smart Environments (MANSE '99)*, Dublin, Ireland, Dec. 1999, pp. 56-67.
- Pascoe et al., "Developing Personal Technology for the Field," *Personal Technologies*, 1998, 2:28-36.
- Tarumi et al., "Public Applications of SpaceTag and Their Impacts," *Digital Cities*, LNCS 1765, 2000, pp. 350-363.
- Tebbutt, "Dial your way out of the woods," *The Australian*, Feb. 2000, 1 page.
- Tso et al., "Always on, Always Connected Mobile Computing," *Mobile Communications Operation—Mobile Handheld Products Group*, 1996, pp. 918-924.
- Wang and Lin, "Location Aware Information Agent over WAP," *Tamkang Journal of Science and Engineering*, 2000, 3(2):107-115.
- "3rd Generation Partnership Project (3GPP); Technical Specification Group (TSP) RAN; Working Group 2 (WG2); Report on Location Services (LCS)," 3G TR 25.923 v.1.0.0, Apr. 1999, 45 pages.
- "Report on Location Service feature (LCS) 25.923 v1.0.0," TSG-RAN Working Group 2 (Radio layer 2 and Radio layer 3), Berlin, May 25-28, 1999, 45 pages.
- "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Functional stage 2 description of location services in UMTS," 3G TS 23.171 v.1.1.0, Nov. 1999, 42 pages.
- "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Stage 2 Functional Specification of Location Services in UTRAN," 3G TS 25.305 v.3.1.0, Mar. 2000, 45 pages.
- "Enabling UMTS/Third Generation Services and Applications," No. 11 Report from the UMTS Forum, Oct. 2000, 72 pages.
- "3rd Generation Partnership Project (3GPP); Technical Specification Group (TSG) RAN; Working Group 2 (WG2); Report on Location Services," TS RAN R2.03 V0.1.0, Apr. 1999, 43 pages.
- "Revised CR to Sep. 31 on work item LCS," ETSI SMG3 Plenary Meeting #6, Nice, France, Dec. 13-15, 1999, 18 pages.
- Digital cellular telecommunications system (Phase 2+); Location Services (LCS); Service description, Stage 1 (GSM 02.71) ETSI, Apr. 1999, 22 pages.
- Akerblom, "Tracking Mobile Phones in Urban Areas," Goteborg University Thesis, Sep. 2000, 67 pages.
- Borsodi, "Super Resolution of Discrete Arrivals in a Cellular Geolocation System," University of Calgary Thesis, Apr. 2000, 164 pages.
- Abowd et al., "Context-awareness in wearable and ubiquitous computing," 1st International Symposium on Wearable Computers, Oct. 13-14, 1997, Cambridge, MA, 9 pages.
- Balsiger et al., "MOGID: Mobile Geo-depended Information on Demand," *Workshop on Position Dependent Information Services (W3C-WAP)*, 2000, 8 pages.
- Cheverst et al., "Architectural Ideas for the Support of Adaptive Context-Aware Applications," *Proceedings of Workshop on Infrastructure for Smart Devices—How to Make Ubiquity an Actuality*, HUC'00, Bristol, Sep. 2000, 3 pages.
- Cheverst et al., "The Role of Connectivity in Supporting Context-Sensitive Applications," HUC'99, LNCS 1707, 1999, pp. 193-209.
- Efstratiou and Cheverst, "Reflection: A Solution for Highly Adaptive Mobile Systems," 2000 Workshop on Reflective Middleware, 2000, 2 pages.
- Cheverst et al., "The Support of Mobile-Awareness in Collaborative Groupware," *Personal Technologies*, 1999, 3:33-42.
- Cheverst et al., "Design of an Object Model for a Context Sensitive Tourist Guide," *Computers and Graphics*, 1999, 23(6):883-891.
- Cheverst et al., "Developing Interfaces for Collaborative Mobile Systems," 1999, 15 pages.
- Cheverst et al., "Experiences of Developing and Deploying a Context-Aware Tourist Guide: The GUIDE Project," 2000, pp. 20-31.
- Cheverst et al., "Exploiting Context to Support Social Awareness and Social Navigation," *SIGGROUP Bulletin* Dec. 2000, 21(3):43-48.
- Cheverst et al., "Services to Support Consistency in Mobile Collaborative Applications," *Proc. 3rd International Workshop on Services in Distributed Networked Environments*, 1996, 8 pages.
- Cheverst et al., "Sharing (Location) Context to Facilitate Collaboration Between City Visitors," 2000, 8 pages.
- Cheverst et al., "Supporting Collaboration in Mobile-aware Groupware," *Workshop on Handheld CSCW*, 1998, 6 pages.
- Change Request for "U.S. specific Emergency Services requirements included as an informative annex," Nov. 29, 1999, 2 pages.
- Costa et al., "Experiments with Reflective Middleware," *Proceedings of the ECOOP'98 Workshop on Reflective Object-Oriented Programming and Systems*, ECOOP'98 Workshop Reader, 1998, 13 pages.
- Davies et al., "L2imbo: A distributed systems platform for mobile computing," *Mobile Networks and Applications*, 1998, 3:143-156.
- Davies et al., "'Caches in the Air': Disseminating Tourist Information in the Guide System," *Second IEEE Workshop on Mobile Computer Systems and Applications*, Feb. 25-26, 1999, 9 pages.
- Dix et al., "Exploiting Space and Location as a Design Framework for Interactive Mobile Systems," *ACM Transactions on Computer-Human Interaction (TOCHI)—Special issue on human-computer interaction with mobile systems*, 2000, 7(3):285-321.
- Drane et al., "Positioning GSM Telephones," *IEEE Communications Magazine*, Apr. 1998, pp. 46-59.
- Drane and Rizos, "Role of Positioning Systems in ITS," *Positioning Systems in Intelligent Transportation Systems*, Dec. 1997, pp. 312, 346-349.
- Efstratiou et al., "Architectural Requirements for the Effective Support of Adaptive Mobile Applications," 2000, 12 pages.
- "Estonian operator to launch world's first Network-based location services," *Ericsson Press Release*, Oct. 11, 1999, 2 pages.
- Fischer et al., "System Performance Evaluation of Mobile Positioning Methods," *IEEE*, Aug. 2002, pp. 1962-1966.
- Flinn and Satyanarayanan, "PowerScope: A Tool for Profiling the Energy Usage of Mobile Applications," *Proc. WMCSA '99 Second IEEE Workshop on Mobile Computing Systems and Applications*, Feb. 25-26, 1999, 9 pages.
- French and Driscoll, "Location Technologies for ITS Emergency Notification and E911," *Proc. 1996 National Technical Meeting of the Institute of Navigation*, Jan. 22-24, 1996, pp. 355-359.
- Friday et al., "Developing Adaptive Applications: The MOST Experience," *J. Integrated Computer-Aided Engineering*, 1999, pp. 143-157.
- Gunnarsson et al., "Location Trial System for Mobile Phones," *IEEE*, 1998, pp. 2211-2216.
- Jose and Davies, "Scalable and Flexible Location-Based Services for Ubiquitous Information Access," HUC'99, LNCS 1707, 1999, pp. 52-66.

(56)

**References Cited**

## OTHER PUBLICATIONS

Klinec and Nolz, "Nexus-Positioning and Communication Environment for Spatially Aware Applications," IAPRS, Amsterdam, 2000, 7 pages.

Kovacs et al., "Adaptive Mobile Access to Context-aware Services," Proc. ASAMA '99 Proc. First International Symposium on Agent Systems and Applications Third International Symposium on Mobile Agents, IEEE Computer Society Washington, DC, 1999, 12 pages.

Kreller et al., "UMTS: A Middleware Architecture and Mobile API/Approach," IEEE Personal Communications, Apr. 1998, pp. 32-38.

Kugler and Lechner, "Combined Use of GPS and LORAN-C in Integrated Navigation Systems," Fifth International Conference on Satellite Systems for Mobile Communications and Navigation, London, UK, May 13-15, 1996, pp. 199-207.

Kyriazakos et al., "Optimization of the Handover Algorithm based on the Position of the Mobile Terminals," Communications and Vehicular Technology, Oct. 2000, pp. 155-159.

Leonhardt and Magee, "Multi-Sensor Location Tracking," MOBICOM 98, Dallas, TX, pp. 203-214.

Leonhardt and Magee, "Towards a general location service for mobile environments," Proc. Third International Workshop on Ser-

vices in Distributed and Networked Environments, Jun. 3-4, 1996, 8 pages.

Long et al., "Rapid Prototyping of Mobile Context-Aware Applications: The Cyberguide Case Study," MobiCom '96, 1996, 11 pages.

Yokote, "The Apertos Reflective Operating System: The Concept and Its Implementation," OOPSLA'92, pp. 414-434.

Popescu-Zeletin et al., "Applying Location-Aware Computing for Electronic Commerce: Mobile Guide," Proc. 5th Conference on Computer Communications, AFRICOM-CCDC'98, Oct. 20-22, 1998, 14 pages.

Zhao, "Mobile Phone Location Determination and Its Impact on Intelligent Transportation Systems," IEEE Transactions on Intelligent Transportation Systems, Mar. 2000, 1(1):55-64.

Examiner E de la Rosa Rivera, European Search Report in EP 12 15 4027 mailed Apr. 10, 2012, 7 pages.

Examiner E de la Rosa Rivera, European Search Report in EP 12 15 4026 mailed Apr. 10, 2012, 5 pages.

Examiner E de la Rosa Rivera, European Search Report in EP 12 15 4025 mailed Apr. 12, 2012, 7 pages.

Examiner E de la Rosa Rivera, European Search Report in EP 12 15 4024 mailed Apr. 10, 2012, 6 pages.

US 6,731,928, 05/2004, Tanaka (withdrawn)

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4






FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG . 9




FIG. 10




FIG. 11




FIG. 12



## INTEGRATION OF MAP SERVICES WITH USER APPLICATIONS IN A MOBILE DEVICE

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority to U.S. Provisional Patent Application Ser. No. 60/946,915 filed Jun. 28, 2007, and entitled "Integration of User Applications in a Mobile Device," the contents of which are incorporated herein by reference.

### TECHNICAL FIELD

This invention generally relates to mobile devices.

### BACKGROUND

Conventional mobile devices are often dedicated to performing a specific application. For example, a mobile phone provides telephony services; a personal digital assistant (PDA) provides a way to organize address, contacts and notes; a media player plays content; email devices provide email communication, etc. Modern mobile devices can include two or more of these applications. Typically, the two or more applications operate independent of one another, and the device functions as a combination of two or more of the devices described above.

### SUMMARY

This invention relates to mobile devices. In general, in one aspect, the invention features a method including (optionally) receiving at a mobile device an email message from an email address and displaying a representation of the email message on a graphical user interface. An input is received from a user indicating a selection of the email address. Contact information corresponding to a set of contacts is searched for a contact having a contact email address matching the email address. Contact information for the contact includes a geographic location for the contact. A display of a map is provided to the user. The display includes a graphical representation indicating the geographic location for the contact having a contact email address matching the email address.

Implementations of the invention can include one or more of the following features. The mobile device can include a multi-touch-sensitive display, and receiving input from a user indicating a selection of the email address can be the user touching the email address on the multi-touch-sensitive display. A current location of the mobile device can be determined, and route information can be provided to the user corresponding to a route from the current location to the geographic location of the contact. The route information can include a graphical display of the route superimposed on the map; textual, directions for the route; and/or audio directions for the route. Providing route information can include providing the geographic location of the contact and the current location of the mobile device to a route service with a request for a route therebetween, and receiving the route information in response to the request. Providing a display of a map can include providing the geographic location of the contact to a map service, with a request for a map including the geographic location and receiving the map in response to the request.

In general, in another aspect, the invention features a method including activating a first user application on a mobile device, such that a user can make a request to a

directory service for a telephone number. In response to the request, a short message including the telephone number is received. A geographic location is determined associated with the telephone number. A display is provided on a graphical user interface of a map including a graphical representation indicating the geographic location.

Implementations can include one or more of the following features. In one example, the first user application is a telephony application and the user request is a telephone call. In another example, the first user application is a short messaging service application and the user request is a short message. The short message received in response to the request can include the geographic location and determining a geographic location can include obtaining the geographic location from the short message. In another example, determining a geographic location associated with the telephone number includes sending a request to a service for providing a geographic location associated with a telephone number, and receiving the geographic location in response to the request.

A current location of the mobile device can be determined, and route information can be provided to the user corresponding to a route from the current location to the geographic location associated with the telephone number. The route information can include a graphical display of the route superimposed on the map; textual directions for the route and/or audio directions for the route. Providing route information can include providing the geographic location of the contact and the current location of the mobile device to a route service with a request for a route therebetween, and receiving the route information in response to the request. Providing a display of a map can include providing the geographic location of the contact to a map service with a request for a map including the geographic location, and receiving the map in response to the request.

In general, in another aspect, the invention features a system including an email application operable to receive an email message from an email address and a data structure including contact information for a set of contacts. The system further includes a processor configurable for receiving user input selecting the email address and, in response to the user input, searching the data structure for a contact having a contact email address matching the email address. The contact has an associated geographic location. The system further includes a map application and a display. The map application is operable to provide a display of a map. The map includes a graphical representation of the geographic location associated with the contact. The display is operable to display the map.

Implementations of the invention can include the following feature. The system can further include a positioning system operable to obtain a current location of a mobile device, and an engine operable to provide a graphical display on the map of a route from the current location to the geographic location associated with the contact.

In general, in another aspect, the invention features a system including a telephony application operable to receive user input calling a telephone directory and requesting a telephone number, and a short messaging service application operable to receive a short message including the telephone number in response to the request for a telephone number. The system further includes a communication system configurable for sending the telephone number to a navigation service, and for receiving from the navigation service a geographic location associated with the telephone number. The system further includes a map application and a display. The map application is operable to provide a display of a map, the

map including a graphical representation of the geographic location associated with the telephone number. The display is operable to display the map.

Implementations of the invention can include the following additional feature. The system can further include a positioning system operable to obtain a current location of a mobile device, and an engine operable to provide a graphical display on the map of a route from the current location to the geographic location associated with the telephone number.

In general, in another aspect, the invention features a computer-readable medium having instructions stored thereon, which, when executed by a processor, cause the processor to perform operations including receiving at a mobile device an email message from an email address and displaying a representation of the email message on a graphical user interface. The operations further include receiving input from a user indicating a selection of the email address and searching contact information corresponding to a set of contacts for a contact having a contact email address matching the email address. The contact information for the contact includes a geographic location for the contact. The operations further include providing a display of a map to the user. The display includes a graphical representation indicating the geographic location for the contact having a contact email address matching the email address.

Implementations of the invention can include one or more of the following features. The mobile device can include a multi-touch-sensitive display and receiving input from a user indicating a selection of the email address can include the user touching the email address on the multi-touch-sensitive display. The operations can further include determining a current location of the mobile device, and providing route information to the user corresponding to a route from the current location to the geographic location of the contact.

In general, in another aspect, the invention features a system including a processor and a storage device. The storage device is coupled to the processor and configurable for storing instructions, which, when executed by the processor, cause the processor to perform operations including receiving at a mobile device an email message from an email address and displaying a representation of the email message on a graphical user interface. The operations further include receiving input from a user indicating a selection of the email address and searching contact information corresponding to a set of contacts for a contact having a contact email address matching the email address. The contact information for the contact includes a geographic location for the contact. The operations further include providing a display of a map to the user. The display includes a graphical representation indicating the geographic location for the contact having a contact email address matching the email address.

In general, in another aspect, the invention features a computer readable medium having instructions stored thereon, which, when executed by a processor, cause the processor to perform operations including activating a first user application on a mobile device, such that a user can make a request to a directory service for a telephone number. The operations further include, in response to the request, receiving a short message including the telephone number and determining a geographic location associated with the telephone number. The operations further include providing a display on a graphical user interface of a map including a graphical representation indicating the geographic location.

Implementations of the invention can include one or more of the following features. In one implementation, the first user application is a telephony application and the user request is by way of a telephone call. In another implementation, the

first user application is a short messaging service application and the user request is by way of a short message. The operations can further include determining a current location of the mobile device and providing route information to the user corresponding to a route from the current location to the geographic location associated with the telephone number.

In general, in another aspect, the invention features a system including a processor and a storage device coupled to the processor and configurable for storing instructions, which, when executed by the processor, cause the processor to perform operations including activating a first user application on a mobile device, such that a user can make a request to a directory service for a telephone number. The operations further include, in response to the request, receiving a short message including the telephone number and determining a geographic location associated with the telephone number. The operations further include providing a display on a graphical user interface of a map including a graphical representation indicating the geographic location.

In general, in another aspect, the invention features a mobile device including a communication system, an input/output (I/O) system, a processor and a map application. The communication system is configurable for receiving a communication from an individual or entity, the communication including information associated with the individual or entity. The I/O system is coupled to the communication system and configurable for displaying a representation of the information on the mobile device, and for receiving input specifying at least a portion of the information. The processor is coupled to the I/O system and configurable for retrieving from a data structure of the mobile device a geographic location associated with the individual or entity. The communication system sends the geographic information to a navigation service, which service responds by sending map information including coordinates for the geographic location. The map application, which when executed by the processor, uses the map information to generate a map for display by the mobile device. The map includes a graphical representation of the coordinates for the geographic location.

In general, in another aspect, the invention features a mobile device including a communication system configurable for sending a communication from a user of the mobile device, the communication including a request for a telephone number, and for receiving a short message including the telephone number. The mobile device further includes an input/output (I/O) system coupled to the communication system and configurable for receiving input specifying the request. The mobile device further includes a processor coupled to the I/O system and configurable for determining a geographic location associated with the telephone number, wherein the communication system sends the geographic information to a navigation service, which service responds by sending map information including coordinates for the geographic location. A map application is included, which when executed by the processor, uses the map information to generate a map for display by the mobile device. The map includes a graphical representation of the coordinates for the geographic location.

Implementations of the invention can include one or more of the following features. The communication including a request for a telephone number can be a telephone call to a telephone directory service. In another example, the communication including a request for a telephone number can be a short message to a telephone directory service.

In general, in another aspect, the invention features, a method including receiving a request from a mobile device for map information and providing the map information to the

mobile device. The request includes a geographic location that was derived by the mobile device from an associated email address and associated contact information included in an address book residing on the mobile device. The map information can be used by the mobile device to display a map including a graphical representation of the geographic location.

Implementations of the invention can include the following feature. The method can further include receiving a request for route information from the mobile device and providing the route information to the mobile device. The route is from a current location of the mobile device to the geographic location and the request includes the current location of the mobile device. The route information can be used by the mobile device to display a map including a graphical representation of the route.

In general, in another aspect, the invention features a system including a processor and a storage device coupled to the processor and configurable for storing instructions, which, when executed by the processor, cause the processor to perform operations including receiving a request from a mobile device for map information and providing the map information to the mobile device. The request includes a geographic location that was derived by the mobile device from an associated email address and associated contact information included in an address book residing on the mobile device. The map information can be used by the mobile device to display a map including a graphical representation of the geographic location.

Implementations of the invention can include the following feature. The instructions, when executed by the processor, further cause the processor to perform operations including receiving a request for route information from the mobile device for a route from a current location of the mobile device to the geographic location. The request includes the current location of the mobile device. The operations further include providing the route information to the mobile device, wherein the route information can be used by the mobile device to display a map including a graphical representation of the route.

In general, in another aspect, the invention features a method include receiving a request from a mobile device for map information and providing the map information to the mobile device. The request includes a geographic location that was derived by the mobile device from a short message including a telephone number received by the mobile device from a telephone directory service. The map information can be used by the mobile device to display a map including a graphical representation of the geographic location.

Implementations of the invention can include the following additional feature. A request for route information can be received from the mobile device for a route from a current location of the mobile device to the geographic location, the request including the current location of the mobile device. The route information can be provided to the mobile device, wherein the route information can be used by the mobile device to display a map including a graphical representation of the route.

In general, in another aspect, the invention features, a system including a processor and a storage device coupled to the processor and configurable for storing instructions, which, when executed by the processor, cause the processor to perform operations including receiving a request from a mobile device for map information and providing the map information to the mobile device. The request includes a geographic location that was derived by the mobile device from a short message including a telephone number received by the

mobile device from a telephone directory service. The map information can be used by the mobile device to display a map including a graphical representation of the geographic location.

Implementations of the invention can include the following feature. The instructions, when executed by the processor, can further cause the processor to perform operations including receiving a request for route information from the mobile device and providing the route information to the mobile device. The route is from a current location of the mobile device to the geographic location. The request includes the current location of the mobile device. The route information can be used by the mobile device to display a map including a graphical representation of the route.

Implementations of the invention can realize one or more of the following advantages. Various different applications provided by a mobile device can be integrated to provide an enhanced user experience. A user can seamlessly use or obtain information provided by multiple applications by interaction with integrated features. The user can efficiently be provided with meaningful information, for example, map and routing information, with reduced effort from the user's perspective.

The details of one or more embodiments of the invention are set forth in the accompanying drawings and the description below. Other features, objects, and advantages of the invention will be apparent from the description and drawings, and from the claims.

## DESCRIPTION OF DRAWINGS

FIG. 1 is a block diagram of a mobile device.

FIG. 2 is a block diagram of an example network operating environment for the mobile device of FIG. 1.

FIG. 3 is a block diagram of an example implementation of the mobile device of FIG. 1.

FIG. 4 is an example graphical user interface displaying an email message.

FIG. 5 is an example graphical user interface displaying contact information.

FIG. 6 is an example graphical user interface displaying an email message.

FIG. 7 is a flowchart showing an example process for providing an integrated email/addressbook/map feature.

FIG. 8 is an example graphical user interface displaying a map.

FIG. 9 is a block diagram representing an example engine.

FIG. 10 is an example graphical user interface displaying a map and a route superimposed thereon.

FIG. 11 is a flowchart showing an example process for providing an integrated telephony/short messaging service/map feature.

FIG. 12 is an example graphical user interface displaying a map and a route and contact information superimposed thereon.

Like reference symbols in the various drawings indicate like elements.

## DETAILED DESCRIPTION

FIG. 1 is a block diagram of an example mobile device 100. The mobile device 100 can be, for example, a handheld computer, a personal digital assistant, a cellular telephone, a network appliance, a camera, a smart phone, an enhanced general packet radio service (EGPRS) mobile phone, a network base station, a media player, a navigation device, an email device, a game console, or other electronic device or a com-

combination of any two or more of these data processing devices or other data processing devices.

#### Mobile Device Overview

In some implementations, the mobile device **100** includes a touch-sensitive display **102**. The touch-sensitive display **102** can implement liquid crystal display (LCD) technology, light emitting polymer display (LPD) technology, or some other display technology. The touch-sensitive display **102** can be sensitive to haptic and/or tactile contact with a user.

In some implementations, the touch-sensitive display **102** can comprise a multi-touch-sensitive display **102**. A multi-touch-sensitive display **102** can, for example, process multiple simultaneous touch points, including processing data related to the pressure, degree and/or position of each touch point. Such processing facilitates gestures and interactions with multiple fingers, chording, and other interactions. Other touch-sensitive display technologies can also be used, e.g., a display in which a point of contact is made using a stylus or other pointing device. An example of multi-touch sensitive display technology is described in U.S. Pat. Nos. 6,323,846; 6,570,557; 6,677,932; and U.S. Patent Publication No. 2002/0015024A1, each of which are incorporated by reference herein in its entirety.

In some implementations, the mobile device **100** can display one or more graphical user interfaces on the touch-sensitive display **102** for providing the user access to various system objects and for conveying information to the user to facilitate an intuitive user experience. In some implementations, the graphical user interface can include one or more display objects **104**, **106**. In the example shown, the display objects **104**, **106**, are graphic representations of system objects. Some examples of system objects include device functions, applications, windows, files, alerts, events, or other identifiable system objects.

#### Example Mobile Device Functionality

In some implementations, the mobile device **100** can implement multiple device functionalities, such as a telephony device, as indicated by a phone object **110**; an e-mail device, as indicated by the e-mail object **112**; a network data communication device, as indicated by the Web object **114**; and a media processing device, as indicated by the media player object **116**. In some implementations, particular display objects **104**, e.g., the phone object **110**, the e-mail object **112**, the Web object **114**, and the media player object **116**, can be displayed in a menu bar **118**. In some implementations, each of the device functionalities can be accessed from a top-level graphical user interface, such as the graphical user interface illustrated in FIG. 1. Touching one of the objects **110**, **112**, **114** or **116** can, for example, invoke the corresponding functionality.

In some implementations, the mobile device **100** can implement network distribution functionality. For example, the functionality can enable the user to take the mobile device **100** and its associated network while traveling. In particular, the mobile device **100** can extend Internet access (e.g., via Wi-Fi) to other wireless devices in the vicinity. For example, mobile device **100** can be configured as a base station for one or more devices. As such, mobile device **100** can grant or deny network access to other wireless devices.

In some implementations, upon invocation of particular device functionality, the graphical user interface of the mobile device **100** changes, or is augmented or replaced with another user interface or user interface elements, to facilitate

user access to particular functions associated with the corresponding device functionality. For example, in response to a user touching the phone object **110**, the graphical user interface of the touch-sensitive display **102** may present display objects related to various phone functions; likewise, touching of the email object **112** may cause the graphical user interface to present display objects related to various email functions; touching the Web object **114** may cause the graphical user interface to present display objects related to various Web-surfing functions; and touching the media player object **116** may cause the graphical user interface to present display objects related to various media processing functions.

In some implementations, the top-level graphical user interface environment or state of FIG. 1 can be restored by pressing a button **120** located near the bottom of the mobile device **100**. In some implementations, each corresponding device functionality may have corresponding “home” display objects displayed on the touch-sensitive display **102**, and the graphical user interface environment of FIG. 1 can be restored by touching the “home” display object.

In some implementations, the top-level graphical user interface can include additional display objects **106**, such as a short messaging service (SMS) object **130**, a calendar object **132**, a photos object **134**, a camera object **136**, a calculator object **138**, a stocks object **140**, a weather object **142**, a maps object **144**, a notes object **146**, a clock object **148**, an address book object **150**, and a settings object **152**. Touching the SMS display object **130** can, for example, invoke an SMS messaging environment and supporting functionality; likewise, each selection of a display object **132**, **134**, **136**, **138**, **140**, **142**, **144**, **146**, **148**, **150** and **152** can invoke a corresponding object environment and functionality.

Additional and/or different display objects can also be displayed in the graphical user interface of FIG. 1. In some implementations, the display objects **106** can be configured by a user, e.g., a user may specify which display objects **106** are displayed, and/or may download additional applications or other software that provides other functionalities and corresponding display objects.

In some implementations, the mobile device **100** can include one or more input/output (I/O) devices and/or sensor devices. For example, a speaker **160** and a microphone **162** can be included to facilitate voice-enabled functionalities, such as phone and voice mail functions. In some implementations, a loud speaker **164** can be included to facilitate hands-free voice functionalities, such as speaker phone functions. An audio jack **166** can also be included for use of headphones and/or a microphone.

In some implementations, a proximity sensor **168** can be included to facilitate the detection of the user positioning the mobile device **100** proximate to the user’s ear and, in response, to disengage the touch-sensitive display **102** to prevent accidental function invocations. In some implementations, the touch-sensitive display **102** can be turned off to conserve additional power when the mobile device **100** is proximate to the user’s ear.

Other sensors can also be used. For example, in some implementations, an ambient light sensor **170** can be utilized to facilitate adjusting the brightness of the touch-sensitive display **102**. In some implementations, an accelerometer **172** can be utilized to detect movement of the mobile device **100**, as indicated by the directional arrow **174**. Accordingly, display objects and/or media can be presented according to a detected orientation, e.g., portrait or landscape. In some implementations, the mobile device **100** may include circuitry and sensors for supporting a location determining capability, such as that provided by the global positioning

system (GPS). In some implementations, a positioning system (e.g., a GPS receiver) can be integrated into the mobile device **100** through an interface (e.g., port device **190**) to provide access to location-based services.

The mobile device **100** can also include a camera lens and sensor **180**. In some implementations, the camera lens and sensor **180** can be located on the back surface of the mobile device **100**. The camera can capture still images and/or video.

The mobile device **100** can also include one or more wireless communication subsystems, such as an 802.11b/g communication device **186**, and/or a Bluetooth™ communication device **188**. Other communication protocols can also be supported, including other 802.x communication protocols (e.g., WiMax, Wi-Fi, 3G), code division multiple access (CDMA), global system for mobile communications (GSM), Enhanced Data GSM Environment (EDGE), etc.

In some implementations, a port device **190**, e.g., a Universal Serial Bus (USB) port, or a docking port, or some other wired port connection, can be included. The port device **190** can, for example, be utilized to establish a wired connection to other computing devices, such as other communication devices **100**, a personal computer, a printer, or other processing devices capable of receiving and/or transmitting data.

In some implementations, a port device **190**, e.g., a USB port, or a docking port, or some other wired port connection, can be included. The port device **190** can, for example, be utilized to establish a wired connection to other computing devices, such as other communication devices **100**, network access devices, a personal computer, a printer, or other processing devices capable of receiving and/or transmitting data. In some implementations, the port device **190** allows the mobile device **100** to synchronize with a host device using one or more protocols, such as, for example, the TCP/IP over USB protocol described in co-pending U.S. Provisional Patent Application No. 60/945,904, filed Jun. 22, 2007, for “Multiplex Data Stream Protocol”, Attorney Docket No. 004860.P5490, which patent application is incorporated by reference herein in its entirety.

#### Network Operating Environment

FIG. 2 is a block diagram of an example network operating environment **200** for the mobile device **100** of FIG. 1. The mobile device **100** of FIG. 1 can, for example, communicate over one or more wired and/or wireless networks **210** in data communication. For example, a wireless network **212**, e.g., a cellular network, can communicate with a wide area network (WAN) **214**, such as the Internet, by use of a gateway **216**. Likewise, an access point **218**, such as an 802.11g wireless access point, can provide communication access to the wide area network **214**. In some implementations, both voice and data communications can be established over the wireless network **212** and the access point **218**. For example, the mobile device **100a** can place and receive phone calls (e.g., using VoIP protocols), send and receive e-mail messages (e.g., using POP3 protocol), and retrieve electronic documents and/or streams, such as web pages, photographs, and videos, over the wireless network **212**, gateway **216**, and wide area network **214** (e.g., using TCP/IP or UDP protocols). Likewise, the mobile device **100b** can place and receive phone calls, send and receive e-mail messages, and retrieve electronic documents over the access point **218** and the wide area network **214**. In some implementations, the mobile device **100** can be physically connected to the access point **218** using one or more cables and the access point **218** can be a personal computer. In this configuration, the mobile device **100** can be referred to as a “tethered” device.

The mobile devices **100a** and **100b** can also establish communications by other means. For example, the wireless device **100a** can communicate with other wireless devices, e.g., other wireless devices **100**, cell phones, etc., over the wireless network **212**. Likewise, the mobile devices **100a** and **100b** can establish peer-to-peer communications **220**, e.g., a personal area network, by use of one or more communication subsystems, such as the Bluetooth™ communication device **188** shown in FIG. 1. Other communication protocols and topologies can also be implemented.

The mobile device **100** can, for example, communicate with one or more services **230**, **240**, **250** and **260** and/or one or more content publishers **270** over the one or more wired and/or wireless networks **210**. For example, a navigation service **230** can provide navigation information, e.g., map information, location information, route information, and other information, to the mobile device **100**. In the example shown, a user of the mobile device **100b** has invoked a map functionality, e.g., by pressing the maps object **144** on the top-level graphical user interface shown in FIG. 1, and has requested and received a map for the location “1 Infinite Loop, Cupertino, Calif.”

A messaging service **240** can, for example, provide e-mail and/or other messaging services. A media service **250** can, for example, provide access to media files, such as song files, movie files, video clips, and other media data. One or more other services **260** can also be utilized by the mobile device **100** (e.g., syncing services, software update services, activation services).

The mobile device **100** can also access other data and content over the one or more wired and/or wireless networks **210**. For example, content publishers **270**, such as news sites, RSS feeds, web sites, blogs, social networking sites, developer networks, etc. can be accessed by the mobile device **100**. Such access can be provided by invocation of web browsing function or application (e.g., a browser) in response to a user touching the Web object **114**.

#### Example Mobile Device Architecture

FIG. 3 is a block diagram **300** of an example implementation of the mobile device **100** of FIG. 1. The mobile device **100** can include a memory interface **302** one or more data processors, image processors and/or central processing units **304**, and a peripherals interface **306**. The memory interface **302**, the one or more processors **304** and/or the peripherals interface **306** can be separate components or can be integrated in one or more integrated circuits. The various components in the mobile device **100** can be coupled by one or more communication buses or signal lines.

Sensors, devices and subsystems can be coupled to the peripherals interface **306** to facilitate multiple functionalities. For example, a motion sensor **310**, a light sensor **312**, and a proximity sensor **314** can be coupled to the peripherals interface **306** to facilitate the orientation, lighting and proximity functions described with respect to FIG. 1. Other sensors **316** can also be connected to the peripherals interface **306**, such as a positioning system (e.g., a GPS receiver), a temperature sensor, a biometric sensor, or other sensing device, to facilitate related functionalities.

A camera subsystem **320** and an optical sensor **322**, e.g., a charged coupled device (CCD) or a complementary metal-oxide semiconductor (CMOS) optical sensor, can be utilized to facilitate camera functions, such as recording photographs and video clips.

Communication functions can be facilitated through one or more wireless communication subsystems **324**, which can

include radio frequency receivers and transmitters and/or optical (e.g., infrared) receivers and transmitters. The specific design and implementation of the communication subsystem **324** can depend on the communication network(s) over which the mobile device **100** is intended to operate. For example, a mobile device **100** may include communication subsystems **324** designed to operate over a GSM network, a GPRS network, an EDGE network, a Wi-Fi or WiMax network, and a Bluetooth™ network.

An audio subsystem **326** can be coupled to a speaker **328** and a microphone **330** to facilitate voice-enabled functions, such as voice recognition, voice replication, digital recording, and telephony functions.

The I/O subsystem **340** can include a touch screen controller **342** and/or other input controller(s) **344**. The touch-screen controller **342** can be coupled to a touch screen **346**. The touch screen **346** and touch screen controller **342** can, for example, detect contact and movement or break thereof using any of a plurality of touch sensitivity technologies, including but not limited to capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with the touch screen **346**.

The other input controller(s) **344** can be coupled to other input/control devices **348**, such as one or more buttons, rocker switches, thumb-wheel, infrared port, USB port, and/or a pointer device such as a stylus. The one or more buttons (not shown) can include an up/down button for volume control of the speaker **328** and/or the microphone **330**.

In one implementation, a pressing of the button for a first duration may disengage a lock of the touch screen **346**; and a pressing of the button for a second duration that is longer than the first duration may turn power to the mobile device **100** on or off. The user may be able to customize a functionality of one or more of the buttons. The touch screen **346** can, for example, also be used to implement virtual or soft buttons and/or a keyboard.

In some implementations, the mobile device **100** can present recorded audio and/or video files, such as MP3, AAC, and MPEG files. In some implementations, the mobile device **100** can include the functionality of an MP3 player, such as an iPod™. The mobile device **100** may, therefore, include a 36-pin connector that is compatible with the iPod. Other input/output and control devices can also be used.

The memory interface **302** can be coupled to memory **350**. The memory **350** can include high-speed random access memory and/or non-volatile memory, such as one or more magnetic disk storage devices, one or more optical storage devices, and/or flash memory (e.g., NAND, NOR). The memory **350** can store an operating system **352**, such as Darwin, RTXC, LINUX, UNIX, OS X, WINDOWS, or an embedded operating system such as VxWorks. The operating system **352** may include instructions for handling basic system services and for performing hardware dependent tasks. In some implementations, the operating system **352** can be a kernel (e.g., UNIX kernel).

The memory **350** may also store communication instructions **354** to facilitate communicating with one or more additional devices, one or more computers and/or one or more servers. The memory **350** may include graphical user interface instructions **356** to facilitate graphic user interface processing; sensor processing instructions **358** to facilitate sensor-related processing and functions; phone instructions **360** to facilitate phone-related processes and functions; electronic messaging instructions **362** to facilitate electronic-messaging related processes and functions; web browsing instructions **364** to facilitate web browsing-related processes and func-

tions; media processing instructions **366** to facilitate media processing-related processes and functions; GPS/Navigation instructions **368** to facilitate GPS and navigation-related processes and instructions; camera instructions **370** to facilitate camera-related processes and functions; and/or other software instructions **372** or data to facilitate other related processes and functions (e.g., security instructions, activation record).

Each of the above identified instructions and applications can correspond to a set of instructions for performing one or more functions described above. These instructions need not be implemented as separate software programs, procedures or modules. The memory **350** can include additional instructions or fewer instructions. Furthermore, various functions of the mobile device **100** may be implemented in hardware and/or in software, including in one or more signal processing and/or application specific integrated circuits.

#### Integrated User Applications

A mobile device, e.g. mobile device **100** shown in FIG. **1**, can provide multiple user applications, as discussed above. Two or more of the user applications can be integrated, to enhance the user's experience and provide improved functionality. Some examples of integrated user application features are described in further detail below.

#### Integrated Address Book/Email Feature

In one implementation, the mobile device **100** provides an address book application. The user of the mobile device can select the address book display object **150** to invoke the address book application. The address book includes information corresponding to a set of the user's contacts. For example, the contact information can include a person or entity's name, address, phone number, email address, and/or other information related to the person or entity. The address book can reside on the mobile device **100**, or be stored externally but accessible by the mobile device **100**. An integrated address book feature can be provided, wherein the address book application is integrated with one or more other applications provided by the mobile device.

In one implementation, the mobile device **100** also includes an email application. The email application can be accessed by a user interaction with a user interface. For example, referring again to FIG. **1**, a user can select the email display object **112** to activate the email application. The email application and the address book application can be integrated, as described further below.

Referring to FIG. **4**, an example graphical user interface is shown displaying an example email message **400**. The email message **400** was received at the mobile device **100** and is displayed using the email application. The email message **400** includes a "to" field **402** indicating the email address to whom the email message **400** was sent, i. e., an email account of the user of the mobile device **100**. The email message further includes a "from" field **404** indicating the email address of the sender of the email message **400**. Optionally, an email message can include a "cc" field **406** indicating email addresses of others copied on the email message. The email message **400** includes a "subject" field **407**, where the sender of the email message can optionally provide an indication of the subject matter of the email message. The email message **400** includes a text field **408**, including the substance of the email message.

In this implementation, the user can interact with the email message **400** to select an email address in either the "from" or "cc" fields **404**, **406**. By way of example, if the mobile device

**100** includes a touch-sensitive display, such as the touch-sensitive display **106** in FIG. **1**, the user can select the email address by touching the email address on the display **106**.

Upon selecting an email address, the address book is automatically searched to determine whether a contact is included in the address book with an email address matching the selected email address. In this example, the email message was sent from Rick.Edward@mac.com. The address book is searched for a contact having the same email address in the email address field of the contact information for the contact. Referring now to FIG. **5**, an example page **500** from the address book is shown including contact information **502** for a contact identified as “Rick Edwards”. The email address **504** for Rick Edwards matches the email address in the “from” field **404** of the email message **400** shown in FIG. **4**.

In one implementation, in response to the user selecting the email address in the “from” field **404** of the email message **400**, if a matching contact is found, the display of the email message is replaced by a display of the page **500** from the address book including the corresponding contact information. In another implementation, both the email message **400** and the page **500** from the address book are displayed simultaneously using a split screen approach. In yet another implementation, at least some of the contact information is displayed superimposed on the email message, for example, within an information balloon **600** as shown in FIG. **6**. Other techniques for conveying the contact information to the user are possible, and different configurations of graphical user interfaces can be used. The ones described herein are examples for illustrative purposes.

In one implementation, the user can use a first mode of selecting the email address to receive a first result and a second mode of selecting the email address to receive a second result. For example, in the case of a mobile device **100** with a touch-sensitive display **106**, a first mode of selecting the email address can be the user briefly touching the email address. The first result displayed in response to the selection can be a display of the information balloon **600** superimposed on the email message **400**, as shown in FIG. **6**. A second mode of selecting the email address can be the user touching the email address for a sustained period of time (e.g., a few seconds). The second result displayed in response to the selection can be a display of the page **500** from the address book including the entire set of contact information for the contact corresponding to the email address, as shown in FIG. **5**.

In another implementation, where a user can interact with the email message **400** using a mouse or other such pointer device to control a position of a cursor, a first mode of selecting the email address can be to hover the cursor over the email address being selected. A second mode of selecting the email address can be to click on the email address. Other manners of interacting with the email message **400** to select the email address are possible, and the ones described are examples.

#### Integrated Address Book/Email/Map/Route Feature

In one implementation, upon a user selecting an email address in the email message **400**, if a matching contact is located in the address book and the contact information for the contact includes an address for a geographic location, then a map is displayed to the user showing the geographic location. Referring to FIG. **7**, a process **700** is shown for displaying a geographic location on a map to a user in response to selecting an email address within an email message. In step **702**, an email message is received from an email address by an email application operating within a mobile device. By

way of example, the email message **400** is received from the email address for Rick Edwards, **404**. A user input is received selecting the email address (Step **704**). Again, by way of example, the user can select the “from” field to select Rick Edwards’ email address. It should be understood that steps **702** and **704** are optional and the process can commence at step **706**.

A geographic location associated with the email address is retrieved from an address book application operated by the mobile device (Step **706**). Referring to the above example, the geographic location associated with the email address for Rick Edwards as shown on a page **500** from the address book is 123 11 Ave SE, Anywhere, USA. An “address” field in the contact information **502** for the contact corresponding to the email address can be searched to retrieve the address. A map is provided on a user interface for display to the user, where the map shows the geographic location (Step **708**). For example, referring to FIG. **8**, the map **800** can be displayed with a graphical representation, i.e., the star **802**, at the geographic location corresponding to 123 11 Ave SE, Anywhere, USA.

In one implementation, a map application is provided by the mobile device **100**, either internally or by way of interfacing with an external map service. By way of example, the map service can be Google Maps API provided by Google, Inc. of Mountain View, Calif., although other map services can be used. A request for a map that is approximately centered about the geographic location can be sent to the map application and the map received from the map application. The map is displayed on a user interface, for example, the touch-sensitive user interface **106** shown on the mobile device **100** in FIG. **1**.

#### Integrated Address Book/Email/Map/Route Feature

In one implementation, the mobile device **100** is location aware (i.e., can determine its current location). Referring again to FIG. **3**, in this implementation, the mobile device **100** includes a positioning system **318**. In various implementations, the positioning system **318** can be provided by a separate device coupled to the mobile device **100**, or can be provided internal to the mobile device. In some implementations, the positioning system **318** can employ positioning technology including a GPS, a cellular grid, television signals, Wi-Fi base stations, URIs or any other technology for determining the geographic location of a device. In other implementations, the positioning system **318** can be provided by an accelerometer and a compass using dead reckoning techniques. In such implementations, the user can occasionally reset the positioning system by marking the mobile device’s presence at a known location (e.g., a landmark or intersection). In other implementations, the positioning system **318** can be provided by using wireless signal strength and one or more locations of known wireless signal sources to provide the current location. Wireless signal sources can include access points and/or cellular towers. In still other implementations, the user can enter a set of position coordinates (e.g., latitude, longitude) for the mobile device. For example, the position coordinates can be typed into the phone (e.g., using a virtual keyboard) or selected by touching a point on a map. Position coordinates can also be acquired from another device (e.g., a car navigation system) by syncing or linking with the other device. Other techniques to determine a current location of the mobile device **100** can be used and other configurations of the positioning system **318** are possible.

Referring again to FIG. 7, in an optional step 710, the mobile device can determine its current location. The current location can be provided to an engine (e.g., embodied in routing instructions 374 included within the memory 350, see FIG. 3). The engine can be used to provide navigation guidance to a user of the mobile device 100. In such implementations, the engine can provide route information to the user from a current location of the mobile device 100 to the geographic location corresponding to a selected email address.

Referring again to FIG. 5, in an implementation where the mobile device is location aware, a proximity to an address included in the contact information. One example of a display of proximity information is shown at 506. The distance can represent a radial proximity, proximity by a closest-travel-route, or another measurement of proximity.

FIG. 9 is a block diagram illustrating an example operation of the engine 900 (e.g., embodied in routing instructions 374). In some implementations, the engine 900 includes a routing engine 902 and a presentation engine 904. In one implementation, the routing engine 902 can derive a route between two locations, i.e., the current location and a contact location (i.e., a geographic location corresponding to a contact in the address book), using existing routing technology. By way of illustration, Google Maps API is one example of existing routing technology, available from Google, Inc. (Mt. View Calif.). The current location is determined using the positioning system 318, as described above. The contact location is determined from the contact information included in the address book corresponding to the selected email address.

The routing engine 902 provides a route from the current location to the contact location to the presentation engine 904. The presentation engine 904 can communicate with the map application used to implement the integrated address book feature. The presentation engine 904 can use a map provided by the map application 906 to overlay the route information. Referring to FIG. 10, the map 800 of FIG. 8 is shown with a route 1004 superimposed thereon. A graphical display object 1002 indicates the current location of the mobile device 100 and the graphical display object 802 indicates the contact location. In one implementation, as described above, the user can select a route display object 804 superimposed on the map 800 (or otherwise displayed to the user) to activate the route application.

In one implementation, the route information can include either in addition to the route displayed on the map, or instead of the route displayed on the map, an audio file including audio directions from the current location of the mobile device 100 to the contact location. The audio file can be delivered, for example, to a voicemail application provided by the mobile device. In one implementation, the audio file includes chapter marks such that the user can play back the voicemail while traveling the route to the contact location, and pause at the chapter marks while progressing along the route from one instruction to the next. In another implementation, the audio file is included in a podcast delivered to the mobile device 100 over the Internet. The audio file included in the podcast may also include chapter marks to facilitate playback of the route information while progressing along the route. In an implementation where the audio file is provided in conjunction with the route displayed on a map, the mobile device's current location as the mobile device progresses along the route can be tracked on the map in sync with the directions being provided by audio to the user.

#### Integrated Telephony/Short Messaging Service/Map/Route Application

In another implementation, a telephony application, short messaging service application, map application and option-

ally, a route application, can be integrated into an integrated user feature. Referring to FIG. 11, an example process 1100 wherein a user employs the integrated user feature is shown. In a first step 1102, the mobile device receives user input selecting and using the telephony application to call a telephone directory service. For example, the user can telephone a "411" or similar type of information number. The user can select to have the telephone number and/or address information provided by the telephone directory service delivered to the mobile device by way of a short message. By way of illustrative example, certain mobile service providers enable text messaging delivery of telephone directory information to their mobile telephone customers. The short message is received by a short messaging service application provided by the mobile device, wherein the short message includes a telephone number and optionally a corresponding address (Step 1104).

If the short message includes an address, then the address can be sent to the map application with a request for a map showing the address. If the short message only includes a telephone number, a corresponding address can be determined based on the telephone number (Optional Step 1106), for example, using a reverse look-up service. By way of illustration, a reverse lookup service is provided by www.reversetelephonedirectory.com, wherein a telephone number can be provided to obtain a corresponding address. This service, or a similar service, can be employed to receive the telephone number provided by the mobile device and to send as a response the corresponding address.

In either case, the address is provided to the map application (Step 1108). The map application provides a map showing the address (Step 1110). For example, the map can be the map 800 shown in FIG. 8, where the star 802 represents the address.

In one implementation, the current location of the mobile device can be determined (Optional Step 1112). The current location and the address can be provided to the route application (Step 1114). The route application can provide route information including displaying the route superimposed on the map (Optional Step 1116). For example, the route 1004 can be superimposed on the map 800, as shown in FIG. 12. As described above, the route information can include an audio file delivered by a podcast, or to a voicemail application.

Accordingly, by a user calling a telephone directory service, the user can receive in response a map generated by the map application including a visual representation of a location corresponding to the telephone number requested from the telephone directory service and optionally a route from the current location of the mobile device (and therefore the user) to the location. An information balloon, or other such visual representation, can be provided in conjunction with the map (e.g., superimposed thereon) providing the telephone number, for example, information balloon 1202 shown in FIG. 12. The telephony application can be employed by the user to automatically call the telephone number. For example, the user can select the telephone number 1204 displayed within the information balloon 1202 to initiate a call to the number.

In another implementation, a user of the mobile device can send a short message (i.e., text message) to a telephone directory service and receive a short message in response including the requested information, e.g., a telephone number and/or address. For example, AT&T Wireless provides a service called TXT-411, wherein mobile customers of AT&T Wireless can use short messaging to communication with a telephone directory service, both to request and receive information. In this implementation, once the short message is



17

received including the telephone number and address, steps 1104 onwards in process 1100 can be performed to provide the user a map and optionally route information. That is, step 1102 can be eliminated in this implementation and replaced by a step wherein user input is received providing a short message to send to a directory service, the short message including a request for a telephone number and/or address.

An engine, as the term is used throughout this application, can be a piece of hardware that encapsulates a function, can be firmware or can be a software application. An engine can perform one or more functions, and one piece of hardware, firmware or software can perform the functions of more than one of the engines described herein. Similarly, more than one piece of hardware, firmware and/or software can be used to perform the function of a single engine described herein.

The foregoing descriptions of specific embodiments of the present invention are presented for purposes of illustration and description. They are not intended to be exhaustive or to limit the invention to the precise forms disclosed. Rather, it should be appreciated that various modifications may be made without departing from the spirit and scope of the invention. Accordingly, other embodiments are within the scope of the following claims.

What is claimed is:

1. A method comprising:
  - receiving an electronic message at a mobile device;
  - displaying the electronic message in an electronic message user interface, the electronic message including sender information;
  - determining a contact entry of an address book application associated with the sender information of the electronic message, the contact entry including physical address information;
  - determining a geographic location of the mobile device; and
  - displaying the contact entry on an address book application user interface, the displayed contact entry including proximity information indicating a distance from the device to the physical address of the contact entry.
2. The method of claim 1, wherein the mobile device includes a multi-touch-sensitive display and further comprising:
  - receiving input from a user indicating a selection of the sender information, where the input comprises the user touching the sender information on the multi-touch-sensitive display.
3. The method of claim 1, further comprising:
  - determining a route from the geographic location of the mobile device to the physical address of the contact entry; and
  - displaying in a map user interface a graphical representation indicating a route from the geographic location of the mobile device to the physical address of the contact entry.
4. The method of claim 3, wherein the graphical representation includes a graphical display of the route superimposed on a map.
5. The method of claim 3, wherein the map user interface presents textual directions for the route.
6. The method of claim 3, wherein the mobile device presents audio directions for the route.
7. The method of claim 3, further comprising:
  - providing the geographic location of the mobile device and the physical address of the contact entry to a route service with a request for a route therebetween; and
  - receiving route information describing the route in response to the request.

18

8. The method of claim 1, further comprising:
  - providing the physical address of the contact entry to a map service with a request for a map including the physical address; and
  - receiving the map in response to the request.
9. A non-transitory computer-readable medium having instructions stored thereon, which, when executed by a processor, cause the processor to perform operations comprising:
  - receiving an electronic message at a mobile device;
  - displaying the electronic message in an electronic message user interface, the electronic message including sender information;
  - determining a contact entry of an address book application associated with the sender information of the electronic message, the contact entry including physical address information;
  - determining a geographic location of the mobile device; and
  - displaying the contact entry on an address book application user interface, the displayed contact entry including proximity information indicating a distance from the device to the physical address of the contact entry.
10. The computer-readable medium of claim 9, wherein the mobile device includes a multi-touch-sensitive display and further comprising:
  - receiving input from a user indicating a selection of the sender information, where the input comprises the user touching the sender information on the multi-touch-sensitive display.
11. The computer-readable medium of claim 9, further comprising instructions, which, when executed by a processor, cause the processor to perform operations comprising:
  - determining a route from the geographic location of the mobile device to the physical address of the contact entry; and
  - displaying in a map user interface a graphical representation indicating a route from the geographic location of the mobile device to the physical address of the contact entry.
12. A system comprising:
  - a processor;
  - a storage device coupled to the processor and configurable for storing instructions, which, when executed by the processor cause the processor to perform operations comprising:
    - receiving an electronic message at a mobile device;
    - displaying the electronic in an electronic message user interface, the electronic message including sender information;
    - determining a contact entry of an address book application associated with the sender information of the electronic message, the contact entry having physical address information;
    - determining a geographic location of the mobile device; and
    - displaying the contact entry on an address book application user interface, the displayed contact entry including proximity information indicating a distance from the device to the physical address of the contact entry.
13. The method of claim 1, wherein the proximity information indicates a radial distance from the device to the physical address of the contact entry.
14. The method of claim 1, wherein the proximity information indicates a distance associated with the closest travel route from the device and the physical address of the contact entry.