



US008783312B2

(12) **United States Patent**
Yamada

(10) **Patent No.:** **US 8,783,312 B2**
(45) **Date of Patent:** **Jul. 22, 2014**

(54) **PNEUMATIC TIRE**

6,142,200 A * 11/2000 Feider et al. 152/209.14
7,422,043 B2 * 9/2008 Miyazaki 152/209.22
2008/0236714 A1 * 10/2008 Kojima 152/209.9

(75) Inventor: **Hiroshi Yamada**, Kobe (JP)

(73) Assignee: **Sumitomo Rubber Industries, Ltd.**,
Kobe (JP)

FOREIGN PATENT DOCUMENTS

EP 0788898 * 8/1997
JP 7-186626 A 7/1995

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 295 days.

OTHER PUBLICATIONS

(21) Appl. No.: **13/323,858**

English machine translation of JP07-186626, dated Jul. 1995.*
English machine translation of EP0788898, dated Aug. 1997.*

(22) Filed: **Dec. 13, 2011**

* cited by examiner

(65) **Prior Publication Data**

US 2012/0145295 A1 Jun. 14, 2012

Primary Examiner — Steven D Maki

(30) **Foreign Application Priority Data**

Dec. 14, 2010 (JP) 2010-278344

Assistant Examiner — Robert Dye

(74) *Attorney, Agent, or Firm* — Birch, Stewart, Kolasch & Birch, LLP

(51) **Int. Cl.**

B60C 11/11 (2006.01)
B60C 11/12 (2006.01)
B60C 11/13 (2006.01)

(57) **ABSTRACT**

(52) **U.S. Cl.**

USPC **152/209.18**; 152/209.22; 152/209.27;
152/DIG. 3

A pneumatic tire comprises a tread portion divided into a crown land region, two middle land regions and two shoulder land regions. The crown land region and middle land regions are each divided into triangular blocks by axial grooves arranged in a zigzag fashion. The shoulder land regions are each divided into shoulder blocks by axial grooves extending at an angle of not less than 70 degrees. The shoulder block is subdivided into an axially inner part and an axially outer part by a secondary groove extending at an angle of not more than 10 degrees. The outer part is provided with sipes extending at an angle of not less than 70 degrees, each angle with respect the circumferential direction.

(58) **Field of Classification Search**

USPC 152/209.18, 209.21, 209.22, 209.27,
152/DIG. 3

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,296,789 A * 10/1981 Roberts et al. 152/209.18
5,733,393 A * 3/1998 Hubbell et al. 152/209.5
5,909,756 A * 6/1999 Miyazaki 152/209.18

11 Claims, 6 Drawing Sheets




FIG. 1




FIG. 2




FIG.3(a)




FIG.3(b)




FIG. 4




FIG.5





FIG. 6



PNEUMATIC TIRE

BACKGROUND OF THE INVENTION

The present invention relates to a pneumatic tire, more particularly to a tread pattern suitable for passenger car tires capable of improving on-the-snow performance, without sacrificing steering stability on dry pavement.

In order to improve on-the-snow performance without sacrificing steering stability on dry pavement, a pneumatic tire (a) having a tread pattern shown in FIG. 6 has been proposed in Japanese Patent Application Publication JP-H07-186626.

The tread portion (b) of this pneumatic tire (a) is provided with a pair of crown main grooves (d) and a pair of shoulder main groove (e) so as to divide the tread portion (b) into a crown land region (f), a pair of middle land regions (g), and a pair of shoulder land regions (h).

The crown land region (f), middle land regions (g) and shoulder land regions (h) are divided into a plurality of blocks (f1, g1 and h1) by narrow grooves (j) and sipes (k1) which are inclined with respect to the circumferential direction.

Each of the blocks (f1-h1) is provided with a sipe (k2) inclined with respect to the tire circumferential direction.

Therefore, by the edges of the sipes (k1 and k2), on-the-snow performance of the pneumatic tire (a) can be improved, but the decrease in the rigidity of the land regions (f-h) is little since the width of the sipes is very narrow, therefore, the steering stability on dry pavement is not sacrificed.

In this tread pattern, however, wandering and one-side drifting of the vehicle is liable to occur when running on snowy roads covered with compacted snow.

SUMMARY OF THE INVENTION

It is therefore, an object of the present invention to provide a pneumatic tire, in which on-the-snow performance including anti-wandering and one-side drifting performance can be improved, without sacrificing the steering stability on dry pavement.

According to the present invention, a pneumatic tire comprises a tread portion provided on each side of the tire equator with an axially inner crown main groove and an axially outer shoulder main groove which extend continuously in the tire circumferential direction so as to divide the tread portion into a crown land region between the crown main grooves, a pair of middle land regions between the crown main grooves and the shoulder main grooves, and a pair of shoulder land regions between the shoulder main grooves and tread edges, wherein

the crown land region is provided with crown axial grooves which are narrow grooves and/or sipes extending across the entire width of the crown land region and arranged in a zigzag fashion so as to divide the crown land region into a plurality of crown blocks having triangular configurations,

the middle land regions are each provided with middle axial grooves which are narrow grooves and/or sipes extending across the entire width of the middle land region and arranged in a zigzag fashion so as to divide the middle land region into a plurality of middle blocks having triangular configurations,

the shoulder land regions are each provided with shoulder axial grooves extending across the entire width of the shoulder land region at an angle of not less than 70 degrees with respect to the tire circumferential direction so as to divide the shoulder land region into a plurality of shoulder blocks,

the shoulder blocks are each provided with a shoulder secondary groove extending at an angle of not more than 10 degrees with respect to the tire circumferential direction and

disposed at a distance of 3 to 15 mm axially outward from the shoulder main groove so as to subdivide the shoulder block into an axially inner part and an axially outer part, and

the outer part is provided with shoulder sipes extending at an angle of not less than 70 degrees with respect to the circumferential direction.

Therefore, in the pneumatic tire according to the present invention, as the crown axial grooves and middle axial grooves are arranged in the zigzag fashions, the circumferential component of the groove edges is increased in the tread central region, and thereby on-the-snow performance can be improved. Further, the crown axial grooves and middle axial grooves are relatively narrow in groove width, therefore, the decrease in the rigidity of the crown land region and middle land regions due to the provision of the axial grooves can be minimized, and the deterioration in the steering stability on dry pavement can be prevented.

Since the shoulder secondary grooves are positioned on the tire equator side of the shoulder land regions where, during cornering, the ground pressure becomes relatively high and the ground contacting length becomes relatively long, the circumferential component of the edges of the shoulder secondary grooves functions effectively, and the cornering performance on snowy roads can be improved.

Further, by the shoulder sipes disposed in the axially outer parts of the shoulder blocks, the traction on snowy roads can be greatly increased.

Furthermore, as the angle of the shoulder secondary grooves is set to be at most 10 degrees, the shoulder secondary grooves are substantially parallel with the tire circumferential direction. As a result, wandering and one-side drifting of the vehicle during running on snowy roads can be effectively suppressed.

In this application including specification and claims, various dimensions, positions and the like of the tire refer to those under a normally inflated unloaded condition of the tire unless otherwise noted.

The normally inflated unloaded condition is such that the tire is mounted on a standard wheel rim and inflated to a standard pressure but loaded with no tire load.

The undermentioned normally inflated loaded condition is such that the tire is mounted on the standard wheel rim and inflated to the standard pressure and loaded with the standard tire load.

The standard wheel rim is a wheel rim officially approved or recommended for the tire by standards organizations, i.e. JATMA (Japan and Asia), T&RA (North America), ETRTO (Europe), TRAA (Australia), STRO (Scandinavia), ALAPA (Latin America), ITTAC (India) and the like which are effective in the area where the tire is manufactured, sold or used.

The standard pressure and the standard tire load are the maximum air pressure and the maximum tire load for the tire specified by the same organization in the Air-pressure/Maximum-load Table or similar list. For example, the standard wheel rim is the "standard rim" specified in JATMA, the "Measuring Rim" in ETRTO, the "Design Rim" in TRA or the like. The standard pressure is the "maximum air pressure" in JATMA, the "Inflation Pressure" in ETRTO, the maximum pressure given in the "Tire Load Limits at various cold Inflation Pressures" table in TRA or the like. The standard load is the "maximum load capacity" in JATMA, the "Load Capacity" in ETRTO, the maximum value given in the above-mentioned table in TRA or the like. In case of passenger car tires, however, the standard pressure and standard tire load are uniformly defined by 180 kPa and 88% of the maximum tire load, respectively.

3

The term "tread width TW" is the axial distance between the tread edges T_e measured in the normally inflated unloaded condition of the tire. The tread edges T_e are the axial outermost edges of the ground contacting patch (camber angle=0) in the normally inflated loaded condition.

The term "sipe" means a groove having a very narrow width which is usually 0.3 to 1.5 mm or a cut having substantially no groove width unless otherwise noted.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a developed view of a part of the tread portion of a pneumatic tire according to an embodiment of the present invention.

FIG. 2 is a cross sectional view of a tread shoulder portion taken along line A-A of FIG. 1.

FIG. 3(a) is an enlarged view of a part of the shoulder block row shown in FIG. 1.

FIG. 3(b) is a cross sectional view taken along line B-B in FIG. 3(a).

FIG. 4 is an enlarged view of a part of the crown block row shown in FIG. 1.

FIG. 5 is an enlarged view of a part of the middle block row shown in FIG. 1.

FIG. 6 is a developed view of a part of the tread portion of a tire used in the undermentioned comparative test.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of the present invention will now be described in detail in conjunction with the accompanying drawings.

The pneumatic tire according to the present invention comprises a tread portion 2, a pair of sidewall portions, a pair of bead portions, a carcass extending between the bead portions, a tread reinforcing belt disposed radially outside the carcass in the tread portion as usual.

The present invention is suitably applied to passenger car tires and the like. FIG. 1 shows the tread portion 2 of such a passenger car tire as an embodiment of the present invention. In the tread portion 2 in this embodiment, by the undermentioned grooves and sipes, there is formed a bidirectional tread pattern which is symmetry with respect to a point on the tire equator c .

The tread portion 2 is provided on each side of the tire equator c with an axially inner crown main grooves 3 and an axially outer shoulder main grooves 4 which extend continuously in the tire circumferential direction so that the tread portion 2 is axially divided into a crown land region 5 between the crown main grooves 3, a pair of middle land regions 6 between the crown main grooves 3 and the shoulder main grooves 4, and a pair of shoulder land regions 7 between the shoulder main grooves 4 and tread edges T_e .

Each main groove 3, 4 may be formed in a various configuration such as wavy configuration and zigzag configuration. In this embodiment, however, the crown main grooves 3 and shoulder main grooves 4 are each formed in a straight configuration. The use of such straight grooves 3 and 4 is desirable because vehicle's unstable motions such as wandering when applying brake, drift to one side and the like can be suppressed to provide steering stability.

The width w_1 of the crown main grooves 3 and the width w_2 of the shoulder main grooves 4 are preferably set in a range of from 3 to 10% of the tread width T_w .

4

The depth D_1 of the crown main grooves 3 and the depth D_2 of the shoulder main grooves 4 are preferably set in a range of from 6 to 10 mm.

If the width w_1 and w_2 and/or depth D_1 and D_2 exceed the respective upper limits, there is a possibility that the rigidity of the land regions 5, 6 and 7 becomes insufficient. If exceed the respective lower limits, it becomes difficult for the snow packed into the grooves to be self discharged.

The axial distance L_1 of the center line G_1 of the crown main groove 3 from the tire equator c is preferably set in a range of not less than 3%, more preferably not less than 6%, but not more than 20%, more preferably not more than 16% of the tread width T_w .

The axial distance L_2 of the center line G_2 of the shoulder main groove 4 from the tire equator C is preferably set in a range of not less than 15%, more preferably not less than 20%, but not more than 40%, more preferably not more than 35% of the tread width T_w .

Therefore, the rigidity balance between the land regions 5-7 is improved to improve the steering stability.

The above-mentioned crown land region 5 is provided with crown axial grooves 8. The crown axial grooves 8 are narrow grooves and/or sipes extending across the entire width of the crown land region 5 and arranged in a zigzag formation so that the crown land region 5 is divided into a plurality of triangular crown blocks 5a.

The middle land region 6 is provided with middle axial grooves 9. The middle axial grooves 9 are narrow grooves and/or sipes extending across the entire width of the middle land region 6 and arranged in a zigzag formation so that the middle land region 6 is divided into a plurality of triangular middle blocks 6a.

The shoulder land region 7 is provided with shoulder axial grooves 10. The shoulder axial grooves 10 extend across the entire width of the shoulder land region 7 so that the shoulder land region 7 is divided into a plurality of shoulder blocks 7a.

In the crown land region 5 and middle land regions 6, therefore, by the crown axial grooves 8 and middle axial grooves 9 arranged in zigzag formations, the circumferential component of the groove edges is greatly increased, and on-the-snow performance can be improved.

Further, as the crown land region 5 and middle land regions 6 are divided into the triangular crown blocks 5a and triangular middle blocks 6a, the rigidity of the blocks 5a and 6a as a whole in the circumferential direction and axial direction is evened, and the rigidity balance between the crown land region 5 and middle land regions 6 is improved. As the crown axial grooves 8 and middle axial grooves 9 are relatively narrow in groove width, the decrease in the rigidity of each land region 5, 6 can be minimized. Accordingly, the steering stability on dry pavement can be effectively maintained.

As shown in FIG. 3(a), the angle θ_1 of the shoulder axial groove 10 with respect to the tire circumferential direction is set to be at least 70 degrees, preferably at least 75 degrees. If the angle θ_1 is less than 70 degrees, the lateral stiffness (rigidity) of the shoulder blocks 7a becomes insufficient for the shoulder 1 and region 7 which is subjected to large ground pressure during cornering, and the shearing force of the snow packed into the shoulder axial grooves 10 decreases.

The angle θ_1 may be constant along the entire length of the shoulder axial groove 10, but preferably the angle θ_1 is gradually increased toward the tread edge T_e . Thereby, the lateral stiffness is further increased near the tread edge T_e which is subjected to a more large ground pressure during cornering, and the steering stability can be further improved. More preferably, the angle θ_1 is set to be not more than 88 degrees in

view of the balance between the lateral stiffness (rigidity) of the shoulder block **7a** and the cornering performance.

In order to derive the rigidity of the shoulder block **7a** and the shearing force of the packed snow in a well balanced manner, the width **w3** of the shoulder axial groove **10** is preferably set in a range of not less than 1.0%, more preferably not less than 2.0%, but not more than 8.0%, more preferably not more than 5.0% of the tread width **Tw**. Further, the depth **D3** of the shoulder axial groove **10** is preferably set in a range of not less than 40%, more preferably not less than 50%, but not more than 100%, more preferably not more than 90% of the depth **D2** of the shoulder main grooves **4**.

Each of the shoulder blocks **7a** is provided with a single shoulder secondary groove **13** in order to axially subdivide the shoulder block **7a** into an axially inner part **11** and an axially outer part **12**.

The angle $\theta 2$ of the shoulder secondary groove **13** with respect to the tire circumferential direction has to be at most 10 degrees, preferably not more than 5 degrees, more preferably 0 degree. If the angle $\theta 2$ exceed 10 degrees, the circumferential component of the groove edges decreases, and the cornering performance on snowy roads is deteriorated, and it becomes hard to control the wandering and one-side drifting.

The axial distance **L3** between the shoulder secondary groove **13** and the shoulder main groove **4** (namely, the axial width of the inner part **11**) has to be in a range of not less than 3 mm, preferably not less than 4 mm, more preferably not less than 5 mm, but, not more than 15 mm, preferably not more than 13 mm, more preferably not more than 11 mm.

If the distance **L3** is less than 3 mm, the lateral stiffness (rigidity) of the inner part **11** becomes insufficient, and wear tends to concentrate in the inner parts **11**. If the distance **L3** is more than 15 mm, the lateral stiffness (rigidity) of the outer parts **12** subjected to large ground pressure during cornering is decreased, and the steering stability is deteriorated.

As shown in FIG. 2, the depth **D4** of the shoulder secondary groove **13** is preferably set in a range of not less than 0.5 mm, more preferably not less than 1.0 mm, but not more than 7.0 mm, more preferably not more than 6.0 mm. Therefore, the rigidity of the shoulder block **7a** can be maintained, while achieving self-discharging of snow packed into the shoulder secondary grooves **13**, and on-the-snow performance and steering stability on dry pavement can be secured in a well balanced manner.

In order to effectively derive the above-mentioned effects, the depth **D4** of the shoulder secondary groove **13** is preferably less than the width **w4** of the shoulder secondary groove **13**. More specifically, the ratio **D4/w4** of the depth **D4** to the width **w4** is preferably set in a range of not less than 40%, more preferably not less than 50%, but not more than 98%, more preferably not more than 90%.

Preferably, the outer part **12** of each of the shoulder blocks **7a** is provided with shoulder sipes **15** extending from the axial outside of the tread edge **Te** toward the shoulder secondary groove **13** but terminating without reaching thereto.

In this embodiment, two shoulder sipes **15** are formed so as to divide the circumferential dimension of the outer part **12** into three equi-parts.

The shoulder sipes **15** have to extend at an angle $\theta 3$ of not less than 70 degrees, preferably not less than 75 degrees with respect to the circumferential direction.

Such shoulder sipes **15** can increase the traction performance during straight running, without excessively decreasing the block rigidity of the outer part **12**, therefore, on-the-snow performance can be improved. If the angle $\theta 3$ is less than 70 degrees, the effect to improve the traction on snowy roads decreases.

In order to secure the cornering performance on snowy roads and the traction performance during straight running in a well balanced manner, the angle $\theta 3$ is preferably set be not more than 88 degrees.

In this embodiment, the angle $\theta 3$ of the shoulder sipes **15** is gradually increased toward the tread edge **Te**. Therefore, the shoulder sipes **15** gradually increase the lateral stiffness (rigidity) toward the tread edge **Te**, and the cornering performance on snowy roads can be improved.

If the axial length **L4** of the shoulder sipes **15** is too long, the rigidity of the outer part **12** is decreased, and there is a possibility that the steering stability on dry pavement is deteriorated. If too short, the edge length becomes insufficient.

The axial length **L4** of the shoulder sipe **15** is preferably not less than 50%. more preferably not less than 60%, but not more than 98%, more preferably not more than 95% of the axial width **ws1** of the outer part **12**.

The groove width **w6** of the shoulder sipe **15** is preferably set in a range of not less than 0.2 mm, more preferably not less than 0.3 mm, but not more than 1.5 mm, more preferably not more than 1.2 mm.

It is preferable that the bottom **13s** of the shoulder secondary groove **13** is provided with a groove-bottom sipe **16** extending along the shoulder secondary groove **13**.

The groove-bottom sipe **16** can provide groove edges in the last stage of tread wear life without excessively decreasing the rigidity of the shoulder block **7a**.

In order to secure the rigidity of the shoulder land region **7**, the groove-bottom sipe **16** in this embodiment is formed as a straight sipe positioned on the center line **G3** of the shoulder secondary groove **13**. And preferably, as shown in FIG. 3(a), both ends of the groove-bottom sipe **16** are closed ends which are respectively spaced apart from the circumferential ends **7b** and **7c** of the shoulder secondary groove **13** by a distance **L5** of not less than 1.0 mm, more preferably not less than 2.0 mm, but not more than 8.0 mm, more preferably not more than 6.0 mm. If the distance **L5** becomes more than 8.0 mm, as the groove-bottom sipe **16** becomes short accordingly, the edge effect becomes insufficient. If the distance **L5** becomes less than 1.0 mm, the shoulder secondary groove **13** is largely opened during cornering, and the inner part **11** and outer part **12** are decreased in the rigidity.

In order to effectively derive the above described advantages, as shown in FIG. 3(b), the width **w5** of the groove-bottom sipe **16** is preferably set in a range of not less than 20%, more preferably not less than 30%, but not more than 90%, more preferably not more than 80% of the width **w4** of the shoulder secondary groove **13**.

Further, the depth **D5** of the groove-bottom sipe **16** is preferably set in a range of not less than 20%, more preferably not less than 40%, but not more than 300%, more preferably not more than 250% of the depth **D4** of the shoulder secondary groove **13**.

In order to increase the apparent stiffness of the shoulder blocks **7a**, the shoulder axial groove **10** is preferably provided with a tie bar **17** rising from the bottom of the shoulder axial groove **10** and connecting the adjacent shoulder blocks.

In this embodiment, since the inner part **11** is small, it is preferable that the tie bar **17** is disposed near or adjacently to the shoulder main groove **4** as shown in FIG. 2 and FIG. 3(a). The depth **D6** of the shoulder axial groove **10** at the tie bar **17** is preferably set in a range of not less than 20%, more preferably not less than 30%, but not more than 90%, more preferably not more than 80% of the depth **D2** of the shoulder main groove **4**. The length **L6** of the tie bar **17** is preferably set in a range of not less than 30%, more preferably not less than 50%, but not more than 120%, more preferably not more than

100% of the block width w_2 of the inner part **11**. If the axial length L_6 of the tie bar **17** is more than 120%, the shearing force of the snow packed into the shoulder axial grooves **10** decreases.

Further, the inner part **11** may be provided with an inner sipe **27** extending from the shoulder main groove **4** toward the tread edge T_e and terminating without reaching to the shoulder secondary groove **13** so as to divide the circumferential dimension of the inner part **11** into two substantially equi-

parts. As shown in FIG. 4, it is preferable that the crown axial grooves **8** are crown sipes **18** whose width w_7 is 0.3 to 1.6 mm. In this embodiment, the crown sipes **18** are first crown sipes **18a** and second crown sipes **18b** which are alternately arranged in the tire circumferential direction.

The first crown sipes **18a** extend straight between the crown main grooves **3** while inclining to one circumferential direction.

The second crown sipes **18b** extend straight between the crown main grooves **3** while inclining to the other circumferential direction.

By the first crown sipes **18a** and second crown sipes **18b**, crown blocks **5a** having an isosceles triangular shape are divided. Since the crown axial grooves **8** have relatively narrow widths, it is possible to minimize the decrease in the rigidity of the crown land region **5** subjected to a large ground pressure during straight running. Accordingly, the steering stability on dry pavement can be maintained.

For that purpose, it is preferable that the width W_7 of the crown sipes **18** is decreased as far as possible. Therefore, the width w_7 is more preferably not less than 0.4 mm, but not more than 1.2 mm.

In order to derive the above mentioned effects, the depth of the crown sipe **18** is preferably set in a range of not less than 20%, more preferably not less than 30%, but not more than 90%, more preferably not more than 80% of the depth of the crown main groove **3**.

In order to effectively utilize the circumferential component of the edges, the angle θ_4 of the crown sipes **18** with respect to the tire circumferential direction is preferably set in a range of not less than 10 degrees, more preferably not less than 20 degrees, but not more than 80 degrees, more preferably not more than 70 degrees.

The angle θ_4 of the first crown sipes **18a** is set to be the same value as the angle θ_4 of the second crown sipes **18b** in order to even the rigidity of the crown blocks **5a**.

It is also preferable that the crown block **5a** is provided with a crown slot **19** extending straight from the crown main groove **3** toward the tire equator c to further increase the edges and thereby to improve on-the-snow performance.

If the crown slot **19** is too large, the rigidity of the crown block **5a** decreases.

Therefore, the width w_8 of the crown slot **19** is preferably not less than 1.0 mm, more preferably not less than 1.5 mm, but not more than 5.0 mm, more preferably not more than 4.0 mm.

The depth of the crown slot **19** is preferably not less than 1.0 mm, more preferably not less than 3.0 mm, but not more than 8.0 mm, more preferably not more than 7.0 mm.

In order to prevent the rigidity of the crown block **5a** from decreasing, it is preferable that the crown slots **19** on all of the crown blocks **5a** are substantially parallel with the first or second crown sipes.

The difference $|\theta_5 - \theta_4|$ between the angle θ_5 of the crown slots **19** and the above-mentioned angle θ_4 is preferably not more than 15 degrees, more preferably 0 degrees.

The crown block **5a** may be provided with a crown slot **19** and a crown cut **23**. The crown cut **23** has a narrow width and extends between the crown slot **19** and the crown axial groove **8** extending parallel with the crown slot **19**.

By the crown cuts **23**, the axially outer edge **5a1** of the crown block **5a** becomes uneven, and the snow grip performance can be improved although the crown main grooves **3** are a straight groove.

During straight running, the ground pressure in the middle land regions **6** becomes smaller than that in the crown land region **5**, therefore, it is permissible that the rigidity of the middle blocks **6a** is somewhat lower than the rigidity of the crown blocks **5a**. It is therefore, preferable that, as shown in FIG. 5, the middle axial grooves **9** include first middle sipes **20** having a narrow width w_9 as well as middle narrow grooves **21** having a wider width w_{10} . The width w_9 of the first middle sipes **20** is not less than 0.3 mm, preferably not less than 0.4 mm, but not more than 1.6 mm, preferably not more than 1.0 mm. The depth of the first middle sipes **20** is not less than 1.0 mm, preferably not less than 2.0 mm, but not more than 7.0 mm, preferably not more than 6.0 mm.

The width w_{10} of the middle narrow grooves **21** is more than 1.6 mm, preferably not less than 1.8 mm, but not more than 5.0 mm, preferably not more than 4.5 mm.

The depth D_7 of the middle narrow grooves **21** is not less than 1.0 mm, preferably not less than 2.0 mm, but not more than 8.0 mm, preferably not more than 7.0 mm.

As a result, by the wider middle narrow grooves **21**, on-the-snow performance such as snow grip can be improved, while retaining the apparent rigidity of the middle blocks **6a** as a whole owing to the narrow first middle sipes **20**.

In this embodiment, as shown in FIG. 5, the first middle sipes **20** and middle narrow grooves **21** are straight.

The angle θ_6 of the first middle sipes **20** with respect to the tire circumferential direction is preferably set in a range of not less than 20 degrees, more preferably not less than 30 degrees, but not more than 90 degrees, more preferably not more than 80 degrees.

The angle θ_7 of the middle narrow grooves **21** with respect to the tire circumferential direction is preferably set in a range of not less than 10 degrees, more preferably not less than 20 degrees, but not more than 90 degrees, more preferably not more than 80 degrees.

If the angle θ_6 becomes less than 20 degrees, the lateral stiffness (rigidity) of the middle blocks **6a** becomes insufficient.

If the angle θ_7 becomes less than 10 degrees, on-the-snow performance such traction and breaking force is deteriorated.

It is preferable that the angles θ_6 and θ_7 are smaller than the angle θ_4 of the first and second crown sipes **18a** and **18b**. Thereby, the middle blocks **6a** subjected to larger ground pressure during cornering, can be increased in the lateral stiffness (rigidity) relatively to the crown blocks **5a**, and the steering stability can be improved.

Further, each of the middle narrow grooves **21** may be provided in a central portion with a middle tie bar **21a** rising from the groove bottom to connect the adjacent blocks each other.

Further, it is preferable that each of the middle blocks **6a** is provided with a second middle sipe **22** extending straight from the crown main groove **3** or shoulder main groove **4** and terminating within the middle block **6a** in order to further increase the edge component of the middle block **6a** and thereby further improve on-the-snow performance.

The axial length L_8 of the second middle sipe **22** is preferably set in a range of not less than 10%, more preferably not less than 20%, but not more than 80%, more preferably not

TABLE 1-continued

D4/W4 (%)	80	80	80	80	80	80	30	50	70
distance L3 (mm)	13	13	13	13	13	13	13	13	13
distance L5 (mm)	5	5	1	2	7	9	5	5	5
<u>Steering stability</u>									
on snowy road	130	130	130	110	110	100	110	120	110
on dry pavement	80	75	80	95	105	105	100	100	100
<u>Snow performance</u>									
braking force	100	100	100	100	100	100	100	100	100
driving force	100	100	100	100	100	100	100	100	100

The invention claimed is

1. A pneumatic tire comprising

a tread portion provided on each side of the tire equator with an axially inner crown main groove and an axially outer shoulder main groove which extend continuously in the tire circumferential direction so that the tread portion is divided into a crown land region between the crown main grooves, a pair of middle land regions between the crown main grooves and the shoulder main grooves, and a pair of shoulder land regions between the shoulder main grooves and tread edges, wherein

the crown land region is provided with crown axial grooves which are narrow grooves and/or sipes extending across the entire width of the crown land region and arranged in a zigzag fashion so as to divide the crown land region into a plurality of crown blocks having triangular configurations,

the middle land regions are each provided with middle axial grooves which are narrow grooves and/or sipes extending across the entire width of the middle land region and arranged in a zigzag fashion so as to divide the middle land region into a plurality of middle blocks having triangular configurations,

the shoulder land regions are each provided with shoulder axial grooves extending across the entire width of the shoulder land region at an angle of not less than 70 degrees with respect to the tire circumferential direction so as to divide the shoulder land region into a plurality of shoulder blocks,

the shoulder blocks are each provided with a shoulder secondary groove extending at an angle of not more than 10 degrees with respect to the tire circumferential direction and disposed at a distance of 3 to 15 mm axially outward from the shoulder main groove so as to subdivide the shoulder block into an axially inner part and an axially outer part, and

the outer part is provided with shoulder sipes extending at an angle of not less than 70 degrees with respect to the circumferential direction, and

wherein:

said shoulder secondary groove extends straight, said shoulder secondary groove is provided in the bottom thereof with a groove-bottom sipe extending along the shoulder secondary groove,

the groove-bottom sipe has a width smaller than the width of the shoulder secondary groove,

one end of the groove-bottom sipe is a closed end located at a distance of 1.0 to 8.0 mm from one circumferential end of the shoulder secondary groove, and the other end of the same groove-bottom sipe is a closed end located at a

distance of 1.0 to 8.0 mm from the other circumferential end of the same shoulder secondary groove, between the axially inner parts of the shoulder blocks, a tie bar rising from the bottom of the shoulder axial groove therebetween is disposed,

the axial length L6 of the tie bar is not less than 30% and not more than 100% of the axial width Ws2 of the axially inner parts, and

said shoulder sipes in the axially outer part of the shoulder block extend from the tread edge toward the shoulder secondary groove and terminate without reaching the shoulder secondary groove.

2. the pneumatic tire according to claim 1, wherein the depth of the shoulder secondary groove is 0.5 to 7.0 mm.

3. The pneumatic tire according to claim 2, wherein the width of the shoulder secondary groove is more than its depth.

4. The pneumatic tire according to claim 2, wherein the crown axial grooves are sipes having a width of from 0.3 to 1.6 mm.

5. The pneumatic tire according to claim 2, wherein the crown blocks are each provided with a crown slot extending from the crown main groove toward the tire equator and terminating within the crown block.

6. The pneumatic tire according to claim 1, wherein the width of the shoulder secondary groove is more than its depth.

7. The pneumatic tire according to claim 6, wherein the crown axial grooves are sipes having a width of from 0.3 to 1.6 mm.

8. The pneumatic tire according to claim 1, wherein the crown axial grooves are sipes having a width of from 0.3 to 1.6 mm.

9. The pneumatic tire according to claim 1, wherein the crown blocks are each provided with a crown slot extending from the crown main groove toward the tire equator and terminating within the crown block.

10. The pneumatic tire according to claim 1, wherein the middle axial grooves are first middle sipes having a width of from 0.3 to 1.6 mm and middle narrow grooves having a width more than 1.6 mm and not more than 7.0 mm, and

the first middle sipes and the middle narrow grooves are arranged alternately in the tire circumferential direction.

11. The pneumatic tire according to claim 1, wherein the middle blocks are each provided with a second middle sipe extending from the crown main groove or the shoulder main groove and terminating within the middle block.

* * * * *