



US008827107B2

(12) **United States Patent**  
**Hakim**

(10) **Patent No.:** **US 8,827,107 B2**  
(45) **Date of Patent:** **Sep. 9, 2014**

(54) **NO-SPILL DRINKING CUP APPARATUS**

(75) Inventor: **Nouri E. Hakim**, Monroe, LA (US)

(73) Assignee: **Luv n' care, Ltd.**, Monroe, LA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 16 days.

(21) Appl. No.: **13/346,777**

(22) Filed: **Jan. 10, 2012**

(65) **Prior Publication Data**

US 2012/0175378 A1 Jul. 12, 2012

**Related U.S. Application Data**

(63) Continuation of application No. 11/981,851, filed on Oct. 31, 2007, now Pat. No. Re. 43,077, which is an application for the reissue of Pat. No. 6,321,931, application No. 13/346,777, which is a continuation of application No. 12/877,021, filed on Sep. 7, 2010, which is a continuation of application No. 11/787,672, filed on Apr. 17, 2007, now Pat. No. 7,789,263, which is a continuation of application No. 10/001,257, filed on Nov. 27, 2001, now Pat. No. 7,204,386, which is a continuation of application No. 09/138,588, filed on Aug. 21, 1998, now Pat. No. 6,321,931, said application No. 12/877,021 is a continuation of application No. 11/825,793, filed on Jul. 9, 2007, now Pat. No. 7,789,264, which is a continuation of application No. 10/083,656, filed on Feb. 25, 2002, now Pat. No. 7,243,814, which is a continuation of application No. 09/271,779, filed on Mar. 18, 1999, now Pat. No. 6,357,620, which is a continuation-in-part of application No. 09/138,588, filed on Aug. 21, 1998, now Pat. No. 6,321,931, said application No. 12/877,021 is a continuation of application No. 12/797,061, filed on Jun. 9, 2010, which is a continuation-in-part of application No. 11/787,672, filed on Apr. 17, 2007, now Pat. No. 7,789,263, which is a continuation of application No.

10/001,257, filed on Nov. 27, 2001, now Pat. No. 7,204,386, which is a continuation of application No. 09/138,588, filed on Aug. 21, 1998, now Pat. No. 6,321,931.

(60) Provisional application No. 60/056,218, filed on Aug. 21, 1997.

(51) **Int. Cl.**  
*A47G 19/22* (2006.01)  
*B65D 51/16* (2006.01)  
*B65D 47/20* (2006.01)  
*F16K 7/12* (2006.01)


(52) **U.S. Cl.**  
CPC ..... *A47G 19/2272* (2013.01); *B65D 51/165* (2013.01); *B65D 47/2031* (2013.01); *F16K 7/12* (2013.01)  
USPC ..... **220/714**; 220/203.18; 251/331; 222/547; 222/561

(58) **Field of Classification Search**  
CPC ..... *A47G 19/2272*; *A47G 19/2266*; *A47G 19/2205*; *A61J 11/002*; *A61J 11/001*; *B65D 47/2031*; *B65D 47/2018*; *B65D 51/165*; *B65D 51/1644*; *B65D 51/1633*; *F16K 7/12*; *F16K 7/14*  
USPC ..... 220/714, 711, 717, 716, 202, 203.01, 220/203.29, 203.28, 203.19, 203.11, 703, 220/694, 200, 203.18, 203.16; 215/11.4, 215/387, 260, 261, 11.1, 200; 222/494, 222/491, 547, 561, 559; 137/859, 852, 843, 137/511; D9/449, 447, 435; 251/331, 358  
IPC ..... *A47G 19/22*  
See application file for complete search history.

(56) **References Cited**  
U.S. PATENT DOCUMENTS

1,560,689 A 11/1925 Holt et al.  
1,954,748 A 4/1934 Punta et al.

(Continued)



FOREIGN PATENT DOCUMENTS

AU	254125	7/1963
CN	2163761	5/1994

(Continued)

OTHER PUBLICATIONS

*Luv n' care, Ltd. v. Koninklijke Philips Electronics N.V., et al.*, 2:11-cv-00512-JRG-RSP (E.D. Tex.): Feb. 19, 2013 Plaintiff Luv n' care's Opening Claim Construction Brief as to Construction of Luv n' care's Patents-In-Suit, and Exhibits 6-27 thereto.

(Continued)

*Primary Examiner* — Robert J Hicks

(74) *Attorney, Agent, or Firm* — Goldberg Cohen LLP

(57)

**ABSTRACT**

An improved no-spill cup construction and valve assembly which provides an extremely secure seal against accidental liquid flow from the cup spout. The act of sucking at the cup spout creates negative pressure or a partial vacuum against a valve near the spout, causing the valve to open and allowing the flow of liquid therethrough.

**12 Claims, 14 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

2,107,442 A 2/1938 Hughes  
 2,174,361 A 9/1939 Condon  
 2,223,179 A 11/1940 Longheed  
 2,250,266 A 7/1941 Kaye  
 2,584,359 A 2/1952 Miles  
 3,206,079 A 9/1965 Mancusi, Jr.  
 3,263,850 A \* 8/1966 Scott ..... 215/261  
 3,292,808 A \* 12/1966 Greene ..... 215/11.5  
 3,321,114 A 5/1967 Croyle  
 3,346,133 A \* 10/1967 Herdman ..... 215/11.1  
 3,360,169 A 12/1967 Susuki et al.  
 3,409,160 A \* 11/1968 Scott ..... 215/261  
 3,618,825 A 11/1971 Clarke  
 3,718,140 A 2/1973 Yamauchi  
 3,840,153 A 10/1974 Devlin  
 3,860,162 A 1/1975 Schutz  
 3,915,331 A 10/1975 Chenault  
 4,102,476 A 7/1978 Loeffler  
 4,135,513 A 1/1979 Arisland  
 4,186,842 A 2/1980 Albert  
 4,226,342 A 10/1980 Laauwe  
 4,324,097 A 4/1982 Schmitt et al.  
 4,414,973 A 11/1983 Matheson  
 4,474,314 A 10/1984 Roggenberg  
 4,506,809 A 3/1985 Corsette  
 4,533,062 A 8/1985 Krautkramer  
 4,545,491 A 10/1985 Bisgaard et al.  
 4,600,111 A 7/1986 Brown  
 4,623,069 A 11/1986 White  
 4,624,286 A 11/1986 Frohn  
 4,646,781 A 3/1987 McIntyre et al.  
 4,685,577 A \* 8/1987 Chen ..... 215/11.5  
 4,801,027 A 1/1989 Hunter  
 4,836,404 A 6/1989 Coy  
 4,850,496 A 7/1989 Rudell  
 4,871,077 A 10/1989 Ogden et al.  
 4,941,598 A 7/1990 Lambelet, Jr. et al.  
 4,946,062 A 8/1990 Coy  
 4,993,568 A 2/1991 Morifuji et al.  
 5,033,647 A 7/1991 Smith et al.  
 5,050,758 A 9/1991 Freeman et al.  
 5,079,013 A \* 1/1992 Belanger ..... 426/115  
 5,101,991 A 4/1992 Morifuji et al.  
 5,101,992 A 4/1992 Serre  
 5,176,271 A \* 1/1993 Painchaud et al. .... 215/261  
 5,186,347 A 2/1993 Freeman et al.  
 5,213,236 A \* 5/1993 Brown et al. .... 222/212  
 D339,197 S 9/1993 Ziegler  
 5,244,105 A 9/1993 Serre  
 5,250,266 A 10/1993 Kanner  
 5,273,172 A \* 12/1993 Rossbach et al. .... 215/229  
 5,339,995 A \* 8/1994 Brown et al. .... 222/173  
 RE34,725 E 9/1994 Braden  
 5,363,983 A 11/1994 Proshan  
 5,377,877 A \* 1/1995 Brown et al. .... 222/105  
 5,388,615 A 2/1995 Edlund et al.  
 5,392,949 A 2/1995 McKenna  
 5,409,144 A \* 4/1995 Brown ..... 222/185.1  
 5,433,328 A 7/1995 Baron et al.  
 5,439,143 A \* 8/1995 Brown et al. .... 222/185.1  
 5,472,122 A 12/1995 Appleby  
 5,542,670 A \* 8/1996 Morano ..... 220/714  
 5,582,315 A 12/1996 Reid  
 5,607,073 A \* 3/1997 Forrer ..... 215/11.4  
 5,609,582 A 3/1997 Krutten  
 5,626,262 A 5/1997 Fitten  
 5,651,471 A 7/1997 Green  
 5,676,289 A 10/1997 Gross  
 5,702,025 A 12/1997 Di Gregorio  
 5,706,973 A \* 1/1998 Robbins et al. .... 220/714  
 5,769,285 A 6/1998 Upham et al.  
 5,784,999 A 7/1998 Larson et al.  
 5,788,097 A 8/1998 McInnes  
 5,791,510 A 8/1998 Paczonay  
 5,797,505 A 8/1998 Kaura

5,839,614 A \* 11/1998 Brown ..... 222/185.1  
 5,890,619 A \* 4/1999 Belanger ..... 220/713  
 5,890,620 A \* 4/1999 Belcastro ..... 220/714  
 5,890,621 A \* 4/1999 Bachman et al. .... 220/717  
 5,893,472 A \* 4/1999 Forrer ..... 215/11.4  
 5,897,013 A \* 4/1999 Manganiello ..... 220/252  
 6,050,445 A 4/2000 Manganiello  
 6,089,418 A 7/2000 Gaiser  
 6,112,919 A 9/2000 Ho  
 6,116,457 A 9/2000 Haberman  
 6,161,710 A 12/2000 Dieringer et al.  
 RE37,016 E 1/2001 Morano  
 6,230,923 B1 5/2001 Hung  
 6,269,968 B1 8/2001 Belcastro  
 6,305,570 B1 10/2001 Atkin et al.  
 6,321,931 B1 11/2001 Hakim  
 6,343,704 B1 2/2002 Prentiss  
 6,994,225 B2 2/2006 Hakim  
 7,204,386 B2 4/2007 Hakim  
 7,243,814 B2 7/2007 Hakim  
 7,789,263 B2 9/2010 Hakim  
 7,789,264 B2 9/2010 Hakim  
 2002/0011583 A1 1/2002 Getzewich et al.  
 2002/0063103 A1 5/2002 Kiernan

FOREIGN PATENT DOCUMENTS

DE 450685 10/1927  
 DE 678886 7/1939  
 DE 1018740 10/1957  
 DE 6946466 2/1970  
 DE 2024427 12/1971  
 DE 2634226 2/1978  
 DE 27 04 164 8/1978  
 DE 295 00 819.9 3/1995  
 DE 195 10 007 10/1995  
 DE 296 08 342 7/1996  
 DE 297 06 653 7/1997  
 EM 0388828 9/1990  
 EM 0388828 A1 9/1990  
 EM 0 473 994 3/1992  
 FR 695291 12/1930  
 FR 780094 4/1935  
 FR 1191181 10/1959  
 FR 2 305 361 10/1976  
 FR 2373740 7/1978  
 FR 2602593 4/1988  
 FR 2717778 9/1995  
 GB 379428 9/1932  
 GB 752796 7/1956  
 GB 1301755 1/1973  
 GB 1448427 9/1976  
 GB 1 593 084 7/1981  
 GB 2 169 210 7/1986  
 GB 2 215 318 9/1989  
 GB 2258860 A 2/1993  
 GB 2 266 045 10/1993  
 GB 2 279 130 12/1994  
 GB 2304545 A 3/1997  
 IT 594286 A 5/1959  
 NL 1 005 120 7/1998  
 WO 9429187 12/1994  
 WO 95/10965 4/1995  
 WO 98/17157 4/1998  
 WO 99/38423 8/1999

OTHER PUBLICATIONS

*Luv n' care, Ltd. v. Koninklijke Philips Electronics N.V., et al.*, 2:11-cv-00512-JRG-RSP (E.D. Tex.): Mar. 4, 2013 Defendants' Responsive Claim Construction Brief Relating to LNC's Asserted Patents, and Exhibits 1-11 thereto.  
*Luv n' care, Ltd. v. Koninklijke Philips Electronics N.V., et al.*, 2:11-cv-00512-JRG-RSP (E.D. Tex.): Mar. 11, 2013 Plaintiff Luv n' care's Reply Brief as to Construction of Luv n' care's Patents-In-Suit, and Exhibits 2-3 thereto.  
*Luv n' care, Ltd. v. Koninklijke Philips Electronics N.V., et al.*, 2:11-cv-00512-JRG-RSP (E.D. Tex.): Mar. 15, 2013 Joint Claim Construction Chart.

(56)

**References Cited**

## OTHER PUBLICATIONS

*Luv n' care, Ltd. v. Koninklijke Philips Electronics N.V., et al.*, 2:11-cv-00512-JRG-RSP (E.D. Tex.): Official Transcript from Mar. 21, 2013 Markman Hearing.

*Luv n' care, Ltd. v. Koninklijke Philips Electronics N.V., et al.*, 2:11-cv-00512-JRG-RSP (E.D. Tex.): Mar. 25, 2013 Plaintiff Luv n' care's Notice of Additional Evidence as to Construction of Luv n' care's Patents-In-Suit, and Exhibits 1-9 thereto.

*Luv n' care, Ltd. v. Koninklijke Philips Electronics N.V., et al.*, 2:11-cv-00512-JRG-RSP (E.D. Tex.): Jul. 9, 2013 Claim Construction Memorandum and Order.

*Hakim v. Cannon Avent Group, PLC*, 479 F.3d 1313 (Fed Cir. 2007).  
Metzstein, A Mugs Game, The Independent, Jun. 30, 1996, United Kingdom.

Oct. 11, 2009 Decision of European Patent Office in Opposition to Patent Application No. EP 99 943 860.9.

Magistrate's Report and Recommendation of Feb. 2, 2005 re U.S. Patent No. 6,321,931, (U.S. District Court, W.D. Louisiana, Civ. 3-02-1371).

Magistrate's Report and Recommendation of Feb. 2, 2005 re U.S. Patent No. 6,357,620, (U.S. District Court, W.D. Louisiana, Civ. 3-02-1371).

Nov. 6, 1998 International Search Report from PCT/US98/17379.

Dec. 1, 1999 International Search Report from PCT/US99/19238.

Nov. 27, 2000 EPO Search from EP98943302.

Sep. 12, 2008 EPO Search from EP 06 00 9518.

Dec. 11, 2007 EPO Search from EP 07 01 5953.

Oct. 8, 2002 EPO Search from EP 99 94 3860.

Oct. 24, 2012 Invalidity Contentions of Defendants in litigation captioned *Luv n' care, Ltd. v. Koninklijke Philips Electronics N.V. et al.*, C.A. No. 2:11-cv-00512-JRG-RSP (E.D. Tex.).

Oct. 24, 2012 Appendix a to Invalidity Contentions of Defendants in litigation captioned *Luv n' care, Ltd. v. Koninklijke Philips Electronics N.V. et al.*, C.A. No. 2:11-cv-00512-JRG-RSP (E.D. Tex.).

Oct. 24, 2012 Appendix B to Invalidity Contentions of Defendants in litigation captioned *Luv n' care, Ltd. v. Koninklijke Philips Electronics N.V. et al.*, C.A. No. 2:11-cv-00512-JRG-RSP (E.D. Tex.).

Oct. 24, 2012 Appendix C to Invalidity Contentions of Defendants in litigation captioned *Luv n' care, Ltd. v. Koninklijke Philips Electronics N.V. et al.*, C.A. No. 2:11-cv-00512-JRG-RSP (E.D. Tex.).

Oct. 24, 2012 Appendix D to Invalidity Contentions of Defendants in litigation captioned *Luv n' care, Ltd. v. Koninklijke Philips Electronics N.V. et al.*, C.A. No. 2:11-cv-00512-JRG-RSP (E.D. Tex.).

Oct. 24, 2012 Appendix E to Invalidity Contentions of Defendants in litigation captioned *Luv n' care, Ltd. v. Koninklijke Philips Electronics N.V. et al.*, C.A. No. 2:11-cv-00512-JRG-RSP (E.D. Tex.).

\* cited by examiner






FIG. 1(A)




FIG. 1(B)

FIGURE 1





FIG. 2(B)

FIGURE 2

FIG. 2(A)










FIG. 5(A)




FIG. 5(B)

FIGURE 5




FIG. 6(E)




FIG. 6(C)




FIG. 6(A)




FIG. 6(B)




FIG. 6(D)

FIGURE 6




FIGURE 7









FIG. 8(C)

FIG. 8(B)




FIGURE 8







FIGURE 9




FIGURE 10






FIG. 11(A)




FIG. 11(B)




FIG. 11(C)

FIGURE 11




FIG. 12(A)




FIG. 12(B)




FIG. 12(C)

FIGURE 12




FIGURE 13






FIGURE 14

## NO-SPILL DRINKING CUP APPARATUS

## RELATED APPLICATIONS

The present application is a continuation of U.S. Nonprovisional application Ser. No. 11/981,851 filed Oct. 31, 2007 (patented, U.S. Pat. No. RE 43,077), which is a reissue application of U.S. Nonprovisional application Ser. No. 09/138,588 filed Aug. 21, 1998 (patented, U.S. Pat. No. 6,321,931), which claims the benefit of U.S. Provisional Application Ser. No. 60/056,218 filed Aug. 21, 1997.

The present application is also a continuation of U.S. Nonprovisional application Ser. No. 12/877,021 filed Sep. 7, 2010 (pending) ("the '021 application"), which is a continuation of U.S. Nonprovisional application Ser. No. 11/787,672 filed Apr. 17, 2007 (patented, U.S. Pat. No. 7,789,263), which is a continuation of U.S. Nonprovisional application Ser. No. 10/001,257 filed Nov. 27, 2001 (patented, U.S. Pat. No. 7,204,386) which is a continuation of U.S. Nonprovisional application Ser. No. 09/138,588 filed Aug. 21, 1998 (patented, U.S. Pat. No. 6,321,931), which claims the priority of U.S. Provisional Application Ser. No. 60/056,218 filed Aug. 21, 1997.

The '021 application is also a continuation of U.S. Nonprovisional application Ser. No. 11/825,793 filed Jul. 9, 2007 (patented, U.S. Pat. No. 7,789,264), which is a continuation of U.S. Nonprovisional application Ser. No. 10/083,656 filed Feb. 25, 2002 (patented, U.S. Pat. No. 7,243,814), which is a continuation of U.S. Nonprovisional application Ser. No. 09/271,779 filed Mar. 18, 1999 (patented, U.S. Pat. No. 6,357,620), which is a continuation-in-part of U.S. Nonprovisional application Ser. No. 09/138,588 filed Aug. 21, 1998 (patented, U.S. Pat. No. 6,321,931), which claims the priority of U.S. Provisional Application Ser. No. 60/056,218 filed Aug. 21, 1997.

The '021 application is also a continuation of U.S. Nonprovisional application Ser. No. 12/797,061 filed Jun. 9, 2010 (pending), which is a continuation-in-part of U.S. Nonprovisional application Ser. No. 11/787,672 filed Apr. 17, 2007 (patented, U.S. Pat. No. 7,789,263), which is a continuation of U.S. Nonprovisional application Ser. No. 10/001,257 filed Nov. 27, 2001 (patented, U.S. Pat. No. 7,204,386), which is a continuation of U.S. Nonprovisional application Ser. No. 09/138,588 filed Aug. 21, 1998 (patented, U.S. Pat. No. 6,321,931), which claims the priority of U.S. Provisional Application Ser. No. 60/056,218 filed Aug. 21, 1997.

The '021 application is also a continuation of U.S. Nonprovisional Ser. No. 12/797,061 filed Jun. 9, 2010 (pending), which is a continuation of U.S. Nonprovisional application Ser. No. 11/825,793 filed Jul. 9, 2007 (patented, U.S. Pat. No. 7,789,264), which is a continuation of U.S. Nonprovisional application Ser. No. 10/083,656 filed Feb. 25, 2002 (patented, U.S. Pat. No. 7,243,814), which is a continuation of U.S. Nonprovisional application Ser. No. 09/271,779 filed Mar. 18, 1999 (patented, U.S. Pat. No. 6,357,620), which is a continuation-in-part of U.S. Nonprovisional application Ser. No. 09/138,588 filed Aug. 21, 1998 (patented, U.S. Pat. No. 6,321,931), which claims the priority of U.S. Provisional Application Ser. No. 60/056,218 filed Aug. 21, 1997.

The priority of all of those applications is claimed, all of which are fully incorporated herein by reference.

## FIELD OF THE INVENTION

The present invention relates to a no-spill cup assembly with an improved valve mechanism to prevent liquid from flowing out of the cup when not desired.

## BACKGROUND OF THE INVENTION

No-spill cup assemblies are well known in the art. In the past, a variety of such assemblies have been developed and marketed. In general, the goal of a no-spill cup is to provide a construction which minimizes or prevents liquid from emerging out of the cup when liquid flow is not desired, i.e. when the user is not drinking. However, though the assemblies of the prior art are intended to avoid such accidents, their construction is such that they generally do not provide a secure enough protection against undesirable spilling or leakage. Thus, when such cups are inverted, or more significantly, when they are shaken vigorously, liquid will often emerge from them. This can be a particular problem with young children, for whom these cups are usually intended. Accordingly, there is a need in the art for an improved cup assembly for preventing undesired spilling of liquids.

## SUMMARY OF THE INVENTION

It is an object of the present invention to provide an improved no-spill cup assembly.

It is a further object of the present invention to provide a cup assembly which prevents liquid from flowing out of the cup when the user is not drinking.

It is a further object of the invention to provide a cup assembly which minimizes and/or eliminates accidental or undesirable liquid flow or spillage out of the cup.

It is a further object of the invention to provide a cup assembly which provides the ability to regulate the flow rate of liquid out of the cup.

It is a further object of the invention to provide a cup assembly which can be used by young children, to avoid accidental spilling of liquid therefrom.

Further objects of the invention will become apparent in conjunction with the disclosure herein.

In accordance with the invention, an improved cup construction and valve assembly is provided which provides an extremely secure seal against accidental liquid flow from the cup spout. Further to the invention, a user places his or her mouth against the spout of the cup assembly to suck liquid out of the cup when desired. The act of sucking at the spout of the cup creates negative pressure or a partial vacuum against a valve in the cup spout, causing the valve to invert, or turn inside out, either partially or totally, thereby unblocking an opening such as an orifice or slit in the valve. Once the opening is unblocked, liquid can flow freely through the valve and spout.

In contrast, when not in use, the valve sits in a resting, closed position, with the valve pressed against the center seal-off, thereby sealing off the opening or slit in the valve assembly. Thus, in its relaxed state, with no negative pressure applied, the valve sits in a closed position with the fluid opening sealed by the center seal-off. Moreover, in accordance with the dual valve nature of the device in the preferred embodiment, an adjacent valve similarly seals when no negative pressure is applied, thereby blocking off the air vents in the cover of the cup, and further preventing the possibility of fluid flow. Consequently, the closed position provides an extremely secure seal against fluid leakage, such that inadvertent spills or even deliberate attempts to force liquid outside of the cup, such as by turning the cup upside down, or shaking the cup, are ineffective.

In a further embodiment of the invention, the cup assembly allows liquid flow to be regulated between regular or maximum flow and minimal flow levels or rates by rotating the position of a valve assembly in the cap or cover of the cup. The



valve holder is constructed as a two subunit assembly, with one subassembly holding a valve with a larger slit or orifice for fluid flow than the valve in the second subunit. Thus, upon rotation of the valve holder, either a low-flow valve or a higher flow valve can be positioned in the hole leading to the spout. In this manner, a dual position valve assembly is provided allowing either regular flow or minimal liquid flow conditions.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1(a) is an exploded front view of a no-spill cup assembly in accordance with the present invention. FIG. 1(b) is an exploded perspective view of the no-spill cup assembly of FIG. 1(a).

FIG. 2(a) is an exploded front view of a second embodiment of a no-spill cup assembly in accordance with the present invention.

FIG. 2(b) is an exploded perspective view of the no-spill cup assembly of FIG. 2(a).

FIG. 3 is a perspective view of the valve assembly of the present invention.

FIG. 4 is an exploded, perspective view of another embodiment of the valve assembly of the no-spill cup, in accordance with the present invention.

FIG. 5(a) is an exploded front view of the cup assembly of the present invention, showing the rotation of the valve holder or assembly, into two alternate positions for placement in the cap or cover of the cup.

FIG. 5(b) is an exploded perspective view, showing the placement of the valve holder into the cap, in either of the two positions illustrated in FIG. 5(a).

FIG. 6 is a series of additional views of the valve holder or assembly of FIG. 3.

FIG. 6(a) is a top view of the valve holder.

FIG. 6(b) is a front view of the valve holder.

FIG. 6(c) is a side view of the valve holder.

FIG. 6(d) is a cross-sectional view of the valve holder wherein the valve is in a relaxed state, sealing off fluid flow.

FIG. 6(e) is a cross-sectional view of the valve holder, showing the valve in an inverted state, to allow fluid flow through the valve.

FIG. 7 is an exploded, perspective view of another embodiment of the valve assembly of the no-spill cup, in accordance with the present invention.

FIG. 8 is a series of additional views of a further embodiment of the valve assembly shown in FIG. 6.

FIG. 8(a) is a top view of the valve holder or assembly.

FIG. 8(b) is a front view of the valve holder.

FIG. 8(c) is a side view of the valve holder.

FIG. 8(d) is a cross-sectional view of the valve holder wherein the valve is in a relaxed state, sealing off fluid flow.

FIG. 8(e) is a cross-sectional view of the valve holder, showing the valve in an inverted state, to allow fluid flow through the valve.

FIG. 9 is a series of additional views of another embodiment of the valve assembly shown in FIG. 8.

FIG. 9(a) is a top view of the valve holder or assembly.

FIG. 9(b) is a front view of the valve holder.

FIG. 9(c) is a side view of the valve holder.

FIG. 9(d) is a cross-sectional view of the valve holder wherein the valve is in a relaxed state, sealing off fluid flow.

FIG. 9(e) is a cross-sectional view of the valve holder, showing the valve in an inverted state, to allow fluid flow through the valve.

FIG. 10 is a side view of a no-spill cup with a soft gripping area, in accordance with the present invention.

FIG. 11 is a series of additional views of another embodiment of the cap of the present invention.

FIG. 11(a) is a partial sectional view of a cap with an insert molded or glued in gasket, in accordance with the invention.

FIG. 11(b) is a side sectional view of the cap of FIG. 11(a).

FIG. 11(c) is a top sectional view of the cap of FIG. 11(b).

FIG. 12 is a series of additional views of another embodiment of the cap of the present invention.

FIG. 12(a) is a partial sectional view of a cap with a molded lip which wedges against into the inside surface of the cup, in accordance with the invention.

FIG. 12(b) is a side sectional view of the cap of FIG. 12(a).

FIG. 12(c) is a top sectional view of the cap of FIG. 12(b).

FIG. 13 is a side sectional view of a cap having a soft spout, in accordance with a further embodiment of the invention.

FIG. 14 is a side sectional view of a cap having a reduced volume spout, in accordance with a further embodiment of the invention.

#### DETAILED DESCRIPTION OF THE INVENTION AND THE PREFERRED EMBODIMENTS

As will be shown in conjunction with the attached drawings, a novel cup assembly is disclosed for providing prevention against accidental liquid spills. FIGS. 1(a) and 1(b) are a front view and a perspective view, respectively, of an embodiment of the cup assembly, in accordance with the present invention. The volume of the cup or liquid holding portion of the assembly can be adjusted as desired. In one embodiment, a 7 oz. drinking cup is provided, as shown in FIG. 1. Alternatively, a 9 oz. drinking cup, as shown in FIG. 2, a 6½ oz. cup, or any other desired size can be provided, as well.

The sides of the cup can be provided with no handles, one handle, two handles or any other number of handles, for the user's use to grip the cup. This handle or handle is preferably sized for a child's hands. In addition, the outside appearance of the cup and/or the cap can be a solid color, or can be printed with any desired design.

In a further embodiment of the invention, a no spill cup with a soft gripping area can be provided, as shown in FIG. 10. In accordance with this embodiment, a soft ring 102 is provided around the outside of the cup. This ring can be of any width desired, and serves as a finger grip, to make it easier to grasp the cup securely. Preferably, the ring is approximately two inches (2") wide. In a preferred embodiment, the soft ring 102 has shapes or designs 106 cut out of it, such as stars, ovals, or so forth. The hard cup, in turn, has raised areas or protuberances corresponding to those shapes or designs. The soft ring fits snugly over these raised areas of the cup, each of the protruding hard shapes fitting into the cutouts of the soft ring, with the surface of the raised areas and the soft ring being flush when the ring is inserted onto the cup.

In one embodiment of the invention, the cup is constructed from polycarbonate. In an alternate embodiment, the cup is constructed from polypropylene. If desired, clear polypropylene can be utilized. Alternatively, any other suitable materials can be used for the components of the no-spill cup. The components of the cup are all made of durable materials, resistant to breakage, dishwasher safe, and preferably color fast.

In accordance with the invention, cup 7 includes a no-spill cap or cover 11, a valve holder or assembly 31 and tumbler cup 22. No-spill cap 11 includes a spout 14 for drinking liquid from the cup. The spout is sized to allow an individual to place his or her mouth over the spout to drink therefrom. In the preferred embodiment, the spout is sized for the mouth of a child, particularly for a child of a young age.



No-spill cap **11** forms a cover for placement over tumbler cup **22**. When attached to the cup **22**, a secure seal is formed such that no liquid can emerge through the connection between the cap **11** and cup **22**. In use, cap **11** is sufficiently secured to cup **22** such that shaking the cup assembly, dropping the cup on the floor, or other vigorous movement of the cup assembly, or application of sharp force thereto, is insufficient to separate the cap from the cup.

In one embodiment, no-spill cap **11** and tumbler cup **22** include mating male and female screw threads, such that the cap **11** is a screw-on cap which can be easily rotated onto the tumbler cup **22**, as shown in FIG. 2. In an alternative embodiment, a snap-on cap is used, as shown in FIG. 1. In this embodiment, a resilient ring portion of cap **11** securely fits over lip **10** of tumbler cup **22**, as is well known in the art. Although a screw-on cap or a snap-on cap are shown as two preferred embodiments, alternatively, any other suitable mechanism to secure the cap to the tumbler cup can be utilized.

Either the screw-on cap and/or the snap-on cap can be further provided with a gasket **110** between the tumbler cup and the cap, to further seal the connection between the cup and the cap. This gasket can be part of the tumbler cup **22** or the cap **11**, or can be a separate element inserted between the cap and the cup. In a preferred embodiment, the gasket **110** is part of cap **11**, as shown in FIGS. 11(a)-(c).

Alternatively, the cap can be provided with a small annular inner lip, on the inside of the cap, which acts as a gasket. This lip, as shown in FIGS. 12(a)-(c), wedges inside the cup when the cap is screwed or placed upon it. The lip acts to further prevent the possibility of liquid flow through the contact between the cup and the cap.

In a preferred embodiment, finger grips **12** are provided on the outside of the cap, such as grooves or the like. These grips facilitate removal and application of the cap, particularly in embodiments requiring the screwing of the cap on and off of the cup.

The cap is also preferably interchangeable with numerous tumbler cups of different sizes. In this embodiment, the rim of the tumbler cups are all of the same diameter, although the tumbler cups themselves are of different volumes. For example, the same sized cap could be used on a 6½ oz. cup and/or a 7 oz. cup and/or a 9 oz. cup, and so forth.

In a further embodiment of the cap, the cap has a soft spout **130** as shown in FIG. 13. Preferably, the spout is made of a thermo-elastimer. Spout **130** can be insert molded to a polypropylene cap, providing a combination cap having a hard section for attachment to the cup, and a soft spout portion. Preferably, the spout has a small channel extending therethrough to reduce the liquid volume which can be trapped within the spout portion.

In a further embodiment of the cap, the cap has a reduced volume spout as shown in FIG. 14. Reduced volume spout **140** is designed to reduce the volume of liquid which can be trapped within the spout. Reduced volume spout **140** has a volume reduction member **144** inserted therein to reduce the internal volume of the spout, and to provide a channel **148** for liquid flow. Preferably, valve assembly subunit **142** extends up into spout **140** to further reduce the amount of liquid which can be trapped in spout **140**. Valve assembly subunit **142** can, for example, extend into volume reduction member **144**. Accordingly, this embodiment reduces the space between the valve and the opening of the drinking spout, to reduce the amount of liquid potentially trapped in this area.

As shown in FIG. 1(b), no-spill cap **11** includes valve assembly carriers **16** and **18**. In the preferred embodiment, valve assembly carriers **16** and **18** are tapered holes provided

on the underside of the cap. Valve assembly carrier or tapered hole **18** leads to an open spout **14**, providing a path for liquid flow. Thus, valve assembly carrier or hole **18** is fully open on both sides, both on its top surface, which leads to spout **14**, and on its bottom surface opposite tumbler cup **22**, for the flow of liquid out of tumbler cup **22** through hole **18** and through spout **14** into the user's mouth.

Valve assembly carrier or tapered hole **16**, in contrast, provides a passage for the flow of air into the cup during use, allowing liquid to exit through opposing hole **18** and spout **14**. Hole **16** is open on one side, i.e. on its lower surface opposite tumbler cup **22**. On the opposing side, hole **16** merges into the inner surface of cap **11**. The inner surface of cap **11** is further provided with one or more, preferably small, vents or holes for air flow, allowing air to flow through the vents of cap **11** and through hole **16** into the cup assembly during use.

As shown in FIGS. 1 and 2, no-spill cup **7** further includes valve holder or assembly **31**. Valve holder **31** is preferably constructed from a high temperature ABS material, and is dimensioned to fit snugly into cap **11**. In the preferred embodiment, valve holder is a separate assembly which fits into cap **11**. Alternatively, the valve holder can be provided as an integral part of cap **11** and/or cup **7**. For example, valve holder **31** can be molded as a part of cap **11**, such that the valve holder is inseparable from the cap.

In the preferred embodiment, valve holder **31** is a two-subunit assembly connected by bridge **34**. Each subunit of the two-subunit assembly is sized to frictionally fit into and be held by either one of tapered holes **16** and **18**. The spacing between tapered holes **16** and **18** is the same as between the subunits of valve holder **31**, such that the valve holder can be easily secured within cap **11**. The sizing and tapering of holes **16** and **18** and the sizing of valve holder **31** are dimensioned so as to provide a secure, snug mating between the valve assembly and the tapered holes. In a preferred embodiment, the top of the valve holder (i.e. the side facing the spout) and the bottom of the valve holder (i.e. the side facing the cup) has two different diameters. The top is proportioned to fit snugly into the tapered hole, and the bottom is proportioned such that it cannot be inserted into hole **16** or **18**. In this way, a mechanism is provided to prevent the valve holder from being inserted into the holes in the wrong orientation, i.e. upside down.

FIG. 3 is an enlarged, exploded, perspective view of the valve holder of the present invention. Valve holder **31** consists of two valve holder subunits **37** and **39**, connected by a bridge **34**. Each valve holder subunit is intended to hold a single valve therein. As shown in the figure, valve or valve member **42** is intended for placement in subunit **37**, and valve or valve member **45** is intended for placement in subunit **39**. Valves **42** and **45** each include a slit for the passage of liquid. The slit is preferably through the center portion of the valve, and is dimensioned to allow a predetermined flow level or rate of liquid therethrough, as desired.

Valve holder subunits **37** and **39** open into sealing units **37a** and **39a** and valve retainers or endcaps **37b** and **39b**, respectively. Taking subunit **37** as an example of the function of each subunit, as shown in FIG. 3, subunit **37** is initially in an open position in which the sealing unit and the valve retainer have been pulled or hinged apart. In one embodiment, the sealing unit and the valve retainer have a tab **60** connecting them, to prevent the components from being permanently separated accidentally. Alternatively, the valve retainer can be welded into place (e.g. by sonic welding), as shown in FIGS. 4 and 7. The sealing units each have at least one open section **58**, such that, in the valve assembly's disassembled state, fluid can pass, unobstructed, through the sealing unit since no valve is



in place. Likewise, the valve retainers are open on both sides for unobstructed passage of fluid through the valve retainer in the disassembled state when no valve is in place.

To assemble the valve assembly, valve **42** is inserted into the valve holder by placement of the valve between sealing unit **37a** and valve retainer **37b**. After a valve has been placed into one or both of the subunits, the valve retainers can each be folded or hinged back about tab **60**, over the sealing unit **37** (or under sealing unit **39**, in the orientation shown in the figure) and snapped into place to close the subunits, as shown in FIG. **5**. The resilience of the sealing unit allows for a tight seal to be established between the valve retainer and the sealing unit. When closed, each subunit secures or encapsulates a valve tightly therein, maintaining the valve in place in the valve holder. For clarity, reference is primarily made to subunit **37**, although subunits **37** and **39** are preferably the same in all features other than the size of the valve opening. For the purposes of the present discussion, it is assumed that subunit **37** is the subunit intended for initial placement into hole **18**.

As shown in FIGS. **5**, **6**, **8** and **9**, upon closing a subunit (e.g. subunit **37** in FIG. **3**), valve **42** sits securely against center seal-off stop or center stop **52** in sealing unit **37a**, with the opening **70** in valve **42** being flush against center seal-off stop **52**. Valve **42** includes a top, proximal side which will face the spout of the cap, and a distal side which rests against the center seal-off stop when the valve is placed in valve holder **31**.

Center stop **52** functions as a sealing portion or blocking element of the valve assembly which seals off and blocks the flow of fluid through the valve. In a preferred embodiment, center stop **52** consists of a solid central area or portion **56** which is impenetrable to the flow of liquid therethrough. Surrounding the central area or portion **56** is preferably a peripheral area or region **58**, having open areas such as slots or so forth, for allowing the passage of liquid therethrough, as shown, for example in FIG. **8(a)**. Central area **56** or center stop **52** further includes stems **74**. As shown in FIG. **9**, stems **74** can further be reinforced with braces **72**, which are reinforcing elements, which provide additional material strength to the connection between the stems and the valve holder.

When in the normal resting position, valve **42** relaxes to sit securely against the center stop **52**, as shown in FIG. **8(d)**. In this resting position, opening or orifice **70** of valve **42** presses firmly against the central area **56** of center stop **52**, preventing any fluid flow through the valve, and maintaining the valve in a closed configuration.

To drink from the cup, a user raises the cup to his or her mouth and begins to suck liquid through spout **14**. In the process, the user creates negative pressure or a partial vacuum against the top of valve **42** in subunit **37**. Valve **42** is constructed of a flexible material which is designed to fully invert and turn inside out, or to begin to invert and turn inside out, upon creation of a partial vacuum against the top of the valve **42**, as shown in FIG. **8(e)**. For example, valve **42** can be a membrane, either in whole or in part. Preferably, the valve is constructed of KRATON® (the trade name for a styrenic block copolymer) or silicone. If silicone is used, a durometer silicone such as Lims 6045 is preferred, which is available from General Electric or from Wacker (a subsidiary of Bayer) of Germany. The materials used for the valve assembly and its components are sufficiently durable and heat resistant that the entire valve assembly can be placed in a dishwasher or boiled.

FIGS. **7** and **8**, for example, show a preferred bowl shape for the flexible material of the valve **42**. FIGS. **8(d)** and **8(e)** show the valve before and after it inverts, with FIG. **8(d)**

showing the valve assembly not in use, with no negative pressure applied, and with FIG. **8(e)** showing the valve assembly in use, with negative pressure applied to the valve. As shown therein, upon application of negative pressure the bottom (distal end) of the bowl and the opening in that bottom move away from the blocking element, toward the top (proximal side) and rim of the bowl, and toward the spout, allowing liquid to exit through the opening. As shown, in a preferred embodiment the application of negative pressure causes the inside surface of the bowl of flexible material to move from concave to convex, and the outside surface of the bowl of flexible material to move from convex to concave.

In a preferred embodiment, the valve material is constructed of a single material with a greater thickness of material on the center area which seals off on the center stop, and with a thinner portion of material on the sidewalls. Providing a thinner sidewall portion contributes to the flexibility of the valve at its edges, which further assists and encourages inversion of the valve, by causing the valve to flex at the sidewalls first upon application of negative pressure thereto. Preferred dimensions for the valve thickness are approximately 0.4 mm of thickness on the sidewalls and approximately 0.9 mm of thickness on the center area.

Upon inversion of valve **42**, opening or orifice **70** is displaced away from central area **56** of center stop **52**. The inversion of the valve therefore unblocks opening **70** allowing fluid flow through the subunit. As negative pressure is being applied to the top of the valve **42** located next to the spout, negative pressure is likewise being applied to the bottom of the adjacent valve in the other subunit, located in the other tapered hole of the cup cover. Thus, this negative pressure, opens the second valve as well, by displacing the opening in the other valve away from its center stop. Inversion of valves **42** allows fluid flow to proceed through both subunits of the assembly. Liquid will flow through one subunit of the valve assembly, the subunit connected to the spout, concurrently accompanied by air flow through the other subunit of the assembly, the subunit connected to the air vents. In this manner, liquid smoothly and easily flows through the valve assembly, the spout, and out of the cup.

In a preferred embodiment, the valve assembly is further provided with a flow bridge **84**. Flow bridge **84** blocks movement or expansion of the valve **42** beyond a certain maximum distance to prevent the valve from overextending itself, or from being subjected to excessive strain or distension, as shown in FIG. **8(e)**. Thus, the flow bridge prevents the valve from inverting beyond the point where it can no longer easily revert to its original position. In addition, the flow bridge provides a shield or a barrier preventing the valve from damage. Thus, it blocks objects such as a spoon or so forth, whether in a dishwasher or otherwise, from easily damaging the valve.

When negative pressure is released or removed from the spout, the valve reverts back to its resting position, and fluid cannot flow through the closed slit in the valve. In the resting position, no liquid will spill from or emerge out of the cup.

Further embodiments of the valve holder and assembly are shown in FIGS. **4** and **7-9**. As shown in FIG. **4**, instead of the valve retainer shown in FIG. **3**, a detachable snap fit valve retainer **81** can alternatively be provided. Or, as shown in FIG. **7**, valve retainer **94** can be provided as well. Valve retainers **81** and **94** serve the same function as valve retainers **37b** and **39(b)**, holding and securing the valve within the valve assembly. It is preferred that the valve retainer, whichever embodiment is utilized, be sonic welded on, to ensure that the valve cannot be dislodged or removed from the holder.



Thus, in accordance with the invention, a system is provided for maintaining a tight seal against fluid flow when the cup is not in use. An extremely secure seal is provided, such that excessive or vigorous shaking is ineffective to force fluid out of the cup. Significantly, the valve construction disclosed results in a much tighter seal than that observed in the no-spill cup assemblies of the prior art. In accordance with the invention, unless the user sucks through the spout, no liquid will flow through the valve.

In the preferred embodiment, subunits **37** and **39** are preferably identical in all respects excepts for the size of the orifice or slit in valve **42** and the slit in valve **45**. It is preferred that one valve be provided with a larger opening than the other valve, such as a longer slit in one valve than the other. In one embodiment, one valve is provided with an opening in the form of a slit of approximately two hundred thousandths ( $200/1000$ ) of an inch in length, while the second valve is provided with a slit of approximately fifty thousandths ( $50/1000$ ) of an inch. Alternatively, other lengths may, of course, be used as well in accordance with the invention.

By varying the size and/or shape of the opening in the valve, the present inventor has further provided a novel dual acting flow system for regulating fluid flow. In this system, the level of flow of liquid out of the cup during use can be easily regulated. Regulation is accomplished by a simple rotation of the valve assembly which converts the cup between a faster or higher liquid flow, and a slower or lower flow system.

As shown in FIG. **5**, valve holder **31** can be inserted into cap **11** in either of two configurations. In a first configuration, valve **45**, having a larger opening or slit, is placed into hole **18**, the hole in communication with spout **14**. In this configuration, a first, higher, flow level of liquid through the valve is established when the user sucks liquid through the spout, due to the use of the valve having the larger opening therein. By removing the valve holder **31** from holes **16** and **18**, and flipping the valve holder **31** one hundred eighty degrees (180.degree.), the other valve **42**, having the smaller opening, can be inserted into hole **18**. This valve **42** provides a second, lower flow state, in which liquid can still flow out of the spout, but at a lower flow rate than flow through the first valve. In this way, the rate of flow of liquid out of the cup can be regulated by a parent. Although a two level flow system is disclosed, greater or fewer flow levels can be provided by varying the number of attached subunits having valves therein, or by providing replacement valve holders having different sized openings **70** therein. In all configurations, however, liquid only flows through the valve when the user sucks through the spout, as disclosed above.

Any form of desired opening suitable for passage of a desired level of liquid can be utilized in the valve. The opening **70** can be, for example, a slit, a slot, an orifice, a hole, or so forth. Likewise, by the term opening, it is contemplated that multiple openings of these or any other types can be provided as well.

In one embodiment, the opening **70** is an "X" shaped slot **78**, as shown in FIG. **7**. In another preferred embodiment, the opening is a "T" shaped slot **76**, as also shown in FIG. **7**. Use of the X-shaped slot **78** shown in FIG. **7**, will provide a higher flow rate than the T-shaped slot **76** shown therein. The flow rate, of course, depends on the total length of the slots, or in general, on the size of the opening. Accordingly, both the X-shaped slot and the T-shaped slot can be used in a single valve assembly, each placed in its respective subunit in this preferred embodiment, a two level flow system is provided, as previously discussed.

In a further embodiment, both openings are X-shaped, with one opening larger than the other. A 7 mm opening (the length

from end to end of each crossbar of the "X") can be used for the fast side, and a 6 mm opening for the slow side.

It is further preferred that the valve holder be marked to indicate which subunit is suitable for higher flow, and which for lower flow of liquid therethrough. Accordingly, the valve holders can be explicitly marked "Fast" and "Slow" as shown in FIGS. **7** and **9**, respectively. Alternatively, or additionally, the subunits or the valve holders can be marked with a hare or rabbit, signifying fast flow, and a tortoise or turtle, signifying slow flow, as respectively also shown in FIGS. **7** and **9**. The subunit connected to the spout is, of course, the subunit which controls the liquid flow rate. The valve holder can be marked, for example, on the subunit itself, or on the bridge in an area directly adjacent to the subunit, as shown in the figures. In one embodiment, the valve holder is marked on the top and bottom (i.e. the sides facing the spout and the cup, respectively), such that the symbols and/or words can be seen from the top when the valve holder is being inserted, and from the bottom, once it has already been inserted, to determine which speed valve is in place in the spout. In an alternate embodiment, the words and/or symbols are only on the bottom of the valve, so that the user can see them from the bottom when inserting the valve holder, and can also view the valve holder from the bottom, once inserted.

Having described this invention with regard to specific embodiments, it is to be understood that the description is not meant as a limitation since further modifications may suggest themselves, or may be apparent to those in the art. It is intended that the present application cover all such modifications and improvements thereon.

What is claimed is:

**1.** An apparatus, comprising:

- (a) a no-spill drinking apparatus;
- (b) said no-spill drinking apparatus comprising a cap, said cap comprising a spout;
- (c) said cap comprising a valve, said valve comprising a flexible material and a hole;
- (d) said apparatus comprising a blocking element;
- (e) wherein said hole rests against said blocking element when the user is not drinking from said spout;
- (f) wherein said hole does not rest against said blocking element when the user sucks through said spout to drink from said spout; and
- (g) said apparatus comprising a barrier, said barrier blocking said flexible material from moving beyond a maximum distance when the user sucks through said spout to drink from said spout.

**2.** An apparatus as claimed in claim **1**, wherein said flexible material comprises a center area and sidewalls, and wherein said center area is of a greater thickness than said sidewalls.

**3.** An apparatus as claimed in claim **1**, wherein said cap comprises an air vent.

**4.** An apparatus as claimed in claim **3**, wherein said air vent comprises a slit.

**5.** An apparatus as claimed in claim **1**, wherein said flexible material hits said barrier upon application of sufficient sucking force.

**6.** An apparatus as claimed in claim **1**, wherein said apparatus comprises a valve holder, said valve holder being separable from said cap and being dimensioned to fit snugly into said cap.

**7.** An apparatus as claimed in claim **1**, wherein said spout of said cap is soft, and wherein said cap comprises a hard section for attachment to a cup.

**8.** An apparatus, comprising:

- (a) a no-spill drinking apparatus;



- (b) said no-spill drinking apparatus comprising a cap, said cap comprising a spout;
- (c) said cap comprising a valve, said valve comprising a flexible material and a hole;
- (d) said apparatus comprising a blocking element; 5
- (e) wherein said hole rests against said blocking element when the user is not drinking from said spout;
- (f) wherein said hole does not rest against said blocking element when the user sucks through said spout to drink from said spout; 10
- (g) said apparatus comprising a barrier, said barrier blocking said flexible material from moving beyond a maximum distance when the user sucks through said spout to drink from said spout; and
- (h) wherein said apparatus comprises an air vent, said air vent comprising a slit. 15

**9.** An apparatus as claimed in claim **8**, wherein said flexible material comprises a center area and sidewalls, and wherein said center area is of a greater thickness than said sidewalls.

**10.** An apparatus as claimed in claim **8**, wherein said flexible material hits said barrier upon application of sufficient sucking force. 20

**11.** An apparatus as claimed in claim **8**, wherein said apparatus comprises a valve holder, said valve holder being separable from said cap and being dimensioned to fit snugly into said cap. 25

**12.** An apparatus as claimed in claim **8**, wherein said spout of said cap is soft, and wherein said cap comprises a hard section for attachment to a cup.

\* \* \* \* \*

30