

(12) **United States Patent**
Igarashi

(10) **Patent No.:** **US 8,845,216 B2**
(45) **Date of Patent:** **Sep. 30, 2014**

(54) **PRINTER AND PRINTING METHOD**

(75) Inventor: **Hitoshi Igarashi**, Nagano (JP)

(73) Assignee: **Seiko Epson Corporation**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 124 days.

(21) Appl. No.: **13/253,458**

(22) Filed: **Oct. 5, 2011**

(65) **Prior Publication Data**

US 2012/0087707 A1 Apr. 12, 2012

(30) **Foreign Application Priority Data**

Oct. 6, 2010 (JP) 2010-226834

(51) **Int. Cl.**
B41J 15/00 (2006.01)
B41J 15/16 (2006.01)
B41J 11/42 (2006.01)

(52) **U.S. Cl.**
CPC **B41J 15/16** (2013.01); **B41J 11/425** (2013.01)
USPC **400/618**; **400/611**

(58) **Field of Classification Search**
USPC 400/618
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,679,200 A * 7/1972 Bailey et al. 270/4
4,277,034 A * 7/1981 Buzzell 242/417.3
4,611,799 A * 9/1986 Nuttin 270/52.01
4,719,855 A * 1/1988 Cannon et al. 101/485

4,966,352 A * 10/1990 Nuttin 270/1.01
5,423,620 A * 6/1995 Tokairin 400/582
5,813,343 A * 9/1998 Harb 101/407.1
6,052,144 A * 4/2000 Reyner 347/262
6,684,776 B2 * 2/2004 Cote et al. 101/228
6,799,507 B2 * 10/2004 Ohba et al. 101/228
6,993,964 B2 * 2/2006 Franz et al. 73/159
7,187,142 B2 * 3/2007 Rehm 318/400.04
7,395,025 B2 * 7/2008 Matsuzuki et al. 399/384
8,206,046 B2 * 6/2012 Koyabu 400/149

FOREIGN PATENT DOCUMENTS

JP 2003-276918 A 10/2003
JP 2009-091146 A 4/2009
JP 2009-198616 A 9/2009
JP 2009-208921 A 9/2009

* cited by examiner


Primary Examiner — Anthony Nguyen

(74) *Attorney, Agent, or Firm* — Global IP Counselors, LLP

(57) **ABSTRACT**

A printer includes a roll paper body driving mechanism that transports a medium by rotating a roll paper body on which the medium is wound, a first transport mechanism provided downstream of the roll paper body to transport the medium, a print head provided downstream of the first transport mechanism to carry out printing on the medium, a second transport mechanism provided between the roll paper body and the first transport mechanism to transport the medium, and a controller carries out control so that, in a range in which a velocity at which the first transport mechanism transports the media changes, the absolute value of a difference in an amount by which the medium is transported between transport mechanisms is larger between the roll paper body driving mechanism and the second transport mechanism than between the second transport mechanism and the first transport mechanism.

10 Claims, 12 Drawing Sheets






FIG. 1

FIG. 2




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14





FIG. 15



1

PRINTER AND PRINTING METHOD

BACKGROUND

1. Technical Field

The present invention relates to a printer and a printing method.

2. Related Art

A printer carries out printing by expelling a jet of ink from a nozzle so that ink droplets (dots) adhere to a medium (roll paper). Another type of printer has a roll paper printing mechanism that appropriately feeds a medium from paper wound in a roll shape (roll paper) by an amount required for printing and carries out printing. During printing, these types of printers adjust an amount by which the medium is transported by controlling an amount by which roll paper is rotated and an amount by which a transport roller that transports the medium (paper) fed from roll paper is rotated.

A printer having a roll paper printing mechanism controls the amounts of roll paper rotation and roller rotation so that a certain tension is applied to the medium to prevent the medium from slackening while the medium is being transported. Since the medium is consumed as printing proceeds and the roll diameter of the roll paper is reduced, however, the amount of roll paper rotation is not correctly controlled. Accordingly, it has been difficult to constantly apply a certain tension to the medium being printed.

To solve the above problem, a method has been proposed in which the amount of roll paper rotation is adjusted by controlling the torque setting of a motor that drives roll paper in correspondence with a change in the roll diameter, enabling a certain tension to be constantly applied to the medium (see JP-A-2009-208921, for example).

In the method in JP-A-2009-208921, an inertia generated due to the rotation of roll paper during printing is not considered. When roll paper with a large roll diameter is used in a large printer for business use or the like, for example, a large inertia is generated accordingly. If the large inertia is applied during the control of the roll paper driving motor or transport roller, response characteristics are worsened in acceleration and deceleration of the motor or the like and control precision is lowered. Since, in particular, the transport roller needs to repeatedly control the transport and stop of the medium being printed, if the operation of the transport roller is affected by the inertia, it becomes difficult to precisely transport the medium.

SUMMARY

An advantage of some aspects of the invention is to enable a printer having a roll paper printing mechanism to achieve medium transport in which the operation of a transport roller is not easily affected by an inertia caused by roll paper.

A printer according to an aspect of the invention includes (A) a roll paper body driving mechanism that transports a medium in a transport direction by rotating a roll paper body on which the medium is wound in a roll shape and a roll paper body driver that drives the roll paper body driving mechanism, (B) a first transport mechanism provided downstream of the roll paper body in the transport direction to transport the medium and a first driver that drives the first transport mechanism, (C) a second transport mechanism provided between the roll paper body and the first transport mechanism to transport the medium and a second driver that drives the second transport mechanism, and (D) a controller that controls the operations of the roll paper body driver, first driver, and second driver so that, in a range in which a velocity at which the

2

first transport mechanism transports the media changes, the absolute value of a difference between an amount by which the medium is transported by the roll paper body driving mechanism and an amount by which the medium is transported by the second transport mechanism is larger than the absolute value of a difference between an amount by which the medium is transported by the second transport mechanism and an amount by which the medium is transported by the first transport mechanism.

Other features of the aspects of the invention will be clarified by this description and the attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be described with reference to the accompanying drawings, wherein like numbers reference like elements.

FIG. 1 is a perspective view showing an example of the external structure of a printer according to an embodiment of the invention.

FIG. 2 shows a relationship, in the printer, between a control system and a driving system in which a DC motor is used.

FIG. 3 is a perspective view showing the structure of rotational holders that hold a roll paper body RP.

FIG. 4 shows a positional relationship among the roll paper body RP, paired transport rollers, paired transport adjusting rollers, and a print head.

FIGS. 5A and 5B show ENC signals.

FIG. 6 is a block diagram showing an example of the functional structure of a controller.

FIG. 7 schematically shows the rotations of rollers when a medium is transported in a comparative example.

FIG. 8 illustrates the time-varying transport velocity of the medium transported by a transport roller.

FIG. 9 schematically shows the rotations of rollers when the medium is transported in a first embodiment as well as the slack of the medium.

FIG. 10 illustrates ranges in which the velocity of the transport roller varies.

FIG. 11 shows a relation, in a variation of the first embodiment, between a control system and a driving system in which a DC motor is used.

FIG. 12 is a block diagram showing an example of the functional structure of the controller in the variation of the first embodiment.

FIG. 13 schematically shows the rotations of rollers and the slacks of the medium when it is transported in a second embodiment.

FIG. 14 is a block diagram showing an example of the functional structure of the controller in the second embodiment.

FIG. 15 is a block diagram showing an example of the functional structure of the controller in a variation of the second embodiment.

DESCRIPTION OF EXEMPLARY EMBODIMENTS

At least the following will be clarified by this description and the attached drawing.

A printer includes (A) a roll paper body driving mechanism that transports a medium in a transport direction by rotating a roll paper body on which the medium is wound in a roll shape and a roll paper body driver that drives the roll paper body driving mechanism, (B) a first transport mechanism provided downstream of the roll paper body in the transport direction to transport the medium and a first driver that drives the first

transport mechanism, (C) a second transport mechanism provided between the roll paper body and the first transport mechanism to transport the medium and a second driver that drives the second transport mechanism, and (D) a controller that controls the operations of the roll paper body driver, first driver, and second driver so that, in a range in which a velocity at which the first transport mechanism transports the media changes, the absolute value of a difference between an amount by which the medium is transported by the roll paper body driving mechanism and an amount by which the medium is transported by the second transport mechanism is larger than the absolute value of a difference between an amount by which the medium is transported by the second transport mechanism and an amount by which the medium is transported by the first transport mechanism.

This type of printer can achieve medium transport which is not easily affected by an inertia caused by the rotation of roll paper.

It is desirable that the controller of the printer control the operations of the roll paper body driver, first driver, and second driver so that, in a range from when the first transport mechanism starts the transport of the medium until it terminates the transport of the medium, the absolute value of a difference between an amount by which the medium is transported by the roll paper body driving mechanism and an amount by which the medium is transported by the second transport mechanism is larger than the absolute value of a difference between an amount by which the medium is transported by the second transport mechanism and an amount by which the medium is transported by the first transport mechanism.

This type of printer can achieve medium transport that is less affected by an inertia even while the transport roller is being accelerated or decelerated, during which the medium transport is likely to be affected by the inertia.

It is desirable that the controller of the printer control the operations of the roll paper body driver, first driver, and second driver so that, in a range from when printing is started until it is terminated, the absolute value of a difference between an amount by which the medium is transported by the roll paper body driving mechanism and an amount by which the medium is transported by the second transport mechanism is larger than the absolute value of a difference between an amount by which the medium is transported by the second transport mechanism and an amount by which the medium is transported by the first transport mechanism.

This type of printer can achieve medium transport that is less affected by an inertia in each printing operation.

It is desirable that the printer have a slack detector that detects the amount of slack of the medium between the roll paper body driving mechanism and the second transport mechanism, the controller drive the roll paper body driving mechanism if the amount of slack detected by the slack detector is less than or equal to a predetermined amount of slack, and the controller stop the roll paper body driving mechanism if the amount of slack detected by the slack detector is larger than the predetermined amount of slack.

This type of printer can control the driving of the roll paper body according to the amount of slack alone, and can achieve medium transport that is less affected by an inertia.

It is desirable that the controller detect the amount of slack of the medium between the roll paper body driving mechanism and the second transport mechanism according to an amount by which the medium is transported by the roll paper body driving mechanism and an amount by which the medium is transported by the second transport mechanism, the controller drive the roll paper body driving mechanism if

the amount of detected slack is less than or equal to a predetermined amount of slack, and the controller stop the roll paper body driving mechanism if the amount of detected slack is larger than the predetermined amount of slack.

This type of printer can control the driving of the roll paper body according to the amount of slack alone without having to use a slack sensor and other extra devices, and can achieve medium transport that is less affected by an inertia.

A printing method is clarified that (A) transports a medium in a transport direction by driving a roll paper body driving mechanism that drives a roll paper body on which the medium is wound in a roll shape, (B) transports the medium by driving a first transport mechanism provided downstream of the roll paper body in the transport direction, (C) transports the medium by driving a second transport mechanism provided between the roll paper body and the first transport mechanism, and (D) makes, in a range in which a velocity at which the first transport mechanism transports the media changes, the absolute value of a difference between an amount by which the medium is transported by the roll paper body driving mechanism and an amount by which the medium is transported by the second transport mechanism larger than the absolute value of a difference between an amount by which the medium is transported by the second transport mechanism and an amount by which the medium is transported by the first transport mechanism.

A printer is clarified that includes (A) a roll paper body driving mechanism that transports a medium in a transport direction by rotating a roll paper body on which the medium is wound in a roll shape and a roll paper body driver that drives the roll paper body driving mechanism, (B) a first transport mechanism provided downstream of the roll paper body in the transport direction to transport the medium and a first driver that drives the first transport mechanism, (C) a second transport mechanism provided between the roll paper body and the first transport mechanism to transport the medium and a second driver that drives the second transport mechanism, and (D) a controller that controls the operations of the roll paper body driver, first driver, and second driver so that the second transport mechanism transports the medium by an amount of transport equivalent to an amount of transport carried out by the first transport mechanism with the medium slackened between the roll paper body driving mechanism and the second transport mechanism.

This type of printer can achieve medium transport that is not easily affected by an inertia caused by the rotation of roll paper.

A printing method is clarified that (A) transports a medium in a transport direction by driving a roll paper body driving mechanism that drives a roll paper body on which the medium is wound in a roll shape, (B) transports the medium by driving a first transport mechanism provided downstream of the roll paper body in the transport direction, (C) transports the medium by driving a second transport mechanism provided between the roll paper body and the first transport mechanism, and (D) causes the second transport mechanism to transport the medium by an amount of transport equivalent to an amount of transport carried out by the first transport mechanism with the medium slackened between the roll paper body driving mechanism and the second transport mechanism.

Basic Structure of the Printer

The printer **10** used in an embodiment of the invention and a method of controlling its driving will be described. The printer **10** is a printer that can carry out printing on a large-sized medium (printing form with a size of at least A2 in the JIS standard, for example). Although the printer **10** in the

5

embodiment is an ink jet printer, the ink jet printer may adopt any jetting method if it can carry out printing by expelling a jet of ink.

In the description that follows, the lower side refers to a side on which the printer **10** is installed and the upper side refers to a side apart from the side on which the printer **10** is installed. A supply side (back) is a side from which a medium is supplied, and an ejection side (front) is a side to which the medium is ejected. Structure of the printer **10**

FIG. **1** is a perspective view showing an example of the external structure of a printer **10** according to an embodiment of the invention. FIG. **2** shows a relationship, in the printer **10** in FIG. **1**, between a control system and a driving system in which a DC motor is used. FIG. **3** is a perspective view showing an example of the external structure of rotational holders **31** and a roll motor **33**.

The printer **10** in this example has a pair of legs **11** and a main body **20** supported by the legs **11**. Each leg **11** has a column **12** and rotatable casters **13** attached to a caster support **14**.

The main body **20** is supported by a chassis (not shown). Various units mounted in the main body **20** are covered by an external case **21**. The driving system of the main body **20**, in which a DC motor is used, includes a roll paper body driving mechanism **30**, a carriage driving mechanism **40**, a medium transport mechanism **50**, and a transport adjusting mechanism **60**, as shown in FIG. **2**.

The roll paper body driving mechanism **30** is disposed in a roll mounting section **22** provided in the main body **20**. The roll mounting section **22** is disposed at the upper side of the back of the main body **20** as shown in FIG. **1**. When an open/close lid **23**, which is one element of the external case **21** described above, is opened, roll paper body RP can be mounted in the roll mounting section **22**, and the rotation of the roll paper body RP can be driven by the roll paper body driving mechanism **30**.

The roll paper body driving mechanism **30**, which rotates the roll paper body RP, includes the rotational holders **31**, a gear train **32**, and the roll motor **33** as shown in FIGS. **2** and **3**. The rotational holders **31**, which are paired, are inserted from both ends of a hollow RP1 formed in the roll paper body RP and support the roll paper body RP from both ends. The roll paper body RP is formed by winding a medium (such as paper P, for example) in a roll shape. When the roll paper body RP is rotated, the paper P is drawn out by an amount used for printing and fed to the medium transport mechanism **50** and transport adjusting mechanism **60**.

The roll motor **33** gives a driving force (rotational force) to a rotational holder **31a** at one end of the paired rotational holders **31** through the gear train **32**. That is, the roll motor **33** is equivalent to a motor that gives a driving force with which the roll paper body RP is rotated.

The roll motor **33** can freely change its rotational direction. In the description that follows, the direction in which the roll motor **33** rotates to feed the medium in a supply direction (also referred to below as the transport direction) will be referred to as the normal direction, and the direction opposite to the normal direction will be referred to as the reverse direction.

A driver, in the roll paper body driving mechanism **30**, that rotates the roll paper body RP is not limited to a motor such as the roll motor **33**; it may be an actuator that is hydraulically operated, for example.

The carriage driving mechanism **40** includes a carriage **41**, which is also a constituent element of an ink supply/jet mechanism, a carriage axis **42**, and a carriage motor (not shown), a belt (not shown), and the like.

6

The carriage **41** has ink tanks **43** that store inks in various colors. An ink can be supplied to each ink tank **43** from an ink cartridge (not shown) secured to the front of the main body **20** through a tube (not shown). A print head **44**, which can spray ink droplets, is provided at the bottom of the carriage **41** as shown in FIG. **2**. The print head **44** has a nozzle string (not shown) in correspondence to different inks. A piezoelectric device is provided in each nozzle of the nozzle string. When the piezoelectric device operates, droplets can be sprayed from the nozzle disposed at an end of an ink passage.

The carriage **41**, the ink tanks **43**, the print head **44**, tubes (not shown), and ink cartridges (not shown) constitute the ink supply/jet mechanism. The print head **44** is not limited to the piezoelectric method in which a piezoelectric device is used for driving; a heater method, in which an ink is heated by a heater and a force of generated foam is used, a magnetostriction method, in which magnetostriction devices are used, and a mist method, in which mists are controlled by an electric field, may be used, for example. The ink cartridges or ink tanks **43** may be filled with any types of inks (such as, for example, dye inks and pigment inks).

FIG. **4** shows a positional relationship among the medium transported from the paper roll RP, paired transport rollers **51**, paired transport adjusting rollers **61**, and the print head **44**.

The medium transport mechanism **50** has the paired transport rollers **51**, a gear train **52**, a PF motor **53**, and a rotation detector **54**, as shown in FIGS. **2** and **4**. The paired transport rollers **51** have a transport roller **51a** and a driven transport roller **51b**. The medium (paper P, for example) drawn out from the roll paper body RP and transported can be held between the transport roller **51a** and driven transport roller **51b**. Although the medium transport mechanism **50** in the printer **10** in the embodiment uses rollers to transport the medium, this is not a limitation; a belt or a suction mechanism may be used to transport the medium, for example.

The PF motor **53** gives a driving force (rotational force) to the transport roller **51a** through the gear train **52**. That is, the PF motor **53** is equivalent to a motor that gives a driving force with which the transport roller **51a** is rotated. As with the roll motor **33**, the PF motor **53** can freely change its rotational direction. In the description that follows, the direction in which the PF motor **53** rotates to feed the medium in the transport direction will be referred to as the normal direction, and the direction opposite to the normal direction will be referred to as the reverse direction. A driver that drives the transport roller **51a** is not limited to a motor such as the PF motor **53**; it may be an actuator that is hydraulically operated, for example.

The rotation detector **54** in the embodiment uses a rotary encoder. Therefore, the rotation detector **54** has a discal scale **54a** and a rotary sensor **54b**. The discal scale **54a** has transmitting portions through which light is transmitted and shielding portions that shield light at constant intervals in the circumferential direction. The main components of the rotary sensor **54b** are a light emitting device (not shown), a light receiving device (not shown), and a signal processing circuit (not shown).

FIG. **5A** is a timing diagram indicating waveforms of output signals while the PF motor **53** is rotated in the normal direction. FIG. **5B** is a timing diagram indicating waveforms of output signals while the PF motor **53** is rotated in the reverse direction. In the embodiment, due to outputs from the rotary sensor **54b**, pulse signals having a phase shift of 90 degrees (ENC signals in a phase A and ENC signals in a phase B), as shown in FIGS. **5A** and **5B**, are input to a controller **100**. Accordingly, whether the PF motor **53** is rotated in the

normal direction or reverse direction can be determined according to the advance or delay of the phase.

A platen **55** is provided downstream of the paired transport rollers **51** (on an ejection side) in the transport direction. The medium is guided on the platen **55** as shown in FIG. **4**. The print head **44** is disposed above the platen **55** so as to face it. A suction hole **55a** is formed in the platen **55** in such a way that the suction hole **55a** can communicate with a suction fan **56**. When the suction fan **56** is operated, air is inhaled from the same side as the print head **44** through the suction hole **55a**. If the medium is placed on the platen **55**, the medium can be held by suction. The printer **10** also has other various types of sensors including a medium width detecting sensor that detects the width of the medium.

The transport adjusting mechanism **60** has almost the same structure as the medium transport mechanism **50**; the transport adjusting mechanism **60** includes the paired transport adjusting rollers **61**, a gear train **62**, an FC motor **63**, and a rotation detector **64** as shown in FIG. **2**. The paired transport adjusting rollers **61** have a transport adjusting roller **61a** and a driven adjusting roller **61b**. The medium drawn out from the roll paper body RP can be held between the transport adjusting roller **61a** and a driven adjusting roller **61b**. The FC motor **63** gives a driving force (rotational force) to the transport adjusting roller **61a** through the gear train **62**. That is, the FC motor **63** is equivalent to a motor that gives a driving force with which the transport adjusting roller **61a** is rotated. As with the roll motor **33**, the FC motor **63** can freely change its rotational direction. In the description that follows, the direction in which the FC motor **63** rotates to feed the medium in the transport direction will be referred to as the normal direction, and the direction opposite to the normal direction will be referred to as the reverse direction. A driver that drives the transport adjusting roller **61a** is not limited to a motor such as the FC motor **63**; it may be an actuator that is hydraulically operated, for example.

The transport adjusting mechanism **60**, which is placed at a midpoint between the roll paper body RP and the medium transport mechanism **50**, has a function to adjust an amount by which the medium is transported. The adjustment of the medium transport will be described later in detail.

A slack sensor **68** is provided between the paired transport adjusting rollers **61** and the roll paper body RP. The slack sensor **68**, disposed below the medium, can detect a vertical position of the medium (a vertical relative position between the slack sensor **68** and the medium) between the paired transport adjusting rollers **61** and the roll paper body RP. By using the slack sensor **68**, it is possible to acquire a slack amount, which indicates the amount of slack with respect to a vertical transport position measured when the medium is transported without a slack (while being tensioned).

About the Controller

FIG. **6** is a block diagram showing an example of the functional structure of the controller **100** in a first embodiment. In the first embodiment, the controller **100** receives signals output from the rotation detector **54** in the medium transport mechanism **50**, the rotation detector **64** in the transport adjusting mechanism **60**, the slack sensor **68**, and a linear sensor (not shown). In addition, the controller **100** receives signals output from a paper width detecting sensor, a gap detecting sensor, a power switch that turns on and off power to the printer **10**, and the like (none of these components are shown).

As shown in FIG. **2**, the controller **100** includes a central processing unit (CPU) **101**, a read-only memory (ROM) **102**, a random-access memory (RAM) **103**, a programmable read-only memory (PROM) **104**, an application-specific integrated

circuit (ASIC) **105**, and a motor driver **106**. These hardware components are mutually connected through a transmission path **107**, such as, for example, a bus. The controller **100** is connected a computer COM. When the hardware components cooperate with software and/or data stored in the ROM **102** and PROM **104** or when a circuit or constituent component that carries out a specific process is added, a main controller **110**, a roll motor controller **111**, a PF motor controller **112**, and an FC motor controller **113**, as shown in FIG. **6**, are implemented.

The main controller **110** controls the operations of the roll motor controller **111**, PF motor controller **112**, and FC motor controller **113** and performs a process to transport the medium in the transport direction. During this transport, the main controller **110** adjusts and controls a balance between an amount by which the medium is transported by the transport roller **51a** and an amount by which the medium is supplied (transported) from the roll paper body RP so that the medium transport mechanism **50** is not affected by an inertia caused by the roll paper body RP.

The roll motor controller **111** controls the driving of the roll motor **33** according to the signal output from the slack sensor **68** so that an appropriate amount of medium is supplied (transported) to the medium transport mechanism **50** in the printer **10**.

The PF motor controller **112** controls the driving of the PF motor **53** according to the signal output from the rotation detector **54**. Then, the amount of rotation of the transport roller **51a** is controlled and the medium is transported in the transport direction.

The FC motor controller **113** controls the driving of the FC motor **63** according to the signal output from the rotation detector **64**. Then, the amount of rotation of the transport adjusting roller **61a**, the amount of medium supplied from the roll paper body RP, and the amount of medium transported by the transport roller **51a** are adjusted.

About A Printing Operation

When the printer **10** receives print data from the computer COM, the controller **100** controls the roll paper body driving mechanism **30**, the carriage driving mechanism **40**, and other units to perform a paper supply process, a dot forming process, a transport process, and other processes.

In the paper supply process, the medium on which to print is supplied from the roll paper body RP to the interior of the printer **10** and paper is positioned at a print start position (also referred to as a cuing position). The controller **100** rotates the roll paper body RP in the normal direction and feeds the medium to the transport adjusting roller **61a** and transport roller **51a**. The controller **100** then rotates the transport adjusting roller **61a** and transport roller **51a**, and positions the paper fed from the roll paper body RP at the print start position.

In the dot forming process, inks are discontinuously sprayed from the print head **44**, which moves in a direction perpendicular to the transport direction of the medium (the direction will also be referred to as the movement direction), to form ink dots on the medium. The controller **100** moves the carriage **41** in the movement direction and sprays inks from the print head **44** according to print data while the carriage **41** is moving. When ink droplets adhere to the medium, dots are formed and a dot line of a plurality of dots is formed along the movement direction.

In the transport process, the medium is moved in the transport direction, relative to the head. The controller **100** rotates the transport roller **51a** and transports paper in the transport direction. The transport process enables the print head **44** to form a dot at a position different from the position of the dot

formed in the dot forming process described above. Control of the amount of medium transported during a transport will be described later.

The controller **100** alternately repeats the dot forming process and transport process until all data to be printed has been processed, gradually printing an image formed by dot lines on the paper. Finally, the controller **100** ejects the medium on which the image has been printed.

Comparative Example

First, medium transport without the transport adjusting mechanism **60** will be described as a comparative example.

FIG. **7** schematically shows the rotations of rollers when a medium is transported in the comparative example. With a printer in the comparative example, the medium fed from the roll paper body **RP** is sent directly to the transport roller **51a** without intervention by the paired transport adjusting rollers **61**. When the transport roller **51a** is rotated in the normal direction, the medium is transported in the transport direction.

This type of printer is assumed to carry out printing by using a roll paper body **RP** with a large roll diameter. When a large mass of roll paper **RP** with a large roll diameter is rotated during the supply of the medium, a large inertia is generated accordingly. The inertia generated in the roll paper body **RP** could be considered to affect the rotation of the transport roller **51a** through the medium.

For example, the printer in the comparative example prints an image by alternately repeating the transport process and dot forming process for the medium as described above. In this case, the transport roller **51a** does not constantly transport the medium at a fixed velocity, but it transports the medium while being repeatedly rotated and stopped. That is, the medium is transported while the transport velocity changes at short intervals. FIG. **8** illustrates the time-varying transport velocity of the medium transported by the transport roller **51a**. The transport roller **51a** starts acceleration at the same time as the start of its rotation, and raises the transport velocity. When a predetermined target velocity is reached, the transport roller **51a** terminates acceleration (the velocity is in the acceleration range in FIG. **8**). Then, the transport roller **51a** continues to be rotated while the constant velocity is maintained (the velocity in the constant velocity range in FIG. **8**). When rotation is stopped, deceleration is started and the transport velocity is gradually lowered. When a predetermined velocity is reached, deceleration is terminated and the velocity is finally reduced to zero (the velocity is in the deceleration range in FIG. **8**). The transport roller **51a** repeats a series of operations described above to transport the medium.

If the rotational speed of the transport roller **51a** is constant in the constant velocity range, even when the inertia is large, medium transport is less likely to be affected. This is because if the roll paper body **RP** continues to be rotated at the same velocity as the medium transport velocity of the transport roller **51a**, that is, if the amount of medium transported by the transport roller **51a** per unit time is equal to the amount of medium fed from the roll paper body **RP** per unit time, the inertia does not affect the rotation of the transport roller **51a**.

When the rotational speed of the transport roller **51a** is gradually increased in the acceleration range, the effect of the inertia becomes problematic. After the roll paper body **RP** has started to be rotated, its rotational speed is also gradually increased in correspondence to the rotation of the transport roller **51a**. During this period, however, a large inertia is exerted due to the roll diameter and weight of the roll itself in a direction in which the rotation of the roll paper body **RP** is impeded. That is, a force with which the medium is tensioned

in a direction opposite to the transport direction is generated. If this force is transmitted directly to the transport roller **51a** through the medium, the operation to accelerate the rotation of the transport roller **51a** is impeded, making control of medium transport difficult. Similarly, in the deceleration range, a large inertia is exerted in a direction in which the rotation of the roll paper body **RP** is continued. If this force is transmitted directly to the transport roller **51a** through the medium, the operation to decelerate the rotation of the transport roller **51a** is impeded, making control of medium transport difficult.

As described above, the rotational speeds of the transport roller **51a** and roll paper body **RP** vary through the transport operation during printing. In particular, the variation of the rotational speed of the transport roller **51a** becomes large when the rotation is started (in the acceleration range in FIG. **8**) and when the rotation is stopped (in the deceleration range in FIG. **8**). The inertia caused by the roll paper body **RP** is likely to affect the transport roller **51a** accordingly. If the transport roller **51a** is affected by the inertia, the rotation of the transport roller **51a** cannot be accurately controlled. This may disturb the transport operation of the medium and may lower the quality of printed images.

First Embodiment

If the roll paper body **RP** is large (heavy), a large inertia is generated accordingly, as described above. In a range in which the rotation velocity of the transport roller **51a** varies during printing, transport control becomes difficult due to the effect of the inertia. In this embodiment, therefore, the transport adjusting roller **61a** is provided between the transport roller **51a** and the roll paper body **RP**.

FIG. **9** schematically shows the rotations of rollers when the medium is transported in the first embodiment as well as the slack of the medium. Control is performed so that, during printing (during medium transport), the medium is constantly slackened while being transported between the transport adjusting roller **61a** and the roll paper body **RP** and is not slackened while being transported between the transport roller **51a** and the transport adjusting roller **61a**. Since the medium is slackened between the transport adjusting roller **61a** and the roll paper body **RP** so that the effect of the inertia generated by the roll paper body **RP** is eliminated by the slack of the medium, the effect of the inertia on the transport roller **51a** is suppressed.

How the rotation of each roller is controlled will be described below.

Controlling the Rotation of the Transport Roller **51a**

The transport roller **51a** transports the medium at a certain velocity **V** in the transport direction.

If the diameter of the transport roller **51a** (roller diameter) is denoted **D1** and its angular velocity during rotation is denoted $\omega 1$, then the transport velocity **V** at which the medium is transported by the transport roller **51a** is represented by equation (1).

$$V = \omega 1 \times D1 / 2 \quad (1)$$

The PF motor controller **112** produces a pulse-width modulation (PWM) output and drives the PF motor **53** to rotate the transport roller **51a** at the angular velocity $\omega 1$. The amount of rotation of the PF motor **53** per unit time is detected by the rotation detector **54**. The current angular velocity of the transport roller **51a** is calculated from the relationship between the detected amount of rotation and the gear ratio of the gear train **52**. The PF motor controller **112** appropriately controls the rotational speed of the transport roller **51a** so that the calculated angular velocity comes close to the target angular velocity $\omega 1$ and the medium is stably transported.

11

The transport roller **51a** transports the medium while repeating acceleration, transport at a constant velocity, and deceleration, as shown in FIG. 8 as well. Therefore, the angular velocity $\bar{\omega}1$ also constantly changes through the printing operation.

Controlling the Rotation of the Transport Adjusting Roller **61a**

The transport adjusting roller **61a** follows the transport roller **51a** and transports the medium in the transport direction at the same velocity V as the transport roller **51a**. Accordingly, the medium is transported between the transport roller **51a** and the transport adjusting roller **61a** while maintaining a certain amount. If the diameter of the transport adjusting roller **61a** (roller diameter) is denoted $D2$ and its angular velocity during rotation is denoted $\bar{\omega}2$, then the transport velocity V at which the medium is transported by the transport adjusting roller **61a** is represented by equation (2).

$$V = \bar{\omega}2 \times D2 / 2 \quad (2)$$

If V in equation (1) equals V in equation (2), since $V = \bar{\omega}1 \times D1 / 2 = \bar{\omega}2 \times D2 / 2$, the following equation holds.

$$\bar{\omega}2 \times \bar{\omega}1 \times D1 / D2 \quad (3)$$

That is, when the transport adjusting roller **61a** is rotated at the angular velocity $\bar{\omega}2$ corresponding to the angular velocity $\bar{\omega}1$ of the transport roller **51a**, the medium can be transported at the predetermined velocity V .

The FC motor controller **113** produces a PWM output and drives the FC motor **63** to rotate the transport adjusting roller **61a** at the angular velocity $\bar{\omega}2$. The amount of rotation of the FC motor **63** per unit time is detected by the rotation detector **64**. The current angular velocity of the transport adjusting roller **61a** is calculated from the relationship between the detected amount of rotation and the gear ratio of the gear train **62**. Thus, the FC motor controller **113** appropriately controls the rotational speed of the transport adjusting roller **61a**, enabling the same amount of medium to be transported per unit time between the transport roller **51a** and the transport adjusting roller **61a**.

In this embodiment, while the medium is transported between the transport roller **51a** and the transport adjusting roller **61a**, a constant tension is maintained. To achieve this, when starting the transport of the medium, the main controller **110** rotates only the PF motor **53** in the normal direction before starting to rotate the FC motor **63**. That is, the main controller **110** rotates only the transport roller **51a** with the transport adjusting roller **61a** stopping. The medium is thereby tensioned between the transport roller **51a** and the transport adjusting roller **61a** without being slackened. Whether the medium is slackened or not between the transport roller **51a** and the transport adjusting roller **61a** is determined by a slack sensor **58**. After the slack of the medium, if any, is removed, the FC motor **63** is also rotated in the normal direction and the rotational speed of the transport adjusting roller **61a** is controlled as described above.

At the start of medium transport, it is also possible to remove the slack of the medium between the transport roller **51a** and the transport adjusting roller **61a** by rotating the PF motor **53** in the normal direction and rotating the FC motor **63** in the reverse direction. After the slack has been removed from the medium, the FC motor **63** may be rotated in the normal direction and the rotational speed of the transport adjusting roller **61a** may be controlled as described above.

Controlling the Rotation of the Roll Paper Body RP

The roll paper body RP is rotated by the roll motor **33** in the normal direction and supplies (transports) the medium toward the transport adjusting roller **61a** and transport roller

12

51a. In this embodiment, to have the medium constantly slackened between the transport adjusting roller **61a** and the roll paper body RP as shown in FIG. 9, the amount of rotation of the roll motor **33** is adjusted and controlled so that an appropriate amount of medium is supplied to the transport adjusting roller **61a** and transport roller **51a**.

To have the medium slackened between the transport adjusting roller **61a** and the roll paper body RP, the medium must be more supplied from the roll paper body RP per unit time during printing than when the medium is transported by the transport adjusting roller **61a** per unit time.

The amount of slack of the medium is monitored by the slack sensor **68**. The slack sensor **68** used in this embodiment, which is disposed below the medium between the transport adjusting roller **61a** and the roll paper body RP as shown in FIG. 9, detects a distance $SL1$ from the medium to be transported (vertical positional relation between the medium and the slack sensor **68**). For example, suppose that the vertical distance between the medium and the slack sensor **68** is 10 cm when the medium has no slack. If the medium is slackened, since the position of the medium is lowered due to its own weight, the vertical distance between the medium and the slack sensor **68** is reduced. If the target value of $SL1$ to be detected has been set to 5 cm, when the detected value is less than or equal to 5 cm, the slack is large; when the detected value is larger than 5 cm, the slack is small (see FIG. 9). The slack sensor **68** monitors the amount of slack of the medium by detecting the vertical distance from the medium (positional relation) in this way.

The slack sensor **68** may be a device, having a scale, that enables the amount of slack to be visually monitored, instead of a device that measures a positional relation to the medium.

A case in which the target value of the distance $SL1$ from the medium in this embodiment is "h" will be described. When the distance $SL1$ detected by the slack sensor **68** is "h" or more, it implies that the amount of slack of the medium is smaller than an assumed reference value. Then, the roll motor controller **111** controls the roll motor **33** so that it rotates in the normal direction. That is, when the amount of slack of the medium falls below or to a predetermined reference value, the roll motor **33** is rotated to feed the medium from the roll paper body RP so that a sufficient amount of medium is supplied to the medium transport mechanism **50**.

Conversely, when the distance $SL1$, detected by the slack sensor **68**, from the medium is smaller than "h", it implies that the amount of slack of the medium is larger than the assumed reference value. Then, the roll motor controller **111** controls the roll motor **33** so as to stop its rotation. That is, when the amount of slack of the medium exceeds the predetermined reference value, the supply of the medium from the roll paper body RP is stopped for a while. Since, during printing, the transport roller **51a** and transport adjusting roller **61a** transport the medium in the transport direction at the predetermined speed of V , when the supply of the medium is stopped, the slack between the transport adjusting roller **61a** and the roll paper body RP is gradually reduced. When the distance $SL1$ detected by the slack sensor **68** is increased again to at least a predetermined value ("h" in the above example), the roll motor **33** is rotated in the normal direction to supply the medium to the medium transport mechanism **50**.

Since the roll paper body RP is very heavy, it may be difficult to brake the roll motor **33**, for example, immediately after printing has been started. In control in which the roll motor **33** is repeatedly rotated and stopped at short intervals as described above, a large load may be applied to the roll motor **33**.

13

In this case, the roll motor **33** may be first rotated and then stopped after a predetermined amount of medium (two meters of medium, for example) has been supplied so that an adequately large slack is formed between the transport adjusting roller **61a** and the roll paper body RP in advance. When printing proceeds, the supplied medium is consumed, and the amount of slack falls below the predetermined target value, the roll motor **33** may be rotated again to supply an adequate amount of medium again and then the roll motor **33** may be stopped. This process may be repeated to have the medium slacked by the predetermined value or more between the transport adjusting roller **61a** and the roll paper body RP. In this method, a rotation detector **34** described later may be attached to the roll motor **33**. Variation in the transport velocity of the transport roller **51a**

The medium supplied (transported) from the roll paper body RP is transported to the transport adjusting roller **61a** and transport roller **51a** in that order in the transport direction. The transport velocity of the medium is controlled by adjusting the rotational speed of the transport roller **51a**. The roll paper body RP itself has a large mass and thereby generates a large inertia when it is rotated. In particular, when the rotational speed of the transport roller **51a** varies, if the inertia generated by the roll paper body RP affects the rotational operation of the transport roller **51a**, the rotation of the transport roller **51a** cannot be accurately controlled, preventing the medium from being stably transported.

In this embodiment, therefore, the transport adjusting roller **61a** is disposed between the transport roller **51a** and the roll paper body RP, and an amount by which each motor is rotated is controlled so that the medium is adequately slackened between the transport adjusting roller **61a** and the roll paper body RP in a certain range in which the velocity of the transport roller **51a** varies. Therefore, the effect of the inertia generated by the roll paper body RP is eliminated by the slack of the medium between the transport adjusting roller **61a** and the roll paper body RP.

The certain range is a period during which the transport velocity varies while the transport roller **51a** is operating to transport the medium. FIG. **10** illustrates the certain range. As in FIG. **8**, FIG. **10** illustrates the time-varying transport velocity of the medium transported by the transport roller **51a**.

In this embodiment, the certain range can be set to a particular range (A), which is indicated by hatching, from a point in time "a" to a point in time "b" in the acceleration range in FIG. **10**. Alternatively, the certain range can be set to a particular range (B), which is indicated by hatching, from a point in time "c" to a point in time "d" in the deceleration range in FIG. **10**. Since the transport velocity caused by the transport roller **51a** varies with time in these ranges, medium transport is likely to be affected by an inertia as described above. Therefore, the absolute value of a difference between an amount by which the medium is transported by the transport adjusting roller **61a** and an amount by which the medium is transported by the roll paper body RP is made larger than the absolute value of a difference between an amount by which the medium is transported by the transport roller **51a** and an amount by which the medium is transported by the transport adjusting roller **61a**. The medium thereby has a slack between the transport adjusting roller **61a** and the roll paper body RP in the certain range, in which the transport velocity changes during a transport operation, and the effect of the inertia generated by the roll paper body RP does not extend to the transport roller **51a**, achieving a stable transport.

The certain range can also be set to the entire acceleration range (range (C) in FIG. **10**) or the entire deceleration range (range (D) in FIG. **10**). Furthermore, the certain range can be

14

set to a range from when the transport roller **51a** starts to be rotated and medium starts to be transported until the rotation is stopped and the medium transport is terminated. That is, the certain range can be set to a range E, which is the sum of the acceleration range, constant velocity range, and deceleration range in FIG. **10**. In these cases as well, when an amount by which the medium is transported by each roller is adjusted in the relevant range, the medium has a slack between the transport adjusting roller **61a** and the roll paper body RP. Since the inertia generated by the roll paper body RP is eliminated by the slack of the medium, the effect of the inertia on the rotational operation of the transport roller **51a** can be suppressed.

Alternatively, the certain range may be set to a range from when printing starts until it is terminated. Since the printing operation of the printer **10** is carried out by repeating the transport process and dot forming process, the transport roller **51a** repeatedly starts to be rotated and stopped. That is, a transport velocity variation caused in the range (E) in FIG. **10** is repeated several times during the printing operation. When an amount by which the medium is transported by each roller is adjusted during this repetition, the effect of the inertia generated by the roll paper body RP on the rotational operation of the transport roller **51a** can be suppressed.

Advantages In the First Embodiment

In this embodiment, the absolute value of a difference between an amount by which the medium is transported by the transport adjusting roller **61a** and an amount by which the medium is transported by the roll paper body RP is made larger than the absolute value of a difference between an amount by which the medium is transported by the transport roller **51a** and an amount by which the medium is transported by the transport adjusting roller **61a** in the certain range in which the transport velocity of the medium transported by the transport roller **51a** varies.

Accordingly, the effect of an inertia, which causes a problem when the rotational speed of the transport roller **51a** varies during printing, is eliminated by the slack of the medium and the effect of the inertia thereby does not extend to the transport roller **51a** disposed downstream in the transport direction. Since the transport roller **51a** is not affected by the inertia, the medium can be accurately transported.

In this embodiment, a certain tension is applied to the medium while it is being transported between the transport roller **51a** and the transport adjusting roller **61a**. That is, the medium is neither slackened nor wrinkled downstream of the transport roller **51a** in the transport direction. Accordingly, the medium is not slackened in an area, on the platen **55**, in which printing is actually carried out, so the problem that ink dots expelled from the head adhere to incorrect positions is less likely to occur and printed images with superior quality can be obtained.

Variation of the First Embodiment

In the embodiment described above, the slack sensor **68** has been used to detect the amount of slack of the medium between the roll paper body RP and the transport adjusting roller **61a**. However, the amount of slack of the medium can also be detected by using another method.

FIG. **11** shows a relation, in a variation of the first embodiment, between a control system and a driving system in which a DC motor is used. FIG. **12** is a block diagram showing an example of the functional structure of the controller **100** in the variation of the first embodiment.

In this variation, the roll paper body driving mechanism **30** has the rotation detector **34** (see FIG. **11**). The slack sensor **68** is not used. The printer structure excluding the slack sensor **68** is the same as in the first embodiment.

15

The rotation detector **34** uses a rotary encoder similar to the rotary encoder in the rotation detectors **54** and **64**; the rotation detector **34** has a discal scale **34a** and a rotary sensor **34b**. The discal scale **34a** has transmitting portions through which light is transmitted and shielding portions that shield light at constant intervals in the circumferential direction. The main components of the rotary sensor **34b** are a light emitting device, a light receiving device, and a signal processing circuit (none of these components are shown). To calculate the amount of slack, the rotation detector **34** for the roll motor **33** detects the amount of rotation of it and the rotation detector **64** for the FC motor **63** detects the amount of rotation of it (see FIG. 12).

Specifically, it is possible to calculate the amount Feed_roll of medium supplied (fed) from the amount of rotation of the roll motor **33**, which is obtained from the rotation detector **34**, and the diameters of the gear train **32** and roll paper body RP. Since the medium (roll paper) supplied from the roll paper body RP is gradually consumed during printing, the diameter of the roll paper body RP changes as the printing proceeds. Therefore, the diameter of the roll paper body RP is inferred according to the amount of medium that has been already transported. It is also possible to calculate the amount Feed_fc of medium transported from the amount of rotation of the FC motor **63**, which is obtained from the rotation detector **64**, and the diameters of the gear train **62** and transport adjusting roller **61a**. When the amount Feed_fc of transport is subtracted from the amount Feed_roll of supply, the current amount of slack can be inferred.

The method of controlling the rollers, excluding the roller used to detect the amount of slack, is the same as in the first embodiment.

Second Embodiment

In a second embodiment, the slack of the medium between the transport adjusting roller **61a** and the transport roller **51a** is also used in control. FIG. 13 schematically shows the rotations of rollers and the slacks of the medium when it is transported in the second embodiment. FIG. 14 is a block diagram showing an example of the functional structure of the controller **100** in the second embodiment.

In the second embodiment, the slack sensor **58** is provided between the transport adjusting roller **61a** and the transport roller **51a** to detect a slack of the medium therebetween (see FIG. 13). As with the slack sensor **68**, the slack sensor **58**, which is disposed below the medium, can detect the vertical position of the medium (vertical relative position between the medium and the slack sensor **58**) between the transport adjusting roller **61a** and the transport roller **51a**. When the slack sensor **58** is used, it is possible to obtain the amount of slack of the medium, relative to a vertical transport position with the medium not slackened (with the medium tensioned).

The components other than the slack sensor **58** are the same as in the first embodiment.

Controlling the Rotation of the Transport Roller **51a**

Control of the transport roller **51a** is the same as in the first embodiment. That is, to transport the medium at the certain velocity V in the transport direction, the transport roller **51a** is rotated at the angular velocity ω_1 that satisfies $V = \omega_1 \times D_1 / 2$.

The PF motor controller **112** produces a PWM output and drives the PF motor **53** to rotate the transport roller **51a** at the angular velocity ω_1 . The amount of rotation of the PF motor **53** per unit time is monitored by the rotation detector **54**. When the amount of rotation of the PF motor **53** is detected, the current angular velocity of the transport roller **51a** is calculated from the relationship between the detected amount of rotation and the gear ratio of the gear train **52**. Then, the PF

16

motor controller **112** appropriately controls the rotational speed of the transport roller **51a** so that the medium is stably transported.

Controlling the Rotation of the Transport Adjusting Roller **61a**

The amount of rotation of the transport adjusting roller **61a** is controlled according to the amount of slack detected by the slack sensor **58**. The slack sensor **58**, which is disposed below the medium between the transport roller **51a** and the transport adjusting roller **61a** as shown in FIG. 13, detects a distance SL2 from the medium to be transported (vertical relative position between the medium and the slack sensor **58**).

The FC motor controller **113** controls the FC motor **63** so that the amount of slack of the medium reaches a predetermined target amount of slack. For example, when rotating the FC motor **63**, the FC motor controller **113** calculates the current amount of slack from SL2 detected by the slack sensor **58** and controls the duty ratio of the FC motor **63** under proportional-integral-derivative (PID) control so that the difference obtained by subtracting the current calculated amount of slack from the target amount of slack becomes zero. Then, the medium can be transported while an appropriate amount of slack is kept. When the amount of slack is set to 0 mm, the medium is transported without being slackened between the transport adjusting roller **61a** and the transport roller **51a**.

Controlling the Rotation of the Roll Paper Body RP

The amount of rotation of the roll paper body RP is controlled as in the first embodiment. That is, the amount of slack between the roll paper body RP and the transport adjusting roller **61a** is a predetermined amount of slack or more, so the medium is transported while being kept slackened.

Advantages in the Second Embodiment

In this embodiment as well, motor control is carried out so that the medium is adequately slackened between the transport adjusting roller **61a** and the roll paper body RP in a certain range in which the transport velocity changes, as in the first embodiment. Accordingly, the effect of an inertia, which causes a problem when the rotational speed of the transport roller **51a** varies, is eliminated by the slack of the medium and the effect of the inertia thereby does not extend to the transport roller **51a** disposed downstream in the transport direction. Since the transport roller **51a** is not affected by the inertia, the medium can be accurately transported.

Furthermore, in this embodiment, the amount of slack of the medium is also monitored between the transport roller **51a** and the transport adjusting roller **61a** to control the motor, enabling the medium to be slackened therebetween. Since the target amount of slack can be set to a desired value, an optimum transport can be achieved according to the material and type of the medium used for printing. If a thin medium is used, for example, there may be a case in which a relatively strong tension should be applied to suppress wrinkles. In this case, the target amount of slack is set to 0 mm. If the medium is not easily wrinkled, the target amount of slack is set to a slightly large value to prevent an extra load from being applied to the rotational operation of the transport roller **51a**. Thus, an optimum medium transport can be achieved under various printing conditions.

Variation of the Second Embodiment

To detect the amount of slack of the medium between the transport adjusting roller **61a** and the transport roller **51a**, it is also possible to infer the amount of slack from the amounts of rotations of various motors, without using the slack sensor **58**. The structure of the printer in a variation of the second embodiment is the same as in the second embodiment, except that the slack sensor **58** is not used.

17

FIG. 15 is a block diagram showing an example of the functional structure of the controller 100 in the variation of the second embodiment. In this variation, it is possible to calculate the amount Feed_pf of medium supplied (fed) from the amount of rotation of the PF motor 53, which is obtained from the rotation detector 54, and the diameters of the gear train 52 and transport roller 51a, in the same way as described in the variation of the first embodiment. It is also possible to calculate the amount Feed_fc of medium transported from the amount of rotation of the FC motor 63, which is obtained from the rotation detector 64, and the diameters of the gear train 62 and transport adjusting roller 61a. When the amount Feed_fc of transport is subtracted from the amount Feed_pf of supply, the current amount of slack can be inferred.

Other Embodiments

Although a printer in an embodiment has been described, the above embodiments should not be construed as restricting the invention; they are described to facilitate the understanding of the invention. It will be appreciated that modifications and variations may be made in the invention and that the invention includes its equivalents. In particular, even the embodiment described below is included in the invention.

The above embodiments have been described for a case in which a motor control apparatus is provided in the printer 10. However, the location of the motor control apparatus is not limited to the interior of the printer 10; the motor control apparatus may be applied to, for example, a facsimile machine that uses a roll paper body (roll paper).

About the Printer

In the above embodiments, a serial scanning type of printer, in which the head moves together with the carriage, has been described as an example. However, the printer 10 may be a so-called line printer, in which the head is secured.

The printer 10 may be part of a composite apparatus such as a scanner or copy machine. Furthermore, although the above embodiments have been described for the printer 10 that uses the ink jet method, the printer 10 is not limited to an ink jet printer; any printer that can expel a jet of fluid can be used. For example, the embodiments can be applied to gel jet printers, printers using toner, dot-impact printers, and other various types of printers.

Plotters are also included as types of printers.

About Inks Used

In the above embodiments, four colored inks, which are cyan (C), magenta (M), yellow (Y), and black (K), can be used for printing. Dye inks, pigment inks, and other types inks can be used. Light cyan inks, light magenta inks, white inks, clear inks, and inks of other colors other than CMYK can also be used.

About the Medium

In the above embodiments, the medium has been roll paper. However, film members, resin sheets, aluminum foils, and other types of materials other than paper can be used.

About the Controller

The controller 100 is not limited to the one in the above embodiments. For example, the controller 100 may be structured so that the ASIC 105 alone controls the roll motor 33, PF motor 53, and FC motor 63. Alternatively, the controller 100 may be structured by combining a single-chip microcomputer in which various peripheral units are incorporated.

What is claimed is:

1. A printer, comprising:

a roll paper body driving mechanism configured to transport a medium in a transport direction by rotating a roll paper body on which the medium is wound in a roll

18

shape, the roll paper body driving mechanism including a rotational holder that is configured to support the roll paper body;

a roll paper body driver that drives the roll paper body driving mechanism;

a first transport mechanism provided downstream of the rotational holder in the transport direction to transport the medium;

a first driver that drives the first transport mechanism;

a print head provided downstream of the first transport mechanism in the transport direction to carry out printing on the medium;

a second transport mechanism provided between the rotational holder and the first transport mechanism to transport the medium;

a second driver that drives the second transport mechanism; and

a controller configured to control operations of the roll paper body driver, the first driver, and the second driver based on an amount of slack between the roll paper body driving mechanism and the second transport mechanism such that, in a timing at which a velocity at which the first transport mechanism transports the media changes, an absolute value of a difference between an amount by which the medium is transported by the roll paper body driving mechanism and an amount by which the medium is transported by the second transport mechanism being larger than an absolute value of a difference between an amount by which the medium is transported by the second transport mechanism and an amount by which the medium is transported by the first transport mechanism, the amount of slack indicating a slack amount of the medium slacking in a slacking direction relative to a hypothetical line that indicates a transport route where the medium is transported without slacking in the slacking direction between the roll paper body driving mechanism and the second transport mechanism, the slacking direction intersecting the transport direction.

2. The printer according to claim 1, wherein the controller controls the operations of the roll paper body driver, the first driver, and the second driver so that, in a range from when the first transport mechanism starts transport of the medium until the first transport mechanism terminates the transport of the medium, the absolute value of a difference between an amount by which the medium is transported by the roll paper body driving mechanism and an amount by which the medium is transported by the second transport mechanism is larger than the absolute value of a difference between an amount by which the medium is transported by the second transport mechanism and an amount by which the medium is transported by the first transport mechanism.

3. The printer according to claim 1, wherein the controller controls the operations of the roll paper body driver, the first driver, and the second driver so that, in a range from when the print head starts printing on the medium until the print head terminates the printing, the absolute value of a difference between an amount by which the medium is transported by the roll paper body driving mechanism and an amount by which the medium is transported by the second transport mechanism is larger than the absolute value of a difference between an amount by which the medium is transported by the second transport mechanism and an amount by which the medium is transported by the first transport mechanism.

4. The printer according to claim 1, further comprising a slack detector that detects the amount of slack of the medium, wherein:

19

the controller drives the roll paper body driving mechanism if the amount of slack detected by the slack detector is less than or equal to a predetermined amount of slack; and

the controller stops the roll paper body driving mechanism if the amount of slack detected by the slack detector is larger than the predetermined amount of slack.

5. The printer according to claim 1, wherein:

the controller detects the amount of slack of the medium according to an amount by which the medium is transported by the roll paper body driving mechanism and an amount by which the medium is transported by the second transport mechanism;

the controller drives the roll paper body driving mechanism if the amount of detected slack is less than or equal to a predetermined amount of slack; and

the controller stop the roll paper body driving mechanism if the amount of detected slack is larger than the predetermined amount of slack.

6. A printing method, comprising:

transporting a medium in a transport direction by driving a roll paper body driving mechanism that drives a roll paper body on which the medium is wound in a roll shape, the roll paper body driving mechanism including a rotational holder that is configured to support the roll paper body;

transporting the medium by driving a first transport mechanism provided downstream of the rotational holder in the transport direction;

carrying out printing on the medium by using a print head provided downstream of the first transport mechanism in the transport direction;

transporting the medium by driving a second transport mechanism provided between the rotational holder and the first transport mechanism; and

controlling the driving of the roll paper body driving mechanism, the driving of the first transport mechanism, and the driving of the second transport mechanism based on an amount of slack between the roll paper body driving mechanism and the second transport mechanism to make, in a timing in which a velocity at which the first transport mechanism transports the media changes, an absolute value of a difference between an amount by which the medium is transported by the roll paper body driving mechanism and an amount by which the medium is transported by the second transport mechanism being larger than an absolute value of a difference between an amount by which the medium is transported by the second transport mechanism and an amount by which the medium is transported by the first transport mechanism, the amount of slack indicating a slack amount of the medium slacking in a slacking direction relative to a hypothetical line that indicates a transport route where the medium is transported without slacking in the slacking direction between the roll paper body driving mechanism and the second transport mechanism, the slacking direction intersecting the transport direction.

7. A printer, comprising:

a roll paper body driving mechanism configured to transport a medium in a transport direction by rotating a roll paper body on which the medium is wound in a roll shape and a roll paper body driver that drives the roll paper body driving mechanism, the roll paper body driving mechanism including a rotational holder that is configured to support the roll paper body;

20

a first transport mechanism provided downstream of the rotational holder in the transport direction to transport the medium and a first driver that drives the first transport mechanism;

a print head provided downstream of the first transport mechanism in the transport direction to carry out printing on the medium;

a second transport mechanism provided between the rotational holder and the first transport mechanism to transport the medium and a second driver that drives the second transport mechanism; and

a controller configured to control operations of the roll paper body driver, the first driver, and the second driver based on an amount of slack between the roll paper body driving mechanism and the second transport mechanism such that the medium is more slackened, in a timing at which a velocity at which the first transport mechanism transports the media changes, between the roll paper body and the second transport mechanism than between the first transport mechanism and the second transport mechanism, the amount of slack indicating a slack amount of the medium slacking in a slacking direction relative to a hypothetical line that indicates a transport route where the medium is transported without slacking in the slacking direction between the roll paper body driving mechanism and the second transport mechanism, the slacking direction intersecting the transport direction.

8. A printing method, comprising:

transporting a medium in a transport direction by driving a roll paper body driving mechanism that drives a roll paper body on which the medium is wound in a roll shape, the roll paper body driving mechanism including a rotational holder that is configured to support the roll paper body;

transporting the medium by driving a first transport mechanism provided downstream of the roll paper body in the transport direction;

carrying out printing on the medium by using a print head provided downstream of the rotational holder in the transport direction;

transporting the medium by driving a second transport mechanism provided between the rotational holder body and the first transport mechanism; and

controlling the driving of the roll paper body driving mechanism, the driving of the first transport mechanism, and the driving of the second transport mechanism based on an amount of slack between the roll paper body driving mechanism and the second transport mechanism to transport the medium so that the medium is more slackened, in a timing at which a velocity at which the first transport mechanism transports the media changes, between the roll paper body and the second transport mechanism than between the first transport mechanism and the second transport mechanism, the amount of slack indicating a slack amount of the medium slacking in a slacking direction relative to a hypothetical line that indicates a transport route where the medium is transported without slacking in the slacking direction between the roll paper body driving mechanism and the second transport mechanism, the slacking direction intersecting the transport direction.

9. The printer according to claim 4, wherein the slack detector is arranged between the roll paper body driving mechanism and the second transport mechanism

in the transport direction and configured to detect a distance between the medium and the slack detector in the slacking direction.

10. The printer according to claim 5, further comprising a first rotation detector configured to detect a first amount of rotation of the roll paper body driver, and a second rotation detector configured to detect a second amount of rotation of the second driver, wherein the controller detects the amount of slack by calculating the amount of slack, using the first amount of rotation and the second amount of rotation.

* * * * *