



US008861770B2

(12) **United States Patent**  
**Blair et al.**

(10) **Patent No.:** **US 8,861,770 B2**  
(45) **Date of Patent:** **Oct. 14, 2014**

- (54) **HEADBAND FOR PERSONAL SPEAKERS**
- (71) Applicant: **Koss Corporation**, Milwaukee, WI (US)
- (72) Inventors: **Nick S. Blair**, Whitefish Bay, WI (US);  
**Stephen Fiacchino**, Port Washington, WI (US); **Michael J. Koss**, Milwaukee, WI (US); **Michael J. Koss, Jr.**, Milwaukee, WI (US); **Michael J. Pelland**, Princeton, WI (US)
- (73) Assignee: **Koss Corporation**, Milwaukee, WI (US)
- (\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 13 days.

3,909,077	A	9/1975	Leonarduzzi	
4,588,868	A	5/1986	Bertagna et al.	
5,035,005	A *	7/1991	Hung	2/209
5,290,120	A	3/1994	Osterfeld et al.	
5,384,857	A	1/1995	Nordin et al.	
5,406,037	A *	4/1995	Nageno et al.	181/129
5,793,878	A *	8/1998	Chang	381/370
5,862,241	A	1/1999	Nelson	
6,333,982	B1	12/2001	Sapiejewski et al.	
6,542,615	B1 *	4/2003	Ito	381/374
6,549,789	B1	4/2003	Kfoury	
6,630,878	B2	10/2003	Pan et al.	
6,715,315	B1	4/2004	Hartgrove	
6,754,361	B1 *	6/2004	Hall et al.	381/370
6,772,853	B2 *	8/2004	Yang	181/129
6,929,076	B2 *	8/2005	Fanuel et al.	175/267

(Continued)

- (21) Appl. No.: **13/747,547**
- (22) Filed: **Jan. 23, 2013**
- (65) **Prior Publication Data**  
US 2014/0205129 A1 Jul. 24, 2014

FOREIGN PATENT DOCUMENTS

JP	2006-112523	A1	4/2006
WO	WO 2011/137034	A1	11/2011

*Primary Examiner* — Davetta W Goins  
*Assistant Examiner* — Phylesha Dabney

(74) *Attorney, Agent, or Firm* — K&L Gates LLP

- (51) **Int. Cl.**  
**H04R 25/00** (2006.01)  
**H04R 1/10** (2006.01)
- (52) **U.S. Cl.**  
CPC ..... **H04R 1/1058** (2013.01)  
USPC ..... **381/378**; 381/379
- (58) **Field of Classification Search**  
USPC ..... 381/309, 182, 183, 370, 371, 374, 378,  
381/379, 383, 384, 386, 395  
See application file for complete search history.


(57) **ABSTRACT**

An assembly for holding a personal speaker relative to a user's ear. A headband assembly can include a band, a sleeve attached to an end of the band, and an arm moveably secured to the sleeve. The sleeve can include a pair of laterally opposed detent channels, and the arm can include a pair of spring-loaded bearings. Each spring-loaded bearing can engage one of the laterally opposed detent channels. The headband assembly can be adjusted by moving the arm relative to the sleeve. An arm of the headband assembly can be pivotally secured to a yoke by a magnetic pivot arrangement. The magnetic pivot arrangement can include a groove, a protrusion, and magnetic elements. A yoke can be pivotally secured to a housing by housing pivot arrangement. The housing pivot arrangement can include a pin extending from the yoke and a collar retained in the housing.

- (56) **References Cited**  
U.S. PATENT DOCUMENTS

1,835,575	A	12/1931	Sanders et al.
2,819,105	A	1/1958	Behnke
3,287,760	A	11/1966	Moore
3,787,899	A	1/1974	Krawagna

**15 Claims, 37 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

D514,087	S	1/2006	Wilson et al.						
6,993,143	B2 *	1/2006	Harris et al. ....	381/379	8,424,470	B2 *	4/2013	Volin .....	108/118
7,171,698	B2	2/2007	Saffran		8,559,665	B2 *	10/2013	Schmidt et al. ....	381/374
7,337,497	B2	3/2008	Seidler et al.		8,605,935	B1 *	12/2013	Huang .....	381/381
7,451,523	B2	11/2008	Chen		2005/0053255	A1 *	3/2005	Harris et al. ....	381/379
7,647,020	B2	1/2010	Chuang		2005/0238189	A1 *	10/2005	Tsai .....	381/309
7,885,419	B2 *	2/2011	Wahl et al. ....	381/74	2006/0256992	A1 *	11/2006	Liao .....	381/371
7,915,986	B2	3/2011	Lu		2009/0061961	A1	3/2009	Ueta	
7,934,291	B2	5/2011	Prest		2009/0257817	A1	10/2009	Chu	
7,941,191	B2	5/2011	Hanssen et al.		2009/0268936	A1 *	10/2009	Goldberg et al. ....	381/379
D639,775	S	6/2011	Horibe et al.		2010/0034414	A1 *	2/2010	Miyata .....	381/374
8,015,666	B2	9/2011	Wang		2010/0046782	A1 *	2/2010	Ito et al. ....	381/378
8,050,444	B2	11/2011	Smith		2010/0205773	A1	8/2010	Kim	
8,055,006	B2	11/2011	Santiago		2011/0051976	A1	3/2011	Tsai	
8,159,834	B2	4/2012	Griffin et al.		2011/0103635	A1 *	5/2011	Asakura et al. ....	381/378
8,213,662	B2 *	7/2012	Ishida .....	381/371	2011/0116672	A1 *	5/2011	Wahl et al. ....	381/375
8,213,667	B2	7/2012	Nelson et al.		2011/0116674	A1 *	5/2011	Asakura et al. ....	381/378
8,233,655	B2	7/2012	Miyata		2011/0194721	A1 *	8/2011	Schmidt et al. ....	381/370
8,270,658	B2 *	9/2012	Goldberg et al. ....	381/384	2012/0140973	A1	6/2012	Olodort et al.	
8,313,492	B2 *	11/2012	Wong et al. ....	606/96	2013/0003984	A1 *	1/2013	Belafonte et al. ....	381/74
8,325,962	B2 *	12/2012	Ishida et al. ....	381/370	2013/0083955	A1 *	4/2013	Miyazawa .....	381/378
8,371,417	B2 *	2/2013	Miyazawa .....	181/129	2013/0136293	A1 *	5/2013	Lee et al. ....	381/378
					2013/0156247	A1 *	6/2013	Boyajian et al. ....	381/370
					2013/0195307	A1 *	8/2013	Mizuno et al. ....	381/374
					2013/0195308	A1 *	8/2013	Tankersley et al. ....	381/378

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14






FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22






FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30






FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37

**HEADBAND FOR PERSONAL SPEAKERS****CROSS-REFERENCE TO RELATED APPLICATIONS**

The Applicant of the present application also owns the U.S. Patent Applications identified below which were filed on even date herewith and which are each herein incorporated by reference in their respective entirety:

U.S. patent application Ser. No. 13/747,549, entitled "Headband for Personal Speakers"; and

U.S. patent application Ser. No. 13/747,551, entitled "Headband for Personal Speakers".

**BACKGROUND**

A headband may be used with personal speakers. The headband may be positioned relative to a user's head and/or neck to hold the personal speakers relative to the user's ears. For example, the headband can hold the personal speakers in, over, and/or around the user's ears. Due to variations in the shape and size of peoples' heads, as well as variations in personal preferences regarding the positioning and fit of headphones, it is often difficult to design a rugged headband that is comfortable for large masses of people.

**SUMMARY**

An aspect of the present disclosure is directed to a headband assembly for holding a personal speaker relative to a user's ear, the headband assembly can comprise a spring band, a sleeve in which is disposed a first end portion of the spring band, and an arm. The sleeve can comprise a first plurality of detent pockets and a second plurality of detent pockets positioned laterally relative to the first plurality of detent pockets. The arm can comprise a first spring-loaded bearing that adjustably engages the first plurality of detent pockets, and a second spring-loaded bearing that adjustably engages the second plurality of detent pockets. The first and second spring-loaded bearings can adjustably secure the arm to the sleeve when the first spring-loaded bearing engages one pocket of the first plurality of detent pockets and the second spring-loaded bearing engages one pocket of the second plurality of detent pockets.

In another aspect of the present disclosure, a headband assembly can comprise a band, a first sleeve attached to an end portion of the band, and a first extension moveably secured to the first sleeve. The first sleeve can comprise a pair of laterally opposed detent channels. The first extension can comprise a pair of spring-loaded bearings, wherein each spring-loaded bearing engages one of the pair of laterally opposed detent channels.

In another aspect of the present disclosure, an assembly can comprise an extension arm, an attachment element, and a spring member secured to the attachment element. The extension arm can comprise a first detent bearing and a second detent bearing. The attachment element can comprise a first row of detent pockets that receives the first detent bearing, and a second row of detent pockets that receives the second detent bearing. The first row of detent pockets can laterally oppose the second row of detent pockets, and the extension arm can be movably positioned relative to the attachment element.

In an aspect of the present disclosure, a headband assembly for holding a personal speaker relative to a user's ear can comprise a band, and a yoke configured to support the personal speaker. The band can comprise a band body, a groove, and a first band magnetic element. The band body can com-

prise a first surface and the groove can extend from the first surface into the band body. The yoke can comprise a yoke body, comprising a second surface, wherein the second surface is positioned relative to the first surface. The yoke can further comprise a protrusion extending from the second surface into the groove of the band, and a first yoke magnetic element. The yoke can be configured to pivot between a first position and at least one second position relative to the band. Further, a magnetic pole of the first band magnetic element can be aligned with a magnetic pole of the first yoke magnetic element when the yoke is in the first position, and a magnetic attraction between the first band magnetic element and the first yoke magnetic element can pull the magnetic poles of the first yoke magnetic element and the first band magnetic element toward alignment when the yoke is in the second position.

In another aspect of the present disclosure, a headband assembly can comprise a band, and a yoke configured to support a personal speaker. The band can comprise a band body, a groove, and a first pair of magnetic elements. The band body can comprise a first surface, and the groove can extend from the first surface into the band body. The yoke can comprise a yoke body, a protrusion, and a second pair of magnetic elements. The yoke body can comprise a second surface, and the protrusion can extend from the second surface into the groove of the band. The yoke can be configured to pivot between a neutral position and pivoted positions relative to the band, wherein the first and second pairs of magnetic elements can interact to generate a magnetic force, and wherein the magnetic force forces the yoke toward the neutral position when the yoke is in one of the pivoted positions.

In an aspect of the present disclosure, an earpiece for holding a personal speaker can comprise a housing configured to hold the personal speaker, a yoke pivotally secured to the housing. The housing can comprise a collar, which can comprise an arm comprising an arm surface, a stop comprising a stop surface, and an opening between the arm surface and the stop surface. The stop surface can be angularly oriented relative to the arm surface. The yoke can comprise a pin configured to engage the housing, wherein the pin can comprise a head, wherein the head can be configured to extend into the opening in the collar, and wherein the head can be configured to pivot between the arm surface and the stop surface.

In an aspect of the present disclosure, an earpiece assembly can comprise a housing configured to hold a personal speaker, a collar fixed to the housing, a yoke, wherein the housing is configured to pivot relative to the yoke, and a pin fixed to the yoke. The collar can comprise a flexible arm and a stop. The flexible arm can comprise an arm surface, and the stop can comprise a stop surface. The stop surface can be angularly oriented relative to the arm surface. The pin can extend from the yoke to between the flexible arm and the stop of the collar, and the pin can be configured to deform the flexible arm as the pin pivots from the arm surface toward the stop surface of the collar.

**BRIEF DESCRIPTION OF THE FIGURES**

Various embodiments of the present invention are described herein by way of example in conjunction with the following Figures, wherein:

FIG. 1 is a perspective view of a headband assembly according to various embodiments of the present disclosure;



3

FIG. 2 is an elevational view of the headband assembly of FIG. 1 according to various embodiments of the present disclosure;

FIG. 3 is another elevational view of the headband assembly of FIG. 1 according to various embodiments of the present disclosure;

FIG. 4 is a perspective view of a spring band of the headband assembly of FIG. 1 according to various embodiments of the present disclosure;

FIG. 5 is a perspective view of a sleeve of the headband assembly of FIG. 1 according to various embodiments of the present disclosure;

FIG. 6 is a perspective view of the sleeve of FIG. 5 and a liner of the headband assembly of FIG. 1 according to various embodiments of the present disclosure;

FIG. 7 is a perspective view of the sleeve of FIG. 5, shown in transparency, and an arm of the headband assembly of FIG. 1 according to various embodiments of the present disclosure;

FIG. 8 is a perspective view of the sleeve of FIG. 5 and a cap of the headband assembly of FIG. 1 according to various embodiments of the present disclosure;

FIG. 9 is a perspective view of the cap of FIG. 8 according to various embodiments of the present disclosure;

FIG. 10 is a perspective view of a first side of the cap of FIG. 8 according to various embodiments of the present disclosure;

FIG. 11 is another perspective view of the cap of FIG. 8 according to various embodiments of the present disclosure;

FIG. 12 is a perspective view of the arm of FIG. 7 with the spring-loaded bearings removed therefrom according to various embodiments of the present disclosure;

FIG. 13 is a perspective view of the arm of FIG. 12, shown in transparency, and including the spring-loaded bearings according to various embodiments of the present disclosure;

FIG. 14 is an elevational view of the arm of FIG. 12 according to various embodiments of the present disclosure;

FIG. 15 is a perspective view of the headband assembly of FIG. 1 with a cushion and a covering according to various embodiments of the present disclosure;

FIG. 16 is a perspective view of the spring band, a frame, and the covering of the headband assembly of FIG. 15 according to various embodiments of the present disclosure;

FIG. 17 is an elevational view of the headband assembly of FIG. 15 according to various embodiments of the present disclosure;

FIG. 18 is another elevational view of the headband assembly of FIG. 15 according to various embodiments of the present disclosure;

FIG. 19 is a plan view of the headband assembly of FIG. 15 according to various embodiments of the present disclosure;

FIG. 20 is a partial, plan view of the headband assembly of FIG. 15 according to various embodiments of the present disclosure;

FIG. 21 is a perspective view of the headband assembly of FIG. 15 with personal speakers attached thereto according to various embodiments of the present disclosure;

FIG. 22 is a detail, perspective view of a joint between the headband assembly and a personal speaker of FIG. 21 according to various embodiments of the present disclosure;

FIG. 23 is a perspective view of the arm of FIG. 12 with magnetic elements embedded therein according to various embodiments of the present disclosure;

FIG. 24 is a perspective view of the yoke of a personal speaker of FIG. 21, including magnetic element embedded therein according to various embodiments of the present disclosure;

4

FIG. 25 is a perspective view of a pivot plate according to various embodiments of the present disclosure;

FIG. 26 is a perspective view of the yoke of FIG. 24 and the pivot plate of FIG. 25 according to various embodiments of the present disclosure;

FIG. 27 is a perspective view of the yoke and the pivot plate of FIG. 26 secured to the arm of FIG. 23 according to various embodiments of the present disclosure;

FIG. 28 is an elevational view of the yoke, the pivot plate, and the arm of FIG. 27, with multiple components shown in transparency, according to various embodiments of the present disclosure;

FIG. 29 is a detail, elevational view of the yoke, the pivot plate, and the arm of FIG. 28, with multiple components shown in transparency, according to various embodiments of the present disclosure;

FIG. 30 is a perspective view of the personal speaker of FIG. 21 according to various embodiments of the present disclosure;

FIG. 31 is another perspective view of the personal speaker of FIG. 30 according to various embodiments of the present disclosure;

FIG. 32 is a perspective view of the personal speaker of FIG. 30 with an outer housing removed therefrom according to various embodiments of the present disclosure;

FIG. 33 is a perspective view of the personal speaker of FIG. 30 with an ear cushion, speaker mount, and speaker element removed therefrom according to various embodiments of the present disclosure;

FIG. 34 is an elevational cross-sectional view of the personal speaker of FIG. 30 taken along the plane indicated in FIG. 32 according to various embodiments of the present disclosure;

FIG. 35 is perspective view of the yoke of the personal speaker of FIG. 30 with a pivot pin and a collar of the yoke pivot arrangement attached thereto according to various embodiments of the present disclosure;

FIG. 36 is a perspective view of the pivot pin and the collar of the yoke pivot arrangement of FIG. 35 according to various embodiments of the present disclosure; and

FIG. 37 is an elevational view of the pivot pin and the collar of the yoke pivot arrangement of FIG. 36 according to various embodiments of the present disclosure.

#### DETAILED DESCRIPTION

According to various embodiments, the present invention is directed to a headband assembly that can be used with personal speakers and worn, for example, on the head of a human user. Referring primarily to FIGS. 1-3, a headband assembly 22 can include a spring band 30, a sleeve or attachment portion 40a, and an extension arm 60a. As described herein, the sleeve 40a can be attached to an end of the spring band 30, and the extension arm 60a can be moveably secured to a sleeve 40a. In various embodiments, the headband assembly 22 can include a single spring band 30, two sleeves 40a, 40b, and two extension arms 60a, 60b, for example. The first sleeve 40a can be attached to a first end 32 of the spring band 30 and the second sleeve 40b can be attached to a second end 34 of the spring band. Furthermore, the first extension arm 60a can be moveably secured to the first sleeve 40a and the second extension arm 60b can be moveably secured to the second sleeve 40b. A component on a first side of the headband assembly may have a corresponding or identical component on a second side of the headband assembly 22. In other words, the components of the headband assembly 22 can be modular. For example, the first sleeve 40a can be interchange-

5

able with the second sleeve **40b** and the first arm **60a** can be interchangeable with the second arm **60b**. Accordingly, throughout this Detailed Description, elements and/or characteristics of a component on a first side or a second side of the headband assembly **22** may be described and, unless otherwise indicated, such description is intended to apply to the corresponding or identical component on the other side of the headband assembly **22**, as well.

In various embodiments, the headband assembly **22** can be positioned relative to a user's head and/or neck. For example, the headband assembly **22** can fit around the top and/or the crown of a user's head, and/or around the back and/or nape of a user's neck. A pair of personal speakers, such as earphones **100a**, **100b** (FIGS. **21** & **22**) may be attached to the headband assembly **22**. The headband assembly **22** can hold the earphones **100a**, **100b** relative to the user's head and/or neck, and specifically relative to the user's ears such that the earphones **100a**, **100b** are in, over, and/or around the user's ears, for example. The headband assembly **22** can be adapted for use with various sizes and styles of earphones **100a**, **100b**, for example.

Referring now to FIG. **4**, the spring band **30** can be contoured or arced. Furthermore, the spring band **30** can have a spring constant such that the deformation of the spring band **30** from an initial configuration to a deformed configuration can result in a springback or restoring force. In various embodiments, the spring band **30** can be deformed from the initial configuration to the deformed configuration when the spring band **30** is positioned relative to the user's head and/or neck. For example, the spring band **30** can be deformed to a less contoured or less arced configuration when positioned relative to the user's head and/or neck. Consequently, the spring band **30** can exert a springback force on the user's head and/or neck as the spring band **30** seeks to return or to substantially return to its initial configuration. Such a springback force can help to secure the spring band **30**, and ultimately the entire headband assembly **22**, in place relative to the user's head and/or neck. Furthermore, in some embodiments, the spring band can generate a springback or restoring force of approximately 1.25 lb when positioned relative to the user's head and/or neck. In at least one embodiment, the spring band **30** can generate a springback or restoring force of approximately 0.75 lb to approximately 2.0 lb when positioned relative to the user's head and/or neck.

The spring constant of the spring band **30** can at least depend on the dimensions and material thereof. In at least one embodiment, the spring band **30** can be approximately 5.3 inches by approximately 0.75 inches by approximately 0.03 inches with an initial, undeformed radius of curvature of approximately 3.3 inches. In various embodiments, the dimensions of the spring band **30**, including the radius of curvature, can be selected such that the spring band **30** comfortably fits the user's head and/or neck. Additionally, the dimensions of the spring band **30** can be selected such that the spring band **30** smoothly interfaces with the other headband assembly **22** components such as the sleeve **40a**, for example. In at least one embodiment, the spring band **30** can comprise stainless steel, for example. In various embodiments, the spring band **30** can comprise metallic and/or polymeric materials, for example, such as nylon and/or acrylonitrile butadiene styrene (ABS), for example.

Referring still to FIG. **4**, the spring band **30** can include the first distal end **32** and the second distal end **34**. As described herein, the first distal end **32** and/or the second distal end **34** of the spring band **30** can be positioned in and/or disposed through a portion of one of the sleeves **40a**, **40b** such that the sleeve **40a**, **40b** is attached to the spring band **30** at or near the

6

respective distal end **32**, **34** thereof. The spring band **30** can include a pronged portion **36** extending from a distal end **32**, **34** along a portion of the spring band **36**. Still referring to FIG. **4**, the spring band **30** can include the pronged portion **36** extending from the first distal end **32** and the pronged portion **36** extending from the second distal end **34**. The pronged portion **36** can be defined by a slot **37** that extends from the respective distal end **32**, **34** through a portion of the spring band **30**, such as 1.0 inch or 20% of the length of the spring band **30**, for example. The pronged portion **36** can taper as the pronged portion **36** approaches the respective distal end **32**, **34**, for example. In various embodiments, the pronged portion **36** can be deformable. For example, the prongs of the pronged portion **36** can move towards each other and the width of the slot can be reduced to compress or narrow the width of the pronged portion **36** of the spring band **30**. When the pronged portion **36** is deformed, the spring band **30** can exert a springback or restoring force as it seeks to return or substantially return to its initial configuration. As described herein, such a springback force generated by the pronged portion **36** can help to secure the spring band **30** to the sleeve **40a**, **40b** positioned relative thereto. In various embodiments, the spring band **30** can include additional slots and/or prongs, for example. In other embodiments, the spring band **30** may not include a slot and/or prongs, but may have other features or geometries that provide springback when a portion of the spring band **30** is deformed or compressed.

Still referring primarily to FIG. **4**, the spring band **30** can include tabs **38a**, **38b**, **39a**, **39b** designed to help secure the spring band **30** to the first sleeve **40a** and/or the second sleeve **40b**. In various embodiments, the tabs **38a**, **38b**, **39a**, **39b** can be laterally opposed tabs. For example, a tab **38a**, **38b**, **39a**, **39b** can extend from a first lateral side of the spring band **30** in a first direction and a corresponding tab **38a**, **38b**, **39a**, **39b** can extend from an opposite lateral side of the spring band **30** in a second direction. In some embodiments, the second direction can be substantially opposite to the first direction. Referring still to FIG. **4**, the first side of the spring band **30** can include two pairs of opposing tabs **38a**, **39a**, for example, and the second side of the spring band **30** can include two additional pairs of opposing tabs **38b**, **39b**, for example. A first pair of opposing tabs **38a** can be positioned near or at the first distal end **32** and/or a second pair of opposing tabs **39a** can be positioned farther from first distal end **32** such as, for example, past the slot of the pronged portion **36**. Furthermore, the spring band **30** can include a third pair of opposing tabs **38b** near or at the second distal end **34** and/or a fourth pair of opposing tabs **39b** farther from second distal end **34** such as, for example, past the slot of the pronged portion **36**. In other words, the spring band **30** can have two pairs of opposing tabs **38a**, **39a** near or around the first distal end **32** and two more pairs of opposing tabs **38b**, **39b** near or around the second distal end **34**. Further, in various embodiments, the tabs **38a**, **39a** on the first side of the spring band **30** can form a mirror image reflection of the tabs **38b**, **39b** on the second side of the spring band **30**. As described herein, when the sleeve **40a** is positioned relative to the first end **32** of the spring band **30**, the tabs **38a**, **39a** of the spring band **30** can engage the sleeve **40a** to help secure the sleeve **40a** to the spring band **30**.

Referring primarily to FIGS. **5-8**, the sleeve or attachment portion **40a** can have a contoured or arced body that is configured for receiving a portion of the spring band **30**. The contour of the sleeve **40a** can be selected such that the sleeve **40a** comfortably fits on and/or around a portion of the user's head and/or neck, for example. Furthermore, as described herein, the sleeve **40a** can be designed to releasably attach to the spring band **30** (FIG. **4**) and to adjustably hold and retain

the extension arm 60a (FIGS. 7 & 12-14). The sleeve 40a can include a slot 42 for receiving a portion of the spring band 30 (FIGS. 1-4) therein. The slot 42 can extend through a portion of the sleeve 40a to an opening 50. In various embodiments, the opening 50 can include a groove or notch 51 (FIGS. 6 & 8) therein. Referring again to FIGS. 1-3, when the first end 32 of the spring band 30 is positioned relative to the sleeve 40a, the first end 32 of the spring band 30 can extend through the slot 42 such that an end portion of the spring band 30 is disposed in the sleeve 40a. Further, the groove 51 of the opening 50 can hold the first distal end 32 of the spring band 30. In other embodiments, the first end 32 of the spring band 30 may be held within the slot 42 of the sleeve 40a, for example.

In various embodiments, the spring band 30 and the sleeve 40a can form a snap-fit connection. For example, referring primarily to FIG. 2, the pronged portion 36 of the spring band 30 can be narrowed or compressed to fit through the slot 42 of the sleeve 40a. In various embodiments, the opposing tabs 38a nearest the first distal end 32 should also fit through the slot 42 when the pronged portion 36 is narrowed or compressed. When the pronged portion 36 is compressed, the pronged portion 36 can exert a springback force on the sleeve 40a in which the pronged portion 36 is retained as the pronged portion 36 seeks to return or substantially return to its undeformed configuration. Opposing tabs 38a can be positioned in the opening 50 and can engage the sleeve 40a as the pronged portion 36 seeks to return to its undeformed configuration. The springback force can cause the opposing tabs 38a that are positioned in the opening 50 to catch the sleeve 40a, which can restrict detachment of the sleeve 40a from the spring band 30. For example, the opposing tabs 38a can catch the sleeve 40a such that the pronged portion 36 cannot be withdrawn through the slot 42. Furthermore, the opposing tabs 39a that are positioned outside of the sleeve 40a (FIGS. 1 & 3) can prevent over-insertion of the spring band 30 into the sleeve 40a. For example, the opposing tabs 39a can catch the sleeve 40a if the first end 32 of the spring band 30 attempts to over-advance through the slot 42. In other words, the opposing tabs 38a, 39a can releasably lock the spring band 30 in position within the sleeve 40a and can prevent unintended retraction and/or over-insertion.

Referring again to FIGS. 1-3, the sleeve 40a can releasably attach to the spring band 30. In other words, the sleeve 40a may be selectively detached from the spring band 30. For example, the pronged portion 36 of the spring band 30 can be compressed or squeezed to move the prongs inward such that the tabs 38a disengage the sleeve 40a and permit the pronged portion 36, including the opposing tabs 38a, to be withdrawn through the sleeve 40a. For example, the pronged portion 36 positioned in the opening 50 can be manually pinched and/or manipulated to release the spring band 30 from the sleeve 40a.

Referring again to FIGS. 5, 7-8, the sleeve 40a can include an opposing detent arrangement 44. The opposing detent arrangement 44 can include a group of one or more detent pockets 48 on a first internal side of the sleeve 40a and an opposing group of one or more detent pockets 48 on a second internal side of the sleeve 40a. In various embodiments, the opposing detent arrangement 44 can include a first plurality of detent pockets 48 on a first side of the sleeve 40a and a second plurality of detent pockets 48 on the second side of the sleeve 40a, preferably equal in number to the first plurality of detent pockets. The second plurality of detent pockets 48 can be laterally positioned relative to the first plurality of detent pockets 48, for example. In various embodiments, the first and second pluralities of detent pockets 48 can each be

arranged in a row. For example, the sleeve 40a can have a pair of laterally opposed channels 46a, 46b (FIG. 5) on opposing internal side of the sleeve 40a. The first channel 46a on the first internal side of the sleeve 40a can include the first plurality of detent pockets 48 arranged in a row, for example, and the second channel 46b on the second internal side of the sleeve 40a can include the second plurality of detent pockets 48 arranged in a row, for example. In various embodiments, the first channel 46a and the first plurality of detent pockets 48 can form a mirror image reflection of the second channel 46b and the second plurality of detent pockets 48. In other embodiments, the channels 46a, 46b and pluralities of detent pockets 48 on each side of the sleeve 40a may be asymmetrical.

Referring again to FIGS. 5-8, the sleeve 40a can include a wing 54 that extends from the body of the sleeve 40a. The wing 54 can be structured for attachment of the cap 80 (FIG. 8). In various embodiments, the wing 54 can have a hole 56 (FIGS. 5-7) therethrough, which can receive a fastener 90 (FIGS. 9 & 11). As described herein, the fastener 90 can secure the cap 80 to the wing 54 of the sleeve 40a. Referring primarily to FIG. 6, the sleeve 40a can have a sleeve liner 98, which can be positioned relative to the sleeve 40a to enclose or encase the opposing detent arrangement 44 of the sleeve 40a. In other words, the opposing detent arrangement 44 can be on an internal surface of the sleeve 40a. When the arm 60a is positioned relative to the sleeve 40a, as described herein, the liner 98 and the sleeve 40a can at least partially surround or enclose a portion of the arm 60a. In various embodiments, the liner 98 and the sleeve 40a can surround the arm 60a such that the arm 60a is protected as it moves relative to the sleeve 40a.

In at least one embodiment, the sleeve 40a can be approximately 2.5 inches by approximately 1.125 inches by approximately 2.25 inches with a radius of curvature of approximately 3.0 inches. In various embodiments, the dimensions of the sleeve 40a, including the radius of curvature, can be selected such that the sleeve 40a comfortably fits the user's head and/or neck. Additionally, the dimensions of the sleeve 40a can be selected such that the sleeve 40a smoothly interfaces with the other headband assembly 22 components such as the spring band 30, the arm 60a and/or the cap 80, for example. In at least one embodiment, the sleeve 40a can comprise nylon and/or acrylonitrile butadiene styrene (ABS) for example. In various embodiments, the sleeve 40a can comprise various metallic and/or polymeric materials, for example.

Referring now to FIGS. 12-14, the extension arm 60a can have a contoured or arced body. The contour of the extension arm 60a can be selected such that the extension arm 60a comfortably fits on and/or around a portion of the user's head and/or neck, for example. Further, the contour of the extension arm 60a can match or substantially match the contour of the sleeve 40a such that the extension arm 60a can move smoothly within the sleeve 40a (FIG. 7), as described herein. Referring primarily to FIGS. 13 & 14, the extension arm 60a can include an opposing detent assembly 62. The opposing detent assembly 62 can include a pair of holes 64a, 64b, which can extend inwardly from a lateral side of the extension arm 60a. The first hole 64a can be positioned on a first lateral side of the extension arm 60, for example, and the second hole 64b can be positioned on an opposite lateral side of the extension arm 60, for example. In various embodiments, the holes 64a, 64b can be positioned near a first end 61 of the extension arm 60. Alternatively or additionally, detent holes 64a, 64b may be positioned elsewhere along the length of the extension arm 60.

Referring still to FIGS. 12-14, the opposing detent assembly 62 can include a pair of detent bearings 68a, 68b. The first detent bearing 68a can be positioned at least partially in the first hole 64a, for example, and the second detent bearing 68b can be positioned at least partially in the second hole 64b, for example. As described herein, each bearing 68a, 68b can engage the opposing detent arrangement 44 of the sleeve 40a (FIGS. 5-8). In various embodiments, the detent bearings 64a, 64b can be spring-loaded bearings. Accordingly, a first coil spring 66a can be positioned in the first hole 64a and can operably exert an outward springback force on the first detent bearing 68a positioned therein. Similarly, a second coil spring 66b can be positioned in the second hole 64b and can operably exert an outward springback force on the second detent bearing 68b positioned therein.

Referring now primarily to FIG. 7, the extension arm 60a can be adjustably secured to the sleeve 40a. The first bearing 68a can adjustably engage one pocket 48 of the first plurality of detent pockets in the first channel 46a (FIG. 5) of the detent arrangement 44 and the second bearing 68b can adjustably engage one pocket 48 of the second plurality of detent pockets 48 in the second channel 46b (FIG. 5) of the detent arrangement 44. In various embodiments, the detent pockets 48 and the bearings 68a, 68b can be symmetrical. When the first bearing 68a engages one pocket 48 of the first plurality of pockets and the second bearing 68b engages one pocket 48 of the second plurality of pockets, the first and second bearings 68a, 68b can adjustably secure the arm 60a to the sleeve 40a. The opposing detent assembly 62 of the arm 60a and the opposing detent arrangement 44 of the sleeve 40 can provide for smooth and balanced adjustment of the arm 60a relative to the sleeve 40a. For example, as the first detent bearing 68a interfaces with the first plurality of detent pockets 48 in the first channel 46a and the second detent bearing 68b interfaces with the second plurality of detent pockets 48a in the second channel 46b, the springback forces generated by the opposing detent bearings 68a, 68b can be balanced. In other words, the springback force generated by the first detent bearing 68a on a first side of the sleeve 40a can match or substantially match the springback force generated by the second detent bearing 68b on an opposing side of the sleeve. Further, the forces can be balanced or substantially balanced as the detent bearings 68a, 68b of the arm 60a transition between detent pockets 48 of the sleeve 40a. The balance of forces can provide for a smoother adjustment or transition as the arm 60a extends and/or retracts relative to the sleeve 40a. In various embodiments, the opposing detent assembly 62 of the extension arm 60a can include a second pair of holes and a second pair of detent bearings. Similar to detent bearings 68a, 68b, the second pair of detent bearings may engage pockets 48 in the opposing detent arrangement 44 to adjustably secure the extension arm 60a to the sleeve 40a.

Referring again to FIG. 5, the sleeve 40a can include a retraction stop 52 that can limit movement of the arm 60a toward the spring band 30. In various embodiments, the retraction stop 52 can comprise a surface or wall at the end of the sleeve 40a. As the extension arm 60a (FIGS. 12-14) retracts into the sleeve 40, the first end 61 of the extension arm 60a can move towards the retraction stop 52 of the sleeve 50. When the first end 61 of the extension arm 60 engages or abuts the retraction stop 52, the retraction stop 52 can block the extension arm 60 such that further retraction of the extension arm 60a relative to the sleeve 40a is prevented.

Referring again to FIGS. 12-14, the extension arm 60a can include a slot 72 therein. As described herein, the slot 72 can guide movement of the cap 80a (FIGS. 8-11) relative to the extension arm 60a. In various embodiments, the extension

arm 60a can include an attachment element 74. The attachment element 74 can be positioned at or near a second end 63 of the extension arm 60, which can be substantially opposite from the first end 61 of the extension arm 60. As described herein, the attachment element 74 can facilitate attachment of the earpiece 100a (FIGS. 21 & 22). In various embodiments, the attachment element 74 and the extension arm 60 can be integrally formed. For example, the attachment element 74 can be an integral part of the extension arm 60. In certain other embodiments, the attachment element 74 and the extension arm 60 can comprise discrete components. For example, the attachment element 74 can comprise a pin, which can be secured to the extension arm 60. In at least one embodiment, the arm 60a can be approximately 3.5 inches by approximately 1.0 inches by approximately 3.0 inches with a radius of curvature of approximately 3 inches. In various embodiments, the dimensions of the arm 60a, including the radius of curvature, can be selected such that the arm 60a comfortably fits the user's head and/or neck. Additionally, the dimensions of the arm 60a can be selected such that the arm 60a smoothly interfaces with the other headband assembly 22 components such as the spring band 30, the sleeve 40a and/or the cap 80a, for example. In at least one embodiment, the arm 60a can comprise aluminum, for example. In various embodiments, the arm 60a can comprise various metallic and/or polymeric materials, for example.

Referring now to FIGS. 8-11, the cap 80a can include a two-part body and can be designed to guide and restrain movement of the arm 60a relative to the sleeve 40a. The cap 80a can be releasably fastened to the sleeve 40a. In certain embodiments, the cap 80a and the sleeve 40a can comprise an integrated component and/or can be permanently fastened together. Referring still to FIGS. 8-11, the cap 80a can include a first part 82 and a second part 84. The first part 82 of the cap 80a can include a grip portion 86. As described herein, a user can grasp the grip portion 86 to manipulate and move the sleeve 40a relative to the arm 60a when the cap 80a is secured to the sleeve 40a. The first part 82 of the cap 80a can also include a tubular protrusion 85, which can receive the fastener 90 to secure the first part 82 to the second part 84.

Referring primarily to FIG. 8, the cap 80a can attach to the wing 54 of the sleeve 40. For example, the fastener 90 can extend through the hole 56 (FIGS. 5-7) in the wing 54 of the sleeve 40a to fasten the first part 82 and the second part 84 to the wing 54. Furthermore, when the arm 60a is positioned relative to the sleeve 40a (FIG. 7), the cap 80a can be positioned around or partially around the arm 60a. In such embodiments, the tubular protrusion 85 of the cap 80a and the fastener 90 therein can extend through the slot 72 (FIG. 7) of the arm 60a. In other words, referring to FIGS. 1-3, when the cap 80a, the sleeve 40a, and the extension arm 80a are assembled, the fastener 90 and/or the tubular protrusion 85 can fit within the slot 72 of the arm 60a and the cap 80a can at least partially surround the arm 60a. Referring primarily to FIG. 11, the cap 80a can include windows 87 and/or an extension stop 88 between the windows 87. When the cap 80a, the sleeve 40a, and the arm 80a are assembled, the arm 60a can extend through the windows 87 of the cap 80 and the extension stop 88 can be positioned within the slot 72 of the arm 60a. In various embodiments, the slot 72 can guide the cap 80a and the attached sleeve 40a relative to the arm 60a as the sleeve 40a moves relative thereto. The extension stop 88 can limit movement of the arm 60a away from the spring band 30. In various embodiments, the extension stop 88 can comprise a surface or wall of the cap 80. As the extension arm 60a (FIGS. 12-14) extends from the sleeve 40a, the extension stop 88 can move towards the end of the slot 72 in the arm 60a.

## 11

When the extension stop **88** engages or abuts the end of the slot **72**, the extension stop **88** can prevent further extension of the arm **60a** relative to the sleeve **40a**.

In at least one embodiment, the cap **80a** can be approximately 1.5 inches by approximately 0.75 inches by approximately 0.5 inches. In various embodiments, the dimensions of the cap **80a** can be selected such that the cap **80a** comfortably fits the user's head and/or neck. Additionally, the dimensions of the cap **80a** can be selected such that the cap **80a** smoothly interfaces with the other headband assembly **22** components such as the sleeve **40a** and/or the arm **60a**, for example. In at least one embodiment, the cap **80a** can comprise aluminum, for example. In various embodiments, the cap **80a** can comprise various metallic and/or polymeric materials, for example.

Referring to FIGS. **15-20**, the headband assembly **22** can include one spring band **30**, two sleeves **40a, 40b**, two extension arms **60a, 60b**, and two caps **80a, 80b**. As described herein, the headband assembly **22** components can be modular. Additionally, the components on a first side of the headband assembly **22** can have a corresponding or identical component on the second side of the headband assembly. In various embodiments, the first and second sides of the headband assembly can be mirror image reflections. In certain embodiments, the components of a headband assembly may not be modular. Furthermore, the components on a first side of the headband assembly may not have corresponding or identical components on a second side of the headband assembly, for example.

Referring primarily to FIG. **16**, the headband assembly **22** can also include a frame **92**. The spring band **30** of the headband assembly **22** can fit within the frame **92**. In various embodiments, the frame **92** can provide a frame or structure for attachment of additional aesthetic components to the headband assembly **22**. The frame **92** can be molded to fit the shape and dimensions of the spring band **30**, the sleeves **40a, 40b**, the arms **60a, 60b**, and/or the caps **80a, 80b**, for example. Referring again to FIGS. **15-20**, the headband assembly **22** can include additional aesthetic components such as a covering **94** and/or a cushion **96**. The cushion **96** can be a pad or foam cushion positioned between the user's head and/or neck and the spring band **30** and/or the sleeves **40a, 40b**. In various embodiments, the covering **94** can cover the top surface of the frame **92** and/or the sides and/or the bottom surface of the cushion **96**. Furthermore, the covering **94** can include indicia **95**.

Referring now to FIGS. **21** and **22**, the assembly **20** can include the personal speaker or earphone **100a, 100b** attached or secured to the extension arm **60a, 60b** by the attachment element **74**. For example, the first earphone **100a** can be attached to the first extension arm **60a**, and the second earphone **100b** can be attached to the second extension arm **60b**. In various embodiments, the earphones **100a, 100b** can comprise in-ear, over-ear and/or around-ear earphones. Various earphones have been proposed such as those described in U.S. Pat. No. 8,190,203, the entire disclosure of which is incorporated by reference herein. For example, the earphones **100a, 100b**, can have a circular, elliptical, and/or polygonal perimeter and can be symmetrical or asymmetrical. Furthermore, the earphones **100a, 100b** can include a clevis or yoke **108** secured to a housing ring **152** (FIG. **31**). In various embodiments, the housing ring **152** can retain a speaker mount **150** (FIG. **32**) and/or a speaker element **151** (FIG. **32**) of the earphone **100a, 100b**, for example. The yoke **108** can include an attachment section **102** that connects to the attachment element **74** of the arm **60a, 60b**, for example. The attachment

## 12

element **74** can engage the attachment section **102** and can be secured by a fastener, such as a retaining ring **105** (FIG. **22**), for example.

In various embodiments, at least one of the earphones **100a, 100b** can pivot relative to the headband assembly **22** to adjust the assembly **20**. For example, the first earphone **100a** can pivot relative to the first extension arm **60a**, and/or the second earphone **100b** can pivot relative to the second extension arm **60b**. The first and/or second extension arms **60a, 60b** can pivot at a magnetic pivot arrangement **70**. In various embodiments, the first extension arm **60a** can be pivotally connected to the first earphone **100a**, for example, and the second extension arm **60b** can be pivotally connected to the second earphone **100b**, for example. Further, as described herein, the yoke **108** of one or more earphones **100a, 100b** can be pivotally connected to an earphone housing ring **152** (FIG. **31**) of the respective earphone **100a, 100b**. The yoke **108** can pivot relative to the housing ring **152** at a housing pivot arrangement **130** (FIG. **31**), for example.

Referring to FIGS. **21-24**, the first earphone **100a** can be pivotally connected to the first extension arm **60a** by the magnetic pivot arrangement **70**. Similarly, in certain embodiments, the second earphone **100b** can be pivotally connected to the second extension arm **60b** by another magnetic pivot arrangement. In various embodiments, the magnetic pivot arrangement **70** can include a magnetic element **78a** in the extension arm **60a**, and a magnetic element **122a** in the yoke **108** of the attached earphone **100a**. For example, the magnetic element **78a** in the first extension arm **60a** can pivot into and/or out of alignment with the magnetic element **122a** in the yoke **108** as the first extension arm **60a** pivots relative to the first earphone **100a**. In various embodiments, the magnetic pivot arrangement **70** can include a pair of magnetic pivot elements **78a, 78b** in the extension arm **60a**, and a pair of magnetic pivot elements **78a, 78b** in the yoke. In certain embodiments, the magnetic pivot arrangement **70** can include additional magnetic elements. As described herein, the magnetic elements **78a, 78b, 122a, 122b** can seek to maintain alignment such that the magnetic elements **78a, 78b, 122a, 122b** exert a force on the extension arm **60a** and/or the yoke **108** that pivots the extension arm **60a** relative to the yoke, for example.

Referring to FIG. **23**, the second end **63** of the extension arm **60a** can include the first pair of magnetic elements **78a, 78b** of the magnetic pivot arrangement **70**. Furthermore, the first extension arm **60a** can include a bearing surface **73**, and a first pair or recesses **79a, 79b** extending from the bearing surface **73** into the body of the extension arm **60a**. In various embodiments, each magnetic element **78a, 78b** can be embedded in a corresponding recess **79a, 79b** in the extension arm **60a**. For example, the magnetic element **78a** can be at least slightly recessed in the recess **79a** of the extension arm **60a**, such that no portion of the magnetic element **78a** projects beyond the bearing surface **73**. Further, the magnetic element **78b** can be at least slightly recessed in the recess **79b** of the extension arm **60a**, such that no portion of the magnetic element **78a** projects beyond the bearing surface **73**, for example. Referring still to FIG. **23**, the extension arm **60a** can include a groove **76** that extends from the bearing surface **73** into the body of the first extension arm **60a**. The groove **76** can form a curved profile in the second end **63** of the first extension arm **60a**, for example. In other words, the groove **76** can define a contour, which can have a radius of curvature. As described herein, the groove **76** can be configured to moveably receive a protrusion **112** (FIG. **25**) that extends from the yoke **108** (FIG. **24**) as the extension arm **60a** pivots relative to the yoke **108** of the first earphone **100a** (FIG. **21**).

Referring to FIG. 24, the attachment portion 102 of the yoke 108 can include the second pair of magnetic elements 122a, 122b. Furthermore, the attachment portion 102 can include a second pair of recesses 118a, 118b that can extend from a mating surface 117 of the yoke 108 into the body of the yoke 108. In various embodiments, each magnetic element 122a, 122b can be embedded in a corresponding recess 118a, 118b in the attachment portion 102 of the yoke 108. For example, the magnetic element 122a can be at least slightly recessed in the recess 118a of the yoke 108, such that no portion of the magnetic element 122a projects beyond the mating surface 117. Further, the magnetic element 122b can be at least slightly recessed in the recess 122b of the yoke 108, such that no portion of the magnetic element 122a projects beyond the mating surface 117, for example. Referring still to FIG. 24, the attachment portion 102 of the yoke 108 can include an aperture 116 that extends through the yoke 108. The aperture 116 can be configured to receive the attachment element 74 (FIG. 23) of the first extension arm 60a (FIG. 23) when the first extension arm 60a is positioned relative to the yoke 108, for example.

Referring now to FIGS. 25 and 26, the magnetic pivot arrangement 70 can include a pivot plate 110, which can include the protrusion 112. In various embodiments, the protrusion 112 can form a curved profile that can match or substantially match the profile of the groove 76 (FIG. 23). In other words, the protrusion 112 can define a contour, which can have a radius of curvature that matches the radius of curvature of the groove 76 contour. For example, at least a portion of the groove 76 can have a radius of curvature of approximately 0.15 inches to approximately 0.25 inches, and at least a portion of the protrusion 112 can have a radius of curvature of approximately 0.2 inches. Furthermore, the protrusion 112 can have a width that is at least slightly smaller than the width of the groove 76 such that the protrusion 112 or at least a portion thereof can fit within the groove 76. For example, the width of the groove 76 can be approximately 0.95 inches to approximately 0.105 inches, and the width of the protrusion 112 can be approximately 0.09 inches to approximately 0.094 inches. In various embodiments, the difference between the width of the protrusion 112 and the width of the groove 76 can be approximately 0.001 inches to approximately 0.015 inches. In at least one embodiment, the groove 76 can guide the protrusion 112 as the protrusion 112 moves therein. For example, the protrusion 112 can slide along at least a length of the groove 76 when the pivot plate 110 is positioned relative to the first extension arm 60a. In various embodiments, the length of the protrusion can be approximately 20% to approximately 30% the length of the groove 76, for example. Referring still to the FIG. 25, the pivot plate 110 can include an aperture 114 therethrough. In various embodiments, the aperture 114 can be configured to receive the attachment element 74 (FIG. 23) of the first extension arm 60a (FIG. 23) when the pivot plate 110 is positioned relative to the second extension arm 60a, for example as illustrated in FIG. 27. As described herein, the attachment element 74 can pivot in the aperture 114 of the pivot plate 110 as the extension arm 60a pivots relative to the yoke 108 of the first earphone 100a.

Referring to FIGS. 24-26, the pivot plate 110 can be secured to the attachment section 102 of the yoke 108. In various embodiments, the yoke 108 can include a mating surface 117, and a rim 115, which can extend from the mating surface 117. The rim 115 can surround or partially surround the mating surface 117 of the attachment section 102, for example. In various embodiments, the pivot plate 110 can be positioned relative to the attachment section 102 of the yoke

108, such that the pivot plate 110 nests in the attachment section 102. For example, the pivot plate 110 can be positioned flush with the mating surface 117, and the rim 115 can extend at least partially around the perimeter of the pivot plate 110, for example. In various embodiments, the rim 115 can help to retain the pivot plate 110 relative to the yoke 108. For example, the rim 115 can surround or partially surround the pivot plate 110 to prevent lateral movement of the pivot plate 110 relative to the yoke 108. In certain embodiments, at least a portion of the pivot plate 110 can be substantially flush with the rim 115 of the yoke 108, and the protrusion 112 can extend beyond the rim 115 of the yoke 108, for example. The pivot plate 110 can be non-pivotally secured to the attachment section 102 of the yoke 108 such that the projection 112 remains fixed relative to the yoke 108 as the first extension arm 60a pivots relative to yoke 108 and the first earpiece 100a. Referring again to FIG. 25, when the pivot plate 110 is secured to the yoke 108, the pivot plate 110 can enclose and/or retain the magnetic elements 122a, 122b in the recesses 118a, 118b of the attachment section 102. For example, the pivot plate 110 can cover the magnetic elements 122a, 122b positioned in the yoke 108. In various embodiments, the pivot plate 110 can be positioned between the magnetic elements 78a, 78b positioned in the extension arm 60a and the magnetic elements 122a, 122b positioned in the yoke 108. For example, the pivot plate 110 can extend between the pairs of magnetic elements 78a, 78b, 122a, 122b.

Referring now to FIGS. 27-29, the retaining ring 105 can secure the yoke 108 to the extension arm 60a. In various embodiments, the bearing surface 74 (FIG. 23) of the extension arm 60a can be positioned relative to the bearing surface 119 (FIGS. 25 and 26) of the pivot plate and the yoke 108. For example, the bearing surface 119 of the pivot plate can be adjacent to, flush with and/or abutting the bearing surface 74 of the extension 60a. The bearing surfaces 74, 119 can be configured to pivot relative to each other, for example. In at least one embodiment, the attachment element 74 of the first extension arm 60a can extend through the aperture 114 in the pivot plate 110 and/or through the aperture 116 in the attachment section 102 of the yoke 108. In various embodiments, the retaining ring 105 can grip the attachment element 74 between a distal shoulder of the attachment element 74 and the yoke 108. The retaining ring 105 can hold the attachment element 74 within the apertures 114, 116 to secure the first extension arm 60a relative to the yoke 108, for example. In various embodiments, a shouldered portion of the attachment element and/or a washer 104 can be positioned between the retaining ring 105 and the yoke 108.

Referring still to FIGS. 27-29, when the attachment element 74 engages the yoke 108 to secure the first extension arm 60a to the yoke 108, the pivot plate 110 can be positioned and held therebetween. In other words, the pivot plate 110 can be sandwiched between the first extension arm 60a and the yoke 108, for example. In certain embodiments, the attachment element 74 and the retaining ring 105 can secure the pivot plate 110 between the yoke 108 and the first extension arm 60a. Additionally or alternatively, the pivot plate 110 can be integrally formed with the yoke 108. In various embodiments, the pivot plate 110 can be fixedly secured to the yoke 108, and the protrusion 112 can extend into the groove 76 in the extension arm 60a. Further, in at least one embodiment, the attachment element 74 of the first extension arm 60a can pivot in the apertures 114, 116 (FIGS. 24 and 25) of the yoke 108 as the first extension arm 60a pivots relative to the yoke 108. As the attachment element 74 pivots in the apertures 114, 116, the protrusion 112 extending from the pivot plate 110 can slide in the groove 76 of the extension arm 60a.

Referring primarily to FIG. 29, the groove 74 can include rotational stops 77a, 77b. In various embodiments, the attachment element 74 can pivot in a first direction relative to the yoke 108 until the protrusion 112 in the groove 76 abuts the first rotational stop 77a, and the attachment element 74 can pivot in a second, opposite direction relative to the yoke 108 until the protrusion 112 in the groove 76 abuts the second rotational stop 77b. In other words, the rotational stops 77a, 77b can limit the range of rotation of the first extension arm 60a relative to the yoke 108. In various embodiments, the rotational stops 77a, 77b of the groove 76 can permit approximately  $\pm 90$  degrees of rotation, or 180 degrees of rotation, for example. In other embodiments, the rotational stops 77a, 77b of the groove 76 can permit less than 180 degrees or more than 180 degrees, for example. In at least one embodiment, the groove 76 can comprise a complete loop or contour such that the groove 76 does not include rotational stops 77a, 77b. In certain embodiments where the groove 76 forms a complete loop, the extension arm 60a can rotate  $\pm 360$  degrees, for example.

In various embodiments, when the first extension arm 60a pivots relative to the yoke 108, the magnetic elements 78a, 78b in the extension arm 60a can pivot relative to the magnetic elements 122a, 122b in the yoke 108. The magnetic poles of the magnetic elements 78a, 78b, 122a, 122b can be arranged such that the magnetic elements 78a, 78b in the first extension arm 60a seek to substantially align with the corresponding magnetic elements 122a, 122b in the yoke 108. For example, the magnetic element 78a can seek alignment with the magnetic element 122a, and the magnetic element 78b can seek alignment with the magnetic element 122b. In various embodiments, when the yoke is pivoted away from a neutral position and into a second, pivoted position, as described herein, a magnetic attraction between the magnetic element 78b, for example, and the magnetic element 122b, for example, can pull the magnetic poles of the magnetic elements 78b, 122b toward alignment. In other words, the magnetic element 78a can exert a magnetic pulling force on magnetic element 122a, and magnetic element 78a can exert a magnetic pulling force on magnetic element 122b. Further, in various embodiments, the magnetic element 78a can resist alignment with the magnetic element 122b, and the magnetic element 78b can resist alignment with the magnetic element 122a, for example. For example, when yoke is pivoted away from a neutral position and into a second pivoted position, as described herein, the magnetic element 78a can exert a magnetic pushing force on magnetic element 122b, and magnetic element 78b can exert a magnetic pushing force on magnetic element 122b. In various embodiments, the magnetic elements 78a, 78b, 122a, 122b can be made of hard, magnetic material. The magnetic elements 78a, 78b, 122a, 122b can be permanent magnets, for example.

In various embodiments, the yoke 108 can pivot between a neutral position and pivoted positions. For example, the yoke 108 can pivot between a first neutral position, a counterclockwise second position, and clockwise second position. The first position can be between the counterclockwise second position and the clockwise second position, for example. In various embodiments, the magnetic element 78a can be aligned with the magnetic element 122a and the magnetic element 78b can be aligned with the magnetic element 122b when the yoke 108 is in the first, neutral position relative to the extension arm 60a. When the yoke 108 pivots toward the counterclockwise or clockwise second position, the magnetic element 78a can move out of alignment with magnetic element 122a and the magnetic element 78b can move out alignment with the magnetic element 122b. As the yoke 108 pivots

toward the clockwise second position, magnetic element 78a can move toward alignment with the magnetic element 122b. In various embodiments, the poles of magnetic elements 78a, 122b can be arranged such that the magnetic elements 78a, 122b resist alignment. In other words, magnetic element 78a can exert a magnetic pushing force on magnetic element 122b, for example. As the yoke 108 pivots toward the counterclockwise second position, the magnetic element 78b can move toward alignment with the magnetic element 122a. In various embodiments, the poles of magnetic elements 78b, 122a can be arranged such that the magnetic elements 78b, 122a resist alignment. In other words, the magnetic element 78b can exert a magnetic pushing force on magnetic element 122a, for example. In at least one embodiment, when the yoke 108 is in the first position relative to the arm 60a, the positive pole of the magnetic element 78a can correspond to the negative pole of the magnetic element 122a, for example, and the negative pole of the magnetic element 78b can correspond to the positive pole of the magnetic element 122b, for example. The reader will understand that the magnetic pivot arrangement 70 can include additional or fewer magnetic elements, that alternative arrangements of the magnetic elements are possible, and that such arrangements are within the scope of this disclosure.

In use, a user can adjust or manipulate the assembly 20 by pivoting the yoke 108 relative to the attached extension arm 60a. For example, the magnetic elements 78a, 78b in the first extension arm 60a can be pivoted out of alignment with the magnetic elements 122a, 122b of the yoke 108 when the user positions the assembly 20 relative to the user's head and/or neck. Once misaligned, the magnetic elements 78a, 78b, 122a, 122b of the magnetic pivot arrangement 70 can seek to realign. In various embodiments, the magnetic elements 78a, 78b can exert a magnetic pull on magnetic elements 122a, 122c to pivot or attempt to pivot the magnetic pivot arrangement 70 back into realignment. In certain embodiments, the magnetic pull or force generated by the magnetic elements 78a, 78b, 122a, 122b can hold the assembly 20 in position relative to a user's head or neck. For example, the magnetic elements 78a, 78b, 122a, 122b can exert a force that comfortably secures the earphone assembly without apply an excessive force to the user's head and/or neck. Further, when the assembly 20 is removed from the user's head or neck and/or when the user stops actively adjusting the assembly 20, the magnetic pivot mechanism 70 can pivot the yoke 108 relative to the first extension arm 60a such that the magnetic pivot arrangement 70 returns to alignment and the assembly 20 returns to its initial configuration. In other words, the yoke can pivot back to the neutral position.

Referring primarily to FIGS. 30-34, the first earphone 100a can include the housing pivot arrangement 130, which can permit the housing ring 152 to pivot relative to the yoke 108. For example, the housing ring 152 can be pivotally secured to the yoke 108 at a housing pivot arrangement 130. In certain embodiments, the housing ring 152 can be pivotally secured to the yoke 108 at two opposing housing pivot arrangements 130. As described herein, the housing ring 152 can be secured to the yoke 108 by the housing pivot arrangement 130, which can permit the housing ring 152 to pivot relative to the yoke 108, for example. In various embodiments, the housing ring 152 can support the speaker mount 150 (FIG. 32), an outer housing 154 (FIG. 31), and/or an ear cushion 148 (FIG. 30) of the first earphone 100a, for example. The housing ring 152 can form a ring or partial ring that defines a perimeter of the earphone 100a, for example. Referring primarily to FIG. 32, the speaker mount 150 can be positioned between the outer housing 154 (FIG. 31) and the ear cushion 148, for example,

such that the speaker mount **150** is secured within the first earphone **100a**. In certain embodiments, the speaker element **151** can be secured to the speaker mount **150** within the first earphone **100a**. In other words, various speaker elements can be positioned in the first earphone **100a** and/or can be contained within and/or by the housing ring **152**, for example.

Referring now to FIGS. **32** and **33**, the housing ring **152** can include a plurality of flanges **158** with apertures **159** there-through. In various embodiments, a fastener can engage the flanges **158** of the housing ring **152** to secure the housing ring **152** to the outer housing **154** and/or to the speaker mount **150**. For example, a fastener, such as a bolt **160**, can extend through an aperture **153** (FIG. **32**) in the speaker mount **150**, an aperture **159** (FIG. **33**) in the flange **158** of the housing ring **152**, and/or an aperture **164** (FIG. **33**) in the outer housing **154**, for example. The flanges **158** can be positioned around an inner perimeter of the housing ring **152**, for example. In various embodiments, four flanges **158** can be spaced around the inner perimeter of the housing ring **152**. In certain embodiments, less than or more than four flanges **158** can be spaced around the inner perimeter of the housing ring **152**, such that the outer housing **154**, speaker mount **150** and/or ear cushion **148** are sufficiently secured to the housing ring **152**.

Referring primarily to FIGS. **32-34**, a portion of the housing ring **152** can hold a collar **132** of the housing pivot arrangement **130**. For example, the housing ring **152** can include a shelf **140**, which can be configured to hold or retain the collar **132**. In certain embodiments, the housing ring **152** can house or retain opposing collars **132** therein. In various embodiments, shelves **140** can be positioned on multiple sides of the collar **132** to hold the opposing collars **132** therebetween. Furthermore, the speaker mount **150** can be positioned on another side of the collar (FIG. **32**), and/or the outer housing **154** can be positioned on still another side of the collar (FIG. **33**). In certain embodiments, a portion of the outer housing **154**, such as extension **142**, for example, can be positioned on still another side of the collar. In various embodiments, when multiple components of the earphone **100a** are assembled, the multiple components can be configured to hold the collar **132** in position relative to the housing ring **152**. For example, the shelf **140**, a portion of the speaker mount **150**, a portion of the outer housing, and/or the extension **142** can at least partially surround the collar **132** such that the collar **132** is fixed in position relative to the housing ring **152**, for example. In other words, in various embodiments, the collar **132** can be immovably or non-pivotally secured to the housing ring **152**. The reader will understand that various different and/or additional components can help to retain the collar **132** relative to the housing ring **152**.

Referring primarily to FIG. **35**, the pivot pin **138** of the housing pivot arrangement **130** can engage the yoke **108**. In various embodiments, the yoke can have a hub **144**, and a portion of the pivot pin **138** can extend into an aperture **143** (FIG. **24**) in the hub **144**. In various embodiments, the yoke **108** can have two hubs **144** on opposing sides of the yoke **108**, for example, and a pivot pin **138** can be secured to each hub **144**. The pivot pin **138** can be fastened or secured to the hub **144**, for example, or can be integrally formed with the hub **144**, for example. In various embodiments, the pivot pin **138** can be fixedly or non-pivotally connected to the hub **144** of the yoke **108**. Referring again to FIGS. **30-34**, the yoke **108** can extend at least partially around the housing ring **152**, such that the hubs **144** of the yoke **108** are positioned on opposite sides of the housing ring **152**, for example. Further, the pivot pins **138**, which extend from the hubs **144**, can each extend through an aperture **145** (FIG. **31**) in the housing ring **152** and into the collar **132** that is secured therein. In various embodi-

ments, the housing ring **152** can be pivotally connected to the yoke **108** by the housing pivot arrangement **130**, which includes the collar **132** and the pivot pin **138**. For example, the pivot pin **138** extending from the housing ring **152** can pivot within the aperture **145** of the housing ring **152** and in the collar **132**. In certain embodiments, the housing ring **152** can be pivotally connected to the yoke **108** at opposing housing pivot arrangement **130** positioned on opposite sides of the housing ring **152**. In other words, the housing ring **152** can pivot relative to the yoke **108** at opposing housing pivot arrangements **130**. The collar **132** can be fixed relative to the housing ring **152**, such that pivoting of the pivot pin **138** causes the yoke **108** to pivot in the collar **132** and relative to the housing ring **152**. As described herein, the collar **132** can control the rotational direction and/or the range of rotation of the pivot pin **138** and the yoke **108** relative to the housing ring **152**, for example.

In various embodiments, referring primarily to FIGS. **36** and **37**, the collar **132** can include an opening or space **135**, an arm **134**, and/or a wedge stop **136**. The arm **134** can define a first side or surface of the opening **135**, for example, and/or the wedge stop **136** can define a second side or surface of the opening **135**, for example. In various embodiments, the wedge stop **136** surface can be angularly oriented relative to the arm **134** surface, for example. In certain embodiments, as described herein, the pivot pin **138** can be received in the opening **135** of the collar **136**. For example, the pivot pin **138** can extend from the hub **144** of the yoke **108** (FIG. **35**) and to between the arm **134** and the wedge stop **136** of the collar **132**. The arm **134** and the wedge stop **136** can control the pivoting movement of the pivot pin **138** in the opening **135**. For example, the pivot pin **138** can pivot counterclockwise from the vertical configuration (FIG. **37**) until the pivot pin **138** reaches the wedge stop **136**. In various embodiments, as the pivot pin **138** pivots towards the wedge stop **136**, the arm **134** can flex, move outward or deform to accommodate the pivot pin **138**. Further, when the pivot pin **138** abuts the wedge stop **136** further rotation of the pivot pin **138** can be prevented by the wedge stop **136**. Referring still to FIGS. **36** and **37**, clockwise rotation of the pivot pin from the vertical configuration can be prevented by the flexible arm **134** and the non-wedged portion of the collar **132**. In alternative embodiments, the opening **135** in the collar **132** can permit approximately 20 degrees of rotation, for example. In other embodiments, the opening **135** can permit less than or more than 20 degrees of rotation, for example. Further, in various embodiments, the opening **135** can be configured to permit clockwise rotation and prevent counterclockwise rotation, for example.

In various embodiments, the collar **132** can be more flexible than the pivot pin **138** such that the arm **134** of the collar **132** substantially flexes or deforms and the pivot pin **138** substantially maintains its shape when the pivot pin **138** pivots into and/or against the arm **134**. For example, the collar **132** can comprise a sufficiently resilient material, such that the flexible **134** can flex or deform to accommodate the pivot pin **138**, and can subsequently return or substantially return to its undeformed position when the pivot pin returns to its initial, non-pivoted configuration. In certain embodiments, the collar **132** can comprise an elastomeric material such as urethane, for example. Further, in certain embodiments, the pivot pin **138** can comprise a substantially rigid material such as brass, for example.

Referring again to FIGS. **32** and **33**, in use, the pivot pin **138** can pivot or turn in the collar **130** to adjust the position of the yoke **108** relative to the housing ring **152**. For example, the pivot pin **138** can pivot away from the arm **134** toward the wedge stop **136** when the user positions the assembly **20**



19

relative to the user's head and/or neck. When the pivot pin **138** pivots toward the wedge stop **136**, the pivot pin **138** can exert a force on the arm **134** such that the arm **134** deforms or flexes to accommodate the pivot pin **138**. In various embodiments, the arm **134** can exert a springback force on the pivot pin **138**, which can help to maintain the relative positions of the yoke **108** and the housing ring **152**, for example. Furthermore, the relative positions of the yoke **108** and the housing ring **152** can help to hold the assembly **20** in position relative to a user's head or neck. For example, the ring housing **152** can be pivoted toward a user's ear, such that the ear cushion **148** of the earpiece **100a** exerts a force on the user's ear that comfortably secures the assembly **20** relative to the user's head and/or neck without applying an excessive force thereto. Further, when the assembly **20** is removed from the user's head or neck and/or when the user stops actively adjusting the assembly **20**, the arm **134** of the collar **132** can exert a force on the pivot pin **138** that causes the pivot pin **138** to pivot away from the wedge stop **136** and toward the arm **134** such that the housing pivot mechanism **130** pivots the ring housing **152** relative to the yoke **108** and the assembly **20** returns to its initial configuration.

In various embodiments, each earphone **100a**, **100b** can include an electrical conduit or wire (not shown) for transmitting audio signals from the audio source. The wire can connect to a receiver or jack **166** (FIG. **31**) of the earphone **100a**, **100b**, for example. Alternatively or additionally, the earphones **100a**, **100b** can include a wireless transmission assembly. In such a wireless assembly, the earpieces may not be physically coupled to the audio source, but can include a battery pack (not shown) and a transceiver (not shown) for wirelessly receiving the audio signal. In various embodiments, one of the earphones **100a**, **100b** can be coupled to a wire for receiving audio signals, and the other earphone **100a**, **100b** can be wirelessly coupled to the wired earphone **100a**, **100b**. In various wired embodiments, the headband assembly **22** can include an electrical conduit or wire (not shown) that passes through the headband assembly **22** from the first earphone **100a** to the second earphone **100b**. For example, a wire can run from the first earphone **100a**, along the first arm **60a**, the first sleeve **40a**, the spring band **30**, the second sleeve **40b**, and the second arm **60b**, to the second earphone **100b**, for example. The wire can be embedded in the headband assembly **22** and/or covered by the frame **92**, cover **94** and/or foam **98**, for example.

At least one embodiment of the present disclosure relates to a headband assembly for holding a personal speaker relative to a user's ear, wherein the headband assembly comprises a spring band, a sleeve in which is disposed a first end portion of the spring band, and an arm. In such embodiments, the sleeve comprises a first plurality of detent pockets and a second plurality of detent pockets positioned laterally relative to the first plurality of detent pockets. Furthermore, the arm comprises a first spring-loaded bearing that adjustably engages one pocket of the first plurality of detent pockets and a second spring-loaded bearing that adjustably engages one pocket of the second plurality of detent pockets. Additionally, the first and second spring-loaded bearings adjustably secure the arm to the sleeve when the first spring-loaded bearing engages one pocket of the first plurality of detent pockets and the second spring-loaded bearing engages one pocket of the second plurality of detent pockets.

In some of these embodiments, the headband assembly further comprises a second sleeve in which is disposed a second end portion of the spring band, and a second arm. In such embodiments, the second sleeve comprises a first plurality of detent pockets and a second plurality of detent pock-

20

ets positioned laterally relative to the first plurality of detent pockets. Furthermore, the second arm comprises a first spring-loaded bearing that adjustably engages one pocket of the first plurality of detent pockets of the second sleeve and a second spring-loaded bearing that adjustably engages one pocket of the second plurality of detent pockets of the second sleeve. Additionally, the first and second spring-loaded bearings of the second arm adjustably secure the second arm to the second sleeve when the first spring-loaded bearing engages one pocket of the first plurality of detent pockets of the second sleeve and the second spring-loaded bearing engages one pocket of the second plurality of detent pockets of the second sleeve. In some of these embodiments, the headband assembly further comprises a first personal speaker attached to the arm, and a second personal speaker attached to the second arm.

In some embodiments, the spring band comprises a pronged portion at the first end portion and laterally opposed tabs that maintain connection between the sleeve and the pronged portion received therein. Furthermore, the pronged portion exerts a springback force on the sleeve when the pronged portion is disposed in the sleeve. In some of these embodiments, the spring band and the sleeve form a snap-fit connection. In some embodiments, the headband assembly comprises a cap attached to the sleeve and at least partially surrounding the arm, wherein the cap guides the arm relative to the sleeve. In some of these embodiments, the arm comprises a slot that receives a portion of the cap, and the portion of the cap is slidable within the slot as the arm moves relative to the sleeve. In some of these embodiments, the cap comprises an extension stop that operably engages an end of the slot to limit movement of the arm away from the spring band.

In some embodiments, the sleeve comprises a retraction stop that operably engages an end of the arm to limit movement of the arm toward the spring band. In some embodiments, the headband assembly comprises a liner positionable relative to the sleeve such that the liner and the sleeve at least partially surround a portion of the arm. In some embodiments, the headband assembly comprises at least one aesthetic component. In some of these embodiments, at least one aesthetic component is selected from a group comprising a frame, a cushion, a cover, and an indicia.

At least one embodiment of the present disclosure relates to a headband assembly comprising a band, a first sleeve attached to an end portion of the band, and a first extension moveably secured to the first sleeve. Furthermore, the first sleeve comprises a pair of laterally opposed detent channels. Additionally, the first extension comprises a pair of spring-loaded bearings, and each spring-loaded bearing engages one of the pair of laterally opposed detent channels.

In some of these embodiments, the headband assembly comprises a personal speaker secured to the first arm. In some embodiments, the headband assembly comprises a cap removably attached to the first sleeve and positioned around a portion of the first arm, wherein the cap guides the first arm relative to the first sleeve. In some embodiments, the headband assembly comprises a second sleeve attached to another end of the band, and a second extension moveably secured to the second sleeve. In such embodiments, the second sleeve comprises a second pair of laterally opposed detent channels, and the second extension comprises a second pair of spring-loaded bearings, wherein each spring-loaded bearing of the second extension engages one of the second pair of laterally opposed detent channels of the second sleeve.

At least one embodiment of the present disclosure relates to an assembly comprising an extension arm, an attachment element, and a spring member secured to the attachment

element. In such embodiments, the extension arm comprises a first detent bearing and a second detent bearing. Furthermore, in such embodiments, the attachment element comprises a first row of detent pockets that receives the first detent bearing, and a second row of detent pockets that receives the second detent bearing, wherein the first row of detent pockets laterally opposes the second row of detent pockets, and wherein the extension arm is moveably positioned relative to the attachment element.

In some of these embodiments, the assembly comprises a second extension arm and a second attachment element. In such embodiments, the second extension arm comprises a first detent bearing and a second detent bearing. Additionally, in such embodiments, the spring member is secured to the second attachment member, which comprises a first row of detent pockets that receives the first detent bearing of the second extension arm, and a second row of detent pockets that receives the second detent bearing of the second extension arm, wherein the first row of detent pockets laterally opposes the second row of detent pockets, and wherein the second extension arm is moveably positionable relative to the second attachment element.

In some of these embodiments, the assembly comprises a plurality of personal speakers. In some embodiments, the assembly comprises a first cap and a second cap. Furthermore, the first cap is attached to the first attachment portion and positioned around a portion of the first extension arm, wherein the first cap guides the first extension relative to the first attachment element. Additionally, in such embodiments, the second cap is removably attached to the second attachment portion and positioned around a portion of the second extension arm, wherein the second cap guides the second extension relative to the second attachment element.

At least one embodiment of the present disclosure relates to a headband assembly for holding a personal speaker relative to a user's ears. The headband assembly comprises a band and a yoke configured to support the personal speaker. The band comprises a band body, a groove, and a first band magnetic element. The band body comprises a first surface, and the groove extends from the first surface into the band body. The yoke comprises a yoke body, a protrusion, and a first yoke magnetic element. The yoke body comprises a second surface, wherein the second surface is positioned relative to the first surface, and the protrusion extends from the second surface into the groove of the band. The yoke is configured to pivot between a first position and at least one second position relative to the band, wherein a magnetic pole of the first band magnetic element is aligned with a magnetic pole of the first yoke magnetic element when the yoke is in a first position, and wherein a magnetic attraction between the first band magnetic element and the first yoke magnetic element pulls the magnetic poles of the first yoke magnetic element and the first band magnetic element toward aligned when the yoke is in the second position.

In some of these embodiments, the band comprises a second band magnetic element, the yoke comprises a second yoke magnetic element, and a pole of the second band magnetic element is aligned with a pole of the second yoke magnetic element when the yoke is in the first position, and a magnetic attraction between the second band magnetic element and the second yoke magnetic element pulls the magnetic poles of the second yoke magnetic element and the second band magnetic element toward alignment when the yoke is in the second position. In some of these embodiments, the first yoke magnetic element resists alignment with the second band magnetic element, and the second yoke magnetic element resists alignment with the first band magnetic

element. In some embodiments, the first and second band magnetic elements are recessed in the band to at least flush with the first surface, and the first and second yoke magnetic elements are recessed in the yoke to at least flush with the second surface.

In some of these embodiments, the groove defines a contour having a first radius of curvature, the protrusion defines a contour having a second radius of curvature, and the second radius of curvature substantially matches the first radius of curvature. In some embodiments, the groove defines a first rotational stop, and the yoke is configured to pivot in a first direction relative to the band until the protrusion abuts the first rotational stop. In some of these embodiments, the groove defines a second rotational stop, and the yoke is configured to pivot in a second direction relative to the band until the protrusion abuts the second rotational stop, wherein the second direction is opposite to the first direction.

In some of these embodiments, the headband assembly comprises a pin configured to hold the second surface of the yoke relative to the first surface of the band. In some of these embodiments, the pin extends from the band and pivotally engages an aperture in the yoke. In some of these embodiments, a retainer secures the pin within the aperture. In some embodiments, the headband assembly comprises a pivot plate secured to the yoke, wherein the pivot plate comprises the protrusion, and wherein the pivot plate is positioned between the first band magnetic element and the second band magnetic element.

At least one embodiment of the present disclosure relates to a headband assembly comprising a band, and a yoke configured to pivot between a neutral position and pivoted positions. The band comprises a band body, a groove, and a first pair of magnetic elements. The band body comprises a first surface, and the groove extends from the first surface into the band body. The yoke comprises a yoke body, a protrusion, and a second pair of magnetic elements. The yoke body comprises a second surface, and the protrusion extends from the second surface into the groove of the band. The yoke is configured to pivot between a neutral position and pivoted positions relative to the band, the first and second pairs of magnetic elements interact to generate a magnetic force, and the magnetic force forces the yoke toward the neutral position when the yoke is in one of the pivoted positions.

In some of these embodiments, the magnetic force comprises a pulling force that seeks to pull the yoke from a pivoted position to the neutral position. In some embodiments, the magnetic force comprises a pushing force that resists movement of the yoke from the neutral position to one of the pivoted positions. In some embodiments, the groove is positioned substantially between the magnetic elements of the first pair of magnetic elements, and the protrusion is positioned substantially between the magnetic elements of the second pair of magnetic elements.

In some of these embodiments, the first pair of magnetic elements are embedded in the band, and the second pair of magnetic elements are embedded in the yoke. In some embodiments, the groove is defined by a first and second stop, and the yoke is configured to pivot in a first direction until the protrusion abuts the first stop and in a second direction until the protrusion abuts the second stop. In some embodiments, the headband assembly comprises a pivot plate positioned between the first surface of the band and the second surface of the yoke. In some of these embodiments, the pivot plate extends between the first pair of magnetic elements and the second pair of magnetic elements. In some embodiments, the headband assembly comprises a plurality of personal speakers.

At least one embodiment of the present disclosure relates to an earpiece for holding a personal speaker, wherein the earpiece comprises a housing configured to hold the personal speaker, and a yoke pivotally secured to the housing. The housing comprises a collar comprising an arm comprising an arm surface, a stop comprising a stop surface, and an opening between the arm surface and the stop surface. The stop surface is angularly oriented relative to the arm surface. The yoke comprises a pin configured to engage the housing, wherein the pin comprises a head, wherein the head is configured to extend into the opening in the collar, and wherein the head is configured to pivot between the arm surface and the stop surface.

In some of these embodiments, the collar comprises an elastomeric material. In some embodiments, the collar comprises a retainer configured to hold the collar in the housing. In some of these embodiments, the retainer comprises a plurality of walls around the collar. In some of these embodiments, the housing comprising an outer housing, and the plurality of walls comprises an extension that extends from the outer housing. In some embodiments, the plurality of walls comprises a speaker mount positioned in the housing. In some embodiments, the plurality of walls comprises a shelf that extends from the housing.

In some of these embodiments, the arm is configured to deform as the pin pivots from the arm surface toward the stop surface, and the arm seeks to return to its undeformed configuration. In some embodiments, the housing comprises a second collar that comprises an arm comprising an arm surface, a stop comprising a stop surface, and an opening between the arm surface and stop surface. The stop surface is angularly oriented relative to the arm surface. The yoke comprises a second pin configured to engage the housing, wherein the second pin comprises a head, wherein the head is configured to extend into the opening in the second collar, and wherein the head is configured to pivot between the arm surface and the stop surface of the second collar. In some of these embodiments, the pin extends toward the collar in a first direction, wherein the second pin extends toward the second collar in a second direction, and wherein the second direction is substantially opposite to the first direction. In some embodiments, the collar is positioned on a first side of the housing, wherein the second collar is positioned on a second side of the housing, and wherein the first side is substantially opposite to the second side.

At least one embodiment of the present disclosure relates to an earpiece assembly comprising a housing configured to hold a personal speaker, a collar fixed to the housing, a yoke, wherein the housing is configured to pivot relative to the yoke, and a pin fixed to the yoke. The collar comprises a flexible arm comprising an arm surface and a stop comprising a stop surface, wherein the stop surface is angularly oriented relative to the arm surface. The pin extends from the yoke to between the flexible arm and the stop of the collar, and the pin is configured to deform the flexible arm as the pin pivots from the arm surface toward the stop surface of the collar.

In some of these embodiments, the pin is configured to pivot from the arm surface to the stop surface, and the stop surface limits further pivoting of the pin. In some embodiments, the collar comprises an elastomeric material. In some of these embodiments, the pin is substantially rigid. In some embodiments, the earpiece assembly comprises a second collar fixed to the housing and a second pin fixed to the yoke. The second collar comprises a flexible arm comprising an arm surface, and a stop comprising a stop surface, wherein the stop surface is angularly oriented relative to the arm surface. The second pin extends from the yoke to between the flexible

arm and the stop of the second collar, and the second pin is configured to deform the flexible arm of the second collar as the second pin pivots from the arm surface toward the stop surface of the second collar. In some of these embodiments, the yoke is pivotally fastened to the housing at the pin and the second pin. In some embodiments, the pin extends from the yoke in a first direction, the second pin extends from the yoke in a second direction, and the second direction is substantially opposite to the first direction. In some embodiments, the collar is laterally opposed to the second collar. In some embodiments, the earpiece assembly comprises a personal speaker.

Various embodiments of the present invention are described and illustrated in this specification to provide an overall understanding of the steps and uses of the disclosed devices and methods. It is understood that the various embodiments described and illustrated in this specification are non-limiting and non-exhaustive. Thus, the invention is not limited by the description of the various non-limiting and non-exhaustive embodiments disclosed in this specification. In appropriate circumstances, the features and characteristics described in connection with various embodiments may be combined with the features and characteristics of other embodiments. Such modifications and variations are intended to be included within the scope of this specification. As such, the claims may be amended to recite any steps, limitations, features, and/or characteristics expressly or inherently described in, or otherwise expressly or inherently supported by, this specification. Further, Applicant(s) reserves the right to amend the claims to affirmatively disclaim steps, limitations, features, and/or characteristics that are present in the prior art regardless of whether such features are explicitly described herein. Therefore, any such amendments comply with the requirements of 35 U.S.C. §112, first paragraph, and 35 U.S.C. §132(a). The various embodiments disclosed and described in this specification can comprise, consist of, or consist essentially of the steps, limitations, features, and/or characteristics as variously described herein.

The grammatical articles “one”, “a”, “an”, and “the”, if and as used in this specification, are intended to include “at least one” or “one or more”, unless otherwise indicated. Thus, the articles are used in this specification to refer to one or more than one (i.e., to “at least one”) of the grammatical objects of the article. By way of example, “a component” means one or more components, and thus, possibly, more than one component is contemplated and may be employed or used in an implementation of the described embodiments. Further, the use of a singular noun includes the plural, and the use of a plural noun includes the singular, unless the context of the usage requires otherwise.

The invention claimed is:

1. A headband assembly for holding a personal speaker relative to a user’s ear, wherein the headband assembly comprises:

- a spring band;
- a sleeve in which is disposed a first end portion of the spring band, wherein the sleeve comprises:
  - a first plurality of detent pockets; and
  - a second plurality of detent pockets positioned laterally relative to the first plurality of detent pockets; and
- an arm, comprising:
  - a first spring-loaded bearing that adjustably engages the first plurality of detent pockets; and
  - a second spring-loaded bearing that adjustably engages the second plurality of detent pockets, wherein the first and second spring-loaded bearings adjustably secure the arm to the sleeve when the first spring-

25

loaded bearing engages one pocket of the first plurality of detent pockets and the second spring-loaded bearing engages one pocket of the second plurality of detent pockets.

2. The headband assembly of claim 1, further comprising: 5  
 a second sleeve in which is disposed a second end portion of the spring band, wherein the second sleeve comprises:  
 a first plurality of detent pockets; and  
 a second plurality of detent pockets positioned laterally 10  
 relative to the first plurality of detent pockets; and  
 a second arm comprising:  
 a first spring-loaded bearing that adjustably engages the 15  
 first plurality of detent pockets of the second sleeve; and  
 a second spring-loaded bearing that adjustably engages 20  
 the second plurality of detent pockets of the second sleeve, wherein the first and second spring-loaded bearings of the second arm adjustably secure the second arm to the second sleeve when the first spring-loaded bearing engages one pocket of the first plurality 25  
 of detent pockets of the second sleeve and the second spring-loaded bearing engages one pocket of the second plurality of detent pockets of the second sleeve.
3. The headband assembly of claim 2, further comprising the personal speaker.
4. The headband assembly of claim 1, wherein the spring band comprises:  
 a pronged portion at the first end portion, wherein the 30  
 pronged portion exerts a springback force on the sleeve when the pronged portion is disposed in the sleeve; and  
 laterally opposed tabs that operably engage the sleeve.
5. The headband assembly of claim 4, wherein the spring band and the sleeve form a snap-fit connection.
6. The headband assembly of claim 1, further comprising a cap attached to the sleeve and at least partially surrounding the arm, wherein the cap guides the arm relative to the sleeve.
7. The headband assembly of claim 6, wherein the arm 35  
 comprises a slot that receives a portion of the cap, and wherein the portion of the cap is slidable within the slot as the arm moves relative to the sleeve. 40

26

8. The headband assembly of claim 7, wherein the cap comprises an extension stop that operably engages an end of the slot to limit movement of the arm away from the spring band.

9. The headband assembly of claim 1, wherein the sleeve comprises a retraction stop that operably engages an end of the arm to limit movement of the arm toward the spring band.

10. The headband assembly of claim 1, comprising a liner positionable relative to the sleeve such that the liner and the sleeve at least partially surround a portion of the arm.

11. The headband assembly of claim 1, comprising at least one aesthetic component.

12. The headband assembly of claim 11, wherein the at least one aesthetic component is selected from a group comprising a frame, a cushion, a cover, and an indicia.

13. A headband assembly, comprising:  
 a band;  
 a first sleeve attached to an end portion of the band, wherein the first sleeve comprises  
 a first pair of laterally opposed detent channels; and  
 a first extension moveably secured to the first sleeve, wherein the first extension comprises  
 a first pair of spring-loaded bearings, and wherein each spring-loaded bearing of the first extension engages one of the first pair of laterally opposed detent channels of the first sleeve;  
 a second sleeve attached to an end of the band, wherein the second sleeve comprises  
 a second pair of laterally opposed detent channels; and  
 a second extension moveably secured to the second sleeve, wherein the second extension comprises  
 a second pair of spring-loaded bearings, and wherein each spring-loaded bearing of the second extension engages one of the second pair of laterally opposed detent channels of the second sleeve.
14. The headband assembly of claim 13, comprising a personal speaker secured to the first arm.
15. The headband assembly of claim 13, comprising a cap removably attached to the first sleeve and positioned around a portion of the first arm, wherein the cap guides the first arm 40  
 relative to the first sleeve.

\* \* \* \* \*