



US008896444B1

(12) **United States Patent**
Knust et al.

(10) **Patent No.:** **US 8,896,444 B1**
(45) **Date of Patent:** ***Nov. 25, 2014**

(54) **SYSTEM AND METHOD FOR CASINO TABLE OPERATION**

(75) Inventors: **Randy L. Knust**, The Woodlands, TX (US); **Eric Schoppe**, Conroe, TX (US)

(73) Assignee: **Genesis Gaming Solutions, Inc.**, Spring, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 74 days.

This patent is subject to a terminal disclaimer.

5,451,054 A	9/1995	Orenstein	
5,649,705 A	7/1997	String	
5,653,640 A *	8/1997	Shirley, Jr.	473/2
5,781,647 A	7/1998	Fishbine et al.	
5,831,527 A	11/1998	Jones, II et al.	
5,919,090 A	7/1999	Mothwurf	
5,957,776 A	9/1999	Hoehne	
6,059,659 A	5/2000	Busch et al.	
6,154,131 A	11/2000	Jones, II et al.	
6,267,671 B1	7/2001	Hogan	
6,313,871 B1	11/2001	Schubert	
6,446,864 B1	9/2002	Kim et al.	
6,460,848 B1	10/2002	Soltys et al.	
6,567,159 B1	5/2003	Corech	
6,848,994 B1	2/2005	Knust et al.	
7,431,650 B2	10/2008	Kessman et al.	
7,690,996 B2 *	4/2010	Iddings et al.	463/42

(Continued)

(21) Appl. No.: **13/297,081**

(22) Filed: **Nov. 15, 2011**

Related U.S. Application Data

(63) Continuation-in-part of application No. 12/270,476, filed on Nov. 13, 2008, now Pat. No. 8,130,097.

(60) Provisional application No. 61/413,633, filed on Nov. 15, 2010, provisional application No. 60/987,570, filed on Nov. 13, 2007.

(51) **Int. Cl.**
G08B 21/00 (2006.01)

(52) **U.S. Cl.**
USPC **340/540**; 340/815.45; 340/332

(58) **Field of Classification Search**
USPC 340/540, 641, 815.45, 545.3, 642, 323, 340/332

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,378,114 A	3/1983	Sargent
4,531,187 A	7/1985	Uhland

OTHER PUBLICATIONS

Parets, Robyn Taylor, "The newer Deal", International Gaming & Wagering Business, Apr. 1997, 2 pages.


Primary Examiner — Daniel Previl

(74) *Attorney, Agent, or Firm* — Winstead PC

(57) **ABSTRACT**

A system includes a gaming table, at least one light sensor, an electronic system, and a central computer. The gaming table includes a tabletop covered by a fabric. The at least one light sensor is positioned in proximity to a player position at the gaming table. In addition, the at least one light sensor is positioned beneath the fabric to detect light intensity through the fabric. The electronic system is communicably coupled to the at least one light sensor. Furthermore, the electronic system is operable to detect changes in light intensity at the at least one light sensor. The central computer is communicably coupled to the electronic system. Additionally, the central computer is operable to perform at least one operation based on a status of the at least one light sensor.

28 Claims, 7 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

7,878,909	B2	2/2011	Kessman et al.	
8,092,293	B2 *	1/2012	Richards et al.	463/17
8,100,753	B2 *	1/2012	Soltys	463/21
2001/0010025	A1	7/2001	Knust et al.	
2002/0111213	A1	8/2002	McEntee et al.	
2003/0003997	A1	1/2003	Vuong et al.	
2003/0171143	A1	9/2003	Valdez et al.	
2005/0026684	A1	2/2005	Sumi et al.	
2005/0090310	A1	4/2005	Knust et al.	
2005/0093241	A1	5/2005	Lipscomb et al.	
2005/0277463	A1	12/2005	Knust et al.	
2007/0045958	A1 *	3/2007	Rader et al.	273/274
2007/0057469	A1 *	3/2007	Grauzer et al.	273/309
2007/0080496	A1	4/2007	Feola	
2007/0296151	A1 *	12/2007	Kyrychenko	273/309

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7





FIG. 8



1

SYSTEM AND METHOD FOR CASINO TABLE
OPERATIONCROSS-REFERENCE TO RELATED
APPLICATIONS

This patent application is a continuation-in-part of U.S. patent application Ser. No. 12/270,476, filed on Nov. 13, 2008 now U.S. Pat. No. 8,130,097, and claims priority from U.S. Provisional Application No. 61/413,633, filed on Nov. 15, 2010. U.S. patent application Ser. No. 12/270,476 claims priority from U.S. Provisional Application No. 60/987,570, filed on Nov. 13, 2007. U.S. patent application Ser. No. 12/270,476, U.S. Provisional Application No. 61/413,633, and U.S. Provisional Application No. 60/987,570 are incorporated by reference herein in their entirety.

BACKGROUND

1. Technical Field

The present invention relates generally to the field of gaming systems, and, more particularly, but not by way of limitation, to a system for facilitating casino table operation.

2. History of Related Art

The card and chip detection system described herein is designed to detect if cards or chips are placed in a certain area on a gaming table. If the casino knows where and when chips or cards are on the table, then player tracking, dealer tracking, surveillance and pit management become very accurate. The casino will know an accurate count of how many total hands are dealt for providing free compensation ("comp") and occupancy purposes. Also, dealer audits are accurate for evaluating dealer efficiency and speed. Security knows immediately when and where hands are being played for video surveillance. Unknown patrons are automatically logged into the system for tracking purposes.

The current hand or chip detection devices are generally positioned on the table on top of the table felt and may comprise a button or light sensor. This is very inefficient for maintenance reasons since every time a felt is changed the device must be disconnected and removed from the table. Damage is more likely from the device being exposed on the table top. Functionality of such known systems is also inhibited since the table top space is limited. The sensors or buttons can only be mounted in certain areas as not to affect or delay the dealing or payout of the game directly.

SUMMARY OF THE INVENTION

In one embodiment, a system includes a gaming table, at least one light sensor, an electronic system, and a central computer. The gaming table includes a tabletop covered by a fabric. The at least one light sensor is positioned in proximity to a player position at the gaming table. In addition, the at least one light sensor is positioned beneath the fabric to detect light intensity through the fabric. The electronic system is communicably coupled to the at least one light sensor. Furthermore, the electronic system is operable to detect changes in light intensity at the at least one light sensor. The central computer is communicably coupled to the electronic system. Additionally, the central computer is operable to perform at least one operation based on a status of the at least one light sensor.

In one embodiment, a method includes detecting a change in light intensity in proximity to a player position at a gaming table. The detection is performed via a light sensor positioned beneath a fabric layer on the gaming table. In addition, the

2

detection includes detecting the change in light intensity through the fabric layer. The method further includes, at a central computer, performing at least one operation based on a status of the at least one light sensor.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the method and apparatus of the present invention may be obtained by reference to the following Detailed Description when taken in conjunction with the accompanying Drawings wherein:

FIG. 1 is a plan schematic diagram of a chip or card detection system;

FIG. 2 is a side section view through a table top illustrating the light sensor sensing change in light energy transmitted through a table top felt on a gaming table;

FIG. 3 is a schematic view of a data transmission portion of the system;

FIG. 4 is a schematic view of a data transmission portion of the system;

FIG. 5 illustrates a dealer keypad and a card-reading apparatus;

FIG. 6 provides another view of a dealer keypad;

FIG. 7 illustrates a process for automatically checking-in a player as a guest;

FIG. 8 illustrates a process for automatically checking-out a player from a gaming table; and

FIG. 9 illustrates an embodiment of a reporting system using card and chip detection systems.

DETAILED DESCRIPTION OF ILLUSTRATIVE
EMBODIMENTS OF THE INVENTION

FIG. 1 illustrates a charge coupled device (CCD) light sensor board 10, in accordance with the teachings of the present invention. One such light sensor board 10 is associated with each player position around a gaming table, as shown and described below in greater detail. The CCD light sensor board 10 generally comprises a cadmium sulphide sensor 12 whose resistance changes in response to light, as powered from a cable 20 through a conductor 22. The light sensor 12 pulls against a resistance 24 to create a changing voltage point, in a manner known in the art. This changing voltage point is measured using an Analog to Digital (A/D) converter 26 through a conductor 25 and calibrated continuously to detect changes in light through fabrics and changing lighting conditions. The light sensor board 10 also contains a light-emitting diode 28 which serves as a location indicator and is optically isolated from the light sensor. The entire light sensor board assembly is preferably mounted to a gaming table beneath the table-covering felt with a set of mounting holes 30.

As shown in FIGS. 1 and 2, a tabletop 40 includes a light sensor 12 mounted in a hole 14 in the tabletop. The light sensor 12 is mounted in such a way that it is substantially flush with the top surface of the tabletop. A felt layer 16 is installed over the tabletop over the light sensor. The light sensor senses changes in light entering the light sensor through the felt. When a new felt is installed, a registration pattern 18 (FIG. 1), which is printed on the felt, is installed over the light sensor. So, when a chip or a card is placed over the sensor, or even if it just passes over the sensor, the sensor detects the change in ambient light and informs the data collection system.

FIG. 3 illustrates one preferred embodiment of a reporting system using the card and chip detection system of FIGS. 1 and 2. The tabletop 40 is covered with a felt layer 16, as previously described. A dealer's position 42 is positioned

3

along one location beside the gaming table, while a plurality of player positions **44** are arrayed in a semi-circle along the side of the table. A sensor **12** is positioned adjacent each player position.

Each of the sensors **12** is coupled electronically with a processing board **46** through a connection **48**. The processing board **46** is electronically coupled to a central processing unit (CPU) **50**, possibly wirelessly, through a connection **52**. In various embodiments, the connection **52** includes a transceiver assigned to the table that receives data from the processing board **52** and transmits the data to the CPU **50**. The transceiver may be, for example, a computing device that communicates via wired Ethernet or wirelessly. In a typical embodiment, the CPU **50** is representative of a management system such as, for example, a casino management system, and may be representative of one or more physical or virtual server computers. In a typical embodiment, the CPU **50** stores for and facilitates management of a plurality of gaming tables.

Preferably, each of the sensors **12** is monitored continuously, so that any alteration in the state of the A/D converter **26** (FIG. 1) associated with any sensor will be sensed by the processing board **46** and transmitted to the CPU and stored. This allows the proprietor to maintain an up to the minute determination of the gaming at each player position throughout the establishment, such as for example in a casino.

FIG. 4 illustrates another embodiment of a reporting system using the card and chip detection system of FIGS. 1 and 2. In particular, a gaming table **400** is illustrated. For purposes of simplicity, the sensors **12** illustrated with respect to FIG. 3 and described above are grouped together in FIG. 4 as a first group **60**. A second group **58** of the sensors **12** is disposed above the first group **60** and adjacent to the player positions **44**. A dealer keypad **102** and a card-reading apparatus **104** are positioned on the tabletop **40** in proximity to the dealer's position **42**.

The dealer keypad **102** and the card-reading apparatus **104** are electronically coupled to the central processing unit (CPU) **50** through a connection **54** and a connection **56**, respectively. In various embodiments, the connections **54** and **56** include a transceiver assigned to the table that receives and transmits data to the CPU **50**. In the case of the connection **54**, the transceiver may relay data intended for the dealer keypad **102** from the CPU **50** to the dealer keypad **102**. The transceiver may be, for example, a computing device that communicates via wired Ethernet and/or wirelessly. In various embodiments, the connections **48**, **54**, and **56** may share a single transceiver.

The dealer keypad **102** and the card-reading apparatus **104** allow a dealer to practice more efficient management of players at the gaming table **400**, for example, in a casino pit. Operation of the dealer keypad **102** and the card-reading apparatus **104** will be described in greater detail with respect to FIGS. 5-8.

In a typical embodiment, the sensors **12** in the second group **58** facilitate additional bets such as proposition bets (i.e. side bets). One of ordinary skill in the art will appreciate that a proposition bet refers to a bet made regarding the occurrence or non-occurrence during a game of an event not directly affecting the game's outcome. For example, during a game of blackjack, proposition bets could be established related to which cards will be dealt (e.g., a "Lucky Ladies" proposition bet that wins only if a player is dealt the queen of hearts and the dealer receives blackjack). Numerous types of proposition bets are possible and will be apparent to one of ordinary skill in the art.

4

In a typical embodiment, the sensors **12** in the second group **58** may be used to determine whether a proposition bet has been placed. If one or more gaming objects (e.g., chips) are placed over any of the sensors **12** in the second group **58**, the alteration in the state of the A/D converter **26** (FIG. 1) associated therewith will be sensed by the processing board **46** and transmitted to the central CPU **50** and stored. In that way, the central CPU **50** stores each proposition bet and can track proposition bets and the frequency with which particular players make proposition bets. This allows the proprietor to maintain an up to the minute determination of proposition bets at each player position throughout the establishment such as, for example, in a casino.

FIG. 5 illustrates the dealer keypad **102** and the card-reading apparatus **104** of FIG. 4 in greater detail. The dealer keypad **102** includes a display **208** that may be, for example, a liquid crystal display (LCD). The dealer keypad **102** additionally includes a numbered section **516** and a command section **518**. The numbered section **516** includes a plurality of numbered buttons **512a** and a plurality of indicator lights **514a** that are each associated with one of the numbered buttons **512a**. The command section **518** includes a plurality of command buttons **512b** and a plurality of indicator lights **514b** that are each associated with one of the command buttons **512b**.

For simplicity of reference herein, individual buttons in the plurality of numbered buttons **512a** or the plurality of command buttons **512b** may be referred to by a label appearing thereon (e.g., "the numbered button **512a** labeled '1'" or "the command button **512b** labeled '#"). Likewise, for simplicity of reference, individual indicator lights in the plurality of indicator lights **514a** or the plurality of indicator lights **514b** may be individually pointed out with reference to an associated button from the plurality of numbered buttons **512a** or the plurality of command buttons **512b**, respectively (e.g., "the indicator light **514a** associated with the numbered button **512a** labeled '1'" or "the indicator light **514b** associated with the command button **512b** labeled '#"). Finally, for further simplicity, individual indicator lights from the plurality of indicator lights **514a** or the plurality of indicator lights **514b** may be individually pointed out solely with reference to a label appearing on a button with which it is associated (e.g., "the indicator light **514a** associated with '1'" or "the indicator light **514b** associated with '#").

In general, numbers that appear on the plurality of numbered buttons **512a** correspond to a player position such as, for example, one of the plurality of player positions **44**. For example, with reference to FIG. 4, each of the plurality of player positions **44** can be assigned a position number from one to six (e.g., from left to right from the dealer's perspective). With reference to FIG. 5, the display **208** indicates, by way of example, that position numbers one, two, three, and five are occupied while position numbers four and six are vacant. In a typical embodiment, the dealer keypad **102** additionally represents table occupancy by causing indicator lights **514a** associated with occupied player positions to be lit. For purposes of the example depicted in FIG. 5, the dealer keypad **102** lights the indicator lights **514a** associated with the numbered buttons **512a** labeled '1', '2', '3', and '5'.

Still referring to FIG. 5, the card-reading apparatus **104** is typically operable to accept, for example, a card having a magnetic stripe **206** disposed thereon. In a typical embodiment, the magnetic stripe **206** includes information that uniquely identifies, for example, a player. The information can be used to access biographical or historical data regarding the player. For example, in operation, the card may be ori-

5

ented so that the magnetic stripe **206** faces left on the card-reading apparatus **104** and is swiped in a downward direction.

Exemplary functionality of the dealer keypad **102** will now be described. In various embodiments, the dealer keypad **102** facilitates dealer check-in functionality. Prior to a dealer being checked-in, operation of the dealer keypad **102** is typically locked. To check-in, the dealer swipes an employee card using the card-reading apparatus **104**. With reference to FIG. 4, the card-reading apparatus **104** transmits identification information gleaned from the employee card to the CPU **50** via the connection **56**. The central CPU **50** registers the dealer for the gaming table **400** and returns the registration to the dealer keypad **102** via the connection **54**. At the dealer keypad **102**, the indicator light **514b** associated with the command button **512b** labeled '✓' becomes lit. After the dealer presses the command button **512b** labeled '✓', the associated indicator light **514b** turns off and the dealer's name appears on the display **208**. At that point, functionality is unlocked and the dealer is enabled to operate the dealer keypad and perform, for example, the functionality described below.

In various embodiments, the dealer keypad **102** facilitates player check-in functionality. In various embodiments, the dealer keypad **102** enables player check-in with or without a cash buy-in. Exemplary functionality for checking-in a player without a cash buy-in will be described first.

To check-in a player without a cash buy-in, the dealer swipes a player card using the card-reading apparatus **104**. With reference to FIG. 4, the card-reading apparatus **104** transmits identification information gleaned from the player card to the CPU **50** via the connection **56**. The CPU **50** subsequently indicates to the dealer keypad **102** that a player-registration process is occurring and the dealer keypad **102** causes the indicator light **514b** associated with the command button **512b** labeled '✓' to become lit. At this point, the dealer presses the command button **512b** labeled '✓' again and then presses the numbered button **512a** labeled with a desired position number at the gaming table **400** (e.g., '1', '2', '3', etc.).

In some embodiments, a buy-in interface may appear on the display **208**. In these embodiments, the dealer presses the command button **512b** labeled '✓' again to exit the buy-in interface. The desired position number and the buy-in amount (i.e., zero) are transmitted to the CPU **50** via the connection **54**. Then, the CPU **50** confirms the player registration and transmits a desired alias such as, for example, the player's first name, to the dealer keypad **102**. At this point, the player's alias (received from the CPU **50**) appears on the display **208** in connection with the desired position number at the gaming table **400**. Also, the dealer keypad **102** causes the indicator light **514a** associated with the desired position number to become lit.

Operation of the dealer keypad **102** to facilitate player check-in with a cash buy-in will now be described. Player check-in with a cash buy-in proceeds as described above with respect to player check-in without a cash buy-in except that the dealer does not immediately exit the buy-in interface. The buy-in interface on the display **208** allows the dealer to enter a buy-in amount as cash, chips, or marker. In a typical embodiment, the buy-in interface on the keypad **102** defaults to cash but can be toggled to chips or marker by pressing, for example, the command button **512b** labeled '*'. In a typical embodiment, the dealer toggles between cash, chips, and marker as appropriate to select the appropriate type of buy-in.

To simplify buy-in entry, in some embodiments, the dealer keypad **102** may utilize a multiplier such as, for example, one-hundred, so that a \$200 buy-in amount could be entered by pressing the numbered button **512a** labeled '2'. In these

6

embodiments, if the buy-in amount is not compatible the multiplier (e.g., the buy-in amount is not a multiple of one-hundred), the dealer can press, for example, the command button **512b** labeled '#' and enter the exact amount via the numbered buttons **512a**.

After the buy-in amount is entered, the dealer presses, for example, the command button **512b** labeled '✓', to indicate completion. The desired position number and the buy-in amount are transmitted to the CPU **50** via the connection **54**. Then, the CPU **50** confirms the player registration and transmits a desired alias such as, for example, the player's first name (received from the CPU **50**), to the dealer keypad **102**. At this point, the player's alias appears on the display **208** in connection with the desired position number. Also, the dealer keypad **102** causes the indicator light **514a** associated with the desired position number to become lit.

In various embodiments, the keypad **102** additionally enables the dealer to check-in a player who does not have a player card as a guest. To check-in a player who does not have a player card, the dealer presses, for example, the command button **512b** labeled '✓', which causes the associated indicator light **514b** to become lit. The guest can be checked-in either with or without a buy-in as described above with respect to players with player cards. Subsequently, the keypad **102** notifies the CPU **50** of the guest's registration and transmits the guest's desired position number and any buy-in amount. Then, the CPU **50** confirms the guest registration and transmits an alias such as, for example, "guest," to the dealer keypad **102**. At this point, the alias appears on the display **208** in connection with the guest's desired position number. Also, the indicator light **514a** associated with the guest's desired position number becomes lit.

In various embodiments, the keypad **102** additionally enables the dealer to enter an average bet for players at the gaming table **400**. In a typical embodiment, the average bet is utilized, for example, to calculate player ratings for purposes of determining comps. To enter an average bet, the dealer presses, for example, the command button **512b** labeled '*' and presses the numbered button **512a** that is labeled with the appropriate player position number. Subsequently, the dealer enters the average bet amount via the numbered buttons **512a** and presses, for example, the command button **512b** labeled '✓' to indicate completion. The entered average bet amount is transmitted to the CPU **50** via the connection **54**.

In various embodiments, the dealer keypad **102** enables the dealer to perform player check-out functionality. In a typical embodiment, players (and guests) can be checked-out from the gaming table with or without a walk-with amount. If a player is being checked-out without a walk-with amount, the dealer can press, for example, the command button **512b** labeled '✓' followed by the numbered button **512a** labeled with the player's position number. Subsequently, the dealer keypad **102** notifies the CPU **50** and receives a confirmation from the CPU **50** that the player is checked-out. At that point, the indicator light **514a** associated with the player's position number turns off and the player's name is removed from the display **208**.

If the player is being checked-out with a walk-with amount, the dealer can press, for example, the command button **512b** labeled '✓' followed by the numbered button **512a** labeled with the player's position number. Subsequently, the dealer enters an amount that the player is leaving the table with (i.e., a walk-with amount) using appropriate buttons from the numbered buttons **512a**. Once the walk-with amount is entered, the dealer presses, for example, the command button **512b** labeled '✓', and the dealer keypad **102** notifies the CPU **50**. Once the dealer keypad **102** receives

7

confirmation from the CPU 50 that the player is checked-out, the indicator light 514a associated with the player's position number turns off and the player's name is removed from the display 208.

In various embodiments, the dealer keypad 102 enables the dealer to perform lobby functionality. For example, if a player gets up to take a break (i.e. lobbying), the dealer logs the player as temporarily away by pressing, for example, the numbered button 512a corresponding to the player's position number. In a typical embodiment, the indicator light 514a associated with the player's position number flashes to indicate that the player is lobbying. The player's status of lobbying is reported to the CPU 50. In this manner, the player's position at a gaming table is reserved but the player is not credited for time or hands when the player is not at the gaming table. In this manner, over-comping of players based on time not spent at the gaming table can be prevented. When the player returns, the dealer can again press the numbered button 512a corresponding to the player's position number and the indicator light 514a associated with the player's position number stops flashing.

In various embodiments, the dealer keypad 102 additionally enables the dealer to move players from one position number to another position number when, for example, a player desires to move to a different position at a gaming table. In various embodiments, the dealer can accomplish a move of the player via a three-button sequence. In particular, the dealer can press the command button 512b labeled 'M', the numbered button 512a corresponding to the player's current position number, and the numbered button 512a corresponding to the player's new position number. Then, the dealer keypad 102 notifies the CPU 50 of the move. Upon receipt of confirmation from the CPU 50, the dealer keypad 102 updates the display 208 to reflect the player's name at the new position number.

In various embodiments, the dealer keypad 102 also enables the dealer to more efficiently accommodate players that are playing at more than position number. Specifically, the dealer keypad 102 permits the dealer to copy a player's information from one position number to a second position number that will be occupied by the same player. In a typical embodiment, a copy can be accomplished via a three-button sequence. In particular, the dealer can press the command button 512b labeled 'C', the numbered button 512a corresponding to the player's current position number, and the numbered button 512a corresponding to the player's additional position number. At that point, the dealer keypad 102 notifies the CPU 50 of the copy. Upon receipt of confirmation from the CPU 50 that the copy has been accomplished, the dealer keypad 102 updates the display 208 to show the player's name at the additional position number.

In various embodiments, the dealer keypad 102 further enables the dealer to input additional cash buy-in for a player. To enter additional cash buy-in, the dealer can press, for example, the command button 512b labeled '#' followed by the numbered button 512a corresponding to the player's position number. Then, the dealer keypad provides a buy-in interface to the dealer. After receiving the additional buy-in amount in a manner similar to that described above with respect to player check-in, the dealer can press, for example, the command button 512b labeled '✓' to indicate completion. At that point, the dealer keypad 102 sends the additional buy-in amount to the CPU 50 via the connection 54.

FIG. 6 provides another view of the dealer keypad 102. For example, the display 208 illustrates a player checked-in as a guest.

8

FIG. 7 illustrates a process 700 for automatically checking-in a player as a guest. In contrast to the procedures described above with respect to FIGS. 5 and 6, the process 700 does not require data entry by a dealer. The process 700 begins at step 702. At step 702, a player approaches a player position such as, for example, one of the player positions 44 of FIG. 4. From step 702, the process 700 proceeds to step 704.

At step 704, a gaming object is placed at the player's player position. For example, the dealer may deal one or more cards to the player's position. From step 704, the process 700 proceeds to step 706. At step 706, with respect to FIG. 4, a sensor from the first group 60 that corresponds to the player's position detects a change in light intensity. From step 706, the process 700 proceeds to step 708. At step 708, the alteration in the state of the A/D converter 26 (FIG. 1) associated therewith is sensed by the processing board 46 and transmitted to the central CPU 50. From step 708, the process 700 proceeds to step 710.

At step 710, the CPU 50 determines whether the player's position is vacant. If not, the process 700 proceeds to step 716 and ends. Otherwise, the process 700 proceeds to step 712. At step 712, the CPU 50 registers a guest at the player's position at the gaming table 400. From step 712, the process 700 proceeds to step 714. At step 714, the CPU 50 transmits the guest registration to the dealer keypad 102 via the connection 54. The dealer keypad 102 then displays the name "guest" for the number associated with the player's position.

In various embodiments, the process 700 provides numerous advantages over manual check-in procedures. Via automatic guest check-in, players are more easily integrated into a gaming table and can immediately begin having activities recorded that can result in comps. Furthermore, guest check-in can occur without the dealer stopping to perform a manual task. Therefore, more hands can be dealt and more money can potentially be made at a casino. Additionally, in various embodiments, via a dealer keypad such as, for example, the dealer keypad 102 of FIG. 4, the dealer can convert a guest to that of a registered player. Once the dealer identifies the guest as a player via, for example, a card swipe, the CPU 50 can apply the activities recorded as a guest to the registered player for purposes of potential comping.

FIG. 8 illustrates a process 800 for automatically checking-out a player (or guest) from a gaming table. In contrast to the procedures described above with respect to FIGS. 5 and 6, the process 800 does not require data entry by a dealer. The process 800 begins at step 802. At step 802, the CPU 50 identifies an idle player position. In a typical embodiment, a player position is determined to be idle if there is a player checked-in at the player position, the player is not in "lobby" as described above, and no gaming activity has occurred for a configurable period of time. For example, for a game of blackjack, it may be determined that no gaming activity has occurred if no hands have been dealt to the player position during the configurable period of time but hands have been dealt to other player positions. In various embodiments, the configurable period of time may be customized for a given establishment such as, for example, a casino.

From step 802, the process 800 proceeds to step 804. At step 804, the CPU 50 checks-out the player from the gaming table. From step 804, the process 800 proceeds to step 806. At step 806, the CPU 50 transmits check-out information to the dealer keypad 102. At that point, the dealer keypad 102 updates the display 208 to reflect that the idle player position is now vacant. After step 806, the process 800 ends.

In various embodiments, the process 800 serves to prevent potential over-comping at gaming tables. For example, until checked-out, a player who is checked-in at a gaming table

(but not in “lobby”) may continue to be given credit for receiving hands at the gaming table. By checking out the player after a configurable period of time, over-comping can thereby be prevented.

FIG. 9 illustrates another embodiment of a reporting system using card and chip detection systems similar to those described with respect to FIGS. 1-4. A mini-baccarat tabletop 40a is covered with a felt layer 16a, as previously described with respect to the tabletop 40 and the felt layer 16 of FIGS. 2-4. A dealer's position 42a is positioned along one side of the tabletop 40a, while a plurality of player positions 44a are arrayed in a semi-circle along an opposite side the tabletop 40a. The tabletop 40a additionally includes the dealer keypad 102 and the card-reading apparatus 104 adjacent to the dealer position 42a.

Consistent with the game of baccarat, each of the player positions 44a provides a betting location for a “banker” bet and a betting location for a “player” bet. Two sensors 12 are positioned in proximity to each of the player positions 44a for purposes of accommodating and detecting each type of bet.

One of ordinary skill in the art will appreciate that baccarat games are often planned by junkets. Junkets serve to organize players that will play baccarat at one or more baccarat tables in casino. Casinos generally compensate junkets by offering a percentage commission that is calculated based on a total sum of money that is put at risk at the baccarat table. In other words, the more money that is bet (either banker or player), the more money the junket can garner.

One scam that sometimes occurs at junket-organized baccarat games involves “balanced betting.” Balanced betting in baccarat refers to a practice of betting approximately equal amounts for both player and banker. Balanced betting can be practiced by an individual player or by multiple players acting in concert. When balanced betting is practiced in concert by all players at a baccarat table, very large sums of money can be bet at greatly reduced risk due to the at least partially offsetting nature of the cumulative bets. Historically, some junkets have recruited players and organized games for the purpose of artificially driving up the total money at risk and increasing the junket's commission. As a result, casinos generally prohibit balanced betting at junket-organized baccarat games.

With reference to FIG. 9, the sensors 12 operate as described with respect to FIGS. 1-4. Thus, although not specifically shown in FIG. 9, the sensors communicate with the processing board 46 and the central CPU 50 as described with respect to FIGS. 3 and 4. In a typical embodiment, the sensors 12 depicted in FIG. 9 are used to determine when a banker bet or a player bet has been placed at one of the player positions 44.

If one or more gaming objects (e.g., chips) are placed over any of the sensors 12 of FIG. 9, the alteration in the state of the A/D converter 26 (FIG. 1) associated therewith will be sensed by the processing board 46 and transmitted to the central CPU 50 and stored. In that way, the central CPU 50 stores each bet and thus can determine a total number of “banker” bets and a total number of “player” bets for a hand. Therefore, the CPU 50 is operable to determine whether a potential balanced-betting situation is present. In a typical embodiment, the CPU 50 determines a potential balanced-betting situation to be present when a total number of “player” bets equals a total number of “banker” bets. If that occurs, in a typical embodiment, the CPU 50 may cause a silent alarm to be sounded or send a notification to the dealer keypad 120. In that way, closer scrutiny may be given to the betting and gaming security may be improved.

The principles, preferred embodiment, and mode of operation of the present invention have been described in the foregoing specification. This invention is not to be construed as limited to the particular forms disclosed, since these are regarded as illustrative rather than restrictive. Moreover, variations and changes may be made by those skilled in the art without departing from the spirit of the invention.

What is claimed is:

1. A system comprising:

a gaming table including a tabletop covered by a fabric; at least one light sensor positioned in proximity to a player position at the gaming table, the at least one light sensor being positioned in the tabletop, beneath the fabric, to detect light intensity through the fabric;

wherein the at least one light sensor is substantially flush with a top surface of the tabletop;

an electronic system communicably coupled to the at least one light sensor, the electronic system operable to detect changes in light intensity at the at least one light sensor; and

a central computer communicably coupled to the electronic system, wherein the central computer is operable to perform at least one operation based on a status of the at least one light sensor;

wherein the operability to perform at least one operation comprises operability to:

receive information related to a change in light intensity at the at least one light sensor;

determine, based on the received information related to the change in light intensity at the at least one light sensor, whether the player position is vacant; and responsive to a determination that the player position is vacant, register a guest at the player position.

2. The system of claim 1, wherein:

the at least one sensor is positioned in proximity to a location on the tabletop designated for placement of proposition bets; and

the operability to perform at least one operation comprises operability to:

receive information related to a change in light intensity at the at least one light sensor; and

record a proposition bet for a player registered at the player position.

3. The system of claim 1, wherein the operability to perform at least one operation comprises operability to:

identify the player position as idle; and

check-out a player registered at the player position from the gaming table.

4. The system of claim 1, wherein the identification of the player position as idle comprises a determination that no changes in light intensity at the at least one light sensor have been reported for a predetermined period of time.

5. The system of claim 4, wherein the predetermined period of time is configurable.

6. The system of claim 1, wherein the at least one light sensor comprises a plurality of light sensors positioned in proximity to a plurality of player positions at the gaming table.

7. The system of claim 6, wherein the operability to perform at least one operation comprises operability to assess bets made at at least a portion of the plurality of player positions.

8. The system of claim 6, wherein:

the gaming table is a baccarat table; and

the operability to perform at least one operation comprises operability to:

11

receive information related to a change in light intensity at said at least a portion of the plurality of light sensors; and

determine a number of banker bets and a number of player bets.

9. The system of claim 8, wherein the operability to perform at least one operation comprises operability to:

determine whether the number of banker bets and the number of player bets constitute potential balanced betting; and

responsive to a determination of potential balanced betting, send a notification.

10. The system of claim 1, wherein the electronic system is operable to detect placement of a gaming object over the at least one sensor.

11. The system of claim 10, wherein the gaming object is selected from the group consisting of a playing card and a chip.

12. The system of claim 1, the system comprising a keypad communicably coupled to the central computer, the keypad positioned on the tabletop in proximity to a dealer position at the gaming table.

13. The system of claim 12, wherein the keypad is operable to receive player check-in information and transmit the player check-in to the central computer.

14. The system of claim 13, wherein the keypad is operable to receive player buy-in information and to toggle between buy-in types selected from the group consisting of: cash, chips, and marker.

15. The system of claim 12, wherein the central computer is operable to transmit information related to the at least one operation to the keypad for display.

16. The system of claim 12, wherein the keypad is operable to:

receive information related to a move of a player from a first player position at the gaming table to a second player position at the gaming table;

transmit said information to the central computer;

receive confirmation from the central computer that said move has been recorded; and

update a display on the keypad responsive to the received confirmation.

17. The system of claim 12, wherein the keypad is operable to:

receive information related to an additional player position at the gaming table that will be occupied by a player occupying at least one existing player position at the gaming table;

transmit said information to the central computer;

receive confirmation from the central computer that a player copy has been recorded; and

update a display on the keypad responsive to the received confirmation.

18. The system of claim 1, wherein the fabric is felt.

19. A method comprising:

detecting a change in light intensity in proximity to a player position at a gaming table, the gaming table comprising a tabletop covered by a fabric layer;

wherein the detection is performed via a light sensor positioned in the table top, beneath the fabric layer, the

12

detecting comprising detecting the change in light intensity through the fabric layer; and

wherein the light sensor is substantially flush with a top surface of the tabletop;

at a central computer, performing at least one operation based on a status of the at least one light sensor;

wherein the performing of at least one operation comprises:

receiving information related to a change in light intensity at the at least one light sensor;

determining, based on the received information related to the change in light intensity at the at least one light sensor, whether the player position is vacant; and

responsive to a determination that the player position is vacant, registering a guest at the player position.

20. The method of claim 19, wherein:

the at least one sensor is positioned in proximity to a location on the tabletop designated for placement of proposition bets; and

the performing of at least one operation comprises:

receiving information related to a change in light intensity at the at least one light sensor; and

recording a proposition bet for a player registered at the player position.

21. The method of claim 19, wherein the performing of at least one operation comprises:

identifying the player position as idle; and

checking-out a player registered at the player position from the gaming table.

22. The system of claim 21, wherein the identifying of the player position as idle comprises determining that no changes in light intensity at the at least one light sensor have been reported for a predetermined period of time.

23. The method of claim 22, wherein the predetermined period of time is configurable.

24. The method of claim 19, wherein the at least one light sensor comprises a plurality of light sensors positioned in proximity to a plurality of player positions at the gaming table.

25. The method of claim 24, wherein the performing of at least one operation comprises assessing one or more bets made at least a portion of the plurality of player positions.

26. The method of claim 24, wherein:

the gaming table is a baccarat table; and

the performing of at least one operation comprises:

receiving information related to a change in light intensity at said at least a portion of the plurality of light sensors; and

determining a number of banker bets and a number of player bets.

27. The method of claim 26, wherein the performing of at least one operation comprises:

determining whether the number of banker bets and the number of player bets constitute potential balanced betting; and

responsive to a determination of potential balanced betting, sending a notification.

28. The method of claim 19, wherein the fabric is felt.