



US008915829B2

(12) **United States Patent**
Endelman et al.

(10) **Patent No.:** **US 8,915,829 B2**
(45) **Date of Patent:** ***Dec. 23, 2014**

(54) **REFORMER EXERCISE APPARATUS**

(71) Applicant: **Balanced Body, Inc.**, Sacramento, CA (US)
(72) Inventors: **Ken Endelman**, Sacramento, CA (US); **Christopher J. Savarino**, Sacramento, CA (US); **Brian Masterson**, Placerville, CA (US); **Elger Oberwelz**, San Francisco, CA (US); **James R. Yurchenco**, Palo Alto, CA (US); **Anthony Patron**, Mountain View, CA (US); **Thomas Dieter Christian Overthun**, San Francisco, CA (US); **Joerg Student**, San Francisco, CA (US); **David Webster**, San Mateo, CA (US); **Jennifer Ellen Davis-Wilson**, Mountain View, CA (US)

(73) Assignee: **Balanced Body, Inc.**, Sacramento, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/197,611**

(22) Filed: **Mar. 5, 2014**

(65) **Prior Publication Data**

US 2014/0187396 A1 Jul. 3, 2014

Related U.S. Application Data

(63) Continuation of application No. 13/181,707, filed on Jul. 13, 2011, now Pat. No. 8,721,511.

(51) **Int. Cl.**
A63B 26/00 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A63B 21/068** (2013.01); **A63B 21/023** (2013.01); **A63B 21/055** (2013.01); **A63B 21/1469** (2013.01); **A63B 21/154** (2013.01); **A63B 22/0089** (2013.01); **A63B 21/0428** (2013.01); **A63B 21/00065** (2013.01); **A63B 21/00069** (2013.01); **A63B 21/0001** (2013.01); **A63B 5/00** (2013.01); **A63B 21/0552** (2013.01); **A63B 2208/0247** (2013.01); **A63B 2210/50** (2013.01)

USPC **482/142**; 482/121; 482/130; 482/135

(58) **Field of Classification Search**

USPC 482/23, 51, 91-96, 121-126, 128-135, 482/140-142, 145, 904; 5/612; 601/23-24
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,338,704 B1 * 1/2002 Endelman 482/142
6,971,976 B2 * 12/2005 Endelman et al. 482/121
7,803,095 B1 * 9/2010 LaGree 482/140

Primary Examiner — Loan H Thanh


Assistant Examiner — Jennifer M Deichl

(74) *Attorney, Agent, or Firm* — Greenberg Traurig, LLP

(57) **ABSTRACT**

A reformer exercise apparatus is disclosed that has a generally rectangular frame. The rail portions of the frame each have an upright outer wall, an integral downwardly slanted inner wall and a hidden outwardly open slot therein between the outer and inner walls. A foot bar support assembly movably carried by each of the outwardly open slots supports the foot bar. Each foot bar support assembly has an elongated slide plate movably supported within the slot, a hook plate fastened to the slide plate, and a foot bar support arm rotatably and slidably fastened to the hook plate. A pair of tubular risers each having an upper roller therein at the head end of the frame direct arm cord ends to a cord retraction assembly mounted on the carriage. The retraction assembly releases the cords by pivoting either one of the shoulder stops toward the foot end of the frame.

20 Claims, 43 Drawing Sheets



(51)	Int. Cl.		<i>A63B 21/068</i>	(2006.01)
	<i>A63B 21/02</i>	(2006.01)	<i>A63B 21/055</i>	(2006.01)
	<i>A63B 21/04</i>	(2006.01)	<i>A63B 22/00</i>	(2006.01)
	<i>A63B 21/00</i>	(2006.01)	<i>A63B 5/00</i>	(2006.01)




FIG.1




FIG. 2




FIG.3




FIG. 4




FIG.5




FIG. 6

FIG. 7




FIG.8




FIG. 9




FIG. 10




FIG. 11




FIG.12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18

FIG.19




FIG.20






FIG.21








FIG.23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG.29




FIG.30




FIG.31




FIG.32




FIG. 33




FIG.34




FIG.35




FIG. 36




FIG.37




FIG.38




FIG. 39




FIG.40




FIG. 41




FIG.42




FIG. 43




FIG. 44






FIG. 45






FIG. 48




FIG. 49

REFORMER EXERCISE APPARATUSCROSS REFERENCE TO RELATED
APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 13/181,707, filed Jul. 13, 2011, entitled Reformer Exercise Apparatus, the content of which is hereby incorporated by reference in its entirety.

BACKGROUND OF THE DISCLOSURE

1. Field of the Disclosure

The present disclosure relates to an exercise apparatus. In particular, it relates to a reformer exercise apparatus of a new and contemporary design that has a number of unique innovations.

2. State of the Art

Exercise machines utilized in the performance of physical exercises originated by Joseph Pilates typically are performed on a stationary apparatus called a reformer. A traditional reformer has a rectangular wood or metal frame supporting two parallel rails or tracks. A wheeled carriage rides on these tracks and is resiliently biased toward a foot end of the frame by one or more elastic members, typically coil springs. A user sits or lies on the carriage and pushes against a foot support bar at the foot end to move the carriage away from and toward the foot end. Alternatively, the user may grasp ends of a pair of ropes or straps that pass through pulleys at the head end of the frame and are attached to the carriage to similarly pull the carriage away from and toward the foot end of the frame.

One emphasis in Pilates training is on core musculature stabilization. The exercises being performed on the reformer ideally are conducted carefully by the user concentrating on body symmetry and symmetrical body movement and proper torso alignment during exercise. It is often somewhat difficult for a user to sense when he or she is properly centered on the reformer, and exerting equal forces with both arms or both legs during movements required. Also, either the user must get off of the reformer or an assistant must change positions of the foot support bar as may be required for different exercises. This, is at least an inconvenience to the user. Furthermore, the user must then reposition his or her body on the carriage to regain proper alignment.

The ends of the arm cords are typically stuffed through holes in the carriage platform to get them out of the way of the user or draped over the sides of the carriage. Thus they can drag on the floor beneath the carriage. The user also has difficulty in adjusting arm cord length while reclining on the reformer carriage. The user generally has to sit upright, adjust the arm cord length in the stop cleats, and then reposition herself on the carriage surface.

The rails upon which the carriage rides typically are horizontal surfaces which collect dust and dirt over time and thus the rollers and tracks must often be cleaned. Furthermore, the user must be careful not to let his or her clothing drape onto the rails to prevent such clothing interfering with operation of the carriage rollers.

There is therefore a need for a reformer apparatus that is simple and straightforward to use, easy for the user to adjust without getting off of the reformer carriage, and overcomes the drawbacks mentioned above.

SUMMARY OF THE DISCLOSURE

A reformer exercise apparatus in accordance with one aspect of the present disclosure includes a generally rectan-

gular frame having a pair of parallel spaced side rail portions, a head end portion, and a foot end portion. A movable carriage is provided that is supported by the side rail portions for movement of the carriage between the head and foot end portions. A bias member, such as one or more coil springs, is connected between the carriage and the foot end portion of the frame for biasing the carriage toward the foot end of the frame. A foot support member such as a foot bar is supported by the side rail portions of the frame.

Each of the side rail portions of the frame has an upright outer wall and an integral horizontal top wall merging into an inwardly and downwardly slanted inner wall. Each side rail portion has a downwardly extending mid wall between the outer wall and the inner wall for supporting the foot support member. The mid wall has a longitudinally extending upper boss and a longitudinally extending lower boss forming an outwardly open slot therebetween facing the outer wall. Each side rail portion includes a horizontal wall between the inner wall and the mid wall.

The mid wall has a lower end portion forming a horizontal track for supporting the carriage. Furthermore, this lower portion of the mid wall also provides lateral support for guide rollers on the carriage to guide its movement between the head and foot ends of the frame.

One end of each foot support member is movably supported in the outwardly open slot between the upper and lower bosses of the mid wall. Furthermore, the mid wall includes a plurality of features, preferably notches for discrete positioning of the foot support member along a length of the side rail members of the frame.

The foot support assembly preferably includes a foot bar. The foot bar is supported at each end by a foot bar support assembly movably carried by each of the outwardly open slots in the side rail portions of the frame. Each foot bar support assembly includes an elongated slide plate movably supported within the slot, a hook plate fastened to the slide plate, and a foot bar support arm having one end fastened to one foot bar end and a portion rotatably and slidably fastened to the hook plate.

The slide plate is an elongated member having opposite ends, each end carrying a roller for riding on a bottom surface of the outwardly open slot in the mid wall of the side rail portion of the reformer frame. The slide plate also preferably has at least one roller for riding against an upright surface of the mid wall within the slot.

The foot bar support arm has a bottom end portion fastened to one foot bar end. The upper end of the foot bar support arm has an engaging member for selectively engaging a discrete feature of the hook plate when the foot bar is slid upward for rotation about the hook plate. The hook plate has an upper edge, the upper edge having a plurality of discrete features at spaced locations for selectively engaging a portion of the foot bar support arm to position the foot bar at predetermined angles from the upper surface plane of the reformer frame.

Each discrete feature is preferably a notch that has a distinctive shape. Each notch corresponds to a particular angular position for the foot bar with respect to the frame. Each hook plate preferably also has an L shaped slot for receiving the engaging member on the foot bar support arm. This L shaped notch positions the foot bar at a level below the upper frame surface and provides a user with a convenient carry handle bar at the foot end of the frame. Preferably the foot bar support arm carries a generally cylindrical pin for removably engaging one of the discrete features, i.e., one of the notches in the hook plate.

In another aspect the present disclosure describes a foot bar assembly for use on a reformer exercise apparatus having a

3

generally rectangular frame with parallel sides, a head end and a foot end, each side having an outwardly open slot extending along at least part of the side. The foot bar assembly includes a generally U shaped foot bar having a first end and a second end, an elongated slide plate movably supported within with each of the slots, a hook plate fastened to each slide plate, and a foot bar support arm rotatably and slidably fastened to each hook plate and fastened to one of the first and second ends of the foot bar.

In another aspect of the disclosure, a reformer exercise apparatus having a generally rectangular frame supporting a carriage for movement between a head end and a foot end of the frame on parallel spaced side rail portions of the frame, and a foot bar supported by the frame is disclosed wherein the head end of the frame has a pair of spaced vertical bores formed therein, and an arm cord support riser disposed in each bore. Each cord support riser includes a hollow cylindrical tube carrying a first roller therein near a bottom end of the tube, a second roller rotatably supported within an upper end of the tube, and a guide adjacent the second roller for directing an arm cord around the second roller.

Preferably in one embodiment the bottom end of the tube is open to receive the arm cord therethrough and the upper end includes a top that has a dome shape with an opening there-through for passage of the arm cord out of the tube. The top of the tube preferably also has a pair of spaced guides adjacent the opening and the second roller, and may also have a horizontal guide between the spaced guides. In some embodiments these guides are rollers. The riser tube further may include an internal cord guide plate above the first roller for guiding the arm cord over the first roller. The riser top may be separable from and rotatably fastened to the riser tube. Furthermore, the top may include a pair of spaced guides adjacent the opening for smooth passage of the arm cord. In another embodiment, the arm cord may be routed through a side of the tube just below an upper roller or pulley wheel. A pair of guide rollers is preferably arranged adjacent the opening through which the arm cord exits the tube. The riser top again may be separable from the riser tube as a cartridge assembly.

In another aspect, the present disclosure is directed to a reformer exercise apparatus that includes an arm cord retraction assembly mounted to an underside surface of the carriage. The retraction assembly has a pair of cord retraction devices, each device having a stationary frame carrying a rotatable spring biased reel therein connected to a free end of one of the arm cords, with each reel having a toothed outer rim.

The retraction assembly also includes a pair of toothed latch members rotatably mounted to the underside of the carriage and connected mechanically together such that rotation of one of the latch members out of toothed engagement with one of the toothed outer rims causes the other of the latch members to rotate out of toothed engagement with the toothed outer rim of the other spring biased reel.

The retraction assembly further has an actuator connected to one of the latch members operable for rotating the latch members into and out of engagement with the toothed rims of the retraction reels. This actuator is preferably resiliently biased out of engagement with the latch members.

In one embodiment of a reformer exercise apparatus in accordance with the present disclosure the actuator is incorporated into a pair of spaced shoulder stops extending from an upper surface of the carriage. Each of the shoulder stops is rotatably mounted to the carriage preferably for rotation about a horizontal axis. The actuator may be an elongated pin member that extends downward from the shoulder stop,

4

through an aperture in the carriage and projects therefrom so as to engage one of the latch members. Pivotal movement, i.e., rotation, by the user, of either shoulder stop about its axis toward the foot end of the frame engages the actuator with one of the latch members which in turn causes both of the latch members to disengage the toothed outer rims. Preferably a spring is connected to each latch member that biases each latch member into engagement with one of the retraction reels.

In another aspect of the present disclosure, there is provided an arm cord retraction kit for retrofitting a conventional reformer exercise apparatus. The components in the kit are designed to be attached to the reformer carriage. The kit includes a pair of cord retraction devices, each device having a stationary frame for mounting to an underside surface of a reformer carriage, each frame carrying a rotatable spring biased reel therein connectable to a free end of an arm cord, each reel having a toothed outer rim, a pair of toothed latch members for pivotal mounting to the underside surface of the carriage, wherein the latch members are connected mechanically together such that rotation of one of the latch members out of toothed engagement with one of the toothed outer rims causes the other of the latch members to rotate out of toothed engagement with the toothed outer rim of the other spring biased reel, and an actuator for engaging one of the latch members when the shoulder stops are mounted to the reformer carriage.

In another aspect of the reformer exercise apparatus of the present disclosure, the carriage includes an integral adjustable headrest. The carriage includes a generally rectangular frame, a generally rectangular plate body portion fastened to the frame, and a generally trapezoidal shaped head rest plate portion hinged to the body portion. A shaped upper pad is fastened to an upper surface of the body and headrest portions.

In a still further aspect of the reformer exercise apparatus of the present disclosure, the frame preferably includes replaceable legs positioned at the corners of the generally rectangular frame. Each leg has an outer surface shape complementary to the shape of the corner. Each leg has an upper end shape configured to fit within a complementary recess in the underside surface of the frame. Each leg is an extrusion secured to the frame with a single bolt passing vertically through the leg into a corresponding boss in the frame. The bottom end of each leg includes a foot pad that facilitates stacking of one apparatus on top of another through engagement of the outer corners of the head end of the reformer and outer corners of the standing platform at the foot end of the reformer into a foot pad recess in each foot pad.

In a still further aspect of the present disclosure, an elastic resistance member may be fastened between the foot bar assembly and the head end of the reformer frame. When the foot bar assembly is free to move along the side rails of the frame it is resiliently biased toward the head end of the reformer frame. In this configuration, the foot bar assembly may be grasped by a user's hands while sitting or reclining on the carriage, and the foot bar assembly pulled along the rails against the resistance toward the carriage in order to perform various upper body exercises separately or in conjunction with leg extensions against the foot end of the reformer frame. The elastic resistance member may alternatively be fastened between the foot bar assembly and the foot end of the frame to facilitate similar exercises from the foot end of the frame by pulling the foot bar assembly toward the carriage.

BRIEF DESCRIPTION OF THE DRAWINGS

The disclosure will be better understood and objects, other than those set forth above, will become apparent when con-

sideration is given to the following detailed description. Such description makes reference to the accompanying drawings wherein:

FIG. 1 is a perspective view of a reformer exercise apparatus in accordance with one embodiment of the present disclosure.

FIG. 2 is a separate perspective view of the frame of the reformer shown in FIG. 1 in accordance with the present disclosure.

FIG. 3 is a cross sectional view of one side rail member of the frame taken along the line 3-3 in FIG. 2.

FIG. 4 is a partial perspective view of the foot end of a reformer in accordance with the present disclosure.

FIG. 5 is a separate perspective view of a foot bar utilized in the reformer exercise apparatus shown in FIG. 1.

FIG. 6 is an outer perspective view of a right side rail member foot bar support assembly in accordance with the present disclosure.

FIG. 7 is an inner perspective view of the right side rail member foot bar support assembly shown in FIG. 6.

FIG. 8 is cross sectional view of a left rail member taken along the line 3-3 in FIG. 2 showing the arrangement of the foot bar support assembly carried therein.

FIG. 9 is a cross sectional view of the reformer exercise apparatus shown in FIG. 1 taken along the line 9-9 in FIG. 1.

FIG. 10 is a partial perspective view of the head end of the reformer apparatus shown in FIG. 1.

FIG. 11 is a separate perspective view of the lower pulley wheel assembly for the riser in the head end of the apparatus shown in FIG. 10.

FIG. 12 is a separate exploded perspective view of the carriage in the reformer exercise apparatus shown in FIG. 1 in accordance with the present disclosure.

FIG. 13 is a bottom plan view of the head end portion of the carriage shown in FIG. 1 in accordance with the present disclosure showing the cord retraction mechanism latch members engaged with the cord retraction reels.

FIG. 14 is a bottom plan view of the head end portion of the carriage as in FIG. 13 with the latch members disengaged with the cord retraction reels.

FIG. 15 is a section al view through the carriage taken along the line 15-15 in FIG. 14.

FIG. 16 is an underside perspective view of a carriage having a cord retraction system in accordance with an alternative embodiment of the present disclosure.

FIG. 17 is an underside view as in FIG. 17 showing the cord retraction system in a released position.

FIG. 18 is an underside perspective view of the head end of an alternative carriage in accordance with the present disclosure.

FIG. 19 is a side view of the head end of the carriage shown in FIG. 18.

FIG. 20 is a side view of the head end of the carriage shown in FIG. 18 with the headrest in a first raised position.

FIG. 21 is a side view of the head end of the carriage shown in FIG. 18 with the headrest in a second raised position.

FIG. 22 is head end perspective view of an alternative reformer in accordance with the present disclosure.

FIG. 23 is an inside separate exploded view of the head end assembly of the alternative reformer shown in FIG. 22.

FIG. 24 is an inside separate exploded perspective view of the foot end assembly of the alternative reformer shown in FIG. 22.

FIG. 25 is a cross sectional view of one of the two frame side rails in the alternative reformer shown in FIG. 22.

FIG. 26 is a separate assembled perspective view of a riser utilized in the reformer shown in FIG. 22.

FIG. 27 is an exploded perspective view of the riser shown in FIG. 26.

FIG. 28 is a partial sectional view of the riser shown in FIG. 26 installed in the head end socket of the reformer shown in FIG. 22.

FIG. 29 is a separate inside perspective view of the foot bar support assembly utilized in the reformer shown in FIG. 22.

FIG. 30 is an outside perspective view of the foot bar support assembly shown in FIG. 29.

FIG. 31 is a separate underside perspective view of the carriage frame assembly of the carriage shown in FIG. 22.

FIG. 32 is an underside perspective view of the support pad removed from the carriage shown in FIG. 22.

FIG. 33 is a separate perspective view of a shoulder rest utilized in the reformer shown in FIG. 22.

FIG. 34 is an upper partial exploded view of the carriage of the reformer shown in FIG. 22.

FIG. 35 is an inverted view of the carriage removed from the reformer shown in FIG. 22 showing the cord retraction system in accordance with this alternative embodiment.

FIG. 36 is an underside plan view of the head end of the carriage shown in FIG. 35 with the cord retraction system in a cord locked position.

FIG. 37 is a view as in FIG. 36 with the cord retraction system in a cord unlocked position.

FIG. 38 is a perspective view of the head end of the carriage with the headrest in a lowered position.

FIG. 39 is a perspective view a pair of reformers shown in FIG. 22 in a stacked configuration for storage.

FIG. 40 is a perspective view of the underside of the head end of the carriage showing the risers and shoulder stops ready for installation in the storage position as shown in FIG. 39.

FIG. 41 is a perspective view of the reformer shown in FIG. 22 including an optional vertical trapeze tower and mat conversion in accordance with the present disclosure.

FIG. 42 is a perspective view of a trapeze tower socket aligned against the end of one side rail of the reformer shown in FIG. 41 for connection to the head end extrusion.

FIG. 43 is a sectional view through the trapeze tower socket of the tower shown in FIG. 41.

FIG. 44 is a partial cutaway view through one of the riser bosses at the head end of the reformer shown in FIG. 41 showing an alternative lower pulley mount installed therein.

FIG. 45 is a perspective view of a reformer as in FIG. 22 with an alternative vertical trapeze tower and mat conversion in accordance with the present disclosure.

FIG. 46 is a perspective view of the hand grip end portion of an arm cord for use with a reformer in accordance with the present disclosure.

FIG. 47 is a perspective view as in FIG. 46 with a handle attached to the arm cord in accordance with the present disclosure.

FIG. 48 is a perspective view of the reformer shown in FIG. 22 with a jump board installed at the foot end of the reformer frame.

FIG. 49 is an enlarged vertical partial sectional view through one of two posts supporting the jump board installed at the foot end of the reformer frame.

DETAILED DESCRIPTION

In the following description, numerous specific details are set forth in order to provide a more thorough disclosure. It will be apparent, however, to one skilled in the art, that the art disclosed may be practiced without these specific details. In

some instances, well-known features may have not been described in detail so as not to obscure the art disclosed.

A perspective view of one embodiment of a reformer exercise apparatus **100** is shown in FIG. **1**. The apparatus **100** has a generally rectangular frame **102** with a head end **104** and a foot end **106**. The ends **104** and **106** are spaced apart by a pair of rail members **108**. A carriage **110** is movably supported on the rail members **108** for movement back and forth between the ends **104** and **106** of the frame **102**.

A foot bar **111** is positioned near the foot end **106** of the frame **102**. This foot bar **111** is carried by the rail members **108** as will be described in detail below. The head end **104** of the frame **102** preferably supports a removable pair of spaced upright arm cord support risers **112**. These risers **112** direct arm cords **114** from the carriage **110** to cord end loops **116** or grips for a user's hands for use in various exercises. When not in use, the end loops **116** may be conveniently positioned on the shoulder stops **118** as shown in FIG. **1**. The carriage **110** is resiliently biased toward the foot end **106** of the frame **102** by one or more elastic members such as springs **120**.

A separate perspective view of the frame **102** is shown in FIG. **2**. Each of the head end **104**, the foot end **106** and the side rail members **108** has a similar outer surface shape that smoothly merge together. This shape includes an outer upright wall **122** merging with a horizontal top wall **124** which merges with a downwardly and inwardly slanted inner wall **126**. The inner wall **126** merges into a vertical skirt portion **128**. Thus the entire frame **102** includes an upright outer wall **122**, a downwardly and inwardly slanted inner wall **126** and a vertical skirt portion **128**.

The head and foot ends **104** and **106** have curved outer ends **107** that curve into and merge smoothly with the side rail members **108**. The head end **104** further includes bosses for receiving the risers **112**. The foot end **106** has an anchor support plate **121** spanning between the curved ends **107** for supporting ends of the bias members or springs **120** to bias the carriage **110** as mentioned above.

Extending downward from each curved end **107** is a complementary shaped upright support leg **129**. These support legs **129** may be removed to place the ends **104** and **106** of the frame **102** on a planar surface such as a floor. The support legs **129** may be interchanged with longer or shorter support legs to change the height of the apparatus **100** above such a floor support surface.

A sectional view of a side rail member **108** is shown in FIG. **3**. Each rail member **108** is preferably an aluminum extrusion having an identical cross sectional shape. The rail member **108**, as mentioned above, has an outer upright wall **122** that merges into a horizontal top wall **124** and then into a downwardly slanted inner wall **126** and then into a vertical skirt portion **128**. The end members **104** and **106** have the same exterior shape, but differ internally from the side rail members **108**.

As is shown in FIG. **3**, each side rail member **108** has a vertical mid wall **130** between the slanted inner wall **126** and the upright outer wall **122**. The mid wall **130** has an outwardly facing upper longitudinally extending boss **132** and a lower outwardly facing longitudinally extending boss **134** parallel to the upper boss **132**. Together the mid wall **130**, the upper boss **132** and lower boss **134** form an outwardly open slot **136** therebetween. This slot **136** receives and carries one of the foot bar support assemblies therein as will be described in detail below. Between the mid wall **130** and the slanted inner wall **126** is an upper horizontal support wall **138**. The support wall **138** extends the length of the rail member **108** and provides torsional rigidity to the structure of the rail member **108**. A horizontal bottom portion **140** of the mid wall **130** acts

as a support for one set of wheels supporting the carriage **110**. The upper wall **138** serves also as an upper guide for the carriage support wheels on the rail members **108**. Furthermore, the mid wall **130** between upper and lower walls **138** and **140** and the skirt portion **128** serves as a lateral guide for the carriage **110**.

The upper boss **132** preferably has a vertical portion **142** that extends downward parallel to the mid wall **130**. This vertical portion **142** is used to provide lateral support for the foot support assembly described more fully below. Furthermore, the lower boss **134** may include a downwardly extending index rail **144**. Alternatively, the indexing rail **144** may be installed along the length of the rail member **108** by a separate, replaceable metal indexing rail carried in the boss **134**.

FIG. **4** is a perspective view of a foot end **106** of the frame **102**. The foot end **106** carries the anchor plate **121** for receiving free ends of one or more of the springs **120**. A plurality of spaced hourglass spool shaped pins **148** are each positioned to receive a loop on a spring **120** in order to fasten the spring **120** to the foot end **106** of the frame **102**. Each of these pins **148** preferably tapers upward and inward from its base to a waist at a first angle from the pin's central axis and then outward at a second angle greater than the first angle so that the free end of a spring placed on the pin **148**, when under tension, is securely held at the waist of the pin **148**.

Each corner of the frame **102**, formed by the ends **104** and **106**, includes curved outer upright wall **122**, top wall **124** and inwardly slanted inner wall **126**. Preferably inner wall **126** terminates in an upright lower skirt portion **128**. The foot end **106** also includes two spaced apart tubular foot support bosses **146** formed therein. These foot support bosses **146** are used to support a flat, generally rectangular foot platform (not shown) often called a "jump board". This jump board is a rectangular plate that has two spaced parallel support posts that removably fit into the foot support bosses **146**.

The foot bar **111** shown in FIG. **1** will now be described specifically with reference to FIGS. **5**, **6**, **7**, **8**, and **9**. The foot bar **111** is part of a foot support assembly that cannot be seen in FIG. **1**. This foot bar **111** is separately shown in FIG. **5**. The foot bar **111** has a central horizontal foot support portion **150** between two parallel leg portions **152**. Each leg portion **152** terminates in a connection portion **154** that is fastened to one of two foot bar support assemblies **170**.

Referring now to FIGS. **6** and **7**, the connection portion **154** is bolted or otherwise fastened to a bottom end **156** of an elongated foot bar support arm **158**. The arm **158**, best shown in FIG. **6**, is an elongated flat plate member that has an engaging pin **161** projecting outward from the upper end **160** of the arm **158**. The arm **158** further has a closed pivot slot **162** radially extending parallel to the leg portion **152** of the foot bar **111** and spaced from where the connection portion **154** of the foot bar **111** is attached to the arm **158**.

The foot support assembly of reformer **100** shown in FIG. **1** includes a left foot bar support assembly **170**, the foot bar **111**, and a right foot bar support assembly **170**. FIGS. **6** and **7** are reverse perspective views of a right one of the foot bar support assemblies **170** in accordance with one embodiment of the present disclosure. Each leg **152** of the foot bar **111** is supported by one of the foot bar support assemblies **170**. As is best shown in FIG. **6**, the assembly **170** includes the foot bar support arm **158** to which the foot bar **111** is attached, a slide portion **172** that rides in the slot **136** in the side rail member **108**, and a hook plate **174** which is rigidly fastened to the slide portion **172**. This hook plate **174** has a series of features, preferably slots or notches **176**, **178**, **180**, **182** and **184** spaced along the upper edge of the hook plate **174**. The pin **161** projecting outward from the upper end **160** of the foot bar

support arm **158** fits within one of these notches **176-184** to position the foot bar **111** at a particular desired angular position with respect to the frame **102** of the reformer **100**.

The foot bar support arm **158** is slidably and pivotally attached to the hook plate **174** by a bolt **186** and square bushing **188**. The bushing **188** rides between and along the parallel sides of a recess **190** in the arm **158** around the pivot slot **162**. Since the foot bar **111** is fastened to the arm **158**, when a user lifts the foot bar **111**, the support arm **158** rides up or down along the slot **162**. In turn, the pin **161** projecting outward from the upper end **160** of the support arm **158** is raised out of one of the slots along the upper edge of the hook plate **174**. When lifted in this manner, a user can then rotate the foot bar **111** about the pivot bolt **186** to a different one of the slots **176, 178, 180, 182** or **184** to reposition the foot bar **111**. When the foot bar **111** is lowered, the pin **161** slides down within one of the slots to fix the foot bar **111** in position.

The end slots or notches **176** and **184** have special significance in this embodiment **100**. When the foot bar **111** has both its pins **161** positioned in slots **176**, the foot bar **111** is rotationally positioned below the upper surface of the frame **102** and beyond the foot end of the frame **102**. In this position, the foot bar **111** may be used as a handle to lift the foot end of the reformer **100**. To ensure that the foot bar **111** does not disengage from the slot **176**, the terminal end of the slot **176** is hooked upward, as can be seen in FIG. 6, to firmly engage with the pin **161** at the closed end of the slot **176**. To disengage the foot bar **111** from this slot **176**, the foot bar **111** must be pushed down and pulled rearward (away from the foot end) to align the pin **161** with the widened slot entrance. The foot bar **111** may then be rotated up and lifted out of the slot **176** and repositioned in a different one of the slots **178, 180, 182** and **184**.

The forward most slot **184** in the hook plate **174** is used to position the foot support assembly comprising each of the assemblies **170** and the foot bar **111** together for translation along the rail members **108**. As the foot bar **111** is raised and is rotated clockwise, as seen in FIG. 6, the arm **158** is rotated about the bolt **186** clockwise until the pin **161** engages a protruding surface **192** at the forward end (toward head end **104**) of the hook plate **174**. In this position, a shoulder **194** on the support arm **158** engages with a latch pin **196** that projects through a slot **198** in the hook plate **174**. The latch pin **196** projects through the hook plate **174** from a latch arm **200** best seen in FIG. 7. When the foot bar **111** is then lowered, the shoulder **194** of the arm **158** pushes the latch pin **196** down.

Latch arm **200** is an elongated bar that has one end rotatably fastened to the inside face of the hook plate **174**. The latch arm **200** can rotate in a plane parallel to the inside surface of the hook plate **174**. The other end of the latch arm **200** has a latch portion **202** that engages a complementary shaped indexing feature in the rail member **108** in order to latch the assembly **170** at a selected position along the rail member **108**. The latch arm **200** is spring biased upward via spring member **201** to maintain the latch portion **202** of the latch arm **200** engaged with the indexing feature of the index rail **144** in the rail member **108**.

When the foot bar **111** is positioned with pins **161** in the slots **184**, and the foot bar **111** is pushed downward to fully seat the pins **161** at the bottom of slots **184**, the latch pins **196** are also pushed downward, rotating the latch arm **200** and moving latch portion **202** out of engagement with the indexing feature of the index rail **144** in the rail member **108**. With the latch portions **202** disengaged with the rail members **108**, the foot bar **111** may be moved toward or away from the foot

end **106** of the frame **102** via the rollers **206**. In fact, the foot bar **111** may be moved fully to the opposite end of the rail members **108** if desired.

The slide assembly **172** is best seen in the view of FIG. 7 which is a perspective inside view of the foot bar support assembly **170** shown in FIG. 6 that is carried in the right side rail member **108**. The slide assembly **172** includes an elongated slide plate **204** that is preferably bolted or otherwise fixed to the hook plate **174**. This slide plate **204** rides in the slot **136** in the rail member **108** with the hook plate **174** and adjacent foot bar support arm **158** disposed within the free/open space between the outer wall **122** and mid wall **130** of the rail member **108**. It is to be understood that another, mirror image foot support assembly **170** is disposed in the other (left) rail member **108**.

A sectional view of a left rail member **108** as in FIG. 3 is shown in FIG. 8 with the left foot bar support assembly **170** riding in the slot **136**. All of the component parts of the assembly **170** are disposed between the outer wall **122** and mid wall **130** of the rail **108**. Thus the complete foot bar support assembly **170** is hidden from view by a user sitting on the carriage **110**. It is to be understood that the right foot bar support assembly **170** in the right rail member **108** is constructed similarly. Thus the component parts of the assemblies **170** are either interchangeable or are mirror images. For example, the foot bar support arms **158** and hook plates **174** are mirrored. The remainder of the component parts of the assembly **170** may be interchangeable.

Turning back now to FIG. 7, the slide plate **204** is supported in the slot **136** by front and rear support rollers **206** that roll along the bottom surface of the slot **136**. A guide roller **208** that rotates about a vertical axis through the slide plate **204** is mounted preferably adjacent to each support roller **206**. The guide rollers **208** roll along inner side surfaces of the slot **136** in the rail member **108** to guide the support assembly **170**, and thus the foot bar **111**, as it is translated (i.e., rolled) fore and aft along the rail members **108**.

The support rollers **206** are preferably bearing supported polymer wheels rotatably supported on horizontal axles. The polymer wheels are sized to fit and smoothly roll within the slot **136**. The guide rollers **208** may be nylon or other polymer rollers supported by a vertical axle in the slide plate **204**.

A further sectional view through the left rail member **108** of the apparatus **100** as in FIG. 1 is shown in FIG. 9 taken along the line 9-9 of FIG. 1. This view shows the foot support assembly **170** carried within the rail member **108** as well as the wheeled support arrangement for the carriage **110**. Specifically, the generally rectangular carriage **110** has four support wheels **210**, one adjacent each corner, and at least two carriage guide wheels **212** positioned preferably along one side of the carriage **110** that also ride in the space between the mid wall **130**, the inner slanted wall **126**, the skirt portion **128** and the bottom portion **140** of the mid wall **130** of the rail member **108**. The support wheels **210** roll on the bottom portion **140**.

The guide wheels **212** roll between the mid wall **130** and the skirt portion **128** of the inner wall **126** to maintain tracking of the carriage **110** as it moves between the foot end **106** and head end **104** of the frame **102**. Because of the guide configuration of the rail member **108**, only two guide wheels **212**, both along only one side, are necessary to guide movement of the carriage **110**. The guide wheels **212** are arranged in only one of the rail members **108**. However, three or four guide wheels **212** may be provided in alternative configurations of the carriage **110**.

Thus in the reformer **100** shown in FIG. 1, both support for the carriage **110** and the support for the foot bar **111** is pro-

11

vided by structures beneath and carried within the side rail members 108 and are thus hidden from external view. This arrangement presents a clean, uncluttered, appearance to the reformer apparatus 100 and minimizes the surface areas that can collect dust over time. Furthermore, in order to provide a direct foot bar position feedback to the user of the exercise apparatus 100, a “J” shaped indicator member 214 is fastened to one or both of the slide plates 172. A distal tip 216 of the indicator 214 extends around a bottom edge and upward outside of the wall 122 of the side rail member 108 to provide a user of the reformer 100 with an indication of the foot support assembly position. Corresponding markings (not illustrated) may be provided along the outer wall 122 for a user to utilize in positioning the foot bar 111 at preselected positions along the frame 102.

The notch 178 in the hook plate 174 is used to locate the foot bar 111 at a lowest position above the frame 102. The notch 180 places the foot bar 111 at a middle height position above the frame 102. The notch 182 corresponds to the foot bar 111 being substantially vertical, and thus its highest position above the frame 102. Additional notches may alternatively be provided to facilitate additional foot bar positions. However, a low, moderate, and high position are believed to be sufficient for most users of the apparatus 100.

A low friction layer 218 of polymer sheet material (shown in FIG. 6) is affixed to the outer surface of the hook plate 174 between the hook plate 174 and the support arm 158. This layer reduces any friction between the arm and the plate during rotation of the foot bar 111 between the notches 176, 178, 180 182 and 184. Alternatively, the low friction layer 218 may be applied to the inner surface of the arm 158. Further, a low friction layer 218 may optionally be applied to both of these facing surfaces.

The structure of the foot support assembly may be other than has been specifically illustrated and described. For example, the rollers 206 and 208 could be replaced by sheets of low friction material to permit the slide plate 204 to easily slide along the slot 136. The configuration of the support arm 158, the hook plate 174 and slide plate 172 may be different than that of the exemplary embodiment shown. Further other mechanisms may be used to engage and disengage the assembly 170 with features in the rail members 108 of the frame 102.

Referring back to FIG. 1, at the head end 104 of the reformer apparatus 100 there are two spaced apart risers 112 for directing arm cords 114 from the carriage 110 to the head end 104 and then to the arm cord end loops 116. Referring now to the close perspective view of one of the risers 112 at the head end 104 shown in FIG. 10, each of these risers 112 includes a lower pulley wheel assembly 220 fastened into a tubular riser boss 222 formed adjacent each curved end 107 of the head end 104. Each riser 112 also includes a hollow tubular body 224 having its bottom end fitted within the tubular riser boss 222. The upper end 228 of the riser tubular body 224 carries a cylindrical roller head 230. This roller head 230 includes a tubular body 232 that fits into or is integrally formed with the body 224. The tubular body 232 has an elongated aperture 234 through its side. A pair of vertically aligned guide rollers 236 are mounted to the head 230 on both sides of the aperture 234. Mounted within and transversely across the tubular body 232 behind the aperture 234 is a horizontal cord pulley wheel or roller 238.

The lower pulley wheel assembly 220 is separately shown in perspective view in FIG. 11. The lower pulley wheel assembly 220 has a flanged cylindrical body 240 that is fastened to the bottom of the boss 222. Carried within the body 240 is a horizontally journaled pulley wheel 242 and an

12

angled cord guide disc 244. The guide disc 244 is positioned in the body 240 above the wheel 242 at an angle of about 45 degrees. An aperture 246 is provided in the disc 244 along its lower edge. This aperture 246 is oriented directly above the periphery of the pulley wheel 242 such that a free end of an arm cord 114 that is lowered into the riser 112 through the aperture 234 in the head assembly 230 is directed over the roller 238 and down through the tubular body 224 and through the aperture 246 and past the pulley wheel 242. A user can then grasp the free end of the cord 114 and fasten the cord to the carriage 110 as described in detail below.

The head assembly 230 may be fixed to the tubular body 224 or optionally may be bearing supported thereon such that it can rotate freely about a vertical axis through the riser 112. Each of the guide rollers adjacent the aperture 234 may be mounted on stationary vertical pins or otherwise bearing supported such that the cord 114 can be pulled through the aperture 234 with minimal resistance or friction. The bottom or lower pulley wheel 242 is oriented with its axis normal to the rail members 108 since movement of the carriage 110 is always either toward or away from the head end 104 of the frame 102.

An exploded perspective view of the carriage 110 is separately shown in FIG. 12. The carriage 110 includes a generally rectangular frame 250, a rectangular support platform 252, a padded upper platform 254, and a pair of shoulder stops 118. The frame 250 has upright side support plates 258, a vertical head end plate 260 and a vertical spring support plate 262, both of which are fastened to the side support plates 258. All of these plates 258, 260 and 262 are also fastened to the underside of the support platform 252 to provide a rigid carriage structure. The spring support plate 262 carries one end of each of the biasing springs 120. The other end of each spring 120 may be removably fastened to the anchor pins 148 in order to vary the resilient bias, i.e. spring tension between the carriage 110 and the foot end 106 of the frame 102. The side support plates 258 each support the platforms 252 and 254 and provide mounting flanges for support wheels 210 and guide wheels 212. The head end plate 260 has a pair of spaced openings 264 therethrough which act as guides for the arm cords (not shown in FIG. 12).

The support platform 252 has a pair of shoulder stop supports 266 fastened to its upper surface. Each of these supports 266 has a vertical bore 268 therethrough and each supports a cross pin 270 (shown in FIG. 15) therein that fastens the stem 272 of the shoulder stop 118 to the carriage 110. The bore 268 extends through the support 266 and through the support platform 252.

FIG. 15 is a partial vertical sectional view through the carriage 110 with the padded upper platform 254 not shown. As can be seen in this view, the cross pin 270 acts as a pivot for the shoulder stop stem 272. A bias device 274 such as a flexible rubber tube positioned against the stem 272 provides a spring force against the stem 272 to maintain the stem 272 oriented vertical and flush with the left side of the bore 268. However, when a user pulls on the top of a shoulder stop 118 toward the foot end of the frame 102, (as is shown) the stop rotates about the cross pin 270, compressing the bias device 274, and pushing a bottom end 276 of the stem 272 toward the head end of the frame 102 (to the right in FIG. 15).

A bottom plan view of a head end portion of the carriage 110 is shown in FIGS. 13 and 14. These two views illustrate the configuration of the cord retraction mechanism 280 in accordance with an embodiment of the present disclosure. The arm cords 114 are not shown in this view for clarity. The cord retraction mechanism 280 includes, for each cord 114, a spring biased reel housing 282 fastened to the support plate

252, a spring biased cord reel 284 rotatably carried in the housing 282, and a toothed plate latch arm 286 rotatably fastened to the underside surface of the support plate 252 adjacent to the reel housing 282.

As is shown in FIGS. 13 and 14, the two housings 282 of the cord retraction mechanism 280 are mounted side by side against the underside surface of the platform 252. The two latch arms 286 are preferably plate members fastened for rotation about pivot pins 288 adjacent the reel housings 282 so that they can rotate in the plane of the underside surface of support platform 252. Each latch arm 286 is preferably an elongated plate shaped body having a toothed end 290 and an opposite linkage end 292. The latch arms 286 are preferably mirror images of each other such that the opposite linkage ends 292 of each latch arm plate 286 movably engage each other to link the latch arms 286 together under the support platform 252.

The toothed end 290 of each latch arm 286 engages corresponding notches of features in a rim of the adjacent cord reel 284 in the adjacent reel housing 282. The toothed end 290 of each latch arm 286 also has a hook 294 that engages with the bottom end 276 of the stem 272 of the shoulder stop 118. FIG. 13 shows the shoulder stops 118 in a normal position, and thus the bottom ends 276 of the stems 272 are not engaged with the hooks 294 of either latch arm 286. One or more springs (not shown) are used to bias both latch arms 286 into engagement with the reels 284. With the arms 286 in this position, the arm cords 114 cannot be retracted or extended from the reels 284. They are locked.

FIG. 14 shows the configuration when the left bottom end 276 of stem 272 of the right shoulder stop 118 is engaged with the hook 294 on the left latch arm 286. This causes the latch arm 286 to rotate clockwise about pin 288, pulling the toothed end 290 out of engagement with the left reel 284 in FIG. 14. At the same time, clockwise rotation of the left latch arm 286 caused counterclockwise rotation of the right latch arm 286 through the linked linkage ends 292. This rotation similarly causes the toothed end 290 of the right latch arm 286 to rotate out of engagement with its adjacent reel 284. Thus a user pulling either shoulder stop 118 toward the foot end 106 of the frame 102 will cause both of the latch arms 286 to disengage from the reels 284, permitting a user to adjust either or both arm cord lengths as desired. Upon release of the shoulder stop 118, the latch arms 286 re-engage the reels 284 to lock the reels and thus the arm cords 114 to the carriage 110.

A retrofit arm cord retraction mechanism kit for a conventional reformer is also envisioned in accordance with the present disclosure. Such a kit would include appropriate installation instructions, two reel housings 282 with enclosed arm cord reels 284, a pair of latch arms 286, replacement shoulder stops 118, two shoulder stop supports 266, and a pair of pivot pins 288 for fastening the latch arms 286 to the carriage.

FIGS. 16 and 17 illustrate an alternative cord retraction mechanism 300 mounted beneath the carriage 110 in accordance with the present disclosure. The arm cords 114 again are not shown in this view for clarity. The cord retraction mechanism 300 includes, for each cord 114, a spring biased cord reel 302 that is mounted beneath the support plate 252 for rotation, in this embodiment, about a horizontal axle 304 supported from the support plate 252 between a bracket 306 and the carriage frame side support plate 258. The cord reel 302 has a band brake portion 308 and a cord support portion 310. One end of the cord 114 (not shown) is fastened to and wrapped around the cord support portion 310 of the reel 302. As is shown in FIGS. 16 and 17, the two reels 302 of the cord

retraction mechanism 300 are rotatably mounted side by side beneath the underside surface of the platform 252.

Around the band brake portion 308 of each reel 302 is wrapped a cable 312 that has one end fastened to the support plate 252 and the other end fastened to one end 318 of a pair of crossed lever arms 314. The other end 320 of each lever arm 314 is positioned to engage the bottom end 276 of the stem 272 of one of the shoulder stops 118 as in the previously described embodiment.

Similar to the previously described embodiment of the retraction mechanism 280, the two lever arms 314 are preferably separate members each fastened for rotation about a separate pivot pin 322 and are crossed and rotatably fastened together in scissor fashion at a common pin 324 so that they can rotate about the pins 322 and 324 in a plane parallel to the underside surface of support platform 252.

During normal reformer operation the end 318 of each lever arm 314 is under tension by a spring 326. This spring 326 pulls the lever arm 314 toward the head end of the carriage 110 and thus pulls the cable 312 so as to tighten the cable 312 around the band brake portion 308 of its reel 302 to prevent rotation of the reel 302. When a user on the reformer 100 pulls (tilts) one of the shoulder stops 118 toward the foot end 106 of the reformer frame 102, both of the lever arms 314 rotate in opposite directions about the pivot pins 322 and 324 so as to release tension on the brake cables 312 as is shown in FIG. 17. When the brakes are thus released, a user can withdraw more cord 114 or permit an internal spring in the reel 302 to rotate the reel 302 and take up slack in the cord 114. When the user releases the shoulder stop 118, the springs 326 again pull on the cables 312 to stop rotation of the reels 302 and thus secure the cords 114 to the carriage 110.

Again, a retrofit arm cord retraction mechanism kit for a conventional reformer is also envisioned in accordance with the present disclosure for this alternative retraction system 300. Such a kit would include two retraction reels 302, axles 304 and brackets 306, band brake cables 312, a pair of crossed lever arms 314, springs 326, replacement shoulder stops 118, two shoulder stop supports 266, and a pair of pivot pins 322 for fastening the lever arms 314 to the carriage 110, and appropriate installation instructions.

In an optional configuration of the reformer carriage 110 in accordance with the present disclosure, an adjustable headrest may be integrated into the structure. A partial bottom view of the head end of this alternative embodiment of the carriage 110 is shown in FIGS. 18, 19, 20 and 21. In this embodiment, on top of the carriage frame 250, the support plate 252 has a trapezoidal shaped extension portion 350 that extends toward the head end of the frame 102. The padded upper plate 254 has the same overall shape as in the first embodiment shown in FIG. 12, but is separated into a rectangular portion 352 and a head rest portion 354 by a transverse hinge 356 beneath the padding near the shoulder stops 118.

An adjustable headrest support plate 358 is fastened to the support plate 252 under the head rest portion 354. The extension portion 350 has an elongated vertical slot 357 there-through preferably centered between the sides of the extension portion 350. The support plate 358 has a transverse channel 360 therein that carries an L shaped headrest adjustment rod 362 sandwiched between the channel 360 and the extension portion 350. Attached to the rod 362 is a cam block 364 that extends through the slot 357. Rotation of handle portion of the rod 362 forces the cam block 364 to rotate against the hinged head rest portion 354. As the cam block 364 is rotated by rotation of the rod 362, the head rest portion 354 is moved between the positions shown in FIGS. 19-21. In particular, FIG. 19 shows the headrest portion 354 in a down

position. FIG. 20 shows the headrest portion 354 in a first raised position, with the rod 362 rotated about 90 degrees counterclockwise. FIG. 21 shows the headrest portion in a second raised position with the rod 362 rotated an additional 90 degrees counterclockwise. In this embodiment, cam block 364 provides three stable positions. Also, note that in FIGS. 16 and 17, the head rest adjustment rod (not numbered) is shown with two handle ends rather than only one as in FIGS. 18-21. Other configurations also are well within the scope of this disclosure. For example, the cam block 364 may be smoothly curved without flat portions for specific headrest elevations and the rod 362 may be configured to provide a frictional hold such that the headrest portion 354 may be held at any desired elevation. Alternatively, the cam block may be configured with four or more flat regions, each corresponding to a different raised height.

A perspective view of another embodiment of a reformer exercise apparatus 400 in accordance with the present disclosure is shown in FIG. 22. The apparatus 400 has a generally rectangular frame 402 with a head end 404 and a foot end 406. The ends 404 and 406 are spaced apart by a pair of rail members 408. A carriage 410 is movably supported on the rail members 408 for movement back and forth between the ends 404 and 406 of the frame 402.

A foot bar 411 is positioned near the foot end 406 of the frame 402. This foot bar 411 is carried by the rail members 408 as will be described in detail below. The head end 404 of the frame 402 preferably supports a removable pair of spaced upright arm cord support risers 412. These risers 412 direct arm cords 414 from the carriage 110 to cord end loops 416 or grips for a user's hands for use in various exercises. When not in use, the end loops 416 may be conveniently positioned on the shoulder stops 418 as shown in FIG. 22. The carriage 410 is resiliently biased toward the foot end 416 of the frame 402 by one or more elastic members such as springs 420 (see FIG. 35).

The exterior of the frame 402 has the same shape as frame 102 shown in FIG. 2. Each of the head end 404, the foot end 406 and the side rail members 408 has a similar outer surface shape that smoothly merge together.

A separate inside perspective view of the head end assembly 404 is shown in FIG. 23. The head end assembly includes an end extrusion 500 that has leg portions 502 and a horizontal stepped support plate 421. The external shape of the extrusion 500, as in the first embodiment, includes an outer upright wall 422 merging with a horizontal top wall 424 which merges with a downwardly and inwardly slanted inner wall 426. The inner wall 426 merges into a vertical skirt portion 428. The vertical skirt portion 428 joins with the horizontal stepped support plate 421.

Both the head and foot ends 404 and 406 have outer end plates 407 that mate with and are attached to the side rail members 408 via alignment pins 409 and threaded connections (not shown). The head end 404 extrusion 500 further includes vertical tubular bosses 506 adjacent the curved corners for receiving the risers 412. A pair of threaded hand bolts 413 inserted from beneath secure the risers 412 into the bosses 506. A standing platform 415 is fastened over and onto the stepped support plate 421.

Extending downward from each curved end of the extrusion 500 is a complementary shaped upright support leg 429. These support legs 429 are used to place the ends 404 and 406 of the frame 402 on a planar surface such as a floor. The support legs 429 may be interchanged with longer or shorter support legs to change the height of the apparatus 400 above a floor support surface. A grip strip 417 is fastened to the outer

lower edge of the outer wall 407 of the extrusion 500 to provide a rounded hand gripping edge for ease of carrying the head end of the reformer 400.

FIG. 24 is a perspective view of a foot end assembly 406 of the frame 402. The foot end assembly 406 is another extrusion 500 that has leg portions 502, bosses 506 and a horizontal stepped support plate 421. Two rows of spool shaped anchor pins 448 are fastened to the plate 421. These pins 448 each can receive and hold a loop on one end of a spring 420 in order to fasten the spring 420 to the foot end 406 of the frame 402 while the other end of the spring 420 is fastened to the carriage 410. Each of these pins 448 preferably tapers upward and inward from its base to a waist at a first angle from the pin's central axis and then outward at a second angle greater than the first angle so that the free end of a spring placed on the pin 448, when under tension, is securely held at the waist of the pin 448. This second angle is preferably at least twice that of the first angle.

The foot support bosses 506 are vertical tubes formed in the extrusion 500. Each boss 506 receives a yoke 508 that fits on the top of the boss 506. A rectangular standing platform plate 423 is pinned onto the yokes 508. Finally a tubular receiver 510 fits through holes in the plate 423 and fits into the bosses 506 to secure the plate 423 to the extrusion 500. A set of bolts 512 fasten each receiver 510, plate 423, and yoke 508 to the boss 506. The receivers 510 receive legs of a removable flat jump board platform (not shown).

A sectional view of a side rail member 408 is shown in FIG. 25. Each rail member 408 is preferably an aluminum extrusion assembly having an identical cross sectional shape. In this particular reformer embodiment 400 the rail member 408 is a composite extrusion formed by two separate extrusion portions: inner portion 417 and outer portion 419 that are joined together by rivets 514. This construction of the side rail member 408 is particularly advantageous for at least two reasons. First, such a configuration is easier to extrude as two separate extrusions that are later joined. Second, the outer portion 419 may be finished differently than the inner portion 417. Thus one version of the outer portion 419 may be either powder coated for durability and/or painted in selectable colors while the inner portion 417 is powder coated or otherwise finished for durability, since it is not in view. Furthermore, the inner portion 417 since it also contains the rolling surfaces and index rail feature for the foot bar 411, may be separated and replaced if required due to wear. The rail member 408, as mentioned above, has an outer upright wall 422 that merges into a horizontal top wall 424 and then into a downwardly slanted inner wall 426 and then into a vertical skirt portion 428. The end members 404 and 406 have the same exterior shape, but differ internally from the side rail members 408.

As is shown in FIG. 25, each side rail member 408 has a vertical mid wall 430 between the slanted inner wall 426 and the upright outer wall 422. The mid wall 430 has an outwardly facing upper longitudinally extending boss 432 and a lower outwardly facing longitudinally extending boss 434 parallel to the upper boss 432. Together the mid wall 430, the upper boss 432 and lower boss 434 form an outwardly open slot 436 therebetween. This slot 436 receives and carries one of the foot bar support assemblies therein as will be described in detail below. Between the mid wall 430 and the slanted inner wall 426 is an upper horizontal support wall 438. The support wall 438 extends the length of the rail member 408 and provides torsional rigidity to the structure of the rail member 408. Furthermore, this support wall 438 facilitates joiner between the inner and outer extrusion portions 417 and 419. A horizontal bottom portion 440 of the mid wall 430 acts as a

support for one set of wheels supporting the carriage **410**. The upper wall **438** serves also as an upper guide for the carriage support wheels on the rail members **408**. Furthermore, the mid wall **430** between upper and lower walls **438** and **440** and the skirt portion **428** serves as a lateral guide for the carriage **410**.

The upper boss **432** preferably has a vertical portion **442** that extends downward parallel to the mid wall **430**. This vertical portion **442** is used to provide lateral support for the foot support assembly described more fully below. Furthermore, the lower boss **434** may include a downwardly extending index rail **444**. Alternatively, the indexing rail **444** may be installed along the length of the rail member **408** by a separate, replaceable metal indexing rail carried in the boss **434**.

Finally, the inside of the outer portion **419** of the rail **408** includes three locating bosses **516**, **518** and **520**. These three locating bosses align with and receive the locating pins **409** projecting from the head and foot end assemblies **406** and **408**, shown in FIGS. **23** and **24**. These bosses help to ensure exact alignment between the rails **408** and ends **406** and **406** such that a smooth exterior frame surface is presented to a user of the apparatus **400**.

The foot bar **411** shown in FIG. **22** is the same as that shown in FIG. **5**. The foot bar support assembly **470** is similar to but differs slightly from that shown and described above specifically with reference to FIGS. **6**, **7**, **8**, and **9**. The foot bar **411** is part of a foot support assembly **470** that cannot be seen in FIG. **22**. Referring now to inner and outer views of the foot support assembly **470** shown in FIGS. **29** and **30**, the connection portion **154** of the foot bar **411** is bolted or otherwise fastened to a bottom end **456** of an elongated foot bar support arm **458**. The arm **458**, best shown in FIG. **29**, is an elongated flat plate member that has an engaging pin **461** projecting outward from the upper end **460** of the arm **458**. The arm **458** further has a closed pivot slot **462** radially extending parallel to the leg portion **152** of the foot bar **411** and spaced from where the connection portion **154** of the foot bar **411** is attached to the arm **458**.

The foot support assembly of reformer **400** shown in FIG. **22** includes a left foot bar support assembly **470**, the foot bar **411**, and a right foot bar support assembly **470**. FIGS. **29** and **30** are reverse perspective views of a right one of the foot bar support assemblies **470** in accordance with one embodiment of the present disclosure. Each leg **152** of the foot bar **411** is supported by one of the foot bar support assemblies **470**. As is best shown in FIG. **29**, the assembly **470** includes the foot bar support arm **458** to which the foot bar **411** (not shown in FIGS. **29** and **30**) is attached, a slide portion **472** that rides in the slot **436** in the side rail member **408**, and a hook plate **474** which is rigidly fastened to the slide portion **472**. This hook plate **474** has a series of features, preferably slots or notches **476**, **478**, **480**, **482** and **484** spaced along the upper edge of the hook plate **474**. The pin **461** projecting outward from the upper end **460** of the foot bar support arm **458** fits within one of these notches **476-484** to position the foot bar **411** at a particular desired angular position with respect to the frame **402** of the reformer **400**.

The foot bar support arm **458** is slidably and pivotally attached to the hook plate **474** by a bolt **486** and square bushing **488**. A flat washer **489** on the bolt **486** holds the support arm **458** on the bushing **488**. The bushing **488** rides in the pivot slot **462**. Since the foot bar **411** is fastened to the arm **458**, when a user lifts the foot bar **411**, the support arm **458** rides up or down along the slot **462**. In turn, the pin **461** projecting outward from the upper end **460** of the support arm **458** is raised out of one of the slots along the upper edge of the hook plate **474**. When lifted out of its slot in this manner, a

user can then rotate the foot bar **411** about the pivot bolt **486** to a different one of the slots **476**, **478**, **480**, **482** or **484** to reposition the foot bar **411**. When the foot bar **411** is lowered into a slot, the pin **461** slides down within one of the slots to fix the foot bar **411** in position.

The end slots or notches **476** and **484** have special significance in this embodiment **400** as in the first embodiment **100**. When the foot bar **411** has both its pins **461** positioned in slots **476**, the foot bar **411** is rotationally positioned slightly above, the upper surface of the frame **402** and beyond the foot end of the frame **402** as is shown in FIG. **39**. In this position, the foot bar **411** may be used as a handle to lift the foot end of the reformer **400**. To ensure that the foot bar **411** does not disengage from this slot **476**, the terminal end of the slot **476** is hooked upward, as can be seen in FIG. **29**, so as to firmly engage with the pin **461** at the closed end of the slot **476**. To disengage the foot bar **411** from this slot **476**, the foot bar **411** must be pushed down and pulled rearward (away from the foot end) to align the pin **461** with the widened slot entrance. The foot bar **411** may then be rotated up and lifted out of the slot **476** and repositioned in a different one of the slots **478**, **480**, **482** and **484**.

The forward most slot **484** in the hook plate **474** is used to position the foot support assembly comprising each of the assemblies **470** and the foot bar **411** together for translation along the rail members **408**. As the foot bar **411** is raised and is rotated clockwise, as seen in FIG. **29**, the arm **458** is rotated about the bolt **486** clockwise until the pin **461** engages a protruding surface **492** at the forward end (toward head end **404**) of the hook plate **474**. In this position, a shoulder **494** on the support arm **458** engages with a latch pin **496** that projects through a slot **498** in the hook plate **474**. The latch pin **496** projects through the hook plate **474** from a latch arm **530** best seen in FIG. **30**. When the foot bar **411** is then lowered, the shoulder **494** of the arm **458** pushes the latch pin **496** down.

Latch arm **530** is an elongated bar that has one end rotatably fastened to the inside face of the hook plate **474**. The latch arm **530** can rotate in a plane parallel to the inside surface of the hook plate **474**. The other end of the latch arm **530** has an upwardly hooked latch portion **532** that engages a complementary shaped indexing feature in the rail member **408** in order to latch the assembly **470** at a selected position along the rail member **408**. The latch arm **530** is spring biased upward via flat spring member **534** to maintain the latch portion **532** of the latch arm **530** engaged with the indexing feature of the index rail **444** in the rail member **408**.

When the foot bar **411** is positioned with pins **461** in the slots **484**, and the foot bar **411** is pushed downward to fully seat the pins **461** at the bottom of slots **484**, the latch pins **496** are also pushed downward, rotating the latch arm **530** and moving latch portion **532** out of engagement with the indexing feature of the index rail **444** in the rail member **408**. With the latch portions **532** disengaged with the rail members **408**, the foot bar **411** may be moved toward or away from the foot end **406** of the frame **402** via the rollers **536**. In fact, the foot bar **411** may be moved fully to the opposite end of the rail members **408** if desired.

The slide assembly **472** is best seen in the view of FIG. **30** which is an opposite perspective view of the foot bar support assembly **470** shown in FIG. **29** that is carried in the right side rail member **408**. The slide assembly **472** includes an elongated slide plate **538** that is preferably bolted or otherwise fixed to the hook plate **474**. This slide plate **538** rides in the slot **436** in the rail member **408** with the hook plate **474** and adjacent foot bar support arm **458** disposed within the free/open space between the outer wall **422** and mid wall **430** of

the rail member **408**. It is to be understood that another, mirror image foot support assembly **470** is disposed in the other (left) rail member **408**.

Turning back now to FIG. **30**, the slide plate **538** is supported in the slot **436** by front and rear support rollers **536** that roll along the bottom surface of the slot **436**. A guide roller **540** that rotates about a vertical axis through the slide plate **538** is mounted preferably adjacent to each support roller **536**. The guide rollers **540** roll along inner side surfaces of the slot **436** in the rail member **408** to guide the support assembly **470**, and thus the foot bar **411**, as it is translated (i.e., rolled) fore and aft along the rail members **408**.

The support rollers **536** are preferably bearing supported polymer wheels rotatably supported on horizontal axles. The polymer wheels are sized to fit and smoothly roll within the slot **436**. The guide rollers **540** may be nylon or other polymer rollers supported by a vertical axle in the slide plate **538**. In this embodiment **400**, the guide rollers **540** may be roller bearings mounted in recesses along the upper edge of the slide plate **538**.

The slide plate **538** also has a spring loaded locating ball **542** mounted in a recess behind the j shaped indexing member **544** utilized as described above with reference to the first embodiment. The spring loaded locating ball **542** provides a user with tactile feedback when moving the foot bar **411** back and forth along the rails **408** between various predetermined positions, by projecting into corresponding depressions that optionally may be provided along the rail **408**.

A low friction layer **546** of polymer sheet material (shown in FIG. **29**) is affixed to the outer surface of the hook plate **474** between the hook plate **474** and the support arm **458**. This layer, as in the first embodiment **100**, reduces any friction between the arm **458** and the plate during rotation of the foot bar **411** between the notches **476**, **478**, **480** **482** and **484**. Alternatively, the low friction layer **546** may be applied to the facing surface of the arm **458**. To further reduce friction, a low friction layer **546** may optionally be applied to both of these facing surfaces.

A removable pull pin **548** may optionally be inserted through aligned bores in the arm **458** and the plate **474** when the foot bar **411** is in the high position, i.e., slot **480**. Insertion of pull pin **548** will lock the foot bar **411** in place and prevent it from being repositioned. The purpose of this is so that the foot bar **411** can act as a support brace when the reformer **400** is vertically positioned on its foot end **406**. This facilitates vertical storage of a number of reformers **400** in a relatively confined space.

When the foot bar **411** is securely positioned with pins **461** seated in slots **484**, the whole foot bar assembly **411** can slide/roll back and forth along the side rails **408**. The plate **474** is preferably also provided with a hole **549**. This hole **549** can be used to store the pull pin **548** when not being used. In addition, this hole **549** may be used to attach an elastic or spring resistance member (not shown) between the carriage **410** and the foot bar **411** support plate **474** or between the foot end **404** and the support plate **474**. Such a resistance member can provide a resistance to translational movement of the foot bar **411** support assembly **470** by a user when the foot support arm **458** is engaged in slot **484**. In this configuration the foot bar **411** may be used to provide additional resistances experienced by a user during performance of various movements while being supported on the carriage **410**. Such a spring or other resistance member, such as an elastic cord, may be attached for this purpose between the carriage **410** and a suitable feature at a different location on the assembly **470** or

to the foot bar **411** itself. For example, such a resistance member may be attached to the connection portion **154** of the foot bar leg portion **152**.

Referring back to FIG. **22**, at the head end **404** of the reformer apparatus **400** there are two spaced apart arm cord risers **412** for directing arm cords **414** from the carriage **410** to the head end **404** and then to the arm cord end loops **416**. A separate perspective view of a riser **412** is shown in FIG. **26** and an exploded assembly view is shown in FIG. **27**. In this embodiment **400**, the riser **412** has no bottom pulley configuration as is utilized in riser **112**. Instead, preferably a pulley and roller assembly **550** is inserted into the upper end of the riser tube **552**. This pulley and roller assembly includes a support housing **554** that supports laterally spaced apart vertical rollers **556** that rotate about parallel vertical axles fastened into the housing **554**, and a pulley **558** mounted between and below the rollers **556** on a horizontal axle **560**. Each of the rollers and the pulley **558** is supported on its respective axle between pairs of ball bearings mounted in the support housing **554**.

Each of these riser tubes **552**, preferably includes two vertically aligned elongated openings **562** and **564** adjacent its upper end through which the arm cord **414** is passed. The pulley and roller assembly **550** slides into upper end of the riser tube **552** and is fastened in place with two screws **566**. When properly positioned in the tube **552**, the vertical rollers **556** are alongside the upper opening **562**. The pulley wheel **558** is centered between the two openings. The arm cord **414** is threaded through the upper opening and down around the pulley wheel **558**, and out through the lower opening **564** to the carriage **410** as is shown in FIG. **26**.

An annular collar **568** is fastened around the lower end portion of the tube **552** via screws **570**. This collar **568** is sized to snugly fit within the open upper end of the boss **506** of the head end extrusion **500** as is shown in the cutaway view in FIG. **28**. A threaded expansion plug **572** is press fit into the bottom end of the riser tube **552**. This threaded expansion plug **572** engages with the threaded hand bolt **413** (FIGS. **23**, **28**). When the hand bolt **413** is tightened, the riser **412** is pulled down into the boss **506** to secure the riser **412** in place. The riser tube **552** may alternately be made of different lengths such that different length risers **412** may be selected for different users. Finally, the lower opening **564** in the riser tube **552**, besides passing the cord **414** therethrough, is used to receive part of a bracket **700** (an example of which is shown in FIG. **31**) to removably hold the riser **412** beneath the head end of the carriage **410** during storage as is shown in FIG. **39**.

The carriage **410** is separately shown in FIGS. **31** and **32**. An underside separate perspective view of part of the carriage **410** is separately shown in FIG. **31**. An underside view of the upholstered upper platform **574** is separately shown in FIG. **32**. The carriage **410** includes a generally rectangular frame **576**, a rectangular support platform **578**, the upholstered upper platform **574**, and a pair of shoulder stops **418**. The frame **576** has upright side support plates **580**, a vertical head end plate **582** and a vertical spring support plate **584**, both of which are fastened to the side support plates **580**. All of these plates **580**, **582** and **584** are also fastened to the underside of the support platform **578** to provide a rigid carriage structure. The upper side of the platform **578** includes shoulder stop supports **594** (See FIG. **34**) as in the first embodiment of the carriage **110** shown in FIG. **12**.

The spring support plate **584** carries one end of each of the biasing springs **420**. The other end of each spring **420** may be removably fastened to the anchor pins **448** in order to vary the resilient bias, i.e. spring tension between the carriage **410** and the foot end **406** of the frame **402**. The side support plates **580**

support the platforms 574 and 578 and provide mounting flanges for support wheels 586 and guide wheels 588. The head end plate 582 has a pair of spaced openings 590 there-through which act as guides for the arm cords 414 (not shown in FIG. 31). A pair of elongated slots 592 are also formed in the head end plate 582. These slots 592 are shaped to receive the stems of the shoulder stops 418 when the shoulder stops 418 are removed and attached to the carriage 410 for storage as is shown in FIG. 39.

The support platform 578 has a pair of shoulder stop supports 594 fastened to its upper surface (as is shown in FIG. 34). Each of these supports 594 has a pair of vertical bores 596 and 598 therethrough. Vertical bore 596 has an oval cross section supports a cross pin 600 on the stem 602 of the shoulder stop 418. Operation of the shoulder stop 418 is identical to that of the shoulder stop 118 of the first embodiment 100, as shown in FIG. 15.

FIG. 33 is a perspective view of the shoulder stop 418. Note that the stem 600 is offset from the axial centerline through the shoulder stop 418. Referring now to FIG. 34, a partial upper view of the upper platform of the carriage 410 is shown. Each of the shoulder stop supports projects through and is flush with the top of the upper platform 574. The inboard bores 598 are circular in cross section. Thus, when the stems 600 of the shoulder stops 418 are placed in these bores 598 the shoulder stops 418 cannot rotate as was the case in the first embodiment 100 described above and shown with reference to FIG. 15. However, when one, or both, shoulder stops 418 are located in the outboard bores 596, they can be tilted toward the foot end 406 just as described with reference to FIG. 15 in the first embodiment 100.

In this embodiment of the reformer 400, not only does a user have an option of rotating the shoulder stops 418 when inserting them into the bores 596 to accommodate different shoulder widths, one or both shoulder stops 418 may be inserted in the inner bores 598 to provide further width adjustment. If both shoulder stops 418 are located in the inner bores 598, then no adjustment of the arm cords 414 can be made. This is called the lockout position. However, if either one or both shoulder stops 418 are placed in the outer bores 596, then adjustment of the arm cords 414 may be made with that shoulder stop in an outer bore 596.

A partial perspective view of the bottom of the carriage 410, removed from the reformer 400, is shown in FIG. 35. In this view the springs 420 are shown attached to the spring support plate 584. An exemplary arm cord 414 is shown threaded through the guide hole 590 and into the cord retraction mechanism 610.

A bottom plan view of a head end portion of the carriage 410 is shown in FIGS. 36 and 37. These two views illustrate the configuration and operation of the cord retraction mechanism 610 in accordance with this embodiment of the present disclosure. The arm cords 414 are not shown in this view for clarity. The cord retraction mechanism 610 includes, for each cord 414, a spring biased cord reel 612 that is mounted beneath the support plate 578 for rotation about a horizontal axis and is supported from the carriage frame side support plate 580. The cord reel 612 has a coil spring portion 614 and a cord support portion 616. One end of the cord 414 (not shown) is fastened to and wrapped around the cord support portion 616 of the reel 612. As is shown in FIGS. 35, 36 and 37, the two reels 612 of the cord retraction mechanism 610 are rotatably mounted side by side beneath the underside surface of the platform 578.

The coil spring portion 614 is bolted to or integral with the cord support portion 616 and preferably carries within it a coil spring (not shown) that provides a takeup preload tension on

the cord 414 when its end is fastened to the cord support portion 616 of the reel 612. The retraction assembly 610 also includes a unique spring loaded cord clamp assembly 618 fastened to the support platform 578 that is operably coupled to an actuator linkage 620, which is, in turn, actuated by either one of the shoulder stops 418 when installed in the appropriate bore 596.

The actuator linkage 620 is carried on an elongated flat plate 622 that is fastened to the support plate 578 via fasteners 624 and spans between the two side support plates 580 directly beneath the shoulder stops 418 and over the bores 596 and 598. Each end of the flat plate 622 has an elongated opening 626 aligned with a bore 596 and a circular opening 628 aligned with the bore 598. Pivotaly carried side by side on the linkage plate 622 are a pair of T shaped links 630. Each T shaped link 630 pivots in the plane of the support plate 578 about the center of the head 632 of the link 630 on a pin 634 fastening the link 630 to the plate 622. One end 636 of the head 632 of each of the links 630 is positioned to engage a stem 600 of the shoulder stop 418 inserted into bore 596. The other end 638 of the head 632 of the T shaped link 630 couples with a corresponding end 638 of the other link 630. The ends 638 of the two links 630 are preferably also coupled together by a coil spring 640. Each T shaped link 630 includes an elongated leg 642. The end of this elongated leg 642 resides adjacent one of the clamp assemblies 618.

The clamp assembly 618 comprises a pair of clamp members 650, the outer one of which is fixed to the support plate 578 by two fasteners 652 and 654. The inner clamp member 650 is rotatably fixed to the support plate 578 by a fastener 652 in a laterally spaced relation to the fixed member 650. Each clamp member has a cord grip portion 656 and an opposite elongated arm portion 658. The arm portion 658 of the inner clamp member 650 is positioned adjacent the leg 642 of the link 630. A coil spring 660 fastens the grip portion 656 of the inner clamp member 650 to the fixed outer clamp member 650 such that the grip portion of the inner clamp member 650 is biased toward the grip portion of the fixed outer clamp member. A flat plate 662 is optionally fastened over the clamp members 650 in each assembly 618 between the fastener 652 and the clamp member 650. Finally, a pair of cord guides 664 is preferably fastened to the support plate 578 and positioned between the link assembly 620 and the reel 612 such that the cord 414 must pass through the hole 590 in the head end plate 582, through a cord guide 664, between the clamp members 650, through another cord guide 664, to the cord retraction reel 612 as is shown in FIG. 35.

The retraction assembly 610 is shown in a cord locked condition in FIG. 36. In FIG. 37, the assembly 610 is shown in an unlocked condition wherein one of the shoulder stops 418, (the left one in FIG. 37) has been tilted toward the foot end of the reformer frame 402. In this view of FIG. 37, the stem 600 of the left shoulder stop 418 pushes up on the end 636 of the link 630. This movement causes the opposite end 638 of the link 630 to rotate downward clockwise. At the same time, the leg 642 must also rotate clockwise, rotating the arm portion 658 of the inner clamp member 650 counterclockwise. This action releases the arm cord 414 from the clamp members 650 and permits the tension in the left cord reel to be felt on the cord 414.

At the same time, the other link 630 is caused to rotate counterclockwise about its pin 632, which, in turn, causes its leg 642 to push against the arm portion 658 of the inner clamp member 650 of the other clamp assembly 618, thus rotating the inner clamp member 650 clockwise. This clockwise rotation of the inner clamp member 650 disengages the clamp member 650 from the other arm cord 414 such that the tension

in the right cord reel **612** pulls on the other cord **414**. It can readily be seen, therefore, that tilting either one of the shoulder stops **418** that is in an outside bore **596** will cause the same result, a release of both clamp assemblies **618** on both of the arm cords **414**, allowing a user to independently adjust the length of each cord.

Again, a retrofit arm cord retraction mechanism kit for a conventional reformer is also envisioned in accordance with the present disclosure for this alternative retraction system **610**. Such a kit would include two retraction reels **612** and mounting hardware, two clamp assemblies **618**, link assembly **630**, replacement shoulder stops **418**, two shoulder stop supports **594**, and appropriate installation instructions.

In the reformer carriage **410** in accordance with the present disclosure, an adjustable headrest may be integrated into the structure. A bottom view of the upholstered upper support platform **574** is shown in FIG. **32**. The rigid base of the upper support plate has two separate sections **672** and **674** spaced apart and joined by a hinge **676**. Each section **672** and **674** may be made of plastic, composite material or wood. The section **672** also has apertures **678** for receiving the shoulder stop supports **594** therethrough as above described. The sections **672** and **674** are spaced apart by about 1/4 inch so as to give clearance for bending the head end portion of the upholstered platform **574** as is shown with reference to the first embodiment in FIGS. **19-21**. However, in this reformer **400**, there is no cam block **364**. Instead, as shown in FIG. **32**, an elongated adjustment lever **680** is fastened to the underside of the head end section **674**. This lever **680** rotates about a fastener **682** secured to the underside of the head end section **674**. The lever **680** has one end **684** bent at 90 degrees from the plane of the platform **574**. This bent end **684** projects through a slot **686** in the support plate **578** as shown in FIG. **38**. The bent end **684** has a series of notches **688** for adjusting the height of the head end section **674**. The opposite end of the lever **680** may have a knob **690** fastened thereto for rotating the lever **680** out of and into engagement of the notches **688** with a corresponding flange of the head end support plate **582**.

The reformer **400** of this present disclosure may be configured so as to be easily stacked for stacked storage. Each of the feet **429** include recessed portions designed to fit onto the outer corner rim of an underlying reformer **400**. The bottom of each foot **429** that facilitates stacking of one apparatus on top of another has a recessed portion. Stacking is facilitated through engagement of the outer corners of the head end of the reformer and outer corners of the standing platform at the foot end of the reformer into the recessed portions in each foot as is shown in FIG. **39**. When two or more reformers **400** are so stacked they are securely held laterally in place by these feet **429**.

Furthermore, the risers **412** are removed from the head end **404** and fastened to one of the brackets **700** (see FIG. **31** and FIG. **40** below). Each of the shoulder stops **418** is removed and the stems **600** passed through the shoulder stop slot openings **592**, turned 90 degrees so that the pins **602** engage the head end support plate **582**.

An underside perspective view of the head end of the carriage **410** is shown in FIG. **40** showing the risers **412** and shoulder stops **418** spaced from these holding features. These holding features are slots **592** in the head end plate **582** and spring brackets **700**. The spring brackets **700** resiliently snap within the lower openings **564** to hold and retain the riser **412** in place without marring or otherwise damaging the exterior finish of the riser **412**.

When the risers **412** and shoulder stops **418** are mounted beneath the carriage **410** as shown in FIGS. **39** and **40**, the carriage **410** may be positioned fully at the head end of the

frame **402**, and an optional mat conversion pad **702** may be placed between the carriage **410** and the standing platform **423** to provide a fully flat mat surface. This mat conversion places the carriage **410** in a stationary position at the head end **404**, and presents to the user a full flat surface.

The reformer **400** may optionally also be configured with a trapeze tower assembly **800** as is shown in FIG. **41**. The tower assembly **800** basically comprises a U shaped tower **802**, a trapeze swing **804**, and a pair of tower sockets **806**. The tower sockets **806** are fastened between the rail members **408** and the head end extrusion **500** of the head end **404** and become an integral part of the frame **402**. The bottom ends of the tower **802** fit within the sockets **806** and are drawn into the sockets **806** as is shown in more detail in FIG. **43**.

The tower **802** is preferably a tubular metal body such as aluminum or steel and may either be bent to the shape as shown in FIG. **41**, or may be formed from straight sections joined by conventional 90 degree elbows. The tower **802** has a plurality of spaced eyebolts **808** for attaching springs, straps, or pulleys **810** as may be needed for particular exercises. Alternatively the vertical legs of the tower **802** may have a vertical slot and adjustable clamp fittings provided therein for anchoring the springs, pulleys **810**, or eyebolts **808** thereto.

In addition, the risers **412** may be utilized or replaced with a U shaped connector assembly **818** so that a pulley **810** may be fastened thereto. This U shaped connector assembly **818** fits within the boss **506** in the head end extrusion **500**, and is bolted in place as shown in FIG. **44**, or alternatively may be configured to be fastened with the same hand bolt **413** as is used to secure the riser **412** in place as is shown in FIG. **28**. When the connector assembly **818** is utilized in place of the riser **412**, then a second pulley **810** (not shown) could be fastened to the assembly **818** and used as a lower arm cord guide directing the arm cord from the carriage **410** to the lower pulley and through the upper pulley **810** to the hand loop as in the embodiments **100** and **400** shown in FIGS. **1** and **22**.

A tower socket **806** is shown mounted on the head end of one of the side rail members **408** in FIG. **42**. The tower socket **806** is a metal extrusion, preferably aluminum, that has a tube portion **820** and an axially extending radial flange portion **822**. The flange portion **822** has a thickened edge **824** and a plate portion **826** that is identically shaped to fit against end plate **407** of the head end extrusion **500** and against the end of the side rail member **408**. Locating pins **409** orient the flange portion **822** with respect to the rail member **408** and the end plate **407**, and nuts (not shown) are used on bolts **828** to fasten the head end **404** and the socket **806** securely to the side rail member **408**.

FIG. **43** is a cutaway view of an assembled tower **802** fastened in a socket **806**. In a fashion similar to that described above with reference to risers **412** being fastened into the bosses **506**, the bottom end of the tower **802** is fitted with a threaded expansion plug **830**. A hand bolt **832** extending into the bottom of the tube portion **820** threads into the plug **830**. When tightened, the expansion plug **830** draws the bottom end of the tower **802** down tightly into the socket **806** to complete the assembly of the tower **800** to the frame **402**.

Alternatively, the bottom ends **850** of a tower **820** may be narrowed and shaped so as to telescopically fit within the bosses **506** in the head end extrusion **500** as is shown in the perspective view of this alternative in FIG. **45**. This construction would preclude the need for tower sockets **806**. In such an alternative, shown in FIG. **45**, a hand bolt **832** would be again used to draw the bottom ends **850** of the tower **820** tightly into the bosses **506** just as the risers **412** would be fastened into the

bosses **506** above described. In such an alternative configuration, of course, the risers **412** are not used. Instead, the arm cords **414** would each be attached to a pulley **810**.

Turning now to FIG. **46**, an exemplary handle end portion **880** of an arm cord **114, 414** is shown attached to a hand strap **900**. End portion **880** is turned back on itself to form a flexible eye **882**. The free end **884** of the end portion **880** is sewn or otherwise permanently secured to the end portion **880** to form the eye **882**. This eye **882** replaces the need for a conventional metal or plastic snap clip for connection to a conventional hand grip.

The hand strap **900** has a looped strap portion **902** sewn to ends of a short length of arm cord material to form a flexible cord ring **904** attached to the strap portion **902**. The flexible cord ring **904** is attached to the eye **882** by passing the ring **904** over the eye **882** and then threading the strap portion **902** through the ring **904**. The result is the hand strap **900** fastened to the arm cord **114, 414** essentially in a square not configuration as is shown in FIG. **46**. The arm cords **114, 414** with hand strap **900** attached in this manner can be utilized with any conventional reformer or other exercise apparatus utilizing arm/foot cords as well as with the reformer **100, 400** of the present disclosure.

A hand grip **910** is shown in FIG. **47** that has a tubular handle **912**. This grip **910** may be utilized in place of hand strap **900**. Again, the hand grip **910** preferably has a flexible cord ring **904** as described above to fasten the hand grip **910** to the end portion **880**. Alternatively, a standard hand grip may be used that includes a metal D ring fastened to the hand grip **910** in place of the cord ring **904**.

The reformer **100** or **400** may be configured with a jump board **950** as is shown in FIG. **48**. This jump board **950** is a generally rectangular plate structure with two parallel posts **952** that fit down into the inserts **510** in the bosses **506** in the foot end **106, 406**. These posts **952** each have a rectangular or square cross sectional shape as is shown in the sectional partial view of FIG. **49**.

Each post **952** includes a pair of spaced leaf springs **954** that bias the post **952** counterclockwise in the insert **510** so that there is a preload on the jump board **950** effectively away from the carriage **110, 410**. This preload prevents rattle and rotational movement of the jump board in response to a user's applied force on the jump board during an exercise. This configuration presents a firm, solid feel to the user of the jump board as it is installed and used.

In FIG. **48**, note that the foot bar **411** is shown positioned adjacent the head end **404** of the frame **402**. Furthermore the foot bar **411** support assemblies **470** are shown in the free rotational position in which pins **461** are engaged in slots **484** as described with reference to FIGS. **29** and **30**. When the foot bar **411** is thus positioned to be movable between the head and foot ends **404** and **406** of the frame **402**, an elastic resistance member **956** may be fastened to the connection portions **154** of the leg portions **156** of foot bar **411** and stretched around the head end **404** of the frame **402** as is shown in FIG. **48**. With the foot bar **411** configured in this manner, a user can sit or lay on the carriage **410**, grasp the leg portions **156** of the foot bar **411** and pull the foot bar **411** toward the carriage **410** against the resistance provided by resistance member **956**.

Alternatively, the user can rotate the foot bar **411** to the vertical position, lower the foot bar **411** to engage pins **461** in notches **482**, which locks each support assembly **470** in place on the rail members **408**. Then the user can pull the carriage **410** toward the head end **404** with his or her arms. It is to be understood that the resistance member **956** may be two separate members each separately connected to the head end **404**, or may be a single resistance member as is illustrated in FIG.

48. Furthermore, the above description applies equally well to the first embodiment, reformer apparatus **100** described above with reference to FIGS. **1-21**.

These are only exemplary embodiments and variations. A reformer exercise apparatus in accordance with the present disclosure may incorporate one or more or any of the features described herein. Other modifications will be readily apparent to one skilled in the art. For a simple example, any of the coil springs shown in the drawing figures may be replaced by stretchable elastic members and vice versa. For another, the holding features for accommodating the risers **412** and shoulder stops in storage positions beneath the upper surface of the reformer carriage **410** may differ from clips **700** and slots **592**. The risers **412** may fit within corresponding openings (not shown) in plate **582** or on pins projecting from plate **582**. The reformers **100, 400** may be configured with short legs as shown in FIG. **48**, or longer legs as shown in at least FIGS. **1** and **22**. Accordingly, all such alternatives, variations and modifications are intended to be encompassed within the scope of and as defined by the following claims.

What is claimed is:

1. A reformer exercise apparatus comprising:

- a generally rectangular frame having a pair of parallel spaced side rail portions, a head end portion, and a foot end portion, wherein each of the side rail portions has an outer surface inverted generally U shape in transverse cross section, formed by an upright outer wall beginning at an outer bottom edge, extending substantially upright to an integral top wall merging into an inwardly and downwardly sloping inner wall and ending at an inner bottom edge spaced from the outer bottom edge;
- a movable carriage supported by the side rail portions for movement of the carriage between the head and foot end portions;
- a bias member connected between the carriage and the foot end portion of the frame for biasing the carriage toward the foot end of the frame; and
- a foot support member supported by the side rail portions of the frame.

2. The apparatus according to claim **1** wherein each side rail portion has a downwardly extending mid wall between the outer wall and the inner wall supporting the foot support member.

3. In a reformer exercise apparatus having a generally rectangular frame supporting a carriage for movement between a head end and a foot end of the frame on parallel spaced side rail portions of the frame, and a foot bar supported by the frame, wherein the side rail portions of the frame each has an outer surface inverted generally U shape in transverse cross section, formed by an upright outer wall beginning at an outer bottom edge, extending substantially upright to an integral top wall merging into an inwardly and downwardly extending inner wall ending at an inner bottom edge spaced from the outer bottom edge, and wherein the top wall supports a mid wall extending downward from the top wall, the mid wall having an open slot therein, a foot bar support assembly movably carried by each of the open slots for supporting one end of the foot bar, each foot bar support assembly comprising:

- an elongated slide plate movably supported within the slot;
- a hook plate fastened to the slide plate; and
- a foot bar support arm having one end fastened to the one foot bar end and a portion rotatably and slidably fastened to the hook plate.

4. The support assembly according to claim **3** wherein the slide plate is an elongated member having opposite ends, each end carrying a roller for riding on a bottom surface of the slot.

27

5. The support assembly according to claim 3 wherein the slide plate has at least one roller for riding against an upright surface of the mid wall within the slot.

6. The support assembly according to claim 3 wherein the one end is a bottom end portion of the foot bar support arm.

7. The support assembly according to claim 3 wherein the foot bar support arm has an upper end including an engaging member for selectively engaging a discrete feature of the hook plate.

8. The support assembly according to claim 3 wherein the hook plate has an upper edge, the upper edge having a plurality of discrete features at spaced locations for selectively engaging a portion of the foot bar support arm.

9. The support assembly according to claim 8 wherein the discrete feature is a notch.

10. The support assembly according to claim 9 wherein the hook plate has an L shaped slot for receiving the engaging member.

11. A reformer exercise apparatus comprising:

a generally rectangular frame supporting a carriage for movement between a head end and a foot end of the frame on parallel spaced side rail portions of the frame, wherein the side rail portions of the frame each has an outer surface inverted generally U shape in transverse cross section, formed by an upright outer wall beginning at an outer bottom edge, extending substantially upright to an integral top wall merging into an inwardly and downwardly extending inner wall ending at an inner bottom edge spaced from the outer bottom edge, and a mid wall extending downward from the top wall, the mid wall having an open slot therein;

a foot bar supported by the side rail portions of the frame; and

a foot bar support assembly movably carried by each of the open slots for supporting an end of the foot bar, each foot bar support assembly comprising:

an elongated slide plate movably supported within the slot;

a hook plate fastened to the slide plate; and

a foot bar support arm having one end fastened to one foot bar end and a portion rotatably and slidably fastened to the hook plate.

12. The reformer according to claim 11 wherein the slide plate is an elongated member having opposite ends, each end carrying a roller for riding on a bottom surface of the slot.

13. The reformer according to claim 11 wherein the slide plate has at least one roller for riding against an upright surface within the slot.

28

14. The reformer according to claim 11 wherein the one end is a bottom end portion of the foot bar support arm.

15. The reformer according to claim 11 wherein the foot bar support arm has an upper end including an engaging member for selectively engaging a discrete feature of the hook plate.

16. The apparatus according to claim 11 further comprising one or more bias members attached between the carriage and the foot end of the frame for urging the carriage toward the foot end of the frame.

17. The apparatus according to claim 16 further comprising one or more hourglass spool shaped pins secured to the foot end of the frame for receiving a free end of one of the bias members to attach that bias member to the foot end.

18. The apparatus according to claim 17, wherein each pin has a central axis and tapers upward and inward from its base to a waist at a first angle from the pin's central axis and then outward at a second angle greater than the first angle so that the free end of the spring placed on the pin is securely held at the waist of the pin.

19. The apparatus according to claim 11 further comprising an elastic resistance member biasing the foot bar support assembly toward one of the head and foot ends of the frame.

20. A reformer exercise apparatus comprising:

a generally rectangular frame supporting a carriage for movement between a head end and a foot end of the frame on parallel spaced side rail portions of the frame, wherein the side rail portions of the frame each has an outer surface inverted generally U shape in transverse cross section formed by an upright outer wall beginning at an outer bottom edge, extending substantially upright to an integral top wall merging into an inwardly and downwardly slopped inner wall and ending at an inner bottom edge spaced from the outer bottom edge, and a vertical mid wall having an open horizontal slot therein; an elongated foot bar extending over both side rail portions; and

a foot bar support assembly movably carried by each of the open slots each for supporting an end of the foot bar, each foot bar support assembly comprising:

an elongated vertical slide plate spaced from the slot and movably supported from within the slot;

a hook plate extending parallel to and fastened to the slide plate; and

a foot bar support arm having one end fastened to one foot bar end and a portion rotatably and slidably fastened to the hook plate.

* * * * *