



US008917262B2

(12) **United States Patent**
Liaw et al.

(10) **Patent No.:** **US 8,917,262 B2**
(45) **Date of Patent:** **Dec. 23, 2014**

(54) **STYLUS AND TOUCH INPUT SYSTEM**

(56) **References Cited**

(75) Inventors: **Shen-Tai Liaw**, Hsinchu (TW); **Nae-Jye Hwang**, Hsinchu (TW); **Feng-Sheng Lin**, Hsinchu (TW); **Chih-Ming Yuan**, Hsinchu (TW)

U.S. PATENT DOCUMENTS

4,111,052 A	9/1978	Sniderman
5,565,632 A	10/1996	Ogawa
5,581,052 A	12/1996	Padula et al.
5,633,471 A	5/1997	Fukushima
6,262,684 B1	7/2001	Stewart et al.

(73) Assignee: **Integrated Digital Technologies, Inc.**, Hsinchu (TW)

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 74 days.

FOREIGN PATENT DOCUMENTS

CN	1145002	3/1997
CN	2785036	5/2006

(21) Appl. No.: **12/984,613**

(Continued)

(22) Filed: **Jan. 5, 2011**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

“Office Action of Taiwan counterpart application” issued on Nov. 1, 2012, p. 1-p. 5.

US 2011/0169775 A1 Jul. 14, 2011

(Continued)

Related U.S. Application Data

(60) Provisional application No. 61/293,209, filed on Jan. 8, 2010.

Primary Examiner — Allison Johnson

Assistant Examiner — Vinh Lam

(74) *Attorney, Agent, or Firm* — Jianq Chyun IP Office

(51) **Int. Cl.**

G06F 3/033	(2013.01)
G06F 3/041	(2006.01)
G06F 3/0354	(2013.01)
G06F 3/038	(2013.01)

(57) **ABSTRACT**

A touch input system including a stylus and a display device is provided. The stylus includes a battery module, a touch portion, a transducer module and a RF transmitting module. When a contact pressure is acted on the touch portion, the touch portion is electrically connected to the battery module by the contact pressure and emits a light signal. The display region receives and reacts to the light signal, and the contact pressure is transformed into an electrical signal by the transducer module. The RF transmitting module is electrically connected to the transducer module and transmitting the electrical signal. The display device includes a display region and a RF receiving module.

(52) **U.S. Cl.**

CPC **G06F 3/041** (2013.01); **G06F 3/03545** (2013.01); **G06F 3/0386** (2013.01); **G06F 3/033** (2013.01)

USPC **345/179**; 178/19.01; 178/19.05


(58) **Field of Classification Search**

CPC ... G06F 3/03545; G06F 3/041; G06F 3/0386; G06F 3/033

USPC 345/173–184; 178/18.01–20.01

See application file for complete search history.

6 Claims, 11 Drawing Sheets



(56)

References Cited

FOREIGN PATENT DOCUMENTS

U.S. PATENT DOCUMENTS

6,441,362	B1	8/2002	Ogawa	
7,348,968	B2	3/2008	Dawson	
2003/0132923	A1	7/2003	Hu	
2005/0116940	A1 *	6/2005	Dawson	345/179
2007/0040817	A1	2/2007	Underwood et al.	
2007/0080282	A1	4/2007	Fann	
2007/0080956	A1	4/2007	Fann	
2007/0165007	A1 *	7/2007	Morrison et al.	345/175
2008/0087796	A1	4/2008	Fann	
2008/0278462	A1 *	11/2008	Chang	345/179
2009/0114459	A1	5/2009	Fukushima et al.	
2009/0167728	A1 *	7/2009	Geaghan et al.	345/179
2010/0001962	A1 *	1/2010	Doray et al.	345/173
2010/0020044	A1 *	1/2010	Abileah et al.	345/175
2011/0007001	A1 *	1/2011	Liu	345/173
2011/0043492	A1 *	2/2011	Elsasser et al.	345/179
2012/0019488	A1 *	1/2012	McCarthy	345/179

CN	101020400	8/2007	
CN	101032907	9/2007	
CN	101289038	10/2008	
CN	101510131	8/2009	
JP	2004-302768	10/2004	
JP	2005-196746	* 7/2005 G06F 3/03
JP	2005-202940	7/2005	
JP	2005-267376	9/2005	
TW	588835	5/2004	
TW	I276986	3/2007	
TW	M320123	10/2007	
TW	I291643	12/2007	
TW	200809635	2/2008	
TW	200846994	12/2008	

OTHER PUBLICATIONS

“Office Action of Japan counterpart application” issued on Jan. 8, 2013, p. 1-p. 4.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

STYLUS AND TOUCH INPUT SYSTEM**CROSS-REFERENCE TO RELATED APPLICATION**

This application claims the priority benefit of U.S.A. provisional application Ser. No. 61/293,209, filed on Jan. 8, 2010. The entirety the above-mentioned patent application is hereby incorporated by reference herein and made a part of specification.

BACKGROUND OF THE INVENTION**1. Field of the Invention**

The present invention generally relates to a touch input system. More particularly, the present invention relates to an input device suitable for emitting light and a touch screen using the input device.

2. Description of Related Art

Display panels traditionally serve the role of displaying the information or the output from a system, while other input device or devices provide inputs to the system. Interactive devices, such as a touch panel that can receive a user's input via touching the display panel, combines both output and input functions and allow a user to interact with the display or the system coupled to the display. As an example, devices such as personal digital assistants (PDAs), mobile phones, personal computers (PCs), tablet PCs, etc. have incorporated touch panels for providing users with more input choices.

Conventional touch panels or touch screens have a number of different designs, such as resistive type, surface-wave type, capacitive type, and infrared-ray type designs. All of these designs typically require combining a display device with a separate touch panel sheet. No matter what type of touch panel, it tries to provide a more convenient way for users, for example, the resistive type, surface-wave type, capacitive type, and infrared-ray type touch panel are operated by users' fingers or stylus. The in-cell type optical touch display panels could be operated by light or shadow, and the touch position is located by photo sensors designed in the in-cell type display panel. Therefore, touch display panel includes a display panel suitable for sensing a light signal emitted or blocked by a stylus to be operated. When a optical pen used as a positional indicator of the in-cell type optical touch display panel, the display panel is capable of displaying a line according to the light signal emitted by the stylus. Several arrangements have been proposed for an optical pen which has a pressure sensitive mechanism, and allowed to produce a certain change when the pen pressure was applied thereto.

SUMMARY OF THE INVENTION

The present invention is to provide a touch input system, including a input device and a display device.

The present invention is to provide a stylus suitable for sensing the depressing force by its pressure sensitive mechanism disposed in the tip of the stylus. The stylus includes a main body and a touch portion, wherein the main body comprises a pressure sensing mechanism, a transducer module, an RF transmitting module, and a battery module. The touch portion is disposed at the front of the main body, and is suitable for contacting with the operation surface.

As embodied and broadly described herein, the present invention provides a touch input system including an optical stylus and a display device for locating the touch position by the optical stylus. The stylus includes a main body and a touch portion capable of emitting light, wherein the main body

comprises a transducer module, a RF transmitting module, and a battery module. The touch portion disposed at the front end of the stylus is electrically connected to the battery module by the contact pressure and emits a light signal continuously when a contact pressure is acted on the touch portion. The display device includes a display region, and a RF receiving module essentially consisted of a RF receiver and a built-in antenna. The RF receiver is electrically connected to the display region and the built-in antenna receives the electrical signal within a predetermined frequency range.

Some example of the present invention may provide a stylus including a housing and a touch portion. The housing has a front end, a back end opposite to the front end and an opening foamed at the front end. The touch portion is sliding disposed at the opening along an axis, wherein the touch portion is suitable for contacting an operation surface to move into the housing. The housing has a capacity of a battery module and a detector; in some cases, it further comprises a transducer module and a RF transmitting module. A blocking plate is disposed in the middle of the housing of the stylus, and is disposed between the battery module and an elastic element. The detector is fixed to the blocking plate and used for detecting a motion of the touch portion to obtain an analog signal. The elastic element and the touch portion is located on the axis of the housing, wherein the elastic element is fixed on the blocking plate and the touch portion is sliding disposed at the opening, such that the touch portion contacts the operation surface to move into the housing, the elastic element is compressed between the blocking plate and the touch portion. The touch portion is electrically connected to the battery module and emits a light signal continuously while writing. However, the touch portion is recovered by an elastic force of the elastic element when the touch portion is distant from the operation surface. Meanwhile, the electrical connection between the touch portion and the battery module is terminated.

Another example of the present invention may provide a stylus including a pipe, a touch portion, a first magnetic element and a second magnetic element. The pipe has a front end, a back end opposite to the front end and an opening formed at the front end, wherein a diameter of the opening is smaller than a diameter of the pipe. The touch portion is sliding disposed at the opening, and at least a part of the touch portion is located in the pipe. The first magnetic element is disposed in the pipe and having a through hole, and a diameter of the through hole is not less than the diameter of the opening. Therefore, the second magnetic element is fixed to the touch portion located in the pipe, and the first magnetic element is located between the second magnetic element and the opening. The second magnetic element is driven to move away from the first magnetic element when the touch portion is driven to move toward the back end by a force resisting a magnetic attractive force generated between the first magnetic element and the second magnetic element.

Another example of the present invention may provide an input device including a pipe, a touch portion, a protrusion and a switch element. The pipe has a front end, a back end opposite to the front end and an opening formed at the front end, wherein a diameter of the opening is smaller than a diameter of the pipe. The touch portion is sliding disposed at the opening, and a part of the touch portion is located in the pipe. The protrusion, the switch element and the touch portion are on the central axis of the stylus. The switch element is fixed and electrically connected to the touch portion and has an elastic element to provide an elastic force for recovery. When the touch portion is driven to move toward the back end by a depressing force, the switch element is also driven to contact the protrusion for actuating the touch portion to emit

a light signal continuously, and the elastic element is compressed between the touch portion and the protrusion.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings are included to provide a further understanding of the invention, and are incorporated in and constitute a part of this specification. The drawings illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention.

FIG. 1 illustrates a touch input system according to an embodiment of the present application.

FIG. 2 partially illustrates a stylus during exerting according to an embodiment of FIG. 1.

FIG. 3 illustrates a touch input system according to another embodiment of the present application.

FIG. 4 partially illustrates a tip of the stylus leaves the operation surface.

FIG. 5 illustrates a stylus according to further another embodiment of the present application.

FIG. 6 illustrates the touch portion contacts the operation surface of FIG. 5.

FIG. 7 partially illustrates a stylus according to further another embodiment of the present application.

FIG. 8 illustrates a touch input system according to further another embodiment of the present application.

FIG. 9 illustrates the touch portion contacts the operation surface of FIG. 8.

FIG. 10 illustrates a light emitting glove according to an embodiment of the present application.

FIG. 11 illustrates a finger portion of the light emitting glove of FIG. 10.

FIG. 12 illustrates an operating manner of the light emitting glove of FIG. 10.

DESCRIPTION OF THE EMBODIMENTS

Reference will now be made in detail to the present embodiments of the invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers are used in the drawings and the description to refer to the same or like parts.

FIG. 1 illustrates a touch input system according to an embodiment of the present application. FIG. 2 illustrates the touch portion contacts the display region of FIG. 1. Referring to FIG. 1, the touch input system 100 includes a stylus 110 and a display device 120. The stylus 110 has a two-terminal main body 112 including a front end 112a and a back end 112b, wherein the front end 112a is separated by a blocking plate 115. The main body 112 comprises a transducer module 118 and an RF transmitting module 119, and a battery module 114. The blocking plate 115 is disposed between the battery module 114 and an elastic conductor 117. The front end 112a has an opening 112c at the pen tip, and the touch portion 116 is slidingly disposed in the opening 112c along an axis A. The touch portion 116 may have a pillar 116a to extend into the front end 112a, and the pillar 116a, the elastic conductor and the touch portion 116 are all on the axis A. The axis A is perpendicular to the blocking plate 115 and pass through the center of the stylus 110. An elastic conductor 117, such as a metal spring or a conducting sponge, is directly connected to the touch portion 116 or via pillar 116a, depending on the function of the stylus. Whether the elastic conductor 117 is fixed to the pillar 116a or the blocking plate 115, the pillar 116a is disposed between the touch portion 116 and the elastic conductor 117, and they all move along the axis A. Taking FIG. 1 for example, the three elements on the axis A,

including the touch portion 116, the pillar 116a and the elastic conductor 117, can be regarded as a switch for lighting up the touch portion 116. The touch portion 116 can be a light emitting diode (LED), a light bulb, a laser, and so on. The transducer module is used for transforming the contact pressure into an electrical signal by the transducer module, and the electrical signal is directly proportional to the contact pressure depressed by a user. The RF transmitting module is electrically connected to the transducer module, and sending the electrical signal to a RF receiving module embedded in the display device. The RF transmitting module is essentially consisted of a RF transmitter and an antenna for transmitting depressing pressure information.

Referring to a display device 120, it includes a display region 122 with an operation surface of the display device 120 and an RF receiving module 124. The display device 120 further includes a light sensor array 126 arranged in a pixel electrode array of the display region 122. Examples of the light sensor array may be found in but are not limited to commonly assigned applications, i.e., U.S. patent application Ser. No. 11/536,403, "Interactive Display Devices and Methods of Making the Same," filed Sep. 28, 2006, and U.S. patent application Ser. No. 11/777,887, "Photo Detector Array with Thin-Film Resistor-Capacitor Network," filed Jul. 13, 2007, which is a continuation-in-part of U.S. patent application Ser. No. 11/534,680, "Photo Detector Array," filed Sep. 25, 2006. Other sensor elements capable of supporting a touch panel based on a pressure source or a non-touch panel based on an optical source may also be applicable to the present invention. In one example, the display device 120 may include but is not limited to one of a photo-sensing panel, an organic light-emitting diode (OLED) panel and a low temperature poly silicon (LTPS) panel. Accordingly, the display region of the display device 120 not only receives the light signal emitted by the optical stylus, but also reacts to the depressing pressure exerted onto the display region. The RF receiving module 124 embedded in the display device 120 is essentially consisted of a receiving antenna and a RF receiver.

FIG. 2 partially illustrates a stylus during exerting against the display device according to an embodiment of FIG. 1. The light detector 113a is suitable for detecting a light 60 emitted by the light emitting element 113b to obtain a variation of a distance between the light emitting element 113b and the light detector 113a, wherein the above-mentioned distance is shortened while the contact pressure acted on the touch portion 116 is increased. The light detector 113a is, for example, a photo transistor, a photo diode or a photo-sensitive resistor. The light emitting element 113b preferably provides a wavelength that the light detector 113a is sensitive to. The light 60 is detected by the light sensor array 126 for locating touch position, and simultaneously provided information for pressure strength operated by the user. One skilled in the art will appreciate that the light 60 is not restricted to a visible light, other electromagnetic wave, such as infrared light, ultraviolet light or other radiation, can be sensed by the light detector 113a and the light sensor array 126 are favorable options. Referring to FIG. 1 and FIG. 2, the touch portion 116 is exerted on the working plane, such as display device 120, when a user is writing by the stylus 110. The elastic conductor 117 would be compressed and electrically contact with the battery module 114, such that the touch portion 116 emits the light 60. The light sensor array 126 embedded in the display device 120 is capable of locating the touch position by sensing the light 60, but the line width depicted by a user can not be shown. The detector 113a is connected with the transducer module 118, and electrically connected with the battery module 114. The detector 113a receives differential light amount

in accordance with distance between the touch portion 116 and the detector 113a when the user is operating the stylus 110. The distance between the touch portion 116 and the detector 113a is inverse proportional to the depressing force from the user, and the light sensed by the detector 113a will be converted to an analog signal. The analog signal can be transmitted to the transducer 118, and converted to a digital signal.

FIG. 3 is a schematic view illustrating another embodiment of the present application. The main body 312 is, for example, a housing having a front end 312a, a back end 312b opposite to the front end 312a and an opening 312c formed at the front end 312a, wherein the touch portion 316 is sliding disposed at the opening 312c along an axis A. The battery module 314 is disposed in the main body 312, and separated from the front end 312a via the blocking plate 315. The elastic conductor 317 is, for example, a spring and connected to the touch portion 316 to be located between the touch portion 316 and the blocking plate 315 along the axis A. When the touch portion 316 is pushed toward the back end 312b when exerting the stylus 310 by a user, the elastic conductor 317 is compressed between the blocking plate 315 and the touch portion 316. Thus, when no depressing force is applied on the stylus (as FIG. 4 showing), the touch portion 322 is recovered by an elastic force of the elastic conductor 317. In other embodiments, the elastic conductor 317 also could be an elastic metal slice or a magnet with a conductive formed plastic. Referring back to FIG. 3, the touch portion 316 is sliding disposed at the main body 312, when the touch portion 316 is applied to the display region 322 to generate a force on the touch portion 316. Then, the touch portion 316 will be driven to move toward the blocking plate 315 and compress the elastic conductor 317. The touch portion 316 is electrically connected to the battery by the elastic conductor 317 and the conductive pillar 316a and emits a light 50 continuously. Simultaneously, the magnitude of the force will be sensed by the pressure sensitive module consisted of detector 313a and emitting element 313b.

In this embodiment, the light 50 irradiated from the touch portion 316 is used for the light sensor array 326 embedded in the display device 320, not for detector 313a. The detector 313a fixed to a surface facing the touch portion 316 of the blocking plate 315 is responsive to the intensity of the light 70 while operating the stylus 310. The emitting element 313b emitting the light 70 is fixed to a pillar 316a of the touch portion 316. The detector 313a is used for detecting a light 70 emitted by the light emitting element 313b to obtain a variation of a distance between the light emitting element 313b and the light detector 313a. The distance is shortened while the force acted on the touch portion 316 is increased, and the light detector 313a is capable of transferring analog signals with the magnitude of the force accordingly. Therefore, the detector 313a and the emitting element 313b are regarded as a pressure sensitive module, responsive to the force exerted by the user while operating the stylus 310. The light 70 is only sensed by the detector 313a of the pressure sensitive module, because the irradiating direction of the light 70 is opposite to the one of light 50. The type of the detector 313a and emitting element 313b are not restricted, for example, the emitting element 313b can be an electromagnetic wave emitting element, such as LED, bulb, or laser, even other element emitting any invisible radiation, and the detector 313a must be a sensor capable of sensing the signal from the emitting element 313b, such as, a photo transistor, a photo diode, a photo-sensitive resistor and so on.

In another embodiment, the emitting element 313b is a magnetic element, the detector 313a is capable of detecting magnetic prosperity. In other words, the pressure sensitive

module includes a magnetic element 313b and a magnetic detector 313a. The magnetic element 313b is fixed to the touch portion 316. The magnetic detector 313a is fixed to the blocking plate 315 and suitable for detecting a magnetic force generated between the magnetic detector 313a and the magnetic element 313b to obtain a variation of a distance between the magnetic element 313b and the magnetic detector 313a. The magnetic element 313b is, for example, a magnet or any object suitable for generating magnetic force and the detector 313a must be a sensor capable of sensing the signal from the magnetic element 313b.

The transducer module 318 disposed in the main body 312 is used to processing the signal from pressure sensitive module including detector 313a and emitting element 313b, and transforming the analog signal 70 into a digital format, wherein the intensity of the signal 70 is directly proportional to the magnitude of the force exerted by a user. The RF transmitting module 319 may be disposed at the back end 312b of the main body, or at the wall of the main body 312 and electrically connected to the transducer module 318. In one embodiment, the RF transmitting module 319 is used for transmitting digital signals within a predetermined frequency range, and the RF receiving module 324 disposed in the display device 320 is capable for receiving signals with the same specific frequency, such that other signal out of the specific frequency range regarded as an interference is prevented.

According to the present invention, the stylus is able to transmit an electrical signal directly proportional to a contact pressure applied to the touch portion of the stylus, and the display device is able to receive the electrical signal to display image according to its information. For example, a width of the line showed by the display device is able to be promptly changed by respective electrical signals transmitted from the stylus, such that the operation of the touch input system is more flexible. Therefore, in addition to the location touched by the stylus 310, the display region 322 shows line width responsive to the magnitude of the signal 70 while writing. The touch portion 316 is exerted on the display region 322 to generate the signals representing line width on the display region 322 by the wireless communication. The RF receiving module 324 is electrically connected to the display region 322 and receives the digital signal from the RF transmitting module 319 within a predetermined frequency range. The display region 322 is suitable for displaying a line width depicted by the user according to the signal 70 sensed by the detector 313a. In other words, the location and the width of the line are both displayed on the display device 320, the line width is changed by signals 70 and the line location is based on signal 50, such that the operation of the touch input system 300 is more flexible.

FIG. 5 illustrates a stylus according to further another embodiment of the present application. FIG. 6 illustrates the touch portion contacts the operation surface of FIG. 5. Referring to FIG. 5 and FIG. 6, the stylus 410 includes a pipe 412, a touch portion 414, a first magnetic element (a fixed magnetic element) 416 and a second magnetic element (a moveable magnetic element) 418. The pipe 412 has a front end 412a, a back end 412b opposite to the front end 412a and an opening 412c formed at the front end 412a, wherein the diameter of the opening 412c is smaller than the diameter of the pipe 412. The touch portion 414 is sliding disposed at the opening 412c, wherein at least a part of the touch portion 414 is located in the pipe 412.

The first magnetic element 416 fixed to the inner wall of the pipe 412 and has an annular shape, in which the diameter of the through hole 416a is larger or substantially equal to the

diameter of the opening **412c**, such that the touch portion **414** sliding disposed at the opening **412c** can penetrate the through hole **416a**. The second magnetic element **418** and the touch portion **414** are bonded together, and regarded as a signal portion. When the depressing force is applied on the stylus, the touch portion **414** and the second magnetic element **418** may move together. Due to the size of the second magnetic element **418** is larger than the through hole **416a**, the second magnetic element **418** is always between the conductive element **411** and the first magnetic element **416** whether the exertion force is applied or not. As shown by this example, the first magnetic element **416** is located between the second magnetic element **418** and the opening **412c**. The exertion force is able to resist a magnetic attractive force generated between the first magnetic element **416** and the second magnetic element **418**, at the same time, the second magnetic element **418** is driven to move away from the first magnetic element **416** (as FIG. 6 shown).

The stylus **410** further includes a battery module **415**, a detector **417** and a converter **419**. The battery module **415** is disposed in the pipe **412** and includes a blocking plate **415a** and at least a battery **415b** (showing two). The touch portion **414** is electrically connected to the battery module **415** and emits a light signal **40** actuating the operation surface **80**. The detector **417** is suitable for detecting a magnetic force produced from the second magnetic element **418** to obtain an analog signal representing a variation of a distance between the second magnetic element **418** and the detector **417**, and the above-mentioned distance is shortened while the contact pressure acted on the touch portion **414** is increased. The converter **419** disposed in the pipe **412** is electrically connected to the detector **417**, and capable of transducing the analog signal into a digital signal and outputting the digital signal to the RF transmitting module **413**. The RF transmitting module is essentially consisted of a RF transmitter and a transmitting antenna, and is suitable for transmitting the digital signal to the RF receiving module **90** by the wireless communication. In this embodiment, a conductive element **411** is disposed on the blocking plate **415a**, and located between the blocking plate **415a** and the touch portion **414**. The conductive element **411**, for example, a conductive sponge, would be compressed and electrically contact with the battery module **415**. When the exertion force is stronger than the magnetic attractive force between the first and the second magnetic element (**416** and **418**), the touch portion **414** is electrically connected to the battery via the conductive element **411** and emits light **40**. The magnetic attractive force is used for driving the touch portion **414** to recover from the state shown in FIG. 6 to the state shown in FIG. 5.

In another embodiment, the conductive element **411** is not compressive, is just regarded as switch. A force exerted by a user is stronger than the magnetic attractive force of the two magnetic elements when writing, the touch portion **414** is electrically connected to the battery via the conductive element **411** and emits the light **40**. Once the stylus is not been exerted, the conductive element **411** and the touch portion **414** will be separated by the magnetic attractive force of the two magnetic elements. The touch portion **414** may contact the operation surface **80** and emit light while the contact pressure being stronger than the magnetic attractive force of the two magnetic elements. In addition, the third magnetic element could be added to enhance the separation strength of the conductive element and the touch portion, the description detailed in FIG. 7. FIG. 7 partially illustrates a stylus according to further another embodiment of the present application. Comparing with the stylus **410** of FIG. 5, the stylus **510** of FIG. 7 further includes a third magnetic element **511**. The

third magnetic element **511** is disposed at the blocking plate **515a** and facing the second magnetic element **518**, wherein a magnetic repulsive force is generated between the second magnetic element **518** and the third magnetic element **511**, such that a greater magnetic force is provided for the touch portion **514** to recover. In one example, the magnetic repulsive force acts as the elastic member to be recovered easily in order to make the style of drawing smooth and easily.

FIG. 8 illustrates a stylus according to further another embodiment of the present application. FIG. 9 illustrates the touch portion contacts the operation surface of FIG. 8. Referring to FIG. 8 and FIG. 9, the stylus **610** includes a pipe **612**, a touch portion **614**, a protrusion **616** and a switch element **618**. The pipe **612** has a front end **612a**, a back end **612b** opposite to the front end **612a** and an opening **612c** formed at the front end **612a**, wherein a diameter of the opening **612c** is smaller than a diameter of the pipe **612**. The touch portion **614** is sliding disposed at the opening **612c**, wherein at least a part of the touch portion **614** is located in the pipe **612**.

The stylus **610** further includes a battery module **615** and a converter **617**, and the protrusion **616**. The battery module **615** is disposed within the pipe **612** and includes a blocking plate **615a** and at least a battery **615b** (showing two). The protrusion **616** is formed on the blocking plate **615a** of the pipe **612** and can be screwed forward or backward to adjust the suitable distance between the protrusion **616** and the switch element **618**. The switch element **618** is fixed and electrically connected to the touch portion **614** and has an elastic element **618a**. When the touch portion **614** is driven to move toward the back end **612b** by an exertion force, the switch element **618** is also pushed forward to contact the protrusion **616** for actuating the touch portion **614** to emit a light signal **30** actuating the operation surface **20** (as FIG. 9 shown). The switch element **618** comprises an elastic element **618a** facing the protrusion **616** and the elastic element **618a** is compressed between the touch portion **614** and the protrusion **616**, such that an elastic force is provided by the elastic element to drive the touch portion **614** to recover from the state shown in FIG. 9 to the state shown in FIG. 8. For example, the protrusion **616** could also be an elastic element to provide a greater elastic force for the touch portion **614** to recover.

In FIG. 9, the switch element **618** is turned on by the protrusion **616**, such that the touch portion **614** emits a light signal **30** actuating the operation surface **20**. However, the light signal **30** is extinguished when the tip of stylus **610** leaves the operation surface **20**, as FIG. 8 shown. For example, the exertion force applied to the touch portion **614** may be sensed by a detector (not shown), and the detecting mechanism is referring to other embodiment in the present invention. In other words, the detector fixed on the blocking plate **615a** also can be added when the stylus is designed to combine the pressure-sensitive function to draw a variable line width by a user's exertion force. In some examples, the switch element **618** is not only a switch, but also integrates a detecting function. In other examples, the detector is embedded in the protrusion **616** such that the protrusion **616** is capable of sensing the level of the contact pressure. The contact pressure is generated between the operation surface **20** and the touch portion **614** when exerting and transmitted to the converter **617**. The converter **617** is disposed in the pipe **612** and electrically connected to the protrusion **616**, wherein the converter **617** is suitable for transducing the analog signal into a digital signal and outputting the digital signal to the RF transmitting module **619**. The RF transmitting module **619** is essentially consisted of a RF transmitter and an antenna for transmitting depressing pressure information. The RF trans-

mitting module 619 is arranged to send the digital signal to the RF receiving module 10 electrically connected to the operation surface 20.

In one embodiment, the protrusion 616 is, for example, screwed to the blocking plate 615a, and a user can rotate the protrusion 616 to adjust a distance between the protrusion 616 and the switch element 618. In some embodiments, the protrusion 616 is designed in a constant distance at the manufacturing stage. The switch element 618 is, for example, electrically connected to the battery module 615 and the touch portion 614 by conductive wires 613. In addition, the switch element 618 has two contacts in a Surface Mount Device (SMD) or four contacts in a Dual In-line Package (DIP).

FIG. 10 illustrates a light emitting glove according to an embodiment of the present application. FIG. 11 illustrates a finger portion of the light emitting glove of FIG. 10. Referring to FIG. 10 and FIG. 11, the light emitting glove 700 includes a glove 710, a control circuit board 720, a plurality of light emitting elements 730 and a plurality of connecting wires 740.

The glove 710 includes an outer layer 712 and an inner layer 714 and having a plurality of finger portions 710a-710e (FIG. 10 illustrates finger portion 710a). The control circuit board 720 is disposed between the outer layer 712 and the inner layer 714. The light emitting elements 730 are, for example, light emitting diode elements and disposed on the finger portions 710a-710e respectively, wherein each of the light emitting elements 730 has a micro switch assembly 732. The connecting wires 740 are disposed between the outer layer 712 and the inner layer 714, wherein the light emitting elements 730 are electrically connected to the control circuit board 720 by the connecting wires 740 respectively.

A user can wear the light emitting glove 700 and touch a display panel by the finger portions 710a-710e. When one or more of the finger portions 710a-710e contact(s) the above mentioned the display panel, the corresponding micro switch assemblies 732 are pressed, and the corresponding light emitting elements 730 are driven to emit light for executing a touch input function. The touch input manner described in FIG. 1 to FIG. 9 can be applied to the micro switch assembly 732 described here.

In this embodiment, the light emitting glove 700 further includes a battery 750 and a plurality of rubber layers 760. The battery 750 is disposed on the control circuit board 720 for providing electric power to the control circuit board 720 and the light emitting elements 730. The rubber layers 760 covers the ends of the finger portions 710a-710e respectively and each of the rubber layers 760 has at least one (showing two) heat dissipation opening 762 for dissipating the heat generated by the corresponding light emitting element 730 or user's hand.

Referring to FIG. 10, each of the connecting wires 740 has a plurality of curled portions 742 for being flexible, such that the user wearing the light emitting glove 700 can crook his fingers without pulling apart the connecting wires 740. In this embodiment, each of the curled portions 742 is flattened between the outer layer 712 and the inner layer 714 in order not to occupy the inner space of the glove 710.

FIG. 12 illustrates an operating manner of the light emitting glove of FIG. 10. Referring to FIG. 12, the control circuit board 720 includes a control circuit 722, an RF transmitting module 724 electrically connected to the control circuit 722, a driver 726 electrically connected to the control circuit 722 and a charging socket 724 for the battery 750 to be charged. The battery 750 provides electric power to the control circuit 722. The control circuit 722 drives the RF transmitting mod-

ule 728 to transmit an RF signal to the RF receiving module 54 of the electronic device 50, such that a touch input function of a touch panel 52 of the electronic device 50 is turned on.

When a user wearing the light emitting glove 100 contacts a touch panel 52 of an electronic device 50 by fingers, the micro switch assembly 732 is pressed, and the control circuit 722 drives the light emitting element 730 to emit light by the driver 726, and the touch panel 52 receives the light emitted by the light emitting element 730, such that a touch input function is executed. Those skilled in the art should appreciate that any of the aforementioned embodiments and combinations could be applied in the finger portions 710a-710e.

In summary, the stylus of the present invention is able to transmit an electrical signal directly proportional to a contact pressure applied to the touch portion of the stylus, and the display device is able to receive the electrical signal to display a line width according to the electrical signal. In other words, a width of the line displayed by the display device is able to be changed by different electrical signals transmitted from the stylus, such that the operation of the touch input system is more flexible. In addition, when the touch portion of the stylus contacts an operation surface and a contact pressure is applied to the touch portion, the touch portion is pushed toward and electrically connected to the battery module to emit light signal actuating the operation surface, such that the operation of the stylus is facilitated.

It will be apparent to those skilled in the art that various modifications and variations may be made to the structure of the present invention without departing from the scope or spirit of the invention. In view of the foregoing, it is intended that the present invention covers modifications and variations of this invention provided they fall within the scope of the following claims and their equivalents.

What is claimed is:

1. A touch input system, comprising:

a stylus, comprising:

a main body;

a battery module, disposed at the main body;

a touch portion, disposed at the main body, wherein when a contact pressure is acted on the touch portion, the touch portion is electrically connected to the battery module by the contact pressure and emits a light signal continuously, when the touch portion is distant from the operation surface, the touch portion is recovered;

a transducer module, disposed at the main body and not electrically connected with the touch portion, wherein the contact pressure is transformed into an electrical signal by the transducer module, and the electrical signal is directly proportional to the contact pressure and

a RF transmitting module, disposed at the main body, electrically connected to the transducer module, and transmitting the electrical signal; and

a display device, comprising:

a display region, detecting the light signal to locate a touch position when the touch portion is exerted on the display region; and

a RF receiving module, electrically connected to the display region and detecting the electrical signal within a predetermined frequency range, wherein the display region receives the electrical signal via the RF receiving module, and the display region displays a line width according to the electrical signal,

wherein the transducer module comprising:

a light emitting element, fixed to the touch portion; and

a light detector, fixed to the main body and suitable for detecting a variation of a distance between the light emitting element and the light detector.

2. The touch input system as claimed in claim 1, wherein the display region displays a line according to the light signal, and a width of the line is according to the electrical signal.

3. The touch input system as claimed in claim 1, wherein the battery module is fixed to the main body, the touch portion 5 is sliding disposed at the main body, and the touch portion is suitable for being contacted the display region to be pushed toward the battery module.

4. The touch input system as claimed in claim 3, wherein the stylus further comprising: 10

a conductive elastic element, disposed between the touch portion and the battery module, wherein when the touch portion is pushed toward the battery module, the elastic element is compressed between the battery module and the touch portion. 15

5. The touch input system as claimed in claim 1, wherein the display device further comprising:

a light sensor array, arranged in a pixel electrode array of the display region.

6. The touch input system as claimed in claim 5, wherein 20 the light signal emitted from the touch portion is suitable for actuating at least one light sensor of the light sensor array.

* * * * *