



US008934848B2

(12) **United States Patent**
Nishio et al.

(10) **Patent No.:** **US 8,934,848 B2**
(45) **Date of Patent:** **Jan. 13, 2015**

(54) **RADIO COMMUNICATION DEVICE AND RADIO COMMUNICATION METHOD CONFIGURED FOR CHANNEL QUALITY REPORTING OF SELECTED SUB-CARRIER BANDS**

USPC 455/453, 436, 65, 67.14, 67.13, 450, 455/522, 501, 509, 114.2, 115.1, 296, 63.1, 455/67.11; 370/338, 328, 484, 210, 329, 370/252; 375/260, 343, 257, 221, 347, 299, 375/222, 375, 219, 224, 346; 342/463, 423, 342/437, 444, 445

(75) Inventors: **Akihiko Nishio**, Yokosuka (JP); **Jun Cheng**, Soraku-gun (JP)

See application file for complete search history.

(73) Assignee: **Panasonic Intellectual Property Corporation of America**, Torrance, CA (US)

(56) **References Cited**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1392 days.

U.S. PATENT DOCUMENTS

5,726,978 A 3/1998 Frodigh et al.
5,960,354 A 9/1999 Einola

(Continued)

(21) Appl. No.: **10/566,732**

FOREIGN PATENT DOCUMENTS

(22) PCT Filed: **Aug. 4, 2004**

DE 198 00 953 7/1999
JP 10-503356 A 3/1998

(86) PCT No.: **PCT/JP2004/011499**

(Continued)

§ 371 (c)(1),
(2), (4) Date: **Mar. 14, 2006**

OTHER PUBLICATIONS

(87) PCT Pub. No.: **WO2005/015801**

PCT International Search Report dated Jan. 11, 2005.

PCT Pub. Date: **Feb. 17, 2005**

(Continued)

(65) **Prior Publication Data**

US 2006/0198293 A1 Sep. 7, 2006

Primary Examiner — Fred Casca

(30) **Foreign Application Priority Data**

Aug. 6, 2003 (JP) 2003-288162

(74) *Attorney, Agent, or Firm* — Seed IP Law Group PLLC

(51) **Int. Cl.**
H04W 24/10 (2009.01)
H04L 1/00 (2006.01)

(Continued)


(57) **ABSTRACT**

A wireless communication apparatus is provided including: a radio receiver configured to acquire, from a base station, a first information indicating a fixed number identifying quantity of sub-carrier bands to be selected for channel quality reporting; a reception quality measurer configured to measure channel quality of each of a plurality of sub-carrier bands within a communication band; a subcarrier selector configured to select sub-carrier bands from the plurality of sub-carrier bands based on the measured channel quality, wherein quantity of the selected sub-carrier bands matches the quantity of sub-carrier bands identified by the fixed number; a modulator configured to modulate a second information indicating channel quality of the selected sub-carrier bands and a third information indicating positions of the selected sub-carrier bands according to a modulation scheme; and a radio transmitter configured to report to the base station the second and third modulated information.

(52) **U.S. Cl.**
CPC **H04W 24/10** (2013.01); **H04L 1/0026** (2013.01); **H04L 5/003** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC H04L 5/0007; H04L 1/0026; H04L 5/006; H04L 5/0053; H04L 5/0094; H04L 1/0003; H04L 5/0037; H04L 5/0064; H04L 27/2602; H04L 1/20; H04L 2025/03414; H04W 72/085; H04W 72/04; H04W 72/0406

16 Claims, 15 Drawing Sheets



(51)	Int. Cl.		2005/0286547 A1* 12/2005 Baum et al. 370/437
	<i>H04L 5/00</i>	(2006.01)	2005/0289256 A1 12/2005 Cudak et al.
	<i>H04W 72/12</i>	(2009.01)	2006/0014542 A1* 1/2006 Khandekar et al. 455/447
	<i>H04L 1/16</i>	(2006.01)	
	<i>H04W 28/06</i>	(2009.01)	

FOREIGN PATENT DOCUMENTS

(52)	U.S. Cl.		JP 11508417 7/1999
	CPC	<i>H04L 5/0044</i> (2013.01);	JP 2002135230 A 5/2002
		<i>H04L 5/0046</i> (2013.01); <i>H04L 5/0053</i>	JP 2002199459 A 7/2002
		(2013.01); <i>H04L 5/006</i> (2013.01); <i>H04W</i>	JP 2002252619 9/2002
		<i>72/1284</i> (2013.01); <i>H04L 1/1671</i> (2013.01);	JP 2003169036 6/2003
		<i>H04W 28/06</i> (2013.01); <i>H04W 72/1231</i>	KR 2003/0019210 3/2003
		(2013.01); <i>Y02B 60/50</i> (2013.01)	WO 98/10542 3/1998
	USPC	455/67.13 ; 455/63.3; 455/67.11;	WO 98/24258 6/1998
		455/65; 455/67.14; 370/203; 370/484; 370/338;	WO 0209334 1/2002
		370/464	WO 02/49305 6/2002
			WO 02/058300 A1 7/2002
			WO 03/049353 A1 6/2003

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,966,657 A	10/1999	Sporre	
6,397,077 B1 *	5/2002	Jensen	455/553.1
7,072,682 B2	7/2006	Uehara et al.	
7,272,162 B2	9/2007	Sano et al.	
2002/0119781 A1 *	8/2002	Li et al.	455/450
2002/0181421 A1 *	12/2002	Sano et al.	370/335
2002/0188723 A1 *	12/2002	Choi et al.	709/225
2003/0054847 A1	3/2003	Kim	
2003/0072395 A1	4/2003	Jia	
2003/0169681 A1	9/2003	Li et al.	
2004/0202103 A1 *	10/2004	Suh et al.	370/208
2005/0025039 A1 *	2/2005	Hwang et al.	370/206
2005/0232135 A1 *	10/2005	Mukai et al.	370/208

OTHER PUBLICATIONS

Y. Hara, et al.; "MC-CDM System for Packet Communications Using Frequency Scheduling," Technical Report of IEICE, NS2002-101, RCS2002-129, (Jul. 2002), The Institute of Electronics, Information and Communication Engineers, pp. 61-66 with English Abstract.
 Notice of Reasons for Rejection for corresponding JP Application No. 2011-098142, dated Nov. 15, 2011, 3 pages.
 Office Action, for Chinese Application No. 200910166194.1, dated Jul. 6, 2012, 8 pages.
 Korean Office Action dated Aug. 2, 2011.
 European Search Report dated Sep. 28, 2011.
 English translation of the Abstract of JP 2003-169036.

* cited by examiner




FIG.1




FIG.2




FIG.3




FIG.4




FIG.5




FIG.6




FIG.7




FIG.8




FIG.9




FIG.10




FIG.11




FIG.12




FIG.13




FIG.14




FIG.15

**RADIO COMMUNICATION DEVICE AND
RADIO COMMUNICATION METHOD
CONFIGURED FOR CHANNEL QUALITY
REPORTING OF SELECTED SUB-CARRIER
BANDS**

TECHNICAL FIELD

The present invention relates to a wireless communication and reception quality reporting method, and particularly relates to a wireless communication apparatus and reception quality reporting method for performing high-speed packet communication using adaptive modulation and scheduling.

BACKGROUND ART

In a conventional art, in HSDPA (High-Speed Downlink Packet Access) of 3GPP, adaptive modulation where the modulation scheme is adaptively controlled according to propagation path conditions and scheduling for transmitting a user signal for which propagation path conditions are comparatively superior have been employed in downlink high-speed packet transmission.

In multi-carrier transmission such as OFDM and MC-CDMA (for example, Hara, Kawabata, Duan and Sekiguchi, "MC-CDM System for Packet Communications Using Frequency Scheduling", TECHNICAL REPORT OF IEICE, RCS2002-129, July 2002, refer to pp. 61-66) being examined as transmission schemes for beyond 3G mobile communication systems, high speed transmission is implemented using a large number of sub-carriers.

In this kind of transmission scheme, performing adaptive modulation and scheduling every sub-carrier is examined.

With this kind of adaptive modulation and scheduling system, it is necessary for the mobile station to give reporting of channel quality information (CQI (Channel Quality Indicator)) of each sub-carrier instantaneously at a base station.

The mobile station reports individual CQI's on every sub-carrier for all sub-carriers to the base station.

A base station then determines the sub-carrier, modulation scheme and encoding rate to be used at each mobile station in accordance with a predetermined scheduling algorithm taking into consideration the CQI's from each mobile station.

Typically, sub-carriers with comparatively good propagation path conditions are allocated to each mobile station, and a modulation scheme and encoding rate satisfying a predetermined packet error rate are employed for these propagation conditions.

In the event that a base station transmits to a plurality of mobile stations at the same time, frequency scheduling is carried out using CQI's of all of the sub-carrier from all of the users.

In other words, if there are 64 sub-carriers, it is necessary for each mobile station to give reporting of 64 CQI's.

In this event, when a CQI is expressed using five bits, it is necessary to transmit a total of $64 \times 5 = 320$ bits per one user in each wireless frame.

However, with wireless communication apparatus of the conventional art, the quantity of signal required for CQI reporting is enormous. This means that interference incurred by other data channels and other cells is large, and the quantity of data that can be transmitted is therefore substantially reduced.

Further, as the quantity of signal for giving CQI reporting is enormous, power consumption of the mobile station is increased and a battery life is shortened.

DISCLOSURE OF INVENTION

It is an object of the present invention to provide a wireless communication apparatus and reception quality reporting method capable of increasing the data capacity that can be transmitted and reducing power consumption by reducing the amount of control signal transmitted, and increasing system capacity by reducing interference with respect to other wireless communication apparatuses.

According to an aspect of the present invention, a wireless communication apparatus is comprised of a measuring section that measures reception quality of a plurality of sub-carriers within a communication band from a received signal every sub-carrier, a selecting section that selects a sub-carrier satisfying a predetermined condition relating to measured reception quality from the plurality of sub-carriers, and a reporting section that gives a reporting of a selection result of the selecting section.

According to a further aspect of the present invention, a base station apparatus is comprised of a modulating section that modulates a packet data using an M-ary number adaptively selected based on a reporting of a selection result in which a sub-carrier satisfying a predetermined condition relating to reception quality at an opposing communication apparatus from a plurality of sub-carriers within a communication band, an encoding section that encodes the packet data using an encoding rate adaptively selected based on the reporting, and a scheduling section that identifies a sub-carrier satisfying the predetermined condition based on the reporting and carries out scheduling so that a packet data of a higher M-ary number or encoding rate to an identified sub-carrier having superior reception quality.

According to a further aspect of the present invention, a reception quality reporting method is comprised of a measuring step of measuring reception quality of a plurality of sub-carriers within a communication band from a received signal every sub-carrier, a selection step of selecting a sub-carrier satisfying a predetermined condition relating to measured reception quality from the plurality of sub-carriers, and a reporting step of giving a reporting of a selection result of the selecting section.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a block diagram showing a configuration of a wireless communication apparatus of Embodiment 1 of the present invention;

FIG. 2 is a block diagram showing a configuration of a base station apparatus of Embodiment 1 of the present invention;

FIG. 3 is a diagram showing an arrangement of sub-carriers on a frequency axis of Embodiment 1 of the present invention;

FIG. 4 is a diagram showing a signal format of Embodiment 1 of the present invention;

FIG. 5 is a diagram showing a signal format of Embodiment 1 of the present invention;

FIG. 6 is a block diagram showing a configuration of a wireless communication apparatus of Embodiment 2 of the present invention;

FIG. 7 is a block diagram showing a configuration of a wireless communication apparatus of Embodiment 3 of the present invention;

FIG. 8 is a block diagram showing a configuration of a base station apparatus of Embodiment 3 of the present invention;

FIG. 9 is a diagram showing a signal format of Embodiment 3 of the present invention;

FIG. 10 is a block diagram showing a configuration of a wireless communication apparatus of Embodiment 4 of the present invention;

FIG. 11 is a block diagram showing a configuration of a base station apparatus of Embodiment 4 of the present invention;

FIG. 12 is a diagram showing a signal format of Embodiment 4 of the present invention;

FIG. 13 is a diagram showing a signal format of Embodiment 4 of the present invention;

FIG. 14 is a block diagram showing a configuration of a wireless communication apparatus of Embodiment 5 of the present invention; and

FIG. 15 is a block diagram showing a configuration of a base station apparatus of Embodiment 5 of the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

The following is a detailed description of embodiments of the present invention with reference to the accompanying drawings.

Embodiment 1

FIG. 1 is a block diagram showing a configuration of wireless communication apparatus 100 of Embodiment 1 of the present invention.

Reception wireless processing section 102 down converts and suchlike a received signal received at antenna 101 from a radio frequency to a baseband frequency and outputs to guard interval (hereinafter referred to as "GI") removing section 103.

GI removing section 103 removes GI's from a received signal inputted from reception wireless processing section 102 and then outputs to fast Fourier transform (hereinafter referred to as "FFT; Fast Fourier Transform") section 104.

After converting the received signal inputted from GI removing section 103 from a serial data format to a parallel data format, FFT section 104 subjects the received signal to FFT and outputs to control information extraction section 105, user data extraction section 108 and pilot signal extraction section 112.

Control information extraction section 105 extracts control information contained in CQI quantity information transmitted from the base station apparatus from the received signal inputted from FFT section 104 and outputs to demodulating section 106.

Demodulating section 106 subjects control information inputted by control information extraction section 105 to demodulation processing and outputs to a decoding section 107.

Decoding section 107 decodes demodulated control information inputted by demodulating section 106, outputs decoded control information, and outputs CQI quantity information contained in the control information to sub-carrier selecting section (hereinafter referred to as "SC selecting section) 127.

User data extraction section 108 extracts user data from the received signal inputted by FFT section 104 and outputs to demodulating section 109.

Demodulating section 109 subjects user data inputted by user data extraction section 108 to demodulation processing and outputs to reception HARQ (Hybrid Automation Repeat Request) section 110.

If user data inputted by demodulating section 109 is new data, reception HARQ section 110 saves all or part of the user data and outputs the user data to a decoding section 111.

If the user data inputted by demodulating section 109 is re-transmitted data, reception HARQ section 110 combines the saved user data with the re-transmitted data, saves the combined use data, and outputs the combined user data to decoding section 111.

Decoding section 111 decodes user data inputted by reception HARQ section 110 and outputs user data.

Further, decoding section 111 performs error detection and decoding, and outputs the result to ACK/NACK generating section 119.

The error detection may use CRC (Cyclic Redundancy Checks).

This error detection is not limited to CRC and arbitrary error detection methods may also be applied.

Pilot signal extraction section 112 extracts a pilot signal from the received signal inputted by FFT section 104 and outputs to reception quality measuring sections 113-1 to 113-*n*.

Reception quality measuring sections 113-1 to 113-*n* are provided for the useable number of sub-carriers. Reception quality measuring sections 113-1 to 113-*n* measures reception quality every sub-carrier for all of the sub-carriers using a pilot signal inputted from pilot signal extraction section 112. Measurement value information indicating reception quality every measured sub-carrier is outputted to CQI generation section 114 and SC selecting section 127.

Arbitrary measurement values such as CIR (Carrier to Interference Ratio), SIR (Signal to Interference Ratio) and suchlike measured every sub-carrier can be used for the measurement value information.

CQI generating section 114 constituting a reception quality information generating section compares measurement value information inputted by reception quality measuring section 113 with a plurality of threshold values (second threshold values) for CQI selection use set according to reception quality, for a sub-carriers of a sub-carrier number (hereinafter referred to as "SC number") information that is identification information inputted from SC selecting section 127, and selects and generates a CQI every sub-carrier.

In other words, CQI generating section 114 has a reference table that stores information for CQI selection use to which different CQI's are allocated every predetermined region for measurement values indicating reception quality separated by threshold values for use in selection of the plurality of CQI's, and selects CQI's by referring to information for CQI selection use employing measurement value information inputted by a reception quality measuring section 113.

CQI generating section 114 generates one CQI for one sub-carrier and therefore generates CQI's for the designated number of sub-carriers.

CQI generating section 114 outputs the generated CQI's to an encoding section 115.

Generation of a CQI is not limited to after selection of a sub-carrier and it is also possible to select a generated CQI based on CQI quantity information after generating CQI's for all of the sub-carriers.

Encoding section 115 encodes CQI's for the number of designated sub-carriers inputted by CQI generating section 114 and outputs to modulating section 116.

Modulating section 116 modulates CQI's inputted by encoding section 115 and outputs to multiplexer 122.

Encoding section 117 encodes SC number information inputted by SC selecting section 127 and outputs to modulating section 118.

Modulating section **118** modulates SC number information inputted by encoding section **117** and outputs to multiplexer **122**.

ACK/NACK generating section **119**, according to error detection result information inputted by decoding section **111**, generates a NACK signal constituting an error determination signal if re-transmission is necessary, generates an ACK signal constituting an error determination signal in the event that re-transmission is not necessary, and outputs the generated NACK signal and ACK signal to an encoding section **120**.

Encoding section **120** encodes a NACK signal or ACK signal inputted by ACK/NACK generating section **119** and outputs to modulating section **121**.

Modulating section **121** modulates a NACK signal or ACK signal inputted by encoding section **120** and outputs to multiplexer **122**.

Multiplexer **122** multiplexes CQI's inputted by modulating section **116**, SC number information inputted by modulating section **118**, and NACK signals or ACK signals inputted by modulating section **121** so as to generate transmission data and outputs the generated transmission data to a serial/parallel (hereinafter referred to as "S/P") converter **123**.

S/P converter **123** converts transmission data inputted by multiplexer **122** from a serial data format to a parallel data format and outputs to inverse fast Fourier transform (hereinafter referred to as "IFFT: Inverse Fast Fourier Transform") section **124**.

IFFT section **124** subjects transmission data inputted by S/P converter **123** to inverse fast Fourier transformation and outputs to GI insertion section **125**.

GI insertion section **125** inserts GI's into transmission data inputted from IFFT section **124** and outputs to transmission wireless processing section **126**.

Transmission wireless processing section **126** upconverts transmission data inputted from GI insertion section **125** from a baseband frequency to a radio frequency and transmits from antenna **101**.

SC selecting section **127** constituting a selecting section selects a number of sub-carriers designated by the CQI quantity information in descending order of reception quality using CQI quantity information inputted by decoding section **107** and measurement value information inputted by reception quality measuring sections **113-1** to **113-n**.

SC selecting section **127** then outputs the selected sub-carriers as SC number information to CQI generating section **114** and encoding section **117**.

In this way, SC selecting section **127** selects the number of sub-carriers designated by control station apparatus.

Not only in the event that the sub-carriers are selected in descending order of reception quality, SC selecting section **127** may also set a predetermined threshold value and select a number of arbitrary sub-carriers designated by the CQI quantity information from sub-carriers of reception quality of the threshold value or higher.

Next, a configuration for a base station apparatus as a higher-level station apparatus of wireless communication apparatus **100** is described using FIG. 2.

FIG. 2 is a block diagram showing a configuration of base station apparatus **200**.

Control information extraction section **205**, demodulating section **206**, decoding section **207**, encoding section **209**, transmission HARQ section **210**, modulating section **211**, encoding section **212** and demodulating section **213** constitute transmission data processing sections **221-1** to **221-n**.

Transmission data processing sections **221-1** to **221-n** are provided for the number of users and each of transmission

data processing sections **221-1** to **221-n** carries out processing on transmission data for transmission to one user.

Further, encoding section **212** and modulating section **213** constitute control data transmission processing section **220**.

Reception wireless processing section **202** down converts a signal received at antenna **201** from a radio frequency to a baseband frequency and suchlike and outputs to GI removal section **203**.

GI removal section **203** removes GI from the received signal inputted by reception wireless processing section **202** and outputs to FFT section **204**.

After a received signal inputted by GI removal section **203** is converted from serial data format to parallel data format, FFT section **204** separates the received signal for each user and outputs to respective control information extraction section **205**.

Control information extraction section **205** then extracts control information from the received signal inputted by FFT section **204** and outputs to demodulating section **206**.

Demodulating section **206** then demodulates control information inputted by control information extraction section **205** and outputs to decoding section **207**.

Decoding section **207** decodes the received signal inputted by demodulating section **206** and outputs CQI's for each of the designated number of sub-carriers included in the received signal to control section **208**.

Further, decoding section **207** decodes the received signal inputted by demodulating section **206** and outputs SC number information included in the received signal to control section **208**.

Moreover, decoding section **207** decodes the received signal inputted by demodulating section **206** and outputs a NACK signal or ACK signal included in the received signal to transmission HARQ section **210**.

Control section **208** as a scheduling section carries out scheduling based on a scheduling algorithm using CQI's and SC number information for wireless communication apparatus **100** of each user inputted by decoding section **207**, and adaptively selects MCS (Modulation Coding Schemes) for the M-ary numbers and encoding rates and suchlike.

In other words, control section **208** is capable of determining reception quality every sub-carrier of each wireless communication apparatus **100** using the CQI's and SC number information for each sub-carrier transmitted from the wireless communication apparatus **100** for each user. The MCS is then selected according to reception quality for each sub-carrier of each wireless communication apparatus **100**.

Control section **208** has knowledge of the number of sub-carriers, and it is possible to allocate transmission data to be sent to each wireless communication apparatus **100**, to each sub-carrier within the range of usable sub-carriers.

At this time, control section **208** carries out the allocation, determining reception quality for sub-carriers for which CQI's have not been transmitted by wireless communication apparatus **100** as being the poorest.

Control section **208** outputs encoding rate information selected for each sub-carrier to encoding section **209** and outputs modulation scheme information selected for each sub-carrier to modulating section **211**, and also outputs information on sub-carriers allocated to each wireless communication apparatus **100** using scheduling to sub-carrier allocation section **215**.

Encoding section **209** encodes inputted transmission data based on encoding rate information inputted by control section **208**, and outputs to transmission HARQ section **210**.

Transmission HARQ section **210** outputs transmission data inputted by encoding section **209** to modulating section **211** and temporarily holds transmission data outputted to modulating section **211**.

In the event that an NACK signal is inputted by decoding section **207**, a re-transmission is requested by wireless communication apparatus **100**, and therefore transmission HARQ section **210** outputs temporarily held transmission data for which output is complete to modulating section **211** again.

On the other hand, in the event that an ACK signal is inputted by demodulating section **207**, transmission HARQ section **210** outputs new transmission data to modulating section **211**.

Modulating section **211** modulates transmission data inputted by transmission HARQ section **210** based on modulation scheme information inputted by control section **208** and outputs to multiplexer **214**.

Encoding section **212** then encodes control data and CQI quantity information inputted by a control station apparatus (not shown) as a higher-level station apparatus of base station apparatus **200**, and outputs to modulating section **213**.

The CQI quantity information is not limited to being inputted by the control station apparatus and may also be set by base station apparatus **200**.

Further, the CQI quantity information can also be set taking into consideration number of users and volume of traffic.

Moreover, this may be set as a value corresponding to reception capability of every mobile station.

Modulating section **213** modulates control data and CQI quantity information inputted by encoding section **212** and outputs to multiplexer **214**.

Multiplexer **214** multiplexes transmission data inputted by modulating section **211** and control data and CQI quantity information inputted by modulating section **213** for data to be transmitted to wireless transmission apparatus **100** of each user and outputs to sub-carrier allocation section **215**.

CQI quantity information is information specific to the wireless communication apparatus **100** of each user.

Sub-carrier allocation section **215** rearranges multiplexed signals inputted by multiplexer **214** based on sub-carrier information for each wireless communication apparatus **100** inputted by control section **208** and outputs to S/P converter **216**.

S/P converter **216** converts transmission data inputted by sub-carrier allocation section **215** from serial data format to parallel data format and outputs to IFFT section **217**.

IFFT section **217** subjects transmission data inputted by S/P converter **216** to IFFT and outputs to GI insertion section **218**.

Transmission data transmitted to each of wireless communication apparatus **100** subjected to IFFT at IFFT section **217** is then allocated to frequency-scheduled sub-carriers at control section **208**.

GI insertion section **218** inserts GI's into transmission data inputted from IFFT section **217** and outputs to a transmission wireless processing section **219**.

Transmission wireless processing section **219** up converts etc. transmission data inputted from GI insertion section **218** from a baseband frequency to a radio frequency and transmits from antenna **201**.

Next, a description is given of a method for selecting sub-carriers at wireless communication apparatus **100** and format for transmission signals during transmission of the CQI's of the selected sub-carriers using FIG. **3** to FIG. **5**.

FIG. **3** is a diagram showing sixty-four sub-carriers allocated within a range of a predetermined communication bandwidth **F1**.

Base station apparatus **200** sends high-speed packet data to the wireless communication apparatus **100** of all the users using the sub-carriers **1** to **64**.

In the event that the reception quality of sub-carriers **11** to **21** and sub-carriers **34** to **41** is good from the reception quality measurement results at reception quality measuring sections **113-1** to **113-n**, SC selecting section **127** selects sub-carriers **11** to **21** and sub-carriers **34** to **41**.

CQI generating section **114** generates CQI's for only sub-carriers **11** to **21** and sub-carriers **34** to **41**, and generates SC number information for sub-carriers **11** to **21** and sub-carriers **34** to **41**.

On the other hand, CQI generating section **114** does not generate CQI's and SC number information for sub-carriers other than sub-carrier **11** to **21** and sub-carrier **34** to **41**.

FIG. **4** is a diagram showing a format for a signal transmitted from wireless communication apparatus **100** to base station apparatus **200**.

Items of six-bit SC number information and five-bit CQI's are then paired together to constitute one item of sub-carrier control information.

As shown in FIG. **4**, control information outputted by multiplexer **122** is a signal resulting from time-division-multiplexing of a pair of control information items for each sub-carrier for which CQI's are generated at CQI generating section **114** and a one-bit ACK/NACK signal.

FIG. **5** is a diagram showing a further example of a format for a signal transmitted from wireless communication apparatus **100** to base station apparatus **200**.

One item of sub-carrier control information is constituted by one bit of SC number information and five bits of CQI.

As shown in FIG. **5**, control information outputted by multiplexer **122** is a signal resulting from time-division-multiplexing of SC number information of 64 bits from the top for 64 sub-carriers, CQI's for only the sub-carriers for which CQI's are generated at CQI generating section **114**, and one bit of ACK/NACK signal.

The SC number information is information time-division-multiplexed in order from the first sub-carrier of the 64 sub-carriers, with SC number information for sub-carriers for which CQI's are generated being indicated as "1", and SC number information for sub-carriers for which CQI's are not generated as "0".

As a result, bit **1**, bits **2** to **10**, bits **22** to **33** and bits **42** to **64** are indicated as "0", and bits **11** to **21** and bits **34** to **41** are indicated as "1".

At base station apparatus **200** receiving the CQI's and SC number information, control section **208** carries out scheduling of each sub-carrier for each wireless communication apparatus **100** by prioritizing allocation of sub-carriers **11** to **21** and sub-carriers **34** to **41**.

Further, it can also be considered to map data (for example, control data of high importance or playback data etc.) for which it is necessary to make the number of errors small with respect to the sub-carriers.

According to this Embodiment 1, a number of sub-carriers for which reception quality is good designated by a base station apparatus are selected and CQI's are generated and transmitted for the selected sub-carriers. Therefore, it is possible to increase the data capacity that can be transmitted and reduce power consumption by reducing the signal volume transmitted through the uplink and also possible to increase system capacity by reducing interference with respect to other wireless communication apparatuses.

Also, according to Embodiment 1, CQI's are generated only for selected sub-carriers and processing time while generating CQI's can therefore be made short. Further, according

to this embodiment, designation upon selecting sub-carriers for which CQI's are generated may be achieved simply by transmitting designation information designating the quantity of CQI's from the base station apparatus. It is therefore possible to reduce the amount of signal transmitted through the uplink without increasing the amount of signal transmitted through the downlink.

Embodiment 2

FIG. 6 is a block diagram showing a configuration for a wireless communication apparatus 600 according to Embodiment 2 of the present invention.

As shown in FIG. 6, wireless communication apparatus 600 according to Embodiment 2 is of a configuration where SC selecting section 127 is omitted and a threshold value determining section 601 is added in wireless communication apparatus 100 of Embodiment 1 shown in FIG. 1.

In FIG. 6, portions with the same configuration as for FIG. 1 are given the same numerals and are not described.

Further, the configuration of the base station apparatus with the exception of sending CQI threshold value information instead of CQI quantity information is the same as the configuration of FIG. 2 and is therefore not described.

Decoding section 107 decodes demodulated control information inputted by demodulating section 106 and outputs control information, and outputs CQI threshold value information contained in the control information to a threshold value determining section 601.

CQI generating section 114 generates CQI's for each sub-carrier for all of the sub-carriers using measurement value information inputted by reception quality measuring section 113.

In other words, CQI generating section 114 has a reference table that stores information for CQI selection use to which different CQI's are allocated every predetermined region for measurement values indicating reception quality separated by threshold values for use in selection of the plurality of CQI's, and selects CQI's by referring to information for CQI selection use employing measurement value information inputted by reception quality measuring section 113.

CQI generating section 114 outputs the generated CQI's to threshold value determining section 601.

CQI generating section 114 is not limited to the case of generating CQI's for all sub-carriers, and CQI's may be generated after sub-carriers are selected by determining threshold values for reception quality for each sub-carrier.

Threshold value determining section 601 as a selecting section selects only CQI's for which the reception quality is greater than or equal to a threshold value using CQI's, which are inputted by CQI generating section 114, and CQI threshold value information, which is a first threshold value inputted by decoding section 107, outputs the selected CQI's to encoding section 115, and outputs SC number information for the selected CQI's to encoding section 117.

Specifically, in the case of using CQI for eight levels of level 1 to 8, only CQI's of level 5 or greater are selected when a threshold value is level 5 or more, and only CQI's of level 4 or greater are selected when a threshold value is level 4 or more.

Threshold value determining section 601 is capable of adopting a method of outputting information for eight levels indicating which level of eight levels, level 1 to level 8, a selected CQI is at, or a method of outputting information of a relative value where, in the event that, for example, a thresh-

old value is level 5 or more and a generated CQI is level 7, a value 2 that is a relative value with respect to the threshold value is outputted.

In the case of adopting the method of outputting information for eight levels, three bits are required in order to express levels 1 to 8. In the case of adopting a method of outputting relative value information, if a difference in threshold value is 0 to 3, then only two bits of information are sufficient. The amount of signals transmitted can therefore be reduced in the case of transmitting relative value information.

In the case of adopting the method of outputting relative value information, the base station stores threshold value information which is in common with wireless communication apparatus 600.

The method for selecting CQI's at wireless communication apparatus 600 and format for transmitting signals during transmission of the selected CQI's is the same as for FIG. 3 to FIG. 5 and is therefore not described.

According to Embodiment 2, the present invention selects sub-carriers satisfying reception quality of a threshold value or more designated by the base station apparatus and generates and transmits CQI's for the selected sub-carriers. By reducing the signal volume transmitted through the uplink, it is possible to increase the data capacity that can be transmitted and reduce power consumption, and, by reducing interference with respect to other wireless communication apparatuses, it is possible to increase system capacity.

Further, according to Embodiment 1, designation upon selecting sub-carriers for which CQI's are generated may be achieved simply by transmitting designation information designating a threshold value from the base station apparatus. It is therefore possible to reduce the amount of signal transmitted through the uplink without increasing the amount of signal transmitted through the downlink.

Embodiment 3

FIG. 7 is a block diagram showing a configuration of a wireless communication apparatus 700 according to Embodiment 3 of the present invention.

As shown in FIG. 7, wireless communication apparatus 700 of Embodiment 3 is of a configuration where encoding section 117, demodulating section 118, and SC selecting section 127 are removed, and threshold value determining section 701, used sub-carrier selecting section 702 and spreading section 703 are added in wireless communication apparatus 100 of Embodiment 1 shown in FIG. 1.

In FIG. 7, portions with the same configuration as for FIG. 1 are given the same numerals and are not described.

CQI generating section 114 generates CQI's for each sub-carrier for all of the sub-carriers using measurement value information inputted by reception quality measuring section 113.

In other words, CQI generating section 114 has a reference table that stores information for CQI selection use to which different CQI's are allocated every predetermined region for measurement values indicating reception quality separated by threshold values for use in selection of the plurality of CQI's, and selects CQI's by referring to information for CQI selection use employing measurement value information inputted by reception quality measuring section 113.

CQI generating section 114 outputs the generated CQI's to threshold value determining section 701.

The CQI generating section is not limited to the case of generating CQI's for all sub-carriers, and CQI's may be generated after sub-carriers are selected by determining threshold values for reception quality for each sub-carrier.

Threshold value determining section 701 as a selecting section selects only CQI's for which the reception quality is greater than or equal to a threshold value using CQI's, which are inputted by CQI generating section 114, and CQI threshold value information, which is inputted by decoding section 107, outputs the selected CQI's to encoding section 115, and outputs SC number information for the selected CQI's to used sub-carrier selecting section 702.

As with the threshold value determining section 601 of Embodiment 2, threshold determining section 701 is capable of threshold value determination adopting either of a method of outputting information for eight levels indicating which of the eight levels, levels 1 to 8, the selected CQI's are at or a method of outputting relative value information.

Used sub-carrier selecting section 702 selects sub-carriers, for which CQI's are generated using SC number information inputted by threshold value determining section 701, or sub-carriers, which have in advance a one-to-one correspondence with such sub-carriers, as transmission sub-carriers, and outputs CQI's to spreading section 703.

Spreading section 703 subjects each CQI inputted by used sub-carrier selecting section 702 to spreading processing using CQI spreading code, allocates CQI signals to sub-carriers allocated by used sub-carrier selecting section 702 and outputs to multiplexer 122.

The CQI spreading code is a spreading code that differs every wireless communication apparatus 700 of each user and the same spreading code is used for the sub-carriers and CQI's of all of wireless communication apparatus 700 of each user.

The SC number information is not subjected to spreading processing by spreading section 703 because SC number information is not transmitted.

Multiplexer 122 multiplexes CQI's inputted by spreading section 703 and NACK signals or ACK signals inputted by modulating section 121 and outputs to S/P converter 123.

The multiplexed signal multiplexed at multiplexer 122 comes into a state where CQI of each sub-carrier is allocated to the sub-carrier itself, or where CQI of each sub-carrier is allocated to a sub-carrier which has one to one correspondence with each sub-carrier.

The details of the method for allocating sub-carriers will be described later.

Next, a description is given using FIG. 8 of a configuration for a base station apparatus of Embodiment 3.

FIG. 8 is a block diagram showing a configuration of a base station apparatus 800.

As shown in FIG. 8, a base station apparatus 800 according to Embodiment 3 is of a configuration where de-spreading section 801 and sub-carrier determining section 802 are added in base station apparatus 200 of embodiment 1 shown in FIG. 2.

In FIG. 8, portions with the same configuration as for FIG. 2 are given the same numerals and are not described.

Transmission data processing sections 803-1 to 803-n are comprised of control information extraction section 205, demodulating section 206, decoding section 207, encoding section 209, transmission HARQ section 210, modulating section 211, encoding section 212, demodulating section 213, de-spreading section 801 and sub-carrier determining section 802.

Transmission data processing sections 803-1 to 803-n are provided for the number of users and each of transmission data processing sections 803-1 to 803-n carries out processing on transmission data for transmission to one user.

De-spreading section 801 stores a plurality of spreading codes used at wireless communication apparatus 700 of one user with which base station apparatus 800 is carrying out communication.

De-spreading section 801 then subjects all of the sub-carriers inputted by control information extraction section 205 to de-spreading processing using the stored de-spreading code and outputs this to sub-carrier determining section 802.

Different spreading codes are stored at each of the de-spreading sections 801 of each of the transmission data processing sections 803-1 to 803-n because a different spreading code is used at each wireless communication apparatus 700.

Sub-carrier determining section 802 determines a sub-carrier, of which de-spreading output inputted by de-spreading section 801 is greater than or equal to a threshold value, to be a sub-carrier selected at wireless communication apparatus 700, and outputs SC number information of a sub-carrier with reception quality of greater than or equal to the threshold value to control section 208 and demodulating section 206.

Because SC number information is not transmitted by wireless communication apparatus 700, sub-carrier determining section 802 stores in advance SC number information that is in common to wireless communication apparatus 700.

Further, the reception quality is taken to be a relative value with respect to the pilot signal taking into consideration fluctuation in reception quality due to fading.

Decoding section 207 decodes the received signal inputted by demodulating section 206 and outputs CQI's for each of the designated number of sub-carriers included in the received signal to control section 208.

Moreover, decoding section 207 decodes the received signal inputted by demodulating section 206 and outputs a NACK signal or ACK signal included in the received signal to transmission HARQ section 210.

Control section 208 carries out scheduling based on CQI's of wireless communication apparatus 700 for each user inputted by decoding section 207 and SC number information for wireless communication apparatus 700 of each user inputted by sub-carrier determining section 802, and MCS including M-ary numbers and encoding rates etc. are adaptively selected.

In other words, control section 208 is capable of determining reception quality every sub-carrier for each wireless communication apparatus 700 using CQI's for each sub-carrier sent by wireless communication apparatus 700 of each user and SC number information for wireless communication apparatus 700 of each user inputted by sub-carrier determining section 802. MCS is then selected according to reception quality of each sub-carrier for each wireless communication apparatus 700.

Control section 208 is capable of allocating data to be transmitted to each wireless communication apparatus 700 to sub-carriers of good reception quality at each wireless communication apparatus 700.

Control section 208 has knowledge of the number of usable sub-carriers and allocates transmission data sent to each wireless communication apparatus 700 within the range of usable sub-carriers to each sub-carrier.

At this time, control section 208 carries out allocation, determining reception quality of a sub-carrier for which CQI's has not been transmitted by wireless communication apparatus 700 as being the poorest.

Control section 208 outputs encoding rate information selected for each sub-carrier to encoding section 209, outputs modulation scheme information selected for each sub-carrier to modulating section 211 and outputs sub-carrier informa-

tion allocated to each wireless communication apparatus **700** using scheduling to a sub-carrier allocation section **215**.

Next, a description is given using FIG. **3** and FIG. **9** of a method for selecting CQI's occurring at wireless communication apparatus **700** for allocation to sub-carriers, and a format for a transmission signal when transmitting selected CQI's.

It is possible to adopt two methods, a method where CQI' of each sub-carrier is allocated to the sub-carrier itself, or a method where CQI' of each sub-carrier is allocated to another sub-carrier with a one-to-one correspondence, as methods for allocating sub-carriers.

First, a description is given of a method for allocating CQI's of each sub-carrier to the sub-carrier itself.

In FIG. **3**, in the event that the reception quality of sub-carriers **11** to **21** and sub-carriers **34** to **41** is good from reception quality measurement results at the reception quality measuring sections **113-1** to **113-n**, threshold value determining section **701** selects the CQI's of sub-carriers **11** to **21** and sub-carriers **34** to **41**, used sub-carrier selecting section **702** allocates CQI's for sub-carriers **11** to **21** to sub-carriers **11** to **21**, and the CQI's for sub-carriers **34** to **41** are allocated to the sub-carriers **34** to **41**.

On the other hand, threshold value determining section **701** does not select CQI's and SC number information for sub-carriers other than sub-carrier **11** to **21** and sub-carrier **34** to **41**.

Next, a description is given of a method for allocating CQI of each sub-carrier to another sub-carrier with a one-to-one correspondence.

In FIG. **3**, in the event that the reception quality of sub-carriers **11** to **21** and sub-carriers **34** to **41** is good from reception quality measurement results at reception quality measuring sections **113-1** to **113-n**, threshold value determining section **701** selects the CQI's of sub-carriers **11** to **21** and sub-carriers **34** to **41**, used sub-carrier selecting section **702** allocates CQI's for sub-carriers **11** to **21** to sub-carriers **22** to **32** each having a one-to-one correspondence, and the CQI's of sub-carriers **34** to **41** are allocated to the sub-carriers **51** to **57** each having a one-to-one correspondence.

On the other hand, threshold value determining section **701** does not select CQI's and SC number information for sub-carriers other than sub-carrier **11** to **21** and sub-carrier **34** to **41**.

By storing sub-carriers having one-on-one correspondence with sub-carriers for which CQI's are generated at wireless communication apparatus **700** and base station apparatus **800** in advance, base station apparatus **800** can recognize which sub-carrier a received CQI is for.

FIG. **9** is a diagram showing a format for a signal transmitted from wireless communication apparatus **700** to base station apparatus **800**.

As shown in FIG. **9**, control information constituted of CQI's each having five bits and ACK signals or NACK signals for sub-carriers selected by a threshold value determination at threshold value determining section **701** is time division multiplexed and transmitted.

According to Embodiment 3, sub-carriers satisfying reception quality of a threshold value or more designated by the base station apparatus are selected and CQI's are generated and transmitted for the selected sub-carriers. By reducing the signal volume transmitted through the uplink, it is possible to increase the data capacity that can be transmitted and reduce power consumption and by reducing interference with respect to other wireless communication apparatuses, it is possible to increase system capacity.

Moreover, according to Embodiment 3, CQI's are allocated to selected sub-carriers with good reception quality and base station apparatus **800** is therefore capable of acquiring good quality CQI's.

Further, according to Embodiment 3, CQI generated for each sub-carrier is allocated to the sub-carrier itself. Base station apparatus **800** can therefore determine which sub-carrier CQI is for even without transmitting SC number information and the volume of signal transmitted can therefore be reduced by the amount resulting from not sending the SC number information.

Still further, in the event that the duplex scheme is TDD, the propagation path characteristics of the uplink and the downlink are substantially the same. It is therefore possible to use sub-carriers with good reception quality for the downlink as those for the uplink also.

In other words, it is possible to transmit a CQI signal using a superior propagation path.

Further, according to Embodiment 3, designation upon selecting sub-carriers for which CQI's are generated may be achieved simply by transmitting designation information designating a threshold value from the base station apparatus. It is therefore possible to reduce the amount of signal transmitted through the uplink without increasing the amount of signal transmitted through the downlink.

According to Embodiment 3, the sub-carriers and CQI's are subjected to spreading processing using a spreading code specific to wireless communication apparatus **700** of each user. In the event that CQI's are transmitted for the same sub-carrier by the wireless communication apparatus **700** of a plurality of users, it is possible for base station apparatus **800** to discriminate which wireless communication apparatus **700** of which user a CQI has been sent from.

Embodiment 4

FIG. **10** is a block diagram showing a configuration for a wireless communication apparatus **1000** according to Embodiment 4 of the present invention.

As shown in FIG. **10**, wireless communication apparatus **1000** of the fourth embodiment is of a configuration where CQI generating section **114**, encoding section **115** and modulating section **116** are excluded in the wireless communication apparatus **100** of Embodiment 1 shown in FIG. **1**.

In FIG. **10**, portions with the same configuration as for FIG. **1** are given the same numerals and are not described.

SC selecting section **127** selects a number of sub-carriers designated by the CQI quantity information in order of good reception quality using CQI quantity information inputted by decoding section **107** and measurement value information inputted by the reception quality measuring sections **113-1** to **113-n**.

SC selecting section **127** then outputs the selected sub-carriers as SC number information to encoding section **117**.

Multiplexer **122** multiplexes SC number information inputted by the modulating section **118**, and NACK signals or ACK signals inputted by modulating section **121** so as to generate transmission data and outputs the generated transmission data to S/P converter **123**.

Next, a description is given using FIG. **11** of a configuration for a base station apparatus **1100** of Embodiment 4.

FIG. **11** is a block diagram showing a configuration for base station apparatus **1100**.

In FIG. **11**, portions with the same configuration as for FIG. **2** are given the same numerals and are not described.

Decoding section **207** decodes the received signal inputted by demodulating section **206** and outputs SC number information included in the received signal to control section **208**.

Moreover, decoding section **207** decodes the received signal inputted by demodulating section **206** and outputs a NACK signal or ACK signal included in the received signal to transmission HARQ section **210**.

Control section **208** is able to be aware of sub-carriers of good reception quality at wireless communication apparatus **1000** of each user from SC number information for wireless communication apparatus **1000** of each user inputted by decoding section **207**. Scheduling is therefore carried out based on a scheduling algorithm in such a manner that transmission data is allocated to sub-carriers of SC numbers with good reception quality.

In other words, control section **208** carries out scheduling in such a manner that transmission data is allocated in order from the top of the SC number because SC number is arranged in descending order of reception quality of sub-carriers.

Control section **208** outputs sub-carrier information for use in transmission to sub-carrier allocation section **215**.

Encoding section **209** encodes transmission data at a fixed encoding rate set in advance and outputs to transmission HARQ section **210**.

Modulating section **211** modulates transmission data inputted by transmission HARQ section **210** using a fixed modulation method set in advance and outputs to multiplexer **214**.

Next, a description is given of a method for selecting CQI's at wireless communication apparatus **1000** and format for transmission signals during transmission of the selected CQI's, using FIG. **3** and FIG. **12**.

In FIG. **3**, in the event that the reception quality of sub-carriers **11** to **21** and sub-carriers **34** to **41** is good from the reception quality measurement results at reception quality measuring sections **113-1** to **113-n**, SC selecting section **127** outputs SC number information only for sub-carriers **11** to **21** and sub-carriers **34** to **41**.

On the other hand, SC selecting section **127** does not output CQI's and SC number information for sub-carriers other than sub-carrier **11** to **21** and sub-carrier **34** to **41**.

FIG. **12** is a diagram showing a format for a signal transmitted from wireless communication apparatus **1000** to base station apparatus **1100**.

As shown in FIG. **12**, control information outputted by multiplexer **122** is a signal of time-division-multiplexing of SC number information comprised of six bits for sub-carriers selected at SC selecting section **127** and a one-bit ACK/NACK signal.

FIG. **13** is a diagram showing a further example of a format for a signal transmitted from wireless communication apparatus **1000** to base station apparatus **1100**.

As shown in FIG. **13**, control information outputted by multiplexer **122** is signal of time-division-multiplexing of SC number information of 64-bits from the top for each of the 64 sub-carriers and a one-bit ACK/NACK signal.

The SC number information is information time-division-multiplexed in order from the first sub-carrier of the 64 sub-carriers, with SC number information for sub-carriers that are selected being indicated as "1", and SC number information for sub-carriers that are not selected being indicated as "0".

Therefore, bit **1**, bits **2** to **10**, bits **22** to **33** and bits **42** to **64** are indicated as "0", and bits **11** to **21** and bits **34** to **41** are indicated as "1".

According to Embodiment 4, a number of sub-carriers designated by a base station apparatus as having good recep-

tion quality are selected and SC number information is sent to the selected sub-carriers. The volume of signal transmitted through the uplink can therefore be reduced compared to the case where CQI's and SC number information are both transmitted. It is therefore possible to increase the data capacity that can be transmitted and reduce power consumption, and increase system capacity by reducing interference with respect to other wireless communication apparatuses.

Further, according to Embodiment 4, designation upon selecting sub-carriers for which CQI's are generated may be achieved simply by transmitting designation information designating the number of CQI's from the base station apparatus. It is therefore possible to reduce the amount of signal transmitted through the uplink without increasing the amount of signal transmitted through the downlink.

Moreover, according to Embodiment 4, a base station apparatus is capable of carrying out encoding using encoding rates fixedly set in advance, modulation and suchlike. It is then possible to make circuits and apparatus smaller and reduce manufacturing costs by simplifying processing for encoding processing and modulation processing and so on.

Embodiment 5

FIG. **14** is a block diagram showing a configuration for a wireless communication apparatus **1400** according to Embodiment 5 of the present invention.

As shown in FIG. **14**, wireless communication apparatus **1400** of Embodiment 5 is of a configuration where encoding section **115**, modulating section **116**, encoding section **117**, demodulating section **118**, and SC selecting section **127** are removed, and threshold value determining section **1401**, CQI spreading code generating section **1402**, used sub-carrier selecting section **1403** and spreading section **1404** are added in wireless communication apparatus **100** of Embodiment 1 shown in FIG. **1**.

In FIG. **14**, portions with the same configuration as for FIG. **1** are given the same numerals and are not described.

Threshold value determining section **1401** as a selecting section selects only CQI's with reception quality greater than or equal to the threshold value using CQI's, which are reception quality information for selection use and inputted by CQI generating section **114**, and CQI threshold value information, which is inputted by decoding section **107**, outputs the selected CQI's to the CQI spreading code generating section **1402**, and outputs SC number information for selected CQI's to the used sub-carrier selecting section **1403**.

As with the threshold value determining section **601** of Embodiment 2, threshold determining section **1401** is capable of threshold value determination adopting either of a method of outputting eight levels of information indicating which of the eight levels, levels 1 to 8, the selected CQI's are at or a method of outputting relative value information.

This is not limited to selecting CQI's greater than or equal to a threshold value from CQI's for all of the sub-carriers, and it is also possible to select sub-carriers with reception quality greater than or equal to a threshold value before generating CQI's and only generating CQI's of the selected sub-carriers.

CQI spreading code generating section **1402** constituting a spreading code selection section has a reference table that stores CQI spreading code information which is spreading code selection information for providing a relationship between associating CQI's and spreading codes.

CQI spreading code generating section **1402** selects spreading codes by referring to CQI spreading code informa-

tion using CQI's inputted by a threshold value determining section **1401** and outputs selected spreading code information to spreading section **1404**.

Spreading codes in the CQI spreading code information are codes that are different at wireless communication apparatus **1400** of each user and are codes that are different for each CQI.

Used sub-carrier selecting section **1403** allocates an ACK signal or NACK signal as an error determination signal inputted by modulating section **121** to a sub-carrier selected using SC number information inputted by threshold value determining section **1401** and outputs to spreading section **1404**.

In the event that a plurality of SC number information are inputted from threshold value determining section **1401**, used sub-carrier selecting section **1403** allocates ACK signals or NACK signals to a plurality of sub-carriers reported using the SC number information.

Spreading section **1404** subjects sub-carriers allocated with ACK signals or NACK signals inputted by used sub-carrier selecting section **1403** to spreading processing using spreading codes inputted by the CQI spreading code generating section **1402** and outputs to multiplexer **122**.

Next, a description is given using FIG. **15** of a configuration for a base station apparatus of Embodiment 5.

FIG. **15** is a block diagram showing a configuration for base station apparatus **1500**.

As shown in FIG. **15**, base station apparatus **1500** of Embodiment 5 is of a configuration where a de-spreading section **1501** and a determining section **1502** are added in base station apparatus **200** of Embodiment 1 shown in FIG. **2**.

In FIG. **15**, portions with the same configuration as for FIG. **2** are given the same numerals and are not described.

Transmission data processing sections **1503-1** to **1503-n** are comprised of control information extraction section **205**, demodulating section **206**, decoding section **207**, encoding section **209**, transmission HARQ section **210**, modulating section **211**, encoding section **212**, demodulating section **213**, de-spreading section **1501** and determining section **1502**.

Transmission data processing sections **1503-1** to **1503-n** are provided for the number of users and each of the transmission data processing sections **1503-1** to **1503-n** carries out processing on transmission data for transmission to one user.

De-spreading section **1501** stores in advance a plurality of spreading codes used at wireless communication apparatus **1400** of one user with which base station apparatus **1500** is carrying out communication.

De-spreading section **1501** then subjects all of the sub-carriers inputted by control information extraction section **205** to de-spreading processing using the stored de-spreading code and outputs to determining section **1502**.

De-spreading sections **1501** of each of transmission data processing sections **1503-1** to **1503-n** stores in advance a different spreading code because a different spreading code is used at each wireless communication apparatus **1400**.

Determining section **1502** has a reference table that stores CQI spreading code information for providing a relationship between the spreading code and CQI's, and stores spreading codes used by wireless communication apparatus **1400** of one user.

Determining sections **1502** of each of transmission data processing sections **1503-1** to **1503-n** stores in advance a different spreading code because a different spreading code is used at each wireless communication apparatus **1400**.

CQI spreading code information is in common with CQI spreading code generating section **1402**.

Determining section **1502** obtains a de-spreading output for received signals inputted by de-spreading section **1501**

every sub-carrier, and compares the largest de-spreading output with a threshold value (a third threshold value) every sub-carrier.

Determining section **1502** determines sub-carriers whose largest de-spreading outputs are greater than or equal to the threshold value are sub-carriers selected by wireless communication apparatus **1400**, selects CQI's of sub-carriers whose largest de-spreading outputs are greater than or equal to the threshold value by referring to CQI spreading code information using spreading codes employed in de-spreading of the largest de-spreading outputs, and outputs the selected CQI's to control section **208**.

At this time, the de-spreading output is expressed as a relative value with respect to the received signal power of a pilot, taking into consideration fluctuation in received signal power due to fading.

Demodulating section **206** then de-modulates an ACK signal or NACK signal inputted by the determining section **1502** and outputs to decoding section **207**.

Decoding section **207** then outputs the results of demodulating the ACK signal or NACK signal inputted by demodulating section **206** to transmission HARQ section **210**.

Control section **208** carries out scheduling based on a scheduling algorithm using CQI's for wireless communication apparatus **1400** of each user inputted by determining section **1502**, and adaptively selects MCS's for the M-ary numbers, encoding rates and suchlike.

In other words, control section **208** is capable of determining reception quality every sub-carrier for each wireless communication apparatus **1400** using CQI's every sub-carrier inputted by determining section **1502**. MCS's are then selected according to reception quality of each sub-carrier for each wireless communication apparatus **1400**.

Control section **208** has knowledge of the number of sub-carriers and it is possible to use and allocates transmission data to be sent to each wireless communication apparatus **1400** within the range of usable sub-carriers to each sub-carrier.

At this time, control section **208** carries out allocation, determining reception quality of a sub-carrier for which CQI's has not been inputted by determining section **1502** as being the poorest.

Control section **208** outputs encoding rate information selected for each sub-carrier to encoding section **209**, outputs modulation scheme information selected for each sub-carrier to modulating section **211** and outputs sub-carrier information allocated to each wireless communication apparatus **1400** using scheduling to sub-carrier allocation section **215**.

Next, a description is given using FIG. **3** of a method for selecting sub-carriers at wireless communication apparatus **1400**.

Used sub-carrier selecting section **1403** allocates ACK signals or NACK signals to sub-carriers **11** to **21** and sub-carriers **34** to **41**.

Control information multiplexed at multiplexer **122** is a signal resulting from time-division-multiplexing of a plurality of ACK signals or NACK signals.

In the case of FIG. **3**, a plurality of ACK signals or NACK signals are transmitted but as the ACK signals or NACK signals are one bit whereas the five bits are required for CQI's, the overall quantity of signal can be reduced.

According to Embodiment 5, a sub-carrier of good reception quality is selected, and an ACK signal or NACK signal is allocated to the selected sub-carrier. By reducing the amount of signal transmitted on the uplink, it is possible to increase the data capacity that can be transmitted that can be transmitted and reduce power consumption, and, by reducing inter-

ference with respect to other wireless communication apparatuses, it is possible to increase system capacity.

According to Embodiment 5, dual purpose use of the ACK signal or NACK signal indicative of whether or not re-transmission is required and reception quality information which is CQI's is possible, and the CQI's and SC number information are not transmitted. The amount of signals transmitted through the uplink is therefore reduced to an extreme level.

Further, according to Embodiment 5, designation while selecting sub-carriers for which CQI's are generated may be achieved simply by transmitting designation information designating the number of CQI's from the base station apparatus. It is therefore possible to reduce the amount of signal transmitted through the uplink without increasing the amount of signal transmitted through the downlink.

In Embodiment 5, wireless communication apparatus 1400 spreads sub-carriers by selecting user-specific spreading codes and spreading sub-carriers allocated with ACK signals or NACK signals. However, this is by no means limiting, and it is also possible to perform scrambling by selecting user-specific scrambling codes and allocating ACK signals or NACK signals using the selected scrambling codes.

In Embodiments 1 to 5, 64 sub-carriers are allocated within communication band F1 but this is by no means limiting and it is also possible to allocate an arbitrary number of sub-carriers other than 64.

The wireless communication apparatus of Embodiments 1 to 5 may also be applied to a communication terminal apparatus.

In Embodiments 3 to 5, sub-carriers to be selected are determined using a threshold determination for reception quality for each sub-carrier, but it is also possible to select just the number of sub-carriers notified by an upper order station as in Embodiment 1.

Each functional block employed in the description of each of the aforementioned embodiments may be typically implemented as an LSI which is an integrated circuit.

These may be integrated into chips individually, or may be integrated into chips in such a manner that each includes part or all of them.

An LSI is adopted here but this may also be referred to as "IC", "system LSI", "super LSI", or "ultra LSI" depending on a difference in degree of integration.

Further, a method of circuit integration is not limited to LSI's, and implementation using dedicated circuitry or general purpose processors is also possible.

After LSI manufacturing, utilization of a programmable FPGA (Field Programmable Gate Array) or a reconfigurable processor where connections and settings of circuit cells within an LSI can be reconfigured is also possible.

Further, if circuit integration technology comes out to replace LSI's as a result of the advancement of semiconductor technology or another derivative technology, it is, of course, possible to carry out functional block integration using such technology.

Application in biotechnology is also possible.

As described above, according to the present invention, by reducing the amount of signal transmitted, it is possible to increase the data capacity that can be transmitted and reduce power consumption and, by reducing interference with respect to other wireless communication apparatuses, it is possible to increase system capacity.

This specification is based on Japanese patent application No. 2003-288162, filed on Aug. 6, 2003, the entire content of which is expressly incorporated by reference herein.

INDUSTRIAL APPLICABILITY

The wireless communication apparatus and reception quality reporting method of the present invention are capable of

increasing data capacity that can be transmitted and reducing power consumption by reducing the amount of control signal transmitted, have an advantage of increasing system capacity by reducing interference with respect to other wireless communication apparatuses, and suitable for use in giving reporting of reception quality for wireless communication apparatus.

FIG. 1

102 RECEPTION WIRELESS PROCESSING SECTION

103 GI REMOVING SECTIONS

104 FFT SECTION

105 CONTROL INFORMATION EXTRACTION SECTION

106 DEMODULATING SECTION

107 DECODING SECTION

126 TRANSMISSION WIRELESS PROCESSING SECTION

108 USER DATA EXTRACTION SECTION

109 DEMODULATING SECTION

20 110 RECEPTION HARQ SECTION

111 DECODING SECTION

125 GI INSERTION SECTION

112 PILOT SIGNAL EXTRACTION SECTION

113-1~113-N RECEPTION QUALITY MEASURING SECTIONS

25 127 SC SELECTING SECTION

124 IFFT SECTION

123 S/P CONVERTER

122 MULTIPLEXER

30 116 MODULATING SECTION

115 ENCODING SECTION

114 CQI GENERATING SECTION

118 MODULATING SECTION

35 117 ENCODING SECTION

121 MODULATING SECTION

120 ENCODING SECTION

119 ACK/NACK GENERATING SECTION

CONTROL INFORMATION

USER DATA

40 FIG. 2

202 RECEPTION WIRELESS PROCESSING SECTION

203 GI REMOVAL SECTION

204 FFT SECTION

205 CONTROL INFORMATION EXTRACTION SECTION 205

206 DEMODULATING SECTION

207 DECODING SECTION

208 CONTROL SECTION

209 ENCODING SECTION

50 210 TRANSMITTED SIGNAL HARQ SECTION

211 MODULATING SECTION

212 ENCODING SECTION

213 MODULATING SECTION

214 MULTIPLEXER

55 215 SUB-CARRIER ALLOCATION SECTION

216 S/P CONVERTER

217 IFFT SECTION

218 GI INSERTION SECTION

219 TRANSMISSION WIRELESS PROCESSING SECTION

220 CONTROL DATA TRANSMISSION PROCESSING SECTION

CQI QUANTITY INFORMATION

CONTROL DATA

65 TRANSMISSION DATA

FIG. 3

FREQUENCY

FIG. 4
6 BITS, 5 BITS, 1 BIT
SC NUMBER INFORMATION 11, CQI FOR SC NUMBER
INFORMATION 11

CONTROL INFORMATION
FIG. 5

1 BIT, 11 BITS
CQI FOR SC NUMBER 11,
BIT 1, BIT 10, BIT 21
CONTROL INFORMATION

FIG. 6 (FIG. 1 参照)
601 THRESHOLD VALUE DETERMINING CIRCUIT

FIG. 7 (FIG. 1 参照)
701 THRESHOLD VALUE DETERMINING SECTION
702 USED SUB-CARRIER SELECTING SECTION
703 SPREADING SECTION

FIG. 8 (FIG. 2 参照)
801 DE-SPREADING SECTION
802 SUB-CARRIER DETERMINING SECTION

FIG. 9
5 BITS, 1 BIT
CQI FOR SC(b)
ACK/NACK SIGNAL
CONTROL INFORMATION

FIG. 10 (FIG. 1 参照)

FIG. 11 (FIG. 2 参照)

FIG. 12 (FIG. 4 参照)

FIG. 13
64 BITS, 1 BIT
1 BIT, 2 BITS,
CONTROL INFORMATION

FIG. 14 (FIG. 1 参照)
1401 THRESHOLD VALUE DETERMINING SECTION
1402 CQI SPREADING CODE GENERATING SECTION
1403 USED SUB-CARRIER SELECTING SECTION
1404 SPREADING SECTION

FIG. 15 (FIG. 2 参照)
1501 DE-SPREADING SECTION
1502 DETERMINING SECTION

The invention claimed is:

1. A wireless communication apparatus comprising:

a radio receiver configured to acquire, from a base station,
a first information indicating a fixed number identifying
quantity of sub-carrier bands to be selected for channel
quality reporting;

a reception quality measurer coupled to the radio receiver
and configured to measure channel quality of each of a
plurality of sub-carrier bands within a communication
band from a received signal;

a subcarrier selector coupled to the radio receiver and con-
figured to select sub-carrier bands from the plurality of
sub-carrier bands based on the measured channel qual-
ity, wherein quantity of the selected sub-carrier bands
matches the quantity of sub-carrier bands identified by
the fixed number indicated by the first acquired infor-
mation;

a modulator configured to modulate a second information
indicating channel quality of the selected sub-carrier
bands according to a modulation scheme and a third
information indicating positions of the selected sub-
carrier bands according to the modulation scheme; and
a radio transmitter configured to report to the base station
the second and third modulated information.

2. The wireless communication apparatus according to
claim 1, wherein the subcarrier selector is configured to select
the indicated fixed number of sub-carrier bands in descending
order of the measured channel quality.

3. The wireless communication apparatus according to
claim 1, wherein the radio transmitter is further configured to
spread the second information indicating channel quality of
the selected sub-carrier bands using a spreading code specific
to each user, and report the spread second information.

4. The wireless communication apparatus according to
claim 1, wherein the radio transmitter is further configured to
spread the third information indicating positions of the
selected sub-carrier bands using a spreading code specific to
each user, and report the spread third information.

5. The wireless communication apparatus according to
claim 1, wherein the second information indicating channel
quality of the selected sub-carrier bands is channel quality
information (CQI).

6. The wireless communication apparatus according to
claim 5, wherein the CQI is generated based on comparison
between a channel quality measurement value and predeter-
mined regions of channel quality measurement values respec-
tively indicating different CQIs.

7. The wireless communication apparatus according to
claim 1, wherein the second information indicates an aggre-
gation of the channel quality of each of the selected sub-
carrier bands.

8. The wireless communication apparatus according to
claim 1, wherein the radio transmitter is further configured to
multiplex the second and third modulated information with
an Acknowledgement/Negative Acknowledgement (ACK/
NACK) signal for reporting to the base station.

9. A wireless communication method comprising:
acquiring, from a base station, a first information indicat-
ing a fixed number identifying quantity of sub-carrier
bands to be selected for channel quality reporting;
measuring channel quality of each of a plurality of sub-
carrier bands within a communication band from a
received signal;

selecting sub-carrier bands from the plurality of sub-carrier
bands based on the measured channel quality, wherein
quantity of the selected sub-carrier bands matches the
quantity of sub-carrier bands identified by the fixed
number indicated by the first acquired information;
modulating a second information indicating channel qual-
ity of the selected sub-carrier bands according to a
modulation scheme and a third information indicating
positions of the selected sub-carrier bands according to
the modulation scheme; and
reporting to the base station the second and third modu-
lated information.

10. The wireless communication method according to
claim 9, wherein the selecting selects the indicated fixed
number of sub-carrier bands in descending order of the mea-
sured channel quality.

11. The wireless communication method according to
claim 9, further comprising spreading the second information
indicating channel quality of the selected sub-carrier bands
using a spreading code specific to each user, wherein the
reporting includes reporting of the spread second informa-
tion.

12. The wireless communication method according to
claim 9, further comprising spreading the third information
indicating positions of the selected sub-carrier bands using a
spreading code specific to each user, wherein the reporting
includes reporting of the spread third information.

13. The wireless communication method according to claim 9, wherein the second information indicating channel quality of the selected sub-carrier bands is channel quality information (CQI).

14. The wireless communication method according to claim 13, wherein the CQI is generated based on comparison between a channel quality measurement value and predetermined regions of channel quality measurement values respectively indicating different CQIs.

15. The wireless communication method according to claim 9, wherein the second information indicates an aggregation of the channel quality of each of the selected sub-carrier bands.

16. The wireless communication method according to claim 9, further comprising multiplexing the second and third modulated information with an Acknowledgement/Negative Acknowledgement (ACK/NACK) signal before reporting to the base station.

* * * * *